

```
$ node breakfast.js --mode=async
```

JavaScript □□□

```
// 00000000 Promise 0 async/await
```

sync

□□□□

promise

□□□□□

await

□□□□□

event loop

□□□□

\$ cat menu.md



01 /



vs



02 / Promise

then/catch

03 / async & await

vs

04 / Event Loop

VIP

async

PART 01



□□□□□□□□□□

```

CONSOLE - 4.5s

██████...
██████
██████...
██████
██████████

```

□ □ □ □ □ . . .

5555

□ □ □ □ □ . . .

666666

□ □ □ □ □ □ □ □ □ □ □ □

```
CONSOLE - ~2s
```

□□□□...
□□□□...
□□□□...
□□□□□□□□□□□□
□□□□□□□□□□□□

□ □ □ □ □ . . .

□ □ □ □ □ . . .

□ □ □ □ . . .

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □



□□□□□

\$ node breakfast.js

□□□□□□□□□□

☕ vs 🍞

▶ ☕□□□□□□□□□□

▶ 🍞□□□□□□□□□□

☕ 2s

🍞 1.5s

🔍 1s

☕ + 🍞 + 🔍 = 2 + 1.5 + 1 = 4.5 ☕ = max(2, 1.5, 1) = 2

PART 02

Promise

□□□□□□□□□□

□□□□□□□□

pending

□□□□□□

fulfilled

□□□□resolve("🍌🍌")

rejected

□□□□reject("🍌🍌")

```
1 let myPromise = new Promise((resolve, reject) => {
2   let success = true;
3   setTimeout(() => {
4     if (success) resolve("🍌🍌");
5     else reject("🍌🍌");
6   }, 2000);
7 });
8
9 myPromise.then(result => console.log(result))
10 .catch(error => console.log(error));
```

□□□□□Promise.race + AbortController

```
1  const delay = (ms) => new Promise((resolve) => setTimeout(resolve, ms));
2
3  const fetchWithTimeout = (url, { timeout = 3000 } = {}) => {
4    const controller = new AbortController();
5    const timer = delay(timeout).then(() => controller.abort());
6
7    const request = fetch(url, { signal: controller.signal });
8
9    return Promise.race([request, timer]).catch((error) => {
10      if (error.name === "AbortError") return Promise.reject("□□□□");
11      return Promise.reject(error.message || "□□□□");
12    });
13  };
```

Promise.race

□□□□□□□□□□ — □□□□□□□□□□

AbortController

□□□□□□□□□□□□

PART 03

async / await

□□□□□□□□□□

then **NOGRAPH** → **await**

```
await then async/await then
```



```
1  async function serial() {  
2    const coffee = await makeCoffee();  
3    const toast = await makeToast();  
4    return [coffee, toast];  
5  }
```

TOTAL TIME

$\approx 2 + 1.5 = 3.5s$

□□

token API — □□□□□



```
1  async function parallel() {  
2    const [coffee, toast] = await Promise.all([  
3      makeCoffee(),  
4      makeToast(),  
5    ]);  
6    return [coffee, toast];  
7  }
```

TOTAL TIME

$\approx \max(2, 1.5) = 2s$

□□

token API

Promise.all vs allSettled

	Promise.all	Promise.allSettled
□□□□□	 reject 	□□□□□□□
□□	□□□□	{status, value/reason} □□
□□	□□□□□□□	□□□□□□□□□□


\$ npm run all □□□□□□□□□□allSettled □□□□□□□□

PART 04

Event Loop

0000 VIP 0000000000

□ □ □ □ □ □ □ □ □



□□□□VIP□
□□□□□□□□□□

□□□□□□□□
□□□□□□□□□□□□



```
1 console.log("1");
2 setTimeout(() => console.log("2"), 0);
3 Promise.resolve().then(() => console.log("3"));
4 console.log("4");
```

ANSWER

1 → 4 → Call Stack

→ 3 → VIP

→ 2 → 0

1 → 4 → 3 → 2

□ □ □ □ □ □ □ □ □ □ □ □ □ □

□□□□□ pending → fulfilled / rejected

await Promise.all

□ □ □ □ □ □ □ □ □ □ □ □



Breakfast served.

fetch AbortController

```
$ node breakfast.js --mode=async
```

promise → await → race → event loop