

```
$ node breakfast.js --mode=async
```

# JavaScript □□□

```
// 00000000 Promise 0 async/await
```

sync

□□□□

promise

□□□□□

await

□□□□□

event loop

□□□□

\$ cat menu.md



01 /



vs □□□□□

02 / Promise

□□□□□then/catch□□□□□

03 / async & await



vs □□

04 / Event Loop

VIP □□□□□□□□□

🔗🔗🔗🔗🔗🔗 async □□□□□□□□□□□□

PART 01



□□□□□□□□□□

□□□□□□□□□

```
1  function makeCoffee() {
2      console.log("☕☕☕☕...");
3      const start = Date.now();
4      while (Date.now() - start < 2000) {} // ☐☐☐
5      console.log("☕☕☕☕");
6  }
7
8  function prepareBreakfastSync() {
9      makeCoffee(); // 2s
10     makeToast(); // 1.5s
11     fryEgg();     // 1s
12 }
```

CONSOLE — 4.5s

☕☕☕☕...

☐☐☐☐☐

☕☕☕☕...

☐☐☐☐☐☐

☐☐☐☐☐☐☐☐☐☐☐☐

[illegible]

□ □ □ □ □ . . .

□ □ □ □ □ . . .

□ □ □ □ . . .

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

1111111111111111

□□□□□

\$ node breakfast.js

□□□□□□□□□□

☕ vs 🍞

▶ ☕□□□□□□□□□□

▶ 🍞□□□□□□□□□□

☕ 2s

🍞 1.5s

🔍 1s

☕ + 🍞 + 🔍 = 2 + 1.5 + 1 = 4.5    ☕ = max(2, 1.5, 1) = 2

PART 02

# Promise

□□□□□□□□□□

□□□□□□□□

**pending**

□□□□□□

**fulfilled**

□□□□resolve("🍌🍌")

**rejected**

□□□□reject("🍌🍌")

```
1 let myPromise = new Promise((resolve, reject) => {
2   let success = true;
3   setTimeout(() => {
4     if (success) resolve("🍌🍌");
5     else reject("🍌🍌");
6   }, 2000);
7 });
8
9 myPromise.then(result => console.log(result))
10 .catch(error => console.log(error));
```



## □□□□□ Promise.race + AbortController

## Promise.race

[illegible]

## AbortController

PART 03

# async / await

□□□□□□□□□□

**then** **NOGRAPH** → **await**

```
await then async/await then
```



```
1  async function serial() {  
2    const coffee = await makeCoffee();  
3    const toast = await makeToast();  
4    return [coffee, toast];  
5  }
```

TOTAL TIME

$\approx 2 + 1.5 = 3.5s$

□□

token API — □□□□□



```
1  async function parallel() {  
2    const [coffee, toast] = await Promise.all([  
3      makeCoffee(),  
4      makeToast(),  
5    ]);  
6    return [coffee, toast];  
7  }
```

TOTAL TIME

$\approx \max(2, 1.5) = 2s$

□□

token API

# Promise.all vs allSettled

|       | Promise.all                                                                                                                                                                     | Promise.allSettled        |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| □□□□□ |  reject  □□□□ | □□□□□□□                   |
| □□    | □□□□                                                                                                                                                                            | {status, value/reason} □□ |
| □□    | □□□□□□□                                                                                                                                                                         | □□□□□□□□□□                |


\$ npm run all □□□□□□□□ allSettled □□□□□□□

PART 04

# Event Loop

0000 VIP 0000000000

□ □ □ □ □ □ □ □ □



□□□□VIP□  
□□□□□□□□□□

□□□□□□□□  
□□□□□□□□□□□□



```
1 console.log("1");
2 setTimeout(() => console.log("2"), 0);
3 Promise.resolve().then(() => console.log("3"));
4 console.log("4");
```

#### ANSWER

1 → 4  
→ 3  
→ 2

1 → 4 → 3 → 2




□ □ □ □ □ □ □ □ □ □ □ □ □ □

□□□□□pending → fulfilled / rejected

await Promise.all

[illegible]



# Breakfast served.

fetch AbortController

```
$ node breakfast.js --mode=async
```

promise → await → race → event loop