



TilBuci

Scripting Actions

All user interaction on TilBuci is managed by JSON-formatted texts with instructions about how to handle both input and playback flow. This document describes this format with all available instructions.

Lucas Junqueira, February 12th, 2025



Contents

1. Scripting actions on TilBuci	11
1.1. Where do I use these interaction scripts?	12
1.1.1. User click/touch.....	12
1.1.2. Movie load	13
1.1.3. Scene start	13
1.1.4. Keyframe end.....	14
1.1.5 Media playback end	15
1.2. Variables	15
1.3. Globals	16
1.3.1. Boolean globals	17
1.3.2. Number globals	17
1.3.3. Text globals	18
1.3.4. Input values.....	18
1.4. Strings.json file.....	19
1.5. Instance text and replace	20
1.5.1. Content replace at runtime	20
2. Available actions.....	21
2.1. Boolean conditions	21
if.bool.....	21
if.boolset.....	21
2.2. Boolean values.....	21
bool.clear.....	21
bool.clearall.....	21
bool.set	21
bool.setinverse	22
2.3. Data	22
data.event	22
data.eventclear.....	22
data.liststates.....	22
data.load	23



data.loadlocal	23
data.loadquickstate	23
data.loadstatelocal	24
data.save	24
data.savelocal	24
data.savequickstate	24
data.savestate	25
data.savestatelocal	25
2.4. Float conditions.....	25
if.floatsdifferent	25
if.floatsequal	25
if.floatset	25
if.floatgreater	26
if.floatgreaterequal	26
if.floatlower	26
if.floatlowerequal	26
2.5. Float values	26
float.abs	27
float.clear	27
float.clearall	27
float.divide	27
float.max	27
float.min	27
float.multiply	27
float.random	28
float.set	28
float.subtract.....	28
float.sum	28
float.toint.....	28
float.tostring	28
2.6. Input	29
input.email.....	29
input.float	29
input.int.....	29



input.list	30
input.login	30
input.message	31
input.string	31
input.add	31
input.place	31
input.remove	31
input.removeall	32
input.settext	32
input.setpassword	32
input.addnumeric	32
input.placenumeric	32
input.removenumeric	32
input.removeallNumerics	32
input.setnumeric	32
input.setnumericbounds	33
input.addtoggle	33
input.placetoggle	33
input.removetoggle	33
input.removealltoggles	33
input.settoggle	33
input.inverttoggle	33
2.7. Instance	34
instance.clearall	34
instance.clearalpha	34
instance.clearcolor	34
instance.clearcoloralpha	34
instance.clearfont	34
instance.clearfontalign	34
instance.clearfontbackground	34
instance.clearfontbold	35
instance.clearfontcolor	35
instance.clearfontitalic	35
instance.clearfontleading	35



instance.clearfontsize	35
instance.clearheight	35
instance.clearorder.....	35
instance.clearrotation	36
instance.clearvisible	36
instance.clearvolume.....	36
instance.clearwidth	36
instance.clearx	36
instance.cleary	36
instance.loadasset.....	36
instance.next.....	36
instance.pause	37
instance.play	37
instance.playpause.....	37
instance.previous	37
instance.scrollbottom	37
instance.scrolldown	37
instance.scrolltop	37
instance.scrollup	37
instance.seek	37
instance.setalpha	38
instance.setcolor.....	38
instance.setcoloralpha	38
instance.setfont	38
instance.setfontalign	38
instance.setfontbackground.....	38
instance.setfontbold	39
instance.setfontcolor	39
instance.setfontitalic	39
instance.setfontleading	39
instance.setfontsize.....	39
instance.setheight.....	39
instance.setorder	39
instance.setparagraph	40



instance.setrotation.....	40
instance.setvisible.....	40
instance.setvolume	40
instance.setwidth	40
instance.setx.....	40
instance.sety.....	41
instance.stop.....	41
instance.zoom	41
2.8. Integer conditions	41
if.intsdifferent.....	41
if.intsequal	41
if.intset.....	41
if.intgreater.....	42
if.intgreaterequal	42
if.intlower.....	42
if.intlowerequal	42
2.9. Integer values	42
int.abs.....	42
int.clear.....	43
int.clearall.....	43
int.divide	43
int.max.....	43
int.min	43
int.multiply	43
int.random	44
int.set	44
int.subtract	44
int.sum.....	44
int.tofloat.....	44
int.tostring	44
2.10. Movie.....	45
movie.load	45
2.11. Replace	45
replace.clearfile	45



replace.clearstring	45
replace.clearallfiles	45
replace.clearallstrings	45
replace.origin	45
replace.setfile	45
replace.setstring	46
if.replacefileset	46
if.replacestringset	46
2.12. Scene	46
scene.load	46
scene.navigate	46
scene.pause	46
scene.play	46
scene.playpause	47
scene.nextkeyframe	47
scene.previouskeyframe	47
scene.loadfirstkeyframe	47
scene.loadlastkeyframe	47
scene.loadkeyframe	47
2.13. Snippets	47
run	47
2.14. String conditions	47
if.stringcontains	47
if.stringendswith	48
if.stringsdifferent	48
if.stringsequal	48
if.stringset	48
if.stringstartswith	48
if.stringemail	48
2.15. String values	49
string.clear	49
string.clearall	49
string.clearglobal	49
string.concat	49



string.replace	49
string.set	49
string.setglobal	50
string.setgroup	50
string.tofloat	50
string.toint	50
2.16. System	50
system.copytext	50
system.fullscreen	50
system.visitoringroup	50
system.logout.....	51
system.openembed	51
system.closeembed	51
system.embedreset.....	51
system.embedplace.....	51
system.openurl	52
system.quit	52
system.sendevent	52
system.setkftime	52
2.17. Text	52
css.clear	52
css.set.....	52
2.18. Timer.....	52
timer.clear.....	52
timer.clearall	53
timer.set	53
3. Plugin actions	54
3.1. Debug plugin	54
trace	54
trace.bools	54
trace.ints	54
trace.floats.....	54
trace.strings.....	54
debuginfo.hide.....	54



debuginfo.show	54
3.2. Share	55
share.facebook	55
share.linkedin	55
share.pinterest	55
share.reddit	55
share.x	55
3.3. Google Analytics	55
analytics.event	55
3.4. Server Call	56
call.process	56
call.sdprocess	57
call.url	57
3.5. Overlay	57
overlay.show	57
4. Contraptions	61
4.1. Menu	61
contraption.menu	61
contraption.menuhide	62
4.2. Cover	62
contraption.cover	62
contraption.coverhide	63
4.3. Loading icon	63
contraption.showloading	63
contraption.hideloadng	63
5. Code assist	64
5.1. Movie and scene actions	65
5.2. Instance and media	66
5.3. Variable actions and conditions	67
5.4. Data and input handling	68
5.5. Additional actions	69
5.6. Contraptions	70
5.7. Available plugins	71
6. Block editor	72



TilBuci

Scripting Actions

Version 12 - 2025/04/12



1. Scripting actions on TilBuci

You may create beautiful scenes and animations on TilBuci but they won't be really useful if you don't provide user interaction to them. A good interaction design is fundamental for your content to get life!

To enable these interactions, TilBuci uses a JSON-formatted text describing the actions. If you are not familiar with the JSON concept, is it a data format based on JavaScript. You don't really need to go too deep on JSON to use it on TilBuci, but if you are interested on it, please check out json.org for further information.

The TilBuci actions are always provided as an *object* with at least two fields: *ac*, a simple string, and *param*, an array of strings (all parameters must be provided as strings, even numeric ones like "3.1416"). If an action does not require parameters, the *param* value must still be given as an empty array.

```
{
  "ac": "actionhere",
  "param": [ "param1", "param2", "param3" ]
}
```

Actions may also be provided as an array of objects. You can use these arrays on every place that accepts a single action.

```
[
  { "ac": "firstaction", "param": [ "param1" ] },
  { "ac": "secondaction", "param": [ ] }
]
```


There are some actions, like conditionals, timers and inputs, that may accept additional fields. Check out the following example:

```
{
  "ac": "if.stringsequal",
  "param": [ "$okemail", "name@email.com" ],
  "then": {
    "ac": "timer.set",
    "param": [ "displaytimer", "1000", "1" ],
    "tick": [ ],
    "end": { "ac": "scene.load", "param": [ "userscene" ] }
  },
  "else": [
    { "ac": "timer.clearall", "param": [ ] },
    {
      "ac": "input.login",
      "param": [ ],
      "ok": {
        "ac": "string.set",
        "param": [ "okemail", "$_USERNAME" ]
      }
    }
  ]
}
```



```
    },  
    "cancel": {  
      "ac": "string.clear",  
      "param": [ "okemail" ]  
    }  
  }  
]  
}
```

You can input your action script on its window at the editor. By clicking on *ok* your JSON text will be evaluated for errors (notice that this will only look for text inconsistencies, not your script logic).




1.1. Where do I use these interaction scripts?

You can provide action scripts on many places. The usual one is on an user click/touch of an instance, but there are many more.

1.1.1. User click/touch


This is the usual place to set an action script. Just select an instance on the stage and click the *Actions > Trigger actions* button at the right menu to show the scripting window.






1.1.2. Movie load

You can provide actions to run just after your movie is loaded. Look for the *Movie > Properties* right menu and access the *Start actions* tab.




The movie properties window also gives you access to the action snippets. These are groups of actions that can be easily reused on your entire movie by calling the *run* command.




1.1.3. Scene start

You can set actions to run when a scene starts playing. Check out the *Start actions* tab from the *Scene > Properties* menu.



1.1.4. Keyframe end


Scenes can contain multiple keyframes. You may set actions to run at the end of each of them. You can set these actions either from the *Keyframes* tab of the *Scene > Properties* menu or the *Keyframes > Manage* one.





1.1.5 Media playback end

Actions triggered when a media, like a movie, finishes playing.



1.2. Variables

You can use variables on TilBuci actions to help design your interactions. Four variable types are available:

- Boolean
- Float
- Integer
- String

There are many actions that set the values for each of these types. The basic ones are *bool.set*, *int.set*, *float.set* and *string.set*. Every time a variable is set you can use it on any action that requires parameters of that type by using the variable name preceded by the appropriate symbol: *?* for Boolean, *#* for integer or float and *\$* for string. Here are some examples:

```
[
  { "ac": "bool.set", "param": [ "boolvar1", "true" ] },
  {
    "ac": "if.bool",
    "param": [ "?boolvar1" ],
    "then": { "ac": "scene.load", "param": [ "tilbuci" ] },
  }
]
```




```
        "else": [ ]
    },
    { "ac": "int.set", "param": [ "intvar1", "10" ] },
    {
        "ac": "int.sum",
        "param": [ "intvar2", "#intvar1", "20" ]
    },
    { "ac": "float.set", "param": [ "floatvar1", "10.7" ] },
    { "ac": "float.set", "param": [ "floatvar2", "10.5" ] },
    {
        "ac": "float.min",
        "param": [ "floatvar3", "#floatvar1", "#floatvar2" ]
    },
    { "ac": "string.set", "param": [ "stringvar1", "Til" ] },
    {
        "ac": "string.concat",
        "param": [ "stringvar2", "$stringvar1", "Buci" ]
    }
]
```

When you use the # mark TilBuci will look for a float variable first and, if not found, look for an integer one. Every time a float is used on integer operations it will be rounded.

1.3. Globals

Besides the variables you can set on your own, TilBuci comes with several global values you can use on your actions to retrieve all sorts of information from the playback. You can use them just like the variables.

Some of these globals are always available, but you can also set your own per movie. Access the left menu *Movie > Properties* and look for the *Texts*, *Numbers* and *Flags* tabs.





To access these globals you must use `$_TEXTS:`, `#_NUMBERS:` or `?_FLAGS:`, according to the type. `#_NUMBERS:` can be used as both integer and float values – it will be rounded for integers. Place the global name you set after the `:` on your scripts, like this example:

```
{
  "ac": "string.set",
  "param": [ "stringvar1", "$_TEXTS:my global" ]
}
```

Another group of globals that use `:` to retrieve information are the ones about instance properties. Place the instance id after the `:` to retrieve the correct value like:

```
{
  "ac": "int.set",
  "param": [ "intvar1", "#_INSTANCEWIDTH:my instance id" ]
}
```

Besides these values, plugins may also define their own globals that add to the standard ones.

1.3.1. Boolean globals

General globals

?_PLAYING	Is the movie playing right now?
?_SERVER	Online server connection active?
?_USERLOGGED	Is there an user logged?
?_HADINTERACTION	Has the visitor ever interacted?

Instance globals

?_INSTANCEPLAYING	playing content?
?_INSTANCEVISIBLE	instance visible?
?_INSTANCEFONTBOLD	text set to bold?
?_INSTANCEFONTITALIC	text set to italic?

1.3.2. Number globals

General globals

#_KEYFRAME	Current keyframe number (starts on 0).
#_AREABIG	Movie "big" dimension.
#_AREASMALL	Movie "small" dimension.
#_CONTENTX	Movie display actual X position
#_CONTENTY	Movie display actual Y position
#_CONTENTWIDTH	Movie display actual width
#_CONTENTHEIGHT	Movie display actual height

Instance globals

#_INSTANCEX	x position
#_INSTANCEY	y position
#_INSTANCEWIDTH	width
#_INSTANCEHEIGHT	height
#_INSTANCEALPHA	alpha value (0 to 1.0)
#_INSTANCEVOLUME	sound volume



#_INSTANCEORDER	order index (starts on 0)
#_INSTANCECOLORALPHA	color overlay alpha (0 to 1.0)
#_INSTANCEROTATION	rotation (0 to 359, experimental)
#_INSTANCEFONTSIZE	text font size
#_INSTANCEFONTLEADING	text leading

1.3.3. Text globals

General globals

\$_MOVIE_TITLE	Current movie title
\$_MOVIE_ID	Current movie id
\$_SCENE_TITLE	Current scene title
\$_SCENE_ID	Current scene id
\$_ORIENTATION	Player orientation (horizontal or vertical)
\$_RENDER	Current display render mode (webgl or dom)
\$_RUNTIME	The current runtime (see below for details)
\$_URLMOVIE	Url to accesse current movie directly
\$_URLSCENE	Url to access current movie+scene directly
\$_USERNAME	Logged user name (e-mail)
\$_VERSION	Current TilBuci player version
\$_WSSERVER	URL for the current webservice requests
\$_SESSION	Current player session ID
\$_YEAR	Current year as YYYY
\$_MONTH	Current month as MM
\$_DAY	Current day as DD
\$_HOUR	Current hour as HH (24h)
\$_MINUTE	Current minute as MM
\$_SECOND	Current seconds as SS
\$_DATE	Current date as YYYY-MM-DD
\$_TIME	Current time as HH:MM:SS (24h)

The Tilbuci content can be played on different runtimes. If necessary, the `$_RUNTIME` global can be used to find out the current one. The possible returns are:

website	Running from an exported website
pwa	Running as a pwa application
desktop	Running from a desktop application (Windows, Linux or macOS)
mobile	Running from a mobile app (Android or iOS/iPadOS)
publish	Running from a publish service like itch.io
embed	Running form a TilBuci player embed on an OpenFL project
tilbuci	Running from the TilBuci installation (default)

Instance globals

\$_INSTANCECOLOR	Overlay color (0x##### hex format)
\$_INSTANCETEXT	Current text set to instance
\$_INSTANCEFONT	Text font name
\$_INSTANCEFONTCOLOR	Text font color (0x##### hex format)

1.3.4. Input values

You can create input elements using actions. Every input has an unique name that can be used to retrieve its current value, just



inform the given name after the : like "\$_INPUT:name". The possible values are:

\$_INPUT	text input value
#_NUMERIC	numeric stepper value
?_TOGGLE	toggle input value

1.4. Strings.json file

Another way to work with strings is the usage of a *strings.json* file. You may upload this file containing pairs of string variable names and values to simplify your creation. At this file, the string variables must be grouped so you can easily change their value from an user interaction (like changing language settings) – you can use any name you want for the groups. A simple *strings.json* file content will look like this:

```
{
  "group1": {
    "string1": "site name: ",
    "string2": "site: "
  },
  "group2": {
    "string1": "nome da página: ",
    "string2": "página: "
  },
}
```

Before using the *strings.json* content you must set the values group with the *string.setgroup* action, like this:

```
[
  { "ac": "string.setgroup", "param": [ "group1" ] },
  {
    "ac": "string.concat",
    "param": [ "stringvar1", "$string1", "TilBuci" ]
  }
]
```

The script above will set the value of *\$stringvar1* to "site name: TilBuci". However, if you set another group, the results are different:

```
[
  { "ac": "string.setgroup", "param": [ "group2" ] },
  {
    "ac": "string.concat",
    "param": [ "stringvar1", "$string1", "TilBuci" ]
  }
]
```

In that case, the *\$stringvar1* value will be "nome da página: TilBuci".



1.5. Instance text and replace

When you set a string variable (by using an action or with the *strings.json* file) you can also retrieve its value on instance text. When you create a paragraph image, just use the variable name (and nothing more) instead of directly input the text. It will be automatically replaced by the current value of the variable when it shows up.

1.5.1. Content replace at runtime

Besides setting a single variable to an instance, you may also set values to be automatically replaced at runtime in both instance display and action operations. There are two actions to set these replacements.

First, *replace.setstring*: using this action you will set string parts that will always be replaced by something else, on paragraph and html instances and also on usual string operations.

```
[
  { "ac": "replace.setstring", "param": [ "[MAIL]", "$_USERNAME" ] },
  { "ac": "string.set", "param": [ "stringvar1", "my email is [MAIL]" ] }
]
```

If there is an user logged with the e-mail "doggo@tilbuci.com.br", the *\$stringvar1* variable will receive the value "my email is doggo@tlbuci.com.br". Also, if you set an html instance content to a file with "<p>the e-mail address is [MAIL]<p>", it will be shown as "the e-mail address is doggo@tlbuci.com.br" as well.

The second automatic replace you can set affects file names used by audio, html, picture and video instances. If you call *repace.setfile*, every time TilBuci attempts to load a file, it will look for the needle text on the name and replace it. This can be very useful to load different assets based on user language choices. Check out this example: if you are using a picture named "en/title.png" on your movie, after you call the following action, TilBuci will load "pt/title.png" instead.

```
{ "ac": "replace.setfile", "param": [ "en/", "pt/" ] }
```



2. Available actions

Here we present a list of currently available actions on TilBuci (*ac* field at the action object). Please note that plugins may add additional commands to this list. Some of these actions require parameters, but even if none is needed you still must add the *param* field to the object. Additional optional fields can be used on some actions, like *then*, *else*, *ok*, *cancel*, *tick*, *end*, *success* and *error*.

2.1. Boolean conditions

Conditional statements based on boolean values.

if.bool

Checks if the boolean value is true.

params

1. the boolean variable to check

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.boolset

Checks if a boolean variable exists.

params

1. the variable name to check

additional optional object fields

- then: actions to run if true
- else: actions to run if false

2.2. Boolean values

Management of boolean variables.

bool.clear

Removes a boolean variable.

params

1. the variable name

bool.clearall

Removes all boolean variables.

bool.set

Sets a boolean variable.

params



1. the variable name
2. the variable value

bool.setinverse

Inverts the value of a boolean variable.

params

1. the variable name

2.3. Data

These actions handle user persistent data management. This can be done both locally on the browser storage or remotely using your server. The user must be logged in to access remote data. Logged user can still access local data. TilBuci uses a dark default theme for the load state UI, but you can adjust the colors according to your content at the *UI colors* tab of the *Movie properties* window.

data.event

Registers an event on TilBuci database at the "events" table. You may use events to record visitor interactions and keep track of your movies' access. While the Google Analytics plugin offers a more sophisticated approach, the *data.event* action is easier to use and keeps the data in your own server.

All events must receive a name, and you can add as many information you want providing additional string parameters to the action call. All events are recorded with the current movie, scene and visitor information. Access the Visitor button on the left menu and go to the Event tab to download the recorded information for analysis.

If TilBuci finds an error while sending the event to the server, such as an Internet connection failure, the data is recorded locally and sent together with the next event sending action. TilBuci holds up to 100 unsent events for future sending. When exporting the events spreadsheet from the "Visitors" left menu on TilBuci editor, both the received date/time and the original one are included.

params

1. the event name

data.eventclear

Clears the unsent events pool for the current movie.

data.liststates

Shows the load state window so the user can choose the one to load from the last 3 saved states on server. When loaded, the current



variable values are replaced by the saved ones and the scene playing while the state was saved is loaded. All interface text must be set as text globals at the *Text* tab of the *Movie properties* window – if not set, default English strings are used. The text names you must set to avoid using default values are shown on table below. Global texts can be changed at runtime by using the *string.setglobal* action.

Global	Description	Default value
titlestates	Window title	Select a state to load
waistates	States load wait message	Please wait while a list of available saves states is loaded.
selectstate	Selects state message	Select a state to load.
nostates	No save states found message	Sorry, no saved states found to load.
dateformat	Date/time format string	Y-m-d h:i a (use the PHP format described here: https://www.php.net/manual/en/datetime.format.php)

additional optional object fields

- success: actions to run after successful data load
- error: actions to run after error on data load

data.load

Loads custom data saved at the server. The loaded values replaces the variables used on *data.save* action.

params

1. data save name

additional optional object fields

- success: actions to run after successful data load
- error: actions to run after error on data load

data.loadlocal

Loads custom data saved at the browser storage. The loaded values replaces the variables used on *data.save/local* action.

params

1. data save name

additional optional object fields

- success: actions to run after successful data load
- error: actions to run after error on data load

data.loadquickstate

Loads the quick state saved on the server. When loaded, the current variable values are replaced by the saved ones and the scene playing while the state was saved is loaded.

additional optional object fields

- success: actions to run after successful data load
- error: actions to run after error on data load



data.loadstatelocal

Loads the state saved on browser storage. When loaded, the current variable values are replaced by the saved ones and the scene playing while the state was saved is loaded.

additional optional object fields

- success: actions to run after successful data load
- error: actions to run after error on data load

data.save

Saves custom data at the server. At least two parameters are required, but you can add as many as you want to be saved under the same name. Each saved value must be the name of an already set variable, preceded by its type, like in the following table.

Variable type	Prefix	Example
boolean	B:	B:boolvar1
float	F:	F:floatvar1
integer	I:	I:intvar1
string	S:	S:stringvar1

params

1. data save name
2. first variable to save

additional optional object fields

- success: actions to run after successful data save
- error: actions to run after error on data save

data.savelocal

Saves custom data at the browser storage. At least two parameters are required, but you can add as many as you want to be saved under the same name. Each saved value must be the name of an already set variable, preceded by its type, like in the following table.

Variable type	Prefix	Example
boolean	B:	B:boolvar1
float	F:	F:floatvar1
integer	I:	I:intvar1
string	S:	S:stringvar1

params

1. data save name
2. first variable to save

additional optional object fields

- success: actions to run after successful data save
- error: actions to run after error on data save

data.savequickstate

Quickly saves all current variable values as well the current scene playing on the server. Saving a quick save overrides the previously saved one for current user/movie.



additional optional object fields

- success: actions to run after successful data save
- error: actions to run after error on data save

data.savestate

Saves all current variable values as well the current scene playing on the server. The server holds up to 3 save states for each user on each movie, besides the *quick save*.

params

1. state title (for reference while loading)

additional optional object fields

- success: actions to run after successful data save
- error: actions to run after error on data save

data.savestatelocal

Saves all current variable values as well the current scene playing on the browser storage. The browser can hold only one state per movie.

additional optional object fields

- success: actions to run after successful data save
- error: actions to run after error on data save

2.4. Float conditions

Conditional statements based on float values.

if.floatsdifferent

Checks if the two float values are different.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.floatsequal

Checks if the two float values are equal.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.floatset

Checks if a float variable exists.

params



1. the variable name to check
- additional optional object fields
- then: actions to run if true
 - else: actions to run if false

if.floatgreater

Checks if the first value is greater than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.floatgreaterequal

Checks if the first value is greater or equal than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.floatlower

Checks if the first value is lower than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.floatlowerequal

Checks if the first value is lower or equal than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

2.5. Float values

Management of float variables.



float.abs

Returns the absolute value of a float.

params

1. the variable name to receive the result
2. the value

float.clear

Removes a float variable.

params

1. the variable name

float.clearall

Removes all float variables.

float.divide

Divides two or more float values. At least 3 parameters are required but you can provide as many as you want and their values are sequentially divided.

params

1. the variable name to receive the result
2. the first value
3. the second value

float.max

Returns the maximum between two float values.

params

1. the variable name to receive the result
2. the first value
3. the second value

float.min

Returns the minimum between two float values.

params

1. the variable name to receive the result
2. the first value
3. the second value

float.multiply

Multiplies two or more float values. At least 3 parameters are required but you can provide as many as you want and their values are sequentially multiplied.

params

1. the variable name to receive the result



2. the first value
3. the second value

float.random

Generates a random float value.

params

1. the variable name to receive the random value
2. minimum value
3. maximum value

float.set

Sets a float variable.

params

1. the variable name
2. the variable value

float.subtract

Subtracts two or more float values. At least 3 parameters are required but you can provide as many as you want and their values are subtracted from the result.

params

1. the variable name to receive the result
2. the first value
3. the second value

float.sum

Sums two or more float values. At least 3 parameters are required but you can provide as many as you want and their values are added to the result.

params

1. the variable name to receive the result
2. the first value
3. the second value

float.toint

Converts a float value to an int one (rounds).

params

1. the int variable name to receive the result
2. the float value

float.tostring

Converts a float value to a string.

params

1. the string variable name to receive the result
2. the float value



2.6. Input

These actions asks for user input to use on the movie. TilBuci uses a dark default theme for input UI, but you can adjust the colors according to your content at the *UI theme* tab of the *Movie properties* window.

Besides the preferred input boxes you may add input elements right into your design using actions. These inputs appear over any graphics on your scene and must also be removed using actions (they do not automatically disappear when a new scene is loaded). The size/place given is relative to your content. These elements also respect the *UI theme* settings of your movie.

input.email

Shows a text input window the checks for a valid e-mail address on confirmation. You may also add buttons to include common e-mail service domains like "@gmail.com" – just add additional string parameters.

params

1. string variable name to get the resulting e-mail address
2. text to display on input window
3. common email service domain, like "@hotmail.com" (optional)

additional optional object fields

- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.float

Shows a dialog window asking for a float input.

params

1. float variable name to get the resulting input
2. text to display on input window
3. numeric stepper step value
4. minimum input value
5. maximum input value

additional optional object fields

- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.int

Shows a dialog window asking for an int input.

params

1. int variable name to get the resulting input
2. text to display on input window
3. numeric stepper step value
4. minimum input value
5. maximum input value

additional optional object fields



- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.list

Presents a list to the user asking for a selection. You must provide at least 4 parameters, but you may add as many as you want – they will be add as additional item options. The returned value is the text of the option selected.

params

4. string variable name to get the resulting input
5. text to display on input window
6. first list option
7. second list option

additional optional object fields

- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.login

Starts the user login procedure. Login is done by sending a confirmation code to the provided e-mail address. All interface text must be set as text globals at the *Text* tab of the *Movie properties* window – if not set default English strings are used. The text names you must set to avoid using default values are shown on table below. Global texts can be changed at runtime by using the *string.setglobal* action.

Global	Description	Default value
logintitle	Window title	Login
logintext	Window message	Please type your e-mail address. You'll receive a 6 digit code to confirm your identity.
termsagree	Terms agree message	I agree with the above terms.
invalidemail	Invalid email address input	Please provide a valid e-mail address.
emailwait	Processing message	Please wait while a confirmation code is sent to your e-mail.
noemailsent	Send email error message	Error while sending the code by e-mail. Please try again.
checkforcode	Code check instructions	Please check out your e-mail inbox. Type below the 6 digit code you received. If you do not find the message, take a look at you spam folder.
codewait	Code check processing	Please wait while the provided code is checked.
invalidcode	Invalid code message	The provided code is invalid. Please try again.
emailsubject	E-mail message subject	TilBuci login
emailbody	E-mail message body	Hi, you are receiving this message to confirm your login at TilBuci. Please provide the code below to proceed:\r\n\r\n[CODE]\r\n\r\nIf you didn't request this code, don't worry: just ignore this message.
emailsender	E-mail sender name	TilBuci



additional optional object fields

- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.message

Shows a message to the user asking for confirmation. If no cancel action is set, the window will only show the ok button.

params

1. window title
2. window text

additional optional object fields

- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.string

Shows a dialog window asking for a string input.

params

1. string variable name to get the resulting input
2. text to display on input window

additional optional object fields

- ok: actions to run after user clicks on ok
- cancel: actions to run after user click on cancel

input.add

Adds a text input element into your screen.

params

1. the input name
2. the x position
3. the y position
4. the width (height is automatically set from the font size of UI theme)
5. (optional) placeholder to show when no text is set

input.place

Sets a text input placement.

params

1. the input name
2. the x position
3. the y position
4. the width (height is automatically set from the font size of UI theme)

input.remove

Removes a text input from screen.

params

1. the input name



input.removeall

Removes all text inputs from screen.

input.settext

Sets the text of a text input element.

params

1. the input name
2. the new text

input.setpassword

Sets a text input password mask display

params

1. the input name
2. show as password? (true/false)

input.addnumeric

Adds a numeric stepper input element into your screen.

params

1. the input name
2. the initial value
3. the minimum value
4. the maximum value
5. the increase/decrease step

input.placenumeric

Sets a numeric stepper input placement.

params

1. the input name
2. the x position
3. the y position
4. the width (height is automatically set from the font size of UI theme)

input.removenumeric

Removes a numeric stepper input from screen.

params

1. the input name

input.removeallnumerics

Removes all numeric stepper inputs from screen.

input.setnumeric

Sets the value of a numeric stepper input element.

params

1. the input name



2. the new value

input.setnumericbounds

Sets a numeric stepper bounds.

params

1. the input name
2. minimum value
3. maximum value
4. increase/decrease step

input.addtoggle

Adds a toggle stepper input element into your screen.

params

1. the input name
2. toggle selected?
3. X position
4. Y position

input.placetoggle

Sets a toggle input placement.

params

1. the input name
2. the x position
3. the y position

input.removetoggle

Removes a toggle input from screen.

params

1. the input name

input.removealltoggles

Removes all toggle inputs from screen.

input.settoggle

Sets the value of a toggle input element.

params

1. the input name
2. the new value

input.inverttoggle

Inverts a toggle input value.

params

1. the input name



2.7. Instance

instance.clearall

Clears any previously set value (instance returns to design setting).

param

1. instance id

instance.clearalpha

Clears previously set alpha value (instance returns to design setting).

param

1. instance id

instance.clearcolor

Clears previously set color overlay value (instance returns to design setting).

param

1. instance id

instance.clearcoloralpha

Clears previously set overlay alpha value (instance returns to design setting).

param

1. instance id

instance.clearfont

Clears previously set font face name value (instance returns to design setting).

param

1. instance id

instance.clearfontalign

Clears previously set text align value (instance returns to design setting).

param

1. instance id

instance.clearfontbackground

Clears previously set font background value (instance returns to design setting).

param

1. instance id



instance.clearfontbold

Clears previously set font bold state value (instance returns to design setting).

param
1. instance id

instance.clearfontcolor

Clears previously set font color value (instance returns to design setting).

param
1. instance id

instance.clearfontitalic

Clears previously set font italic state value (instance returns to design setting).

param
1. instance id

instance.clearfontleading

Clears previously set font leading value (instance returns to design setting).

param
1. instance id

instance.clearfontsize

Clears previously set font size value (instance returns to design setting).

param
1. instance id

instance.clearheight

Clears previously set height value (instance returns to design setting).

param
1. instance id

instance.clearorder

Clears previously set order value (instance returns to design setting).

param
1. instance id



instance.clearrotation

Clears previously set rotation value (instance returns to design setting - experimental).

param
1. instance id

instance.clearvisible

Clears previously set visible state (instance returns to design setting).

param
1. instance id

instance.clearvolume

Clears previously set sound volume value (instance returns to design setting).

param
1. instance id

instance.clearwidth

Clears previously set width value (instance returns to design setting).

param
1. instance id

instance.clearx

Clears previously set x value (instance returns to design setting).

param
1. instance id

instance.cleary

Clears previously set y value (instance returns to design setting).

param
1. instance id

instance.loadasset

Loads a collection asset into the instance.

param
1. instance id
2. new asset id to load

instance.next

Load the next collection item on instance.

param
1. instance id



instance.pause

Pauses an instance content.

param

1. instance id

instance.play

Plays an instance content.

param

1. instance id

instance.playpause

Plays an instance content if it is paused, pauses it otherwise.

param

1. instance id

instance.previous

Load the previous collection item on instance.

param

1. instance id

instance.scrollbottom

Scrolls text to bottom.

param

1. instance id

instance.scrolldown

Scrolls text down.

param

1. instance id

instance.scrolltop

Scrolls text to top.

param

1. instance id

instance.scrollup

Scrolls text up.

param

1. instance id

instance.seek

Jumps an instance to a time position (integer, seconds).



param

1. instance id
2. time position

instance.setalpha

Changes the instance alpha level (0 to 1.0).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setcolor

Changes the instance overlay color (0x##### hex format).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setcoloralpha

Changes the instance color overlay alpha level (0 to 1.0).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setfont

Changes the instance font face name.

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setfontalign

Changes the instance alignment (*left*, *right*, *center* or *justify*).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setfontbackground

Changes the instance font background color (0x##### hex format, empty string for none).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)



instance.setFontbold

Changes the instance font to bold (boolean).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setFontcolor

Changes the instance text font color (0x##### hex format).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setFontitalic

Changes the instance font to italic (boolean).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setFontleading

Changes the instance font leading space (integer).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setFontsize

Changes the instance text font size (int value).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setheight

Changes the instance height size (numeric).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setorder

Changes the instance order on display list (int value).



param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setparagraph

Sets a paragraph instance content.

param

1. instance id
2. new text

instance.setrotation

Changes the instance rotation (experimental).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setvisible

Changes the instance visible state (boolean).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setvolume

Changes the instance sound volume (0 to 1.0).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setwidth

Changes the instance width size (numeric).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.setx

Changes the instance x position (numeric).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)



instance.sety

Changes the instance y position (numeric).

param

1. instance id
2. new value for horizontal display
3. new value for vertical display (optional)

instance.stop

Stops an instance playback.

param

1. instance id

instance.zoom

Enlarges the instance content to cover the stage. Works on picture and video content. The enlarged content will be hidden on user click.

param

1. instance id

2.8. Integer conditions

Conditional statements based on integer values.

if.intsdifferent

Checks if the two int values are different.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.intsequal

Checks if the two int values are equal.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.intset

Checks if an int variable exists.

params

1. the variable name to check



additional optional object fields

- then: actions to run if true
- else: actions to run if false

if.intgreater

Checks if the first value is greater than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.intgreaterequal

Checks if the first value is greater or equal than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.intlower

Checks if the first value is lower than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

if.intlowerequal

Checks if the first value is lower or equal than the second one.

params

1. first value
2. second value

additional optional object fields

- then: actions to run if the result is true
- else: actions to run if the result is false

2.9. Integer values

Management of integer variables.

int.abs

Returns the absolute value of an int.



params

1. the variable name to receive the result
2. the value

int.clear

Removes an int variable.

params

1. the variable name

int.clearall

Removes all int variables.

int.divide

Divides two or more int values. At least 3 parameters are required but you can provide as many as you want and their values are sequentially divided.

params

1. the variable name to receive the result
2. the first value
3. the second value

int.max

Returns the maximum between two int values.

params

1. the variable name to receive the result
2. the first value
3. the second value

int.min

Returns the minimum between two int values.

params

1. the variable name to receive the result
2. the first value
3. the second value

int.multiply

Multiplies two or more int values. At least 3 parameters are required but you can provide as many as you want and their values are values are sequentially multiplied.

params

1. the variable name to receive the result
2. the first value
3. the second value



int.random

Generates a random int value.

params

1. the variable name to receive the random value
2. minimum value
3. maximum value

int.set

Sets an int variable.

params

1. the variable name
2. the variable value

int.subtract

Subtracts two or more int values. At least 3 parameters are required but you can provide as many as you want and their values are subtracted from the result.

params

1. the variable name to receive the result
2. the first value
3. the second value

int.sum

Sums two or more int values. At least 3 parameters are required but you can provide as many as you want and their values are added to the result.

params

1. the variable name to receive the result
2. the first value
3. the second value

int.tofloat

Converts an int value to a float one.

params

1. the float variable name to receive the result
2. the int value

int.tostring

Converts an int value to a string.

params

1. the string variable name to receive the result
2. the int value



2.10. Movie

movie.load

Loads a new movie into player.

params

1. new movie id

2.11. Replace

Use these actions to set automatic replaced both in string processing and file naming.

replace.clearfile

Removes a file replacement.

params

1. the needle (text to search) to remove

replace.clearstring

Removes a string replacement.

params

1. the needle (text to search) to remove

replace.clearallfiles

Clears all file replacement needles.

replace.clearallstrings

Clears all string replacement needles.

replace.origin

Replaces the current movie images origin set while loading scenes/keyframes. Possible values are "alpha", "center", "top", "topkeep", "bottom", "bottomkeep", "left", "leftkeep", "right" and "rightkeep".

params

1. the new origin

replace.setfile

Sets a needle that will replace of its occurrences on loaded file names.

params

1. the needle (text to search)
2. the string to replace the needle on file names



replace.setstring

Sets a needle that will replace of its occurrences by the value given in both string processing and text display.

params

1. the needle (text to search)
2. the string to replace the needle

if.replacefileset

Checks if a file replacement exists.

params

1. the replacement name to check

additional optional object fields

- then: actions to run if true
- else: actions to run if false

if.replacestringset

Checks if a string replacement exists.

params

1. the replacement name to check

additional optional object fields

- then: actions to run if true
- else: actions to run if false

2.12. Scene

scene.load

Loads a new scene.

params

1. new scene id

scene.navigate

Loads the scene set at the navigation settings of the current one.

params

1. the navigation direction: *up*, *down*, *left*, *right*, *nin* or *nout*

scene.pause

Pauses the current scene playback.

scene.play

Plays the current scene.



scene.playpause

Plays a stopped scene or pauses a playing one.

scene.nextkeyframe

Loads the next keyframe of a paused scene.

scene.previouskeyframe

Loads the previous keyframe of a paused scene.

scene.loadfirstkeyframe

Loads the first keyframe of a paused scene.

scene.loadlastkeyframe

Loads the last keyframe of a paused scene.

scene.loadkeyframe

Loads a keyframe from a paused scene.

params

1. the keyframe number to load (keyframe numbers start at 1)

2.13. Snippets

Action snippets can be defined at the *Action snippets* tab of the *Movie properties* window.

run

Runs a named action (set at *Movie > Properties* window).

params

1. action snippet name

2.14. String conditions

Conditional statements based on string values.

if.stringcontains

Checks if the first string contains the second one.

params

1. first string to compare
2. second string to compare

additional optional object fields

- then: actions to run if the string contains the other one
- else: actions to run if the string does not contain the other one



if.stringendswith

Checks if the first string ends with the second one.

params

1. first string to compare
2. second string to compare

additional optional object fields

- then: actions to run if the string ends with the other one
- else: actions to run if the string does not end with the other one

if.stringsdifferent

Checks if two strings are different.

params

1. first string to compare
2. second string to compare

additional optional object fields

- then: actions to run if the strings are different
- else: actions to run if the strings are equal

if.stringsequal

Checks if two strings are equal.

params

1. first string to compare
2. second string to compare

additional optional object fields

- then: actions to run if the strings are equal
- else: actions to run if the strings are different

if.stringset

Checks if a string variable exists.

params

1. the variable name to check

additional optional object fields

- then: actions to run if true
- else: actions to run if false

if.stringstartswith

Checks if the first string starts with the second one.

params

1. first string to compare
2. second string to compare

additional optional object fields

- then: actions to run if the string starts with the other one
- else: actions to run if the string does not start with the other one

if.stringemail

Checks if the strig is a valid e-mail address.



params

1. the address to check
- additional optional object fields
- then: actions to run if the string is a valid email
 - else: actions to run if the string isn't a valid email

2.15. String values

Management of string variables.

string.clear

Removes a string variable.

params

1. the variable name

string.clearall

Removes all string variables.

string.clearglobal

Clears a text global.

params

1. the global name

string.concat

Concatenates two or more strings. Three parameters are required. Each additional one will be concatenated at the string end. You can use any type of variable (string, int, float or bool) – the value will be automatically converted to string.

params

1. the variable name to receive the concatenated one
2. the first string to concatenate
3. the second string to concatenate

string.replace

Replaces all occurrences of the needle string by the given one at the provided text.

params

1. the variable name to receive the replace result
2. the original string
3. the needle (string to look for)
4. the replacement text

string.set

Sets a string variable.

params



2. the variable name
3. the variable value

string.setglobal

Sets a text global.

params

1. the global name
2. the global value

string.setgroup

Sets a group of the *strings.json* file to look for string variable values.

params

1. the group name

string.tofloat

Converts a string value to a float one.

params

1. the float variable name to receive the result
2. the string to convert

string.toint

Converts a string value to an integer one.

params

1. the integer variable name to receive the result
2. the string to convert

2.16. System

system.copytext

Copies a string into the user clipboard.

params

1. the string to copy

system.fullscreen

Shows the content at fullscreen or brings back the display to normal state. Please note that you must trigger this action only on an user interaction. It won't work on movie/scene/keyframe actions due to browser policies. No parameters are required.

system.visitoringroup

Checks if the current logged visitor is part of a give group. If no visitor is currently logged, always return false.

params



1. the group name to check (case sensitive)
- additional optional object fields
- then: actions to run if the visitor belongs to the provided group
 - else: actions to run if the visitor is not in the group or if no visitor is logged at all

system.logout

Logs out the current user.

system.openembed

Opens an overlay with a previously embedded HTML5 content (access Media > Embed on the left menu to send the HTML5 content to embed).

params

1. the embed name used when sending the content

Embed content can exchange information with the host movie using javascript methods. Since the embed content is displayed using an iframe, all methods must be called from "parent".

parent.tilbuci_getstring(\$name)	gets the current value of the \$name variable (empty string if it is not set)
parent.tilbuci_setstring(\$name, \$value)	sets the value of the string variable \$name
parent.tilbuci_getfloat(\$name)	gets the current value of the \$name variable (0 if it is not set)
parent.tilbuci_setfloat(\$name, #value)	sets the value of the float variable \$name
parent.tilbuci_getint(\$name)	gets the current value of the \$name variable (0 if it is not set)
parent.tilbuci_setint(\$name, #value)	sets the value of the integer variable \$name
parent.tilbuci_getbool(\$name)	gets the current value of the \$name variable (false if it is not set)
parent.tilbuci_setbool(\$name, ?value)	sets the value of the boolean variable \$name
parent.tilbuci_runaction(\$action)	runs any json-formatted action on movie

system.closeembed

Closes the HTML5 embed content display.

system.embedreset

Resets the HTML5 embed display site and position so it appears covering all display area.

system.embedplace

Sets the position and size of the HTML5 embed content area. The placement values are absolute, considering the entire stage, not only your movie display area. Because of that, the #_CONTENTX, #_CONTENTY, #_CONTENTWIDTH and #_CONTENTHEIGHT values can be useful to help figuring out the desired values.

params

1. x position



2. y position
3. width
4. height

system.openurl

Opens an URL on user browser.

params

2. the UL to open

system.quit

While running as a desktop application, this action ends the app execution, closing its window.

system.sendevent

Sends a custom event (TilBuciEvent.EVENT) to everyone listening to the player object. The event info field will be filled with any string parameters you add to this action.

system.setkftime

Sets the time between keyframes in milliseconds. Values lower than 250 will be ignored.

params

1. the new time between keyframes in miliseconds

2.17. Text

Text actions adjust the css styles used on html instances. You can provide a default css stylesheet at the *CSS* tab of the *Movie properties* window.

css.clear

Clears current css styles.

css.set

Sets css styles.

params

1. css styles text

2.18. Timer

Timers allow you to run actions in intervals and after some time.

timer.clear

Stops and clears a timer.



params

1. the timer name to clear

timer.clearall

Stops and clears all set timers.

timer.set

Sets a timer with a given interval in milliseconds and a number of iterations.

params

1. timer name
2. interval among timer ticks in milliseconds (minimum of 250)
3. number of iterations

additional optional object fields

- tick: actions to run after every tick
- end: actions to run on timer end



3. Plugin actions

Plugins may add actions and conditions to TilBuci. The software comes with some of them already available. Here are the actions they provide.

3.1. Debug plugin

This plugin is intended to be used during your content development. It is recommended to turn it off in movies already available to the public.

trace

This command will display a text on the browser's console. You can use it to show anything. It requires one parameter, but you may add as many as you want – all of them will be displayed at the console.

params

1. content to display on browser's console

params

trace.bools

Displays all current boolean variables as their values at the browser console.

trace.ints

Displays all current integer variables as their values at the browser console.

trace.floats

Displays all current float variables as their values at the browser console.

trace.strings

Displays all current string variables as their values at the browser console.

debuginfo.hide

Hides the debug info window if it is being displayed (F8 on keyboard).

debuginfo.show

Shows the debug info window over your content with many . You may also press F8 on the keyboard to show this window.



3.2. Share

This plugin provides actions to open a browser tab ready for the user to share a content from your movies. They don't require any parameters – the movie url and title are automatically add to the share call – but you may add a boolean one set to true to force the share url to point to the movie index instead of the current scene, even if the share mode on movie properties is set to scene.

share.facebook

share.linkedin

share.pinterest

share.reddit

share.x

3.3. Google Analytics

This plugin enables measurement of user activities while checking out your content. It must be configured with the *Measurement ID* before use. Movie and scene load operations are automatically registered as events on the Analytics platform, but you may also create your custom events.

When a movie is loaded, a new campaign is automatically set on Analytics with these parameters:

- id: the movie ID
- name: the movie name
- source: your TilBuci base installation domain

Automatic movie load events set these parameters:

- movie_id: the loaded movie ID
- movie_name: the loaded movie title

Automatic scene load events hold these parameters:

- movie_id: the current movie ID
- movie_name: the current movie title
- scene_id: the loaded scene ID
- scene_name: the loaded scene title

analytics.event

Registers a custom event at the Google platform. You must provide the event name and its description.



The recorded event will set these parameters:

- movie_id: the current movie ID
- movie_name: the current movie title
- scene_id: the current scene ID
- scene_name: the current scene title
- about: the provided description

params

1. event name
2. event description

3.4. Server Call

This plugin is aimed at operations that must run at your TilBuci installation server.

call.process

Calls a server script to process and return data to TilBuci. The script can even be loaded from another domain, but it must always return a JSON text considering the format below.

This is a versatile function. It can be used to collect data from other internet sources, process data collected while viewing your content, and even create communication systems like your own user management and data storage.

The function requires at least two string parameters but you may add as many as you want. When called, it will make a POST request to the URL of the first parameter with the following values:

value	content
movieid	Current movie ID
sceneid	Current scene ID
movietitle	Current movie title
scenetitle	Current scene title
visitor	Current visitor e-mail or "system" if none is logged in
data	A JSON-encoded array with all string parameters set, in order, except the script url

Your script must process the information and return a JSON encoded object with values that will be loaded into TilBuci variables when received. The JSON object can contain as many variables as you want to return, described as:

```
"name": { "t": "the variable type", "v": "the value" }
```

Possible types are "B" (boolean), "I" (integer), "F" (float) and "S" (string). A return example that sets four variables:

```
{
```




```
"mystring":{"t":"S","v":"the string value"},  
"myfloat":{"t":"F","v":100.101},  
"myint":{"t":"I","v":10},  
"mybool":{"t":"B","v":true}  
}
```

You may provide the "success" and "error" optional object fields to run after a successful or failure call.

params

1. the url to call
2. string parameter to send for processing

additional optional object fields

- success: actions to run on successful call
- error: actions to run on call failure

call.sdprocess

This action is like the previous one, but the URL to call must always be hosted at the same domain as your TilBuci movie is loaded from. Everything else works just like call.process. Because of the same domain URL limitation, you can still use this action to access server data on exported websites or PWA applications, unlike the other Server Call plugin actions.

call.url

Calls any URL from the server. By transferring the request to the server, TilBuci avoids browser "CORS" limitations. You may provide a string variable name to receive the return on a successful request. You may provide the "success" and "error" optional object fields to run after a successful or failure call.

params

1. the url to call
2. optional string variable name to receive the result

additional optional object fields

- success: actions to run on successful call
- error: actions to run on call failure

3.5. Overlay

This plugin can load an external content and display it above your TilBuci movie. You can even exchange data between them.

overlay.show

Loads an external content on an overlay frame above your movie.

params

1. the url to load
2. title to display above the overlay content (may be an empty string)
3. optional bool value to send additional information as get parameters



additional optional object fields

- success: actions to run after the overlay is successfully displayed and closed
- error: actions to run on overlay error

The overlay is a powerful feature to enhance your TilBuci creation. It can be anything loaded as a web page, from a simple page to a detailed form or a complex game.

The first parameter is the url of the overlay content. You can set it to an address on your domain (recommended) or event to other sites. TilBuci will automatically assign a unique key to every overlay call. This key will be sent as a get "key" parameter add to your url, like:

<https://tilbuci.com.br/myoverlaycontent/?key=uniquekey>

This key is very important: you can use it to exchange data between your movie and the overlay.

The second parameter is a title that will appear above the overlay content. If you do not want a title, just use a blank string.

The third parameter is optional. You can add as many additional parameters as you want to send to your overlay. If the third parameter is set to "true", this extra information will be included as get values on your url. Check out this example:

```
{
  "ac": "overlay.show",
  "param": [
    "https://tilbuci.com.br/myoverlaycontent/",
    "My overlay title",
    "true",
    "param4",
    "param5"
  ]
}
```

Will open an overlay calling this address:

<https://tilbuci.com.br/myoverlaycontent/?key=uniquekey&v1=param4&v2=param5>

Since there are limitations regarding the size of get requests, use this with caution. The "key" value is always sent.

Even if you do not add the additional information as get values, your overlay can still retrieve it by calling the TilBuci webservice interface. To do so, you must call the "ws" route of your TilBuci installation with a POST request, like <https://tilbuci.com.br/ws/>, with the following values:

POST parameter	Value
a	Overlay/GetKeyData
k	The overlay key you received



s	A signature made of MD5(secret key + overlay key)
---	---

You must set a secret key at your TilBuci overlay plugin configuration. This secret key, add to the unique key of your overlay and encoded as a MD5 string must always be sent as the "s" signature parameter to validate your request.

The response you receive will always be a JSON-formatted string. To evaluate it, you must first look for the "e" (error) value. If the error is "0", your request was successful, and you may proceed parsing the "data" value. You'll receive it as a JSON-encoded object with name/value pairs with the same names you'd receive as get values.

You can also use this webservice request to send data back to the TilBuci movie. This data will be loaded into variables when the overlay is closed. Here are the required POST parameters:

POST parameter	Value
a	Overlay/SetKeyData
k	The overlay key you received
s	A signature made of MD5(secret key + overlay key)
d	The data to send as a JSON-encoded string

The "d" parameter is a JSON-encoded string describing the variables to set on your TilBuci movie. It can contain as many variables as you want to return, described as:

```
"name": { "t": "the variable type", "v": "the value" }
```

Possible types are "B" (boolean), "I" (integer), "F" (float) and "S" (string). A return example that sets four variables:

```
{
  "mystring": {"t": "S", "v": "the string value"},
  "myfloat": {"t": "F", "v": 100.101},
  "myint": {"t": "I", "v": 10},
  "mybool": {"t": "B", "v": true}
}
```

If you call this webservice more than once, new values will replace the previous ones. The TilBuci movie will only receive this information when the overlay is closed. This happens when the visitor clicks at the close button that will always appear above your overlay. You may also call this javascript function from your content to force it to close but notice that if the url of the overlay request is not at the same domain of your TilBuci installation, the browser may block this call.

```
parent.overlay_close();
```



The *overlay.show* action supports the *success* and *error* additional optional object fields. Error actions are run on any problem regarding the overlay display, while the success ones will run after the overlay is closed and the return variables are set.




4. Contraptions

Contraptions are ways to simplify creation by grouping together tools that help you develop your content more quickly. They can include both settings found in the left menu and specific actions.

4.1. Menu

The menu contraption is a quick way to create menus and display them in your scenes. The process starts with creating layouts from the left menu. To do this, you need to provide some information such as the name of the font to be used and the images for both the background and the menu buttons. Once the layouts are created, they can be used in the *contraption.menu* action to start displaying them at any time.



contraption.menu

This command allows you to display a menu from a previously defined layout. It receives 6 parameters. When a button is clicked, its number is stored at the provided int variable (first button value is 0, second is 1 and so on). After setting the value, the actions set at "select" are run. The menu won't automatically disappear after a button is clicked – you'll need to add the *contraption.menuhide* when you want to remove it.



params

1. the layout name
2. the menu option texts (all of them, split by ;)
3. integer variable name to receive the click result
4. placement (top, topleft, topright, center, centerleft, centerright, bottom, bottomleft, bottomright, absolute)
5. x distance from border (or position for absolute placement)
6. y distance from border (or position for absolute placement)

additional optional object fields


- select: actions to run on a menu button selection

contraption.menuhide

Hides any menu currently displayed. No parameters needed.

4.2. Cover

The cover contraption is a simple way to create an image layer on top of your content, easy to display at any time. To do this, covers must be configured in the left menu contraptions > content cover.



When configuring, in addition to giving a name, you must indicate at least one picture that will be used to cover the entire movie area. You can also define one image for horizontal display and one for vertical display. Finally, you can also indicate whether the cover will block click/touch interactions with the content below.

contraption.cover

This action will cause a defined cover to be displayed. If there is already a cover displayed, it will be replaced with the indicated one.



params


1. the cover name

contraption.coverhide

Removes any currently displayed cover.

4.3. Loading icon

The loading icon is a way to give visual feedback to the visitor while some processing is taking place, such as loading content. It is defined in the movie properties, as a spritemap type media.



contraption.showloading

Displays the loading icon set for the movie at the display center (notice that scene loading automatically triggers this action).

contraption.hideloading

Hides the loading icon from display (notice that when a scene loading finishes, this action is automatically triggered).



5. Code assist

To simplify the action coding process, TilBuci provides some assistants to help the script creation. On every scripting window there are some buttons to display these tools.



These buttons actions are, in order:

1. return to the block editor
2. copy current action script
3. show movie and scene actions
4. show media/instance actions
5. show variable management actions and conditions
6. show data and input handling actions
7. show additional actions, like system and timer
8. show contraption-related actions
9. show available plugin actions

All windows shown from these buttons have tools to help code creation. Just set what you want and click the buttons with the copy icon – the code will be copied to clipboard so you can paste it on your creations. Please note that this copy functions will only work if TilBuci is running from secure “https” urls due to browser policies. You will also find the “show action” buttons that will display the action at the “Action/value” area, from which you can manually copy the result – this will work from both https and http.



5.1. Movie and scene actions

Scene and movie actions

Available movies

ESP32 connection*

movie load action

show action

Current movie scenes

Input

scene id

scene load action

show action

Other scene actions

scene.navigate

Navigation

right

selected action

show action

Close

Action/value



5.2. Instance and media

Instance actions

Current keyframe instances

7766338c67

Action

set

Property

x position

Horizontal value to set

Vertical value to set

Other parameters (seek, paragraph text, load asset)

create action

show action

Close

Action/value

Scene collections

Shape 2024-08-20 09:40:25

Collection assets

Shape

get asset ID

General globals

is the movie playing right now?

get value

Instance globals

Property

playing content?

Name

7766338c67

get value

Movie globals and input content

Text

Global or input name

get value



5.3. Variable actions and conditions

Variable actions and conditions

Avaliable variable-related actions and conditions

int.abs

int.clear

int.clearall

int.divide

int.max

int.min

int.multiply

int.random

Parameters

create action

show action

Close

Action/value

General globals

? is the movie playing right now?

? is there a server connection?

? is there an user logged?

current keyframe number

movie big dimension

movie small dimension

movie actual x position

get value

Instance globals

Property

playing content?

Name

7766338c67

get value

Movie globals and input content

Text

Global or input name

get value



5.4. Data and input handling

Data and input

Available data and input actions

data.event

data.eventclear

data.liststates

data.load

data.loadlocal

data.loadquickstate

data.loadstatelocal

data.save

Parameters

create action

show action

Close

Action/value

General globals

? is the movie playing right now?

? is there a server connection?

? is there an user logged?

current keyframe number

movie big dimension

movie small dimension

movie actual x position

get value

Instance globals

Property

playing content?

Name

7766338c67

get value

Movie globals and input content

Text

Global or input name

get value



5.5. Additional actions

Additional actions

Avaliable miscellaneous actions

replace.clearfile

replace.clearstring

replace.clearallfiles

replace.clearallstrings

replace.origin

replace.setfile

replace.setstring

Parameters

create action

show action

Close

Action/value

General globals

? is the movie playing right now?

? is there a server connection?

? is there an user logged?

current keyframe number

movie big dimension

movie small dimension

movie actual x position

get value

Instance globals

Property

playing content?

Name

7766338c67

get value

Movie globals and input content

Text

Global or input name

get value

TilBuci is a free software developed by Lucas Junqueira <doggo@tilbuci.com.br>.
Please check out tilbuci.com.br for further information.



5.6. Contraptions

Contraption actions

Available contraption actions

contraption.menu

contraption.menuhide

Parameters

create action

show action

Close

Action/value

General globals

is the movie playing right now?

is there a server connection?

is there an user logged?

current keyframe number

movie big dimension

movie small dimension

movie actual x position

get value

Instance globals

Property

playing content?

Name

7766338c67

get value

Movie globals and input content

Text

Global or input name

get value



5.7. Available plugins

Plugin actions

Available original plugin actions

analytics.event

call.sdprocess

call.process

call.url

debuginfo.hide

debuginfo.show

overlay.show

...

Parameters

create action

show action

Close

Action/value

General globals

is the movie playing right now?

is there a server connection?

is there an user logged?

current keyframe number

movie big dimension

movie small dimension

movie actual x position

get value

Instance globals

Property

playing content?

Name

7766338c67

get value

Movie globals and input content

Text

Global or input name

get value




6. Block editor

Even though you can write the code for your actions in TilBuci, using or not the assistants, the simplest way to create interactions is through the block editor. The action blocks are a visual way to enter commands and the software's default method.



The block area always displays a + button used to create a block. Click it to show the action groups available. By clicking on one of them, you'll see the available actions. Select the one you want and, then click on "create action block".






The next window will show all necessary parameters to finish setting your action.

You can add as many blocks as you want to an action: just press the + button to add another one. The actions will be run at the numbered order.



Some blocks, like conditions, can hold themselves further actions. In these cases, additional + buttons are displayed where necessary.



Just below the blocks area you'll find some buttons to help your coding.



They represent, in order:

1. switch to the code view (you can switch between block and code display at any time, both methods are 100% compatible)
2. delete the selected block
3. edit the selected block
4. expand the selected block (or mouse center button click)
5. reduces the selected block view
6. move selected block up in execution order
7. move selected block down in execution order