A Small Nervous System as Sequencer: Neuroevolved Spiking Networks for Three-Voice Pentatonic Music

Anonymous Author(s)
Submission to the AI Music Composition Competition, AIMG 2026

***Abstract*—A small spiking neural network is run as an autonomous dynamical system and shaped by evolutionary search until its activity, read out as notes, forms three-voice music in a Japanese pentatonic scale. The network receives no input beyond an initial stimulus and is not trained on musical data. The submitted piece has two movements: the first from a network of three loosely coupled modules in the Kumoi scale, the second from a network with a single shared pool of neurons in the Iwato scale. The evolved MIDI was not edited. Tempo, orchestration, real-time MIDI and audio effects, and mixing were decided by a human in a digital audio workstation, and we describe them explicitly.**

***Index Terms*—spiking neural networks, neuroevolution, reservoir computing, algorithmic composition, human–AI co-creation**

I. Introduction

Most neural music generators are trained on data and sampled. Here the network is treated as a physical system with its own dynamics, and evolution shapes those dynamics until the output is acceptable as music. The composition is encoded in the weights and topology of the network rather than in any input or dataset.

The architecture is a reservoir in the sense of liquid state machines [1] and echo state networks [2]. In those frameworks the reservoir is random and fixed and the readout is trained by regression against target data. Here no musical data is used: evolution determines both the reservoir and the readout, and the network runs freely after a single initial stimulus.

The division of labor between algorithm and interpreter was inspired by John Cage, some of whose chance compositions leave decisions to the performer [5]. The network's MIDI output is the score, and a human interprets it.

II. System

The network consists of threshold neurons connected by a sparse random matrix of excitatory and inhibitory weights. At each time step, a neuron accumulates input from neurons that fired on the previous step, its activation decays by a leak factor, and it fires when activation reaches its threshold. After firing, it is refractory for a period drawn per neuron from a uniform distribution. The simulation runs for 288 steps, interpreted as sixteenth notes, after a single stimulus to the most strongly connected neuron. The update rule and all parameters are given in Appendices A and B.

Three readouts, one per voice, each have five output units, one per degree of the pentatonic scale. At each step, the highest output in a readout sounds its scale degree if it exceeds a fixed threshold of 0.3, with MIDI velocity proportional to its value; a degree that wins on consecutive steps is sustained. Because the outputs are scale degrees, every note is in the scale by construction. Because the threshold is fixed, the network controls its own note density.

Two configurations were used. In the unified configuration, all readouts draw from one pool of 120 neurons, and the voices tend to move together. In the modular configuration, 255 neurons form three blocks of 85, each readout is restricted to one block, and connections between blocks have half the density of connections within them. The whole network is evolved as one genome.

III. Evolution and Fitness

The search is a $(\mu + \lambda)$ evolution strategy [3] with $\mu = 24$, $\lambda = 120$, and 88 generations. The genome comprises reservoir and readout weights, thresholds, and refractory periods. Three fifths of the offspring come from Gaussian mutation with age-based annealing, and two fifths from differential mutation [4]. There is no crossover.

Fitness is a product of terms in $[0, 1]$, each computed per voice and aggregated by the minimum across voices, except activity. The unified configuration was evolved under activity $\times$ diversity, where *activity* rewards a target note count and *diversity* combines pitch-class entropy with a penalty for repeated two- and three-note figures. The modular configuration was evolved under activity $\times$ tonal gravity $\times$ repetition $\times$ metric gravity. *Tonal gravity* compares each voice's distribution of melodic transitions with a hand-written target for the scale. *Metric gravity* rewards stable tones on strong beats. Definitions are in Appendix C.

IV. The Submitted Work

A. Two movements

The submitted piece consists of two movements of four minutes each. The first, *The Enduring Enso*, was produced by the modular configuration in the Kumoi scale. The second, *Echo Chamber*, was produced by the unified configuration in the Iwato scale. The unified configuration was developed first; presenting the modular movement first is an artistic decision.

Each configuration was run as a batch with a fixed random seed per run: twelve runs (four per scale) for the unified configuration and nine runs (three per scale) for the modular configuration. Each run yields one composition, its best-scoring MIDI file in the final generation. No intermediate or lower-ranked outputs were considered. Selection among runs was made by listening: for each movement, the compositions from several runs in the same scale were auditioned and one was kept. The chosen runs were not the highest-scoring in their scale.

The MIDI output is sparse and rhythmically uneven, with bursts of activity separated by silences, which suits a tradition in which silence carries structural weight.

B. Interpretation

The MIDI files are treated as scores and were imported into a digital audio workstation without modification. All further decisions were made by a human interpreter.

Tempo. The scores were played at 20 BPM, so that the 72-beat score lasts 3 minutes 36 seconds. The remaining 24 seconds of each movement are a fade-out that separates the movements.

Orchestration. The first voice is played by a koto. The second voice is doubled by a koto and a shamisen, and the third by two flutes. The shamisen receives its voice through a counter-based MIDI device that drops one note in every twelve in the first movement and one in every nine in the second. The shamisen is also sparser than the koto it doubles for a second reason: the chosen instrument responds strongly to note velocity, which the network sets from the strength of the winning output, so low-velocity notes are faint or nearly inaudible. No velocity remapping was applied, but the choice of this instrument acts as an implicit mapping from velocity to presence. Together, the note dropping and the velocity response make the shamisen an intermittent shadow of the koto line.

Timing drift. On the first and second voices, every note is delayed by a few milliseconds through a MIDI delay device whose delay time is modulated by a slow low-frequency oscillator. The effect is a small, continuously varying offset from the sixteenth-note grid, similar to the timing variation of a human player. The third voice is played on the grid.

Effects and mix. Audio processing includes reverb, delay, saturation, filtering, and echo. In the second movement, an audio rendering of the flute voice was reversed and mixed in alongside the forward voice. The voices were balanced and placed in the stereo field.

The note data of the score is therefore identical to the network's output, while the sounding result includes doublings, omissions within doublings, small timing offsets, audio echoes, and a reversed copy of one voice, all introduced by the interpreter. The fitness function evaluated symbolic MIDI only and was never applied to audio, and no production decision was iterated against any metric. The premise of the larger project here is that the notes and the sound can be separated, with computation responsible for the former and a human interpreter for the latter.

C. Listening notes

In the first movement, the three voices maintain distinct rhythmic identities and are anchored by C and G on strong beats; the coupling between modules can be heard as occasional entrainment between voices. In the second movement, the voices share a single pool of neurons and tend to move together, and the two half-step pairs of Iwato (C–D♭ and F–G♭) recur as points of tension. In both, the silences between bursts are the primary formal device.

V. Discussion

The network's physical parameters, chiefly the activation leak and the spread of refractory periods, determined the musical result more than any property of the search, and building the scale into the readout was the most consequential design decision. The pieces have local coherence but no large-scale form. The two movements were evolved under different fitness functions and network sizes, so they document two stages of the system rather than a controlled comparison. The transition targets encode the author's reading of the scales, and no listening study was conducted.

AI Usage Disclosure

An AI coding assistant was used throughout the development of the system, for writing and refactoring code, and for discussing design options, evaluation metrics, and related literature; design decisions and evaluation of the results by listening were made by the author. The assistant also helped summarize experimental logs into lab notes. This paper was co-written with an AI assistant from the author's notes, experiment outputs, and prior writing, and the final text was co-edited by the author and the assistant. All parameters, results, and references were verified by the author against the code, the experiment records, and the cited sources. No AI tools were used to generate or process the audio; the music was produced from the network's output with conventional software instruments and effects.

References

[1] W. Maass, T. Natschläger, and H. Markram, "Real-time computing without stable states: A new framework for neural computation based on perturbations," *Neural Computation*, vol. 14, no. 11, pp. 2531–2560, 2002.

[2] H. Jaeger, "The 'echo state' approach to analysing and training recurrent neural networks," GMD Report 148, German National Research Center for Information Technology, 2001.

[3] H.-G. Beyer and H.-P. Schwefel, "Evolution strategies: A comprehensive introduction," *Natural Computing*, vol. 1, no. 1, pp. 3–52, 2002.

[4] R. Storn and K. Price, "Differential evolution: A simple and efficient heuristic for global optimization over continuous spaces," *Journal of Global Optimization*, vol. 11, no. 4, pp. 341–359, 1997.

[5] J. Pritchett, *The Music of John Cage*. Cambridge, U.K.: Cambridge University Press, 1993.

APPENDIX A
UPDATE RULE

One simulation step, as implemented. W is the reservoir weight matrix, W_{out} the readout weight matrix, a the activation vector, f the Boolean firing vector, `ok` the mask of non-refractory neurons, r the refractory counter vector, p the per-neuron refractory period vector, and o the output vector.

```
incoming = W.T @ f
ok       = (r == 0)
a        = where(ok, clip(a + incoming, 0, 1), a)
f        = ok & (a >= thresholds)
r_new    = where(f, p, r)
a        = where(r > 0, a * refraction_leak, a)
o        = o * refraction_leak + W_out.T @ f
a        = a * activation_leak
r        = max(0, r_new - 1)
```

Per readout, the step's note is the scale degree at $\arg\max$ of the readout's outputs if the maximum exceeds 0.3, with velocity $\mathrm{round}(127 \cdot \max)$; otherwise the voice is silent. A degree that wins on consecutive steps is sustained.

APPENDIX B
PARAMETERS

Parameter	Mvt. 1 (modular)	Mvt. 2 (unified)
Scale	Kumoi	Iwato
Neurons	255 (3×85)	120
Modules	3	1
Inter-/intra-module density ratio	0.5	—
Readouts × outputs	3×5	3×5
Reservoir sparsity / weight std.	0.2 / 0.3	0.2 / 0.3
Readout sparsity / weight std.	0.05 / 0.3	0.05 / 0.3
Activation leak	0.98	0.98
Refraction leak	0.75	0.75
Refractory period (steps)	$2 + U\{0, \ldots, 61\}$	$2 + U\{0, \ldots, 61\}$
Trigger threshold	0.3	0.3
Initial stimulus	most-connected neuron	most-connected neuron
Steps (sixteenth notes)	288	288
Tempo, evaluation / playback	60 / 20 BPM	60 / 20 BPM
μ / λ / generations	24 / 120 / 88	24 / 120 / 88
Weight mutation rate / scale	0.1 / 0.01	0.1 / 0.01
Threshold mutation rate / scale	0.1 / 0.01	0.1 / 0.01
Refractory mutation rate	0.1	0.1
Annealing factor / max. multiplier	0.1 / 10	0.1 / 10
Gaussian : differential, F	3 : 2, 0.7	3 : 2, 0.7
Fitness	act × ton × rep × met	act × div
Runs in batch	9 (3 per scale)	12 (4 per scale)
Recorded fitness	0.79	0.91
Orchestration (voices 1 / 2 / 3)	koto / koto + shamisen / two flutes	same, plus reversed flute audio
Note-skip on shamisen	1 in 12 dropped	1 in 9 dropped
LFO timing drift	voices 1, 2	voices 1, 2

APPENDIX C
FITNESS DEFINITIONS

Every term except activity is computed per voice and aggregated by the minimum across voices. The two composites are

$$F_{\text{mvt 1}} = \text{activity} \times \text{tonal} \times \text{repetition} \times \text{metric}, \tag{1}$$

$$F_{\text{mvt 2}} = \text{activity} \times \text{diversity}. \tag{2}$$

Activity. With n the total note count across voices and $T = 288$ the target,

$$\text{activity} = \max\bigl(0,\ 1 - \tfrac{1}{2}\,|\log_2(n/T)|\bigr)\,. \tag{3}$$

Repetition. For $k \in \{2, 3\}$, let $c_{\max}$ be the count of the most frequent k-gram of pitch classes in the voice and N the number of k-grams. With two occurrences allowed,

$$\pi_k = \left(\frac{\max(0,\ c_{\max} - 2)}{N - 2}\right)^2, \tag{4}$$

$$\text{repetition} = \tfrac{1}{2}\left[(1 - \pi_2) + (1 - \pi_3)\right]. \tag{5}$$

Diversity (movement 2). With H the Shannon entropy in bits of the voice's pitch-class distribution,

$$\text{diversity} = \tfrac{1}{2}\min\left(1, \frac{H}{\log_2 7}\right) + \tfrac{1}{2}\,\text{repetition}. \tag{6}$$

The normalization by $\log_2 7$ is carried over from an earlier seven-note version; for a five-note scale the entropy component cannot exceed ≈ 0.83.

Tonal gravity (movement 1). Let q be the target distribution over the 20 ordered pairs of distinct scale degrees (Table I), and p the observed distribution of a voice's transitions between distinct degrees, with additive smoothing $\alpha = 1$. A voice with fewer than four notes or eight such transitions scores 0. Otherwise

$$\text{tonal} = \exp(-D_{\mathrm{KL}}(q \,\|\, p))\,. \tag{7}$$

Because q assigns probability to all twenty transition types, a voice that uses only a few is heavily penalized, so the term also enforces pitch variety.

TABLE I
KUMOI TRANSITION TARGET (ROWS: FROM; COLUMNS: TO)

	C	D	E♭	G	A
C	—	0.30	0.15	0.35	0.20
D	0.25	—	0.40	0.20	0.15
E♭	0.20	0.45	—	0.20	0.15
G	0.30	0.15	0.10	—	0.45
A	0.25	0.15	0.15	0.45	—

Metric gravity (movement 1). Sixteenth-note positions in a four-beat cycle receive weights $w = (4, 0, 1, 0, 2, 0, 1, 0, 3, 0, 1, 0, 2, 0, 1, 0)$. Let ρ be the weighted fraction of a voice's notes on positions with $w > 0$ whose pitch class is C or G. Then metric $= \rho/0.5$ for $\rho \le 0.5$ and $1 - (\rho - 0.5)$ otherwise, so that neither ignoring the meter nor always playing the root is rewarded.