GOT a Flight

http://www.delay.ml/demo/

by Aviators

Technical Specifications

Table of Contents

| Why GOT a Flight? | 2 |
|---|---|
| Background | 2 |
| Proposed solution | 3 |
| Prediction - How it works | 4 |
| Model validation | 6 |
| Roadmap - Improvements Aviators is working on | 9 |
| Resources | 9 |

Why GOT a Flight?

The potential and complexity of the solution is that the prediction is not based on old statistics, but it is based on the future and current forecasts combined with aviation reports and multiple factors that influence the weather-related delays, such as the position of the runways at the airport, the number of runways, the aircraft specifications, the conditions for emergency landings at the departure airport and the International Aviation Standards and Regulations. This information is public; the key point is to combine the correct factors and to generate the most precise rules.

In addition, GOT a Flight introduces the new concept of "insurance" in the aviation sector by offering flight insurance policies to cover extra expenses incurred due to the delay.

As part of the project, we also present a roadmap with additional features aimed to improve the accuracy of the prediction.

Background

According to the Federal Aviation Administration (FAA) the 69% of flight delays in the National Airspace System are caused by adverse weather conditions. Currently, the cost to the air carrier operators for a one-hour delay ranges from \$1,400 to \$4,500, depending on the class of aircraft, and whether the delay is taken on the ground or in the air. If the value of passenger time is included, the cost goes up to an additional of \$35 per hour (personal travel) or \$63 per hour (business travel) for every person on board.

In the airports with the worst weather-related delays (i.e. New York), the percentage of delays caused by the weather could reach 80%.




Chart 1, Weather-related delays compared to total delays at Newark, LaGuardia and Kennedy airports




Chart 2, Types of weather contributing to delays at Newark, LaGuardia and Kennedy

Furthermore, a study carried out by researchers at the University of California, Berkeley, states that the cost to the passengers doubles the cost incurred by the airlines.

Proposed solution

The complex work of predicting a flight delay was resolved by merging data from diverse sources: weather conditions, aircraft specs, airport design and International Standards and Regulations.

The result is an application that predicts the probability of a flight being delayed because of the weather conditions. Moreover, it offers the possibility to take out an insurance policy to cover the expenditures incurred due to the delay, thus proposing an innovative business model to the aviation market.

According to the FAA, the airports that have the worst weather-related delays in USA are New York (3), Chicago, Philadelphia, San Francisco and Atlanta. In order to address this scenario, GOT a Flight has been implemented for those airports to address those 120,000 weather delays.




Chart 3, Airports with the worst weather-related delay


The application was implemented for Boeing 737, which is the best-selling plane in the aviation history. Moreover, it is one of the most used airplanes in the US and the largest 737 operator in the world is an American airline. This aircraft is a great representative of those used for regional flights.

As explained in the sections below, the aircraft is not indifferent as the calculations depend on the specifications of each particular plane.

Prediction - How it works

GOT a Flight predicts the weather conditions by analyzing parameters within different categories and by combining all the variables involved in a flight delay:

- Aircraft specifications: Aircraft specs are one of the most important factors when it comes to
 defining minima or limitations. For example, the range of acceptable crosswinds, the certification to
 operate in icy conditions operations and runway limitations are all parameters given by the
 manufacturer. This means the delays will depend on the aircraft and that is one of the most difficult
 challenges of building the application.
- International Aviation Standards and Regulations: FAA and NOAA dispositions and Manual of All-Weather Operations, DOC 9365, from the International Civil Aviation Organization (ICAO).
- Weather forecast and pre-flight reports: The application combines long term forecasts taken
 from forcaset.io and aviation reports from the National Oceanic and Atmospheric Administration
 (NOAA) and the Aviation Weather Center (AWC), which are used by pilots to plan the flights. These
 aviation reports include METAR, TAF, SIGMET and AIRMET, and the variables are temperature,
 wind speed and direction, humidity, precipitations, visibility and ceiling.
- The position of the runways in the airport and crosswind: The orientation (*Image 1*) is needed to calculate the crosswind, the orthogonal component of the wind toward the runway (*Image 2*). I.e., if the orthogonal component is higher than 34 knots, then the conditions are not good for the aircraft to take off. The maximum crosswind component is limited by the aircraft model and is given by the manufacturer. It is common for airports and/or airlines to have their own limitations, lowering this maximum. There might even be more limitations if there's reduced visibility or low ceiling. In this case, the range of acceptable crosswind was taken from one of the Boeing 737 specifications document.



For informational use. Effective March 05, 2015 - April 02, 2015.

Image 1, JFK airport map, FAA (source)




Image 2, Wind components

- Visibility: Even if the international and national standards and regulations allow take-off and landing with almost no visibility and ceilings as low as 200ft, the delays start as soon as the pilot needs to take off or land with IFR. What's more, in the most crowded airports delays could start with MVFR procedures. The limits of each type of flight can be found in NOAA's documents.
- **Icy conditions:** Most of the commercial aircraft are certificated to fly up to moderately icy conditions, but is highly recommendable to avoid flying in severe icing conditions. Even if the plane can take-off in such conditions, it is plausible that after a long taxing, the aircraft might be de-iced, resulting in delays.

- **Ceiling:** The thickness and height of clouds covering the sky, within the limits of the different flight categories: Visual Flight Rules (VFR), Marginal Visual Flight rules (MVFR), Instrument Flight Rules (IFR) and Low Instrument Flight Rules (LIFR).
- The number of runways available in the airport: If any of the runways cannot be used because of the weather conditions, then the same number of departures and arrivals has to be distributed between the remaining number of available runways. This situation will also generate a delay.
- Departure and arriving airports: The departure of an aircraft could be delayed by weather
 conditions at the departure airport, but it could also be delayed due to the bad conditions at the
 arriving airport. There are regulations that have to be met at both the departure and the arriving
 airports.
- Emergency landing at the departure airport: For flight initiation, departure weather minima at an airport should not be less than the applicable minima for landing at that airport unless a suitable take-off alternate aerodrome is available.

Model validation

The model has proven to have accurate results, following two different kinds of tests:

1) The prediction of the application was compared with the actual status of the flights and airports.

For instance, the case below was recorded on April 26th, 2016, at 8 PM CT, at JFK (New York) airport. *Image 3* shows the status of the airport regarding delays due to bad weather conditions, and *Image 4* presents the prediction of GOT a Flight to fly from New York to Philadelphia on April 26th, 2016, at 8 PM CT.



Image 3, JFK airport delayed on April 26th, 2016, 8PM CT Source http://flightaware.com/live/airport/delays




Image 4, GOT a Flight prediction to fly from New York to Philadelphia on April 26th, 2016, 8PM CT

2) Some historic TAF and METAR reports available in the United States Department of Transportation were selected and those data were used as input to test the logic of the application.

For example, on January 1st, 2015, 22% of the flights were delayed in New York due to bad weather conditions, especially because of the wind speed. The wind speed and direction were

extracted from the archive of TAF and METAR and the analysis suggested that 2 out of 4 runways could not be used because the crosswind was almost 28 KT. As GOT a Flight takes into account the level of availability of each runway, the prediction for that particular situation was Medium, which matches 22% of weather-related flight delays.

TAF for JFK on 01-01-2015:

```
**************
# TAF LARGOS de KJFK
**************
201501010321 TAF AMD KJFK 010321Z 0103/0206 24012KT P6SM SKC FM010700 25015G23KT
                      P6SM SKC FM011100 26016KT P6SM SKC FM011600
                      24019G27KT P6SM FEW250 FM020100 25017KT
                      P6SM SKC=
201501010539 TAF KJFK 010539Z 0106/0212 25016KT P6SM SKC FM011600 25020G28KT
                      P6SM FEW250 FM020600 26014KT P6SM SKC=
201501010841 TAF AMD KJFK 010841Z 0109/0212 25016KT P6SM SKC FM011600 25020G28KT
                      P6SM FEW250 FM020600 26014KT P6SM SKC=
201501011139 TAF KJFK 0111392 0112/0218 25016KT P6SM SKC FM011600 24020G28KT
                      P6SM FEW250 FM020400 26014KT P6SM SKC FM021500
                      28012KT P6SM FEW250=
201501011431 TAF AMD KJFK 011431Z 0115/0218 26014G23KT P6SM FEW050 FEW250 FM011700
                      24020G28KT P6SM FEW250 FM020400 26014KT
                      P6SM SKC FM021500 28012KT P6SM FEW250=
201501011721 TAF KJFK 011721Z 0118/0224 24020G28KT P6SM SCT250 FM020000 25016G22KT
                      P6SM SCT250 FM020300 26013KT P6SM BKN250
                      FM021400 28014G20KT P6SM BKN250 FM022200
                      29011KT P6SM BKN250=
201501012033 TAF AMD KJFK 012033Z 0121/0224 24019G27KT P6SM FEW250 FM020000
                      25016G22KT P6SM SCT250 FM020300 26013KT
                      P6SM BKN250 FM021400 28014G20KT P6SM BKN250
                      FM022200 29011KT P6SM BKN250=
201501012333 TAF KJFK 012333Z 0200/0306 23018G26KT P6SM FEW250 FM020500 26014KT
                     P6SM SKC FM021400 28015G23KT P6SM SCT250
                      FM022200 29013KT P6SM SCT250 FM030300 30007KT
                      P6SM SKC=
```

Image 5, TAF for JFK on 01-01-2015

- The TAF shows a wind speed between 23 KT and 28 KT, and wind direction 240°.
- JFK has 4 runways with the following orientation: 40°, 130°, 220° and 310°. Runways with an orientation of 130° and 310° could be delayed because of the crosswind, so the remaining ones needed to handle almost all of the airport traffic.

Roadmap - Improvements Aviators is working on

- Implement Supervised machine learning techniques to gain even more accuracy upon each delayed flight predicted. Currently the application is hosted in IBM Bluemix, so a potential candidate could be the Watson service.
- Add more forecast sources and validate estimates: detect if the weather prediction of a particular source is not reliable at a particular time.
- Include historical statistics and compare them with each prediction to test the results and adjust the
 estimate if found beneficial.
- Check and analyze non-weather data to cover more delay factors, apart from weather conditions.
- Load more aircraft models and airports with the corresponding specifications.
- Insert the flight number instead of the itinerary.

Resources

- Aeronautical Information Publication (AIP)
- National Oceanic and Atmospheric Administration (NOAA)
- Aviation Weather Center (AWC)
- Federal Aviation Association (FAA)
- Aeronautical Charts (Instrument Flight Rules Enroute High Altitude Charts) FAA
- Boeing 737 600/700/800/900 Flight Crew Training Manual
- International Civil Aviation Organization (ICAO): Manual of All-Weather Operations DOC 9365
- United States Department of Transportation, Bureau of Transportation Statistics
- Forecast.io
- University of California, Berkeley: Flight Delay Study http://its.berkeley.edu/node/2299
- IBM Bluemix