

Rigid-Body Ackermann EKF: A Review

Lucas Libshutz

Cornell University, Mechanical and Aerospace Engineering

Abstract—For modern autonomous driving of high speed vehicles, high-accuracy localization is an essential requirement for proper control and planning, especially in competition environments. More specifically, for the Shell Eco Marathon, a car that is going 20+ MPH and on an angled track needs to have high confidence in both angle and position in order to control the car properly on a banked track. This work aims to do exactly this - provide a rigid body based EKF that can provide the orientation and position data to a high level of accuracy, while maintaining model fidelity and speed at runtime. Using JAX to formulate automatically differentiable dynamics, the EKF runs at 5 ms per step, and results in an average RMSE of approximately 2.8 cm and 3.5 cm/s for position and velocity respectively.

I. GOAL

One of the main motivations for this project was to create a base on which the team could test and run an autonomous car in a low stakes environment, and use that to tune the kinematic parameters and the dynamic assumptions for the larger, more complex vehicle that would be tested afterwards. Because of the complex nature of the dynamics of the larger car, some of the main aspects of the system that were modeled included:

- Contact dynamics in z of the tires and the ground
- Orientation and tilt of the vehicle in roll, pitch, *and* yaw
- Tire slip parameters in both lateral and longitudinal directions

To do the last part is especially important for a larger car in a variable driving environment, where variable amounts of tire slip can drastically impact the localization accuracy of a filter, and contribute to large amounts of uncertainty.

II. DERIVATION OF RELEVANT DYNAMICS

A. Notation

- $\mathcal{I}$ denotes an inertial frame, with its z axis pointing in the direction against gravity.
- The position vector in frame $\mathcal{A}$ to a point Q relative to the frame origin is denoted as ${}^{\mathcal{A}}\mathbf{p}_Q$.
- ${}^{\mathcal{A}}R_{\mathcal{B}}$ denotes the rotation matrix from frame $\mathcal{B}$ to frame $\mathcal{A}$. This is such that ${}^{\mathcal{A}}\mathbf{p} = {}^{\mathcal{A}}R_{\mathcal{B}}\mathbf{p}$.
- Let $S(\mathbf{x}) \in \mathbb{R}^{3 \times 3}$ be the skew-symmetric matrix such that $S(\mathbf{x})\mathbf{y} = \mathbf{x} \times \mathbf{y}$, where $\times$ is the cross product operator in $\mathbb{R}^3$.
- The Jacobian of a function $f : \mathbb{R}^n \rightarrow \mathbb{R}^m$ is denoted as $\mathbf{J}_f(\mathbf{x})$, and is defined as the matrix of partial derivatives of f with respect to $\mathbf{x}$.

B. System Dynamics Formulation

With the above notation in mind, we formulate the state of the vehicle as a whole as the following vector:

$$\mathbf{x} = \begin{bmatrix} \mathbf{p} \in \mathbb{R}^3 \\ R \in SO(3) \\ \mathbf{v} \in \mathbb{R}^3 \\ {}^{\mathcal{B}}\boldsymbol{\omega} \in \mathbb{R}^3 \\ \boldsymbol{\omega}_w \in \mathbb{R}^4 \end{bmatrix}$$

From this, we now derive the full state space model of the system. First, we define the translational and rotational kinematics of the car as a whole:

$$\begin{aligned} m\dot{\mathbf{v}} &= m\mathbf{g} + \sum_i \mathbf{f}_i \\ \dot{\mathbf{p}} &= \mathbf{v} \end{aligned} \quad (1)$$

And similarly, for rotational kinematics:

$$\begin{aligned} \mathbb{I}_G {}^{\mathcal{B}}\dot{\boldsymbol{\omega}} + {}^{\mathcal{B}}\boldsymbol{\omega} \times (\mathbb{I}_G {}^{\mathcal{B}}\boldsymbol{\omega}) &= \boldsymbol{\tau} \\ \dot{R} &= R[{}^{\mathcal{B}}\boldsymbol{\omega}]_{\times} \end{aligned} \quad (2)$$

And the formulation for the update of the orientation uses the built-in `jaxlie.SO3.exp` formulation, which evolves on $SO(3)$ while using a quaternion ($q \in S^3$) representation internally within the `jaxlie` library.

The quantity $\mathbf{f}_i$ is the force generated by the i -th wheel, and is calculated by both contact dynamics in z and slip dynamics in both x and y . To calculate the wheel dynamics, we first start with the normal force $f_{z,i}$:

$$f_{z,i} = k_n \text{relu}(z_0 - z) + c_n \text{relu}(0 - v_z) \quad (3)$$

where $f_{z,i}$ is enforced to be positive, such that the car is not pulled into the ground. z_0 is the initial height, and z is the current height of the wheel. v_z is the vertical velocity of the wheel, and k_n and c_n are the stiffness and damping coefficients for the normal force, respectively.

Then, the wheel slip *ratios* are then found via the Pacejka slip model, which is a commonly used empirical model for tire slip dynamics. The slip ratios are defined as follows:

$$\begin{aligned} \kappa_i &= \kappa_{\max} \cdot \frac{v_{t,i} - r\omega_i}{\sqrt{v_{t,i}^2 + \epsilon^2}} \\ \alpha_i &= \arctan \left(\frac{v_{n,i}}{\sqrt{v_{t,i}^2 + \epsilon^2}} \right) \end{aligned} \quad (4)$$

In equation (4), the tolerance ϵ is added to prevent division by zero when the tangential velocity $v_{t,i}$ is very small. The slip ratios κ_i and α_i are then used to calculate the longitudinal and lateral forces generated by the wheel: