

# INF721

2024/2



# Deep Learning

## L17: Transformers

# Logistics

## Last Lecture

- ▶ Machine Translation
- ▶ Decoding
  - ▶ Greedy Search
  - ▶ Beam Search
- ▶ Attention in RNNs

# Lecture Outline

- ▶ Machine Translation
- ▶ Problems with RNNs
- ▶ Transformers
  - ▶ Self-Attention
  - ▶ Multi-head Attention
  - ▶ Encoder & Decoder
  - ▶ Positional Encoding
  - ▶ Masked Multi-head Attention

# Machine Translation

Given a dataset of sentence pairs:


$$(x = \{x^{<1>}, x^{<2>}, \dots, x^{<T_x>}\}, y = \{y^{<1>}, y^{<2>}, \dots, y^{<T_y>}\}),$$

we want to learn a model that maps  $x$  into  $y$ .

Portuguese	English
Olá, como vai você?	Hello, how are you?
O livro está em cima da mesa.	The book is on the table.
Lucas irá viajar ao Rio em Dezembro.	Lucas is travelling to Rio in December.
Em Dezembro, Lucas irá viajar ao Rio.	Lucas is travelling to Rio in December.
....	....

# Problems with RNNs

- ▶ Struggle to capture long dependencies in sequences
- ▶ Hard to parallelize




# Transformers

**Transformers** are an encoder-decoder architecture to process sequences using only attention (eliminating recurrence).


Initially proposed for machine translation, but proved to be very effective in many other problems in:

- ▶ Natural Language Processing
- ▶ Computer Vision
- ▶ Reinforcement Learning
- ▶ ...




# Attention in RNNs vs. Transformers

## RNNs    Badahnau (Additive) Attention




## Transformers    Scaled Dot-Product Attention





# Encoder Input


The transformer encoder takes as input a sequence of word embeddings summed with positional encodings. This sequence has the constant size  $(T_x, d_{model})$  throughout the entire model



The contextual embeddings size is typically called  $d_{model}$

  $X_{epe} = X_e + PE$   
 $X_{epe} \in \mathbb{R}^{T_x \times d_{model}} \rightarrow \text{word + pos. embed.}$


  $X_e = EX$   
 $X_e \in \mathbb{R}^{T_x \times d_{model}} \rightarrow \text{word embedding}$   
 $E \in \mathbb{R}^{|V| \times d_{model}} \rightarrow \text{embedding matrix}$

  $X \in \mathbb{R}^{T_x \times |V|} \rightarrow \text{one-hot}$





# Self-Attention

The key idea behind the Transformer is the **self-attention mechanism**, which learns a context vector  $c^{<t>}$  for each input element  $x^{<t>}$  based on the input sequence  $x$  itself.





# Self-Attention

The contextual representation  $C = \{c^{<1>}, \dots, c^{<T_x>}\}$  of the entire input sequence  $x = \{x^{<1>}, \dots, x^{<T_x>}\}$  can be computed in a vectorized way combining vectors  $q^{<t>}, k^{<t>}, v^{<t>}$  in matrices  $Q, K$  e  $V$



# Self-Attention

$$C = \text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$



The attention layer receives the embedded sequence  $X_{epe}$  as input

$X_{epe} \in \mathbb{R}^{T_x \times d_e}$


Lucas			
will			
travel			

$$d_e = d_q = d_k = d_v = 3$$

The sizes of key and query have to be the same. But embeddings and value typically also have same sizes.

# Multi-Head Attention

The Multi-Head Attention layers learns  $h$  independent representations  $C_i$  (called heads) using Self-Attention



# Multi-Head Attention

$Multihead(Q, K, V) = Concat(C_1, C_2, C_3)W^o$

$$\begin{matrix} C_1 & C_2 & C_3 \\ \hline \end{matrix} \times W^o \in \mathbb{R}^{d_{model} \times d_{model}} = C \in \mathbb{R}^{T_x \times d_{model}}$$

$C_1 = softmax(\frac{Q_1 K_1^T}{\sqrt{d_k}}) V_1$

$C_2 = softmax(\frac{Q_2 K_2^T}{\sqrt{d_k}}) V_2$

$C_3 = softmax(\frac{Q_3 K_3^T}{\sqrt{d_k}}) V_3$

$Q_1 = X_{epe} W_1^q \quad K_1 = X_{epe} W_1^k \quad V_1 = X_{epe} W_1^v$

$Q_2 = X_{epe} W_2^q \quad K_2 = X_{epe} W_2^k \quad V_2 = X_{epe} W_2^v$

$Q_3 = X_{epe} W_3^q \quad K_3 = X_{epe} W_3^k \quad V_3 = X_{epe} W_3^v$

Number of heads  $h = 3$   
 $d_k = \frac{d_{model}}{h} = 3$

$W^q \in \mathbb{R}^{d_{model} \times d_{model}}$   
 $W^k \in \mathbb{R}^{d_{model} \times d_{model}}$   
 $W^v \in \mathbb{R}^{d_{model} \times d_{model}}$   
 $W^o \in \mathbb{R}^{d_{model} \times d_{model}}$

$T_x = 3$   
(sequence length)  
 $d_{model} = 9$

Lucas  
will  
travel

$X_{epe} \in \mathbb{R}^{T_x \times d_{model}}$


# Encoder

**Input:** a sequence  $x = \{x^{<1>}, \dots, x^{<T_x>}\}$

**Output:** a contextual representation  $C = \{c^{<1>}, \dots, c^{<T_x>}\}$  of  $x$

The encoder applies a **Multihead Layer** followed by a **Feed Forward Neural Network** (MLP).

Both are normalized with Layer Norm (**Norm**) and connected with a residual connection (**Add**)






# Decoder

**Input:** Input context  $C$  and previous  $\{\hat{y}^{<1>}, \dots, \hat{y}^{<t-1>}\}$  output tokens


**Output:** The next token  $\hat{y}^{<t>}$

## Decoder Nx



# Inference Example


At inference time, the model is autoregressive, i.e., it generates one word at a time.






# Inference Example

At inference time, the model is autoregressive, i.e., it generates one word at a time.



# Inference Example

At inference time, the model is autoregressive, i.e., it generates one word at a time.




# Positional Encoding

The self-attention mechanism does not consider the position of the words.

$C$


 $= \text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V$

To add this information to the learned contextual representation  $C$ , both encoder and decoder add a positional information to each element  $x^{<t>}$  of the input  $x = \{x^{<1>}, \dots, x^{<T_x>}\}$




# Positional Encoding

$$PE_{(t,2i)} = \sin(\frac{t}{10000^{\frac{2i}{d}}}) \quad \text{if } i \text{ is even}$$
$$PE_{(t,2i+1)} = \cos(\frac{t}{10000^{\frac{2i}{d}}}) \quad \text{if } i \text{ is odd}$$



# Training with Masked Multi-head Attention



- ▶ During training, the model **does not** produce  $\hat{y}$  one token at a time;
- ▶ Instead, the output  $\hat{y}$  is produced once, in parallel with vectorization.
- ▶ Thus, the full target sentence  $y = \{y^{(1)}, \dots, y^{(T_y)}\}$  is given as input to the Decoder, which uses a **mask** to predict  $\hat{y}^{(t)}$ , so it does not attend to the future tokens ( $\hat{y}^{(t')}, t' > t$ ). For example, for  $t = 5$ :

# Training with Masked Multi-head Attention

Attention weights (normalized by row) of word  $i$  to word  $j$  after mask application

$$\begin{array}{c} Q \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} \times \begin{array}{c} K^T \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} = \begin{array}{c} \begin{bmatrix} 31 & 27 & 22 \\ 27 & 42 & 31 \\ 22 & 31 & 37 \end{bmatrix} \\ \sqrt{(d_k)} \end{array} + \begin{array}{c} \text{Mask} \\ \begin{bmatrix} 0 & -\text{inf} & -\text{inf} \\ 0 & 0 & -\text{inf} \\ 0 & 0 & 0 \end{bmatrix} \end{array} = \text{softmax}\left( \begin{array}{c} \begin{bmatrix} 31 & -\text{inf} & -\text{inf} \\ 27 & 42 & -\text{inf} \\ 22 & 31 & 37 \end{bmatrix} \\ \sqrt{(d_k)} \end{array} \right) = \begin{array}{c} \begin{bmatrix} .1 & .0 & .0 \\ .3 & .7 & .0 \\ .3 & .3 & .4 \end{bmatrix} \end{array}$$

$$\begin{array}{c} Q \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} = \begin{array}{c} X_{epe} \\ \begin{bmatrix} \square & \square & \square \\ \square & \square & \square \\ \square & \square & \square \end{bmatrix} \end{array} \times \begin{array}{c} W^q \in \mathbb{R}^{d_e \times d_q} \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} \quad \begin{array}{c} K \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} = \begin{array}{c} X_{epe} \\ \begin{bmatrix} \square & \square & \square \\ \square & \square & \square \\ \square & \square & \square \end{bmatrix} \end{array} \times \begin{array}{c} W^k \in \mathbb{R}^{d_e \times d_k} \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} \quad \begin{array}{c} V \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array} = \begin{array}{c} X_{epe} \\ \begin{bmatrix} \square & \square & \square \\ \square & \square & \square \\ \square & \square & \square \end{bmatrix} \end{array} \times \begin{array}{c} W^v \in \mathbb{R}^{d_e \times d_v} \\ \begin{bmatrix} \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \\ \blacksquare & \blacksquare & \blacksquare \end{bmatrix} \end{array}$$

The attention layer receives the embedded sequence  $X_{epe}$  as input

$X_{epe} \in \mathbb{R}^{T_x \times d_e}$

Lucas			
will			
travel			

$d_e = d_q = d_k = d_v = 3$

The sizes of key and query have to be the same. But embeddings and value typically also have same sizes.

# Next Lecture

## **L17:** Transformers (Part II)

Case studies of transformers: BERT and GPT