





Intuiting Nondeterminism

- Nondeterministic machines are a serious departure from physical computers. How can we build up an intuition for them?
- There are two particularly useful frameworks for interpreting nondeterminism:
 - *Perfect guessing*
 - *Massive parallelism*




Perfect Guessing





Perfect Guessing





Perfect Guessing





Perfect Guessing





Perfect Guessing





Perfect Guessing





Perfect Guessing





Perfect Guessing





Perfect Guessing



Perfect Guessing






Perfect Guessing






Perfect Guessing

- We can view nondeterministic machines as having *Magic Superpowers* that enable them to guess choices that lead to an accepting state.
 - If there is at least one choice that leads to an accepting state, the machine will guess it.
 - If there are no choices, the machine guesses any one of the wrong guesses.
- No known physical analog for this style of computation – this is totally new!




Massive Parallelism






Massive Parallelism






Massive Parallelism






Massive Parallelism





Massive Parallelism





Massive Parallelism





Massive Parallelism





Massive Parallelism





Massive Parallelism





Massive Parallelism






Massive Parallelism






Massive Parallelism





Massive Parallelism





Massive Parallelism





Massive Parallelism





Massive Parallelism




Massive Parallelism



Massive Parallelism



Massive Parallelism



a	b	a	b	a
---	---	---	---	---

We're in at least one accepting state, so there's some path that gets us to an accepting state.

Therefore, we accept!

Massive Parallelism

- An NFA can be thought of as a DFA that can be in many states at once.
- At each point in time, when the NFA needs to follow a transition, it tries all the options at the same time.
- (Here's a rigorous explanation about how this works; read this on your own time).
 - Start off in the set of all states formed by taking the start state and including each state that can be reached by zero or more ϵ -transitions.
 - When you read a symbol **a** in a set of states S :
 - Form the set S' of states that can be reached by following a single **a** transition from some state in S .
 - Your new set of states is the set of states in S' , plus the states reachable from S' by following zero or more ϵ -transitions.

So What?

- Each intuition of nondeterminism is useful in a different setting:
 - Perfect guessing is a great way to think about how to design a machine.
 - Massive parallelism is a great way to test machines – and has nice theoretical implications.
- Nondeterministic machines may not be feasible, but they give a great basis for interesting questions:
 - Can any problem that can be solved by a nondeterministic machine be solved by a deterministic machine?
 - Can any problem that can be solved by a nondeterministic machine be solved *efficiently* by a deterministic machine?
- The answers vary from automaton to automaton.

Designing NFAs

Designing NFAs


- When designing NFAs, *embrace the nondeterminism!*
- Good model: ***Guess-and-check***:
 - Is there some information that you'd really like to have? Have the machine *nondeterministically guess* that information.
 - Then, have the machine *deterministically check* that the choice was correct.
- The *guess* phase corresponds to trying lots of different options.
- The *check* phase corresponds to filtering out bad guesses or wrong options.

Guess-and-Check

$$L = \{ w \in \{ \mathbf{0}, \mathbf{1} \}^* \mid w \text{ ends in } \mathbf{010} \text{ or } \mathbf{101} \}$$


Guess-and-Check

$$L = \{ w \in \{0, 1\}^* \mid w \text{ ends in } 010 \text{ or } 101 \}$$




Guess-and-Check

$$L = \{ w \in \{ \mathbf{0}, \mathbf{1} \}^* \mid w \text{ ends in } \mathbf{010} \text{ or } \mathbf{101} \}$$



Guess-and-Check

$$L = \{ w \in \{0, 1\}^* \mid w \text{ ends in } 010 \text{ or } 101 \}$$




Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$

Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$




Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$



Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$






Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$




Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$




Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$




Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$



Guess-and-Check

$L = \{ w \in \{\mathbf{a}, \mathbf{b}, \mathbf{c}\}^* \mid \text{at least one of } \mathbf{a}, \mathbf{b}, \text{ or } \mathbf{c} \text{ is not in } w \}$



Nondeterministically **guess** which character is missing.

Deterministically **check** whether that character is indeed missing.

Just how powerful are NFAs?