

Bachelor Thesis

June 2, 2017

GUI usability and testing of mobile applications

Example subtitle

Lucas Pelloni

of 18.03.1993, Switzerland (13-722-038)

supervised by

Prof. Dr. Harald C. Gall
Dr. Sebastiano Panichella
Giovanni Grano (PhD student)



University of
Zurich^{UZH}



Bachelor Thesis

GUI usability and testing of mobile applications

Example subtitle

Lucas Pelloni



University of
Zurich^{UZH}



Bachelor Thesis

Author: Lucas Pelloni, lucas.pelloni@uzh.ch

URL: https://github.com/lucaspelloni2/BA_PROJ

Project period: 08.01.2017 - 08.07.2017

Software Evolution & Architecture Lab
Department of Informatics, University of Zurich

“Program testing can be used to show the presence of bugs, but never to show their absence.”
Edsger W. Dijkstra

Acknowledgements

Abstract

Zusammenfassung

Contents

1	Introduction	1
1.1	Context	2
1.2	Motivation	3
1.3	Motivation Example	3
1.4	Research questions	3
1.4.1	Subsection	3
2	Related Work	5
2.1	Automated tools for Android Testing	5
2.2	Usage of users reviews in Software maintenance activities	6
3	Approach	9
4	Tool	11
5	Results and Discussion	13
6	Conclusions and Future Work	15

List of Figures

1.1	imgs/seal logo	3
-----	--------------------------	---

List of Tables

List of Listings

1.1	An example code snippet	3
-----	-----------------------------------	---

Introduction

Testing is the action of inspecting the behaviour of a program, with the intention of finding anomalies or errors [22]. The goal behind Software testing is to reach the highest testing coverage finding the largest number of errors with the smallest number of *test cases* (a set of test inputs associated with an expected result when they are processed by a program).

Software testing is widely recognised as an essential part of any software development process, presenting however an extremely expensive activity. This because, trying to test all combinations of all possible input values for an application [9] requires a lot of workforce and it is almost always unthinkable to reach a testing-coverage of 100%, since testing needs to be performed under time and budget constraints [11]. In fact, as observed by *Dijkstra* [8], testing a software does not imply a demonstration of the right behaviour of the program, but it only aims to demonstrate the presence of faults, not their absence. Even though a full testing coverage normally cannot be reached, a program that would be carefully tested (and all bugs found would have been corrected), would increase the probability that it would behave as expected in the untested cases [9].

In general, there are four testing levels:

1. Unit testing;
2. Integration testing;
3. System testing;
4. Acceptance testing.

With *unit testing*, the application components are viewed and split into individual *units* of source code, which are normally functions or small methods. Intuitively, one can view a unit as the smallest testable part of an application. This kind of testing is usually associated with a *white-box* approach (see in the next paragraph). *Integration testing* is the activity of finding faults after testing the previous individually tested units combined and tested as a group together. *System testing* is conducted on a complete, integrated system to evaluate the compliance with its requirements. You can imagine system testing as the last checkpoint before the end customer. Indeed, *acceptance testing* (or *customer testing*) is the last level of the testing process, which states whether the application meets the user needs and whether the implemented system works for the user. This kind of testing is usually associated with a *black-box* approach.

These mentioned testing levels represent the main steps a tester should perform in order to validate a software. They shall be sequentially executed and are combined with two other testing methodologies [24,25]:

- black-box testing;

- white-box testing.

With *Black-box* testing, also called functional testing, the tester doesn't need to have any prior knowledge of the interior structure of the application. He tests only the functionalities provided by the software without any access to the source code. Typically, when performing a black box test, a tester will interact with the system's user interface by providing inputs and examining outputs without knowing how and where the inputs are worked upon. On the other side, with *white-box* testing, also *glass testing* or *open box testing* [11], the test cases are extrapolated from the internal software's structure. Indeed, the tester writes the test cases defining a paths through the code, which has to provide a sensible output.

Since, testing costs has been estimated at being at least half of the entire development cost [4], it is necessary to reduce them, trying to improve the effectiveness of testing with the goal to automate the testing process.

1.1 Context

While mobile applications are becoming so widely adopted, it is still unclear if they deserve any specific testing approach for their verification and validation [2].

Since, unlike traditional software, applications are mainly exercised by user inputs, an extremely valid approach to ensure the reliability of these applications is the GUI¹ testing. In particular, in this kind of testing, each test case is designed and run in the form of sequences of GUI interaction events.

The most famous automated GUI testing tools and their properties are discussed in the chapter *Related Work*.

Despite a strong evidence for automated testing approaches in verifying GUI application and revealing bugs, these state-of-art tools cannot always achieve a high code coverage [21]. One reason is that an automated event-test-generation tool is not suited for generating inputs that require human intelligence (e.g., inputs to text boxes that expect valid passwords, or playing and winning a game with a strategy, etc.). For this reason, sometimes a time-consuming manual approach can be needed for testing an application [21].

However, GUI testing could not be the only approach to help developers find bugs in a mobile application. Nowadays, the exponential growth of the mobile stores offers an enormous amount of informations and feedbacks from users. Therefore, another different strategy is to incorporate opinions and reviews of the end-users during the software's evolution process.

In this direction, in a recent work Panichella *et al.* introduced a tool called SURF (Summarizer of User Reviews Feedback), that is able to analyse the useful informations contained in app reviews and to performs a systematic summarisation of thousands of user reviews through the generation of an interactive agenda of recommended software changes [23].

¹Graphical User Interface

1.2 Motivation

1.3 Motivation Example

1.4 Research questions

Subsubsection



Figure 1.1: imgs/seal logo

1.4.1 Subsection

Paragraph. Always with a point.

```
/**
 * Javadoc comment
 */
public class Foo {
    // line comment
    public void bar(int number) {
        if (number < 0) {
            return; /* block comment */
        }
    }
}
```

Listing 1.1: An example code snippet

Related Work

In the following two sections, I summarize the main related works on *automated testing tools for Android apps* and on *the broadly usage of user reviews from app store in Software maintenance activities*. An overview of the recent research in the field can be found in the survey by Martin *et al.* [18].

2.1 Automated tools for Android Testing

Unlike traditional software, mobile applications are mainly exercised by user inputs.

In the mobile world, an extremely valid approach to ensure the reliability of these applications is the GUI¹ Testing.

In particular, in this kind of testing, each test case is designed and run in the form of sequences of GUI interaction events.

Depending on their exploration strategy, there are in general three approaches for creating a generation of user inputs on a mobile device [7, 14]: *random testing* [10, 14], *systematic testing* [16] and *model-based testing* [3, 5, 13].

Fuzz testing

When test automation does occur, it typically relies on Google's Android *Monkey* command-line [10]. Since it comes directly integrated in Android Studio, the standard IDE for Android Development, it is regarded as the current state-of-practice [15].

This tool simply generates, for the specified Android applications, pseudo-random streams of user events into the system, with the goal to stress the AUT² [10].

The effort required for using *Monkey* is very low [7]. Users have to specify in the command-line the type and the number of the UI events they want to generate and in addition they can establish the verbosity level of the *Monkey log*.

The set of possible *Monkey parameters* can be found in the official *User Guide* for *Monkey* [10].

The kind of testing implemented by *Monkey* follows a black-box approach. Despite the robustness, the user friendliness [7, 14] and the capacity to find out new bugs outside the stated scenarios [1], this tool may be inefficient if the AUT would require some human intelligence (*e.g.* a login field) for providing sensible inputs [14].

For this reason, *Monkey* may cause highly redundant and senseless user events. Even though it would find out a new bug for a given app, the steps for reproducing it may be very difficult to follow, due also to the randomness in the testing strategy implemented by *Monkey* [1].

¹Graphical User Interface

²Application Under Test

Dynodroid [14] is also a random-based testing approach. However, this tool has been discovered being more efficient than *Monkey* in the exploration process [7].

One of the reasons behind a better efficacy has been that *Dynodroid* is able to generate both *UI inputs* and *system events* (unlike *Monkey*, which can only generate UI events) [7].

Indeed, *Dynodroid* can simulate an incoming SMS message on a mobile device, a notification of another app or an request of use for available wifi networks in the neighborhood [14]. All these events represent *non-UI events* and they are often unpredictable and therefore difficult to simulate in a suitable context (cita?).

Dynodroid views the *AUT* as an event-driven program and follows a cyclical mechanism, also known as the *observe-select-execute* cycle [14]. First of all, it *observes* which events are relevant to the *AUT* in the current state, grouping them together (an event must be considered relevant if it triggers a part of code which is part of the *AUT*). After that, it *selects* one of the previously observed events with a randomized algorithm [7, 14] and finally *executes* it. After the execution of that event it reaches a new state and can start the cycle again.

Another advantage of *Dynodroid* compared to *Monkey* is that it allows users to interact in the testing process providing UI inputs. In doing so, *Dynodroid* is able to exploit the benefits of combining automated with manual testing [14].

Systematic testing

The tools using a systematic explorations strategy rely on more sophisticated techniques, such as symbolic execution and evolutionary algorithms [7].

Sapienz [17] introduced a Pareto multi-objective search-based technique to simultaneously maximize coverage and fault revelation, while minimizing the sequence lengths.

It combines the above mentioned random-based approach with a new systematic exploration and as mentioned in the experimental results published on [17], *Sapienz* is an outperformer in the automated mobile testing area.

Indeed, in an empirical study described on [17], *Sapienz* has illustrated the strength of its approach. It found from a set of 68 benchmark apps, 104 unique crashes (while *Monkey* 41 and *Dynodroid* 13).

Model-based testing

Model-based tools for testing Android applications are quite popular [17]. Most of these tools [3, 5, 6, 13, 20] generate UI events from models, which are either manually designed or created from XML configuration files [17].

For example, *SwiftHand*³ uses a machine learning algorithm to learn a model of the current *AUT*. This final state machine model [7] generates UI events and due their execution the app reaches new unexplored states. After that, it exploits the execution of these events to adapt and refine the model [6]. *SwiftHand*, in a similar way to *Monkey* generates only touching and scrolling UI events and is not able to generate System events [7].

2.2 Usage of users reviews in Software maintenance activities

The concept of app store mining was first introduced by *Harman et al.* [12]. In this context, many researchers focused on the analysis of user reviews to support the maintenance and evolution of

³<https://github.com/wtchoi/SwiftHand>

mobile applications [19].

Approach

Chapter 4

Tool

Results and Discussion

Conclusions and Future Work

Bibliography

- [1] What is monkey testing? types, advantages and disadvantages. .
- [2] D. Amalfitano, A. R. Fasolino, P. Tramontana, and B. Robbins. Testing Android Mobile Applications: Challenges, Strategies, and Approaches. *Advances in Computers*, 2013.
- [3] D. Amalfitano, A. R. Fasolino, P. Tramontana, B. D. Ta, and A. M. Memon. Mobiguitar: Automated model-based testing of mobile apps. *IEEE Software*, 32(5):53–59, 2015.
- [4] B. Beizer. *Software testing techniques*. Van Nostrand Reinhold Co., 1990.
- [5] W. Choi, G. Necula, and K. Sen. Guided gui testing of android apps with minimal restart and approximate learning. *SIGPLAN Not.*, 48(10):623–640, Oct. 2013.
- [6] W. Choi, G. Necula, and K. Sen. Guided gui testing of android apps with minimal restart and approximate learning. In *ACM SIGPLAN Notices*, volume 48, pages 623–640. ACM, 2013.
- [7] S. R. Choudhary, A. Gorla, and A. Orso. Automated test input generation for android: Are we there yet? (e). In *Proceedings of the 2015 30th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, ASE '15, pages 429–440, Washington, DC, USA, 2015. IEEE Computer Society.
- [8] W. E. W. Dijkstra. Edsger w. dijkstra. .
- [9] M. Glinz and T. Fritz. *Kapitel 8: Testen von Software*. University of Zurich, 2006-2013.
- [10] Google. Android monkey. .
- [11] G. Grano. Implementation and comparison of novel techniques for automated search based test data generation. Master’s thesis, University of Salerno, 2015.
- [12] M. Harman, Y. Jia, and Y. Zhang. App store mining and analysis: Msr for app stores. In *2012 9th IEEE Working Conference on Mining Software Repositories (MSR)*, pages 108–111, June 2012.
- [13] M. Linares-Vásquez, M. White, C. Bernal-Cárdenas, K. Moran, and D. Poshyvanyk. Mining android app usages for generating actionable gui-based execution scenarios. In *Proceedings of the 12th Working Conference on Mining Software Repositories, MSR '15*, pages 111–122, Piscataway, NJ, USA, 2015. IEEE Press.
- [14] A. Machiry, R. Tahiliani, and M. Naik. Dynodroid: An input generation system for android apps. In *Proceedings of the 2013 9th Joint Meeting on Foundations of Software Engineering, ES-EC/FSE 2013*, pages 224–234, New York, NY, USA, 2013. ACM.

- [15] R. Mahmood and S. Malek. EvoDroid : Segmented Evolutionary Testing of Android Apps. *Fse*, pages 599–609, 2014.
- [16] R. Mahmood, N. Mirzaei, and S. Malek. Evodroid: Segmented evolutionary testing of android apps. In *Proceedings of the 22Nd ACM SIGSOFT International Symposium on Foundations of Software Engineering, FSE 2014*, pages 599–609, New York, NY, USA, 2014. ACM.
- [17] K. Mao, M. Harman, and Y. Jia. Sapienz: Multi-objective automated testing for android applications. In *Proceedings of the 25th International Symposium on Software Testing and Analysis, ISSTA 2016*, pages 94–105, New York, NY, USA, 2016. ACM.
- [18] W. Martin, F. Sarro, Y. Jia, Y. Zhang, and M. Harman. A survey of app store analysis for software engineering. *IEEE Transactions on Software Engineering*, PP(99):1–1, 2016.
- [19] W. Martin, F. Sarro, Y. Jia, Y. Zhang, and M. Harman. A survey of app store analysis for software engineering. *IEEE Transactions on Software Engineering*, PP(99):1–1, 2016.
- [20] A. M. Memon, I. Banerjee, and A. Nagarajan. Gui ripping: Reverse engineering of graphical user interfaces for testing. In *WCRE*, volume 3, page 260, 2003.
- [21] M. Nagappan and E. Shihab. Future Trends in Software Engineering Research for Mobile Apps. *Saner’15*, 2015.
- [22] M. D. Network. Testing process. .
- [23] A. D. Sorbo, S. Panichella, C. V. Alexandru, J. Shimagaki, C. A. Visaggio, G. Canfora, and H. C. Gall. What would users change in my app? summarizing app reviews for recommending software changes. In *Proceedings of the 24th ACM SIGSOFT International Symposium on Foundations of Software Engineering, FSE 2016, Seattle, WA, USA, November 13-18, 2016*, pages 499–510, 2016.
- [24] Wikipedia. black-box testing. .
- [25] Wikipedia. white-box testing. .