

Mesh Addition Based on the Depth Image (MABDI)

Lucas Chavez

Dr. Lumia¹ Dr. Fierro¹
Dr. Anderson²

¹University of New Mexico

²Sandia National Laboratories

November 2016



*This work was supported in part by:
Sandia National Laboratories under Purchase Order: 1179196 and NSF grant OISE #1131305.*

Outline

1 Introduction

- Overview
- RBG-D Sensor
- Map
- Contribution

2 Approach

- Algorithm
- Surface Reconstruction

3 Experimental Setup

- Simulated Sensor
- Simulation Parameters

4 Results

5 Conclusion

Outline

1 Introduction

- Overview
- RBG-D Sensor
- Map
- Contribution

2 Approach

- Algorithm
- Surface Reconstruction

3 Experimental Setup

- Simulated Sensor
- Simulation Parameters

4 Results

5 Conclusion

Overview

Motivation for this work: provide a map of the environment

Examples applications:


- Autonomous agents (robots)
- Teleoperation (human)

Overview

In the literature this is referred to as the SLAM problem

- Simultaneous Localization and Mapping
- Environmental Mapping
- Research began around 1987
- Sensing and computing technology

Overview




RBG-D Sensor



- 30 frames per second
- D - 9 million pixel values per second
- Algorithms must handle a high rate of data


Mesh




Mesh

- Supported
- Computationally Inexpensive
- Low Memory Requirement

Pipeline



Pipeline



Contribution

MABDI's algorithmic design identifies redundant information and removes it *before* it is added to the global mesh.

Outline

1 Introduction

- Overview
- RGB-D Sensor
- Map
- Contribution

2 Approach

- Algorithm
- Surface Reconstruction





3 Experimental Setup

- Simulated Sensor
- Simulation Parameters




4 Results

5 Conclusion

MABDI Algorithm



MABDI Algorithm



Simulated for the Experiments

Input

Depth Image (D) and Pose (P) from sensor.

Classification

Generate Expected Depth Image (E)

Classify Depth Image (D):

Classification is based on the difference between expected (E) and actual (D).
 (D_n) are novel values in the depth image (D).

Surface Reconstruction:

Novel Surface (S) generated from Novel Values (D_n).
Any surface reconstruction algorithm can be used.

Add Novel Surface (S) to Global Mesh (M)

D

P





E

M





D_n

S





MABDI Algorithm



MABDI Algorithm



MABDI Algorithm




Initial Mesh

Surface Reconstruction component is responsible for creating the novel surface S from the novel points D_n


My Method:

- Define topology in 2D, on the depth image
- Project to 3D
- Remove elements


Initial Mesh




Initial Mesh




Removing elements



Removing elements




Removing elements



$$D_n = |D - E| > threshold$$

$$D_{known} = D \setminus D_n$$


Removing elements



$$K = \begin{bmatrix} 2 & -1 \\ -1 & 0 \end{bmatrix}$$

$$D_{boundary} = (D * K) > threshold$$

Removing elements



Outline

1 Introduction

- Overview
- RGB-D Sensor
- Map
- Contribution

2 Approach

- Algorithm
- Surface Reconstruction



3 Experimental Setup

- Simulated Sensor
- Simulation Parameters

4 Results

5 Conclusion


Overview




Simulating a RGB-D Sensor


- Adding noise to the depth image
- Sensor path

Rendering Pipeline



T_{pcm} 

Adding Noise



Adding Noise


$$D_{noisy}(i, j) = D(i, j) + \mathcal{N}(\mu=0, \sigma=0.002)$$

Adding Noise


K. Khoshelham and S. O. Elberink, "Accuracy and resolution of Kinect depth data for indoor mapping applications." *Sensors (Basel, Switzerland)*

$$\sigma_z = 1.425 \times 10^{-5} \times Z^2$$

Adding Noise



Sensor Path



Simulation Parameters

	Environment	Noise	Dynamic	Iterations
Experiment 1	Table	False	False	30
Experiment 2	Bunnies	True	False	50
Experiment 3	Bunnies	True	True	50

Outline

1 Introduction

- Overview
- RBG-D Sensor
- Map
- Contribution

2 Approach

- Algorithm
- Surface Reconstruction


3 Experimental Setup

- Simulated Sensor
- Simulation Parameters

4 Results


5 Conclusion

During the Experiment




During the Experiment


(a)




(b)




(c)




(d)



(e)




(f)




During the Experiment


(a)





(b)




(c)



(d)




(e)





(f)





Mesh Quality





Mesh Progression



Mesh Progression



Mesh Progression



Outline

1 Introduction

- Overview
- RBG-D Sensor
- Map
- Contribution

2 Approach

- Algorithm
- Surface Reconstruction

3 Experimental Setup

- Simulated Sensor
- Simulation Parameters

4 Results

5 Conclusion

Conclusion

- The MABDI algorithm runs at around 2Hz on a consumer grade laptop with an Intel i7 processor.
- MABDI's algorithmic design identifies redundant information and removes it *before* it is added to the global mesh.
- MABDI does this by leveraging the difference between what we are actually seeing and what we expect to see.
- MABDI can work in conjunction with any current mesh-based surface reconstruction algorithms, and can be thought of as a general means to provide introspection to those types of reconstruction methods.

Conclusion

- The MABDI algorithm runs at around 2Hz on a consumer grade laptop with an Intel i7 processor.
- MABDI's algorithmic design identifies redundant information and removes it *before* it is added to the global mesh.
- MABDI does this by leveraging the difference between what we are actually seeing and what we expect to see.
- MABDI can work in conjunction with any current mesh-based surface reconstruction algorithms, and can be thought of as a general means to provide introspection to those types of reconstruction methods.

Conclusion

- The MABDI algorithm runs at around 2Hz on a consumer grade laptop with an Intel i7 processor.
- MABDI's algorithmic design identifies redundant information and removes it *before* it is added to the global mesh.
- MABDI does this by leveraging the difference between what we are actually seeing and what we expect to see.
- MABDI can work in conjunction with any current mesh-based surface reconstruction algorithms, and can be thought of as a general means to provide introspection to those types of reconstruction methods.

Conclusion

- The MABDI algorithm runs at around 2Hz on a consumer grade laptop with an Intel i7 processor.
- MABDI's algorithmic design identifies redundant information and removes it *before* it is added to the global mesh.
- MABDI does this by leveraging the difference between what we are actually seeing and what we expect to see.
- MABDI can work in conjunction with any current mesh-based surface reconstruction algorithms, and can be thought of as a general means to provide introspection to those types of reconstruction methods.

Thank you for your attention