
SYSC 4806 Software Engineering Laboratory

Dependency Injection and the Spring Framework

Java Components, a.k.a JavaBeans


- JavaBeans are basically Plain Old Java Objects (POJOs)
 - they just follow a few conventions, so they can be easily initialized and assembled by 3rd party tools:
 - provide a default constructor
 - getter/setter method naming
 - As standalone components they could be assembled in a “BeanBox”, although the original BeanBox implementation didn’t last long...
 - GUI design tools perpetuate the idea (most Swing classes are JavaBeans)
 - Enterprise JavaBeans (EJBs) extended the idea for web app development (with support for threading, transactions, data access, etc.), but got too complex:
 - introduced many constraints and *dependencies*
 - backlash against EJBs led to a return to the POJO model
-

Dependency Injection

- Another term and pattern coined by Martin Fowler
 - see the [blog post](#) where it came from
 - also described in PEAA as the Plugin pattern
- It's about decoupling pushed to the extreme, to help with “componentization” and ease of unit testing
 - components and services are supposed to be even more reusable than typical classes
 - this means the component shouldn't be dependent on the implementations of other classes unless they are part of the service that it is supposed to provide
 - the component can be tested in isolation, using stubs when appropriate


The dependency problem by example

(from Fowler's blog post)




Dependency Lookup using a Service Locator

Used by EJBs via JNDI
(fig. from Fowler's blog post)



Dependency Injection with Inversion of Control

(from Fowler's blog post)



Benefits of Dependency Injection

- Ease of unit testing: the dependency can be mocked by the container, no change to the unit required
- No boilerplate code to hook up components together
- No dependency on a framework on the container. It calls *you*.

Bean Configuration in Spring

- three possibilities: XML, Java code, Java annotations,
- XML is the old way, Java annotations are probably the best way now
- the beans we want to configure are the ones whose dependencies we don't want to hard code: data mapper, various services, etc.

XML-based Configuration

- `<beans>`, `<bean>` tags

```
<beans>
    <bean id="transferService" class="com.acme.TransferServiceImpl"/>
</beans>
```

- To load:

```
ApplicationContext context = new
    ClassPathXMLApplicationContext("/path/to/config.xml");
```

Java-based Configuration

- @Configuration, @Bean annotations
 - corresponding respectively to <beans> and <bean> tags

```
@Configuration
public class AppConfig {

    @Bean
    public TransferService transferService() {
        return new TransferServiceImpl();
    }

}
```

- To load:

```
ApplicationContext context = new
    JavaConfigApplicationContext(AppConfig.class);
```

Annotation-based Configuration

- My preferred way! Works especially well for *Spring Boot*
- `@Component`, `@Service`, `@Repository` to declare beans

```
@Service
```

```
public class TransferServiceImpl implements TransferService
```

- `@Autowired` to declare injection point
- `@ComponentScan` to do away with config files

Spring Boot

- Takes an “opinionated view” to help do away with most configuration. Only need to:
 - use annotation-based configuration for your beans
 - declare Spring Boot starter kit dependencies in Maven or Gradle
 - “properly” annotate the main class so that it auto-configures, scans for beans, and launch `SpringApplication` in the `main()` method
- Best understood by checking out [the docs](#)

Spring MVC annotations

- @Controller, @RestController, @Service
- [@Repository, @CRUDRepository](#): for DAO and Models
- @Resource