

Lucas Waclawczyk

Decidability of Logical Theories

Proseminar Theoretical Computer Science // Dresden, May 4, 2020

Inhalt

Basics

$\text{Th}(\mathbb{N}, +)$ – A Decidable Theory

$\text{Th}(\mathbb{N}, +, \times)$ – An Undecidable Theory


Gödel's Incompleteness Theorem

Conclusion

References


Basics

Automata




Example automaton that accepts all binary strings containing "00"
source: [1]

Automata



Example automaton that accepts all binary strings containing an even number of "1"
source: [1]

Turing Machines



Example turing machine
source: [2]

First-Order Logic

$$\forall q \exists p \forall x, y [p > q \wedge (x, y > 1 \rightarrow xy \neq p)]$$

First-Order Logic

$$\forall q \exists p \forall x, y [p > q \wedge (x, y > 1 \rightarrow xy \neq p)]$$

"There are infinitely many prime numbers."

First-Order Logic

$$\forall q \exists p \forall x, y [p > q \wedge (x, y > 1 \rightarrow xy \neq p)]$$

"There are infinitely many prime numbers."

- *universe \mathcal{U}*
 - set of assignable variable values
 - here \mathbb{N}

First-Order Logic

$$\forall q \exists p \forall x, y [p > q \wedge (x, y > 1 \rightarrow xy \neq p)]$$
$$= \forall q \exists p \forall x, y \left[R_1(p, q) \wedge \left((R_1(x, 1) \wedge R_1(y, 1)) \rightarrow R_2(x, y, p) \right) \right]$$

"There are infinitely many prime numbers."

-
- *universe \mathcal{U}*
 - set of assignable variable values
 - here \mathbb{N}
 - *model \mathcal{M}*
 - universe with assignment of relations
 - here $(\mathbb{N}, >, (\times \neq)_3)$

First-Order Logic

$$\forall q \exists p \forall x, y [p > q \wedge (x, y > 1 \rightarrow xy \neq p)]$$

"There are infinitely many prime numbers."

- *universe* \mathcal{U}
 - set of assignable variable values
 - here \mathbb{N}
- *model* \mathcal{M}
 - universe with assignment of relations
 - here $(\mathbb{N}, >_2, (\times \neq)_3)$
- *language* $L(\mathcal{M})$
 - sentences that make sense in \mathcal{M}
 - here $L(\mathbb{N}, >_2, (\times \neq)_3)$

First-Order Logic

$$\forall q \exists p \forall x, y [p > q \wedge (x, y > 1 \rightarrow xy \neq p)]$$

"There are infinitely many prime numbers."

- *universe* \mathcal{U}
 - set of assignable variable values
 - here \mathbb{N}
- *model* \mathcal{M}
 - universe with assignment of relations
 - here $(\mathbb{N}, >_2, (\times \neq)_3)$
- *language* $L(\mathcal{M})$
 - sentences that make sense in \mathcal{M}
 - here $L(\mathbb{N}, >_2, (\times \neq)_3)$
- *theory* $\text{Th}(\mathcal{M})$
 - true sentences formed with \mathcal{M}
 - here $\text{Th}(\mathbb{N}, >_2, (\times \neq)_3)$

What Is Decidability?

Generally:

- M, N sets, $\varphi \in M$
- N decidable \coloneqq there is an algorithm that decides whether $\varphi \in N$

What Is Decidability?

Generally:

- M, N sets, $\varphi \in M$
- N decidable $:=$ there is an algorithm that decides whether $\varphi \in N$

For logic:

- \mathcal{M} model, $\varphi \in L(\mathcal{M})$
- $\text{Th}(\mathcal{M})$ decidable $:=$ there is an algorithm that decides whether φ is true in \mathcal{M}

$\text{Th}(\mathbb{N}, +)$ – A Decidable Theory

Theorem 1

$\text{Th}(\mathbb{N}, +)$ is decidable

Theorem 1

$\text{Th}(\mathbb{N}, +)$ is decidable

i.e., there is an algorithm that can decide, whether a sentence $\varphi \in L(\mathbb{N}, +)$ is true or false.

Proof of Theorem 1

Let $i \in \mathbb{N} \setminus \{0\}$ and define

$$\Sigma_i := \left\{ \begin{pmatrix} 0 \\ \vdots \\ 0 \\ 0 \end{pmatrix}, \begin{pmatrix} 0 \\ \vdots \\ 0 \\ 1 \end{pmatrix}, \begin{pmatrix} 0 \\ \vdots \\ 1 \\ 0 \end{pmatrix}, \dots, \begin{pmatrix} 1 \\ \vdots \\ 1 \\ 0 \end{pmatrix}, \begin{pmatrix} 1 \\ \vdots \\ 1 \\ 1 \end{pmatrix} \right\} \subset \{0, 1\}^i$$

and $\Sigma_0 := \{()\}$. An example for a word in Σ_2 :

$$\begin{pmatrix} 0 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} \begin{pmatrix} 1 \\ 1 \end{pmatrix} \sim \begin{pmatrix} 3 \\ 5 \end{pmatrix}$$

Proof of Theorem 1

Now, let

- $i \in \{1, \dots, l\}$
- $\varphi = Q_1 x_1 \dots Q_l x_l [\psi] \in L(\mathbb{N}, +)$ where $Q_1, \dots, Q_l \in \{\forall, \exists\}$
- $\varphi_i := Q_{i+1} x_{i+1} \dots Q_l x_l [\psi]$ and by convention $\varphi_l := \psi$

Proof of Theorem 1

Now, let

- $i \in \{1, \dots, l\}$
- $\varphi = Q_1 x_1 \dots Q_l x_l [\psi] \in L(\mathbb{N}, +)$ where $Q_1, \dots, Q_l \in \{\forall, \exists\}$
- $\varphi_i := Q_{i+1} x_{i+1} \dots Q_l x_l [\psi]$ and by convention $\varphi_l := \psi$

Also, for $a_1, \dots, a_i \in \mathbb{N}$, let $\varphi_i(a_1, \dots, a_i)$ be φ_i with all occurrences of x_j replaced by a_j for $j \in \{1, \dots, l\}$.

$\implies \varphi_l$ is only a Boolean expression.

Proof of Theorem 1

Take

- an automaton that accepts simple addition ($a + b = c$)
- an automaton that accepts boolean "and" expressions ($p \wedge q$)
- an automaton that accepts boolean "or" expressions ($p \vee q$)
- an automaton that accepts boolean "not" expressions ($\neg p$)

Proof of Theorem 1

Take

- an automaton that accepts simple addition ($a + b = c$)
- an automaton that accepts boolean "and" expressions ($p \wedge q$)
- an automaton that accepts boolean "or" expressions ($p \vee q$)
- an automaton that accepts boolean "not" expressions ($\neg p$)

Combine them (closure, union, intersection, complementation) to get the automaton A_I that accepts tuples $(a_1, \dots, a_I) \in \mathbb{N}^I$ for which $\varphi_I(a_1, \dots, a_I)$ is true.

Proof of Theorem 1

Take

- an automaton that accepts simple addition ($a + b = c$)
- an automaton that accepts boolean "and" expressions ($p \wedge q$)
- an automaton that accepts boolean "or" expressions ($p \vee q$)
- an automaton that accepts boolean "not" expressions ($\neg p$)

Combine them (closure, union, intersection, complementation) to get the automaton A_I that accepts tuples $(a_1, \dots, a_I) \in \mathbb{N}^I$ for which $\varphi_I(a_1, \dots, a_I)$ is true.

Important: There is an algorithm that constructs A_I from $\varphi_I = \psi$.

Proof of Theorem 1

If $Q_i = \exists$, construct automaton A_i from A_{i+1} by

- copying all states
- adding a new start state
- making A_i guess the right a_{i+1} indeterministically

Proof of Theorem 1

If $Q_i = \exists$, construct automaton A_i from A_{i+1} by

- copying all states
- adding a new start state
- making A_i guess the right a_{i+1} indeterministically

If else $Q_i = \forall$, use complementation twice ($\forall x_i \varphi_{i+1} = \neg \exists x_i \neg \varphi_{i+1}$)

Proof of Theorem 1

If $Q_i = \exists$, construct automaton A_i from A_{i+1} by

- copying all states
- adding a new start state
- making A_i guess the right a_{i+1} indeterministically

If else $Q_i = \forall$, use complementation twice ($\forall x_i \varphi_{i+1} = \neg \exists x_i \neg \varphi_{i+1}$)

$\Rightarrow A_i$ accepts input $(a_1, \dots, a_i) \in \mathbb{N}^i \Leftrightarrow \varphi_i$ is true

Proof of Theorem 1

If $Q_i = \exists$, construct automaton A_i from A_{i+1} by

- copying all states
- adding a new start state
- making A_i guess the right a_{i+1} indeterministically

If else $Q_i = \forall$, use complementation twice ($\forall x_i \varphi_{i+1} = \neg \exists x_i \neg \varphi_{i+1}$)

$\Rightarrow A_i$ accepts input $(a_1, \dots, a_i) \in \mathbb{N}^i \Leftrightarrow \varphi_i$ is true

$\Rightarrow A_0$ accepts input $() \Leftrightarrow \varphi_0 = \varphi$ is true

Proof of Theorem 1

If $Q_i = \exists$, construct automaton A_i from A_{i+1} by

- copying all states
- adding a new start state
- making A_i guess the right a_{i+1} indeterministically

If else $Q_i = \forall$, use complementation twice ($\forall x_i \varphi_{i+1} = \neg \exists x_i \neg \varphi_{i+1}$)

$\Rightarrow A_i$ accepts input $(a_1, \dots, a_i) \in \mathbb{N}^i \Leftrightarrow \varphi_i$ is true

$\Rightarrow A_0$ accepts input $() \Leftrightarrow \varphi_0 = \varphi$ is true

Let the algorithm return " $\varphi \in \text{Th}(\mathbb{N}, +)$ " $\Leftrightarrow A_0$ accepts input $()$

$\text{Th}(\mathbb{N}, +, \times)$ – An Undecidable Theory

Theorem 2

$\text{Th}(\mathbb{N}, +, \times)$ is undecidable

Theorem 2

$\text{Th}(\mathbb{N}, +, \times)$ is undecidable

i.e., there is no algorithm that can decide, whether a sentence $\varphi \in L(\mathbb{N}, +)$ is true or false.

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.
- There is a mapping reduction that translates
 - a Turing machine M and a string w

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.
- There is a mapping reduction that translates
 - a Turing machine M and a string w
 - to a formula $\varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ that contains only one free variable x , such that

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.
- There is a mapping reduction that translates
 - a Turing machine M and a string w
 - to a formula $\varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ that contains only one free variable x , such that
 - $\varphi_{M,w}$ is true $\Leftrightarrow x$ is a (suitably encoded) computation history of M with which M accepts w

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.
- There is a mapping reduction that translates
 - a Turing machine M and a string w
 - to a formula $\varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ that contains only one free variable x , such that
 - $\varphi_{M,w}$ is true $\Leftrightarrow x$ is a (suitably encoded) computation history of M with which M accepts w

Assume $\text{Th}(\mathbb{N}, +, \times)$ is decidable.

\Rightarrow The formulas $\exists x \varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ are decidable.

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.
- There is a mapping reduction that translates
 - a Turing machine M and a string w
 - to a formula $\varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ that contains only one free variable x , such that
 - $\varphi_{M,w}$ is true $\Leftrightarrow x$ is a (suitably encoded) computation history of M with which M accepts w

Assume $\text{Th}(\mathbb{N}, +, \times)$ is decidable.

- \Rightarrow The formulas $\exists x \varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ are decidable.
- \Rightarrow The word problem for Turing machines is decidable.

Proof Idea for Theorem 2

- The word problem for Turing machines is undecidable.
- There is a mapping reduction that translates
 - a Turing machine M and a string w
 - to a formula $\varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ that contains only one free variable x , such that
 - $\varphi_{M,w}$ is true $\Leftrightarrow x$ is a (suitably encoded) computation history of M with which M accepts w

Assume $\text{Th}(\mathbb{N}, +, \times)$ is decidable.

- \Rightarrow The formulas $\exists x \varphi_{M,w} \in \text{Th}(\mathbb{N}, +, \times)$ are decidable.
- \Rightarrow The word problem for Turing machines is decidable.
- \Rightarrow ⚡

Thinking further...

Assumptions:

A_1 Proofs can be checked by a machine.

A_2 Provable statements are true.

Thinking further...

Assumptions:

A_1 Proofs can be checked by a machine.

A_2 Provable statements are true.

Lemmas:

1. The provable statements of $\text{Th}(\mathbb{N}, +, \times)$ are Turing recognizable.

Proof idea: Just try all possible (suitably encoded) proofs.

Thinking further...

Assumptions:

A_1 Proofs can be checked by a machine.

A_2 Provable statements are true.

Lemmas:

1. The provable statements of $\text{Th}(\mathbb{N}, +, \times)$ are Turing recognizable.

Proof idea: Just try all possible (suitably encoded) proofs.

2. There is a true statement in $\text{Th}(\mathbb{N}, +, \times)$ that is not provable.

Proof idea: Contradiction to Theorem 2 by using 1.

Gödel's Incompleteness Theorem



A True, Unprovable Statement

We can construct a true statement in $\text{Th}(\mathbb{N}, +, \times)$, that is not provable.

A True, Unprovable Statement

We can construct a true statement in $\text{Th}(\mathbb{N}, +, \times)$, that is not provable.

Construction: Let M be a Turing machine that operates as follows.

- Delete the input
- Look for proof of $\neg\exists x[\varphi_{M,0}] \in \text{Th}(\mathbb{N}, +, \times)$
- Accept on proof, reject if no proof can be found

A True, Unprovable Statement

We can construct a true statement in $\text{Th}(\mathbb{N}, +, \times)$, that is not provable.

Construction: Let M be a Turing machine that operates as follows.

- Delete the input
- Look for proof of $\neg\exists x[\varphi_{M,0}] \in \text{Th}(\mathbb{N}, +, \times)$
- Accept on proof, reject if no proof can be found

$\implies \neg\exists x[\varphi_{M,0}]$ is the wanted statement.

Gödel's Method

- Construct the statement "This statement cannot be proved by the axioms."

Gödel's Method

- Construct the statement "This statement cannot be proved by the axioms."
- Argue against just adding this statement to the axiom.

Gödel's Method

- Construct the statement "This statement cannot be proved by the axioms."
- Argue against just adding this statement to the axiom.

\Rightarrow Incompleteness 😊

Conclusion

Conclusion

\Rightarrow There are (very simple) undecidable logical theories.

Conclusion

- ⇒ There are (very simple) undecidable logical theories.
- ⇒ Mathematics cannot be mechanized.

Conclusion

- ⇒ There are (very simple) undecidable logical theories.
- ⇒ Mathematics cannot be mechanized.
- ⇒ No sound logical system can be complete.

References

References

- [1] Martin Alessandro - Own work, CC BY-SA 4.0,
<https://commons.wikimedia.org/w/index.php?curid=75082873>
- [2] https://www.inf-schule.de/grenzen/berechenbarkeit/turingmaschine/station_turingmaschine
- [3] Michael Sipser: Introduction to the Theory of Computation. Thomson Course Technology, 2006
- [4] <https://www.youtube.com/watch?v=04ndIDcDSGc>
- [5] Prof. Dr. Franz Baader: Skript Theoretische Informatik und Logik (Sommersemester 2020), TU Dresden