

MODELING AND SIMULATION OF THE BOILING CRISIS  
WITHIN PWR AT CFD SCALE

LUC FAVRE

Towards Improvements of the Modeling of Wall Boiling for Multiphase CFD Simulations  
Paris, December 2022



---

## ABSTRACT

---

In Pressurized Water Reactors (PWR), the heat released by the nuclear fuel is transferred to the water flowing in the primary circuit which is pressurized at 150 bar to avoid boiling. However, water can sometimes reach the Onset of Nucleate Boiling (ONB) under accident conditions that can further lead to the Boiling Crisis. At this point, an instantaneous transition between nucleate and film boiling occurs, inducing the formation of a vapor blanket around the fuel rods which acts as a thermal insulation and causes a rapid rise of their temperature, posing a risk of fuel cladding damage. Prediction of the Critical Heat Flux (corresponding to Boiling Crisis occurrence) is thus a primal safety stake, currently achieved using dedicated experimental correlations that do not include any detailed description of the boiling physics.

This thesis aims to study the modeling of the boiling physics at a local scale, so-called “CFD” (Computational Fluid Dynamics), which allows to simulate boiling flows using a millimeter spatial discretization. The in-house code NEPTUNE\_CFD is the reference tool used by EDF RD to investigate the local-scale multiphase physics.

First, simulations of boiling flows in a vertical tube are achieved using NEPTUNE\_CFD. Results are compared to the DEBORA experiment (flow boiling of refrigerant R12 that mimics PWR dimensionless numbers) in conditions representative of the industrial situation. The results show a global agreement with the measurements but display significant discrepancies regarding bubble diameter and wall temperature. The latter is computed through the wall boiling model of NEPTUNE\_CFD called “Heat Flux Partitioning”, which splits the wall heat flux between different heat transfer mechanisms (convection, phase change, transient conduction, etc.).

The main objective of the thesis then consisted in the development of a new Heat Flux Partitioning model in order to account for a more extensive descriptions of the boiling phenomena, including notably the effect of bubble sliding. A fine modeling of bubble dynamics at the wall has been proposed thorough a mechanistic approach based on a force balance over the bubble. Forces at stake have been reassessed (drag, added mass, etc.) and allowed satisfactory prediction of bubble detachment diameter as well as sliding velocity at low and high pressure. The Heat Flux Partitioning model has been completed by conducting a precise evaluation of the numerous required closure laws (waiting time, nucleation site density, etc.) through comparisons with experimental measurements from the literature. The newly assembled model has finally been validated against wall temperature measurements and implemented in NEPTUNE\_CFD.

The Critical Heat Flux prediction is anchored as a perspective of this framework. Recent experiments showed that the Boiling Crisis can be described using physical parameters involved in the Heat Flux Partitioning formulation. A criterion based on the proportion of wall area covered by bubbles has further been tested using the old NEPTUNE\_CFD formulation and showed a coherent qualitative behavior.

Finally, the focus was put on a configuration consisting of a tube with mixing vanes similar to those present in PWR cores. Results of NEPTUNE\_CFD simulations showed significant discrepancy regarding core void fraction prediction. Single-phase flow simulations of the same case displayed an overestimation of the liquid’s rotation which could explain the too large vapor gathering at the center for the boiling cases.

**keywords :** phase change, heat transfer, fluid mechanics, multiphase flows, numerical simulations

---

## RÉSUMÉ

---

Dans un Réacteur à Eau Pressurisée (REP), la chaleur dégagée par le combustible nucléaire est transférée à l'eau du circuit primaire, pressurisée à 150 bars pour éviter son ébullition. Cependant, en situation accidentelle, elle peut entrer en régime d'ébullition nucléée pouvant s'intensifier jusqu'à atteindre la crise d'ébullition. Ce point de transition quasi-instantané entre l'ébullition nucléée et l'ébullition en film entraîne la formation d'une couche de vapeur stable sur les crayons combustible, associée à une forte augmentation de leur température pariétale créant un risque de rupture de leur gaine. La prédition du flux critique (flux de chaleur auquel se produit la crise d'ébullition) représente donc un enjeu de sûreté majeur et est actuellement réalisée à l'aide de corrélations expérimentales spécifiques à une configuration, n'incluant pas de représentation fine de la physique de l'ébullition.

Cette thèse s'intéresse à la modélisation de la physique de l'ébullition à l'échelle locale dite « CFD » (Computational Fluid Dynamics), à laquelle il est possible de réaliser des simulations d'écoulements bouillants avec une discrétisation spatiale de l'ordre du millimètre. Le code maison NEPTUNE\_CFD, proposant une description eulerienne des écoulements multiphasiques à changement de phase, est l'outil de référence de EDF RD pour investiguer ces problématiques aux échelles locales.

Dans un premier temps, des simulations d'écoulements bouillants convectifs en tube vertical sont réalisées avec NEPTUNE\_CFD. Des comparaisons avec l'expérience DEBORA (écoulement bouillant de réfrigérant R12 en similitude REP sur plusieurs adimensionnels) ont permis une évaluation du code dans des conditions similaires au cas industriel. Les résultats obtenus sont globalement en accord avec l'expérience mais présentent des écarts notables sur le diamètre des bulles et la température paroi. Cette dernière est calculée au travers du modèle d'ébullition en paroi de NEPTUNE\_CFD dit à « Partition du Flux Pariétal » (Heat Flux Partitioning), où le flux appliqué est découpé entre plusieurs mécanismes de transfert de chaleur (convection, évaporation, conduction instationnaire, etc.).

Le coeur des travaux de thèse a alors consisté en la construction d'un nouveau modèle de Partition du Flux, avec pour objectif une prise en compte plus fine de la phénoménologie de l'ébullition en considérant notamment le glissement des bulles. Une modélisation de la dynamique des bulles en paroi a été développée par une approche mécaniste décrivant les forces appliquées sur la bulle. Les formulations de certaines forces (masse ajoutée, traînée, etc.) ont été réévaluées et permettent une prédition satisfaisante des diamètres de détachement et des vitesses de glissement à basse et haute pression. Le modèle de Partition du Flux a été complété par une évaluation des nombreuses lois de fermetures requises (temps d'attente, densité de sites de nucléation, etc.) par comparaison avec des mesures expérimentales tirées de la littérature. Le nouveau modèle ainsi développé a ensuite été validé par comparaison avec des mesures de température de paroi et implémenté dans NEPTUNE\_CFD.

La prédition du flux critique s'ancre en perspective de ces développements. Des observations expérimentales récentes décrivent la crise d'ébullition à l'aide de paramètres physiques inclus dans le modèle de Partition du Flux. Un critère basé sur la proportion de surface occupée par les bulles a été testé avec l'ancien modèle de NEPTUNE\_CFD et semble proposer un comportement qualitativement cohérent.

Enfin, on s'intéresse à une configuration de type tube avec des ailettes de mélange similaires à celles présentes en cœur de REP. Les simulations NEPTUNE\_CFD montrent des écarts significatifs à l'expérience sur la prédition du taux de vide à cœur. Des simulations monophasiques montrent une surestimation de la rotation du liquide, pouvant expliquer la trop grande accumulation de vapeur dans le cas bouillant.

**mots-clés :** changement de phase, transfert de chaleur, mécanique des fluides, écoulements multiphasiques, simulations numériques

---

## PUBLICATIONS

---

Some ideas and figures have appeared previously in the following publications:

Put your publications from the thesis here. The packages `multibib` or `bibtopic` etc. can be used to handle multiple different bibliographies in your document.

---

## CONTENTS

---

I	MODELING AND SIMULATION OF BOILING FLOWS USING CFD	2
1	NEPTUNE_CFD CODE	3
1.1	Introduction . . . . .	3
1.2	Governing Equations for Turbulent Boiling Bubbly Flows . . . . .	3
1.2.1	Mass Conservation : . . . . .	4
1.2.2	Momentum Balance : . . . . .	4
1.2.3	Energy Conservation : . . . . .	4
1.3	Interfacial transfers closure laws . . . . .	4
1.3.1	Heat and mass transfers : . . . . .	4
1.3.2	Interfacial Forces : . . . . .	5
1.4	Turbulence Modeling . . . . .	6
1.5	Wall Boiling Model . . . . .	6
1.6	Wall Function for Dispersed Boiling Flows . . . . .	7
2	THE DEBORA DATABASE	8
2.1	Introduction . . . . .	8
2.2	Simulating PWR water using R12 . . . . .	8
2.2.1	Conservation of the Phase Density Ratio . . . . .	9
2.2.2	Conservation of the Weber Number . . . . .	9
2.2.3	Conservation of the Boiling Number . . . . .	10
2.2.4	Conservation of the Inlet Thermodynamic Quality . . . . .	11
2.2.5	Same Geometry . . . . .	11
2.2.6	Transposition ranges . . . . .	11
2.3	Description of the Test Section . . . . .	11
2.3.1	Geometrical Description . . . . .	11
2.3.2	Measurement Instrumentation . . . . .	12
2.4	Measurements Campaigns and Results . . . . .	14
2.4.1	Cases Nomenclature and Test Series . . . . .	14
2.4.2	Verification of Control Parameters Coherency . . . . .	15
2.4.3	Qualitative Analysis of the Experimental Results . . . . .	16
2.5	Further Verifications . . . . .	21
2.5.1	Reconstruction of the Applied Heat Flux . . . . .	21
2.5.2	Verification of Wall Temperature Measurements . . . . .	23
2.6	Conclusions . . . . .	25
3	NEPTUNE_CFD SIMULATIONS OF DEBORA CASES	27
3.1	Simulation Setup . . . . .	27
3.2	Mesh Sensitivity Study . . . . .	28
3.3	C800 Cases Simulation : Thermal Measurements . . . . .	28
3.3.1	High Subcooling Cases . . . . .	29
3.3.2	Low Subcooling Cases . . . . .	30
3.3.3	Saturated Cases . . . . .	30
3.3.4	Investigating the nucleation site density modeling $N_{sit}$ . . . . .	33
II	DEVELOPMENT OF A NEW WALL HEAT FLUX PARTITIONING MODEL	35
4	INTRODUCTION TO HEAT FLUX PARTITIONING	36
4.1	Introduction . . . . .	36
4.1.1	Empirical Approaches . . . . .	36
4.1.2	First Heat Flux Partitioning Approaches . . . . .	37
4.2	Kurul & Podowski (1990) . . . . .	38
4.3	Basu, Warrier & Dhir (2005) . . . . .	39
4.3.1	Case 1 : Bubble Sliding, $D_d < s$ . . . . .	40
4.3.2	Case 2 : Bubble Coalescence without Sliding, $D_d \geq s$ . . . . .	41
4.4	Gilman (2017) . . . . .	42

4.5	Kommajosyula (2020) . . . . .	44
4.6	Conclusion . . . . .	45
5	<b>BOILING BUBBLE DYNAMICS</b> . . . . .	46
5.1	Introduction . . . . .	47
5.1.1	Experimental Insights . . . . .	47
5.1.2	Existing Approaches . . . . .	49
5.2	Bubble Force Balance in Vertical Flow Boiling . . . . .	53
5.2.1	Introduction . . . . .	53
5.2.2	General Considerations . . . . .	54
5.2.3	Buoyancy and Contact Pressure Force . . . . .	55
5.2.4	Capillary Force . . . . .	55
5.2.5	Drag and Lift Forces . . . . .	56
5.2.6	Inertia Force . . . . .	61
5.2.7	Force Balance Summary . . . . .	63
5.2.8	Liquid Velocity . . . . .	64
5.3	Bubble Growth . . . . .	66
5.3.1	Introduction . . . . .	66
5.3.2	Heat Diffusion in Uniformly Superheated Liquid . . . . .	66
5.3.3	Microlayer Evaporation . . . . .	67
5.3.4	Bubble Growth in Subcooled Flow Boiling . . . . .	68
5.3.5	Analytic Approach of Bubble Growth in a Linear Thermal Boundary Layer . . . . .	69
5.3.6	Comparison with DNS Results . . . . .	72
5.3.7	Comparison with Experimental Measurements . . . . .	72
5.3.8	Conclusions on Bubble Growth Modeling . . . . .	75
5.4	Departure by Sliding . . . . .	75
5.4.1	Non-Dimensional Analysis . . . . .	75
5.4.2	Application to Experimental Data . . . . .	77
5.4.3	Departure Diameter Prediction . . . . .	79
5.4.4	Discussion and accounting for parameters uncertainties . . . . .	81
5.5	Sliding phase . . . . .	83
5.5.1	Modeling . . . . .	83
5.5.2	Low Pressure Sliding . . . . .	84
5.5.3	High Pressure Sliding . . . . .	84
5.5.4	Comparison of Forces in Sliding Stage . . . . .	85
5.6	Bubble Lift-Off . . . . .	86
5.6.1	Introduction . . . . .	86
5.6.2	Experimental Measurements of Lift-Off Diameter . . . . .	90
5.6.3	Influence of the Flow Boiling Conditions . . . . .	90
5.6.4	Predicting the Lift-Off with a Force Balance . . . . .	91
5.6.5	A Simple Non-Dimensional Correlation . . . . .	94
5.6.6	Conclusion on the Lift-Off . . . . .	94
5.7	Conclusion . . . . .	95
6	<b>CLOSURE LAWS AND CONSTRUCTION OF A NEW HEAT FLUX PARTITIONING MODEL</b> . . . . .	97
6.1	Introduction . . . . .	97
6.2	Single-Phase Heat Transfer Coefficient . . . . .	98
6.3	Nucleation Site Density . . . . .	100
6.3.1	Existing Correlations . . . . .	101
6.3.2	Comparison with Experimental Measurements . . . . .	103
6.4	Growth time . . . . .	104
6.5	Waiting Time . . . . .	105
6.5.1	Existing Models . . . . .	105
6.5.2	Experimental Measurements . . . . .	107
6.5.3	Evaluation of the Models . . . . .	108
6.6	Considerations on Bubble Interactions and Nucleation Sites Deactivation . . . . .	110
6.6.1	Nucleation Site Distribution . . . . .	110
6.6.2	Static Deactivation . . . . .	112
6.6.3	Static Coalescence . . . . .	113
6.6.4	Sliding Coalescence . . . . .	114

6.7	Bubble Sliding Length . . . . .	115
6.8	Single Bubble Quenching Area . . . . .	117
6.9	Assembling a New Heat Flux Partitioning . . . . .	118
6.9.1	Liquid Convective Heat Flux . . . . .	118
6.9.2	Static Coalescence Evaporation Heat Flux . . . . .	119
6.9.3	Sliding Coalescence Evaporation Heat Flux . . . . .	119
6.9.4	Quenching Heat Flux . . . . .	119
6.9.5	Vapor Convective Heat Flux . . . . .	120
6.9.6	Liquid Convection Area . . . . .	120
6.9.7	Model Summary . . . . .	120
6.10	Conclusion . . . . .	123
7	VALIDATION OF THE HEAT FLUX PARTITIONING MODEL	125
7.1	Detailed Comparison and Assessment of the Heat Flux Partitioning . . . . .	125
7.1.1	Active Nucleation Site Density . . . . .	126
7.1.2	Wait Time, Growth Time, Quenching Time and Nucleation Frequency . . . . .	126
7.1.3	Single Bubble Area and Total Bubble Area . . . . .	127
7.1.4	Flux Proportions and Wall Superheat . . . . .	127
7.2	Wall Temperature Predictions . . . . .	130
7.2.1	Kossolapov Data . . . . .	130
7.2.2	Jens-Lottes Data . . . . .	131
7.2.3	Kennel Data . . . . .	132
7.3	Validation for DEBORA Experiment . . . . .	135
7.4	Conclusions . . . . .	135
8	PERSPECTIVES TOWARDS CRITICAL HEAT FLUX PREDICTION	136
III	TOWARDS THE INDUSTRIAL GEOMETRY	137
9	PROMOTEUR	138
9.1	Boiling freon in a tube with mixing vanes : DEBORA-Promoteur experiments . . . . .	138
9.1.1	Description of the experiment . . . . .	138
9.1.2	Analysis of the Experimental Measurements . . . . .	138
9.1.3	NEPTUNE_CFD simulations of DEBORA-Promoteur cases . . . . .	138
9.2	Liquid water flow in a tube with mixing vanes : AGATE-PROMOTEUR experiment . . . . .	141
9.2.1	Description of the experiment . . . . .	141
9.2.2	NEPTUNE_CFD simulations of AGATE-Promoteur case . . . . .	141
10	CONCLUSION	144
IV	APPENDIX	145
A	DETAILS ON THE BUBBLE GROWTH CALCULATION	146
A.0.1	Case 1 : $\delta_b$ is constant . . . . .	148
A.0.2	Case 2 : $\delta_b = \sqrt{\eta_l t}$ . . . . .	148
A.0.3	Case 3 : $\delta_b = CR$ . . . . .	149
B	DETAILS ON THE BUBBLE FORCE BALANCE	150
B.1	Appendix Section Test . . . . .	151
B.2	Another Appendix Section Test . . . . .	151
	BIBLIOGRAPHY	153

---

## LIST OF FIGURES

---

Figure 2.1	Density ratio of pressurized R12 and water . . . . .	9
Figure 2.2	Weber number for R12 and water at $G = 2000 \text{ kg/m}^2/\text{s}$ and $R = 0.1 \text{ mm}$ . . . . .	10
Figure 2.3	Boiling number for R12 and water at $G = 2000 \text{ kg/m}^2/\text{s}$ . . . . .	10
Figure 2.4	Sketch of the DEBORA test section. Adapted from [31]. . . . .	12
Figure 2.5	Example of Phase Indicator Function signal . . . . .	13
Figure 2.6	Picture of the bi-optical probe with a zoom over the two optical fibers. Reproduced from [40]. . . . .	13
Figure 2.7	30G2P26W16 and 29G2P26W16 results . . . . .	17
Figure 2.8	8G2P26W16 results . . . . .	18
Figure 2.9	30G2P14W16 and 29G2P14W16 results . . . . .	19
Figure 2.10	8G2P14W16 results . . . . .	20
Figure 2.11	Interpolation profiles for cases Te66 (Table 2.5). . . . .	23
Figure 2.12	Correlations comparison with P14 cases. . . . .	24
Figure 2.13	Correlations comparison with P26 cases. . . . .	25
Figure 3.1	View of the computational domain. . . . .	27
Figure 3.2	View of the radial meshes. . . . .	28
Figure 3.3	Mesh sensitivity study for 30G2P26Te66.6 case . . . . .	29
Figure 3.4	Simulation results for cases 8G2P26W16Te31. 5& Te44.9 . . . . .	30
Figure 3.5	Simulation results for cases 8G2P26W16Te55.7 & Te61.5 . . . . .	31
Figure 3.6	Simulation results for cases 8G2P26W16Te66.6 & Te70.3 . . . . .	31
Figure 3.7	NCFD (lines) vs. Exp. (circles) - $T_L$ and $T_w$ - Cases C8G2P26W16Te44.9, Te49.6, Te66.6 and Te70.3 - Simulations using two meshes M1 (coarse) and M2 (fine). . . . .	32
Figure 3.8	NCFD (lines) vs. Exp. (circles) - $\alpha$ , $d_G$ and $U_{G,z}$ - Cases C30G2P26W16Te66.6 and Te70.6 - Simulations using two meshes M1 (coarse) and M2 (fine). . . . .	32
Figure 3.9	$N_{sit}$ correlations of Lemmert & Chawla (left) and Hibiki & Ishii (right) vs. exp. data from literature. Operation pressures are displayed. $\pm 50\%$ error bars are drawn in black. . . . .	33
Figure 3.10	NCFD results for $\alpha$ , $T_L$ and $T_w$ using Lemmert & Chawla and Hibiki & Ishii correlation. Cases 8G2P26W23Te66.6 and Te70.3, 30G2P26W23Te66.6 and 70.6. . . . .	33
Figure 4.1	Sketch of the HFP considered by Kurul & Podowski (by Manon [70]). . . . .	38
Figure 4.2	Sketch of the heat transfers zones and bubble behavior considered by Basu <i>et al.</i> . (Adapted from [4]) . . . . .	40
Figure 4.3	Heat Flux Partitioning considered by Gilman [35] (Adapted from [36]). . . . .	43
Figure 5.1	Visualization of bubble sliding at various pressures. . . . .	47
Figure 5.2	Visualization of bubble sliding thermal impact. . . . .	48
Figure 5.3	Sketch of a typical bubble lifetime in vertical flow boiling. Left depicts a typical side view of the heater with identification of departure, sliding and lift-off. Right depicts a top view of the heater, exhibiting the area that will undergo transient heat transfer. . . . .	48
Figure 5.4	Sketch of the forces applied to the bubble facing an upward flow $\overline{U}_L$ and sliding at velocity $\overline{U}_b$ . . . . .	54
Figure 5.5	Physical situation considered by Shi <i>et al.</i> [96]. . . . .	57
Figure 5.6	Drag correction from Shi <i>et al.</i> [96]. . . . .	58
Figure 5.7	$C_L$ computed using Shi <i>et al.</i> correlation. . . . .	60
Figure 5.8	Values of the computed added mass coefficients in Eq. 5.63 and 5.65. . . . .	63
Figure 5.9	Microlayer appearing beneath the bubble in DNS conducted by and adapted from Urbano <i>et al.</i> [109]. . . . .	67
Figure 5.10	Studied geometry . . . . .	70
Figure 5.11	Comparison with DNS results of Urbano <i>et al.</i> [108] ( $\delta = 3\text{mm}$ and $\theta = 50^\circ$ ). Lines : Model predictions - Markers : DNS . . . . .	72
Figure 5.12	Comparison with experimental measurements of Maity [69]. . . . .	73

Figure 5.13	Comparison with experimental measurements of Kossolapov [57]. $\Delta T_w$ values are recalculated from analytical growth profiles fitted by the author. . . . .	74
Figure 5.14	Regime map regarding departure by sliding. Boundaries plotted for water at 1 bar and $D_d = 0.5\text{mm}$ . ( $K = 2$ ) . . . . .	76
Figure 5.15	Regime map plotted for water at different pressures and bubble departure diameters. ( $K = 2$ ) . . . . .	77
Figure 5.16	Regime map for R12 as simulating fluid for PWR. $D_d = 0.05\text{mm}$ is chosen according to R12 measurements from Garnier <i>et al.</i> [31] who observed bubbles of $\sim 0.1\text{mm}$ diameter after lift-off. The same value is taken for water. ( $K = 2$ ) . . .	77
Figure 5.17	Regime maps for each water data sets from Table ?? . . . . .	79
Figure 5.18	Predicted bubble departure diameters. $\pm 50\%$ error bars are indicated. . . . .	81
Figure 5.19	Initially assumed, real and reassessed bubble shape for Sugrue cases (picture adapted from [100]). . . . .	82
Figure 5.20	Proposed model performance while accounting for contact angle uncertainties . .	83
Figure 5.21	Bubble sliding velocity predictions on Maity cases . . . . .	85
Figure 5.22	Bubble sliding length predictions on Kossolapov cases - $P = 20\text{ bar}$ . . . . .	86
Figure 5.23	Bubble sliding length predictions on Kossolapov cases - $P = 40\text{ bar}$ . . . . .	87
Figure 5.24	Amplitude of each force during sliding . . . . .	87
Figure 5.25	Visualization of bubble lift-off in horizontal boiling conducted by and adapted from Maity [69]. The detachment the the bubble base from the surface is clear in the last frame. . . . .	88
Figure 5.26	Visualization of bubble lift-off in vertical boiling. The moment when bubble leaves the surface appears less clearly than for horizontal boiling. . . . .	88
Figure 5.27	Visualization of boiling surfaces in vertical boiling, where single bubble lift-off is not systematically observed. . . . .	89
Figure 5.28	Evolution of $D_{lo}/L_c$ depending on the flow conditions. . . . .	92
Figure 5.29	Prediction of Eq. 5.113 versus data from Table 5.5. Value of $K = 0.24$ was used and only converged points are presented. . . . .	93
Figure 5.30	Comparison of simple direct correlations with data from Table 5.5 . . . . .	95
Figure 6.1	Predictive capability of wall temperature by single-phase heat transfer correlations. $\pm 3K$ error bars indicated. . . . .	99
Figure 6.2	Predictive capability of wall temperature by NCFD law and Gnielinski correlation including corrections. $\pm 3K$ error bars indicated (dashed lines). . . . .	100
Figure 6.3	HSV Visualization of bubble density at various pressures adapted from Kossolapov [57] (left to right: 1.01 bar, 3 bar, 19.8 bar, 75.8 bar). . . . .	101
Figure 6.4	Sketch of the link between bubble contact angle and wettability / cavity flooding	102
Figure 6.5	Predictions of the chosen models against the experimental data of Table 6.3 with $\pm 50\%$ error bars. The contact angles . . . . .	103
Figure 6.6	Evolution of the wait time values with the wall Jakob number. . . . .	107
Figure 6.7	Evolution of the product $t_w \times f$ with the reduced Jakob number. . . . .	108
Figure 6.8	Predictions using the correlations. $\pm 50\%$ dashed lines are represented. . . . .	109
Figure 6.9	Yeoh <i>et al.</i> formulation of $t_w$ with Han & Griffith cavity radius. $\pm 50\%$ dashed lines are represented. . . . .	109
Figure 6.10	Nucleation site distribution by and adapted from Kossolapov [57]. Red circles represent the active sites positions with diameter increasing with the site's nucleation frequency. . . . .	110
Figure 6.11	Examples of experimental nucleation sites distribution in flow boiling. . . . .	111
Figure 6.12	Sketch of the geometrical overlapping leading to static deactivation. Bubbles in red can not be accommodated on the surface due to their site laying below an existing bubble. . . . .	112
Figure 6.13	Static deactivation correction tested with Hibiki & Ishii and Li <i>et al.</i> correlations for water at 40 bar, $f = 200\text{ Hz}$ , $t_{g,d} = 0.1\text{ ms}$ , $\theta = 80^\circ$ and $R_d = 0.01\text{ mm}$ . . .	113
Figure 6.14	Sketch of the static coalescence phenomenon. . . . .	114
Figure 6.15	Static coalescence probability with corrected Li <i>et al.</i> for water at 40 bar, $f = 200\text{ Hz}$ , $t_{g,d} = 0.1\text{ ms}$ and $\theta = 80^\circ$ . . . . .	114
Figure 6.16	Comparison of sliding distance estimations with Kossolapov measurements [57]. NSD was estimated using Li <i>et al.</i> correlation (Eq. 6.11). . . . .	116

Figure 6.17	Quenching area shape depending on the relation between $R_d$ , $R_{lo}$ and $l_{sl}$ , if the bubble do not experience multiple coalescence while sliding. . . . .	117
Figure 6.18	Sketch of all the considered heat transfers for the new HFP model. . . . .	118
Figure 7.1	Comparison of active nucleation site density with and without a correction for Li <i>et al.</i> formulation. . . . .	126
Figure 7.2	Comparison of bubble nucleation frequency, wait time, average growth time and quenching time. . . . .	127
Figure 7.3	Comparison of average area visited by a bubble and total wall fraction area impacted by bubbles (footprint or transient conduction). . . . .	128
Figure 7.4	Bubble radiiuses, sliding length and distances between sites. . . . .	128
Figure 7.5	Comparison of the resulting heat flux partitioning along with the boiling curve. .	129
Figure 7.6	Comparison with measured boiling curves from Kossolapov [57]. $\Delta T_L = 10^\circ\text{C}$ and $G_L = 1000 \text{ kg/m}^2/\text{s}$ . . . . .	131
Figure 7.7	Wall temperature predictions achieved by the different HFP models on Kossolapov data. . . . .	131
Figure 7.8	Comparison with measured boiling curve by Jens & Lottes [48]. $P = 138 \text{ bar}$ , $G = 2600 \text{ kg/m}^2/\text{s}$ , $\Delta T_L = 64^\circ\text{C}$ . . . . .	132
Figure 7.9	Wall temperature predictions achieved by the different HFP models on Jens data. .	133
Figure 7.10	Wall temperature predictions achieved by the different HFP models on Kennel data. .	134
Figure 9.1	Picture of the mixing device (left) and its fine meshing (right). . . . .	138
Figure 9.2	Experimental results from the 48G3P26W23 series. . . . .	139
Figure 9.3	Experimental results from the 52G3P26W23 series. . . . .	139
Figure 9.4	Experimental results from the 52G3P26W27 series. . . . .	139
Figure 9.5	Relative difference of interference frequency for the two probes. . . . .	140
Figure 9.6	Average relative importance of radial velocity to axial velocity in AGATE experiment	140
Figure 9.7	Estimation of bubble diameter on C5200 measurements series. . . . .	140
Figure 9.8	NCFD (lines) vs. Exp. (circles) - $\alpha$ profiles for two MV positions ( $23.5D_h$ in blue, $10D_h$ in orange) - $T_{in} = 65^\circ\text{C}$ (left), $T_{in} = 69^\circ\text{C}$ (middle), $T_{in} = 75^\circ\text{C}$ (right) - Simulations using two meshes M1 (coarse) and M2 (fine) for $T_{in} = 69^\circ\text{C}$ . . . . .	141
Figure 9.9	NCFD vs. Exp. - Top & Middle : Radial velocity and turbulent RMS ( $z = 30\text{mm}$ & $z = 440\text{mm}$ ) - Bottom : Axial velocity and turbulent RMS ( $z = 440\text{mm}$ ). . . . .	142
Figure A.1	Studied geometry . . . . .	146

---

## LIST OF TABLES

---

Table 2.1	Water R12 scaling, $R = 0.01\text{mm}$ for $\text{We}$	11
Table 2.2	Test matrix of the DEBORA cases. $\bigcirc$ : C800 - $\nabla$ : C2900 - $\triangle$ : C3000	14
Table 2.3	Recalculated control parameters for the 30G2P14W16 cases. ( $T_{sat} = 58.07^\circ\text{C}$ )	16
Table 2.4	Recalculated control parameters for the 30G2P26W16 cases. ( $T_{sat} = 86.81^\circ\text{C}$ )	16
Table 2.5	Similar conditions cases between the C3000 and C800 campaigns. Outlet quality calculated with Eq. 2.9	22
Table 2.6	Heat flux recalculation results	22
Table 3.1	Mesh parameters	28
Table 5.1	Summary of the presented correlations	52
Table 5.2	Summary of different force-balance mechanistic approaches.	64
Table 5.3	Bubble departure diameters data sets in vertical flow boiling	78
Table 5.4	Average relative error reached by the models.	83
Table 5.5	Bubble lift-off diameters data sets in vertical flow boiling	91
Table 6.1	Experimental data range of wall temperature measurements from the single-phase part of boiling curves. $N_{mes}$ is the number of measurements of each data set.	98
Table 6.2	Average errors achieved by the considered models on each data sets.	100
Table 6.3	Nucleation Site Density data in flow boiling	103
Table 6.4	Bubble wait time data in vertical flow boiling. Wall superheat values for Richen-derfer data are estimated using Frost & Dzakowic correlation (Eq. 5.107).	107
Table 6.5	Summary of the HFP model closure laws	122
Table 6.6	Summary of the HFP model formulation	123
Table 7.1	Experimental data range of wall temperature measurements in the boiling region.	130
Table 7.2	Wall superheat values obtained with different models versus the measurements on DEBORA case at 26.6 bar	135
Table B.1	Autem usu id	151

---

## LISTINGS

---

Listing B.1	A floating example ( <code>listings</code> manual)	152
-------------	--	-----

---

## NOMENCLATURE

---

### Acronyms

BC	Boiling Crisis
CHF	Critical Heat Flux
DNS	Direct Numerical Simulations
HFP	Heat Flux Partitioning
PWR	Pressurized Water Reactor
RPE	Rayleigh-Plesset Equation
SMR	Small Modular Reactor

### Greek symbols

$\eta$	Thermal diffusivity [m <sup>2</sup> /s]
$\gamma$	Shear rate [s <sup>-1</sup> ]
$\lambda$	Thermal conductivity [W/m/K]
$\mu$	Dynamic viscosity [J.s/m <sup>-3</sup> ]
$\nu$	Kinematic viscosity [m <sup>2</sup> /s]
$\phi$	Heat flux [J/m <sup>2</sup> /s]
$\rho$	Density [kg/m <sup>3</sup> ]
$\sigma$	Surface tension [J/m <sup>2</sup> ]
$\theta, d\theta$	Contact angle and half-hysteresis [° or rad]
$\theta_i$	Bubble inclination angle [° or rad]

### Latin symbols

$C$	Force coefficient [-]
$D$	Bubble diameter [m]
$D_h$	Hydraulic diameter [m]
$E$	Kinetic energy [J]
$F$	Force [N]
$G$	Mass flux [kg/m <sup>2</sup> /s]
$g$	Gravity acceleration [m <sup>2</sup> /s]
$h_{LV}$	Latent heat of vaporization [J/kg]
$K$	Bubble growth constant [-]
$L_c = \sqrt{\frac{\sigma}{(\rho_L - \rho_V)g}}$	Capillary length [m]
$l_{sl}$	Bubble sliding length [m]
$R$	Bubble radius [m]

$R_c$	Bubble curvature radius [m]
$r_w$	Bubble foot radius [m]
$T$	Temperature [K]
$U$	Velocity [m/s]
$U_\tau$	Wall friction velocity [m/s]
$U_{rel} = U_L - U_b$	Relative velocity [m/s]
$V$	Volume [ $\text{m}^3$ ]

### Non-dimensional numbers

$\text{Ca} = \frac{\mu_L U_L}{\sigma}$	Capillary number [-]
$\text{Eo} = \frac{(\rho_L - \rho_V)gR^2}{\sigma}$	Eotvos number [-]
$\text{Fr} = \frac{\rho_L U_L^2}{(\rho_L - \rho_V)gR}$	Froude number [-]
$\text{Ja} = \frac{\rho_L c_{P,L}  T - T_{sat} }{\rho_V h_{LV}}$	Jakob number [-]
$\text{Pr} = \frac{\nu}{\eta}$	Prandtl number [-]
$\text{Re}_b = \frac{U_{rel} D_b}{\nu_L}$	Bubble Reynolds number [-]
$\text{Re}_{D_h} = \frac{G_L D_h}{\mu_L}$	Liquid bulk Reynolds number [-]
$\text{Sr} = \frac{2\gamma R}{ U_{rel} }$	Non-dimensional shear rate [-]
$y^+ = \frac{y U_\tau}{\nu_L}$	Non-dimensional wall distance [-]

### Subscripts

$AM$	Added-Mass
$b$	Bubble
$D$	Drag
$d$	Departure or Downstream
$L$	Liquid or Lift
$lo$	Lift-off
$sat$	Saturation
$u$	upstream
$V$	Vapor
$w$	Wall

### ACRONYMS

CFD	Computational Fluid Dynamics
CMFD	Computational Multi-Fluid Dynamics
NCFD	NEPTUNE_CFD
DNS	Direct Numerical Simulation

NSD Nucleation Site Density

---

## NOMENCLATURE

---

$N_{sit,0}$  Nucleation Site Density computed by correlation [m<sup>-2</sup>]

---

## INTRODUCTION

---

To write :

- nuclear in france
- progressive zoom toward the primary circuit and nuclear fuel assembly
- heat transfer and boiling
- CHF issue
- Modeling, component approach, THYC
- New approaches, CFD, objective of the thesis

## Part I

### MODELING AND SIMULATION OF BOILING FLOWS USING CFD

---

NEPTUNE\_CFD CODE

---

**Contents**


---

1.1	Introduction	3
1.2	Governing Equations for Turbulent Boiling Bubbly Flows	3
1.2.1	Mass Conservation :	4
1.2.2	Momentum Balance :	4
1.2.3	Energy Conservation :	4
1.3	Interfacial transfers closure laws	4
1.3.1	Heat and mass transfers :	4
1.3.2	Interfacial Forces :	5
1.4	Turbulence Modeling	6
1.5	Wall Boiling Model	6
1.6	Wall Function for Dispersed Boiling Flows	7

---

**1.1 INTRODUCTION**

The NEPTUNE\_CFD project (started in 2001) is a research program coordinated by four entities : EDF, CEA, IRSN and Framatome. The initial goals of the project were related to nuclear safety by developing a thermal-hydraulics simulation tool to :

- Predict the Boiling Crisis in PWR cores ;
- Study the Loss Of Coolant Accident (LOCA) to predict fuel rod cladding temperature.

The code consists of a local three-dimensional modeling based on a two-fluid one pressure approach combined with mass, momentum and energy conservation equations for each phase[guelfi2007].  
is an eulerian multiphase CFD solver co-developed

The constitutive equations are solved using a pressure correction, and is based on a finite-volume discretization along with a collocated arrangement of the variables. Moreover, NEPTUNE\_CFD allows the use of all type of meshes (hexahedra, tetrahedra, pyramids, etc.), even non-conforming ones, thanks to its face-based data structure. Finally, the code is well-suited for parallel computing, widening its computing capacity to very large meshes.

The simulations presented in this thesis have all been conducted using the NEPTUNE\_CFD 7.0 modeling framework for dispersed bubbly flows. In the next sections, we will detail the constitutive equations and closures laws of the code for the simulation of boiling bubbly flows.

**1.2 GOVERNING EQUATIONS FOR TURBULENT BOILING BUBBLY FLOWS**

To simulate two-phase dispersed boiling flows, NEPTUNE\_CFD solves the ensemble-averaged equations of mass conservation, momentum balance and energy conservation for each phase :

### 1.2.1 Mass Conservation :

$$\frac{\partial \alpha_k \rho_k}{\partial t} + \bar{\nabla} \cdot (\alpha_k \rho_k \bar{U}_k) = \Gamma_k \quad (1.1)$$

Where  $\alpha_k$ ,  $\rho_k$ ,  $\bar{U}_k$  are the time fraction, average density and velocity of phase  $k$ ;  $\Gamma_k = \Gamma_{k,i} + \Gamma_{k,w}$  the interfacial mass transfer term per unit of volume and time splitted between bulk and wall contribution. Subscripts  $k = L$  or  $V$  denotes the liquid or vapor phase,  $i$  the interfacial quantities and  $w$  the wall contribution.

### 1.2.2 Momentum Balance :

$$\frac{\partial \alpha_k \rho_k \bar{U}_k}{\partial t} + \bar{\nabla} \cdot (\alpha_k \rho_k \bar{U}_k \otimes \bar{U}_k) = -\alpha_k \bar{\nabla} (P) + \bar{F}_{k,i} + \Gamma_k \bar{U}_{k,i} + \alpha_k \rho_k \bar{g} + \bar{\nabla} \cdot (\alpha_k (\bar{\tau}_{k,m} + \bar{\tau}_{k,T})) \quad (1.2)$$

Where  $P$  is the pressure,  $\bar{g}$  the gravity,  $\bar{F}_{k,i}$  the interfacial forces accounting for momentum transfer between phases per unit of volume and time,  $\bar{U}_{k,i}$  the interfacial velocity,  $\bar{\tau}_{k,m}$  and  $\bar{\tau}_{k,T}$  respectively the viscous and turbulent (or Reynolds) stress tensor. Subscript  $m$  and  $T$  respectively denote the molecular (or laminar) and turbulent terms.

### 1.2.3 Energy Conservation :

$$\begin{aligned} \frac{\partial \alpha_k \rho_k H_k}{\partial t} + \bar{\nabla} \cdot (\alpha_k \rho_k H_k \bar{U}_k) &= \frac{\partial \alpha_k P}{\partial t} + \Gamma_k H_{k,i} + \bar{F}_{k,i} \cdot \bar{U}_k + Q_{k,I} + \bar{\nabla} \cdot (\alpha_k (\bar{\tau}_k + \bar{\tau}_{k,T}) \cdot \bar{U}_k) \\ &\quad + \bar{\nabla} \cdot (\alpha_k (-(\lambda_{k,m} + \lambda_{k,T}) \bar{\nabla} (T_k))) + \alpha_k \rho_k \bar{g} \cdot \bar{U}_k + Q_{k,w} \end{aligned} \quad (1.3)$$

Where  $H_k = e_k + \frac{U_k^2}{2} + \frac{P}{\rho_k} = h_k + \frac{U_k^2}{2}$  is the total enthalpy of phase  $k$ ,  $H_{k,i}$  the interfacial-averaged enthalpy,  $Q_{k,i}$  the interfacial heat flux per unit of volume and time,  $\lambda_{k,m}$  and  $\lambda_{k,T}$  respectively being the laminar and turbulent thermal conductivity,  $T_k$  the temperature,  $Q_{k,w}$  the heat flux from the wall to phase  $k$  per unit of volume and time.

However, this ensemble-average approach requires a given number of closure laws since this mathematical operation removes most of the information about smaller scales physics such as interfacial exchanges between phases or wall-fluid interaction. Terms for which this modeling effort is needed are colored in orange in equations 1.1, 1.2 and 1.3. The chosen expressions for those terms are detailed in subsections 1.3, 1.4 and ??.

## 1.3 INTERFACIAL TRANSFERS CLOSURE LAWS

The interfacial transfers of mass, momentum and energy are respectively noted in equations 1.1, 1.2 and 1.3 :  $\Gamma_k$ ,  $\bar{F}_{k,i}$  and  $Q_{k,i}$ .

### 1.3.1 Heat and mass transfers :

The mass transfer term, can be written as :  $\Gamma_{L,i} + \Gamma_{G,i} = 0$ ,  $\Gamma_{L,w} + \Gamma_{G,w} = 0$  with  $\Gamma_{G,w} \geq 0$  in the case of boiling flows. This finally gives  $\Gamma_L = -\Gamma_G$ .

The interfacial heat flux  $Q_{k,i}$  can be rewritten in terms of interfacial area concentration  $a_i$  :  $Q_{k,i} = q''_{k,i} a_i$ . Neglecting the mechanical contribution compared to the thermal terms, the energy jump condition can then be expressed as :

$$\sum_{k=L,G} \left( \Gamma_{k,i} h_{k,i} + q''_{k,i} a_i \right) = 0 \quad (1.4)$$

The estimation of  $h_{k,i}$  is not straightforward since it can either be supposed to be the saturation enthalpy of phase  $k$  at the system pressure (H1) or  $h_{k,i}$  can be identified to the phase-averaged enthalpy (H2). In NEPTUNE\_CFD, the assumption H2 is chosen, thus giving the bulk condensation rate :

$$\Gamma_{L,i} = \frac{a_i (q''_{L,i} + q''_{G,i})}{h_{G,sat} - h_{L,sat}} \quad (1.5)$$

The interfacial heat flux densities  $q''_{k,i}$  and interfacial area concentration  $a_i$  are expressed as  $q''_{k,i} = C_{k,i} (T_{sat}(P) - T_k)$  and  $a_i = 6\alpha_G/d_G$ ,  $d_G$  being the gas phase Sauter mean bubble diameter. The interfacial area is computed using the transport equation of RUYER & SEILER [ruyer2009]. For subcooled liquid, the following heat transfer coefficient is used [manon2000]:

$$C_{L,i} = \frac{Nu_L \lambda_L}{d_G} \text{ and } Nu_L = 2 + 0.6 Re^{1/2} Pr_L^{1/3} \quad (1.6)$$

Where  $Re$  is the bubble Reynolds number  $Re = ||\bar{U}_G - \bar{U}_L|| d_G / \nu_L$  and  $Pr_L$  the liquid Prandtl number  $Pr_L = \nu_L / \eta_L$  with  $\nu_L$  and  $\eta_L$  respectively being the liquid kinematic viscosity and thermal diffusivity. On the other hand, if the liquid is overheated, the maximum of three heat transfer coefficients accounting for different heat transfer mechanisms is taken [berne1983]:

$$C_{L,i} = \max(C_{L,i,1}; C_{L,i,2}; C_{L,i,3}) \quad (1.7)$$

With  $C_{L,i,n} = \lambda_L Nu_{L,n} / d_G$  and :

$$Nu_1 = \sqrt{\frac{4}{\pi} Pe} ; Nu_2 = 2 ; Nu_3 = \frac{12}{\pi} Ja \quad (1.8)$$

where  $Pe = ||\bar{U}_G - \bar{U}_L|| d_G / \eta_L$  is the Peclet number and  $Ja = \rho_L c_{p,L} |T_{sat} - T_L| / (\rho_g h_{lg})$  the Jakob number, with  $h_{lg}$  the latent heat of vaporization. Those three Nusselt numbers respectively correspond to convection heat transfer, stationary conduction and transient conduction.

For the gas phase, a simple law that ensures that the vapor temperature remains close to the saturation temperature is used (which is expected for small bubbles, *e.g.* in a PWR) :

$$C_{G,i} a_i = \frac{\alpha_G \rho_v c_{p,G}}{t_c} \quad (1.9)$$

where  $c_{p,G}$  is the gas heat capacity at constant pressure, and  $t_c$  a characteristic (relaxation) time given by the user (default value being  $t_c = 0.01s$ ) .

### 1.3.2 Interfacial Forces :

The interfacial momentum transfer (excluding transfer associated to transfer of mass  $\Gamma_k$ ) is assumed to be composed of 4 different forces being the, drag  $D$ , the added mass  $AM$ , the lift  $L$  and the turbulent dispersion  $TD$  :

$$\overline{F_{k,i}} = \overline{F_{k,D}} + \overline{F_{k,AM}} + \overline{F_{k,L}} + \overline{F_{k,TD}} \quad (1.10)$$

The turbulent dispersion force  $\overline{F_{k,TD}}$  originates from the averaging operation conducted on the three other forces' expressions, detailed in equations 1.11, 1.15, 1.16 and 1.18.

$$\overline{F_{G,D}} = -\overline{F_{L,D}} = -\frac{1}{8} a_i \rho_L C_D ||\bar{U}_G - \bar{U}_L|| (\bar{U}_G - \bar{U}_L) \quad (1.11)$$

$$C_D = \frac{2}{3} D_b \sqrt{\frac{g(\rho_L - \rho_V)}{\sigma}} \left( \frac{1 + 17.67 f(\alpha)^{1.67}}{18.67 f(\alpha)} \right), \quad f(\alpha) = (1 - \alpha)^{1.5} \text{ for distorted bubbles.} \quad (1.12)$$

$$C_D = \frac{8}{3} (1 - \alpha)^2 \text{ for churn-turbulent regime.} \quad (1.13)$$

$$\overline{F_{G,AM}} = -\overline{F_{L,AM}} = -C_{AM} \frac{1 + 2\alpha_G}{1 - \alpha_G} \alpha_G \rho_L \quad (1.14)$$

$$\times \left[ \left( \frac{\partial \bar{U}_G}{\partial t} + \bar{\nabla}(\bar{U}_G) \cdot \bar{U}_G \right) - \left( \frac{\partial \bar{U}_L}{\partial t} + \bar{\nabla}(\bar{U}_L) \cdot \bar{U}_L \right) \right] \quad (1.15)$$

with  $C_{AM} = \frac{1}{2}$ .

$$\overline{F_{G,L}} = -\overline{F_{L,L}} = -C_L \alpha_G \rho_L (\bar{U}_G - \bar{U}_L) \wedge (\bar{\nabla} \wedge \bar{U}_L) \quad (1.16)$$

$$C_L = \begin{cases} \min(0.288\tanh(0.121\text{Re}_b) ; 0.00105\text{Eo}_H^3 - 0.0159\text{Eo}_H^2 - 0.0204\text{Eo}_H + 0.474), & \text{if } \text{Eo}_H < 4 \\ 0.00105\text{Eo}_H^3 - 0.0159\text{Eo}_H^2 - 0.0204\text{Eo}_H + 0.474, & \text{if } 4 \leq \text{Eo}_H \leq 10 \\ -0.27, & \text{if } \text{Eo}_H > 10 \end{cases} \quad (1.17)$$

$$\overline{F_{G,TD}} = -\overline{F_{L,TD}} = -\frac{2}{3}\alpha_L\alpha_G C_{TD}\bar{\nabla}(\alpha_G) \quad (1.18)$$

with  $C_D$ ,  $C_{AM}$ ,  $C_L$  and  $C_{TD}$  the associated forces coefficients, respectively taken from ISHII[**ishii1967**], ZUBER[**zuber1964**], TOMIYAMA[**tomiyama2002**] and the Generalized Turbulent Dispersion model (GTD) from LAVIEVILLE *et al.* [**lavieville2017**].

#### 1.4 TURBULENCE MODELING

$$\frac{\partial R_{ij}}{\partial t} + U_k \frac{\partial R_{ij}}{\partial x_k} = \quad (1.19)$$

$$\frac{\partial \bar{R}}{\partial t} + \bar{U}_k \cdot \bar{\nabla}(R_{ij}) = \quad (1.20)$$

For bubbly flow simulations, only liquid phase turbulence is taken into account. The prescribed model is the Reynolds Stress Model (RSM)  $R_{ij} - \varepsilon$  SSG from SPEZIALE, SARKAR and GATSKI[**speziale1991**] adapted to two-phase boiling flows by MIMOUNI *et al.* [**mimouni2011**].

$$\frac{\partial R_{ij}}{\partial t} + U_k \frac{\partial R_{ij}}{\partial x_k} = -R_{ik} \frac{\partial U_j}{\partial x_k} \quad (1.21)$$

#### 1.5 WALL BOILING MODEL

The modeling of the heterogeneous boiling phenomenon at the wall is based on a Heat Flux Partitioning (HFP) model, inspired by KURUL & PODOWSKI original work[**kurul1990**] who divided the wall heat flux density  $\phi_w$  in three terms :

- A single phase convective heat flux  $\phi_{c,L}$  heating the liquid through the fraction of the wall area unaffected by the vapor bubbles
- A vaporization heat flux  $\phi_e$  which accounts for the generation of vapor through heterogeneous nucleation
- A quenching heat flux  $\phi_q$  to represent the thermal impact of bubbles departing from the wall and being replaced by cool liquid

A fourth flux is added to this HFP in NEPTUNE\_CFD, following MIMOUNI *et al.* [**mimouni2016**] who consider a convective heat flux heating the vapour  $\phi_{c,G}$  when the wall area is covered by a dense accumulation of bubbles.

The model thus gives Equation 1.22 :

$$\phi_w = \phi_{c,L} + \phi_e + \phi_q + \phi_{c,G} \quad (1.22)$$

The convective heat fluxes are expressed as  $\phi_{c,k} = A_k h_{k,\log} (T_w - T_k)$  with :

$$h_{k,\log} = \rho_k c_{p,k} u^* / T_L^+ \quad (1.23)$$

where  $A_k$  the fraction of the wall area facing phase  $k$ ,  $T_w$  the wall temperature and  $h_{k,\log}$  the wall logarithmic convective heat transfer coefficient to phase  $k$  based on the wall functions for friction velocity  $u^*$  and non-dimensional liquid temperature  $T_L^+$  described in 1.6.

The vaporization heat flux is computed following  $\phi_e = N_{sit} f \rho_G h_{lg} \pi d_d^2 / 6$  with :

- $N_{sit}$  the nucleation site density modeled as [lemmert1977] :  $N_{sit} = [210 (T_w - T_{sat})]^{1.8}$

- $f$  the bubble detachment frequency expressed as [cole1960] :  $f = \sqrt{\frac{4}{3} \frac{g|\rho_v - \rho_l|}{\rho_l d_d}}$
- $d_d$  the bubble detachment diameter given by Unal correlation[unal1976] corrected by Borée *et al.* [ref] (Equation 1.24)

$$d_d = 2.42 \times 10^{-5} P^{0.709} \frac{a}{\sqrt{b\varphi}} \text{ with } a = \frac{(T_w - T_{sat}) \lambda_w}{2\rho_G h_{lg} \sqrt{\pi \eta_w}} \text{ and } b = \begin{cases} \frac{T_{sat} - T_L}{2(1 - \rho_G/\rho_L)}, & \text{if } St \leq 0.0065 \\ \frac{1}{2(1 - \rho_G/\rho_L)} \frac{\phi_{c,L} + \phi_e + \phi_q}{0.0065 \rho_L c_{p,L} \|\bar{U}_L\|}, & \text{if } St > 0.0065 \end{cases} \quad (1.24)$$

where  $\lambda_w$  and  $\eta_w$  are the wall thermal conductivity and diffusivity,  $St = \frac{\phi_{c,L} + \phi_e + \phi_q}{\rho_L c_{p,L} \|\bar{U}_L\| (T_{sat} - T_L)}$  is the

Stanton number and  $\varphi = \max \left( 1; \left( \frac{\|\bar{U}_L\|}{U_0} \right)^{0.47} \right)$  with  $U_0 = 0.61 \text{ m/s}$

Finally, the quenching heat flux follows the approach of DEL VALLE & KENNING[delvalle1985] supposing that it follows a semi-infinite transient conduction regime :  $\phi_q = A_G t_q f \frac{2\lambda_L (T_w - T_L)}{\sqrt{\pi \eta_L t_q}}$  where  $t_q$  is the quenching time, supposed to be equal to  $1/f$ .

## 1.6 WALL FUNCTION FOR DISPERSED BOILING FLOWS

In boiling flows, the formation of bubbles at the wall may disturb the liquid velocity profile in the boundary layer. To take this phenomena into account, MIMOUNI *et al.* [mimouni2016] proposed a wall function for boiling flows which tends to the single-phase formulation when  $\alpha_G \rightarrow 0$  and depends on the bubble diameter and density at the wall :

$$u^+ = \frac{1}{\kappa} \ln(y^+) + B - \Delta u^+ \text{ with } \Delta u^+ = \begin{cases} 0 & \text{if } k_r^+ \leq 11.3 \\ \frac{1}{\kappa} \ln(1 + C_{kr} k_r^+) & \text{if } k_r^+ > 11.3 \end{cases} \quad (1.25)$$

where  $\kappa=0.41$  is the Von Karman constant,  $B = 5.3$  the standard single-phase logarithmic law constant.  $\Delta u^+$  represents the offset of  $u^+$  due to the wall roughness induced by the presence of bubble. We have  $C_{kr} = 0.5$  and  $k_r = \frac{k_r \sqrt{u^* u_T}}{\nu_L}$  the "roughness Reynolds number" with  $u_T = C_\mu^{1/4} \sqrt{k_L}$  defined from the  $k - \varepsilon$  constant  $C_\mu = 0.09$  and  $k_L$  the liquid turbulent kinetic energy. Finally,  $k_r = \alpha_G d_G$ . The non-dimensional wall liquid temperature  $T_L^+$  is modeled according to LEDUC[leduc1995]:

$$T_L^+ = \begin{cases} Pr_L y^+, & \text{if } y^+ \leq 13.2 \\ 8.67 Pr_{L,T} \left( \frac{Pr_L}{Pr_{L,T}} - 1 \right) \left( \frac{Pr_{L,T}}{Pr_L} \right)^{0.25} + \frac{Pr_{L,T}}{\kappa} \ln(Ey^+) & \text{if } y^+ > 13.2 \end{cases} \quad (1.26)$$

With  $Pr_{L,T} = 0.9$  the turbulent liquid Prandtl number, and  $E = 7.76$  a constant for smooth walls.

# 2

---

## THE DEBORA DATABASE

---

### Contents

---

2.1	Introduction . . . . .	8
2.2	Simulating PWR water using R12 . . . . .	8
2.2.1	Conservation of the Phase Density Ratio . . . . .	9
2.2.2	Conservation of the Weber Number . . . . .	9
2.2.3	Conservation of the Boiling Number . . . . .	10
2.2.4	Conservation of the Inlet Thermodynamic Quality . . . . .	11
2.2.5	Same Geometry . . . . .	11
2.2.6	Transposition ranges . . . . .	11
2.3	Description of the Test Section . . . . .	11
2.3.1	Geometrical Description . . . . .	11
2.3.2	Measurement Instrumentation . . . . .	12
2.4	Measurements Campaigns and Results . . . . .	14
2.4.1	Cases Nomenclature and Test Series . . . . .	14
2.4.2	Verification of Control Parameters Coherency . . . . .	15
2.4.3	Qualitative Analysis of the Experimental Results . . . . .	16
2.5	Further Verifications . . . . .	21
2.5.1	Reconstruction of the Applied Heat Flux . . . . .	21
2.5.2	Verification of Wall Temperature Measurements . . . . .	23
2.6	Conclusions . . . . .	25

---

### 2.1 INTRODUCTION

The validation of any existing modeling of multiphase flows must rely on extensive databases from experimental investigations in operating conditions that are representative of industrial configurations in PWR. This naturally lead to an important demand for measurements of local phase-related properties of vertical pressurized subcooled boiling flows.

To meet this need, CEA and EDF built a test facility called DEBORA in the 1990's. Its goal was to establish a consistent database of local measurements of the flow structure for vertical subcooled boiling freon Refrigerant 12 (R12) from the Onset of Nucleate Boiling to the Boiling Crisis.

In this chapter, we will describe the test section and analyze the available results from past measurements campaigns.

### 2.2 SIMULATING PWR WATER USING R12

The choice of using R12 as the working fluid in the DEBORA loop emerged from the interesting properties that boiling freon presents when compared to the highly pressurized water in PWR cores. Indeed, the conditions for which the Boiling Crisis must be studied for water in PWR are:

- Pressure  $P$  between 100 and 180 bar ;
- Inlet liquid mass flux  $G$  between 1000 and 5000  $\text{kg/m}^2/\text{s}$  ;

- Wall heat flux  $\phi_w$  between 0.5 and 6 MW/m<sup>2</sup> ;
- Inlet thermodynamic flow quality  $x_{eq,in}$  between -0.4 and 0.4.

In those ranges, sensors dedicated to local measurements are not suited to sustain such conditions.

The experimental strategy is then to "simulate" the aimed industrial conditions using a different fluid. It has to present thermophysical properties that allow to reproduce non-dimensional numbers of the industrial flow using less constraining operating conditions.

This explains the choice of R12 as it permits to transpose relevant parameters for PWR as detailed below.

### 2.2.1 Conservation of the Phase Density Ratio

Freon 12 can reach the same density ratio as water in PWR using limited pressurized conditions no larger than 30 bars. It is an important parameter to mimic the behavior of the boiling two-phase flow since it has a strong influence over the bubble size for example [54].

$$\left(\frac{\rho_{V,sat}}{\rho_{L,sat}}\right)_{P_1}^{water} = \left(\frac{\rho_{V,sat}}{\rho_{L,sat}}\right)_{P_2}^{R12} \quad (2.1)$$

with  $P_2 < P_1$ .

The evolution of the density ratio of water and R12 with pressure are shown on Figure 2.1.




Figure 2.1: Density ratio of pressurized R12 and water

For instance, we can see that R12 at approximatively 26 bar ( $T_{sat} \approx 86.8^\circ\text{C}$ ) has the same density ratio as water at 155 bar ( $T_{sat} \approx 344.8^\circ\text{C}$ ).

**Note :** This tranposition criteria thus scales the operating pressure  $P$  of the experiment.

### 2.2.2 Conservation of the Weber Number

The Weber number is also similar to those encountered in PWR.

$$We = \frac{G^2 R}{\rho_L \sigma} \quad (2.2)$$

This number characterizes physical phenomena such as bubble break-up or deformation under the influence of the liquid inertia.




Figure 2.2: Weber number for R12 and water at  $G = 2000 \text{ kg/m}^2/\text{s}$  and  $R = 0.1 \text{ mm}$

Similar to the phase density ratio, Figure 2.2 shows that Weber number equivalent to water at 155 bar can be reached with R12 around 23 bar.

**Note :** For a same value of  $R$ , this transposition scales the inlet liquid mass flux  $G$ .

### 2.2.3 Conservation of the Boiling Number

The boiling number is defined as:

$$\text{Bo} = \frac{\phi_w}{G h_{LV}} \quad (2.3)$$

It represents the comparison between the vapor mass flux  $\phi_w/h_{LV}$  if all the heat flux contributes to phase change versus the inlet liquid mass flux. Thus, its value can be associated to the boiling and two-phase flow regime.




Figure 2.3: Boiling number for R12 and water at  $G = 2000 \text{ kg/m}^2/\text{s}$

Figure 2.3 shows that Boiling number values similar to PWR can be reproduced using R12 with wall heat fluxes one order of magnitude lower and pressure around 23 bar.

**Note :** This transposition criteria scales the applied heat flux  $\phi_w$ .

#### 2.2.4 Conservation of the Inlet Thermodynamic Quality

Water in PWR being highly subcooled to avoid boiling, reproducing the inlet subcooling in the DEBORA experiment allows to mimic the early stages of boiling between the ONB and OSV. It allows to reproduce Boiling Crisis by Departure from Nucleate Boiling for low quality flows. This is achieved through the inlet thermodynamic quality:

$$x_{eq,in} = \frac{h_{L,in} - h_{L,sat}}{h_{LV}} \quad (2.4)$$

**Note :** This transposition is achieved by scaling the R12 inlet temperature.

#### 2.2.5 Same Geometry

The last similarity achieved in the DEBORA experiment is related to the geometry. The heated length  $L_{ch}$  of the test section is similar to the height of a nuclear fuel assembly and the hydraulic diameter  $D_h$  is equal to that of a subchannel.

#### 2.2.6 Transposition ranges

As a result of those conservation criteria, Table 2.1 sums up the transposition ranges for each parameters.

Fluid	Water	Freon R12
$P$ [bar]	100 - 180	14 - 30
$G$ [kg/m <sup>2</sup> /s]	1000 - 5000	1000 - 5000
$\phi_w$ [MW/m <sup>2</sup> ]	0.5 - 6	0.05 - 0.65
$x_{eq,in}$ [-]	(-0.4) - (+0.4)	(-0.4) - (+0.4)
$\rho_{V,sat}/\rho_{L,sat}$ [-]	0.08 - 0.25	0.07 - 0.22
We [-]	49.5 - 307.1	69.1 - 365.8
$Bo \times 10^{-3}$ [-]	0.19 - 3.86	0.21 - 4.33

Table 2.1: Water R12 scaling,  $R = 0.01\text{mm}$  for We

### 2.3 DESCRIPTION OF THE TEST SECTION

#### 2.3.1 Geometrical Description

To apply the aforementioned transport criteria, four thermal-hydraulic control parameters are imposed in the test section:

- The outlet pressure  $P$  ;
- The inlet mass flow rate  $G \times S_{in}$  with  $S_{in} = \pi R^2 \approx 2.9 \times 10^{-4} \text{ m}^2$  the inlet area ;
- The inlet liquid temperature  $T_{L,in}$  ;
- The electrical power transferred to the liquid  $\phi_w \times S_{heat}$  with  $S_{heat}$  the heated area.

The test section is presented on Figure 2.4. It consists of an inconel tube with inner diameter  $D_h = 19.2 \text{ mm}$ , a 1 mm thickness and a heated length  $L_{heat}=3.5 \text{ m}$ . A detailed description of the whole experimental loop is given in Garnier *et al.* [31].




Figure 2.4: Sketch of the DEBORA test section. Adapted from [31].

### 2.3.2 Measurement Instrumentation

The control parameters are adjusted and measured using pressure, temperature, flow rate and power measurements. They are further detailed in Cubizolles [18].

The local measurements are conducted at the end of the heating length using a controllable probe that can cover the whole diameter of the test section with an accuracy of  $10\mu\text{m}$ . Only one diameter is covered since the chosen geometry induces an axisymmetry.

Three type of measurements have been conducted over different experimental campaigns.

#### 2.3.2.1 Mono-Optical Probe Measurements

Optical probe measurement rely on the difference of optical refractive index between the liquid and vapor phase. Using an optical fiber in which light is emitted towards the probe tip allows to detect the actual phase flowing on the probe.

The resulting signal is called a Phase Indicator Function (PIF) which looks like to a square signal (Figure 2.5) that can be post-processed to identify the average time spent by the probe in each phase and then estimate their volume fraction *e.g.* the void fraction.

If the PIF is measured over a period  $T$ , the void fraction  $\alpha$  at the measurement point  $x$  can be estimated by:

$$\alpha(x) = \nu(x) \bar{t_V} = \frac{1}{T} \sum t_V \quad (2.5)$$




Figure 2.5: Example of Phase Indicator Function signal

where  $\nu$  is called the interference frequency that represents the number of phase interface detection per second by the probe.

**Note :** This measurement technique was performed in the **measurement campaign C2900** where void fraction profiles at the outlet were obtained for various flow conditions.

### 2.3.2.2 Bi-Optical Probe Measurements

Using the technology of the optical phase detection, adding a second optical probe permits to measure more parameters of the two-phase flow. Indeed, the use of two probes placed close to each other with a small shift in the flow direction (Figure 2.6) allows to estimate the velocity of the interface between the two probes by measuring the time difference between the two PIF.




Figure 2.6: Picture of the bi-optical probe with a zoom over the two optical fibers. Reproduced from [40].

Considering the following assumptions:

- The flow is mainly one-directional in aligned with the probes ;
- The vapor phase is composed of spherical inclusions ;
- The velocity gradient and center density gradient are small along a bubble diameter length.

Then we can estimate:

- The vapor axial velocity  $U_{V,z}$  that can be supposed equal to the measured interface velocity between the probes ;

- The interfacial area density  $a_i$ :

$$a_i = \frac{4\nu}{U_{V,z}} \quad (2.6)$$

- The bubble Sauter diameter:

$$D_V = \frac{6\alpha}{a_i} \quad (2.7)$$

**Note :** This measurement technique was performed in the **measurement campaign C3000**.

### 2.3.2.3 Thermocouples Measurements

Thermal measurements are conducted using chromel-alumel thermocouples. The liquid temperature is measured along the outlet diameter at the end of the heating length. Wall temperature measurements are conducted with 4 thermocouples placed at different heights (1.465 m, 2.465 m, 2.965 m, 3.485 m) on the outside of the tube.

**Note :** This measurement technique was performed in the **measurement campaign C800**.

## 2.4 MEASUREMENTS CAMPAIGNS AND RESULTS

### 2.4.1 Cases Nomenclature and Test Series

As mentioned before, three different campaigns have been performed:

- Campaign C2900 with solely void fraction measurements using mono-optical probe ;
- Campaign C3000 with void fraction, vapor velocity, bubble Sauter diameter and interfacial area density measurements using bi-optical probe ;
- Campaign C800 with liquid and wall temperature measurements using thermocouples.

Each measurement series is conducted under fixed outlet pressure, liquid mass flux and electrical power. Inlet temperature is then changed to cover different inlet quality. Experimental cases are named in the form **CccGgPppWwwTett** with **cc** the campaign number (29, 30 or 8), **g** the inlet mass velocity ( $G$  in  $\text{t/m}^2/\text{s}$ ), **pp** the outlet pressure ( $P$  in bars), **ww** the total heat power applied ( $\Phi_w$  in kW) and **tt** the inlet temperature ( $T_{L,in}$  in K). For instance, the case named C30G2P26W16Te66 has been conducted with  $P = 26.2$  bar,  $G = 2049 \text{ kg/m}^2/\text{s}$ ,  $\Phi_w = 15.6 \text{ kW} \equiv \phi_w = 73.89 \text{ kW/m}^2$  and  $T_{L,in} = 66.59^\circ\text{C}$ .

P	G	W16	W17	W23	W24	W25	W27	W29	W30	W31	W33	W34	W36	W38	W39	W40	W42	W44
14	2	○ ▽ △	△															
	4				○													
	5							▽	▽		▽	▽	▽	▽	▽	▽	▽	
26	2	○ ▽ △			▽ △		▽	▽ △	▽	▽ △	▽	▽ △	▽	▽	▽ △	▽	▽	▽ △
	3																	
	5	○				○												

P	G	W12	W14
30	1	▽	▽

Table 2.2: Test matrix of the DEBORA cases. ○: C800 - ▽: C2900 - △: C3000

If we want to obtain a full description of the two-phase flow from the DEBORA tests, we need to have measurements from campaigns C3000 and C800 (flow topology and thermal) with the same control parameters. Table 2.2 unfortunately shows that only very few test series between C3000 and C800 have common operating conditions, namely:

- Series 8G2P14W16 and 30G2P14W16 ;
- Series 8G2P26W16 and 30G2P26W16.

Other flow conditions have either been covered with thermal measurements or topology measurements but not both.

**Remark :** Cases from the campaign C2900 would only be relevant for void fraction profiles comparison. Estimations of the bubble diameter can not be achieved except if one assumes a velocity profile as suggested by Cubizolles [18] and re-used by Guéguel [40] who supposes:

$$U_{V,z}(r) \approx U_{M,z}(r) = 1.22 \frac{G}{\langle \rho_M \rangle_2} \left( \frac{R-r}{R} \right)^{1/7} \quad (2.8)$$

where  $U_{M,z}$  is the mixture axial velocity, assuming a mechanical equilibrium between the phases.

For further studies, we will mainly focus on the G2P26W16 and G2P14W16 test series. Although we will mainly rely on the results from the C3000 campaign (where vapor velocity was actually measured) for flow topology qualification, we will evaluate the assumption of Eq. 2.8 with the C2900 measurements.

#### 2.4.2 Verification of Control Parameters Coherency

For each case, the total heat input  $\Phi_w$  is given along with the inlet mass flux  $G$ , inlet liquid temperature  $T_{L,in}$  and outlet quality  $x_{eq,out}$ . To verify the consistency of those values, we can recalculate the outlet quality:

$$x_{eq,out,calc} = \frac{h_{M,out,calc} - h_{L,sat}}{h_{LV}} \quad (2.9)$$

with  $h_{M,out,calc}$  the recalculated outlet mixture enthalpy:

$$h_{M,out,calc} = h_{in} + \frac{\Phi_w}{GS_{in}} = h_{in} + \frac{4\phi_w L_{heat}}{GD_h} \quad (2.10)$$

with  $h_{in}$  the inlet enthalpy calculated from the fluid properties using the inlet liquid temperature.

The difference between the given and recalculated outlet quality can also be converted to input power error by recalculating the heat needed to reach the given  $x_{eq,out}$ :

$$\Phi_{w,calc} = \frac{G\pi R^2}{\underbrace{[x_{eq,out}h_{LV} + h_{L,sat}] - h_{L,in}}_{h_{M,out}}} \quad (2.11)$$

Moreover, for a given set of experiments at the same  $P$ ,  $G$  and  $\Phi_w$  changing the inlet quality can be associated to moving the measurement diameter along the axial direction following the relationship:

$$x_{eq}(z) = x_{eq,in} + \frac{4\phi_w z}{GD_h h_{LV}} \quad (2.12)$$

Thus, taking the maximum inlet quality case  $x_{eq,in,max}$  as a reference ( $z = 3.5$  m), we can estimate the corresponding measurement height  $z_{eq}$  of each other cases if the inlet quality was  $x_{eq,in,max}$ .

We calculated the equivalent heights and outlet quality / power input errors for two series of the C3000 campaigns. Results are displayed on Tables ?? and ??.

As we can see, the given values of outlet quality for the 30G2P14W16 tests are coherent with the one-dimensional enthalpy balance with errors mostly less than 0.1% on the recalculated quality and less than

$T_{L,in}$ [K]	$x_{eq,in,calc}$ [-]	$x_{eq,out,calc}$ [-]	$x_{eq,out}$ [-]	$z_{eq}$ [m]	$x_{eq,out}$ error [-]	$\Phi_w$ error [kW]
22.39	-0.317	-0.0821	-0.0832	1.075	0.114 %	-0.078
26.8	-0.28	-0.0422	-0.0431	1.653	0.089 %	-0.061
28.76	-0.263	-0.0267	-0.0273	1.896	0.056 %	-0.038
30.08	-0.252	-0.0152	-0.0157	2.065	0.05 %	-0.034
31.39	-0.241	-0.004	-0.0043	2.234	0.035 %	-0.023
38.95	-0.175	0.0674	0.0681	3.229	-0.072 %	0.049
39.96	-0.166	0.077	0.0776	3.357	-0.063 %	0.042
41.16	-0.155	0.0875	0.0882	3.509	-0.064 %	0.043

Table 2.3: Recalculated control parameters for the 30G2P14W16 cases. ( $T_{sat} = 58.07^\circ\text{C}$ )

$T_{L,in}$ [K]	$x_{eq,in,calc}$ [-]	$x_{eq,out,calc}$ [-]	$x_{eq,out}$ [-]	$z_{eq}$ [m]	$x_{eq,out}$ error [-]	$\Phi_w$ error [kW]
58.57	-0.395	-0.0893	-0.0819	1.792	-0.747 %	0.381
60.54	-0.370	-0.0650	-0.0578	2.072	-0.722 %	0.369
62.54	-0.344	-0.0392	-0.0318	2.369	-0.741 %	0.378
64.6	-0.318	-0.0123	-0.0050	2.674	-0.736 %	0.376
66.59	-0.292	0.0140	0.0213	2.973	-0.728 %	0.371
68.57	-0.266	0.0402	0.0473	3.271	-0.716 %	0.365
70.59	-0.239	0.0670	0.0743	3.583	-0.723 %	0.369

Table 2.4: Recalculated control parameters for the 30G2P26W16 cases. ( $T_{sat} = 86.81^\circ\text{C}$ )

100 W on the recalculated power input. This naturally leads to an equivalent height very close to 3.5 m for the hottest case.

However, a more significant error is observed on the 30G2P26W16 cases where errors up to 0.75% on the outlet quality and close to 0.4 kW on the power input are found. Those values are significant especially for cases close to saturation where uncondensed vapor will start to appear in the bulk. Moreover, this results in an equivalent height 8.3 cm longer than the actually 3.5m heated length.

Since the inlet temperature, mass flux and power input are controlled parameters for each test, it is likely that the error may come from the given value of outlet quality  $x_{eq,out}$  which is calculated and not imposed.

**Note :** Similar quality / input power errors were obtained on corresponding C29 and C8 campaigns:

- Negligible errors on for 29G2P14W16 and 8G2P14W16 cases ;
- Roughly 0.7 % outlet quality error and 0.3 to 0.4 kW power error for 29G2P26W16 and 8G2P26W16 cases.

#### 2.4.3 Qualitative Analysis of the Experimental Results

On Figures 2.7, 2.8, 2.9 and 2.10 we respectively plot the experimental measurements of cases 29/30G2P26W16, 8G2P26W16, 29/30G2P14W16 and 8G2P14W16. The colorbar representing the oulet quality of each test is based on the computed value of  $x_{eq,out}$  (Eq. 2.9).

##### 2.4.3.1 G2P26W16 cases

Void fraction profiles obtained in for C2900 (single optical probe) and C3000 (bi-optical probe) cases are compared to verify the consistency of the measurements (Figure 2.7a). The two campaigns are in good agreement with each other, displaying a void fraction profile monotonously increasing with the outlet quality. The estimation of the vapor velocity by Eq. 2.8 for the C29 results is acceptable but presents




Figure 2.7: 30G2P26W16 and 29G2P26W16 results

an growing underestimation as the outlet title increases (Figure 2.7b). This results in bubble diameter underestimation close to the wall and consequently interfacial area overestimation.

We observe that the void fraction naturally increases with the outlet quality and that we reach net vapor generation with  $\alpha(R = 0) > 0$  when  $x_{eq,out} > 0$ . Otherwise, vapor is not detected over the whole measurement section. Each case has its maximum void fraction near the wall with values up to approximately 40% when the outlet quality approaches 0.1.

The bubble diameter displays different behaviors (Figure 2.7c):

- It grows from the wall and reaches a maximum around  $r/R \approx 0.6$ , indicating bubble coalescence ;
- It stays nearly constant for negative outlet quality cases ;
- It decreases from  $r/R = 0.6$  to  $r/R = 0$  for saturated cases , indicating either bubble break-up or bulk condensation.

**Remark :** It seems that bubble diameter very close to the wall do not vary much between different cases, indicating that bubbles leave the wall at a nearly constant diameter over the different explored liquid temperatures ( $D_V \approx 0.2$  mm).

Vapor velocity also increases with the outlet quality, with a nearly flat profile reached for saturated cases. The increase in vapor velocity may result of the larger bubble diameters which enhance the effect of buoyancy, acting as an accelerating term increasing the drift velocity.

**Remark :** Eq. 2.8 fails to predict this flattening of the vapor velocity on C2900 cases, which may indicate a change in the flow structure that can not be detected when assuming liquid-vapor mechanical equilibrium.




Figure 2.8: 8G2P26W16 results

Regarding the liquid temperature measurements (Figures 2.8a and 2.8b), we see that temperature profiles linearly rise with the inlet quality while presenting an unmodified parabolic shape. The only change appears when reaching significant superheated conditions ( $x_{eq,out} \sim 0.1$ ) where the liquid temperature profile flattens over the test section.

Moreover, we observe that measurements very close to the wall present a very large temperature gradient even for low quality cases (temperature jump of nearly 30 degrees for coldest cases). This jump reduces as flow quality increases and reduces even more for boiling cases, indicating the well-known rise of the global heat transfer coefficient in boiling regime vs. single-phase convection regime.

We can also note that for the hottest case, the liquid becomes superheated near the wall ( $\Delta T_L (\pm 1) \approx 0.1^\circ\text{C}$ ). The bulk is still slightly subcooled with  $\Delta T_L (0) = -1^\circ\text{C}$

**Remark :** The liquid being subcooled in the bulk for superheated cases hints that the decrease in bubble diameter observed in Figure 2.7c for  $r/R < 0.6$  may be associated to condensation.

Wall temperature measurements (Figures 2.8c) display linear growth for subcooled cases which is in agreement with traditional liquid convection problems. When reaching boiling, the wall superheat stabilizes at  $\Delta T_w \approx 2^\circ\text{C}$ . Rearranging the different wall temperature measurements versus the local flow quality

(Figure 2.8d) presents a coherent overlapping between cases with different inlet subcooling. This further validates the transposition of inlet quality into variation into an evolution of the measurement probe's axial position.

#### 2.4.3.2 G2P14W16 cases




Figure 2.9: 30G2P14W16 and 29G2P14W16 results

Similar to the G2P26W16 cases, we observe the consistency of the void fraction measurements between the C2900 and C300 campaigns (Figure 2.9a). Although the vapor velocity estimation using Eq. 2.8 for C2900 cases also produces acceptable results for subcooled cases, the discrepancy when saturation is reached is even more observed here (Figure 2.9b). The overestimation when  $x_{eq,out} > 0$  is larger than for the G2P26W16 cases, with nearly 1 m/s error on hottest cases.

This logically yields larger underestimations of the bubble diameter and associated overestimations of the interfacial area concentration.

The void fraction profiles (Figure 2.9a) present a particular evolution with a moving  $\alpha$  peak that shifts from the wall to the bulk as the outlet quality increases. This may indicate a particular bubble dynamics regime inducing transverse bubble migration and accumulation far from the wall. Bulk void fraction can reach values as high as 70% with a flattening profile when  $x_{eq,out} \rightarrow 0.1$ .

**Remark :** It seems that saturated cases tend to reach a fixed value of near-wall void fraction between 35% and 40%.

Similar to previous observations, the bubble diameter grows when moving to the bulk, also presenting a peak value around  $0.8 > r/R > 0.6$  for subcooled cases (Figure 2.9c). The saturated cases however

present much larger increase in bubble diameter when reaching the bulk flow, with  $D_V$  close to 2 mm for the hottest case. This definitely indicates predominant coalescence effects.

**Remark :**  $D_V \approx 2$  mm is observed at a point where  $\alpha > 60\%$  which shows that even at such high void fraction values, the flow is still in a bubbly regime with small vapor inclusions ( $D_V \approx 0.1D_h$ ).

The vapor velocity also increases with the outlet quality (Figure 2.9b), but reaches much larger value compared to the G2P26W16 cases. This may be due to the larger bubble size and local void fractions associated to the imposed mass flow rate.




Figure 2.10: 8G2P14W16 results

The liquid temperature profiles (Figure 2.10a) are behaving in a very similar way to the G2P26W16 cases (Figure 2.8a): stable parabolic profile, linear shift with inlet quality and flattening when reaching superheated conditions ( $x_{eq,out} \sim 0.1$ ).

We also have the huge temperature jump when approaching the wall which reduces when reaching boiling regimes. The measurements also detect superheated liquid near the wall for the hottest cases ( $\Delta T_L \approx 0.1^\circ$ ). The case with the greatest outlet quality presents a surprisingly flat liquid temperature profile with measurements being nearly constant ( $\Delta T_L = -0.3^\circ$ ) over the whole measurement section.

**Remark :** Such a constant temperature profile could be interpreted as a limit of the liquid temperature in this regime. Since it corresponds to flow conditions where void fraction is large ( $\alpha > 60\%$ ) and bubbles do not condense (Figure 2.9c), any extra heat input may only contribute to phase change and leave the liquid phase thermally unchanged.

Unfortunately, the 8G2P15W16 campaign did not cover as large quality range as the 8G2P26W16 campaign. We thus do not have access to many single-phase flow wall temperature measurements (Figure 2.10c). Only one point for  $x_{eq,out} \approx -0.1$  seem to be in the single-phase convection region. All the other measurements are close to each other and correspond to boiling regimes where we observe a wall superheat stabilization around  $\Delta T_w = 4^\circ\text{C}$ .

The comparison of wall temperature with local flow quality (Figure 2.10d) is not as interesting as the G2P26W16 cases but still display a welcomed overlapping of the measurements over the different inlet temperatures.

## 2.5 FURTHER VERIFICATIONS

### 2.5.1 Reconstruction of the Applied Heat Flux

To further quantify the coherency of the DEBORA database, we want to reconstruct the wall heat flux injected in the flow from the experimental measurements of void fraction, vapor velocity and liquid temperature measurements.

#### 2.5.1.1 Methodology

To do so, we will estimate the total enthalpy change between the inlet and outlet. The inlet liquid enthalpy  $h_{L,in}$  is estimated using the inlet temperature and the outlet mixture enthalpy  $h_{M,out}$  is computed as:

$$h_{M,out} = x_{m,out} h_{V,sat} + (1 - x_{m,out}) \langle h_{L,out} \rangle_2 \quad (2.13)$$

supposing that the vapor is at saturation temperature and where  $x_{m,out}$  is the outlet mass quality.

Using the experimental values of  $\alpha$  and  $U_{V,z}$ , we can compute the outlet mass quality  $x_{m,out}$  as:

$$x_{m,out} = \frac{\rho_V \langle \alpha U_{V,z} \rangle_2}{G} \quad (2.14)$$

where:

$$\langle \alpha U_{V,z} \rangle_2 = \frac{1}{\pi R^2} \int_{\vartheta=0}^{2\pi} \int_{r=0}^R \alpha(r) U_{V,z}(r) r dr d\vartheta = \frac{2}{R^2} \int_{r=0}^R \alpha(r) U_{V,z}(r) r dr \quad (2.15)$$

for an axisymmetric profile such as the DEBORA measurements.

From the mass quality we can compute the mixture enthalpy as:

$$h_M = x_m h_{V,sat} + (1 - x_m) \frac{\langle \rho_L (1 - \alpha) U_{L,z} h_L \rangle_2}{\langle \rho_L (1 - \alpha) U_{L,z} \rangle_2} \quad (2.16)$$

Similarly, the average liquid enthalpy at the outlet is estimated as:

$$\langle h_L \rangle_2 = \frac{2}{R^2} \frac{1}{G_L} \int_{r=0}^R \rho_L(r) U_{L,z}(r) h_L(r) r dr \quad (2.17)$$

where  $h_L$  is estimated using the local temperature measurements and  $U_{L,z}$  is estimated using the drift velocity of Ishii [47]:

$$U_{L,z} = U_{V,z} - U_{rel} = U_{V,z} - \sqrt{2} \left( \frac{g\sigma(\rho_L - \rho_V)}{\rho_L^2} \right)^{1/4} (1 - \langle \alpha \rangle_2)^{1.75} \quad (2.18)$$

Then, writing the one-dimensional energy balance of the flow permits to express the actually applied heat flux:

$$G\pi R^2 (h_{M,out} - h_{L,in}) = \Phi_w = \phi_w 2\pi R L_{heat} \Rightarrow \phi_w = \frac{(h_{M,out} - h_{L,in}) GR}{2L_{heat}} \quad (2.19)$$

which can be compared to the given control parameter for the experiment.

### 2.5.1.2 Application

To apply the presented reconstruction of the heat flux, we either need:

- A pure single-phase case with an outlet liquid temperature profile (C800 case alone);
- A boiling two-phase case with void fraction and vapor velocity measurements (C3000 case) along with liquid temperature (C800 case).

This means that for boiling cases, we need to "merge" cases from the C3000 and C800 campaign conducted in very close operating conditions ( $P$ ,  $G$ ,  $T_{L,in}$ ) and assume that the liquid temperature measurements of the C800 case are actually representative of the liquid temperature in the C3000 case and reciprocally for the void fraction and vapor velocity.

Such a constraint leaves us with very few boiling cases that can accommodate those conditions. They are summed up on Table 2.5.

Case Name	$P$ [bar]	$G$ [kg/m <sup>2</sup> /s]	$\phi_w$ [kW/m <sup>2</sup> ]	$T_{L,in}$ [°C]	$x_{eq,in}$ [-]	$x_{eq,out}$ [-]
30G2P26W16Te66	26.2	2049.0	73.893	66.59	-0.2919	0.014
8G2P26W16Te66.6	26.2	1982.0	73.9	66.57	-0.2927	0.0237
30G2P26W16Te70	26.19	2051.2	73.893	70.59	-0.2386	0.067
8G2P26W16Te70.3	26.2	1983.0	73.9	70.31	-0.2428	0.0734

Table 2.5: Similar conditions cases between the C3000 and C800 campaigns. Outlet quality calculated with Eq. 2.9.

To actually compute the surface-averaged quantities, we need to interpolate the experimental profiles which is done using the `python` package `scipy`. Figure 2.11 presents typical interpolation profiles used in this sections.

The results obtained for the heat flux recalculations are presented on Table 2.6.

Case name	$x_m$ [-]	$\phi_{w,rec}$ [kW/m <sup>2</sup> ]	$\phi_{w,exp}$ [kW/m <sup>2</sup> ]	$\Delta\phi_w$ [%]
30G2P26W23Te66.6	0.0193	70.432	73.893	-4.68%
30G2P26W23Te70.6	0.0500%	68.041	73.893	-7.9%

Table 2.6: Heat flux recalculation results

We see that reconstructing the heat flux yields values significantly lower than the experimental values given in the database. This underestimation was also noted in a similar approach conducted by Guéguen [40] who found discrepancy of a few %.

In our case, these discrepancies can be partially explained by:

- The difference of inlet mass fluxes that are roughly 70 kg/m<sup>2</sup>/s lower for the C800 cases ;
- The difference of inlet liquid temperature for the Te70 cases with a C800 case 0.3°C lower than the C300 case.

Those small discrepancies lead to outlet qualities (computed with Eq. 2.9 using the given  $\phi_w$ ) that differ of approximately 1%. Even though boiling flows near saturation, such as those studied here, are very sensitive to the local quality and flow parameters, this would hardly suffice to explain differences in heat flux as much as 5%.




Figure 2.11: Interpolation profiles for cases Te66 (Table 2.5).

**Remark :** Unfortunately, our methodology do not rely on collocated measurements of all the variables of interest since the campaigns were conducted separately. The "correction" values presented in Table 2.6 can not be considered as accurate estimations but still point out that an uncertainty over the heat flux can be considered in further work.

### 2.5.2 Verification of Wall Temperature Measurements

In order to test the coherency of wall temperature measurements both in single phase and boiling regions, we compare them to one-dimensional correlations along the ( $\Delta T_w$ ,  $x_{eq}$ ) curve.

Single-phase measurements are confronted to the estimations of Dittus-Boelter (Eq. 2.20,  $DB$ ) correlation and Gnielinski correlation (Eq. 2.21,  $G$ ):

$$\text{Nu}_{DB} = 0.023 \left( \text{Re}^{4/5} \right) \text{Pr}^{0.4} \quad (2.20)$$

$$\text{Nu}_G = \frac{\frac{C_f}{2} (\text{Re} - 1000) \text{Pr}}{1 + 12.7 \sqrt{\frac{C_f}{2}} \left( \text{Pr}^{2/3} - 1 \right)} \quad (2.21)$$

where the friction coefficient  $C_f$  is estimated following Churchill [15] as recommended by Delhaye [21] and Guéguen [40]:

$$C_f = 2 \left[ \left( \frac{8}{\text{Re}} \right)^{12} + \frac{1}{(A+B)^{1.5}} \right]^{1/12} \quad (2.22)$$

$$A = \left[ 2.457 \ln \left( \frac{1}{\left( \frac{7}{\text{Re}} \right)^{0.9} + 0.27 \frac{\varepsilon}{D_h} } \right) \right]^{16} \quad (\varepsilon=0 \text{ supposed here})$$

$$B = \left( \frac{37530}{\text{Re}} \right)^{16}$$

Wall superheat in boiling region is compared with the simple correlation of Frost & Dzakowic [29]:

$$\Delta T_{w,FD} = \text{Pr}_{L,sat} \sqrt{\frac{8\sigma\phi_w T_{sat}}{\lambda_{L,sat} h_{LV} \rho_V}} \quad (2.23)$$

where  $T_{sat}$  is expressed in Kelvin.

The results are presented on Figure 2.13 for cases at 26 bar and Figure 2.12 for cases at 14 bar. Since we do not need combination with void fraction measurements, every cases of the C800 campaign were used for comparison.




Figure 2.12: Correlations comparison with P14 cases.

Wall temperature measurements for the liquid convective regime are in fairly good agreement with the predictions of the Gnielinski correlation. The slope of the model is very close to the experimental data in the single-phase region. It is particularly true for the P26 cases (Figure 2.13) where a large range of subcooled conditions in the single-phase region was covered.

Regarding the P14 cases (Figure 2.12), very few measurements are available outside of the boiling region. However we can see that the Gnielinski correlation seem to consistently meet the boiling measurements and follow a trend that agrees with the experimental data.

On the other hand, the Dittus-Boelter correlation fails to predict the wall temperature with a constant overestimation of approximately 5°C regardless of the case.

**Note :** The average liquid temperature at different heights was estimated using a one-dimensional energy balance before computing the local wall temperature predicted by correlations. The virtual length used for single-phase correlations was adjusted to cover the whole range of  $x_{eq}$ .




Figure 2.13: Correlations comparison with P26 cases.

The nucleate boiling temperature predicted by Frost & Dzakowic correlation are in good agreement with the experimental observations where we saw the wall temperature stabilization. The prediction is better for the P26 cases than for the P14 cases where an underestimation of  $1^\circ\text{C}$  is observed. We can also note that the measurements are more dispersed for the P14 cases and span over a range of more than  $1^\circ\text{C}$  around the average temperature.

Those comparisons are comforting the consistency of the wall temperature database which correspond to traditional behavior of wall to fluid heat transfer in both single-phase and boiling two-phase regimes.

## 2.6 CONCLUSIONS

The DEBORA database is a very rich source of experimental insights for boiling flows representative of PWR industrial conditions. The large range of control parameters that was covered during the tests also is encouraging regarding the variety of flow regimes that can occur in PWR conditions

After a finer analysis of the data, in the continuation of the work of Cubizolles [18], Manon [70] and Guéguen [40], we concluded that:

- The test matrix unfortunately shows that very few series were covered with both bi-optical probe (C3000) and thermocouples (C800) measurements, limiting the availability of a full boiling database to the series G2P26W16 and G2P14W16.
- Small but significant errors on the reported outlet quality could be observed when compared to a one-dimensional energy balance based on the control parameters (Table 2.4).

- Good agreement was found between the void fraction measurements with the mono (C2900) and bi-optical probe (C3000), which comforts the validity of the acquired data in close flow conditions.
- Extension of the C2900 data to estimate bubble diameter and interfacial area concentration using Eq. 2.8 to compute vapor velocity was acceptable in subcooled conditions but showed increasing underestimations in the saturated region (Figures 2.7b and 2.9b).
- Void fraction measurements in the G2P14W16 series showed a particular behavior with a peak value moving from the wall to the bulk as the inlet temperature increases.
- Bubble diameter measurements clearly exhibited coalescence phenomena when leaving the wall with a maximum value reached at  $r/R \approx 0.6$  before decreasing under condensation and / or break-up (Figure 2.7c). It was also observed that measurements closest to the wall were nearly constant among a given test series regardless of the inlet temperature.
- Liquid temperature can overcome the saturation temperature for the hottest cases close to the wall ( $T_L - T_{sat} \approx 0.1^\circ\text{C}$ ) and flattens at the bulk with a subcooling roughly around  $0.5^\circ\text{C}$ .
- Wall temperature measurements followed a coherent linear profile in the single-phase region before stabilizing when boiling starts, which was further reproduced by comparison with one-dimensional correlations. Measurements were also overlapping each other when plotted versus the local quality, confirming the transposition between change of inlet temperature and axial translation of the measurement section.
- Reconstruction of the applied wall heat flux in the experiments by merging the values from very close C3000 and C800 cases (Table 2.5) suggested that the heat flux values provided in the measurements were too large by 5% to 8%. Such a large difference is surprising and could partially be explained by the small change of operating conditions between C3000 and C800 cases.

At last, the different evaluations conducted over the chosen experiments have reasonably validated the consistency and coherency of the measurements. Further comparisons with NEPTUNE\_CFD simulations will be conducted using the experimental results of the G2P26W16 series. **Still, we keep in mind that an error of a few % is possible on  $\phi_w$ .**

# 3

---

## NEPTUNE\_CFD SIMULATIONS OF DEBORA CASES

---

Due to the large amount of measurements along with its scaling conditions with PWR flows, the DEBORA cases have been often used for validation of multiphase simulation tools, from simple 1D / 2D codes [**kledy\_DEBORA**, 40, 70] to CFD softwares [**mimouni\_debora**, **guelfi\_neptune**, **bestion\_debora**, **baglietto\_debora**], helping to conduct separate validation and comparison of several modeling aspects involved in such codes (interfacial heat and momentum transfer, turbulence, interfacial area transport, etc.).

In this Chapter, we present neptune\_cfd simulations of the DEBORA experiment. The objective is to assess the current modeling of the code for dispersed two-phase boiling flows. To do so, we will simulate cases from the different campaigns of the DEBORA database (C800 and C3000) to conduct comparisons of void fraction, bubble diameter, vapor velocity, liquid temperature and wall temperature profiles.

As identified in Chapter 2, our focus will be on cases from the G2P26W16 series, since they provide the most extensive set of measurements in very close operating conditions.

### 3.1 SIMULATION SETUP

Since the geometry of the DEBORA experiment presents an axisymmetry, we simplify the simulation setup in order to realize a 2D axisymmetric computation. The computational domain consists of a  $1^\circ$  angular section of radius  $R = 9.6$  mm and 3.85 m length (Figure 3.1).




Figure 3.1: View of the computational domain.

The boundary conditions are:

- Uniform heat flux for  $0.2 \text{ m} \leq z \leq 3.5 \text{ m}$  ;
- Adiabatic wall for  $z < 0.2 \text{ m}$  and  $z > 3.7 \text{ m}$  ;
- Uniform outlet pressure ;
- Uniform inlet velocity ;
- Symmetry condition on remaining faces.

The inlet section before heating is approximately  $10D_h$  long and the extracted radial profile for comparisons is located at the end of the heating length. The angular section consists of 1 mesh while radial and

Mesh name	M1	M2	M4	M8
Number of cells (radial $\times$ axial)	$10 \times 100$	$20 \times 200$	$40 \times 400$	$80 \times 800$

Table 3.1: Mesh parameters

axial direction are uniformly discretized. Four meshes are considered, presented on Table 3.1 and Figure 3.2.




Figure 3.2: View of the radial meshes.

The computation runs using the transient solver of NCFD for a long enough physical time ensuring temporal stabilization and convergence of the results.

**Note :** First simulated case was simulated up to a physical time of 40 s, ensuring the time-convergence. Further simulations used this first case as a restart point, allowing to reach time-convergence in less than 10 s when changing boundary conditions.

### 3.2 MESH SENSITIVITY STUDY

On Figure 3.3, we present simulation results for the 4 meshes (Table 3.1) of the case 30G2P26W16Te66.6. We see that the different meshes provide similar results for the void fraction, bubble diameter, vapor velocity and liquid temperature. This is particularly true for the M4 and M8 meshes, allowing to assume that an acceptable grid convergence is reached with the M4 mesh. **Therefore, further simulations will be conducted using the M4 mesh.**

**Remark :** One of the most remarkable impact of the mesh concerns the liquid temperature in the wall-adjacent cell. As the mesh refines, the strong temperature gradient at the wall is logically better captured, inducing a net rise in the liquid temperature when  $r/R \rightarrow 1$ .

### 3.3 C800 CASES SIMULATION : THERMAL MEASUREMENTS

In this Section, we focus our attention on cases from the 8G2P26W16 series to assess liquid and wall temperature predictions. We sub-divide the case in three parts depending on the degree of subcooling at the outlet in order to cover both single-phase and fully boiling cases.




Figure 3.3: Mesh sensitivity study for 30G2P26Te66.6 case

### 3.3.1 High Subcooling Cases

We start by simulating cases 8G2P26W16Te31.5 and Te44.9 which both have an outlet quality  $x_{eq,out} < -0.25$ , meaning that the fluid remains in its liquid phase along nearly the entire heating length. Results obtained for those cases are presented on Figure 3.4.

The liquid temperature profiles are fairly reproduced with experimental the parabolic shape correctly captured along with quite precise prediction of the temperature values in the bulk (Figure 3.4a). Still, we note that an overestimation near the wall and a small underestimation (less than 1°C) when approaching the center of the pipe.

Wall temperature predictions in the single-phase region present a good agreement with the experimental measurements along the axial positions (Figure 3.4b). This is further verified by transposition along the local quality  $x_{eq}$  (Figure 3.4c) gathering all the measurements from the 8G2P26W16 campaign, showing an average error of approximately 1°C up to  $x_{eq} \approx -0.5$ .

Those comparisons highlight the validation of the code for the single-phase flow part, implying that **the local liquid heat transfer coefficient (Eq. 1.23) is correctly computed along with a good heat transport along the radial direction.**




Figure 3.4: Simulation results for cases 8G2P26W16Te31. 5& Te44.9

### 3.3.2 Low Subcooling Cases

Next cases to be simulated are 8G2P26W16Te55.7 and Te61.5. Their outlet quality is closer to saturation with  $x_{eq,out} \geq -0.1$  and thus present a subcooled boiling region during a significant portion of the heating length. However, the bulk flow is expected to stay fully liquid in those conditions (Figure 2.7a). The results are presented of Figure 3.5.

Liquid temperature profiles (Figure 3.5a) are similar to those of the high subcooling cases (Figure 3.4a). The parabolic shape of the measurements is reasonably reproduced, with liquid temperature values close to the experiment. The same discrepancies are observed, namely a overestimation close to the wall and a small underestimation at the center (also lower than 1°C).

However, the wall temperature start to show significant discrepancies with the measurements (Figure 3.5b). The deviation from the linear profile observed in the pure-single phase region towards a stabilization corresponding to the boiling regime fails to be reproduced (Figure 3.5c). First, the temperature plateau appears to start later than the experiment (around  $x_{eq} \approx -0.3$  for the simulations contrary to  $x_{eq} \approx -0.4$  for the experiments) and further reaches a wall temperature up to 6°C above the measurements.

Albeit the liquid temperature seems correctly distributed along the radial direction in the subcooled boiling region (also meaning that any amount of vapor potentially produced at the wall is correctly re-condensed), the wall temperature behavior significantly deviates from the experiments both by missing the ONB and exhibiting a too large superheat in the boiling region. **This consequently casts interrogations towards the modeling of the wall temperature in the code, which is a result of the wall boiling model (Section 1.5).**

### 3.3.3 Saturated Cases




Figure 3.5: Simulation results for cases 8G2P26W16Te55.7 &amp; Te61.5




Figure 3.6: Simulation results for cases 8G2P26W16Te66.6 &amp; Te70.3

In this work, we present the simulations of the following cases:

- C8G2P26W16Te44.9 and C8G2P26W16Te49.6 (single-phase flow)
- C8G2P26W16Te66.6 and C8G2P26W16Te70.3 (two-phase flow)
- C30G2P26W16Te66.6 and C30G2P26W16Te70.6 (two-phase flow)

The pressure of 26 bar is chosen to match the pressure of the mixing vanes cases (DEBORA-Promoteur, Section 9.1). Mesh sensitivity is performed over two meshes: a large mesh (M1) with 460 356 cells = 338 radial  $\times$  1362 axial cells and a fine mesh (M2) with 3 157 952 cells = 1568 radial  $\times$  2014 axial cells. On Figure 3.7, we present the results regarding liquid temperature at the outlet and wall temperature. The liquid temperature profile seems to be correctly reproduced by the simulations, though we see a slight overestimation close to the wall. Looking closer at boiling cases shows a difference of  $\approx 0.5^\circ\text{C}$ , which is close to the uncertainty of the measurements [31]. Concerning the wall temperature, it appears that it is underestimated before the **Onset of Nucleate Boiling** (ONB) ( $T_w < T_{sat}$ ) and overestimated after the ONB ( $\approx +5^\circ\text{C}$ ). Post-ONB wall temperature is characterized by a stabilization of its value above the saturation temperature (here  $T_{w,ONB} - T_{sat} \approx 2^\circ\text{C}$ ).




Figure 3.7: NCFD (lines) vs. Exp. (circles) -  $T_L$  and  $T_w$  - Cases C8G2P26W16Te44.9, Te49.6, Te66.6 and Te70.3  
- Simulations using two meshes M1 (coarse) and M2 (fine).




Figure 3.8: NCFD (lines) vs. Exp. (circles) -  $\alpha$ ,  $d_G$  and  $U_{G,z}$  - Cases C30G2P26W16Te66.6 and Te70.6 - Simulations using two meshes M1 (coarse) and M2 (fine).

On Figure 3.8, we compare the results of the simulations to the experiments regarding void fraction, bubble Sauter diameter and axial gas velocity. Void fraction profiles are quite correctly reproduced, though we observe a 10% higher peak at the wall for  $T_{in} = 66.6^\circ\text{C}$ . The order of magnitude of bubble diameter is correct ( $\sim 0.1\text{mm}$ ) and NEPTUNE\_CFD manages to detect coalescence (increase of bubble diameter when leaving the wall) and bulk condensation (decrease of bubble diameter when reaching the core of the

flow), which is in qualitative agreement with the experiments. Quantitatively speaking, bubble diameter is globally underestimated. Finally, gas velocity profile is reasonably reproduced for  $T_{in} = 66.6^\circ\text{C}$ , but not for  $T_{in} = 70.6^\circ\text{C}$ . The latter experimental profile is flatter, which could be explained by a change of flow regime since uncondensed vapor is detected in the bulk.

Finally, the simulations reasonably agree with the experiments. The strongest discrepancies being mostly the wall temperature and bubble diameter. Potential ways of improving those results are investigated in next sub-section.

### 3.3.4 Investigating the nucleation site density modeling $N_{sit}$

In NEPTUNE\_CFD, wall temperature is computed through the Heat Flux Partitioning model, which role is to find the appropriate  $T_w$  which balances Equation 1.22. However, some laws used to express parameters such as  $N_{sit}$ ,  $f$ , or  $d_d$  are quite old and simple. For instance, the Lemmert & Chawla[62] expression of  $N_{sit}$  only depends on the wall superheat (Sub-section ??).

A comparison of the Lemmert & Chawla law[62] with the Hibiki & Ishii[46] law for  $N_{sit}$  against 4 data sets from the literature is presentend on Figure 3.9. The Hibiki & Ishii correlation depends simultaneously on wall superheat, pressure and contact angle. Experimental measurements of Borishanskii *et al.* [5], Richenderfer *et al.* [90], Kossolapov *et al.* [57] and Zhou *et al.* [121] are used to assess the two nucleation site density correlations.




Figure 3.9:  $N_{sit}$  correlations of Lemmert & Chawla (left) and Hibiki & Ishii (right) vs. exp. data from literature. Operation pressures are displayed.  $\pm 50\%$  error bars are drawn in black.

Figure 3.9 clearly shows that the Lemmert & Chawla law lack of pressure dependence fails to reproduce high pressure measurements contrary to the Hibiki & Ishii one. Even though Hibiki & Ishii correlation shows significant discrepancies with measurements of Kossolapov *et al.* and Richenderfer *et al.*, its prediction capability is greater in average than Lemmert & Chawla correlation.




Figure 3.10: NCFD results for  $\alpha$ ,  $T_L$  and  $T_w$  using Lemmert & Chawla and Hibiki & Ishii correlation. Cases 8G2P26W23Te66.6 and Te70.3, 30G2P26W23Te66.6 and 70.6.

To assess the influence of nucleation site density law on NEPTUNE\_CFD computations, we compare results obtained with both correlations on Figure 3.10, which shows a remarkable impact of the modification of  $N_{sit}$  correlation. Using Hibiki & Ishii correlation reduces the error on  $T_w$  by approximately 2°C while  $\alpha$  and  $T_L$  remain unchanged. This implies that the same heat flux partitioning is found with the two models, but that the pressure dependence of Hibiki & Ishii law helped to balance Equation 1.22 using a lower  $T_w$ , thus closer to experimental measurements.

Such a result indicates that the HFP model could be improved through a systematic analysis of each parameter's impact and modeling (bubble departure diameter, detachment frequency, etc.). Assembling a more recent and consistent model could provide better results regarding wall temperature prediction. Models such as the one developed by Kommajosyula[56] could be interesting to apply for high-pressure flows.

Now that simple tube boiling flow has been assessed through the presented results, next section will focus on the simulation of boiling flow in a tube equipped with a mixing device.

## Part II

### DEVELOPMENT OF A NEW WALL HEAT FLUX PARTITIONING MODEL

# 4

---

## INTRODUCTION TO HEAT FLUX PARTITIONING

---

### Contents

4.1	Introduction . . . . .	<b>36</b>
4.1.1	Empirical Approaches . . . . .	<b>36</b>
4.1.2	First Heat Flux Partitioning Approaches . . . . .	<b>37</b>
4.2	Kurul & Podowski (1990) . . . . .	<b>38</b>
4.3	Basu, Warrier & Dhir (2005) . . . . .	<b>39</b>
4.3.1	Case 1 : Bubble Sliding, $D_d < s$ . . . . .	<b>40</b>
4.3.2	Case 2 : Bubble Coalescence without Sliding, $D_d \geq s$ . . . . .	<b>41</b>
4.4	Gilman (2017) . . . . .	<b>42</b>
4.5	Kommajosyula (2020) . . . . .	<b>44</b>
4.6	Conclusion . . . . .	<b>45</b>

---

### 4.1 INTRODUCTION

#### 4.1.1 Empirical Approaches

In the field of heat transfer and boiling, establishing a physical relationship between the applied heat flux at the wall  $\phi_w$  and the wall temperature  $T_w$  has always been a primal goal for system design and safety analysis. Traditional approaches for single-phase flows rely on the estimation of the heat transfer coefficient  $h_{SP}$  defined as:

$$\phi_w = h_{SP} (T_L - T_w) \quad (4.1)$$

where  $T_w$  and  $T_L$  are the wall and bulk liquid temperature.

Estimating  $h_{SP}$  is usually done using dedicated correlations depending on flow parameters such as the hydraulic Reynolds number  $Re_{D_h}$ , the fluid Prandtl number  $Pr_L$ , etc. Correlations of Dittus-Boelter (Eq. 2.20) or Gnielinski (Eq. 2.21) that were presented earlier are typical example of widely used expressions to estimate  $h_{SP}$ .

For boiling multiphase flows, different types of empirical approaches have been developed through the history. For instance, some authors proposed direct correlations relating wall heat flux and temperature such as:

- Jens & Lottes [48]:

$$\phi_w = \left( \frac{\Delta T_w}{25} e^{P/62} \right)^4 \quad (4.2)$$

- Thom *et al.* [103]:

$$\phi_w = \left( \frac{\Delta T_w}{22.65} e^{P/87} \right)^2 \quad (4.3)$$

with  $P$  in bar and  $\phi_w$  in MW/m<sup>2</sup>.

On the other hand, some models are based on the estimation of heat transfer coefficients similar to single-phase approaches. They mostly rely on the separation between a single phase  $h_{SP}$  and nucleate boiling  $h_{NB}$  heat transfer coefficients. Well-known correlations of this type are proposed by Chen [11], Gungor & Winterton [43] or Liu & Winterton [66]. For instance, Chen correlation writes:

$$\phi_w = \phi_{SP} + \phi_{NB} = h_{SP} (T_w - T_L) F + h_{NB} (T_w - T_{sat}) S \quad (4.4)$$

with  $F$  an amplification factor for the single phases heat transfer due to bubble agitation and  $S$  a suppression term hindering the nucleate boiling under the effect of bulk liquid flow.

The single phase part  $h_{SP}$  is calculated using Dittus-Boelter [23] formulation (Eq. 2.20) while the nucleate boiling part is:

$$h_{NB} = 0.00122 \frac{\lambda_L^{0.79} c_{p,L}^{0.45} \rho_L^{0.49}}{\sigma^{0.5} \mu_L^{0.29} h_{LV}^{0.24} \rho_V^{0.24}} \Delta T_w^{0.25} (P_{sat}(T_w) - P_{sat}(T_{sat}))^{0.75} \quad (4.5)$$

along with the factors  $F$  and  $S$ :

$$\frac{1}{X_{tt}} = \left( \frac{x}{1-x} \right)^{0.9} \left( \frac{\rho_L}{\rho_V} \right)^{0.5} \left( \frac{\mu_V}{\mu_L} \right)^{0.1} \quad (4.6)$$

$$F = \begin{cases} 1 & \text{if } X_{tt} \geq 1 \\ 2.35 \left( \frac{1}{X_{tt}} + 0.213 \right)^{0.736} & \text{if } X_{tt} \leq 1 \end{cases} \quad (4.7)$$

$$S = \frac{1}{1 + 2.53 \times 10^6 \text{Re}_{D_h}^{1.17}} \quad (4.8)$$

where  $X_{tt}$  is the Lockhart-Martinelli parameter [67] and  $x$  the vapor quality.

Each of those correlations has been developed for given experimental conditions such as high pressure flows up to 150 bar for Thom and Jens & Lottes correlations while Chen correlation is dedicated for low to moderate pressure ( $\sim 35$  bar).

#### 4.1.2 First Heat Flux Partitioning Approaches

The spirit of splitting the different heat transfer mechanisms (single-phase, nucleate boiling) using different heat transfer coefficients is actually a premise to what is nowadays called the "Heat Flux Partitioning" approach. Bowring [6] is among the first author who actually expressed the total heat flux at the wall as separate contributions between different heat transfer mechanisms by writing:

$$\phi_w = \phi_e + \phi_a + \phi_{SP} \quad (4.9)$$

where  $\phi_e$  is the latent-heat transfer associated to evaporation,  $\phi_a$  the convection due to bubble agitation and  $\phi_{SP}$  the single-phase heat transfer to the liquid.

Making steps towards a more mechanistic description of boiling, he wrote:

$$\phi_e = N_{sit} f V_b \rho_V h_{LV} \quad (4.10)$$

where  $N_{sit}$  is the nucleation site density on the surface,  $f$  the bubble nucleation frequency,  $V_b$  the bubble volume. Those parameters need dedicated description and modeling based on experimental measurements. Nonetheless, an empirical parameter is introduced by Bowring to estimate the bubble-agitation term  $\phi_a$  as:

$$\phi_w = \phi_{SP} + (1 + \varepsilon) \phi_e \quad (4.11)$$

$$\varepsilon = \frac{\phi_a}{\phi_e} \approx \frac{\rho_L c_{p,L}}{\rho_V h_{LV}} (T_w - T_L) \quad (4.12)$$

where  $\varepsilon$  has to be experimentally estimated. We can notably observe that its expression is that of a Jakob number based on the temperature difference between the wall and the liquid temperature.

This idea of splitting the wall heat flux and try to precisely model each heat transfer mechanisms using detailed parameters (nucleation site density, frequency, nucleated bubble diameter, etc.) has been since a very active matter of research in the field of boiling heat transfer [20, 49]. With increasing experimental insights allowing to access local parameters relevant for the physics at stake close to the wall [57, 69, 90, 100, 113], the development of such models has become increasingly important both for analytic and simulation grounds. Indeed, the clear separation of the different heat fluxes is a very useful mathematical formulation for multiphase CFD computations where each term can be used as a phase-related source term at the wall [35, 41].

In the following sections, we chronologically present four different Heat Flux Partitioning models developed between 1990 and 2020. For each model, we detail the mathematical formulation of the different fluxes along with associated physical assumptions and highlight the parameters that require a dedicated closure law.

#### 4.2 KURUL & PODOWSKI (1990)

In their original work published in 1990, Kurul & Podowski [58] proposed a complete closure for the wall heat flux partitioning. Their model is among the most referred to by many authors and has been particularly used in CMFD codes due to its simple formulation and closure laws.

**Note :** The wall boiling model of NCFD mostly rely on the Kurul & Podowski formulation as presented in Chapter 1.

Kurul & Podowski considered the applied heat flux to be divided between three mechanisms (Figure 4.1):

- A liquid single-phase convective heat flux  $\phi_{c,L}$  ;
- A boiling heat flux  $\phi_e$  ;
- A quenching heat flux  $\phi_q$  induced by bubble movement when leaving the surface.




Figure 4.1: Sketch of the HFP considered by Kurul & Podowski (by Manon [70]).

The total wall heat flux being :

$$\phi_w = \phi_{c,L} + \phi_e + \phi_q \quad (4.13)$$

The convective heat flux is expressed as :

$$\phi_{c,L} = A_{c,L} \rho_L c_{p,L} U_{L,\delta} \text{St}_{L,\delta} (T_w - T_{L,\delta}) \quad (4.14)$$

with  $A_{c,L}$  the portion of the wall unaffected by boiling,  $U_L$  the liquid velocity,  $\text{St}$  the Stanton number and  $\delta$  a location in the buffer layer.

Assuming bubbles are spherical and leave the surface at diameter  $D_{lo}$ , they write:

$$\phi_e = \frac{1}{6} \pi D_{lo}^3 \rho_V h_{LV} f N_{sit} \quad (4.15)$$

$$(4.16)$$

with  $N_{sit}$  the nucleation site density and  $f$  the nucleation frequency.

The quenching heat flux occurring over the wait time  $t_w$  between two nucleated bubbles is computed following:

$$\phi_q = t_w f A_q \frac{2\lambda_L (T_w - T_{L,\delta})}{\sqrt{\pi \eta_L t_w}} \quad (4.17)$$

This expression corresponds to the time-average (over a time  $t_w$ ) conductive heat flux from a surface at  $T_w$  towards a semi-infinite liquid medium initially at  $T_{L,\delta}$  as expressed by Del Valle and Kenning [20].

They also estimate the portion of the surface affected by the bubbles as:

$$A_q = \min(1 ; F_A \pi R_{lo}^2 N_{sit}) = 1 - A_{c,L} \quad (4.18)$$

where  $F_A = 4$  accounts for the bubble area of influence when leaving the surface.

One of the main hypothesis of the model is also to suppose that the bubble departure frequency  $f$  is directly related to the wait time  $t_w$  by neglecting the bubble growth time as:

$$f = \frac{1}{t_w} \quad (4.19)$$

**Required closure relationships :**  $N_{sit}$ ,  $f$  (or  $t_w$ ),  $D_{lo}$

#### 4.3 BASU, WARRIER & DHIR (2005)

In 2005, Basu *et al.* [3, 4] proposed a new HFP model together with a series of experiments to further study the different closure relationships required in their approach. This model was meant to account for finer descriptions of the multiple phenomena at stake in subcooled flow boiling. In particular, they account for bubble sliding and merging and thus distinguish bubble departure diameter  $D_d$  (leaving the nucleation site) and lift-off diameter  $D_{lo}$  (leaving the wall).

Their approach consist of separating the boiling flow in three regions (Figure 4.2a):

- Pre-ONB zone, where only liquid forced convection occurs, yielding:

$$\phi_w = h_{c,L} (T_w - T_L) \quad (4.20)$$

- Zone between the ONB and the OSV, prior to observing a net amount of vapor with bubble lifting off the surface. The heat flux is still totally transferred to the liquid, but the equivalent convective heat transfer coefficient  $\bar{h}_{c,L}$  is supposed to be enhanced by 30% due to the presence of bubbles on the wall:

$$\phi_w = \bar{h}_{c,L} (T_w - T_L) \approx 1.3 h_{c,L} (T_w - T_L) \quad (4.21)$$

Basu *et al.* compute the ONB wall temperature as:

$$T_{w,ONB} = T_{sat} + \frac{4\sigma T_{sat}}{D_c \rho_V h_{LV}} \quad (4.22)$$

$$D_c = \sqrt{\frac{8\sigma T_{sat} \lambda_L}{\rho_V h_{LV} \phi_w}} (1 - \exp(-\theta^3 - 0.5\theta)) \quad (4.23)$$

where  $D_c$  represents the diameter of active cavities and  $\theta$  the static contact angle.

- Post-OSV zone, where bubbles now leave the surface towards the bulk flow and the other parts of the HFP appear *i.e.* the boiling and quenching fluxes. The beginning of OSV is defined by Basu *et al.* using a critical liquid temperature  $T_{L,OSV}$  as:

$$T_{L,OSV} = T_{sat} - 0.7 \exp \left( -0.065 \frac{D_d h_{c,L}}{\lambda_L} \right) \frac{\phi_w}{h_{c,L}} \quad (4.24)$$




Figure 4.2: Sketch of the heat transfer zones and bubble behavior considered by Basu *et al.*. (Adapted from [4])

The hypothesis of Basu *et al.* is that the heat flux is first transferred to the superheated liquid close to the wall (by convection and transient quenching), part of which contributing to the evaporation through the liquid-vapor interface. The remaining heat is transferred to the bulk liquid ( $\phi_L$ ) either from the superheated liquid layer or bubble condensation. The whole heat transfer mechanism thus writes:

$$\phi_w = \phi_{c,L} + \phi_q = \phi_e + \phi_L \quad (4.25)$$

In order to estimate the quenching heat flux associated to bubble sliding and lift-off, Basu *et al.* consider two cases:

- 1) Bubble sliding from departure ( $D = D_d$ ) to lift-off ( $D = D_{lo}$ ) ;
- 2) Bubble coalescence with neighboring sites before departure.

Those two cases are distinguished using the average distance between nucleation sites  $s$ , which they suppose equal to  $1/\sqrt{N_{sit}}$ .

#### 4.3.1 Case 1 : Bubble Sliding, $D_d < s$

In this case, the bubble will grow up to its departure diameter  $D_d$  and slide over a length  $l_{sl,0}$  before lifting-off. If  $l_{sl,0} < s$ , the bubble will slide up to its lift-off diameter  $D_{lo}$  and leave the wall without colliding with other bubbles. On the contrary, if  $l_{sl,0} \geq s$  the sliding bubble will merge with bubbles growing on their nucleation site, inducing a sudden growth of the bubble diameter that can exceed  $D_{lo}$  and thus trigger lift-off after sliding over a reduced length  $l_{sl} < l_{sl,0}$ . Those assumptions are summarized on Figure 4.2b.

If bubble coalescence occurs, the number of bubbles lifting-off the surface is lower than the actual number of nucleating sites. Basu *et al.* thus define a reduction factor:

$$R_f = \begin{cases} \frac{s}{l_{sl}} = \frac{1}{l_{sl}\sqrt{N_{sit}}} & \text{if } l_{sl,0} \geq s \\ 1 & \text{if } l_{sl,0} < s \end{cases} \quad (4.26)$$

Regarding bubble sizes, they suppose that bubbles coalesced by a sliding bubble while growing have a diameter  $D_d$  *i.e.* they were close to departure. This results in a bubble of diameter  $D = (D_{sl}^3 + D_d^3)^{1/3}$  which will trigger lift-off if  $D > D_{lo}$ . Consequently, a sliding bubble is allowed to merge with numerous bubbles before lifting off. Noting  $N_{merg}$  the number of coalesced bubble and  $D_N$  the resulting bubble diameter, the sliding distance is:

$$l_{sl} = N_{merg}s + l_{D_N \rightarrow D_{lo}} \quad (4.27)$$

where  $l_{D_N \rightarrow D_{lo}}$  is the remaining distance to slide if  $D_N < D_{lo}$ , being 0 if  $D_N \leq D_{lo}$ .

The surface swiped by the sliding bubble is then expressed as  $A_{sl} = C\bar{D}l_{sl}$  with  $\bar{D}$  the average bubble diameter during sliding and  $C$  the ratio between the bubble diameter and its foot, expressed based on measurements from Maity [69] as :

$$C = 1 - \exp(2 - \theta^{0.6}) \quad (4.28)$$

After observing in their experiments that  $D_d \approx 0.5D_{lo}$ , Basu *et al.* choose:

$$\bar{D} = \frac{D_{lo} + D_d}{2} \approx 0.75D_{lo} \quad (4.29)$$

Defining:

$$t^* = \left(\frac{\lambda_L}{h_{c,L}}\right)^2 \frac{1}{\pi\eta_L} \quad (4.30)$$

the time at which transient conduction heat transfer becomes equal to forced liquid convection, the resulting quenching heat transfer  $\phi_q$  is computed as:

$$\phi_q = \frac{1}{t_w + t_g} \int_0^T \frac{\lambda_L}{\sqrt{\pi\eta_L t}} (T_w - T_L) A_{sl} R_f N_{sit} dt \quad (4.31)$$

where  $T = t^*$  if  $t^* < t_w + t_g$  (forced convection dominates at some point during a nucleation cycle which total time is the wait time  $t_w$  plus the bubble growth time  $t_g$ ) or  $T = t_w + t_g$  if  $t^* \geq t_w + t_g$  (transient conduction dominates over the whole nucleation cycle).

The liquid convective heat transfer is therefore:

$$\phi_{c,L} = \overline{h_{c,L}} (T_w - T_L) A_{c,L} + \overline{h_{c,L}} (T_w - T_L) A_{sl} R_f N_{sit} \left(1 - \min\left(1 ; \frac{t^*}{t_w + t_g}\right)\right) \quad (4.32)$$

with  $A_{c,L} = 1 - A_{sl} R_f N_{sit}$  the wall area unaffected by bubbles.

The boiling heat flux is:

$$\phi_e = \rho_V h_{LV} \frac{\pi}{6} D_{lo}^3 R_f N_{sit} \frac{1}{t_w + t_g} \quad (4.33)$$

#### 4.3.2 Case 2 : Bubble Coalescence without Sliding, $D_d \geq s$

Under higher wall superheats, the subsequent rise in the nucleation site density  $N_{sit}$  can lead to boiling regimes where bubbles coalesce with each other at early stages of their lifetime *i.e.* while still attached to their nucleation site. This situation is accounted for by Basu *et al.* in the case when  $D_d \geq s$  by considering immediate lift-off of coalesced bubble at radius  $D > D_{lo}$ . In this case, the total density of bubbles leaving the surface is lower than  $N_{sit}$  and is thus reduced using:

$$R_f = \frac{s^3}{D_{lo}^3} \quad (4.34)$$

Under this massively coalescing regime, the entire surface will experience quenching due to bubble lift-off all over the heater. Depending on the values of  $t^*$ , we have:

$$\phi_q = \begin{cases} \frac{1}{t_w + t_g} \int_0^{t^*} \frac{\lambda_L}{\sqrt{\pi \eta_L t}} (T_w - T_L) dt & \text{if } t^* < t_w \\ \frac{1}{t_w + t_g} \left[ \int_0^{t_w} \frac{\lambda_L}{\sqrt{\pi \eta_L t}} (T_w - T_L) dt + \int_0^T \frac{\lambda_L}{\sqrt{\pi \eta_L t}} (T_w - T_L) [1 - S_b N_{sit}] dt \right] & \text{if } t^* \geq t_w \end{cases} \quad (4.35)$$

$$\phi_{c,L} = \begin{cases} \overline{h_{c,L}} (T_w - T_L) \frac{t_w - t^*}{t_w + t_g} + \overline{h_{c,L}} (T_w - T_L) [1 - A_b N_{sit}] \frac{t_g}{t_w + t_g} & \text{if } t^* < t_w \\ \overline{h_{c,L}} (T_w - T_L) [1 - A_b N_{sit}] \frac{t_w + t_g - t^*}{t_w + t_g} & \text{if } t^* \geq t_w \end{cases} \quad (4.36)$$

with  $A_b = \frac{\pi (Cs)^2}{4}$ .

The boiling heat flux still expressed as Eq. 4.33.

**Remark :** We can note that contrary to Kurul & Podowski model, the bubble nucleation frequency is computed without neglecting the bubble growth time  $t_g$  and is thus expressed as:

$$f = \frac{1}{t_g + t_w} \quad (4.37)$$

**Required closure relationships :**  $N_{sit}$ ,  $t_w$ ,  $t_g$ ,  $D_d$ ,  $D_{lo}$ ,  $l_{sl,0}$ ,  $h_{c,L}$ .

#### 4.4 GILMAN (2017)

A more recent HFP model dedicated to CFD simulations has been proposed in Gilman PhD work [35] and summarized in Gilman & Baglietto [36]. Among the different evolutions proposed in their work, we can mention:

- A probabilistic law to account for static interaction between nucleation sites ;
- A force-balance approach to compute the bubble departure and lift-off diameters ;
- A generic law for the enhanced forced convection coefficient accounting for bubble presence ;
- The presence of a modified quenching term accounting for local wall superheat beneath a bubble dry spot.

The total heat flux is partitioned between the liquid forced convection  $\phi_{c,L}$ , the solid quenching  $\phi_{q,s}$ , the quenching due to bubble sliding  $\phi_{q,sl}$  and the evaporation flux  $\phi_e$ . Yielding:

$$\phi_w = \phi_{c,L} + \phi_{q,s} + \phi_{q,sl} + \phi_e \quad (4.38)$$

The convective term is computed in a way similar to Basu *et al.* [4] in Eq. 4.32:

$$\phi_{c,L} = h_{c,L} (1 - A_{sl} N_{sit,a}) (T_w - T_L) + \overline{h_{c,L}} A_{sl} N_{sit,a} \left( 1 - \frac{t^*}{t_w + t_g} \right) (T_w - T_L) \quad (4.39)$$

where  $N_{sit,a}^*$  is the active nucleation site density that will generate sliding bubbles, that can differ from the empirical value of available sites  $N_{sit}$  usually computed by a correlation. The time  $t^*$  is the same time as in Eq. 4.30,  $A_{sl}$  the bubble sliding area,  $t_w$  and  $t_g$  respectively the wait and bubble growth times.




Figure 4.3: Heat Flux Partitioning considered by Gilman [35] (Adapted from [36]).

The actually active nucleation site density  $N_{sit,a}$  (that will generate bubbles) is considered by Gilman to be smaller than  $N_{sit}$  by considering a static interaction between the available sites *i.e.* the fact that a bubble laying on a site may be blocking nucleation from an other site laying beneath its foot. Following a so-called Complete Spatial Randomness (CSR) approach, they express the probability  $\mathcal{P}$  to find a site under a growing bubble of radius  $R_d$  as:

$$\mathcal{P} = 1 - e^{-N_b \pi R_d^2} \quad (4.40)$$

where  $N_b = \frac{t_g}{t_w + t_g} N_{sit} = t_g f N_{sit}$  is the density of bubbles covering the heated surface.

The number of active sites is then computed as:

$$N_{sit,a} = (1 - \mathcal{P}) N_{sit} = \exp\left(-\frac{t_g}{t_w + t_g} N_{sit} \pi R_d^2\right) N_{sit} \quad (4.41)$$

This value is then reduced by Gilman to obtain the density of sites generating sliding bubbles  $N_{sit,a}^*$  using a reduction factor accounting for sliding bubble coalescence (similar to Basu *et al.* in Eq. 4.26):

$$N_{sit,a}^* = R_f N_{sit,a} = \frac{s}{l_{sl,0} + s} N_{sit,a} \quad (4.42)$$

where  $l_{sl,0}$  is the sliding length of a single bubble and  $s = 1/\sqrt{N_{sit,a}}$ .

The sliding quenching term is also computed in a similar to Basu *et al.* as:

$$\phi_{q,sl} = \frac{2\lambda_L (T_w - T_L)}{\sqrt{\pi\eta_L t^*}} A_{sl} N_{sit,a}^* \quad (4.43)$$

$$A_{sl} = \overline{D} l_{sl} = \frac{D_d + D_{lo}}{2} (N_{merg}s + l_{D_N \rightarrow D_{lo}}) \quad (4.44)$$

Regarding the boiling heat flux, Gilman splits it in two contributions respectively associated with the inception of nucleation ( $\phi_{e,init}$ ) and liquid microlayer evaporation ( $\phi_{e,ML}$ ):

$$\phi_e = \phi_{e,init} + \phi_{e,ML} \quad (4.45)$$

$$= \frac{4}{3} \pi R_d^3 \rho_V h_{LV} \frac{1}{t_w + t_g} N_{sit,a} + V_{ML} \rho_L h_{LV} \frac{1}{t_w + t_g} N_{sit,a} \quad (4.46)$$

$$V_{ML} = \frac{2}{3} \pi \left(\frac{R_d}{2}\right)^3 \delta_{max} \quad (4.47)$$

where  $\delta_{max} = 2 \mu\text{m}$  is the largest bubble microlayer thickness based on experiments from Gerardi [33].

Finally, the solid quenching term is written as:

$$\phi_{q,s} = \rho_w c_{p,w} V_q \Delta T_q \frac{1}{t_g + t_w} N_{sit,a} \quad (4.48)$$

$$V_q = \frac{2}{3} \pi r_w^2 \quad (4.49)$$

with subscript  $w$  denoting the wall properties,  $r_w$  the dry patch radius and  $\Delta T_q = 2 K$  the extra wall superheat as suggested by Gerardi *et al.* [34].

**Required closure relationships :**  $N_{sit}$ ,  $t_w$ ,  $t_g$ ,  $D_d$ ,  $D_{lo}$ ,  $l_{sl,0}$ ,  $h_{c,L}$ ,  $\bar{h}_{c,L}$ .

#### 4.5 KOMMAJOSYULA (2020)

The last HFP model we will look through in this Chapter was proposed by Kommajosyula [56] in the continuation of Gilman [35] work. In particular, he proposed:

- A finer modeling of the bubble microlayer evaporation ;
- Simpler empirical correlations for closure parameters such as bubble departure diameter and wait time ;
- A modification of the probabilistic approach for the static interaction between sites.

The total heat flux is partitioned by Kommajosyula between four fluxes : the forced liquid convection  $\phi_{c,L}$ , the sliding conduction  $\phi_{q,sl}$ , the evaporation  $\phi_e$  and a direct convective flux to the vapor  $\phi_{vap}$ . Using the wall dry area  $S_{dry}$ , he writes:

$$\phi_w = (1 - S_{dry}) (\phi_{c,L} + \phi_{q,sl} + \phi_e) + S_{dry} \phi_{vap} \quad (4.50)$$

The liquid convective term is expressed as:

$$\phi_{c,L} = (1 - S_{sl}) h_{c,L} (T_w - T_L) \quad (4.51)$$

where  $S_{sl}$  is the surface covered by sliding bubbles.

Assuming that the transient conduction during quenching operates during the time  $t^*$  (Eq. 4.30), Kommajosyula rewrites the total quenching flux using the forced-convection heat transfer coefficient as:

$$\phi_{q,sl} = 2h_{c,L} A_{sl} N_{sit,a} \frac{t^*}{t_g + t_w} (T_w - T_L) \quad (4.52)$$

$$A_{sl} = \frac{1}{\sqrt{N_{sit,a}}} \frac{D_d + D_{lo}}{2} \quad (4.53)$$

with  $N_{sit,a}$  the active nucleation site density,  $D_d$  and  $D_{lo}$  respectively the bubble departure and lift-off diameters.

The total sliding surface is then expressed as:

$$S_{sl} = \min (1 ; A_{sl} N_{sit,a} t^* f) \quad (4.54)$$

The evaporation heat flux is based on Gilman approach by splitting it between inception and microlayer evaporation:

$$\phi_e = \phi_{e,init} + \phi_{e,ML} \quad (4.55)$$

$$= \frac{4}{3} \pi \left( \frac{D_{init}}{2} \right)^3 \rho_V h_{LV} f N_{sit,a} + V_{ML} \rho_V h_{LV} f N_b \quad (4.56)$$

The microlayer terms are modeled based on the contact angle  $\theta$  and the capillary number  $\text{Ca} = \frac{\mu_L U_b}{\sigma}$ , where  $U_b$  is the bubble interface velocity, as:

$$D_{init} = D_d \max(1 ; 0.1237 \text{Ca}^{-0.373} \sin(\theta)) \quad (4.57)$$

$$V_{ML} = \delta_{ML} D_{ML}^2 \frac{\pi}{12} \left( 2 - \left( \frac{D_{dry}}{D_{ML}} \right)^2 - \frac{D_{dry}}{D_{ML}} \right) \quad (4.58)$$

with  $D_{ML} = D_{init}/2$  and  $\frac{D_{dry}}{D_{ML}} = \max(1 ; 0.1237 \text{Ca}^{-0.373} \sin(\theta))$ .

The microlayer thickness  $\delta_{ML}$  is expressed as:

$$\delta_{ML} = 4 \times 10^{-6} \sqrt{\frac{\text{Ca}}{\text{Ca}_0}} \quad (4.59)$$

with  $\text{Ca}_0 = 2.16 \times 10^{-4} \Delta T_w^{1.216}$ .

The active nucleation site density  $N_{sit,a}$  is computed based on the Complete Spatial Randomness approach proposed by Gilman. However, it is expressed using Lambert's W-function  $\mathcal{W}$  as:

$$N_{sit,a} = \frac{\mathcal{W}\left(f t_g \pi \frac{D_d^2}{4} N_{sit}\right)}{f t_g \pi \frac{D_d^2}{4}} \quad (4.60)$$

with  $\mathcal{W}$  being approximated to avoid an implicit solving of this equation.

**Required closure relationships :**  $N_{sit}$ ,  $t_w$ ,  $t_g$ ,  $D_d$ ,  $D_{lo}$ ,  $h_{c,L}$ .

## 4.6 CONCLUSION

As we have seen, the HFP approach is widely studied since decades and is still an active field of work to hopefully reach an exhaustive and precise modeling of all the heat transfer phenomena that are at stake in wall boiling. While most models are similar to each other regarding terms such as single-phase convection or transient conduction heat transfer, they may differ in their methods to account for bubble sliding, microlayer evaporation or modeling of the bubble nucleation cycle.

Moreover, each of those approaches requires a certain number of closure laws to compute important physical parameters among which we can in particular cite:

- The nucleation site density  $N_{sit}$  ;
- The bubble nucleation period / frequency :  $f = \frac{1}{t_g + t_w}$  ;
- The bubble departure and lift-off diameters  $D_d$  and  $D_{lo}$ .

In this global framework, we will propose the development of a new HFP model by first trying to have a close look at boiling bubble dynamics to propose an acceptable modeling of a bubble lifetime growing and sliding on the wall (Chapter 5). Then, we will tackle the problem of the closure laws aiming to compute important yet highly uncertain parameters ( $N_{sit}$ ,  $t_w$ , etc.) before proposing a final formulation for the HFP that will be compared to experimental measurements (Chapter 6). In order to complete the description of the aforementioned models, we will highlight throughout the development when a given closure law is used in one of the presented models.

# 5

---

## BOILING BUBBLE DYNAMICS

---

### Contents

5.1	Introduction . . . . .	47
5.1.1	Experimental Insights . . . . .	47
5.1.2	Existing Approaches . . . . .	49
5.2	Bubble Force Balance in Vertical Flow Boiling . . . . .	53
5.2.1	Introduction . . . . .	53
5.2.2	General Considerations . . . . .	54
5.2.3	Buoyancy and Contact Pressure Force . . . . .	55
5.2.4	Capillary Force . . . . .	55
5.2.5	Drag and Lift Forces . . . . .	56
5.2.6	Inertia Force . . . . .	61
5.2.7	Force Balance Summary . . . . .	63
5.2.8	Liquid Velocity . . . . .	64
5.3	Bubble Growth . . . . .	66
5.3.1	Introduction . . . . .	66
5.3.2	Heat Diffusion in Uniformly Superheated Liquid . . . . .	66
5.3.3	Microlayer Evaporation . . . . .	67
5.3.4	Bubble Growth in Subcooled Flow Boiling . . . . .	68
5.3.5	Analytic Approach of Bubble Growth in a Linear Thermal Boundary Layer . . . . .	69
5.3.6	Comparison with DNS Results . . . . .	72
5.3.7	Comparison with Experimental Measurements . . . . .	72
5.3.8	Conclusions on Bubble Growth Modeling . . . . .	75
5.4	Departure by Sliding . . . . .	75
5.4.1	Non-Dimensional Analysis . . . . .	75
5.4.2	Application to Experimental Data . . . . .	77
5.4.3	Departure Diameter Prediction . . . . .	79
5.4.4	Discussion and accounting for parameters uncertainties . . . . .	81
5.5	Sliding phase . . . . .	83
5.5.1	Modeling . . . . .	83
5.5.2	Low Pressure Sliding . . . . .	84
5.5.3	High Pressure Sliding . . . . .	84
5.5.4	Comparison of Forces in Sliding Stage . . . . .	85
5.6	Bubble Lift-Off . . . . .	86
5.6.1	Introduction . . . . .	86
5.6.2	Experimental Measurements of Lift-Off Diameter . . . . .	90
5.6.3	Influence of the Flow Boiling Conditions . . . . .	90
5.6.4	Predicting the Lift-Off with a Force Balance . . . . .	91
5.6.5	A Simple Non-Dimensional Correlation . . . . .	94
5.6.6	Conclusion on the Lift-Off . . . . .	94
5.7	Conclusion . . . . .	95

---


## 5.1 INTRODUCTION

Dynamics of boiling bubbles is playing an important role in the Heat Flux Partitioning models. For instance, the evaporation heat flux  $\phi_e$  is directly proportional to the bubble lift-off radius  $R_{lo}$  4.16 while the quenching heat flux  $\phi_q$  depends on the wall area visited by a bubble  $A_{q,1b}$  (Eq. 4.43) which depends on the bubble sliding length  $l_{sl}$ , departure radius  $R_d$  and lift-off radius  $R_{lo}$ .


### 5.1.1 Experimental Insights

Consequently, many experimental investigations have been conducted to further understand the behavior of nucleated bubbles on a wall of a liquid flow. In the case of vertical flow boiling, a typical bubble life cycle can be described as follows:

- Beginning of nucleation, growth while attached to the nucleation site ;
- Detachment occurring when the bubble has a radius  $R_d$ , from which the bubble will start to slide and accelerate along the wall while continuing to grow ;
- Lift-off from the wall when the bubble reaches a radius  $R_{lo}$  after sliding over a length  $l_{sl}$ .



(a) Bubble sliding visualized and adapted from Maity [69] at atmospheric pressure.



(b) Bubble sliding visualized and adapted from Kossolapov [57] at higher pressure.

Figure 5.1: Visualization of bubble sliding at various pressures.

This behavior has been supported by many experimental observations who clearly observed three stages (departure, sliding, lift-off) both at low pressure (Maity [69], Situ [97], Thorncroft [104], Prodanovic [84], Chen [10], Ren [88], etc.) and high pressure (March [71], Kossolapov [57]). Altogether, those works cover various flow conditions and operating fluids which demonstrate the dominance of this bubble behavior in vertical flow boiling. Examples from the literature of visualizations of bubble sliding at atmospheric and high pressure are reproduced on Figure 5.1.

The bubble sliding process has also been thermally studied to quantify its impact on the wall heat transfer. Estrada-Perez *et al.* [27] observed the significant thermal impact of sliding bubbles footprints. Kossolapov [57] also investigated the sliding of boiling bubbles and measured the magnitude of the transient heat transfer induced by the disruption of the liquid thermal boundary layer in the bubble's wake. Typical experimental observations from those works are reproduced on Figure 5.2




Figure 5.2: Visualization of bubble sliding thermal impact.

Those experimental observations highlight the significant magnitude of the transient heat transfer triggered by bubble movement on the wall that can represent up to 40% of the total wall heat flux [57]. All the aforementioned observations are summed-up on Figure 5.3.




Figure 5.3: Sketch of a typical bubble lifetime in vertical flow boiling. Left depicts a typical side view of the heater with identification of departure, sliding and lift-off. Right depicts a top view of the heater, exhibiting the area that will undergo transient heat transfer.

Predicting the HFP in vertical flow boiling thus requires a description of single bubble dynamics that includes accurate estimations of bubble departure and lift-off radii  $R_d$  and  $R_{lo}$  as well as bubble sliding velocity  $\overline{U_b}$  to predict the sliding length  $l_{sl}$ .

### 5.1.2 Existing Approaches

#### 5.1.2.1 Departure / Lift-Off Diameters

Historically, first approaches to estimate the bubble diameter consisted of experimental-based correlations for pool boiling of horizontal surfaces through photographic studies. In those cases, departure from the nucleation site coincides with the bubble lift-off. Among the mainly used in HFP models and CFD, we can mention the law of Tolubinsky & Kostanchuk (1970)[106] that estimates the lift-off diameter  $D_{lo}$  based on the local liquid subcooling  $\Delta T_L = T_{sat} - T_L$  with  $T_L$  the liquid temperature:

$$D_{lo} = D_0 e^{-\Delta T_L/45}, \quad D_0 = 15\text{mm} \quad (5.1)$$

On the other hand, authors such as Cole & Rohsenow (1968) (mentioned in [54]) proposed relationships including the influence of pressure through the capillary length  $L_c = \sqrt{\frac{\sigma}{g(\rho_L - \rho_V)}}$ :

$$D_{lo} = CL_c \left( \frac{\rho_L c_{p,L} T_{sat}}{\rho_V h_{LV}} \right)^{5/4} \quad (5.2)$$

$C = 1.5 \times 10^{-4}$  for water and  $4.65 \times 10^{-4}$  otherwise.

This equations provides a good trend for the evolution of bubble departure diameter with pressure for pool boiling as shown by Kossolapov [57].

More recently, the developments around HFP models has lead meany researchers to propose dedicated correlations for bubble departure or lift-off diameter. For instance, Zhou *et al.* (2021) [120] proposed simple correlations for the departure and lift-off diameter in horizontal flow boiling at low pressure based on their experiments:

$$\frac{D_d}{L_o} = 10^{2.4086} \left( \frac{\rho_V}{\rho_L} \right)^{-0.6613} \text{Ja}_w^*^{0.1557} \text{Ja}_L^*^{-0.01592} \text{Re}_{L_o}^{-0.6647} \text{Pr}_L^{-1.8477} \sin(\theta_s)^{0.4} \quad (5.3)$$

$$\frac{D_{lo}}{L_c} = 10^{-1.1990} \left( \frac{\rho_V}{\rho_L} \right)^{-0.9785} \text{Ja}_w^*^{0.1435} \text{Ja}_L^*^{-0.0119} \text{Re}_{L_c}^{-0.5129} \text{Pr}_L^{-1.8784} \quad (5.4)$$

with the Reynolds numbers based on  $L_o = \frac{\rho_L \nu_L^2}{\sigma}$  and  $L_c$  the capillary length, and  $\text{Ja}^* = \frac{\rho_L c_{p,L}}{h_{LV}}$  reduced Jakob numbers that do not inclued the density ratio.

In the case of vertical flow boiling, Ünal (1976)[124] derived a correlation based on semi-analytical approach of the heat transfer mechanisms around a bubble to estimate its maximum diameter, including simultaneous influences of pressure, heater material, liquid velocity and subcooling:

$$D_{lo} = 2.42 \times 10^{-5} P^{0.709} \frac{a}{\sqrt{b\varphi}} \quad (5.5)$$

$$a = \frac{\Delta T_w \lambda_w}{2\rho_V h_{LV} \sqrt{\pi \eta_w}}$$

$$b = \frac{\Delta T_L}{2(1 - \rho_V/\rho_L)}$$

$$\varphi = \max \left( 1 ; \left( \frac{U_L}{U_0} \right)^{0.47} \right), \quad U_0 = 0.61 \text{ m/s}$$

Ünal validated his law against several measurements from the literature covering pressures from 1 to 177 bars, liquid velocities from 0.08 to 9.15 m/s, subcoolings from 3 to 86K and heat fluxes from 0.47 to 10.64 MW/m<sup>2</sup>.

**Note :** The law of Ünal is used in the HFP model of Kurul & Podowski. It as also implemented in NEPTUNE\_CFD and includes a correction of Borée *et al.* (Eq. ??) to avoid divergence in bubble diameter when reaching saturated conditions.

In the framework of their HEP model development, Basu *et al.* fitted expressions for  $D_d$  and  $D_{lo}$  based on their own measurements in vertical flow boiling at atmospheric pressure:

$$\frac{D_d}{L_c} = 1.3 \sin(\theta_s)^{0.4} [0.13 e^{-1.75 \times 10^{-4} Re_{L,D_h}} + 0.005] Ja_w^{0.45} e^{-0.0065 Ja_L} \quad (5.6)$$

$$\frac{D_{lo}}{L_c} = 1.3 \sin(\theta_s)^{0.4} [0.2 e^{-1.28 \times 10^{-4} Re_{L,D_h}} + 0.005] Ja_w^{0.45} e^{-0.0065 Ja_L} \quad (5.7)$$

They were validated for  $14 \leq Ja_w \leq 56$ ,  $1 \leq Ja_L \leq 138$ ,  $0 \leq Re_{L,D_h} \leq 7980$  and  $30^\circ \leq \theta_s \leq 90^\circ$ .

**Note :** Basu *et al.* use these own-developed laws in their HFP formulation to estimate bubble diameters.

Similarly, Kommajosyula[56] gathered several bubble departure and lift-off diameter measurements from the literature (both in vertical and horizontal boiling) and proposed the following reduced correlation:

$$D_d = 18.9 \times 10^{-6} \left( \frac{\rho_L - \rho_V}{\rho_V} \right)^{0.27} Ja_w^{0.75} (1 + Ja_L)^{-0.3} U_{L,bulk}^{-0.26} \quad (5.8)$$

$$D_{lo} = 1.2 D_d \quad (5.9)$$

**Note :** This formulation is used in Kommajosyula's HFP model. Having a proportionality between  $D_d$  and  $D_{lo}$  allows the comparison with a database gathering both departure and lift-off diameter measurements.

Although this law presents coherent trends with flow conditions, the raw presence of  $U_{L,bulk}$  in the expression is questionable because:

- The relationship is not dimensionless and the constant  $18.9 \times 10^{-6}$  must be in  $m^{1.26} \cdot s^{-0.26}$  ;
- The negative exponent will yield diverging values when reaching pool boiling conditions, which is physically inconsistent.

### 5.1.2.2 Sliding Length and Velocity

Regarding bubble sliding phase, one of the most used correlations to predict bubble diameter evolution has been developed by Maity [69]. Based on atmospheric pressure visualization of boiling single bubbles in water, it predicts the resulting sliding diameter  $D_{sl}$  provided a sliding time  $t_{sl}$  and an arbitrary initial diameter  $D_{in}$  (not obligatorily the departure diameter) through:

$$\frac{(D_{sl}^2 - D_{in}^2)}{t_{sl} \eta_L Ja_w} = \frac{1}{15 (0.015 + 0.023 Re_b^{0.5}) (0.04 + 0.023 Ja_L^{0.5})} \quad (5.10)$$

where  $Re_b = \frac{U_L D_b}{\nu_L}$

Using Maity measurements of bubble sliding velocity, Basu *et al.* proposed an estimation of the sliding distance for a single bubble  $l_{sl,0}$ :

$$l_{sl,0} = \int_0^{t_{sl}} U_b dt = \int_0^{t_{sl}} C_U \sqrt{t} dt = \frac{2}{3} C_U t_{sl}^{3/2} \quad (5.11)$$

$$C_U = 3.2 U_L + 1 \quad (5.12)$$

where  $C_U$  represents a correlated acceleration coefficient.

**Note :** Basu *et al.* use this correlation along with Eq. 5.10 in their model to estimate the bubble sliding and growth.

The estimation of the bubble sliding velocity through an explicit correlation is difficult since it varies over the bubble lifetime. Therefore, some authors simply suppose that  $U_b = U_L$  such as Gilman & Baglietto who also use Eq. 5.10 for the sliding growth.

Other assumptions regarding the sliding length relies on the value of the bubble-generating site density on the heater  $N_{sit,a}$ . Supposing that bubbles usually lift-off after sliding a distance between two active sites gives:

$$l_{sl} = \frac{1}{\sqrt{N_{bub}}} \quad (5.13)$$

**Note :** This modeling choice is made by Kommajosyula.

### 5.1.2.3 Conclusion on Correlations

Albeit proposing coherent trend with the flow boiling conditions along with good estimations of the desired parameters on given experimental datasets, explicit correlations inherently include a limited range of application. Moreover, the constant increase of the number of works proposing data-fitted laws makes the selection of a proper relationship a complicated matter due to their potential lack of generality.

To try to overcome this drawback and come up with more generalized models, researchers have explored an alternative approach by developing Mechanistic Models based on a force-balance to precisely depict the external efforts experienced by the growing bubble. The goal is to compute the sum of the forces applied to the bubble over its growing time and to detect departure and lift-off events using associated criteria such as a change in the force balance sign. This will be the subject of the next section.

As a summary, we gather the presented correlations on Table 5.1.

Bubble Departure Diameter	
Author (Year)	Correlation
Basu <i>et al.</i> (2005)	$\frac{D_d}{L_c} = 1.3 \sin(\theta_s)^{0.4} \left[ 0.13 e^{-1.75 \times 10^{-4} \text{Re}_{L,D_h}} + 0.005 \right] \text{Ja}_w^{0.45} e^{-0.0065 \text{Ja}_L}$ $L_c = \sqrt{\frac{\sigma}{g(\rho_L - \rho_V)}}$
Kommajosyula (2020)	$D_d = 18.9 \times 10^{-6} \left( \frac{\rho_L - \rho_V}{\rho_V} \right)^{0.27} \text{Ja}_w^{0.75} (1 + \text{Ja}_L)^{-0.3} U_{L,bulk}^{-0.26}$
Zhou (2021)	$\frac{D_d}{L_o} = 10^{2.4086} \left( \frac{\rho_V}{\rho_L} \right)^{-0.6613} \text{Ja}_w^{*0.1557} \text{Ja}_L^{*-0.01592} \text{Re}_{L_o}^{-0.6647} \text{Pr}_L^{-1.8477} \sin(\theta_s)^{0.4}$ $L_o = \frac{\rho_L \nu_L^2}{\sigma}$
Bubble Lift-Off Diameter	
Author (Year)	Correlation
Tolubinsky & Kostanchuk (1970)	$D_{lo} = D_0 e^{-\Delta T_L / 45}, D_0 = 15 \text{mm}$
Cole & Rohsenow (1968)	$D_{lo} = CL_c \left( \frac{\rho_L c_{p,L} T_{sat}}{\rho_V h_{LV}} \right)^{5/4}$ $C = 1.5 \times 10^{-4} \text{ (water)} \text{ or } 4.65 \times 10^{-4} \text{ (other)}, L_c = \sqrt{\frac{\sigma}{g(\rho_L - \rho_V)}}$
Ünal (1976)	$D_{lo} = 2.42 \times 10^{-5} P^{0.709} \frac{a}{\sqrt{b\varphi}}, a = \frac{\Delta T_w \lambda_w}{2\rho_V h_{LV} \sqrt{\pi \eta_w}}$ $b = \frac{\Delta T_L}{2(1 - \rho_V/\rho_L)}, \varphi = \max \left( 1 ; \left( \frac{U_L}{U_0} \right)^{0.47} \right), U_0 = 0.61 \text{ m/s}$
Basu <i>et al.</i> (2005)	$\frac{D_{lo}}{L_c} = 1.3 \sin(\theta_s)^{0.4} \left[ 0.2 e^{-1.28 \times 10^{-4} \text{Re}_{L,D_h}} + 0.005 \right] \text{Ja}_w^{0.45} e^{-0.0065 \text{Ja}_L}$ $L_c = \sqrt{\frac{\sigma}{g(\rho_L - \rho_V)}}$
Kommajosyula (2020)	$D_{lo} = 1.2 D_d$
Zhou (2021)	$\frac{D_{lo}}{L_c} = 10^{-1.1990} \left( \frac{\rho_V}{\rho_L} \right)^{-0.9785} \text{Ja}_w^{*0.1435} \text{Ja}_L^{*-0.0119} \text{Re}_{L_c}^{-0.5129} \text{Pr}_L^{-1.8784}$ $L_c = \sqrt{\frac{\sigma}{g(\rho_L - \rho_V)}}$
Sliding Length, Diameter and Velocity	
Author (Year)	Correlation
Maity (2000)	$\frac{(D_{sl}^2 - D_{in}^2)}{t_{sl} \eta_L \text{Ja}_w} = \left[ 15 \left( 0.015 + 0.023 \text{Re}_b^{0.5} \right) \left( 0.04 + 0.023 \text{Ja}_L^{0.5} \right) \right]^{-1}$ $\text{Re}_b = \frac{U_L D_b}{\nu_L}$
Basu <i>et al.</i> (2005)	$l_{sl,0} = \frac{2}{3} C_U t_{sl}^{3/2}, C_U = 3.2 U_L + 1$
Bubble Density Average Distance	$l_{sl} = \frac{1}{\sqrt{N_{bub}}}$

Table 5.1: Summary of the presented correlations

## 5.2 BUBBLE FORCE BALANCE IN VERTICAL FLOW BOILING

### 5.2.1 Introduction

The derivation of the force balance over a growing bubble on a wall in a liquid flow is a very complicated problem that many researchers have tried to tackle over the past decades. Many theoretical and numerical approaches have been conducted to estimate the forces at stake in bubble dynamics and sometimes compared to experimental visualization of bubbles in movement.

Among the first propositions of the whole force-balance closure, the work of Klausner *et al.* in 1993 [53] is probably among the most referred to. They proposed a tentatively complete force-balance for a growing bubble in a boiling flow and supposed that departure from the nucleation site is reached when the force balance becomes positive either in the direction of the flow or perpendicular to the wall. They validated their approach against measurements for horizontal flow boiling of refrigerant R113.

In the same framework, many subsequent works were published such as:

- Van Helden *et al.* [110] (1995) who assessed forces coefficients using injected air bubbles in a vertical flow ;
- Thorncroft *et al.* [104, 105] (1998, 2001) who conducted experiments on horizontal and vertical flow boiling of R113 while proposing more general formulations of the force balance that were used to predict bubble diameter measurements ;
- Duhar & Colin [26] (2006) who validated a force balance on bubbles created by air injection in a shear flow. They extended their work with boiling N-pentane experiments and studied the growth and detachment of single bubbles [24] ;
- Van Der Geld (2009) [32] used potential flow theory to analytically derive the force balance for deforming bubbles near a plane ;
- Sugrue *et al.* (2014) [100] conducted measurements on boiling bubble for water at atmospheric pressure and various surface orientations. Their measurements were then used to validate a force-balance approach predicting bubble departure by sliding [99] ;
- Mazzocco *et al.* (2018) [72] gathered several measurements of bubble departure and lift-off diameters and proposed a reassessed force-balance approach including new drag coefficient and growth law to achieve predictions with a reasonable accuracy over the database ;
- Ren *et al.* (2020) [88] measured bubble departure diameter for vertical flow boiling of water up to 5 bars which they used to validate a force-balance model.

While not exhaustive, this list aims to show that force-balance modeling has become an increasingly interesting approach for authors. It is though not exempted of limitations because each force requires a proper modeling which needs sometimes to go through empirical choices as we will later discuss. This drawback is particularly noted by Bucci *et al.* [7] who points out that traditional force balances are not equal to zero when the bubble is immobile. On the other hand, they show that this is not due to the absence of unknown forces in the balance but rather associated to the computation of well-known forces such as capillary forces. Moreover, Duhar & Colin [26] managed to reach a zero total balance for their air-injected bubbles, and emphasized the interest of force modeling to deeper understand the physical phenomena behind bubble dynamics. The difficulty to close the balance of the forces in the case of a boiling bubble is due to the approximated expression of the forces which expressions are expected to be more complicated in the case of a phase change compared to air injection.

Each of the previously listed models proposed different upgrades and modifications to the force balance over the bubble. Unfortunately, they were all validated using low pressure experiments due to the lack of pressurized measurements in the literature. In addition, the mentioned common use of empirical parameters makes it difficult to reach a general validation of those models as we will see.

**Note :** The HFP model of Gilman & Baglietto [36] is based on such a force balance for departure and lift-off prediction.

In this section, we aim to propose an update of the bubble force balance for vertical flow boiling with a reduced empiricism and to cover the whole bubble lifetime (departure, sliding, lift-off) while achieving a larger generality by including pressurized measurements up to 40 bar conducted by Kossolapov [57].

### 5.2.2 General Considerations

When trying to derive the force balance over a bubble, the first step consists of splitting the whole effort experienced by the bubble between different contributions depending on their nature. In our case, we focus on a bubble growing on a vertical wall and facing an upward flow as depicted in Figure 5.4.

The static forces are :

- The buoyancy force  $\overline{F_B}$ , including Archimedes force and the weight of the bubble ;
- The capillary or surface tension force  $\overline{F_C}$  ;
- The contact pressure force  $\overline{F_{CP}}$ .

The hydrodynamic forces are :

- The drag and lift forces  $\overline{F_D}$  and  $\overline{F_L}$  ;
- The inertia force  $\overline{F_I}$ , including added-mass and Tchen force.




Figure 5.4: Sketch of the forces applied to the bubble facing an upward flow  $\overline{U_L}$  and sliding at velocity  $\overline{U_b}$

Regarding the bubble shape, we consider a quasi-spherical bubble of radius  $R$  with a circular contact area with the wall of radius  $r_w$ .

**Remark :** This assumption is mainly supported for high pressure boiling where bubble elongation and deformation is not observed [57]. At lower pressure, the bubble shape can somewhat deviate from a spherical shape especially before lift-off. It seems however reasonably quasi-spherical at early growth stages [69].

The bubble has a static contact angle  $\theta$  and is tilted under the influence of the flow by an inclination angle  $d\theta$  (half the total angle hysteresis). The resulting downstream and upstream contact angles are therefore  $\theta_d = \theta - d\theta$  and  $\theta_u = \theta + d\theta$ . If the bubble has a shape close to a truncated sphere, we can approximate the bubble foot radius as:

$$r_w \approx R \sin \left( \frac{\theta_u + \theta_d}{2} \right) = R \sin (\theta) \quad (5.14)$$

Some authors rather take  $r_w \approx \frac{1}{2}R (\sin(\theta_u) + \sin(\theta_d)) = R \sin(\theta) \cos(d\theta)$ , however this expression tends to zero when reaching  $d\theta \rightarrow 90^\circ$  which is undesirable regarding the expression of forces such as Contact Pressure and Surface Tension.

We suppose  $V_b \approx \frac{4}{3}\pi R^3$  for the bubble volume.

### 5.2.3 Buoyancy and Contact Pressure Force

Following the work of Thorncroft *et al.* [105] and Duhar & Colin [26], the global force balance for a bubble growing on a wall can be written as:

$$\underbrace{\frac{4}{3}\pi R^3 \rho_V \bar{g}}_{\text{Bubble weight}} + \overline{F_C} - \underbrace{\int_{S_b} (P_L - \rho_L g z) \bar{n} \, dS}_{\text{Outer liquid pressure}} - \underbrace{\int_{S_w} P_V \bar{n} \, dS}_{\text{Inner vapor pressure}} + \underbrace{\int_{S_b} \overline{\tau_L} \cdot \bar{n}}_{\text{Viscous efforts}} = \bar{0} \quad (5.15)$$

where  $\bar{n}$  is the local normal unity vector,  $S_b$  is the bubble surface facing the liquid,  $S_w$  the wall-contact area and  $\overline{\tau_L}$  the deviatoric stress tensor associated to viscous effects.

Re-writing the two pressure integrals versus the liquid pressure at the wall  $P_0$  yields:

$$\begin{aligned} - \int_{S_b} (P_L - \rho_L g z) \bar{n} \, dS - \int_{S_w} P_V \bar{n} \, dS &= - \int_{S_b + S_w} (P_0 - \rho_L g z) \bar{n} \, dS + \int_{S_w} (P_0 - \rho_L g z - P_V) \bar{n} \, dS \\ &\quad - \int_{S_b} (P_L - P_0) \bar{n} \, dS \\ &= \int_{S_b + S_w} \rho_L g z \bar{n} \, dS + \int_{S_w} (P_0 - P_V) \bar{n} \, dS \\ &\quad - \int_{S_b} (P_L - P_0) \bar{n} \, dS \end{aligned} \quad (5.16)$$

Summing the first term on the RHS of Eq. 5.16 with the bubble weight results in the buoyancy force:

$$\overline{F_B} = V_b (\rho_V - \rho_L) \bar{g} = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) g \bar{e}_x \quad (5.17)$$

The second term of Eq. 5.16 is the so-called "contact pressure force" and can be expressed versus the difference of liquid and vapor pressure at the bubble top:

$$\int_{S_w} (P_0 - P_V) \bar{n} \, dS = (P_0 - P_V) \pi r_w^2 \bar{e}_y \quad (5.18)$$

$$= (P_L - P_V - \rho_L g h) \pi r_w^2 \bar{e}_y \quad (5.19)$$

where  $P_L$  is the liquid pressure at the bubble top and  $h$  the bubble height.

Using Laplace's equation  $\Delta P = 2\sigma/R_c$  and assuming that  $\rho_L g h \ll \Delta P$  yields:

$$\overline{F_{CP}} \approx \frac{2\sigma}{R_c} \pi r_w^2 \bar{e}_y \approx \pi R \sigma 2 \sin(\theta)^2 \bar{e}_y \quad (5.20)$$

Here,  $R_c$  is the curvature radius of the bubble which is often assumed to be equal to  $5R$  [53, 72, 99] without other explanation than avoiding an overestimation of the contact pressure force. To avoid this arbitrary choice, following the hypothesis of a nearly spherical bubble shape gives  $R_c = R$ .

### 5.2.4 Capillary Force

The capillary force acts at the triple contact line at the bubble's foot and is an important adhesive force maintaining the bubble attached to the wall. Its derivation can be done by integration of the effort exerted over the triple contact line. Noting  $\Phi$  the polar angle around the bubble foot, we have :

$$\overline{F_C} = 2 \int_0^\pi \sigma r_w \bar{\tau}(\Phi) \, d\Phi \quad (5.21)$$

where  $\bar{\tau}$  is the unit vector tangent to the interface and perpendicular to the contact line.

To compute the resulting components parallel and tangent to the wall, Klausner *et al.* [53] account for a contact angle difference between the upstream (receding) contact angle  $\theta_u$  and downstream (advancing) contact angle  $\theta_d$ . If the local contact angle is noted  $\gamma$ , then:

$$\bar{\tau}(\Phi) = \cos(\gamma) \cos(\Phi) \bar{e}_x + \sin(\gamma) \bar{e}_y \quad (5.22)$$

Then representing the evolution of the local contact angle  $\gamma$  from  $\theta_u$  to  $\theta_d$  using a polynomial expression of degree 3:

$$\gamma(\Phi) = \theta_d + (\theta_u - \theta_d) \left[ 3 \left( \frac{\Phi}{\pi} \right)^2 - 2 \left( \frac{\Phi}{\pi} \right)^3 \right], \quad 0 \leq \Phi \leq \pi \quad (5.23)$$

which verifies symmetry conditions:

$$\gamma'(0) = \theta_d, \quad \gamma(\pi) = \theta_u, \quad \gamma'(0) = \gamma'(\pi) = 0 \quad (5.24)$$

To obtain analytic expression, Klausner *et al.* also consider a first order linear interpolation:

$$\gamma(\Phi) = \theta_d + (\theta_u - \theta_d) \frac{\Phi}{\pi} \quad (5.25)$$

This yields:

$$\bar{F}_C = -2r_w \sigma \frac{\pi(\theta_u - \theta_d)}{\pi^2 - (\theta_u - \theta_d)^2} (\sin(\theta_u) + \sin(\theta_d)) \bar{e}_x - 2r_w \sigma \frac{\pi}{\theta_u - \theta_d} (\cos(\theta_d) - \cos(\theta_u)) \bar{e}_y \quad (5.26)$$

By comparing the analytic expression of Eq. 5.26 with the values obtained by numerical integration of Eq. 5.23, Klausner *et al.* introduce a correction factor of 1.25 over the  $x$  component, finally giving :

$$\bar{F}_C = -2.5r_w \sigma \frac{\pi(\theta_u - \theta_d)}{\pi^2 - (\theta_u - \theta_d)^2} (\sin(\theta_u) + \sin(\theta_d)) \bar{e}_x - 2r_w \sigma \frac{\pi}{\theta_u - \theta_d} (\cos(\theta_d) - \cos(\theta_u)) \bar{e}_y \quad (5.27)$$

$$= -\pi R \sigma \underbrace{\left[ 2.5 \frac{r_w}{R} \frac{d\theta}{\left( \frac{\pi}{2} \right)^2 - d\theta^2} \sin(\theta) \cos(d\theta) \right]}_{f_{C,x}} \bar{e}_x - \pi R \sigma \underbrace{\left[ 2 \frac{r_w}{R} \sin(\theta) \frac{\sin(d\theta)}{d\theta} \right]}_{f_{C,y}} \bar{e}_y \quad (5.28)$$

**Remark :** We can see that  $f_{C,x} \rightarrow 0$  and  $f_{C,y} \rightarrow 2 \frac{r_w}{R} \sin(\theta)$  when  $d\theta \rightarrow 0$ . In that case,  $\bar{F}_C = -\bar{F}_{CP}$ .

## 5.2.5 Drag and Lift Forces

The external liquid flow over the bubble induces the well-known drag and lift forces, acting respectively in the flow direction and perpendicular to the flow. They are usually expressed using associated coefficients  $C_D$  and  $C_L$  defined by:

$$\bar{F}_D = \frac{1}{2} C_D \rho_L S_p \|\bar{U}_L - \bar{U}_b\| (\bar{U}_L - \bar{U}_b) \quad (5.29)$$

$$\bar{F}_L = \frac{1}{2} C_L \rho_L S_p \|\bar{U}_L - \bar{U}_b\|^2 \bar{e}_y \quad (5.30)$$

with  $S_p = \pi R^2$  the projected area of the bubble in the direction of the flow.

### 5.2.5.1 Drag Coefficient

Derivations of analytic expressions for the drag coefficient in an infinite fluid medium exist for more than a century, starting with Hadamard-Ryzbinski (1911) [45]:

$$C_D = \frac{16}{Re_b}, \quad \text{if } Re_b < 1 \quad (5.31)$$

where  $Re_b = \frac{|U_{rel}| D_B}{\nu_L}$  is the bubble Reynolds number and  $U_{rel} = U_L - U_b$  the relative velocity between the bubble and the surrounding fluid.

For  $\text{Re}_b \gg 1$ , Levich (1962) [64] found for a potential flow:

$$C_D = \frac{48}{\text{Re}_b} \quad (5.32)$$

For intermediate values of  $\text{Re}_b$ , traditional approaches rely on expressions of the drag force for a bubble in an infinite medium based on numerical correlations as proposed by Mei & Klausner [75], used in many different mechanistic approaches [10, 88, 99, 105, 118]:

$$C_{D,U} = \frac{16}{\text{Re}_b} \left[ 1 + \left( \frac{8}{\text{Re}_b} + \frac{1}{2} \left( 1 + \frac{3.315}{\sqrt{\text{Re}_b}} \right) \right)^{-1} \right] \quad (5.33)$$

Results from DNS conducted by Legendre *et al.* [61] proposed expressions of the drag and lift forces for a hemispherical bubble on a wall facing a viscous shear flow. Earlier, Legendre & Magnaudet [61] analytically derived coefficients to transpose drag and lift expressions for a particle to the case of a bubble. This was applied by Mazzocco *et al.* [72] to the Drag for a solid particle near a wall in a shear flow proposed by Zeng *et al.* [119].

In this work, we propose to rely on the recent work of Shi *et al.* [96] who conducted DNS of a shear flow over a spherical bubble of constant radius close to a wall for bubble Reynolds number between  $10^{-1}$  and  $10^3$  and non-dimensional shear rates between -0.5 and 0.5. A sketch of the situation simulated by Shi *et al.* is depicted on Figure 5.5.




Figure 5.5: Physical situation considered by Shi *et al.* [96].

They computed the resulting drag and lift coefficients for each simulations and proposed correlations fitting their numerical results. The total Drag coefficient is expressed as a correction of the Drag coefficient for a bubble in an unbounded uniform flow  $C_{D,U}$ . The total drag is given by:

$$C_D = (1 + \Delta C_D) C_{D,U} \quad (5.34)$$

where  $\Delta C_D$  accounts for both the effect of the shear flow and the wall vicinity.

To cover the whole range of bubble Reynolds numbers, correlations at low and high  $\text{Re}_b$  are smoothly connected using an exponential term.

$$\Delta C_D = \Delta C_{D,\text{Re}_b=O(1)} + \left( 1 - e^{-0.07\text{Re}_b} \right) \Delta C_{D,\text{Re}_b \gg 1} \quad (5.35)$$

Each of those corrections is computed depending on  $\text{Re}_b$ , the non-dimensional shear rate  $\text{Sr} = \frac{2\gamma R}{|U_{rel}|}$  where  $\gamma = \frac{\partial U_{L,x}}{\partial y}$ , the non dimensional wall distance  $L_R = \frac{y}{R}$  ( $L_R = 1$  being a spherical bubble laying on a wall) and non-dimensional viscous (or Stokes) length  $L_u = \frac{y}{\nu_L / |U_{rel}|}$ .

$$\Delta C_{D,\text{Re}_b=O(1)} = \frac{1 + \tanh(0.012\text{Re}_b^{0.8}) + \tanh(0.07\text{Re}_b^{0.8})^2}{1 + 0.16L_u(L_u + 4)} \\ \times \left[ \left( \frac{3}{8}L_R^{-1} + \frac{3}{64}L_R^{-4} \right) \left( 1 - \frac{3}{8}L_R^{-1} - \frac{3}{64}L_R^{-4} \right)^{-1} - \frac{1}{16} \left( L_R^{-2} + \frac{3}{8}L_R^{-3} \right) \text{Sr} \right] \quad (5.36)$$

$$\Delta C_{D,\text{Re}_b \gg 1} = 0.47L_R^{-4} + 0.0055L_R^{-6}\text{Re}_b^{3/4} + 0.002|\text{Sr}|^{1.9}\text{Re}_b + 0.05L_R^{-7/2}\text{Sr}\text{Re}_b^{1/3} \quad (5.37)$$

Figure 5.6 shows the evolution of the drag correction  $\Delta C_D$  against the bubble Reynolds number for different dimensionless distances to the wall  $L_R$  and two values of Sr. We can see that as the distance between the wall and the bubble increases the drag correction logically approaches zero and that increasing the shear rate Sr increases  $\Delta C_D$  for higher values of  $\text{Re}_b$ .

Shi *et al.* [96] conducted DNS for wall distances down to  $L_R = 1.5$ . However, Scheiff *et al.* [93] compared the values obtained for  $L_R = 1$  with measured drag coefficients of bubbles sliding on a wall and observed a good agreement, which legitimates the use of this new drag correlation by extending its application to the case of a bubble laying on a wall and using the uniform drag coefficient of Eq. 5.33.




Figure 5.6: Drag correction from Shi *et al.* [96].

**Remark :** In PWR conditions, a static bubble of radius 0.01 mm on a wall with a bulk liquid velocity of 5 m/s leads to a non-dimensional shear rate  $\text{Sr} \approx 0.7$  with  $\text{Re}_b \approx 500$ . In this case, the drag correction can reach 180% compared to the unbounded uniform flow formulation.

### 5.2.5.2 Lift Coefficient

In 1987, Auton *et al.* [2] analytically derived the lift force for an inviscid fluid in unstationary motion in a weak velocity gradient and found  $C_L = 0.5$ , with the lift force defined as:

$$\overline{F_L} = -\rho_L C_L V_b (\overline{U_L} - \overline{U_b}) \wedge \overline{\omega} \quad (5.38)$$

where  $\overline{\omega}$  is the flow vorticity.

This result was enriched by Legendre & Magnaudet (1998) [61] who used numerical results to propose a dependency of  $C_L$  on the bubble Reynolds number for a sphere in an infinite medium facing a weakly sheared flows as:

$$C_L = (C_{L,\text{Re}_b \sim 1}^2 + C_{L,\text{Re}_b \gg 1}^2)^{1/2} \quad (5.39)$$

$$= \left( \left[ \frac{6}{\pi^2} \frac{2.255 (\text{Re}_b \omega^*)^{-1/2}}{\left(1 + 0.2 \frac{\text{Re}_b}{\omega^*}\right)^{3/2}} \right]^2 + \left[ \frac{1}{2} \frac{1 + 16 \text{Re}_b^{-1}}{1 + 29 \text{Re}_b^{-1}} \right]^2 \right)^{1/2} \quad (5.40)$$

where  $\omega^* = \frac{2R |\bar{\omega}|}{|U_{rel}|}$  is the non-dimensional vorticity of the flow, equal to Sr here for the linear shear flow case.

Later, Mei & Klausner (1994) [74] derived the lift force induced by the shear for a spherical bubble in an unbounded flow for low Reynolds numbers, based on the expression of Saffmann [92]. By interpolating this result with the solution of Auton [2], they obtained a formulation for a large range of  $\text{Re}_b$  :

$$C_L = 2.74 \sqrt{\text{Sr}} \times \left[ \text{Re}_b^{-2} + (0.24 \sqrt{\text{Sr}})^4 \right]^{1/4} \quad (5.41)$$

This expression is actually used in many mechanistic force balance [10, 53, 88, 99].

In his force-balance approach, Mazzocco *et al.* [72] used a constant lift coefficient by using the upper bound for the lift of a solid particle touching a wall in a Stokes flow, multiplied by  $\frac{4}{9}$  to transpose this value to the bubble case as suggested by Legendre & Magnaudet [61]. This resulted in:

$$C_L = 2.61 \quad (5.42)$$

In accordance with the computation of the drag coefficient, our model will rely on the expression of the lift coefficient proposed by Shi *et al.* [96]. Their formulation includes extra parameters compared to the drag coefficient :

- The non-dimensional Saffman length  $L_\omega = \frac{y}{\sqrt{\nu_L/\omega}}$  ;
- The Stokes (or Oseen) length to Saffman length ratio  $\varepsilon = \frac{\nu_L / |U_{rel}|}{\sqrt{\nu_L/\omega}}$ , which quantifies the origin of inertial effects being either shear ( $\varepsilon > 1$ ) or the relative slip of the bubble ( $\varepsilon < 1$ ).

The resulting formulation of  $C_L$  corresponds to the superpositions of two contributions respectively associated to the uniform flow and the shear rate, both coupled with the wall presence.

$$C_L^W = C_{Lu}^W + C_{L\omega}^W \quad (5.43)$$

The lift associated to the uniform flow near a wall is computed as follows:

$$\begin{aligned} C_{Lu}^W &= e^{-0.22 \varepsilon^{0.8} L_\omega^{2.5}} \frac{[1 + \tanh(0.012 \text{Re}_b^{0.8}) + \tanh(0.07 \text{Re}_b^{0.8})]^2}{1 + 0.13 L_u (L_u + 0.53)} \\ &\times \left( \frac{L_R}{3} \right)^{-2.0 \tanh(0.01 \text{Re}_b)} C_{Lu}^{\text{W-in}} \\ &+ \left( 1 - e^{-0.22 \text{Re}_b^{0.6}} \right) \left[ C_{Lu, \text{Re}_b \rightarrow \infty}^W + 15 \tanh(0.01 \text{Re}_b) \text{Re}_b^{-1} L_R^{-4} \right] \end{aligned} \quad (5.44)$$

Where:

$$C_{Lu}^{\text{W-in}} = \frac{1}{2} \left( 1 + \frac{1}{8} L_R^{-1} - \frac{33}{64} L_R^{-2} \right) \quad (5.45)$$

$$C_{Lu, \text{Re}_b \rightarrow \infty}^W = -\frac{3}{8} L_R^{-4} \left[ 1 + \frac{1}{8} L_R^{-3} + \frac{1}{6} L_R^{-5} \right] + O(L_R^{-10}) \quad (5.46)$$

The lift associated to the vorticity near a wall is computed as follows:

$$C_{L\omega}^W = \left[ 1 - \exp \left( -\frac{11}{96} \pi^2 \frac{L_\omega}{J_L(\varepsilon)} \left( 1 + \frac{9}{8} L_R^{-1} - \frac{1271}{3520} L_R^{-2} \right) \right) \right] C_{L\omega, \text{Re}_b \ll 1}^U \quad (5.47)$$

$$+ \left( 1 - e^{-0.3 \text{ Re}_b} \right) \left[ 1 + 0.23 L_R^{-7/2} \left( 1 + 13 \text{ Re}_b^{-1/2} \right) \right] C_{L\omega, \text{Re}_b \gg 1}^U \quad (5.48)$$

Where:

$$J_L(\varepsilon) = 2.254 (1 + 0.2\varepsilon^{-2})^{-3/2} \quad (5.49)$$

$$C_{L\omega, \text{Re}_b \ll 1}^U = \frac{8}{\pi^2} \frac{\text{Sr}}{|\text{Sr}|} \varepsilon J_L(\varepsilon) \quad (5.50)$$

$$C_{L\omega, \text{Re}_b \gg 1}^U = \frac{2}{3} \text{Sr} (1 - 0.07 |\text{Sr}|) \frac{1 + 16 \text{Re}_b^{-1}}{1 + 29 \text{Re}_b^{-1}} \quad (5.51)$$

On Figure 5.7, we plot the values of  $C_L$  obtained by the formulation of Shi *et al.* different values of the non-dimensional wall distance  $L_R$  (extending down to  $L_R = 1$ ) and non-dimensional shear rate Sr.




Figure 5.7:  $C_L$  computed using Shi *et al.* correlation.

We can see that the magnitude of the lift coefficient globally increases with the wall distance when  $\text{Sr} > 0$  and that negative lift values are easily reached when  $\text{Sr} < 0$ . This means that correlations for unbounded medium may overestimate the lift experienced by the bubble compared to the situation with a wall.

The extension to the case  $L_R = 1$  may be more questionable compared to the drag since the bubble touching the wall will stop any flow in between, leading to inertial and shear regimes that would be significantly different due to the redirection of the liquid at the bubble's foot towards the bulk. In particular, we can see that the values reached for  $L_R = 1$  on Figure 5.7 are not following the general trend of simulated  $L_R$ :

- Negative values of  $C_L$  are reached with positive Sr at high  $\text{Re}_b$  while getting close to the wall seemed to tend to a value of  $C_L \geq 0$  at high  $\text{Re}_b$ ;
- Magnitude of  $C_L$  with negative Sr are not coherent with the observed trend down to  $L_R = 1.5$ .

This observation suggest that we should include the effect of the wall using the lift of Shi *et al.* by limiting its use to  $L_R = 1.5$  contrary to the drag which extension to  $L_R = 1.0$  was coherent and validated.

**Remark :** In PWR conditions, taking  $\text{Sr} \approx 0.7$  with  $\text{Re}_b \approx 500$  for the static bubble on a wall leads to  $C_L \approx 0.45$  both with Mei & Klausner (Eq. 5.41) and Shi *et al.* (Eq. 5.43). For a bubble that would slide at 90% of the local liquid velocity, this gives  $\text{Sr} \approx 7$  and  $\text{Re}_b \approx 50$  yielding  $C_{L, \text{Mei}} \approx 4$  and  $C_{L, \text{Shi}} \approx 2.8$ .

### 5.2.6 Inertia Force

The Inertia force originates from various effects (bubble growth, freestream and bubble acceleration, etc.) and includes both added mass and Tchen forces and is expressed as presented in Magnaudet & Eames (2000) [68]:

$$\overline{F}_I = \underbrace{\rho_L V_b \left( \frac{\partial \overline{U}_L}{\partial t} + \overline{\nabla}(\overline{U}_L) \cdot \overline{U}_L \right)}_{\text{Liquid inertia or Tchen force}} + \underbrace{\frac{d}{dt} (\rho_L C_{AM} V_b (\overline{U}_L - \overline{U}_b))}_{\text{Added Mass force } \overline{F}_{AM}} \quad (5.52)$$

Since we consider a steady and quasi-parallel liquid flow, we respectively have:

$$\frac{\partial \overline{U}_L}{\partial t} = 0 \text{ and } \overline{\nabla}(\overline{U}_L) \cdot \overline{U}_L = 0 \quad (5.53)$$

Thus only remains the added mass force to be expressed in the considered force balance. In the next subsections, we detail former approaches to tackle the added mass derivation and propose a more rigorous one to re-evaluate the added mass coefficients.

#### 5.2.6.1 Former Approaches

In previous mechanistic models, the derivation of the added mass force was conducted with different approaches. In particular, some authors chose to rely on the Rayleigh-Plesset Equation (RPE) for a growing hemispherical bubble in a quiescent flow to obtain the reaction force from the liquid, oriented perpendicularly to the wall:

$$\overline{F}_{AM,RPE} = -\rho_L \pi R^2 \left[ R \ddot{R} + \frac{3}{2} \dot{R}^2 \right] \overline{e}_y \quad (5.54)$$

Then, assuming a bubble inclination angle  $\theta_i$ , this force was projected along the  $x$  axis to obtain an Added Mass force parallel to the wall that hinders departure. The inclination angle value is often empirical and used for data fitting [16, 72, 88, 118].

$$\overline{F}_{AM,RPE} = -\rho_L \pi R^2 \left[ R \ddot{R} + \frac{3}{2} \dot{R}^2 \right] (\sin(\theta_i) \overline{e}_x + \cos(\theta_i) \overline{e}_y) \quad (5.55)$$

This approach is questionable on different aspects. First, the RPE assumes a moving boundary in a quiescent unbounded liquid, which is physically far from the real situation of a bubble growing on a wall in a boiling flow. Moreover, the subsequent projection along the different directions regarding an unknown angle is hardly reasonable if  $\theta_i$  is chosen arbitrarily. Values of  $\theta_i$  selected by different authors are mentioned in Table 5.2.

On the other hand, some authors [39, 53, 105] considered two distinct contributions:

- Hemispherical bubble growth in a stagnant liquid, leading to Eq. 5.55 including the inclination angle  $\theta_i$  ;
- Spherical bubble growth in a uniform unbounded and inviscid liquid flow, which yields a detaching Added Mass term due to the interaction of bubble growth with the external flow:

$$\overline{F}_{AM,U} = \frac{3}{2} \rho_L V_b \frac{\dot{R}}{R} U_L \overline{e}_x \quad (5.56)$$

This last term is usually called a "bulk growth force". By including the effect of the liquid flow, this approach can be considered as closer to the reality. However, it relies on two separate derivations associated to different physical considerations.

#### 5.2.6.2 Proposed Approach

To tackle the added mass derivation in a proper way, we propose to follow the approach of Lamb [59] (also presented by Milne Thomson [77] or Van Winjgaarden [111]). By solving the potential flow around a bubble and its image, we can obtain the total liquid kinetic energy  $E_L$  that corresponds to a situation where a bubble is at a given distance from a wall (represented by the line normal to the line of centers of the bubbles).

Then we can use Lagrange equation to compute the resulting forces along a given coordinate  $q$ :

$$F_{AM,q} = -\frac{\partial}{\partial t} \left( \frac{\partial E_L}{\partial \dot{q}} \right) + \frac{\partial E_L}{\partial q} \quad (5.57)$$

This method was also used by Duhar [26] who developed an asymptotic expression of  $E_L$  to compute the added mass coefficient when a growing bubble approaches the wall. Here, we express the liquid kinetic energy by relying on the work of Van Der Geld [32] who derived  $E_L$  in the case of a full or truncated spherical bubble laying on a wall and facing an uniform flow parallel to the wall of velocity  $U_L$  (Eq. 5.58). If the bubble slides at a velocity  $U_b = \dot{x}$ , it sees a liquid velocity  $U_{rel} = U_L - \dot{x}$ .

$$E_L = \frac{\rho_L V_b}{2} \left( \alpha \dot{y}^2 + \text{tr}(\beta) \dot{R}^2 + \psi \dot{R} \dot{y} + \alpha_2 (U_L - \dot{x})^2 \right) \quad (5.58)$$

where  $(x, y)$  are the coordinates of the bubble's center and  $\alpha$ ,  $\text{tr}(\beta)$ ,  $\psi$ ,  $\alpha_2$  are polynomials of  $R/y = 1/L_R$  derived by Van Der Geld for  $1 < R/y < 2$  i.e.  $0.5 < L_R < 1$ , corresponding to contact angles  $0^\circ < \theta < 60^\circ$ .

For each polynomial expression ( $\alpha$  is used as an example), we note  $n$  its degree and write:

$$\alpha = \sum_{k=0}^n \alpha_k \left( \frac{R}{y} \right)^k \quad \text{and} \quad \tilde{\alpha} = \sum_{k=0}^n k \alpha_k \left( \frac{R}{y} \right)^k \quad (5.59)$$

This allows to express the following derivatives:

$$\frac{\partial \alpha}{\partial y} = -\frac{1}{y} \tilde{\alpha} \quad \text{and} \quad \frac{\partial \alpha}{\partial t} = \left( \frac{\dot{R}}{R} - \frac{\dot{y}}{y} \right) \tilde{\alpha} \quad (5.60)$$

Noticing that the derivatives of the polynomials along  $x$  will be 0 and injecting  $E_L$  in Eq. 5.57 allows to express the added mass force in  $x$  and  $y$  directions. If we express it using geometrical ratios  $\frac{R}{y} = \frac{1}{F_1}$ ,  $\frac{\dot{y}}{\dot{R}} = F_2$  and  $\frac{\ddot{y}}{\ddot{R}} = F_3$ , we can obtain:

$$F_{AM,x} = \rho_L V_b \left[ \left( 3\alpha_2 + \left( 1 - \frac{F_2}{F_1} \right) \tilde{\alpha}_2 \right) \frac{\dot{R}}{R} U_{rel} - \alpha_2 \frac{\partial U_b}{\partial t} \right] \quad (5.61)$$

$$\begin{aligned} F_{AM,y} = -\rho_L V_b & \left[ \left( 3F_2\alpha + \frac{3}{2}\psi + \left( 1 - \frac{F_2}{F_1} \right) F_2 \tilde{\alpha} + \left( 1 - \frac{F_2}{F_1} \right) \frac{\tilde{\psi}}{2} + \frac{F_2}{F_1} \frac{\tilde{\alpha}}{2} + \frac{1}{F_1} \frac{\text{tr}(\tilde{\beta})}{2} + \frac{F_2}{F_1} \frac{\tilde{\psi}}{2} \right) \frac{\dot{R}^2}{R} \right. \\ & \left. + \left( F_3\alpha + \frac{\psi}{2} \right) \ddot{R} + \frac{1}{F_1} \frac{\alpha_2}{2} \frac{U_{rel}^2}{R} \right] \end{aligned} \quad (5.62)$$

In the case of a truncated sphere,  $F_1 = \frac{y}{R} = \cos(\theta) = L_R$ . If we suppose that the bubble keeps a nearly constant contact angle during its lifetime, we can further write  $F_1 = F_2 = F_3 = \cos(\theta) = L_R$ , which simplifies the forces in:

$$F_{AM,x} = \rho_L V_b \left[ 3\alpha_2 \frac{\dot{R}}{R} U_{rel} - \underbrace{\alpha_2}_{C_{AM,x}} \frac{\partial U_b}{\partial t} \right] \quad (5.63)$$

$$F_{AM,y} = \rho_L V_b \left[ - \left( \underbrace{3 \left( L_R \alpha + \frac{\psi}{2} \right)}_{C_{AM,y1}} + \underbrace{\frac{\tilde{\alpha}}{2} + \frac{1}{L_R} \frac{\text{tr}(\tilde{\beta})}{2} + \frac{\tilde{\psi}}{2}}_{C_{AM,y2}} \right) \frac{\dot{R}^2}{R} \right. \quad (5.64)$$

$$\left. - \left( L_R \alpha + \frac{\psi}{2} \right) \ddot{R} + \underbrace{\frac{-1}{L_R} \frac{\tilde{\alpha}_2}{2} \frac{U_{rel}^2}{R}}_{C_{AM,y3}} \right] \quad (5.65)$$




Figure 5.8: Values of the computed added mass coefficients in Eq. 5.63 and 5.65.

On Figure 5.8, we plot the values of the added mass coefficients against the values of  $L_R$ . For the case of a spherical bubble laying on a wall ( $L_R = 1$ ), we finally have:

$$F_{AM,x} = \rho_L V_b \left[ 3C_{AM,x} \frac{\dot{R}}{R} U_{rel} - C_{AM,x} \frac{\partial U_b}{\partial t} \right] \quad (5.66)$$

with  $C_{AM,x} \approx 0.636$ .

$$F_{AM,y} = \rho_L V_b \left[ -(3C_{AM,y1} + C_{AM,y2}) \frac{\dot{R}^2}{R} - C_{AM,y1} \ddot{R} + C_{AM,y3} \frac{U_{rel}^2}{R} \right] \quad (5.67)$$

with  $C_{AM,y1} \approx 0.27$ ,  $C_{AM,y2} \approx 0.326$  and  $C_{AM,y3} \approx 8.77 \times 10^{-3}$ .

Parallel to the wall, the coupled term  $\frac{\dot{R}}{R} U_{rel}$  in Eq. 5.66 promotes detachment and sliding of the bubble if  $U_{rel} > 0$  e. g. if the bubble is attached to its nucleation site. This contradicts the aforementioned approach where solely projecting the RPE on both axes lead to an Added-Mass term related to bubble growth that only hinders the departure by sliding. Moreover, Eq. 5.67 exhibits a term induced by the relative velocity that acts as a lift force, which seems to rarely appear in other approaches.

**Remark :** The derived values of the added mass coefficients are only valid for  $0.5 < L_R < 1$  as previously mentioned. When the bubble leaves the wall, added mass calculations of Duhar [25] would be more appropriate.

Those theoretical results highlight the importance of conducting a rigorous approach when possible to deriving those transient aspects of the force balance. Otherwise, some terms may be missing and lead to contradictory physical conclusions.

In the spirit of avoiding to introduce extra empirical terms, we keep the Added Mass force as presented in Eq. 5.66 and 5.67 and consider no projection along the inclination angle.

### 5.2.7 Force Balance Summary

Writing Newton's second law, we have the total force balance over the bubble in both directions:

$$\begin{aligned} \rho_V \frac{\partial V_b U_{b,x}}{\partial t} &= -\pi R \sigma f_{C,x}(\theta, d\theta) + V_b (\rho_L - \rho_V) g + \frac{1}{2} C_D \rho_L \pi R^2 |U_L - U_b| (U_L - U_b) \\ &\quad + \rho_L V_b \left[ 3C_{AM,x} \frac{\dot{R}}{R} (U_L - U_b) - C_{AM,x} \frac{\partial U_b}{\partial t} \right] \end{aligned} \quad (5.68)$$

$$\rho_V \frac{\partial V_b U_{b,y}}{\partial t} = -\pi R \sigma f_{C,y}(\theta, d\theta) + 2\pi R \sigma \sin(\theta)^2 + \frac{1}{2} C_L \rho L \pi R^2 (U_L - U_b)^2 + \rho_L V_b \left[ -(3C_{AM,y1} + C_{AM,y2}) \frac{\dot{R}^2}{R} - C_{AM,y1} \dot{R} + C_{AM,y3} \frac{(U_L - U_b)^2}{R} \right] \quad (5.69)$$

Those force balances will respectively be used later to study the departure by sliding (along  $x$ ) and the lift-off from the wall (along  $y$ ).

On Table 5.2, we sum up some of the mentioned mechanistic approaches and their models along with the proposed force balance.

	Klausner (1993) [53]	Thorncroft (2001) [105]	Sugrue (2016) [99]
Forces	$\overline{F}_B = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) \bar{g}$	$\overline{F}_B = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) \bar{g}$	$\overline{F}_B = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) \bar{g}$
	$\overline{F}_C = \text{Eq. 5.28, } r_w = 0.045 \text{ mm}$	$\overline{F}_C = \text{Eq. 5.28, } r_w = R \sin(\theta_a)$	$\overline{F}_C = \text{Eq. 5.28, } r_w = 0.025R$
	$\overline{F}_{CP} = \text{Eq. 5.20, } R_c = 5R$	Neglected	$\overline{F}_{CP} = \text{Eq. 5.20, } R_c = 5R$
	$\overline{F}_D = C_D = \frac{16}{Re_b} \left[ 1 + \frac{3}{2} \left( \left( \frac{12}{Re_b} \right)^n + 0.796^n \right)^{1/n} \right], n = 0.65$	$C_D = \frac{16}{Re_b} \left[ 1 + \left( \frac{8}{Re_b} + \frac{3.315}{\sqrt{Re_b}} \right) \right]^{-1}$	$C_D = \frac{16}{Re_b} \left[ 1 + \frac{3}{2} \left( \left( \frac{12}{Re_b} \right)^n + 0.796^n \right)^{1/n} \right], n = 0.65$
	$\overline{F}_L = C_L = 2.74\sqrt{Sr} \times \left[ Re_b^{-2} + (0.24\sqrt{Sr})^4 \right]^{\frac{1}{4}}$	$C_L = 0.71\sqrt{Sr} \times \left[ \left( \frac{1.15J(\varepsilon)}{\sqrt{Re_b}} \right)^2 + \left( \frac{3\sqrt{2Sr}}{8} \right)^2 \right]^{\frac{1}{2}}$	$C_L = 2.74\sqrt{Sr} \times \left[ Re_b^{-2} + (0.24\sqrt{Sr})^4 \right]^{\frac{1}{4}}$
	$\overline{F}_{AM} = \frac{3}{2}\rho_L V_b \frac{\dot{R}}{R} U_L \bar{e}_x - \rho_L \pi R^2 \left( \frac{3}{2}\dot{R}^2 + R\ddot{R} \right) \times (\cos(\theta_i) \bar{e}_y + \sin(\theta_i) \bar{e}_x), \theta_i = 10^\circ$	$\overline{F}_{AM} = 2\pi\rho_L R^2 \dot{R} U_L \bar{e}_x - \rho_L \pi R^2 \left( \frac{3}{2}\dot{R}^2 + R\ddot{R} \right) \times (\cos(\theta_i) \bar{e}_y + \sin(\theta_i) \bar{e}_x), \theta_i = 45^\circ$	$\overline{F}_{AM} = -\rho_L \pi R^2 \left( \frac{3}{2}\dot{R}^2 + R\ddot{R} \right) \times (\cos(\theta_i) \bar{e}_y + \sin(\theta_i) \bar{e}_x), \theta_i = 10^\circ$
	Mazzocco (2018) [72]	Ren (2020) [88]	Present model
Forces	$\overline{F}_B = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) \bar{g}$	$\overline{F}_B = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) \bar{g}$	$\overline{F}_B = \frac{4}{3}\pi R^3 (\rho_L - \rho_V) \bar{g}$
	$\overline{F}_C = \text{Eq. 5.28, } r_w = R/15$	$\overline{F}_C = \text{Eq. 5.28, } r_w = 0.2R$	$\overline{F}_C = \text{Eq. 5.28, } r_w = R \sin(\theta)$
	$\overline{F}_{CP} = \text{Eq. 5.20, } R_c = 5R$	$\overline{F}_{CP} = \text{Eq. 5.20, } R_c = 5R$	$\overline{F}_{CP} = \text{Eq. 5.20, } R_c = R$
	$\overline{F}_D = C_D = 1.13 \frac{24}{Re_b} \left( 1 + 0.104 Re_b^{0.753} \right)$	$C_D = \frac{16}{Re_b} \left[ 1 + \frac{3}{2} \left( \left( \frac{12}{Re_b} \right)^n + 0.796^n \right)^{1/n} \right], n = 0.65$	$C_D = C_{D,U} (1 + \Delta C_D)$ $C_{D,U}$ by Eq. 5.33, $\Delta C_D$ by Eq. 5.35
	$\overline{F}_L = C_L = 2.61$	$C_L = 2.74\sqrt{Sr} \times \left[ Re_b^{-2} + (0.24\sqrt{Sr})^4 \right]^{\frac{1}{4}}$	$C_L$ by Shi <i>et al.</i> [96]
	$\overline{F}_{AM} = -\frac{1}{4}\pi\rho_L K^4 (\cos(\theta_i) \bar{e}_y + \sin(\theta_i) \bar{e}_x), \sin(\theta_i) = 0.2, \cos(\theta_i) = 1$	$\overline{F}_{AM} = -\rho_L \pi R^2 \left( \frac{3}{2}\dot{R}^2 + R\ddot{R} \right) \times (\cos(\theta_i) \bar{e}_y + \sin(\theta_i) \bar{e}_x), \theta_i = 15^\circ$	$\frac{F_{AM,x}}{\rho_L V_b} = C_{AM,x} \left[ 3 \frac{\dot{R}}{R} U_{rel} - \frac{\partial U_b}{\partial t} \right],$ $C_{AM,x} = 0.636, F_{AM,y}$ by Eq. 5.67

Table 5.2: Summary of different force-balance mechanistic approaches.

### 5.2.8 Liquid Velocity

To compute the liquid velocity and shear rate at bubble center height, we use the wall law of Reichardt [87], which describes the velocity profile from the viscous sublayer to the logarithmic region in a single-phase flow.

$$\begin{aligned} U_L^+ &= \frac{1}{\kappa} \ln(1 + \kappa y^+) + c \left( 1 - e^{-y^+/\chi} + \frac{y^+}{\chi} e^{-y^+/3} \right) \\ U_L &= U_L^+ U_\tau \end{aligned} \quad (5.70)$$

with  $\kappa = 0.41$ ,  $\chi = 11$  and  $c = 7.8$ .

$$\begin{aligned} \frac{\partial U_L^+}{\partial y^+} &= \frac{1}{1 + \kappa y^+} + \frac{c}{\chi} \left( e^{-y^+/\chi} + \left( 1 - \frac{y^+}{3} \right) e^{-y^+/3} \right) \\ \frac{\partial U_L}{\partial y} &= \gamma = \frac{U_\tau^2}{\nu_L} \frac{\partial U_L^+}{\partial y^+} \end{aligned} \quad (5.71)$$

The friction velocity is computed using Mac Adams correlation [73].

$$U_\tau = \sqrt{\frac{\tau_w}{\nu_L}} \quad (5.72)$$

$$\tau_w = 0.018 \text{ Re}_{D_h}^{-0.182} \frac{G_L^2}{\rho_L} \quad (5.73)$$

### 5.3 BUBBLE GROWTH

#### 5.3.1 Introduction

In order to properly represent the bubble dynamics, it is mandatory to model the evolution of the bubble radius over time *i.e.* the bubble growth law. Since the bubble radius  $R$  and its derivatives  $\dot{R}$  and  $\ddot{R}$  appear in the force balance (notably in the expression of the added mass force 5.65), failing to predict the evolution of the bubble with time will definitely result in a force unbalance.

The problem of the bubble growth during its lifetime on the wall, including the sliding phase, is still an open question that aims to cover various types of heat transfer mechanisms. First, two growth regimes exist for a boiling bubble:

- Inertial growth, which occurs at the beginning of nucleation for low temperature difference between liquid and vapor. The evolution of the bubble size can be solved by the mass and momentum balances, through the solution of Rayleigh (1917) [86]. The form of the bubble growth is usually  $R(t) = A \times t$  (Mikic & Rohsenow, [76]).
- Heat diffusion growth happening post the inertial phase. This type of bubble growth has been widely studied by different authors [76, 82, 95, 123] and is usually of the form  $R(t) = B\sqrt{t}$ , derivable using the energy balance around the bubble.

Those two regimes can be compared using the non-dimensional time  $t^+$  defined as:

$$t^+ = \frac{A^2}{B^2} t \quad (5.74)$$

where

$$A = \sqrt{b \frac{h_{LV} \rho_V \Delta T_w}{\rho_L T_{sat}}} \text{ and } B = \sqrt{\frac{12}{\pi} \eta_L \text{Ja}} \quad (5.75)$$

with  $b = \frac{2}{3}$  for a bubble in an infinite liquid medium and  $b = \frac{\pi}{7}$  for a spherical bubble laying on a wall.

So that when  $t^+ \ll 1$ ,  $R(t) = At$  (inertial growth) and when  $t^+ \gg 1$ ,  $R(t) = B\sqrt{t}$  (heat diffusion growth). A general solution asymptotically covering the two regimes has been derived by Mikic & Rohsenow:

$$R^+ = \frac{2}{3} \left[ (t^+ + 1)^{3/2} + t^{+3/2} - 1 \right], \quad R^+ = \frac{R}{B^2/A}, \quad t^+ = \frac{t}{B^2/A^2} \quad (5.76)$$

In most cases associated to wall nucleation and boiling flows, experimental observations showed that bubbles' lifetime is long enough to be mostly of heat conduction nature [57, 69, 122].

#### 5.3.2 Heat Diffusion in Uniformly Superheated Liquid

The analytic derivation of a bubble growth law in a pure heat diffusion regime has been tackled by various authors, mostly for the case of a bubble in a uniformly superheated and quiescent liquid. A reference solution is the work of Plesset & Zwick (1954) [82] who found an asymptotic solution for high values of Ja:

$$R(t) = \frac{2\sqrt{3}}{\sqrt{\pi}} \text{Ja} \sqrt{\eta_L t} \quad (5.77)$$

This result was generalized by Scriven (1959) [95] who derived for any value of Ja:

$$R(t) = 2\mathcal{F}(\text{Ja}) \text{Ja} \sqrt{\eta_L t} \quad (5.78)$$

where  $\mathcal{F}$  is implicitly defined by assuming  $\frac{\rho_L}{\rho_V} \gg 1$ :

$$\mathcal{F}(\text{Ja}) = \frac{F}{2\text{Ja}^2}, \text{ and } \text{Ja} = F \exp\left(\frac{3}{2}F\right) \int_1^\infty \frac{1}{x^2} \exp\left(-\frac{F}{x} - \frac{F}{2}x^2\right) dx \quad (5.79)$$

which falls back to  $\mathcal{F}(\text{Ja}) \rightarrow \frac{\sqrt{3}}{\sqrt{\pi}}$  when  $\text{Ja} \gg 1$ .

The general formulation of  $\mathcal{F}$  has been verified by Legendre *et al.* [60] with Direct Numerical Simulation of spherical bubble growth in a quiescent superheated liquid.

Usually, most authors are accepting  $R(t) = K\text{Ja}_w\sqrt{\eta_L t}$  for the bubble growth. With  $K$  usually expressed as  $K = \frac{2b}{\sqrt{\pi}}$  with  $b$  being used as an adjustable constant depending on the flow conditions and the fluid, or derived analytically as presented before ( $b = \sqrt{3}$  [82],  $b = \frac{\pi}{2}$  [28],  $1 \leq b \leq \sqrt{3}$  [123],  $b = 1.56$  [117],  $b = 0.24$  [116], etc.).

When the bubble presents a relative velocity with the ambient liquid, the disturbance of the thermal boundary layer around the liquid-vapor interface will impact its growth. This phenomenon has been numerically studied by Legendre *et al.* [60] who found that the ratio between the growth rate  $\dot{R}$  and the relative velocity  $U_{\text{rel}}$  was controlling the growth regime as follows:

- If  $\frac{\dot{R}}{U_{\text{rel}}} \gg 1$ , the regime is close to the static heat diffusion and correspond to the Scriven formulation (Eq. 5.78) ;
- If  $\frac{\dot{R}}{U_{\text{rel}}} \ll 1$ , the relative velocity impacts the thermal boundary layer formation and leads to a growth matching the solution of Ruckenstein (1964) [91] where the Nusselt number is:

$$\text{Nu} = 2\sqrt{\frac{\text{Pe}(t)}{\pi}}, \quad \text{Pe}(t) = \text{Pr}_L \times \text{Re}_b(t) \quad (5.80)$$

In this case, the bubble growth is accelerated and  $R \propto t^{2/3}$ .

### 5.3.3 Microlayer Evaporation

In addition to the traditional heat diffusion from superheated liquid to the bubble through the liquid-vapor interface, bubble growth can also be enhanced by the evaporation of a so-called "microlayer". This term denotes a very thin layer of liquid (typically  $\sim \mu\text{m}$  [57]) which is trapped between the heated wall and the bubble base, as shown on Figure 5.9. The existence of this microlayer has now been supported by both experimental visualizations [12, 13, 55, 57] and numerical investigations [8, 42, 109].




Figure 5.9: Microlayer appearing beneath the bubble in DNS conducted by and adapted from Urbano *et al.* [109].

Parallel to the heat diffusion approach, some authors computed the bubble growth by considering a pure microlayer evaporation regime. A well-known model of this type has been derived by Cooper & Lloyd in 1969 [17] and considers the wall thermal properties so that:

$$R(t) = 2.5 \frac{\text{Ja}}{\sqrt{\text{Pr}_L}} \sqrt{\eta_L t} \text{ if } \lambda_w \gg \lambda_L \quad (5.81)$$

$$R(t) = \frac{2}{\sqrt{\pi}} \sqrt{\frac{\lambda_w \rho_w c_{p,w}}{\lambda_L \rho_L c_{p,L}}} \text{ if } \lambda_w \ll \lambda_L \quad (5.82)$$

**Remark :** The parameter  $\sqrt{\frac{\lambda_w \rho_w c_{p,w}}{\lambda_L \rho_L c_{p,L}}}$  that accounts for the wall properties is the same used in the correlation of Ünal for the maximum bubble diameter (Eq. 5.5).

The microlayer is also often taken into account for HFP modeling by enhancing the boiling heat flux through a computation of the microlayer volume [22, 56].

However, the presence of a liquid microlayer beneath the nucleated bubble is not assured for every boiling conditions. Indeed, experimental observations recently realized by Kossolapov [57] showed that the microlayer only existed for pressures below 3 bars when using water as working fluid. Moreover, Direct Numerical Simulations of Urbano *et al.* [109] where a full coupling between mass, momentum and energy balance was achieved managed to detect whether if the bubble grows in a contact-line regime or if a microlayer appears. They proposed a criterion based on the capillary and Jakob numbers determining the formation of a microlayer :

$$\frac{\text{JaCa}}{(\theta - \theta_0)^3} > \frac{1}{A^3}, \quad \theta_0 = 5^\circ, \quad A = 313 \quad (5.83)$$

**Remark :** Computing the capillary number using  $\dot{R} = \frac{K \text{Ja}}{2} \sqrt{\frac{\eta_L}{t}}$  as the interface velocity, we use Urbano *et al.* criterion to compute the time  $t_{max}$  after which the microlayer would cease to exist. Applying this to PWR conditions ( $K = 1$ ,  $\Delta T_w = 5K$ ) yields  $t_{max} < 10^{-11}\text{s}$  for  $6^\circ \leq \theta \leq 90^\circ$ , meaning that there is no time during the bubble growth during which a microlayer could grow. This agrees with the observation that increasing pressure would lead to microlayer disappearance.

We will not further detail the study of the microlayer regime since its existence is very unlikely if not impossible in the pressurized conditions typical of a PWR.

### 5.3.4 Bubble Growth in Subcooled Flow Boiling

If we consider the full problem of bubble growth in subcooled flow boiling, the analytic expressions presented above may fall out of their validation range since extra physical phenomena will be at stake. This more generic type of growth lack of proper theoretical derivations due to the complexity of the considered system (turbulence, condensation, convection, etc.). That is why authors trying to represent such complex bubble growth often combine different heat transfer mechanisms such as:

- Evaporation due to conduction from the superheated liquid near the bubble base ;
- Evaporation of the liquid microlayer ;
- Condensation on top of the bubble when it reaches subcooled liquid ;
- Convective heat transfer due to relative velocity between the bubble and the liquid.

To our knowledge, such models always consider empirical or fitted parameters. For instance Yoo *et al.* [116] wrote for a sliding bubble:

$$\frac{\partial R}{\partial t} = \underbrace{\gamma \text{Pr}_L^{-0.5} \text{Ja}_w \sqrt{\frac{\eta_L}{t}} \frac{A_{ML}}{A_b}}_{\text{Microlayer}} + \underbrace{(1-f) \frac{b}{\sqrt{\pi}} \text{Ja}_w \sqrt{\frac{\eta_L}{t}}}_{\text{Superheated liquid}} - \underbrace{\frac{f \Delta T_L C}{1 - \rho_V / \rho_L} R}_{\text{Subcooled convection}} \quad (5.84)$$

where  $\gamma = \sqrt{\frac{\lambda_w \rho_w c_{p,w}}{\lambda_L \rho_L c_{p,L}}}$ ,  $\frac{A_{ML}}{A_b} = 1.22\gamma^{-0.79}\exp(-0.204\text{Ja}_w)$ ,  $f = 0.5$ ,  $b = 0.24$  and  $C = 0.1$ .

Their model was validated against low pressure sliding of boiling bubbles for different fluids (Water [69], FC87 [104], R113 [113]). They account for wall properties through the parameter  $\gamma$  in the microlayer term while assuming that 50% of the bubble faces subcooled liquid ( $f = 0.5$ ) and condenses following the formulation of Levenspiel [63].

Zhou *et al.* [122] also proposed a similar modeling of the bubble growth, validated on their own measurements for boiling water at low pressure:

$$\frac{\partial R}{\partial t} = \underbrace{\frac{1}{C} \text{Pr}_L^{-0.5} \text{Ja}_w \sqrt{\frac{\eta_L}{t}}}_{\text{Microlayer}} + \underbrace{\sqrt{\frac{3}{\pi}} \text{Ja}_T \sqrt{\frac{\eta_L}{t}} \min\left(\frac{y_{sat}}{2R}, 1\right)}_{\text{Superheated liquid}} - \underbrace{\frac{\eta_L}{2R} \text{Ja}_L (2 + 0.6 \text{Re}_b^{0.5} \text{Pr}_L^{0.3}) \max\left(\frac{H - y_{sat}}{2R}, 0\right)}_{\text{Subcooled convection}} \quad (5.85)$$

where  $C = 1.45$ ,  $\text{Ja}_T$  is the Jakob number taken at  $\min(\bar{T} - T_{sat}, 0)$ ,  $\bar{T}$  the average liquid temperature around the bubble,  $H = R(1 + \cos(\theta))$ .

While they consider a constant coefficient for the microlayer evaporation, they propose a finer modeling of the condensation term by evaluating the height  $y_{sat}$  at which  $T_L = T_{sat}$  using the turbulent wall law of Kader [50]. The condensation is modeled by the Ranz & Marshall correlation [85] that accounts for the relative velocity through the bubble Reynolds number.

**Remark :** As mentioned before, those model rely on numerous empirical parameters due to the variety of considered phenomena. In particular, microlayer evaporation is systematically considered which could be questioned regarding the observations made in Subsection 5.3.3.

Contrary to those models, Mazzocco *et al.* [72] propose to keep the radius as  $K \text{Ja}_w \sqrt{\eta_L t}$  and to include subcooling and microlayer influence in the value of  $K$ :

$$K = \frac{1.243}{\sqrt{\text{Pr}_L}} + 1.945\chi \quad (5.86)$$

with

$$\chi = 1.55 \text{ (saturated flow)} \text{ or } \chi = -0.05 \frac{\Delta T_L}{\Delta T_w} \text{ (subcooled flow)} \quad (5.87)$$

**Remark :** This approach is interesting because it keeps the simple growth law in  $t^{1/2}$  but the definition of  $\chi$  is hardly general since it can lead to  $K \leq 0$  for high values of  $\frac{\Delta T_L}{\Delta T_w}$  which would be unphysical.

### 5.3.5 Analytic Approach of Bubble Growth in a Linear Thermal Boundary Layer

In this Subsection, we propose an analytic derivation of bubble growth for a truncated sphere laying on a wall in a boundary layer with a linear temperature profile. The considered geometrical and thermal definitions are depicted on Figure 5.10.

We consider an established single-phase thermal boundary layer of thickness  $\delta$ . When the bubble start to grow, an other boundary layer will of thickness  $\delta_b$  grow between the liquid-vapor interface and the surrounding liquid which temperature depends on the wall distance  $y$ .

The liquid temperature is assumed to follow a linear profile:




Figure 5.10: Studied geometry

$$T_L(y) = T_w + \frac{T_{L,bulk} - T_w}{\delta} y \quad (5.88)$$

Assuming that the vapor stays at a temperature close to  $T_{sat}$ , the radial component of the temperature gradient at the bubble's interface can be expressed as:

$$\nabla(T) \cdot \bar{e}_r = \frac{\partial T}{\partial r}(R, \vartheta, \varphi) \approx \frac{T_L(y) - T_{sat}}{\delta_b} \quad (5.89)$$

Applying Fourier's law to the liquid close to the bubble to estimate the heat flux density vector  $\bar{j}_Q = -\lambda_L \nabla(T)$ . Between  $t$  and  $t+dt$  the heat exchanged through  $d^2S$  is:

$$d^2Q_b \approx -\frac{\lambda_L}{\delta_b} \left[ \Delta T_w R^2 \sin(\vartheta) - \frac{\Delta T_w + \Delta T_L}{\delta} R^3 [\cos(\vartheta) - \cos(\Theta)] \sin(\theta) \right] d\vartheta d\varphi \quad (5.90)$$

Then assuming that  $\delta_b$  is constant between  $t$  and  $t+dt$ , the total heat flux can be expressed by integrating over the bubble's surface:

$$Q_b = \frac{2\pi\lambda_L R^2}{\delta_b} (1 + \cos(\theta)) \left[ \Delta T_w - \frac{R}{2\delta} (\Delta T_w + \Delta T_L) (1 + \cos(\theta)) \right] \quad (5.91)$$

Writing the mass balance by considering that the heat flux contributes solely to phase change:

$$\frac{\partial V_b}{\partial t} = \frac{Q_b}{\rho_V h_{LV}} \quad (5.92)$$

$$V_b = \frac{4}{3}\pi R^3 f_V, \quad f_V = \frac{1}{4} (2 - \cos(\theta)) (1 + \cos(\theta))^2 \quad (5.93)$$

Writing this in terms of bubble radius:

$$\frac{\partial R}{\partial t} = \frac{\text{Ja}_w \eta_L}{2\delta_b f_V} (1 + \cos(\theta)) \left[ 1 - \frac{R}{2\delta} \left( 1 + \frac{\text{Ja}_L}{\text{Ja}_w} \right) (1 + \cos(\theta)) \right] \quad (5.94)$$

Which reduces to the following differential equation:

$$\frac{\partial R}{\partial t} + aR = b \quad (5.95)$$

$$a = \frac{\text{Ja}_w \eta_L}{4\delta_b \delta f_V} \left(1 + \frac{\text{Ja}_L}{\text{Ja}_w}\right) (1 + \cos(\theta))^2 \quad \text{and} \quad b = \frac{\text{Ja}_w \eta_L}{2\delta_b f_V} (1 + \cos(\theta)) \quad (5.96)$$

Solutions of this differential equation depend on the hypothesis over  $\delta$  and  $\delta_b$ . If we assume that the bubble grows in a fully established liquid flow then  $\delta$  can be considered as constant.

When the bubble will start to nucleate, the liquid-vapor interface will delimit a frontier through which a transient heat transfer between the vapor at constant temperature  $T_{sat}$  and liquid at  $T_L(y)$  will occur. To estimate the associated local boundary layer thickness  $\delta_b$ , we can rely on the solution of semi-infinite transient conduction as treated in Del Valle & Kenning [20] or Mikic & Rohsenow [76]:

$$\delta_b = \sqrt{\eta_L t} \quad (5.97)$$

The differential equation Eq. 5.95 becomes:

$$\frac{\partial R}{\partial t} + a(t) R = b(t) \quad (5.98)$$

$$a(t) = \frac{\text{Ja}_w \sqrt{\eta_L}}{4\delta f_V \sqrt{t}} \left(1 + \frac{\text{Ja}_L}{\text{Ja}_w}\right) (1 + \cos(\theta))^2 = K_a t^{-1/2} \quad (5.99)$$

$$b(t) = \frac{\text{Ja}_w \sqrt{\eta_L}}{2f_V \sqrt{t}} (1 + \cos(\theta)) = K_b t^{-1/2} \quad (5.100)$$

With the initial condition  $R(t=0) = 0$ , the solution to this differential equation is:

$$R(t) = R_\infty \left(1 - e^{-2K_a \sqrt{t}}\right) \quad (5.101)$$

$$R_\infty = \frac{K_b}{K_a} = \frac{2 \delta}{\left(1 + \frac{\text{Ja}_L}{\text{Ja}_w}\right) (1 + \cos(\theta))} \quad (5.102)$$

This type of bubble growth presents interesting properties. First, it degenerates to the uniformly superheated liquid solution when  $t \rightarrow 0$ :

$$R(t) \underset{t \rightarrow 0}{\sim} \frac{1 + \cos(\theta)}{f_V} \text{Ja}_w \sqrt{\eta_L t} \quad (5.103)$$

with a purely geometrical growth constant depending on the contact angle, equal to 2 for the spherical case.

Moreover, this growth law accounts for the liquid subcooling and thus presents an equilibrium radius  $R_\infty$  when  $t \rightarrow \infty$ , corresponding to the bubble size at which the vaporization from the superheated liquid is exactly compensated by the condensation at the bubble top.

To the best of our knowledge, this simple bubble growth law has never been proposed in the literature. However, this equation has some limitations :

- It requires the knowledge of the liquid thermal boundary layer thickness  $\delta$  which estimation can be tricky ;
- This law can't be applied if  $T_{L,bulk} > T_{sat}$ .

**Remark :** It is worthy to note that this solution is derived solely using the energy balance at the liquid-vapor interface. No momentum balance was used when solving this physical problem, which can be considered as a limit of the approach.

### 5.3.6 Comparison with DNS Results

To assess the validity of Eq. 5.101, we will compare the radius time profile with DNS results by Urbano *et al.* [108] who simulated the same physical situation as depicted in Figure 5.10 for pool boiling. They also solved the heat conduction in the wall and studied the growth dynamics depending on the values of  $\Delta T_L$  and  $\Delta T_w$  as well as the equilibrium diameter reached by the bubble.

In their analysis, Urbano *et al.* derived the same equilibrium radius as in Eq. 5.102 by equating the condensation and vaporization heat fluxes. By comparing with the equilibrium radius reached in their simulations, they found that a corrective factor  $C = 1.15829$  was needed to correct Eq. 5.102. This difference could be explained by the heat conduction in the wall that is not accounted for in the theoretical approach.

DNS results obtained for three couples of subcooling  $\Delta T_L$  and superheat  $\Delta T_w$  are used for comparison. Results are displayed on Figure 5.11 with and without the corrective factor on  $R_\infty$  suggested by Urbano *et al.*




Figure 5.11: Comparison with DNS results of Urbano *et al.* [108] ( $\delta = 3\text{mm}$  and  $\theta = 50^\circ$ ). Lines : Model predictions  
- Markers : DNS

The analytical formulation of the bubble growth matches very well with the DNS results when the equilibrium radius is corrected. The different growth regime induced by the pairs  $(\Delta T_L, \Delta T_w)$  are correctly captured by the model. DNS results present different equilibrium radius values when the subcooling and superheat changes, which can not be accounted for by the model.

**Remark :** Those results are encouraging and validate the modeling of  $\delta_b$  with the semi-infinite conduction model (Eq. 5.97).

### 5.3.7 Comparison with Experimental Measurements

#### 5.3.7.1 Low Pressure Measurements

To further evaluate the proposed model, we compare the result with experimental measurements of bubble radius in vertical boiling of water at atmospheric pressure by Maity [69]. The choice of  $\delta$  is adapted to each case and  $\theta = 45^\circ$  is the average measured contact angle in the experiments.

In addition, we also plot the predictions by the heat diffusion solution  $R = K J_{\alpha w} \sqrt{\eta_L t}$  with  $K = \frac{2b}{\sqrt{\pi}}$  and  $1 \leq b \leq \sqrt{\pi}$ . A solution with an optimized value of  $K$  is also represented. The models of Mazzocco and Yoo *et al.* are also compared. The results are presented on Figure 5.12.




Figure 5.12: Comparison with experimental measurements of Maity [69].

The new formulation globally reproduces the experimental results better than the other models. In particular, the progressively damped growth rate when the bubble start to face colder liquid seems to correctly captures the nonlinear experimental growth. Values of  $\delta$  needed to produce those results were between 0.85 mm and 1.55mm, which reasonably agrees with measurements of Maity in his experiment for horizontal flow giving  $\delta$  roughly between 1 mm and 1.5 mm.

**Remark :** We can note that the optimal value of  $\delta$  decreases as liquid mass flux increases, which is physically coherent as the thermal boundary layer will diminish in size with the Reynolds number.

On the other hand, the fitted value of  $K$  is often smaller than the lower bound  $\frac{2}{\sqrt{\pi}}$  suggested by Zuber [123]. This is a consequence of the subcooled flow which deviates from the uniformly superheated liquid from which those values were derived. This fitted profile manages to capture some stages of bubble growth but can not predict the asymptotic behavior where bubble reaches a quasi-constant radius. We see that the model of Mikic & Rohsenow produces results that are nearly identical to the  $K = 2\sqrt{3}/\pi$  solution. The growth constant computed by Mazzocco *et al.* (Eq. 5.86) is constant over the four cases and lower than  $2/\sqrt{\pi}$  which is slightly better than other analytic values of  $K$  but underestimates the pool boiling case.

Finally, we see that the model of Yoo *et al.* underestimates the bubble radius. We suspect this could come from the assumption considering that half of the bubble faces subcooled liquid ( $f = 0.5$ , Eq. 5.84), which is hardly reasonable especially at early growth stages.

### 5.3.7.2 High Pressure Measurements

The model is now compared to higher pressure measurement (20 bar and 40 bar) for water boiling by Kossolapov [57]. All the experiments are conducted with 10K of subcooling, and we take a contact angle of  $\theta = 80^\circ$  (typical for water and ITO). The range of the measured diameters over time are represented since Kossolapov observed the growth of thousands of bubbles over the heater surface. Results are presented on Figure 5.13.




Figure 5.13: Comparison with experimental measurements of Kossolapov [57].  $\Delta T_w$  values are recalculated from analytical growth profiles fitted by the author.

The values of  $\delta$  needed to match the experimental measurements using Eq. 5.101 are much smaller than the low pressure case, with  $\delta \leq 0.1$  mm. The higher mass fluxes in Kossolapov measurements could explain lower values of  $\delta$ , nevertheless they do not follow a particular trend with  $G_L$ .

Contrary to low pressure measurements, the Plesset & Zwick solution with  $\frac{2}{\sqrt{\pi}} \leq K \leq \frac{2\sqrt{3}}{\sqrt{\pi}}$  provides an acceptable estimation of the bubble radius. This is probably due to the smaller bubble size in pressurized boiling (roughly 10 times smaller compared to atmospheric pressure).

**Remark :** The non-dimensional positions of the center of gravity of the bubble  $R^+ = \frac{R u_\tau}{\nu_L}$  rise up to 40 for Maity cases and 20 for Kossolapov cases while having larger liquid mass fluxes. This supports the fact that bubbles at higher pressure are less likely to be impacted by subcooled liquid, spending most of their lifetime between the viscous and buffer layer.

### 5.3.8 Conclusions on Bubble Growth Modeling

- Recent experimental and numerical research have shown that the presence of a liquid microlayer contributing to the bubble growth strongly depends on the boiling conditions. In particular, disappearance of this microlayer at pressures higher than 3 bar has been observed by Kossolapov [57]. This microlayer should thus not be systematically taken into account.
- A new formulation derived from the heat diffusion in a linear temperature profile has been proposed (Eq. 5.101). Provided a correct value of the thermal boundary thickness  $\delta$ , validation both on DNS and low pressure measurements shows that the model better captures the growth regime of bubbles in subcooled boiling compared to traditional models. However, this improvement appears limited at higher pressure when bubbles are smaller, where the Plesset & Zwick treatment also proposes an acceptable estimation of the bubble growth.
- Mechanistic models that includes several heat transfer mechanisms require a certain number of empirical closures that limits the model generality, making them unsuitable for application to any boiling conditions.
- Whatever the conditions, a proper choice of the growth constant  $K$  in the  $R = KJa_w\sqrt{\eta_L t}$  solution for a uniform liquid superheat can yield reasonable results. Moreover, it presents interesting mathematical properties such as the time independence of the products  $R\dot{R}$  and  $R^3\ddot{R}$  that appear in the bubble force balance (Eq. 5.69).

All things considered, it seems that the proposed new growth law of Eq. 5.101 can be of greater interest for low pressure boiling where larger bubbles are more impacted by the bulk flow. Although it provides finer physical representation of bubble radius evolution, its application is limited by the estimation of  $\delta$  to which the model is strongly sensitive. **On the other hand, less precise yet acceptable predictions of bubble growth are achieved using the  $t^{1/2}$  law with a growth constant  $K$  close to unity.**

## 5.4 DEPARTURE BY SLIDING

The question of departure by sliding being central for bubble dynamics in vertical flow boiling, we will tackle the problem by starting with a non-dimensional analysis before moving to predictions of experimental measurements of departure diameters.

### 5.4.1 Non-Dimensional Analysis

To study the departure by sliding, we rely on force balance parallel to the wall (Eq. 5.68). Before departure, the bubble grows on its nucleation site while staying immobile, thus with a sliding velocity  $U_b = \frac{\partial U_b}{\partial t} = 0$ . The force balance parallel to the wall becomes:

$$-\pi R \sigma f_{C,x} + \frac{4}{3} \pi R^3 (\rho_L - \rho_V) g + \frac{1}{2} C_D \rho_L \pi R^2 U_L^2 + \frac{4}{3} \pi R^3 \rho_L 3C_{AM,x} \frac{\dot{R}}{R} U_L = 0 \quad (5.104)$$

We can note that in this equation, departure by sliding is promoted by the buoyancy, the drag and the added mass forces. Only the capillary force keeps the bubble attached to its nucleation site, which will be discussed later. As discussed in the previous section, the bubble growth is modeled as:

$$R(t) = KJa_w\sqrt{\eta_L t} \quad (5.105)$$

with  $K$  as an adjustable constant.

Re-writing Eq. 5.104 in non-dimensional form by dividing the LHS by the added mass force yields:

$$-\frac{1}{2} \frac{f_{C,x}}{K^2 C_{AM,x}} \frac{1}{Ca} \frac{Pr_L}{Ja_w^2} + \frac{1}{3} \frac{1}{K^2 C_{AM,x}} \frac{Re_b}{Fr} \frac{Pr_L}{Ja_w^2} + \frac{1}{8} \frac{C_D}{K^2 C_{AM,x}} \frac{Pr_L}{Ja_w^2} + 1 = 0 \quad (5.106)$$

where we have the following non-dimensional numbers:

$$\begin{aligned} \text{Re}_b &= \frac{2R U_L}{\nu_L} ; \quad \text{Fr} = \frac{\rho_L U_L^2}{(\rho_L - \rho_V) g R} ; \quad \text{We} = \frac{\rho_L U_L^2 R}{\sigma} ; \quad \text{Eo} = \frac{(\rho_L - \rho_V) g R^2}{\sigma} ; \\ \text{Ja}_w &= \frac{(T_w - T_{sat}) \rho_L c_{P,L}}{\rho_V h_{LV}} ; \quad \text{Pr}_L = \frac{\nu_L}{\eta_L} ; \quad \frac{\dot{R}}{U_L} = \frac{K^2 \text{Ja}_w^2}{\text{Pr}_L \text{Re}_b} ; \quad \text{Ca} = \frac{\mu_L U_L}{\sigma} \end{aligned}$$

Eq. 5.106 exhibits terms that can be used to compare the magnitude of each detaching forces and obtain the following conditions:

$$\text{Added mass force greater than drag if: } \frac{\text{Ja}_w^2}{\text{Pr}_L} > \frac{1}{8} \frac{C_D}{C_{AM,x}} \frac{1}{K^2} \text{Re}_b \quad (\text{Bd. 1})$$

$$\text{Added mass greater than buoyancy if: } \frac{\text{Ja}_w^2}{\text{Pr}_L} > \frac{1}{3} \frac{1}{C_{AM,x} K^2} \frac{\text{Re}_b}{\text{Fr}} \quad (\text{Bd. 2})$$

$$\text{Drag greater than buoyancy if: } \text{Fr} > \frac{8}{3} \frac{1}{C_D} \quad (\text{Bd. 3})$$

Those three conditions can be seen as boundaries in a  $(\text{Ja}_w^2/\text{Pr}_L ; \text{Re}_b)$  plane. With a given fluid and bubble diameter  $D = 2R$ , we can represent the different regimes of force dominance by plotting those three boundaries simultaneously on a regime map. Eq. Bd. 3 corresponds to a vertical line in the plane since  $C_D \sim \frac{1}{\text{Re}_b}$ . An example of such a map is presented on Figure 5.14.




Figure 5.14: Regime map regarding departure by sliding. Boundaries plotted for water at 1 bar and  $D_d = 0.5\text{mm}$ . ( $K = 2$ )

This allows to visualize the operating conditions under which each of the detaching forces will be dominant. Logically, buoyancy dominates for low Fr numbers, thus low  $\text{Re}_b$  regimes contrary to drag. Added mass dominates when values of  $\text{Ja}_w^2/\text{Pr}_L$  are high *i.e.* when bubble grows rapidly.

#### 5.4.1.1 Influence of Pressure

On Figure 5.15, we draw the regime map for 3 different pressures and associated orders of magnitude of bubble departure diameter [54].

The impact of pressure is mostly seen through the decrease of bubble departure diameter. As pressure increases, buoyancy force decreases while drag and added mass forces display much larger dominance zones. The competition between those two terms mainly relies on the competition between liquid flow velocity and wall superheat or heat flux.

#### 5.4.1.2 Comparison between Fluids

On Figure 5.16, we compare the dominance zones for R12 at 26 bar and water at 155 bar. Moderately pressurized R12 (10 to 30 bar) has often been used as a simulating fluid to mimic water in PWR since




Figure 5.15: Regime map plotted for water at different pressures and bubble departure diameters. ( $K = 2$ )

it has the same density ratio and Weber number for instance (see Section ?? related to the DEBORA experiments).




Figure 5.16: Regime map for R12 as simulating fluid for PWR.  $D_d = 0.05\text{mm}$  is chosen according to R12 measurements from Garnier *et al.* [31] who observed bubbles of  $\sim 0.1\text{mm}$  diameter after lift-off. The same value is taken for water. ( $K = 2$ )

Assuming that the conservation of Weber and Boiling numbers may lead to similar bubble departure diameters, we can observe that the boundaries between the two fluids are very close. This qualitatively indicates that R12 shall present bubble departure by sliding mechanisms similar to what happens in PWR.

**Remark :** This approach could easily be applied to comfort the confidence one may have in extrapolating the observations done using a simulating fluid to industrial applications.

#### 5.4.2 Application to Experimental Data

Now we want to apply this non-dimensional approach to experimental measurement in order to determine the actual bubble departure by sliding regimes. We rely on 7 experiments in which bubble departure diameters in vertical flow boiling were measured. The operating conditions are gathered in Table 5.3.

Author	Fluid	$D_h$ [mm]	$P$ [bar]	$G_L$ [kg/m <sup>2</sup> /s]	$\Delta T_L$ [K]	$\phi_w$ [kW/m <sup>2</sup> ]	$\Delta T_w$ [K]	$D_d$ [mm] ( $N_{mes}$ )
Thorncroft [104] (1998)	FC-87	12.7	N.A.	0 - 319	0.99 - 3.27	2.83 - 11.8	0.54 - 6.89	0.094 - 0.237 (10)
Maity [69] (2000)	Water	20	1.01	0 - 239.6	0.3 - 0.7	N.A.	5 - 5.9	0.788 - 1.71 (9)
Chen [10] (2012)	Water	3.8	1.2 - 3.35	214 - 702	14.5 - 30.3	83.6 - 334	N.A.	0.549 - 2.255 (22)
Sugrue [99] (2014)	Water	16.6	1.01	250 - 400	10 - 20	50 - 100	2 - 6	0.229 - 0.391 (16)
Guan [39] (2014)	Water	9	1.01	87.3 - 319.2	8.5 - 10.5	68.2 - 104	4.5 - 8.5	0.62 - 1.85 (12)
Ren [88] (2020)	Water	3.8	2 - 5.5	488.4 - 1654	28.7 - 51	160.7 - 643.2	N.A.	0.045 - 0.111 (42)
Kossolapov [57] (2021)	Water	11.8	19.9 - 39.8	500 - 1500	10	178 - 613	10.1 - 16.2	0.01 - 0.047 (11)

Table 5.3: Bubble departure diameters data sets in vertical flow boiling

If the value of  $\Delta T_w$  is not available in the considered data-set, we estimate it  $\Delta T_w$  using Frost & Dzakowic correlation [29].

$$\Delta T_w = \text{Pr}_{L,sat} \sqrt{\frac{8\sigma\phi_w T_{sat}}{\lambda_L \rho_V h_{LV}}} \quad (5.107)$$

To place experimental measurements on the non-dimensional map, we need a bubble detachment diameter value  $D_d$  to plot the dominance zones. Since measured  $D_d$  vary significantly in each experiment, we draw the boundaries for the maximum and minimum values of  $D_d$  as shown on Figure 5.17a. If the considered data covers different pressures, boundaries for each pressure are plotted to exhibit its impact (Figures 5.17d, 5.17e and 5.17f). We chose a value of  $K = 1$  to draw the boundaries.

The Figure 5.17 shows that for most of the low pressure experiments, the detaching forces are the added mass and the buoyancy. Smaller bubbles are mainly detached under the effect of the added mass force (Figures 5.17c, 5.17d and 5.17e). When the bubbles detach at higher diameters, the impact of the buoyancy force naturally increases and is comparable to the added mass force (Figures 5.17a and 5.17b).

When the pressure increases, we observe that the experimental measurements gradually move towards the drag dominant zone as seen on Figures 5.17e and 5.17f. This main difference in the dynamic regime when bubble departs by sliding arises from multiple effects:

- The decrease of  $\rho_L / \rho_V$  with pressure, thus reducing  $\text{Ja}_w$  and the impact of the detaching added mass term ;
- The higher liquid mass fluxes in Kossolapov experiments, increasing the impact of the drag ;
- The decrease of  $D_d$  with pressure, reducing the magnitude of buoyancy.

However, we see that some measurements lie close to the added mass / drag boundary (Figure 5.17f), indicating that the added mass force still plays a significant role for bubble detachment. This means that regardless of the operating pressure, the detaching term associated to the coupling between bubble growth and outer liquid flow should not be neglected in the force balance (Eq. 5.104).




Figure 5.17: Regime maps for each water data sets from Table ??.

### 5.4.3 Departure Diameter Prediction

#### 5.4.3.1 About the Use of Empiricism

As previously mentioned, the case of bubble detachment in vertical flow boiling is particular since only one force maintains the bubble attached to its nucleation site: the capillary force (Eq. 5.104). Its expression depends on the contact angle  $\theta$ , the half-angle of hysteresis  $d\theta$  and the bubble foot radius  $r_w$  (or ratio to bubble diameter  $r_w/R$ ) and is thus very sensitive to those values.

Paradoxically, those terms are among the least precisely known due to the difficulty of measurement and associated uncertainties. For instance, conducting precise evaluations of the contact angle near the bubble

base through optical techniques can be challenging because of the strong temperature gradients close to the heated surface leading to a strong deformation of the bubble image.

Consequently, empirical choices have to be made in order to set a value to those parameters, often by relying on data-fitting or approximate measurements in other conditions. For instance, contact angles are often taken as arbitrary average values [88] or measurements in room conditions [99] and applied over a whole set of experiments. This is questionable since contact angle is unlikely to remain unchanged over different operating conditions and surfaces with varying roughness, properties and wall superheat. [98].

However, no better information except those given by the authors can be used to evaluate the capillary force since no generic model exist to compute the contact angle and hysteresis. In this work, admitting a significant uncertainty (typically 5°, as in Guan [39]), we will use the following values for the contact angles :

- $\theta_u = 25.3^\circ$  and  $\theta_d = 6.6^\circ$  for Thorncroft data (measured values for FC-87 on nichrome [105]) ;
- $\theta_u = 50^\circ$  and  $\theta_d = 40^\circ$  for Maity data (measured average contact angles for each bubble during its lifetime [69]) ;
- $\theta_u = 130^\circ$  and  $\theta_d = 65^\circ$  for Chen data (chosen values in their study following measurements for water on stainless steel at high temperature by Kandlikar *et al.* [51]) ;
- $\theta_u = 91^\circ$  and  $\theta_d = 8^\circ$  for Sugrue data (measured values at room temperature [101]) ;
- $\theta_u = 75^\circ$  and  $\theta_d = 30^\circ$  for Guan data (measured average value through experimental visualizations [39]) ;
- $\theta_u = 45^\circ$  and  $\theta_d = 36^\circ$  for Ren data (chosen values in their study [88]) ;
- $\theta = 80^\circ$  for Kossolapov data (typical contact angle for water on ITO [57]) and  $d\theta = 1^\circ$  assuming that the very small bubbles at high pressure are nearly not tilted.

Similarly, the bubble foot radius  $r_w$  is often empirically assumed to be either constant [53] proportional to the bubble radius [72, 99] or to follow a linear or logarithmic law of  $R$  [39, 122]. That is why we chose to use the truncated sphere hypothesis (Eq. 5.14) to compute  $r_w$  using  $R$  and  $\theta$ .

Finally, we would like to acknowledge that the empiricism to evaluate those parameters represents one of the biggest flaws of the force-balance approach. Indeed, such a model aims to detect small sign changes in a sum of a few  $\mu\text{N}$  of forces that are decades larger as pointed out by Bucci *et al.* [7]. Mechanistic models are thus strongly sensitive to any extra parameter included in the modeling of the forces.

#### 5.4.3.2 Growth Constant Value

As discussed in Section 5.3, a value close to one or lower for the contant  $K$  in the bubble growth rate usually provides reasonable approximation of the bubble radius. In particular, subcooled flow boiling may need smaller values of  $K$ , as well as fluids with high Prandtl numbers.

To avoid a systematic overestimation of the added mass term which could lead to strong underestimations of the departure diameter in cases that would present strong subcoolings, liquid velocity or working fluids with low thermal conductivity, we will use:

$$K = \frac{2b}{\sqrt{\pi}}, \quad b = 0.24 \quad (5.108)$$

as proposed by Yoo *et al.* [116] to model the superheated liquid diffusion growth term.

#### 5.4.3.3 Predictions

We consider the non-dimensional force balance before departure.

$$C_{AM,x} K^2 \frac{\text{Ja}_w^2}{\text{Pr}_L} + \frac{1}{3} \frac{\text{Re}_b}{\text{Fr}} + \frac{1}{8} C_D \text{Re}_b = \frac{1}{2} \frac{f_{C,x}}{\text{Ca}} \quad (5.109)$$

Since we only have the capillary term hindering departure as a first approach, we can suppose that departure is reached when:

$$C_{AM,x}K^2 \frac{\text{Ja}_w^2}{\text{Pr}_L} + \frac{1}{3} \frac{\text{Re}_b}{\text{Fr}} + \frac{1}{8} C_D \text{Re}_b > \frac{1}{2} \frac{f_{C,x}}{\text{Ca}} \quad (5.110)$$

which is similar to considering that the other forces overcome the capillary force.

On Figure 5.18, we show the predictions obtained with the proposed modeling and those obtained with Mazzocco's recent model [72].




Figure 5.18: Predicted bubble departure diameters.  $\pm 50\%$  error bars are indicated.

The model has an acceptable trend on some experimental sets, but strong overestimation occur on the cases of Sugrue. Moreover, we observe significant underestimations on the data of Ren at 2 bar and Thorncroft.

Mazzocco's model provides a good accuracy on the data of Sugrue, Guan, Maity and Ren (2 bar). However, we observe very large overestimation over Thorncroft's measurements and significant underestimation on Chen, Ren (3 and 5 bar) and Kossolapov measurements.

#### 5.4.4 Discussion and accounting for parameters uncertainties

The aforementioned errors observed for the proposed model may originate from various reasons:

- The contact angle proposed for Sugrue cases is high with a large hysteresis, suggesting strongly deformed and flattened bubbles under the truncated sphere hypothesis. Based on images from Sugrue's work [100], a comparison between a real bubble with the assumed shape is presented on Figure 5.19. This shows a huge difference which indicates that the contact angle and hysteresis values may be overestimated. Using the available images, the ratio of the bubble diameter to the

apparent bubble foot would lead to an average contact angle  $\theta \approx 20^\circ$  for a truncated sphere. Noting that a larger inclination is observed for the bubbles under higher mass fluxes leads us to suppose a value  $d\theta \approx 15^\circ$ . This represent a similar inclination to contact angle ratio ( $d\theta/\theta$ ) compared to the initially proposed values. The resulting new shape is also presented on Figure 5.19 and seem to better represent the actual bubble.




Figure 5.19: Initially assumed, real and reassessed bubble shape for Sugrue cases (picture adapted from [100]).


- For cases where limited under and overestimation is observed, we may allow to account for an uncertainty as high as  $5^\circ$  for the average contact angle  $\theta$  and half-hysteresis  $d\theta$ .
- As mentioned earlier, applying the same contact angle and hysteresis over a wide range of measurements is a strong assumption, especially for cases where different pressures and bubble diameter variations are observed. Thus, we may slightly distinguish the applied values of  $\theta$  and  $d\theta$  for different pressures within a given experiment, keeping a change no larger than  $5^\circ$ .
- Kossolapov cases at  $G_L = 500 \text{ kg/m}^2/\text{s}$  are better predicted. Cases under higher mass fluxes (1000 and  $1500 \text{ kg/m}^2/\text{s}$ ) present underestimation that could come from the value of  $d\theta$ . At such mass fluxes, the Weber number can be up to a decade higher and bubbles may thus accept a larger inclination before detachment.
- Cases of Ren and Chen rely on chosen values for  $\theta$  and  $d\theta$  and not on measured ones. They are therefore subject to strong uncertainties. We can note that the values for Chen cases are significantly high.
- The proposed growth law is still rather simple and may miss significant information, especially regarding bubble size and fluid properties such as the Prandtl number.
- Errors on Thorncroft cases may be linked to uncertainties regarding FC-87 properties. Indeed, we use the values given at  $T_{sat} = 29^\circ$  at 1 bar in his work [104]. However, the saturation temperature indicated in his test matrix is close to  $40^\circ$  which means that measurements were conducted at a higher pressure, for which we do not have FC-87 properties.

Therefore, using modified values of  $\theta$  and  $d\theta$  among experimental data sets with no more than a  $5^\circ$  change (except for Sugrue cases reassessed values) leads to predictions on Figure 5.20.

The predictive capacity of the model is significantly enhanced, especially on Sugrue's cases which tends to indicate that the contact angle reassessment was justified under the truncated sphere hypothesis. Table 5.4 summarizes the average errors obtained with the present model and Mazzocco's one.

The proposed model achieves an overall better predictive capability even when excluding measurements from Thorncroft on which Mazzocco's model strongly overestimates the departure diameter. Mazzocco's model is still better on Sugrue and Guan cases since it was built and validated using those measurements. It better predicts results from Ren but only for the 2 bar cases while it underestimates the departure diameter for higher pressures. Those results are a coupled effect of his optimized growth law along with the imposed value of  $r_w/R$  and the use of the inclination angle to hinder departure as mentioned in 5.2.6.

Author	$\theta$ [°]	$d\theta$ [°]
Thorncroft	21	14
Maity	45	10
Chen	92.5	27.5
Sugrue	20	15
Guan	47.5	17.5
Ren (2 bar)	45.5	7.5
Ren (3 bar)	37.5	3.5
Ren (5 bar)	35.5	3.5
Koss. (500 kg/m²/s)	80	0.5
Koss. (1000 kg/m²/s)	80	1
Koss. (1500 kg/m²/s)	80	1.5



(a) Modified contact angle and hysteresis values.

(b) Predicted bubble departure diameters.

Figure 5.20: Proposed model performance while accounting for contact angle uncertainties

Author	Mazzocco	Present model
Thorncroft	4874%	46.2%
Maity	39.7%	13.8%
Chen	83.8%	73.6%
Sugrue	9.73%	21%
Guan	25.5%	44.5%
Ren	40.32%	47%
Kossolapov	78.3%	24.2%
Total (without Thorncroft)	46.58%	43.3%

Table 5.4: Average relative error reached by the models.

The approach demonstrated the importance and the strong influence of the contact angle and hysteresis. A small change of their value (staying in the uncertainty range of 5°) allowed to reach reasonable predictions over a large range of bubble departure diameters with the proposed model, using a reduced number of empirical parameters.

## 5.5 SLIDING PHASE

### 5.5.1 Modeling

After departure, bubbles slide over a distance  $l_{sl}$  which scales the impact of the sliding phenomenon over the wall heat transfer. Achieving good prediction of bubble sliding velocity is then important if one wishes

to correctly quantify its impact. Following the force balance framework presented in Section 5.2, we can write Newton's second law parallel to the wall for the sliding bubble.

$$\rho_V \frac{d(V_b U_b)}{dt} = -\pi R \sigma f_{C,x} + \frac{4}{3} \pi R^3 (\rho_L - \rho_V) g + \frac{1}{2} C_D \rho_L \pi R^2 U_L^2 + \frac{4}{3} \pi R^3 \rho_L \left[ 3C_{AM,x} \frac{\dot{R}}{R} U_{rel} - C_{AM,x} \frac{dU_b}{dt} \right] \quad (5.111)$$

This equation can be re-written to express the bubble acceleration.

$$\left( 1 + \frac{\rho_L}{\rho_V} C_{AM,x} \right) \frac{dU_b}{dt} = \left( \frac{\rho_L}{\rho_V} - 1 \right) g + \frac{3}{8} \frac{C_D}{R} \frac{\rho_L}{\rho_V} (U_L - U_b) |U_L - U_b| + 3 \frac{\dot{R}}{R} \left[ C_{AM,x} \frac{\rho_L}{\rho_V} (U_L - U_b) - U_b \right] - \frac{3}{4} \frac{\sigma}{\rho_V} \frac{f_{C,x}}{R^2} \quad (5.112)$$

Then, we numerically solve this equation from the moment when  $R \geq R_d$  using a first order Euler scheme for a duration close to the experimental sliding time. To assess the validity of Eq 5.112, we modify the growth constant  $K$  in order to roughly match experimental radius measurements. The goal is to verify if the force balance allows a good prediction of bubble velocity provided a correct bubble growth. Next sections compare obtained results against low and high pressure data.

### 5.5.2 Low Pressure Sliding

Maity [69] provided simultaneous measurements of bubble radius and velocity over time in vertical boiling for three liquid mass fluxes near saturation conditions. The contact angles were kept the same as in 5.4.3 since Maity provided average values over the bubble lifetime.

Results are displayed on Figure 5.21. The model seems to fairly good predict bubble sliding velocity for the 3 cases. The moment of departure is a bit underestimated as previously observed (Figure 5.18).

The biggest discrepancy is observed for the case at  $G_L = 143.8 \text{ kg/m}^2/\text{s}$ . The slope of the velocity profile is close to the experiments, but the bubble reaches a nearly constant acceleration too rapidly which yields an approximately constant overestimation of 0.1 m/s.

The case with  $G_L = 239.6 \text{ kg/m}^2/\text{s}$  is well predicted regarding the velocity. However, the growth profile was difficult to match since measurements exhibit significant changes in growth regime after departure, which is probably due to the bubble being large enough to be impacted by the bulk flow. We can note that values of  $K$  between 0.5 and 1 were used to better fit the bubble radius time profile.

Regarding the relative velocity between the bubble and the surrounding liquid, the ratio  $\frac{U_b}{U_L}$  greatly overcomes 1 which means the bubble slides much faster than the liquid. This is a consequence of both the low values of  $G_L$  along with the large bubble sizes inducing a great acceleration by the buoyancy force.

### 5.5.3 High Pressure Sliding

In his work, Kossolapov [57] conducted measurements of radius and sliding length over thousands of individual bubbles and then provided the associated statistical distributions. To compare our model with his measurements, we took the upper and lower bounds of  $R$  and  $l_{sl}$  over time and plotted the associated bands of measured values as shown on Figure 5.22 and 5.23.

Comparisons were done for cases at 20 bar and 40 bar and 3 different values of  $G_L$ . The value of  $d\theta$  for the simulations was kept really small ( $2^\circ$  at 20 bar and  $0.5^\circ$  at 40 bar) since bubble tilt is supposed to reduce during sliding because the relative velocity regarding the liquid flow is diminishing. Moreover, higher pressure means smaller bubbles that are even more unlikely to present a significant contact angle hysteresis. We also want to mention that neglecting the capillary term in Eq. 5.112 had a minor impact over the results except that the bubble accelerates a little bit faster.




Figure 5.21: Bubble sliding velocity predictions on Maity cases

The obtained results are in good agreement with the sliding length profile vs. time, which means bubble sliding velocity is well predicted for those cases. Values of  $K$  between 0.8 and 2 were needed to match the bubble radius measurements.

We see that bubbles are rapidly reaching sliding velocities between 80% and 95% of the local liquid velocity. Only the 20 bar case at  $G_L = 500 \text{ kg/m}^2/\text{s}$  where the bubble departs slightly later, reaching approximately 55% of the liquid velocity.

#### 5.5.4 Comparison of Forces in Sliding Stage

In order to identify the main accelerating forces, we compare the amplitude of the forces during the sliding phase for one low pressure case of Maity and one high pressure case of Kossolapov (Figure 5.24).

It appears that at high pressure and liquid velocity, the drag force is the main driving force and stays positive since the bubble do not slide faster than the rapid surrounding liquid (reaching approximately 80% of the local liquid velocity). On the other hand, larger bubbles observed at low pressure and liquid velocity are accelerated by buoyancy due to their larger volume, with a nearly negligible Drag force. In both cases, the added mass force can not be neglected especially when bubble velocity rises by limiting its




Figure 5.22: Bubble sliding length predictions on Kossolapov cases -  $P = 20 \text{ bar}$

acceleration induced by the larger force (buoyancy or drag in the presented cases). This further emphasizes the importance of a proper derivation of the added mass force regardless of the boiling conditions. The capillary force seem to be a limited but constant slowing term in both cases. Finally, the amplitude of the forces involved can span from roughly  $10 \times 10^{-4} \text{ N}$  at low pressure (much greater than the rate of change of bubble momentum laying around  $10^{-9} \text{ N}$ ) down to a few nN at higher pressure (same order of magnitude as the rate of change of bubble momentum), especially due to the bubble size.

This comparison highlights the fact that the proposed model is able to represent different forces hierarchy depending on the flow conditions and to acceptably predict the associated bubble sliding velocity, which is an encouraging point regarding its generality.

## 5.6 BUBBLE LIFT-OFF

### 5.6.1 Introduction

The question of lift-off for a single bubble in vertical boiling is trickier than for horizontal boiling. Indeed, in horizontal boiling, lift-off is ensured thanks to the buoyancy force that will continuously increase as





(a)  $\phi_w = 0.291 \text{ MW/m}^2$ ,  $\Delta T_w = 10.1 \text{ K}$ ,  $G_L = 500 \text{ kg/m}^2/\text{s}$ (b)  $\phi_w = 0.361 \text{ MW/m}^2$ ,  $\Delta T_w = 10.8 \text{ K}$ ,  $G_L = 994 \text{ kg/m}^2/\text{s}$ (c)  $\phi_w = 0.613 \text{ MW/m}^2$ ,  $\Delta T_w = 12.2 \text{ K}$ ,  $G_L = 1504 \text{ kg/m}^2/\text{s}$ Figure 5.23: Bubble sliding length predictions on Kossolapov cases -  $P = 40 \text{ bar}$ (a) Maity :  $\Delta T_w = 5.9^\circ \text{ C}$ ,  $G_L = 239.6 \text{ kg/m}^2/\text{s}$ (b) Kossolapov :  $P = 40 \text{ bar}$ ,  $\phi_w = 0.613 \text{ MW/m}^2$ ,  $G_L = 1504 \text{ kg/m}^2/\text{s}$ 

Figure 5.24: Amplitude of each force during sliding

the bubble grows. It can also be promoted by the lift force if the bubble slides slower than the liquid. This facilitates the identification of the moment when bubble leaves the surface (Figure 5.25).





Figure 5.25: Visualization of bubble lift-off in horizontal boiling conducted by and adapted from Maity [69]. The detachment of the bubble base from the surface is clear in the last frame.


However, in vertical boiling, the lift-off from the surface only results from the competition between the added mass force and lift force (capillary force and contact pressure compensating each other for a truncated sphere). The added mass force keeps the bubble attached and the lift force which can either promote lift-off or push the bubble against the wall depending on the value of the lift coefficient  $C_L$ . As seen in Subsection 5.2.5, the lift coefficient can become negative when reaching negative relative velocity  $U_{rel}$ , yielding negative non-dimensional shear rates  $Sr$  in Eq. 5.43. In this case, the force balance perpendicular to the wall (Eq. 5.69) will never become positive and thus never predict bubble lift-off using criterion based on the force balance sign.

In addition, those two forces are difficult to precisely evaluate since they rely on complex phenomena such as the bubble growth ( $R$ ,  $\dot{R}$ ,  $\ddot{R}$ ) and the fine hydrodynamics of a bubble attached to a wall. A small error on the evaluation of one of those forces can therefore lead to erroneous predictions of the lift-off phenomenon.

On the experimental side, different behavior for boiling bubbles in vertical boiling have been observed. Single bubble experiments such as those of Maity [69] and Situ *et al.* [97] observed bubble lift-off for single bubble at atmospheric pressure as shown on Figure 5.26.



(a) Lift-off observed in Maity experiment [69]



Diameter (mm): 0.574      0.588      0.609      0.617      0.615      0.605

(b) Lift-off observed in Situ experiment [97]


Figure 5.26: Visualization of bubble lift-off in vertical boiling. The moment when bubble leaves the surface appears less clearly than for horizontal boiling.

Although bubble lift-off is observed for those single bubble cases, the exact moment of lift-off is complicated to identify since the bubbles sometimes stay very close to the wall and can even re-attach to the wall, presenting a bouncing motion while moving close to the wall as in Yoo *et al.* [114].

Contrary to those observations, other authors who realized experimental visualizations of vertical flow boiling of surfaces with numerous bubbles saw that single bubbles did not leave the wall by themselves. For instance, Scheiff [94] observed different possible behaviors in highly subcooled liquid:

- Bubble growth up to an equilibrium diameter while sliding on the wall and keeping the same size.
- Rapid sudden growth of bubbles can enlarge them up to the subcooled liquid, yielding to condensation while sliding on the wall.
- Bubble lift-off under application of a high heat flux (rapid growth) or after coalescence with another bubble on its path.

Similar behaviors of bubbles sliding along the wall and not leaving it until a coalescence occurs have also been reported for vertical flow boiling by Prodanovic *et al.* [84] or Thorncroft *et al.* [104]. In particular, Prodanovic *et al.* mentioned that bubbles that would detach from the wall by themselves cannot be interpreted as typical bubble behavior in those conditions since there were very few of them. Typical experimental visualizations of this nature are presented on Figure 5.27



(a) Boiling visualization by and adapted from Prodanovic *et al.* [84] in the region where bubble coalescence started to occur.

(b) Boiling visualization by and adapted from Scheiff *et al.* [93], highlighting the observed layer of sliding bubbles.

Figure 5.27: Visualization of boiling surfaces in vertical boiling, where single bubble lift-off is not systematically observed.

Generally speaking, it seems that single bubbles in vertical boiling are not likely to present a lift-off behavior by themselves in every flow conditions that could be explored. As concluded by Okawa *et al.* [80] and discussed in Yoo *et al.* [114], it seems that a more general trigger for bubble lift-off would be either associated to strong deformation / elongation of the bubble shape (inducing a change in the lift coefficient) or to a coalescence event between two bubbles.

**Note :** Such a lift-off mechanism is considered by Gilman & Baglietto [36] who consider lift-off when the Eotvos number of the bubble reaches 0.1.

To further discuss this question, we will nevertheless try to consider the bubble lift-off as a single event and therefore try to attribute a given lift-off diameter  $D_{lo}$  based on available experimental measurements.

### 5.6.2 Experimental Measurements of Lift-Off Diameter

Observations and measurements of bubble diameter in various flow conditions have been conducted by numerous authors since the middle of the XX<sup>th</sup> century. Although recent experimental techniques allow to identify the moment at which bubble diameter is measured (departure from nucleation site, lift-off, etc.), older experiments could not ensure the nature of the bubbles that were observed.

For instance, the work of Ünal [124] measured the maximum bubble diameter and used other experimental results (Gunther [44], Griffith [38], Treshchев [107] and Tolubinsky [106]) to build a correlation. However, it can not be clearly stated that those measurements were single bubbles lifting off the surface or bubbles resulting of coalescence.

**Remark :** As explained by Ünal, their measurements (detailed in De Munk [79]) are based on enlarged photographic observations of the bubble population near the boiling surface from which they extracted the maximum diameter, meaning there is no evidence that it was actually a lift-off diameter of a single bubble.

This was also pointed out by Kossolapov [57] who showed that at very high pressure, old measurements of bubble diameter were larger for flow boiling compared to pool boiling, which is intuitively unphysical. This could be explained as mentioned above if those measurements were actually coalesced bubbles which would naturally exhibit larger diameters than single bubbles at lift-off.

However, those measurements can still be interesting since their evolution with the operating conditions should present trends similar to single bubble experiments. To do so, we gathered several experimental data sets of maximum / lift-off diameter from the literature for vertical subcooled flow boiling of water. The experimental conditions of the data set are presented on Table 5.5.

### 5.6.3 Influence of the Flow Boiling Conditions

To evaluate the influence of the flow boiling conditions over the various experimental measurements, we have represented the values of the non-dimensional lift-off diameter  $\frac{D_{lo}}{L_c}$  ( $L_c$  is the capillary length) versus 6 dimensionless flow parameters:

- The reduced Jakob numbers of superheat and subcooling  $Ja_w^*$  and  $Ja_L^*$ . With  $Ja^* = \frac{c_{p,L}\Delta T}{h_{LV}}$  which excludes the impact of pressure through the density ratio.
- The density ratio  $\rho^* = \frac{\rho_L}{\rho_V}$ , scaling the operating pressure.
- The saturated liquid Prandtl number  $Pr_L$ , quantifying the liquid thermal properties.
- The local wall Reynolds number  $Re_\tau = \frac{\rho_L U_\tau L_c}{\mu_L}$ , evaluating the impact of the liquid flow, with  $U_\tau$  the shear friction velocity as in Eq. 5.72.
- The capillary number  $Ca$  which can be related to bubble deformability under viscous effects.

The results are presented on Figure 5.28.

The experimental values of  $\frac{D_{lo}}{L_c}$  display the following trends:

- Increase with  $Ja_w^*$  ;
- Decrease with  $Ja_L^*$  ;
- Increase with  $\rho^*$  ;
- Increase with  $Pr_L$  ;
- Decrease with  $Re_\tau$  and  $Ca$ .

Author	Fluid	$D_h$ [mm]	$P$ [bar]	$G_L$ [kg/m <sup>2</sup> /s]	$\Delta T_L$ [K]	$\phi_w$ [kW/m <sup>2</sup> ]	$\Delta T_w$ [K]	$D_{lo}$ [mm] ( $N_{mes}$ )
Gunther [44] (1951)	Water	6.92	1 - 1.7	1492 - 6070	33 - 86	2.3 - 10.64	N.A.	0.32 - 1.02 (12)
Griffith [38] (1958)	Water	12.7	34.5 - 103	4651 - 7593	11 - 80	3.25 - 8.53	N.A.	0.081 - 0.146 (6)
Treshchev [107] (1969)	Water	10.18	5 - 50	1643 - 1789	30 - 62	1.4 - 2.9	N.A.	0.12 - 0.26 (3)
Tolubinsky [106] (1970)	Water	10	1 - 10	72.6 - 198.4	5 - 60	0.47	N.A.	0.19 - 1.24 (9)
Ünal [124] (1976)	Water	8	139 - 177	2082 - 2171	3 - 5.9	0.38 - 0.55	N.A.	0.11 - 0.18 (7)
Maity [69] (2000)	Water	20	1.01	0 - 239.6	0.3 - 0.7	N.A.	5 - 5.9	1.8 - 2.4 (4)
Prodanovic [84] (2002)	Water	9.3	1.01 - 3	76.7 - 815.8	10 - 60	0.1 - 1.2	N.A.	0.366 - 2.68 (44)
Situ [97] (2005)	Water	19.1	1.01	471.8 - 910.8	1.5 - 20	0.06 - 0.2	N.A.	0.145 - 0.605 (90)
Chu [9] (2010)	Water	22.25	1.45	301 - 702	3.4 - 22.6	0.135 - 0.201	N.A.	0.51 - 1.71 (14)
Ahmadi [1] (2012)	Water	13.3	0.96 - 1.13	169 - 497	8.4 - 20.6	0.16 - 0.318	11.4 - 18.4	0.12 - 3.9 (13)
Okawa [81] (2018)	Water	14	1.27 - 1.86	252 - 490	10 - 39	0.161 - 0.487	N.A.	0.64 - 0.188 (10)

Table 5.5: Bubble lift-off diameters data sets in vertical flow boiling

A great range of  $D_{lo}$  values at low pressure (for which we have the larger number of measurements) are reached in the experiments. This further indicates the complicated behavior of bubble lift-off, for which similar flow conditions can lead to very different bubble diameters.

**Remark :** This variation could be associated to the heater material and surface morphology, which are not quantified here.


Moreover, we can observe that measurements from Ünal do not follow the general tendency of other data as on Figure 5.28c, with values of  $D_{lo}/L_c$  above the trend, further supporting the assumption that those experimental values were actually those of coalesced bubbles.

#### 5.6.4 Predicting the Lift-Off with a Force Balance

As previously discussed, the prediction of the lift-off using the force balance perpendicular to the wall (Eq. 5.69) is complicated because:

- The spherical shape without tilt ( $d\theta = 0$ ) leads to exact compensation between contact pressure force and capillary force. Leaving only the added mass force and lift force to predict the lift-off.
- Those two forces can both be directed towards the wall depending on the flow conditions, making it impossible for a single bubble to lift-off by itself.
- The estimation of those forces rely on complicated description of thermal and hydrodynamic phenomena, making any uncertainty a source of large errors on lift-off prediction.

This difficulty has already been pointed out by Montout [78] who faced difficulties in consistently using the force balance perpendicular to the wall for bubble lift-off. Depending on the flow conditions, the force

Figure 5.28: Evolution of  $D_{lo}/L_c$  depending on the flow conditions.

balance would sometimes predict an immediate lift-off right after or even before departure by sliding, which is in contradiction with aforementioned experimental observation.

Following a similar approach to the departure diameter (Section 5.4), we can rearrange Eq. 5.69 into the following non-dimensional force balance perpendicular to the wall, supposing that  $U_{b,y} = \dot{R}$ :

$$\underbrace{\rho^* \left( \frac{C_L}{8} + \frac{C_{AM,y3}}{3} \right)}_{\text{Promotes lift-off}} - \underbrace{\frac{1}{3} \left[ \rho^* (2C_{AM,y1} + C_{AM,y2}) + \frac{2}{3} \right] \left( \frac{K^2 \text{Ja}_w^2}{\text{Pr}_L \text{Re}_b} \right)^2}_{\text{Hinders lift-off}} > 0 \quad (5.113)$$

This formulation sums up the competition between the lift-off promoted by the first term on the LHS combining effect of the lift force and the added mass force due to the external flow versus the growth terms that will hinder the lift-off by pushing the bubble against the wall.

**Remark :** Eq. 5.113 mathematical formulation present some coherent trend with physical observations:

- The hindering term will increase with bubble growth rate (*i.e.*  $\text{Ja}_w$  increase) thus increasing  $R_{lo}$  ;
- The hindering term will reduce with the liquid velocity (*i.e.*  $\text{Re}_\tau$  or  $\text{Re}_b$  increase), thus reducing  $R_{lo}$ .

Other influence of the flow parameters are less directly possible to anticipate.

The solving of the equation of bubble departure (Eq. 5.104) and sliding (Eq. 5.112) while checking when Eq. 5.113 detects lift-off can be performed to estimate the lift-off diameter  $D_{lo}$ . Applied over the experimental database of Table 5.5, this yields the predictions of Figure 5.29.




Figure 5.29: Prediction of Eq. 5.113 versus data from Table 5.5. Value of  $K = 0.24$  was used and only converged points are presented.

First, it is important to note that among every experimental data used for comparisons, many points did not converge to a lift-off diameter value, Eq. 5.113 failing to become positive at any moment of the simulated bubble lifetime. As a consequence, 61 measurements (27 from Prodanovic, 5 from Tolubinsky, 3 from Maity, 13 from Ahmadi, 6 from Chu, 7 from Okawa) out of 211 could not be compared to the force balance approach.

For the converged cases, this yields an acceptable order of magnitude at low pressure especially for Situ data. On the contrary, high pressure measurements are greatly underestimated with lift-off diameters lower than  $1\mu\text{m}$ .

At last, even though the force-balance approach presents many interests for modeling grounds, its application to lift-off prediction in vertical boiling seems a bit tricky contrary to the departure by sliding. The sole competition based on fine hydrodynamics (lift and added mass) and the bubble growth (for which a proper complete modeling is still unavailable) makes it a very complicated solution to address the lift-off diameter estimation problem.

### 5.6.5 A Simple Non-Dimensional Correlation

Alternatively, in case it would prove to be necessary to define a lift-off diameter value for the HFP model, we propose a simple direct correlation based on non-dimensional parameters characterizing the boiling conditions. We chose to model the value of the non-dimensional lift-off diameter  $D_{lo}/L_c$  using the liquid Prandtl number  $\text{Pr}_L$  at saturation, the density ratio  $\rho^* = \rho_L/\rho_V$ , the reduced Jakob numbers  $\text{Ja}_w^*$  and  $\text{Ja}_L^*$  and the wall Reynolds number  $\text{Re}_\tau$ . Using the `sklearn` module to estimate the value of the coefficient for the multilinear regression over the data of Table 5.5 yields:

$$\frac{D_{lo}}{L_c} = e^{8.43\text{Pr}_L^{-0.005}} \left( \frac{\rho_L}{\rho_V} \right)^{-0.36} \text{Ja}_w^{*1.15} (1 + \text{Ja}_L)^{-6.68} (1 + \text{Re}_\tau)^{-0.53} \quad (5.114)$$

We chose to correlate  $(1 + \text{Ja}_L)$  and  $(1 + \text{Re}_\tau)$  so that the formulation degenerates those terms to 1 for saturated and pool boiling conditions. This simple care is often forgotten in similar approaches [56, 121] where the resulting correlations either diverges or tend to 0 when reaching those conditions.

The correlation is compared to Kommajosyula's correlation [56] on Figure 5.30. The proposed formulation, though simple, allows to reach an average error of approximately 45% over the whole data set versus approximately 94% of error for Kommajosyula's formulation. Even if the approach may lack of detailed physical modeling, it seems appropriate to obtain an acceptable order of magnitude of the lift-off (or maximum observed) bubble diameter over various flow conditions including high pressure.

**Remark :** The use of  $\text{Re}_\tau$  instead of the bulk liquid velocity of Reynolds number allows the correlation to be more easily applied in CFD computations where obtaining bulk quantities from wall cells can be tricky depending on the geometry.

### 5.6.6 Conclusion on the Lift-Off

As discussed in this section, the question of the bubble lift-off in vertical flow boiling is very complicated and can not be answered in a straightforward way. First, we saw that the lift-off is not always observed for individual bubbles that can slide for a very long time before leaving the surface as a result of a coalescence by colliding with an other bubble. This difficulty was also experienced when using the force-balance approach to predict the lift-off diameter, with bubble lifetime and sliding simulations that would not converge, *i. e.* yield a positive force balance perpendicular to the wall that would detach the bubble.

Moreover, existing database, though diverse, are lacking of high pressure measurements using recent experimental techniques. The existing high-pressure data present a qualitative uncertainty regarding the nature of the measured bubbles that can result of coalescence events.

Finally, the question of lift-off in the framework of the HFP model can be answered in three ways:

- 1) No lift-off diameter value is attributed to single bubbles. It is thus computed by solving the bubble sliding until it collides and coalesces with an other bubble growing on its nucleation site. This approach is likely to be the most representative of the general behavior of bubbles in vertical boiling according to experiments. However, it may lead to very large, if not unphysical, values of sliding length at low heat fluxes values where the average distance between bubbles would increase greatly.
- 2) Same as above 1) but the lift-off is considered when a non-dimensional number representative of bubble deformation reaches a critical value. Several bubble coalescence can thus occur until that moment occurs.




Figure 5.30: Comparison of simple direct correlations with data from Table 5.5

- 3) A lift-off / maximum diameter is attributed for single bubble behaviors and sliding is computed between the fixed values of  $D_d$  and  $D_{lo}$ , with coalescence that can be considered between those two events and trigger earlier lift-off. This choice would be in fewer concordance with experimental observations but would allow to consider distinct bubble lifetime scenario including full single bubbles.

## 5.7 CONCLUSION

In this chapter, we discussed the different aspects of boiling bubble dynamics in vertical flow boiling. This is a pivotal aspect of the HFP to reach modeling representative of the boiling phenomenon. However, the great variety of both experimental observations and existing models demonstrate the high complexity of the physics at stake here. At last, we can conclude that:

- The problem of bubble growth in complicated conditions (external flow, subcooling, wall presence) remains an open question that could benefit from new experimental insights trying to account for those effects. A new model based on simple heat diffusion accounting for subcooling was proposed and could achieve better predictions compared to traditional model when using a correct value of the thermal boundary layer thickness  $\delta$ . However, a general precise estimation of  $\delta$  is complicated

and simpler model of the form  $R = KJa_w\sqrt{\eta_L t}$  can also propose reasonable predictions provided an optimal choice of  $K$ .

- Modeling the bubble dynamics through a force balance faces modeling uncertainties that still have to be leveraged, especially regarding wall-related effects (contact angle, thermal properties, etc.). Nonetheless, the development of a simpler force balance with less empiricism and enhanced forces expressions allowed to reach acceptable predictions of the departure by sliding diameter  $D_d$  over a large database in vertical boiling.
- The same force balance was also able to propose good estimations of the bubble sliding velocity along the wall, both at low and high pressure.
- A similar approach was more complicated to apply for lift-off predictions due to the high sensitivity of the force balance perpendicular to the wall. Moreover, single bubble lift-off can not be considered as a general bubble behavior in vertical boiling according to many experimental observations.
- The many different correlations for bubble dynamics predictions are tied to their establishment range and can lack of generality or present undesirable mathematical behavior (*e. g.* divergence or tending to 0 in pool boiling or saturated conditions). A direct correlation was proposed to estimate the bubble lift-off diameter (or maximum bubble diameter for a single bubble) based on a large experimental database in vertical boiling. The simple use of terms in the form  $(1 + Ja_L^*)^a$  and  $(1 + Re_\tau)^b$  that degenerates to 1 in pool or saturated boiling allow the correlation to be applied in any flow conditions.

# 6

---

## CLOSURE LAWS AND CONSTRUCTION OF A NEW HEAT FLUX PARTITIONING MODEL

---

### Contents

---

6.1	Introduction . . . . .	97
6.2	Single-Phase Heat Transfer Coefficient . . . . .	98
6.3	Nucleation Site Density . . . . .	100
6.3.1	Existing Correlations . . . . .	101
6.3.2	Comparison with Experimental Measurements . . . . .	103
6.4	Growth time . . . . .	104
6.5	Waiting Time . . . . .	105
6.5.1	Existing Models . . . . .	105
6.5.2	Experimental Measurements . . . . .	107
6.5.3	Evaluation of the Models . . . . .	108
6.6	Considerations on Bubble Interactions and Nucleation Sites Deactivation . . . . .	110
6.6.1	Nucleation Site Distribution . . . . .	110
6.6.2	Static Deactivation . . . . .	112
6.6.3	Static Coalescence . . . . .	113
6.6.4	Sliding Coalescence . . . . .	114
6.7	Bubble Sliding Length . . . . .	115
6.8	Single Bubble Quenching Area . . . . .	117
6.9	Assembling a New Heat Flux Partitioning . . . . .	118
6.9.1	Liquid Convective Heat Flux . . . . .	118
6.9.2	Static Coalescence Evaporation Heat Flux . . . . .	119
6.9.3	Sliding Coalescence Evaporation Heat Flux . . . . .	119
6.9.4	Quenching Heat Flux . . . . .	119
6.9.5	Vapor Convective Heat Flux . . . . .	120
6.9.6	Liquid Convection Area . . . . .	120
6.9.7	Model Summary . . . . .	120
6.10	Conclusion . . . . .	123

---

### 6.1 INTRODUCTION

When constructing a Heat Flux Partitioning model, different modeling steps have to be followed:

- Definition of the heat transfer mechanisms to be accounted for ;
- Identification of the physical parameters requiring a specific computation ;
- Conduct analytic approaches or correlation selection to choose dedicated closure laws.

In this work, we want to account for four different heat fluxes:

- The liquid convective heat-flux :
- The evaporation heat flux ;
- The transient conduction / quenching heat flux including the impact of sliding bubbles ;

- The vapor convective heat flux located at dry spot locations beneath bubble footprints.

The evaluation of those different heat fluxes requires to model a certain number of parameters, namely:

- The single-phase heat transfer coefficient toward the liquid phase  $h_{c,L}$ ;
- The nucleation site density  $N_{sit}$ , representing the number of cavities per unit of area where bubbles will be allowed to nucleate ;
- The different times involved in the bubble nucleation cycle, *i.e.* the growth time until bubble departure by sliding  $t_{g,d}$  and the waiting time between two nucleation events on a site  $t_w$  ;
- The bubble dynamics at the wall, including bubble departure radius  $R_d$ , sliding velocity  $U_b$ , lift-off (discussed in Chapter 5), sliding length  $l_{sl}$  and area  $A_{q,1b}$  ;
- Possible interactions between bubbles (coalescence) or nucleation sites (deactivation).

In this Chapter, we will go through each physical parameter and discuss their modeling in the light of experimental measurements when possible. Finally, a new model formulation for the Heat Flux Partitioning is proposed in Section 6.9.

## 6.2 SINGLE-PHASE HEAT TRANSFER COEFFICIENT

The choice of a proper correlation to compute the single-phase heat transfer coefficient is a first but unavoidable step to build a HFP model. Indeed, if the single-phase convection term is badly computed, the resulting boiling model will fail to predict the wall temperature. For instance, if the liquid convective HTC is overestimated, it would result in a delayed increase of the boiling and quenching heat fluxes which would in turn lead to an overprediction of the wall temperature.

To assess existing correlations for the single-phase HTC, we will use wall temperature measurements extracted from experimental boiling curves for water where  $T_w \leq T_{sat}$ . They correspond to the single-phase part of the experimental data later used to assess the HFP model. As discussed before, good prediction of the single-phase HTC is very important in the frame of boiling heat transfer, which means achieving good wall temperature predictions prior to the Onset of Nucleate Boiling. The chosen data are presented on Table 6.1.

Author	$D_h$ [mm]	$P$ [bar]	$G_L$ [kg/m <sup>2</sup> /s]	$\Delta T_L$ [K]	$\phi_w$ [MW/m <sup>2</sup> ]	$T_{sat} - T_w$ [K]	$N_{mes}$ [-]
Kossolapov [57] (2021)	12	10.5	500 - 2000	10	0.1 - 0.6	0.22 - 9.5	12
Richenderfer [89] (2018)	15	1 - 5	1000 - 2000	10-20	0.1 - 0.63	1 - 18.7	13
Jens-Lottes [48] (1951)	5.74	137.9	2617.5	53.3 - 92.2	0.91 - 2.37	0.33 - 44.1	15
Kennel [52] (1948)	4.3 - 13.2	2 - 6.2	284 - 10 577	11.1 - 83.3	0.035 - 1.89	0.35 - 69	52

Table 6.1: Experimental data range of wall temperature measurements from the single-phase part of boiling curves.  $N_{mes}$  is the number of measurements of each data set.

On Figure 6.1, we compare the results of wall temperature prediction in the single-phase region obtained with the correlation of Dittus-Boelter (Eq. 2.20) and Gnielinski (Eq. 2.21).

**Note :** The Gnielinski correlation is used in Kommajosyula's HFP model to compute the liquid heat transfer coefficient.

The two correlations are of similar efficiency regarding wall temperature predictions over the considered data sets. They both have very good agreement with Kennel data and clear overestimations of  $\Delta T_w$  on Richenderfer and Kossolapov measurements. The slope difference compared to the parity implies that the correlations are predicting too small Nusselt numbers for those cases. Regarding Jens-Lottes data, both models underestimate the wall temperatures, with better results achieved by Gnielinski correlation.




Figure 6.1: Predictive capability of wall temperature by single-phase heat transfer correlations.  $\pm 3K$  error bars indicated.

**Remark :** We tested different friction factor along with different values of wall roughness in the Gnielinski correlation and observed a negligible impact on the overall results. This allows to stay with a simple formulation for the friction coefficient.

The error obtained on Richenderfer and Kossolapov data can be explained by the definition of the HTC computed by Gnielinski correlation. Indeed, Gnielinski correlated a Nusselt number associated to a forced convection coefficient  $h_{fc,Gniel}$  in the case of a internal flow with a completely heated wall. However, only one side of the channel is heated in Richenderfer ans Kossolapov experiments. If  $S_{heat}$  denotes this actual heated surface, then Gnielinski correlation estimates the HTC for a surface  $4S_{heat}$ . With the same imposed total heat power  $\Phi_w$  and bulk liquid temperature  $T_L$ , we have:

$$h_{fc,Gniel} = \frac{\Phi_w}{(T_{w,Gniel} - T_L) 4S_{heat}} \quad (6.1)$$

$$h_{fc,exp} = \frac{\Phi_w}{(T_{w,exp} - T_L) S_{heat}} \quad (6.2)$$

Writing  $T_{w,Gniel} = T_{w,real}$  then yields:

$$h_{fc,exp} = 4h_{fc,Gniel} \quad (6.3)$$

**Remark :** This correction can be interpreted as using the thermal diameter instead of the hydraulic diameter, which is 4 times smaller when only one side of the channel is heated.

On Figure 6.2 we display the predictions of Gnielinski correlation including this correction by a factor 4 on the HTC for Richenderfer and Kossolapov cases. On the same Figure, we also present predictions achieved with the local HTC estimation implemented in NCFD (Eq. 1.23), using a value of  $y^+ = 100$ .

The NCFD approach yields predictions similar to the 1D correlations (Figure 6.1) with larger underestimations on Jens-Lottes measurements. On the other hand, we see that applying a constant correction to the Gnielinski correlation (4 for Kossolapov and Richenderfer cases, 0.9 for Jens-Lottes cases) suffices to yield accurate predictions on the whole range of wall temperature measurements.

**Remark :** The NCFD law was tested without running CFD simulations. The equations were re-written in python to allow its testing outside of the whole code. The use of  $y^+ = 100$  as well as the Mac Adams correlation (Eq. 5.72) for the friction velocity  $U_\tau$  may induce a difference with the predictions that could be achieved by running a complete CFD computation of the considered cases.




Figure 6.2: Predictive capability of wall temperature by NCFD law and Gnielinski correlation including corrections.  $\pm 3K$  error bars indicated (dashed lines).

The average errors obtained with each model are summed up on Table 6.2

Model	Kossolapov err. [K]	Richenderfer err. [K]	Jens-Lottes err. [K]	Kennel err. [K]
Dittus-Boelter [23]	19.67	15.07	10.09	3.13
Gnielinski [37]	20.31	14.06	6.09	1.74
NCFD law [41]	15.52	9.25	23.69	3.36
Corrected Gnielinski	1.34	3.08	6.09	1.74

Table 6.2: Average errors achieved by the considered models on each data sets.

Recalling that Gnielinski correlation was also providing good results on the DEBORA cases with R12 (Chapter 2) further indicates it as a proper choice regarding single-phase HTC estimation in the HFP model.

**Note :** We will later allow the use of the correction factor when needed to ensure a proper representation of the single-phase part when trying to assess the models associated to boiling.

### 6.3 NUCLEATION SITE DENSITY

The Nucleation Site Density is among the most influencing parameters over the HFP models predictions, particularly regarding wall temperature [**favre\_nureth19**]. Indeed, its value directly controls the density of bubbles generated at the heater and therefore impacts both the boiling ( $\phi_e$ ) and quenching ( $\phi_q$ ) heat fluxes to the first order. Being able to come up with correct predictions of the NSD is thus critical if one wishes to properly capture the thermal behavior of the boiling surface.

In particular, a distinction has to be made between the density of sites or cavities over the surface, which is an intrinsic property of the material, versus the active sites density, *i.e.* the cavities that will actually reach thermal-hydraulics conditions to allow nucleation, which usually depends on the cavity radius  $R_c$ . The smallest cavities are less likely to be flooded by the liquid due to capillary effects and can thus become a place where a vapor bubble will grow.

The active nucleation site density, noted  $N_{sit}$ , is the one of interest when trying to model wall boiling since it control the density of bubbles that can be generated on the heater. Its value is actually influenced by

many parameters being either linked to thermal-hydraulics (wall temperature, pressure, operating fluid) or the heater material (roughness, wettability, thermal conductivity, diffusivity, etc.). That is why it is often estimated through empirical correlations, for which many different expression have been proposed over the years since the end of the XX<sup>th</sup> century as discussed below.

### 6.3.1 Existing Correlations

One of the firstly identified behavior of the NSD was its power dependency with the wall superheat ( $N_{sit} \propto \Delta T_w^m$ ), which is form adopted in the correlation of Lemmert & Chawla [62] :

$$N_{sit} = [210 (T_w - T_{sat})]^{1.8} \quad (6.4)$$

**Note :** This law is used in the HFP model of Kurul & Podowski and NEPTUNE\_CFD to compute  $N_{sit}$ .

However, such an expression misses the influence of other parameters such as pressure, which has been proven to be strongly impacting the range of active cavities that can generate bubbles as shown on Figure 6.3 and induces a larger bubble density over the heater.




Figure 6.3: HSV Visualization of bubble density at various pressures adapted from Kossolapov [57] (left to right: 1.01 bar, 3 bar, 19.8 bar, 75.8 bar).

Moreover, experimental measurements such as in Borishanskii [5] showed that the power dependency on the wall superheat changes by increasing both with pressure and the superheat value itself. This was accounted for by Hibiki & Ishii in 2003 [46] who came up with a new correlation that requires an estimation of the minimum activated cavity radius  $R_c$  :

$$N_{sit} = N_0 \left( 1 - \exp \left( -\frac{\theta^2}{8\mu^2} \right) \right) \left[ \exp \left( f(\rho^+) \frac{\lambda'}{R_c} \right) - 1 \right] \quad (6.5)$$

$$R_c = \frac{2\sigma \left( 1 + \frac{\rho_V}{\rho_L} \right) / P}{\exp \left( \frac{h_{LV}\Delta T_w}{R_g M T_w T_{sat}} \right) - 1} \quad (6.6)$$

$$f(\rho^+) = -0.01064 + 0.48246\rho^+ - 0.22712\rho^{+2} + 0.05468\rho^{+3} \quad (6.7)$$

with  $\theta$  the contact angle,  $R_c$  the cavity radius,  $\sigma$  the surface tension,  $h_{LV}$  the latent enthalpy of vaporization,  $P$  the operating pressure,  $T_w$  and  $T_{sat}$  the wall and saturation temperature in Kelvins,  $R_g = 8.314 \text{ J/mol/K}$  the perfect gas constant,  $M$  the molar mass of the fluid (18 g/mol for water),  $N_0 = 4.72 \times 10^5 \text{ m}^{-2}$ ,  $\mu = 0.722 \text{ rad}$ ,  $\lambda' = 2.5 \times 10^{-3} \text{ m}$  and  $\rho^+ = \log_{10} \left( \frac{\rho_L - \rho_V}{\rho_V} \right)$ .

**Note :** This law is used in the HFP model of Gilman & Baglietto [36] and Kommajosyula [56].

We can note that it also includes the value of the static contact angle  $\theta$  which can be used as a parameter to accounts for wall properties, since it is dependent on the wall roughness, wettability and the operating fluid. Indeed, a high-wetting material (low values of  $\theta$ ) will allow smaller cavities to be flooded by the surrounding liquid, thus hindering non-condensable gases to be captured inside and become a potentially active nucleation site (Figure 6.4).




Figure 6.4: Sketch of the link between bubble contact angle and wettability / cavity flooding

This influence of the contact angle on the NSD was confirmed by experimental observations of Basu *et al.* [4] and was also included in a law correlated on their own measurements :

$$N_{sit} = \begin{cases} 0.34 [1 - \cos(\theta)] \Delta T_w^2 & \text{if } \Delta T_{w,ONB} < \Delta T_w < 15 K \\ 3.4 \times 10^{-5} [1 - \cos(\theta)] \Delta T_w^{5.3} & \text{if } \Delta T_w > 15 K \end{cases} \quad (6.8)$$

Similarly, Zhou *et al.* [122] correlated their measurements, including an influence of the pressure:

$$N_{sit} = N_0 (1 - \cos(\theta)) [\exp(f(P) \Delta T_w) - 1] \quad (6.9)$$

$$f(P) = 0.218 \ln\left(\frac{P}{P_0}\right) + 0.1907 \quad (6.10)$$

with  $N_0 = 55\,395.26 \text{ m}^{-2}$  and  $P_0 = 1.01 \text{ bar}$ .

Finally, one of the most recent NSD correlation has been proposed by Li *et al.* in 2018 [65] and validated over a large range of measurements by including a more realistic power law for  $\Delta T_w$ . It avoids the divergence of  $N_{sit}$  observed in Hibiki & Ishii law (Eq. 6.5) when reaching high pressure and superheats. It also includes the impact of pressure and contact angle and its evolution with temperature *e.g.* its decrease close to 0 ° when approaching the critical temperature [98]:

$$N_{sit} = N_0 e^{f(P)} \Delta T_w^{A \Delta T_w + B} (1 - \cos(\theta)) \quad (6.11)$$

$$f(P) = 26.006 - 3.678e^{-2P} - 21.907e^{-P/24.065} \quad (6.12)$$

$$A = -2 \times 10^{-4} P^2 + 0.0108P + 0.0119 \quad (6.13)$$

$$B = 0.122P + 1.988 \quad (6.14)$$

$$1 - \cos(\theta) = (1 - \cos(\theta_0)) \left( \frac{T_c - T_{sat}}{T_c - T_0} \right)^\gamma \quad (6.15)$$

with  $P$  in MPa,  $\theta_0$  the contact angle at room temperature  $T_0$ , and default value being for water  $\theta_0 = 41.37^\circ$ ,  $T_c = 374^\circ\text{C}$   $T_0 = 25^\circ\text{C}$ ,  $\gamma = 0.719$ .

**Remark :** We can question the absence of bulk liquid velocity and temperature in the presented law since they should logically influence the nucleation process. However, this impact is rather limited as observed in experimental measurements of Zhou *et al.* [122] and Kossolapov [57].

### 6.3.2 Comparison with Experimental Measurements

In order to assess existing NSD correlations and choose the most pertinent to include in a HFP model, we gather NSD measurements from 4 different authors. The different operating conditions of the chosen data sets are gathered on Table 6.3.

Author	Fluid	$P$ [bar]	$G_L$ [kg/m <sup>2</sup> /s]	$\Delta T_L$ [K]	$\Delta T_w$ [K]	$\theta_0$ [°]	$N_{mes}$ [-]
Zhou [122] (2020)	Water	1.21 - 3.12	482.7 - 1930.6	8 - 15	6.7 - 20.2	51	60
Richenderfer [89] (2018)	Water	1.01	500 - 1000	10	21.7 - 42.8	80	49
Kossolapov [57] (2021)	Water	1.01 - 75.8	500 - 2000	80	10	80°	63
Borishanskii [5] (1966)	Water	1.01 - 198	N.A.	N.A.	1.75 - 17.3	45	132

Table 6.3: Nucleation Site Density data in flow boiling

We then compare the predictions achieved by the model of Lemmert & Chawla (Eq. 6.4), Hibiki & Ishii (Eq. 6.5), Zhou *et al.* (Eq. 6.9) and Li *et al.* (Eq. 6.11). The comparison with measurements are presented on Figure 6.5.




Figure 6.5: Predictions of the chosen models against the experimental data of Table 6.3 with  $\pm 50\%$  error bars.  
The contact angles

The Lemmert & Chawla model appears to fail in predicting the NSD at high pressures. This is a logical drawback of its sole dependence on the wall superheat. More importantly it increasingly underestimates the NSD as pressure increases, which makes it a clearly unsuitable correlation to compute  $N_{sit}$  particularly for pressurized flows such as in PWR.

Although the model of Zhou *et al.* includes a pressure term, its partial calibration on data covering a low range of pressure may explain the large error observed when compared to higher pressure measurements.

On the contrary, models from Hibiki & Ishii and Li *et al.* seem to better reproduce the different trends with flow conditions, especially with pressure. The model from Li *et al.* achieves better predictions by avoiding to reach unphysically high values of  $N_{sit}$  at higher wall superheat compared to Hibiki & Ishii. This behavior is clear over Kossolapov data at high pressure, where both model lead to overestimations, the strongest discrepancy being associated to Hibiki & Ishii model.

Overall, the model of Li *et al.* is the most efficient with an acceptable agreement on most of the data of Borishanskii and Zhou *et al.*. The measurements of Richenderfer and Kossolapov fail to be precisely reproduced, but it shows a coherent trend and the most limited error when compared to other correlations.

**Remark :** The coherency of NSD predictions is hard to ensure since we do not know the exact contact angle and boiling surface morphology in the experiments. This was pointed out by Richenderfer [89] who observed significant variation in the NSD value depending on the heater, though keeping the same material (ITO). For instance, this may explain the fact that the NSD measured by Kossolapov at 10.5 bar is higher than any other pressure on his experiment, leading to both underpredictions and overpredictions of the model of Li *et al.* depending on the pressure.

All things considered, those comparisons show that the Nucleation Site Density remains among the most difficult quantity to evaluate because of its very large variations over experiments, boiling surfaces and flow conditions. Dedicated correlations are hardly precise outside of their establishment databases. However, it remains the best yet only way to compute  $N_{sit}$ . **In that regard, the NSD correlation of Li *et al.* appears to be the most coherent choice.**

#### 6.4 GROWTH TIME

As discussed in Section 5.3, the bubble growth can be acceptably modeled as:

$$R(t) = K \text{Ja}_w \sqrt{\eta_L t} \quad (6.16)$$

with value of  $K$  laying roughly between 0.1 and 2 depending on the boiling conditions.

With a given departure radius  $R_d$ , the bubble growth time until departure from nucleation site  $t_{g,d}$  can be estimated as:

$$t_{g,d} = \left( \frac{R_d}{K \text{Ja}_w} \right)^2 \frac{1}{\pi \eta_L} \quad (6.17)$$

**Note :** This formulation is used in Gilman [35] and Kommajosyula [56] HFP models, with their own choice of value for  $K$ .

By correlating their own growth time measurements, Basu *et al.* [4] propose the following relationship including an influence of the liquid subcooling:

$$\frac{D_d^2}{\eta_L \text{Ja}_w t_{g,d}} = 45 e^{-0.02 \text{Ja}_L} \quad (6.18)$$

which is naturally used in their HFP model to compute the bubble growth time.

**Remark :** If precise estimations of the thermal boundary layer thickness is achievable, the new analytic expression of the bubble growth proposed in Eq. 5.101 can be used to express the growth time:

$$t_{g,d} = \left[ \frac{1}{K_a} \ln \left( 1 - \sqrt{1 - \frac{R_d}{R_\infty}} \right) \right]^2 \quad (6.19)$$

with  $K_a$  defined as in Eq. A.25 and  $R_\infty$  in Eq. 5.101.

This formulation requires  $R_d < R_\infty$  the equilibrium radius in subcooled pool boiling. Though this condition seems logical physically speaking, it can't be ensured numerically due to the range of values attainable using correlations or other mechanistic models to estimate  $R_d$ .

## 6.5 WAITING TIME

The waiting time  $t_w$  between two nucleation events on an active site corresponds to the time needed for the thermal boundary layer to reconstruct after its disruption due to bubble departure from the nucleation site. This process is then intrinsically related to the heater properties and the transient heat transfer with the external liquid flow.

### 6.5.1 Existing Models

#### 6.5.1.1 Analytic Approaches

Traditional approaches of the wait time estimation rely on the analytic solution to the transient heat transfer in a semi-infinite medium. Assuming that after bubble departure liquid at  $T_{L,bulk}$  is displaced towards the wall at  $T_w$ , one can solve the the differential problem with the initial and boundary conditions:

$$T_L(y, 0) = T_{L,bulk}, \forall y > 0 \quad (6.20)$$

$$T_L(0, t) = T_w, \forall t \geq 0 \quad (6.21)$$

The solution of this heat transfer problem if given by:

$$T_L(y, t) = T_{L,bulk} + (\Delta T_w + \Delta T_L) \operatorname{erfc} \left( \frac{y}{2\sqrt{\eta_L t}} \right) \quad (6.22)$$

For instance, Mikic & Rohsenow [76] combine this solution with the assumption that a new nucleation will occur over a cavity of radius  $R_c$  when the vapor temperature reaches:

$$T_{V,nuc} = T_{sat} + \frac{2\sigma T_{sat} \left( \frac{1}{\rho_V} - \frac{1}{\rho_L} \right)}{R_c h_{LV}} \quad (6.23)$$

The wait time is then assumed to be the time needed for the transient temperature field to reach  $T_{V,nuc}$  at height  $y = R_c$  i. e.  $T_L(R_c, t_w) = T_{V,nuc}$ . Combining Eq. 6.22 and 6.23 allow to write:

$$t_w = \frac{1}{4\eta_L} \left[ \frac{R_c}{\operatorname{erfc}^{-1} \left( \frac{\Delta T_L}{\Delta T_L + \Delta T_w} + T_{sat} \left( \frac{1}{\rho_V} - \frac{1}{\rho_L} \right) \frac{2\sigma}{(\Delta T_w + \Delta T_L) h_{LV} R_c} \right)} \right]^2 \quad (6.24)$$

$$\approx \frac{1}{\pi \eta_L} \left[ \frac{(\Delta T_w + \Delta T_L) R_c}{\Delta T_w - T_{sat} \left( \frac{1}{\rho_V} - \frac{1}{\rho_L} \right) \frac{2\sigma}{R_c h_{LV}}} \right]^2 \quad (6.25)$$

Using the same approach, Han & Griffith [14] use the same expression of the transient liquid temperature field but consider  $T_L \left( \frac{3}{2} R_c, t_w \right) = T_{V,nuc}$ , which yields a wait time that is  $\frac{9}{4}$  times Eq. 6.25.

Later, Yeoh *et al.* [112] followed a similar derivation to propose an expression of the wait time that accounts for the contact angle value:

$$t_w = \frac{1}{\pi \eta_L} \left[ \frac{(\Delta T_L + \Delta T_w) C_1 R_c}{\Delta T_w - \frac{2\sigma T_{sat}}{C_2 \rho_V h_{LV} R_c}} \right]^2 \quad (6.26)$$

$$C_1 = \frac{1 + \cos(\theta)}{\sin(\theta)} ; \quad C_2 = \frac{1}{\sin(\theta)} \quad (6.27)$$

All those analytical approaches present one pivotal parameter: the activated cavity radius  $R_c$ . It is a very complicated parameter to evaluate since it can vary by decades depending on the flow conditions and the boiling surface morphology.

Among existing expressions of  $R_c$ , we can mention:

$$R_c = \frac{2\sigma T_{sat}}{\rho_V h_{LV} \Delta T_w}, \text{ used by Han \& Griffith [14]} \quad (6.28)$$

$$R_c = \sqrt{\frac{1}{C_1 C_2} \frac{2\sigma T_{sat} \lambda_L}{\rho_V h_{LV} \phi_w}}, \text{ used by Yeoh } et \text{ al. [112]} \quad (6.29)$$

$$R_c = \frac{2\sigma \left(1 + \frac{\rho_V}{\rho_L}\right) / P}{\exp \left(h_{LV} \frac{\Delta T_w}{R_g T_w T_{sat}}\right)}, \text{ used by Hibiki \& Ishii [46]} \quad (6.30)$$

**Remark :** Those analytic expressions do not include the influence of an external liquid velocity, which could have an impact over the wait time since it modifies the hydrodynamics controlling the reconstruction of the thermal boundary layer. In particular, turbulent flows could induce a larger mixing effect between the bulk and the wall thus increasing the time needed to reach sufficient superheat to allow a new nucleation to occur.

### 6.5.1.2 Empirical Correlations

Alternatively, other authors considered the wait time estimation through empirical correlations based on data-fitting on given measurements. For instance, Basu *et al.* [4] proposed:

$$t_w = 139.1 \Delta T_w^{-4.1} \quad (6.31)$$

based on low pressure and low liquid velocity experiments.

**Note :** This expression of  $t_w$  is used in Basu *et al.* HFP model [4].

More recently, Kommajosyula [56] included the effect of the liquid subcooling through the liquid Jakob number  $Ja_L$  as:

$$t_w = 0.061 \frac{Ja_L^{0.63}}{\Delta T_w} \quad (6.32)$$

**Remark :** This expression, used in Kommajosyula's HFP model, will yield  $t_w = 0$  for saturated boiling conditions, which is hardly reasonable since a non-zero wait time exists between two nucleation events even at saturation [34].

### 6.5.2 Experimental Measurements

To try to assess the proposed expressions of the bubble wait time, we rely on some experimental measurements available in the literature from Basu *et al.* [4], Richenderfer [89] and Kossolapov [57]. The boiling conditions of the data are summed up on Table 6.4.

Author	Fluid	$P$ [bar]	$G_L$ [kg/m <sup>2</sup> /s]	$\Delta T_L$ [K]	$\phi_w$ [MW/m <sup>2</sup> ]	$\Delta T_w$ [K]	$t_w$ [ms] ( $N_{mes}$ )
Basu <i>et al.</i> [4] (2005)	Water	1.01	346.0	8.35 - 46.5	N.A.	9.83 - 17.5	0.797 - 13.3 (19)
Richenderfer [89] (2018)	Water	1 - 2	1000 - 2000	5 - 20	0.74 - 7.13	N.A.	0.914 - 6.02 (259)
Kossolapov [57] (2021)	Water	10.5	500 - 2000	10	N.A.	0.12 - 25.9	6.13 - 85.9 (33)

Table 6.4: Bubble wait time data in vertical flow boiling. Wall superheat values for Richenderfer data are estimated using Frost & Dzakowic correlation (Eq. 5.107).

The experimental data are all using water as working fluid. We can see at first glance that values measured by Kossolapov are nearly a decade larger compared to the other experiments. This may be an effect of pressure due to:

- The bubbles that are smaller and depart nearly right after nucleation, leaving wait time as the main part of the nucleation cycle ;
- The wall Jakob number values that are smaller ;
- The heterogeneity in nucleation sites behavior (their number increasing with pressure), with sites exhibiting very large wait time due to their very low nucleation frequency versus very active sites that contributes much more to the overall nucleation. This can partially be explained by the local decrease in wall temperature when a bubble nucleates (acting locally as a heat sink), potentially deactivating the neighboring sites. Averaging over those events as done by Kossolapov [57] may result in a large wait time.




Figure 6.6: Evolution of the wait time values with the wall Jakob number.

On Figure 6.6, we show the evolution of the measures wait times with the wall Jakob number. We can see that the lower values of Jakob number actually correspond to lower wait times, which seems to confirm the previous assumptions.

Moreover, we see that there is a steep decrease of the wait time with  $\text{Ja}_w$ . The slope however changes depending on the data set, which would logically depend on the heater thermal properties as well as on the operating fluid. It seems that the slope followed by Kossolapov data at 10 bar seem to align with that of Richenderfer data at 2 bar, which would exhibit a sort of coherency between those two data sets. On the contrary, values at 1 bar from Basu do not clearly match with Richenderfer data at 1 bar.

The data sets from Kossolapov and Richenderfer also give the associated frequency to each wait time measurement. This allows to plot the product  $t_w \times f$  to evaluate the proportion of the nucleation cycle occupied by wait time. The value of  $t_w \times f$  would physically be expected to tend to 1 when  $\Delta T_w \rightarrow 0$  (highly reduced nucleation) and to 0 when  $\Delta T_w \rightarrow \infty$  due to the intense nucleation and increased transient heat transfer under the high temperature gradient between the wall and the fluid. Experimental values are plotted on Figure 6.7 versus the reduced Jakob number  $\text{Ja}_w^* = \frac{c_{p,L}\Delta T_w}{h_{LV}}$  values to regroup the values by excluding the influence of the density ratio  $\rho_L / \rho_V$ .




Figure 6.7: Evolution of the product  $t_w \times f$  with the reduced Jakob number.

We can see that for lower values of  $\text{Ja}_w^*$ , the product  $t_w \times f$  starts to tend to 1. For higher values, a linear decrease seem to be the general trend of the measurements. However, it can't decrease linearly forever, which is why the trend on Figure 6.7 extrapolated to higher values of  $\text{Ja}_w^*$  looks like a sigmoid in order to approach zero for large superheats. Nevertheless, we clearly lack of measurements at larger values of  $\text{Ja}_w^*$  to confirm this supposed trend.

**Remark :** The range of values attained by the product  $t_w \times f$  can vary from 1 down to 0.5 on the chosen experimental data. This clearly shows that the relation between the wait time and the growth time is not straightforward as assumed in some works who neglects the growth time or suppose a constant relationship such as  $t_w = 3t_g$  [14].

Moreover the boiling conditions range covered by the data are not that exhaustive, leaving room for even larger ranges of  $t_w \times f$  with different fluids and heater material for instance.

### 6.5.3 Evaluation of the Models

Using the data of Table 6.4 to evaluate the different approaches presented above, we obtain the results presented on Figures 6.8 and 6.9.

The correlation of Basu *et al.* naturally performs well on their own data but largely underestimates the wait time for Richenderfer and Kossolapov data. Kommajosyula's formulation produces better results on




Figure 6.8: Predictions using the correlations.  $\pm 50\%$  dashed lines are represented.

the low pressure cases, particularly on Richenderfer cases. However, it fails to capture the increase in  $t_w$  for Kossolapov data and largely underestimates them.




Figure 6.9: Yeoh *et al.* formulation of  $t_w$  with Han & Griffith cavity radius.  $\pm 50\%$  dashed lines are represented.

When testing the analytic formulations of the wait time, we tested different combinations of  $(t_w, R_c)$  expressions. Overall, we saw that the results were strongly dependent on the value of the cavity radius with values that can change by decades depending on the chosen formulation.

At last, it appeared that choosing the Yeoh *et al.* expression of  $t_w$  (Eq. 6.26) along with the cavity radius of Han & Griffith (Eq. 6.28) resulted in good results in average over the three chosen datasets. As we can see on Figure 6.9, it produces overall better results compared to the correlation. Moreover, we used contact angle values that were representative of each experimental conditions according to each author:

- $\theta = 31^\circ$  for Basu *et al.* data [3] (metallic surface) ;
  - $\theta = 72^\circ$  for Richenderfer data [89] (ITO on sapphire) ;
  - $\theta = 80^\circ$  for Kossolapov data [57] (ITO on sapphire).

**Remark :** Obviously, since the wait time results from a transient heat transfer between the wall and the liquid after the bubble departure, it should strongly depend on the wall thermal properties. However, they are not accounted for in the analytic expressions, with solely the contact angle being related to the wall material.

The fact that the analytic expression is able to correctly predict the large range of  $t_w$  values from the different experiments is encouraging since it is based on a physical approach contrary to correlations which mainly relies on data-fitting.

**To conclude, it seems appropriate to use the wait time formulation of Yeoh *et al.* along with expressing cavity radius using Han & Griffith estimation.**

## 6.6 CONSIDERATIONS ON BUBBLE INTERACTIONS AND NUCLEATION SITES DEACTIVATION

### 6.6.1 Nucleation Site Distribution

NSD correlations actually estimate the total number of sites where bubbles can nucleate on a surface. However, experimental observations showed that nucleation sites exhibit largely heterogeneous behaviors. For instance, Figure 6.10 shows experimental observations from Kossolapov [57] that demonstrate the variety of nucleation frequency measured for each site on a boiling surface.




Figure 6.10: Nucleation site distribution by and adapted from Kossolapov [57]. Red circles represent the active sites positions with diameter increasing with the site's nucleation frequency.

This large difference in nucleation frequency between the different sites indicates that a minority of sites contribute to most of the total phase change process. Those differences may originate from different interactions such as:


- Thermal deactivation: a bubble nucleating at a site gathers the energy in the wall to use it for phase change, which in turns locally decreases the temperature and will hinder nucleation to occur at neighboring sites.
- Static deactivation: given a number of active sites, distributing a number of bubbles of radius  $R_d$  over them can lead to overlapping that can not geometrically be accommodated on the wall. This effect was notably considered by Gilman & Baglietto [36].
- Sliding deactivation: if a bubble slides and swipes a given area, sites laying on its path may experience quenching even before holding a nucleating bubble. This consequently will impact their nucleation frequency and may lead to partial deactivation under the sliding effect.

In order to consider such interactions between nucleation sites, we need to know their spatial distribution over the boiling surface. Usual approaches considered that the nucleation sites followed an homogeneous spatial Poisson process *i.e.* the probability of finding a site in an area  $A$  only depends on the value of  $A$  and not on its location over the boiling surface.


This has been supported by different experimental observations such as those of Gaertner [30] or Sultan [102] for pool boiling who found an agreement between site distribution and Poisson process by studying sites populations in subdivisions of the boiling surface. It was also confirmed for flow boiling by Del Valle & Kenning [20] who observed site distribution at different heat fluxes. However, they noticed that the

increase in nucleation site with the heat flux did not come from an additive effect of new sites since some active sites at low heat fluxes became inactive at higher heat fluxes before sometimes reactivating later (see Figure 6.11a). This further highlights that the interactions and deactivation processes originate from complex physics that simultaneously include wall morphology and thermal behavior, external flow influence and bubble presence.

More recent observations also show a random distribution of the sites such as in Zhou *et al.* [121] (Figure 6.11b).



(a) Nucleation site distribution in flow boiling from Del Valle & Kenning [20], each symbol represent a family of active nucleation site observed at different heat fluxes. Black triangles circled in red are sites that deactivate when the heat flux exceeded 70% of the CHF.



(b) Nucleation site distribution at 3 bar by and adapted from Zhou *et al.* [122].

Figure 6.11: Examples of experimental nucleation sites distribution in flow boiling.

Considering an homogeneous spatial (two-dimensional) Poisson process with an event density (*i.e.* average number of events per unit of area)  $\lambda$ , then the probability that the number of events  $N$  in an area  $A$  is equal to  $n \in \mathbb{N}$  is [19]:

$$\mathcal{P}(N(A) = n) = \frac{(\lambda A)^n}{n!} e^{-\lambda A} \quad (6.33)$$

Then, one can express the probability density function of the nearest-neighbor, depending on the distance  $r$  between two events as:

$$f(r) = 2\lambda\pi r e^{-\lambda\pi r^2} \quad (6.34)$$

This special case of Poisson point-processes is also called "Complete Spatial Randomness".

**Remark :** Although observations of the boiling surface presented random distributions of sites close to a Poisson process, Del Valle & Kenning [20] found that the measured nearest-neighbor distance distribution was deviating from Eq. 6.34 for low values of  $r$ .

Eq. 6.34 allows to compute the average distance  $s$  between two events:

$$s = \int_0^{+\infty} r f(r) dr = 2 \frac{\sqrt{\pi}}{4\sqrt{\lambda\pi}} = \frac{1}{2\sqrt{\lambda}} \quad (6.35)$$

**Note :** In the case of boiling physics, the word "event" can refer to active nucleation sites or bubbles on the surface.

From those mathematical expressions, we can then model different type of interactions between sites by choosing proper event densities  $\lambda$ . Further subsections propose treatments of a few of them.

### 6.6.2 Static Deactivation

**Note :** This calculation has originally been conducted by Gilman [36] and continued by Komma-josyula [56].

Let us consider the nucleation site density  $N_{sit}$  computed by a correlation as in Section 6.3. As mentioned earlier, if we distribute a given number of bubbles of radius  $R_d$  over the different sites, we have no guarantee that the correlation avoids too large values of  $N_{sit}$  that would lead to geometrical overlapping as shown on Figure 6.12.




Figure 6.12: Sketch of the geometrical overlapping leading to static deactivation. Bubbles in red can not be accommodated on the surface due to their site laying below an existing bubble.

Thus, we need a correction of  $N_{sit}$  to obtain the actual number of active sites  $N_{sit,a}$  that can geometrically fit on the surface regarding the nucleation parameters. Given a bubble growth time before departure  $t_{g,d}$  and an average nucleation frequency  $f$ , we can estimate the actual number of bubbles growing attached to their sites on the boiling surface as:

$$N_b = t_{g,d} \times f \times N_{sit,a} \quad (6.36)$$

If  $N_b$  is used as an event density in the Poisson process, we can estimate the probability to have an undesired overlapping *i.e.* two simultaneous bubbles of radius  $R_d$  on neighboring sites at a distance  $r \leq R_d$ :




Figure 6.13: Static deactivation correction tested with Hibiki & Ishii and Li *et al.* correlations for water at 40 bar,  $f = 200$  Hz,  $t_{g,d} = 0.1$  ms,  $\theta = 80^\circ$  and  $R_d = 0.01$  mm.

$$\mathcal{P}(r \leq R_d) = 1 - \underbrace{\mathcal{P}(N(\pi R_d^2) = 0)}_{\text{No bubble nucleates within } \pi R_d^2} = 1 - e^{-N_{sit,a} t_{g,d} f \pi R_d^2} = \mathcal{P} \quad (6.37)$$

This overlapping probability  $\mathcal{P}$  can then be used to ponderate the number of sites given by the NSD correlation, yielding:

$$N_{sit,a} = (1 - \mathcal{P}) N_{sit} \quad (6.38)$$

$$\Leftrightarrow N_{sit,a} t_{g,d} f \pi R_d^2 e^{N_b t_{g,d} f \pi R_d^2} = N_{sit} t_{g,d} f \pi R_d^2 \quad (6.39)$$

$$\Leftrightarrow N_{sit,a} = \frac{\mathcal{W}(N_{sit} A_{sit})}{A_{sit}} \quad (6.40)$$

where  $A_{sit} = t_{g,d} f \pi R_d^2$  and  $\mathcal{W}$  is Lambert's W-function (reciprocal of  $x \rightarrow xe^x$ ).

The evaluation of  $\mathcal{W}$  can easily be achieved with a few iterations of a bisection method. Otherwise, Kommajosyula proposed an approximation to allow its direct computation [56].

On Figure 6.13 we show the impact of the correction of Eq. 6.40 on NSD correlations of Hibiki & Ishii (Eq. 6.5) and Li *et al.* (Eq. 6.11).

Li *et al.* correlation present a significant correction for larger wall superheat due to its formulation that damps the exponential growth of the NSD at high superheat. On the contrary, the well-known drawback of Hibiki & Ishii correlation which yields too large  $N_{sit}$  value at high superheat is strongly ponderated by the static deactivation correction.

### 6.6.3 Static Coalescence

Now that the actual number of bubble-generating sites have been identified, we can consider other interaction phenomena that can occur on the boiling surface. For instance, if two bubbles are simultaneously growing on sites at a distance lower than  $2R_d$ , the bubbles will coalesce while growing up to the detachment diameter (Figure 6.14).

Using the bubble density  $N_b$  (Eq. 6.36) as the event density in Eq. 6.34, the probability of static coalescence is:

$$\mathcal{P}(r \leq 2R_d) = \int_0^{2R_d} f(r) dr = 1 - e^{-N_b \pi (2R_d)^2} = \mathcal{P}_{coal,st} \quad (6.41)$$




Figure 6.14: Sketch of the static coalescence phenomenon.

The density of bubble-generating sites that will lead to a static coalescence can then be estimated as :

$$N_{coal,st} = \mathcal{P}_{coal,st} N_{sit,a} \quad (6.42)$$

Figure 6.15 shows the evolution of  $\mathcal{P}_{coal,st}$  with the wall superheat for two departure radius values, using the same conditions as in Figure 6.13.




Figure 6.15: Static coalescence probability with corrected Li *et al.* for water at 40 bar,  $f = 200$  Hz,  $t_{g,d} = 0.1$  ms and  $\theta = 80^\circ$ .

#### 6.6.4 Sliding Coalescence

The question of sliding coalescence is partly addressed by Basu *et al.* [4] (Section 4.3) by comparing the computed sliding distance of a single bubble  $l_{sl,0}$  with the average distance between two active nucleation sites  $s = 1/\sqrt{N_{sit,a}}$  (twice the value obtained if we use the Poisson distribution Eq. 6.35). They suppose that if  $l_{sl,0} > s$  bubble coalescence will occur during the sliding phase and reduces the number of sites generating sliding bubbles.

**Remark :** Their approach is based on the distribution of active nucleation sites  $N_{sit,a}$  and not on the bubble density  $N_b$  which could better represent the average distance between two bubbles actually living on the surface.

Using the spatial distribution, if the total area covered by a single sliding bubble is  $A_{q,1b}$  and the number of sites generating sliding bubbles  $N_{sl}$ , we can estimate:

- The probability of finding no growing bubbles in area  $A_{q,1b}$ , meaning no sliding coalescence (NC):  

$$\mathcal{P}_{NC} = \exp(-N_{sit,a}t_{g,d}fA_{q,1b})$$
- The number of sites generating sliding bubbles without coalescence :  $N_{sl,NC} = N_{sl} \times \mathcal{P}_{NC}$
- The number of sites generating sliding bubbles that will coalesce with others:  $N_{sl,C} = N_{sl} \times (1 - \mathcal{P}_{NC})$
- The number of sites, present in sliding bubbles path, that will not be holding growing bubbles :  

$$N_{nob} = N_{sit,a} \times N_{sl,NC} \times A_{q,1b}$$

Those types of calculations are interesting if one wishes to further distinguish many different types of bubble behavior, and particularly *if we dispose of a sliding length for single bubbles  $l_{sl,0}$  meaning that single bubble lift-off would be considered*. This point being questionable in vertical flow boiling as discussed in Section 5.6.

## 6.7 BUBBLE SLIDING LENGTH

Estimation of the bubble sliding length is critical for the evaluation of the quenching term since it acts as an enhancing factor of the wall area that will undergo transient heat transfer.

As discussed in Section 5.6, is we consider that bubble lift-off occurs when a sliding bubble coalesces with an other bubble growing on its site, the sliding length  $l_{sl}$  shall be close to the average distance between two nucleation bubbles on the boiling surface. This value has been derived in Section 6.6:

$$l_{sl} = s_b = \frac{1}{2\sqrt{N_b}} \quad (6.43)$$

with  $N_b$  the bubble density from Eq. 6.36.

To assess the validity of this assumption, we compare on Figure 6.16 values of sliding length obtained using either the bubble density  $N_b$  or the active site density  $N_{sit,a}$  (Eq. 6.40). Since their expression depend on the values of  $f$ ,  $t_{g,d}$  and  $R_d$ , we take:

- $R_d = 0.015$  mm at 40 bar and  $R_d = 0.02$  mm at 20 bar (see Table 5.3) ;
- $ft_{g,d} = 0.1$  or  $ft_{g,d} = 0.01$  since bubble departure by sliding becomes nearly instantaneous after nucleation as pressure increases [57].

First, we must acknowledge that the ranges of measured sliding length by Kossolapov include bubbles that do not slide to the longest observed distance. When looking at the statistical distribution provided in his work [57], bubbles seem to averagely slide around half the longest distance measured in the experiments.

The evaluation using the average distance between two active sites is always clearly underestimating the sliding distance. This seems natural due to the heterogeneity and temporal asynchronism between active sites regarding their nucleation behavior. On the contrary, estimating the distance using the bubble density with very low values of  $ft_{g,d}$  seem to better approach the actual sliding length. Only a clear overestimation is observed for the  $P = 20$  bar and  $G = 500$  kg/m<sup>2</sup>/s case for which we can speculate that values of  $ft_{g,d}$  may be larger.




Figure 6.16: Comparison of sliding distance estimations with Kossolapov measurements [57]. NSD was estimated using Li *et al.* correlation (Eq. 6.11).

## 6.8 SINGLE BUBBLE QUENCHING AREA

When computing the quenching heat flux, we need to provide the total wall area visited by a single bubble  $A_{q,1b}$  that will undergo quenching. In wall boiling model that do not consider bubble sliding [41, 58, 83] the impacted area at bubble lift-off is often considered as :

$$A_{q,1b} = F_A \pi R_{lo}^2 \quad (6.44)$$

with  $F_A$  being an enhancement factor that accounts for the possibility that the bubble will induce quenching over a surface larger than its projected area. For instance, we remind that Kurul & Podowski used  $F_A = 4$  in their model [58].

**Remark :** This question of bubble influence area has been discussed by different authors. Yoo *et al.* [115] experimentally found enhancement factor up to 14 for small sliding bubbles. On the contrary, Kossolapov [57] observed that the area undergoing quenching was exactly the surface covered by the bubble footprint that can be even smaller than the bubble projected area. This aspect seems still open to discussions and may need extra experimental observations to reach a solid conclusion. **In this work, we will simply consider that the bubble induces transient heat transfer over its projected area.**

Otherwise, models that account for bubble sliding [4, 36, 56, 112] compute the quenching area using the sliding length  $l_{sl}$  as:

$$A_{q,1b} = l_{sl} (R_d + R_{lo}) \quad (6.45)$$

However, depending on the relationship between  $l_{sl}$ ,  $R_d$  and  $R_{lo}$ , the quenching area induced by a single sliding bubble without coalescence can have different shapes as pictured in Figure 6.17.




Figure 6.17: Quenching area shape depending on the relation between  $R_d$ ,  $R_{lo}$  and  $l_{sl}$ , if the bubble do not experience multiple coalescence while sliding.

Based on Figure 6.17, we can then write:

$$A_{q,1b} = \begin{cases} \pi R_{lo}^2 & \text{if } l_{sl} \leq R_{lo} - R_d \\ \frac{1}{2}\pi R_d^2 + l_{sl} (R_d + R_{lo}) + \frac{1}{2}\pi R_{lo}^2 & \text{if } l_{sl} \geq R_{lo} + R_d \end{cases} \quad (6.46)$$

Which can be re-expressed by defining  $l_{sl}^* = \frac{l_{sl}}{R_{lo}}$  and  $A_{q,1b}^* = \frac{A_{q,1b}}{\pi R_{lo}^2}$

$$A_{q,1b}^* = \begin{cases} 1 & \text{if } l_{sl}^* \leq 1 - \frac{R_d}{R_{lo}} \\ \frac{1}{2} \left( 1 + \left( \frac{R_d}{R_{lo}} \right)^2 \right) + \frac{l_{sl}^*}{\pi} \left( 1 + \frac{R_d}{R_{lo}} \right) & \text{if } l_{sl}^* \geq 1 + \frac{R_d}{R_{lo}} \end{cases} \quad (6.47)$$

and we linearly interpolate those two expressions for the region where  $1 - \frac{R_d}{R_{lo}} \leq l_{sl}^* \leq 1 + \frac{R_d}{R_{lo}}$ .

## 6.9 ASSEMBLING A NEW HEAT FLUX PARTITIONING

Based on all the discussions conducted in Chapter 5 and in previous Sections of this Chapter, we will now propose a formulation for the HFP model.

In our approach, we consider the following partitioning (Figure 6.18):

- A liquid convective heat flux  $\phi_{c,L}$  associated to forced convection ;
- An evaporation heat flux based on static coalescence between adjacent bubbles nucleating on very close sites  $\phi_{e,coal,st}$  ;
- An evaporation heat flux based on sliding coalescence between a sliding bubble and a growing bubble on its site  $\phi_{e,coal,sl}$  ;
- A quenching heat flux due to transient conduction following bubble departure, sliding and lift-off ;
- A vapor convective heat flux  $\phi_{c,V}$  that accounts for the portion of the wall directly in contact with vapor under a bubble footprint.




Figure 6.18: Sketch of all the considered heat transfers for the new HFP model.

The total wall heat flux then writes:

$$\phi_w = \phi_{c,L} + \phi_{e,coal,st} + \phi_{e,coal,sl} + \phi_q + \phi_{c,V} \quad (6.48)$$

### 6.9.1 Liquid Convective Heat Flux

The liquid convective heat flux  $\phi_{c,L}$  is naturally computed as:

$$\phi_{c,L} = A_{c,L} h_{c,L} (T_w - T_L) = h_{c,L} (\Delta T_w + \Delta T_L) \quad (6.49)$$

where  $A_{c,L}$  is the proportion of the wall area that is affected by liquid forced convection.

The liquid heat transfer coefficient  $h_{c,L}$  is computed using Gnielinski correlation (Eq. 2.21) that has proven to be efficient for wall temperature predictions in single-phase regimes both for R12 and water (2.5.2 and 6.2).

### 6.9.2 Static Coalescence Evaporation Heat Flux

The static coalescence arises from the calculation of the probability for two bubbles to nucleate at a distance lower than  $2R_d$  (Eq. 6.41) which gives the proportion of active nucleation sites that will produce this type of bubble (Eq. 6.42).

Assuming that the bubbles will merge at a radius close to  $R_d$ , we can compute the associated evaporation heat flux:

$$\phi_{e,coal,st} = N_{coal,st} f \rho_V h_{LV} \frac{4}{3} \pi R_d^3 \quad (6.50)$$

This heat flux can also be expressed using the resulting radius of the coalescence:

$$\phi_{e,coal,st} = \frac{N_{coal,st}}{2} f \rho_V h_{LV} \frac{4}{3} \pi R_{coal,st}^3 \quad (6.51)$$

$$R_{coal,st} = (R_d^3 + R_d^3)^{1/3} = 2^{1/3} R_d \quad (6.52)$$

### 6.9.3 Sliding Coalescence Evaporation Heat Flux

Since we identified the active sites that will lead to static coalescence, we consider that the remaining sites will generate bubbles for which lift-off occurs under sliding coalescence. Meaning that half of the sites will generate a sliding bubble and the other half a static bubble that will coalesce with the sliding one. This results in a bubble of diameter:

$$R_{coal,sl} = (R_{sl}^3 + R_d^3)^{1/3} \quad (6.53)$$

Where  $R_{sl}$  is the diameter of the sliding bubble after a distance  $l_{sl} = \frac{1}{2\sqrt{N_b}}$  (Eq. 6.43). The sliding part is solved following the bubble dynamics model that has been developed in Section 5.5 after departure at radius  $R_d$  computed using Eq. 5.106.

We can thus write:

$$\phi_{e,coal,sl} = \frac{N_{coal,sl}}{2} f \rho_V h_{LV} \frac{4}{3} \pi (R_{sl}^3 + R_d^3) \quad (6.54)$$

### 6.9.4 Quenching Heat Flux

The quenching heat flux is split in two parts:

- Quenching from static coalescing bubbles, each of them having a projected area of  $\pi R_d^2$  ;
- Quenching from sliding coalescing bubbles, for which the total swiped area can be expressed using Eq. 6.46 with a lift-off radius being the resulting coalescence radius (Eq. 6.53).

The time during which the transient heat transfer will take place depends on the relationship between the total wait time  $t_w$  and the theoretical time  $t^*$  at which the heat transfer coefficient of transient conduction and forced convection are equal:

$$h_{c,L} (\Delta T_w + \Delta T_L) = \frac{\lambda_L (\Delta T_w + \Delta T_L)}{\sqrt{\pi \eta_L t^*}} \quad (6.55)$$

$$\Leftrightarrow t^* = \left( \frac{\lambda_L}{h_{c,L}} \right)^2 \frac{1}{\pi \eta_L} \quad (6.56)$$

If the wait time  $t_w$  is lower than  $t_*$ , then transient conduction dominates during the whole period between two nucleation and the quenching time  $t_q$  is thus equal to  $t_w$ .

Otherwise, if  $t_w > t^*$  the wait time will consist of transient heat transfer during  $t^*$  before being dominated by forced convection up to  $t_w$ . The quenching time  $t_q$  in this case is then  $t^*$ .

Then, using the transient heat transfer solution (mentioned in Section 6.5, also derived by Del Valle [**delvalle\_phd**]), we can write the total quenching flux as:

$$\phi_q = A_q t_q f \frac{2\lambda_L (\Delta T_w + \Delta T_L)}{\sqrt{\pi \eta_L t_q}} \quad (6.57)$$

$$A_q = N_{coal,st} \pi R_d^2 + \frac{N_{coal,sl}}{2} A_{q,1b} \quad (6.58)$$

$$t_q = \min(t_w, t^*) \quad (6.59)$$

where  $A_{q,1b}$  is computed using Eq. 6.46 with  $R_{coal,sl}$  as the lift-off radius.

### 6.9.5 Vapor Convective Heat Flux

Assuming that the vapor is at saturation temperature, we can write:

$$\phi_{c,V} = A_{c,V} h_{c,V} (T_w - T_{sat}) = A_{c,V} h_{c,V} \Delta T_w \quad (6.60)$$

where  $A_{c,V}$  is the portion of the wall area in direct contact with vapor.

The vapor heat transfer coefficient is estimated simply based on a conductive transfer over a bubble radius:

$$h_{c,V} = \frac{\lambda_V}{R} \quad (6.61)$$

For a truncated spherical bubble, the vapor contact area is its foot area :  $\pi R^2 \sin(\theta)$ . Since the bubbles are supposed to grow following a  $\sqrt{t}$  law (Section 5.3), the average radius for a bubble over its growth time  $t_g$  is:

$$\bar{R} = \frac{1}{t_g} \int_0^R r \, dr = \frac{1}{t_g} \int_0^{t_g} K \text{Ja}_w \sqrt{\eta_L t} \, dt = \frac{1}{t_g} K \text{Ja}_w \frac{2}{3} \sqrt{\eta_L} t_g^{3/2} = \frac{2}{3} R \quad (6.62)$$

Distinguishing between the bubbles that coalesce while growing up to  $R_d$  on their site and sliding bubbles that reaches  $R_{sl}$ , we have:

$$A_{c,V} = \left( N_{coal,st} + \frac{N_{coal,sl}}{2} \right) \pi \left( \frac{2}{3} R_d \sin(\theta) \right)^2 + \frac{N_{coal,sl}}{2} \pi \left( \frac{2}{3} R_{sl} \sin(\theta) \right)^2 \quad (6.63)$$

The time-averaged surface proportion occupied by bubble footprints is then:

$$\overline{A_{c,V}} = \left( N_{coal,st} + \frac{N_{coal,sl}}{2} \right) \pi \left( \frac{2}{3} R_d \sin(\theta) \right)^2 \times t_{g,df} + \frac{N_{coal,sl}}{2} \pi \left( \frac{2}{3} R_{sl} \sin(\theta) \right)^2 \times t_{g,lof} \quad (6.64)$$

### 6.9.6 Liquid Convection Area

Using the expressions of  $A_q$  and  $A_{c,V}$ , we can deduce the remaining unaffected area  $A_{c,L}$ :

$$A_{c,L} = 1 - A_q t_q f - \overline{A_{c,V}} \quad (6.65)$$

### 6.9.7 Model Summary

On Tables 6.5 and 6.6, we gather the formulations and closure laws of the proposed Heat Flux Partitioning model.

In the end, we can see that to fully close the model, we need to set 3 parameters values being:

- The contact angle  $\theta$  which should be chosen in reasonable ranges regarding the heater surface and working fluid. As discussed earlier, usual uncertainties for contact angle measurements usually lie around 5° to 10° [39].

- The contact angle hysteresis  $d\theta$  of the tilted bubble. It plays a role in determining the capillary term in the non-dimensional approach (Chapter 5). Although precise measurements and its dependency on flow parameters are clearly lacking, it seems that values higher than  $10^\circ$  are acceptable for low pressure flows (larger bubbles) and decrease down to a few degrees when reaching higher pressures such as 40 bar.
- The bubble growth constant  $K$  whose value has been discussed earlier (Section 5.3). Its value should roughly lie between 0.1 and 2 depending on the flow conditions. It appeared that for subcooled low pressure flow match with values of  $K < 1$  while at higher pressures  $1 \leq K \leq 2$  better represent the bubble growth regime.

Closure Laws	
Physical Parameter	Modeling
Liquid Convective Heat Transfer Coefficient $h_{c,L}$	$\text{Nu}_L = \frac{h_{c,L} \lambda_L}{D_h} = \frac{\frac{C_f}{2} (\text{Re}_{D_h} - 1000) \text{Pr}}{1 + 12.7 \sqrt{\frac{C_f}{2} (\text{Pr}^{2/3} - 1)}}, C_f = 0.036 \text{Re}_{D_h}^{-0.1818}$
Departure Radius $R_d$	$C_{AM,x} K^2 \frac{\text{Ja}_w^2}{\text{Pr}_L} + \frac{1}{3} \frac{\text{Re}_b}{\text{Fr}} + \frac{1}{8} C_D \text{Re}_b > \frac{1}{2} \frac{f_{C,x}(\theta, d\theta)}{\text{Ca}}$ $C_{AM,x} = 0.636, C_D = (1 + \Delta C_D) C_{D,U}$ (See Eq. 5.35)
Sliding Velocity $U_b$	$\left(1 + \frac{\rho_L}{\rho_V} C_{AM,x}\right) \frac{dU_b}{dt} = \left(\frac{\rho_L}{\rho_V} - 1\right) g + \frac{3}{8} \frac{C_D}{R} \frac{\rho_L}{\rho_V} (U_L - U_b)  U_L - U_b  + 3 \frac{\dot{R}}{R} \left[ C_{AM,x} \frac{\rho_L}{\rho_V} (U_L - U_b) - U_b \right] - \frac{3}{4} \frac{\sigma}{\rho_V} \frac{f_{C,x}}{R^2}$
Bubble Growth Law & Times $t_g$	$R(t) = K \text{Ja}_w \sqrt{\eta_L t}, t_g = \left(\frac{R}{K \text{Ja}_w}\right)^2 \frac{1}{\eta_L}$
Bubble Wait Time $t_w$	$t_w = \frac{1}{\pi \eta_L} \left[ \frac{(\Delta T_L + \Delta T_w) C_1 R_c}{\Delta T_w - \frac{2\sigma T_{sat}}{C_2 \rho_V h_{LV} R_c}} \right]^2, C_1 = \frac{1 + \cos(\theta)}{\sin(\theta)}, C_2 = \frac{1}{\sin(\theta)}$ $R_c = \frac{2\sigma T_{sat}}{\rho_V h_{LV} \Delta T_w}$
Nucleation Frequency $f$	$f = \frac{1}{t_{g,d} + t_w}$
Nucleation Site Density $N_{sit}$	$N_{sit} = N_0 e^{f(P) \Delta T_w A \Delta T_w + B} (1 - \cos(\theta))$ $f(P) = 26.006 - 3.678e^{-2P} - 21.907e^{-P/24.0.65}$ $A = -2 \times 10^{-4} P^2 + 0.0108P + 0.0119, B = 0.122P + 1.988$ $1 - \cos(\theta) = (1 - \cos(\theta_0)) \left(\frac{T_c - T_{sat}}{T_c - T_0}\right)^\gamma, \gamma = 0.719$ $P$ in MPa, $\theta_0$ contact angle at room temperature. (Eq. 6.11)
Active Nucleation Site Density $N_{sit,a}$	$N_{sit,a} = \frac{\mathcal{W}(N_{sit} A_{sit})}{A_{sit}}, A_{sit} = t_{g,d} f \pi R_d^2, \mathcal{W}$ is Lambert's W-function
Nucleating Bubbles Density $N_b$	$N_b = t_{g,d} f N_{sit,a}$
Average Sliding Distance $l_{sl}$	$l_{sl} = \frac{1}{2\sqrt{N_b}}$
Static & Sliding Coalescing Site Density $N_{coal,st}$ & $N_{coal,sl}$	$N_{coal,st} = \mathcal{P}_{coal,st} N_{sit,a}, N_{coal,sl} = (1 - \mathcal{P}_{coal,st}) N_{sit,a}$ $\mathcal{P}_{coal,st} = 1 - \exp(-N_b \pi (2R_d)^2)$
Static & Sliding Coalescence Radiiuses $R_{coal,st}$ & $R_{coal,sl}$	$R_{coal,st} = 2^{1/3} R_d, R_{coal,sl} = (R_d^3 + R_{sl}^3)^{1/3}, R_{sl}$ sliding diameter after $l_{sl}$

Table 6.5: Summary of the HFP model closure laws

Physical Parameter	Mathematical Formulation
Liquid Convective Heat Flux $\phi_{c,L}$	$\phi_{c,L} = A_{c,L} h_{c,L} (\Delta T_w + \Delta T_L)$ $A_{c,L} = 1 - A_q - A_{c,V} + A_q \max\left(0, \frac{t_w - t_q}{t_q}\right)$
Static Coalescence Evaporation Heat Flux $\phi_{e,coal,st}$	$\phi_{e,coal,st} = N_{coal,st} f \rho_V h_{LV} \frac{4}{3} \pi R_d^3$
Sliding Coalescence Evaporation Heat Flux $\phi_{e,coal,sl}$	$\phi_{e,coal,sl} = \frac{N_{coal,sl}}{2} f \rho_V h_{LV} \frac{4}{3} \pi (R_{sl}^3 + R_d^3)$
Quenching Heat Flux $\phi_q$	$\phi_q = A_q t_q f \frac{2\lambda_L (\Delta T_w + \Delta T_L)}{\sqrt{\pi \eta_L t_q}}$ $A_q = N_{coal,st} \pi R_d^2 + \frac{N_{coal,sl}}{2} A_{q,1b}$ $A_{q,1b} = \pi R_{coal,sl}^2 \times A_{q,1b}^* \text{ with } A_{q,1b}^* \text{ by Eq. 6.47}$
Vapor Convective Heat Flux $\phi_{c,V}$	$\phi_{c,V} = A_{c,V} h_{c,V} \Delta T_w$ $h_{c,V} = \frac{\lambda_V}{R}$ $A_{c,V} = \left( N_{coal,st} + \frac{N_{coal,sl}}{2} \right) \pi \left( \frac{2}{3} R_d \sin(\theta) \right)^2 + \frac{N_{coal,sl}}{2} \pi \left( \frac{2}{3} R_{sl} \sin(\theta) \right)^2$

Table 6.6: Summary of the HFP model formulation

## 6.10 CONCLUSION

In this Chapter, we covered different aspects related to the construction of the HFP model, including the evaluation of closure laws required to complete the mathematical model.

At last, we can remember that:

- Single phase heat transfer coefficient is well predicted using Gnielinski correlation, with errors on the wall temperature below 3K for single-phase water flows in various conditions. A corrective factor of 4 had to be used for cases where only one side of the channel is heated to account for geometry difference regarding the correlation establishment.
- Nucleation site density using existing correlations have been assessed using different experiments with water. Covering a large range of pressure, it appeared that Li *et al.* [65] formulation was better at predicting the experimental nucleation site density. In particular, the influence of pressure is very significant and must be accounted for. However, we must keep in mind that although the nucleation site density is critical for wall boiling modeling, its value depends on very fine details of the boiling surface which are not always accessible.
- The bubble wait time has been studied using some existing experimental measurements. Its strong decrease with the wall superheat makes it accounting between nearly 100% down to 50% of the total nucleation period. Comparison of wait time values predictions showed that analytic approaches could perform better than correlations, though this requires an estimation of the active cavity radius which can be very tricky depending and surface-dependent.
- Considering sites and bubble interactions can be achieved under the hypothesis that they both follow an homogeneous spatial Poisson point-process. The mathematical formulations can then be used to account for events such as nucleation site suppression and bubble static coalescence.
- Bubble sliding length was found to be in reasonable agreement with the average distance between two nucleating bubbles on the wall, which can be associated to the fact that bubble leave the surface when coalescing with another one.

- A new heat flux partitioning model was finally proposed in which the boiling flux is computed based on coalescence event avoiding the need of a particular closure law for the lift-off diameter  $D_{lo}$ , which estimation for single bubbles was questionable as discussed in Section 5.6. Moreover, the departure and sliding includes the detailed force balance approach developed in Chapter 5.

Next chapter will be dedicated to the validation of the new HFP model through comparisons with wall temperature measurements in vertical flow boiling.

# 7

---

## VALIDATION OF THE HEAT FLUX PARTITIONING MODEL

---

### Contents

7.1	Detailed Comparison and Assessment of the Heat Flux Partitioning . . . . .	125
7.1.1	Active Nucleation Site Density . . . . .	126
7.1.2	Wait Time, Growth Time, Quenching Time and Nucleation Frequency . . . . .	126
7.1.3	Single Bubble Area and Total Bubble Area . . . . .	127
7.1.4	Flux Proportions and Wall Superheat . . . . .	127
7.2	Wall Temperature Predictions . . . . .	130
7.2.1	Kossolapov Data . . . . .	130
7.2.2	Jens-Lottes Data . . . . .	131
7.2.3	Kennel Data . . . . .	132
7.3	Validation for DEBORA Experiment . . . . .	135
7.4	Conclusions . . . . .	135

---

In this Chapter, we want to assess the validity of the new Heat Flux Partitioning formulation proposed in Chapter 6. To do so, we will conduct two different validations:

- The first part will be dedicated to validation on a single experimental subcooled boiling case at 10.5 bar from Kossolapov [57] for which numerous physical parameters have been measured. This will ensure that the mathematical formulation and the closure laws propose an acceptable physical modeling of the boiling parameters.
- The second part will consist on wall temperature predictions for vertical subcooled flow boiling of water in various conditions, including pressure. Experimental database from Jens & Lottes [48], Kennel [52] and Kossolapov [57]. Comparison with other HFP models from Kurul & Podowski, Basu and Kommajosyula will be performed.

### 7.1 DETAILED COMPARISON AND ASSESSMENT OF THE HEAT FLUX PARTITIONING

In this section, we compare our results to those obtained by Kossolapov [57] in vertical subcooled flow boiling. At a pressure of 10.5 bar, he realized measurements of many relevant parameters regarding the Heat Flux Partitioning:

- Active nucleation site density  $N_{sit,a}$  ;
- Bubble nucleation frequency  $f$  ;
- Bubble wait time  $t_w$  ;
- Transient heat transfer (quenching) time  $t_q$  ;
- Average bubble growth time  $t_g$  ;
- Average area visited by a bubble  $A_{q,1b}$  ;
- Proportion of the heater area impacted by bubbles  $A_{b,tot}$
- Liquid single-phase heat flux proportion  $\frac{\phi_{c,L}}{\phi_w}$  ;

- Quenching heat flux proportion  $\frac{\phi_q}{\phi_w}$  ;
- Wall superheat  $\Delta T_w$ .

The only lacking parameters to conduct a full evaluation of the model would be the average bubble departure diameter  $R_d$ , sliding length  $l_{sl}$  and lift-off diameter / coalescence diameter.

The values provided by Kossolapov are an average conducted over all the observed nucleation events during the time of the experiment. Such data are representative of what we want to achieve using a HFP model since we represent average values of the boiling parameters for the considered boiling surface.

All those variables were measured for a subcooling  $\Delta T_L = 10^\circ\text{C}$  at three different liquid mass fluxes  $G_L = 500, 1000$  and  $2000 \text{ kg/m}^2/\text{s}$ .

We present the results obtained by comparison with the case at  $G_L = 2000 \text{ kg/m}^2/\text{s}$  for each variable. The simulations using the HFP model were conducted using a contact angle  $\theta = 85^\circ$  (usual contact angle for water and ITO [57]), an hysteresis  $d\theta = 2^\circ$  and a growth constant  $K = 0.8$

### 7.1.1 Active Nucleation Site Density

On Figure 7.1, we compare the values obtained for the active nucleation site density. The Li *et al.* correlation used in the model (Eq. 6.11) propose a reasonable prediction of the measured values of  $N_{sit,a}$  with an underestimation of less than a decade. The correlation correctly reproduce the experimental trend where we observe a sort of saturation in the nucleation site density for higher wall superheat.

To better match the asymptotic value of the experiment, we correct the Li *et al.* correlation for this case by a factor  $\Delta T_w^{2-0.3\Delta T_w^{0.5}}$  which better fits the measurements for  $\Delta T_w > 10 \text{ K}$  but yields a small overestimation before.




Figure 7.1: Comparison of active nucleation site density with and without a correction for Li *et al.* formulation.

**Note :** Following comparisons are conducted using the corrected value of  $N_{sit,a}$  to limit the impact of the nucleation site density prediction over the other parameters.

### 7.1.2 Wait Time, Growth Time, Quenching Time and Nucleation Frequency

Figure 7.2 compares the different times involved in the boiling physics and the bubble nucleation frequency. As seen in Section 6.5, the wait time is quite fairly reproduced along with the nucleation frequency. Actually, the bubble departure is nearly instantaneous and the nucleation cycle is mainly composed of the wait period, which means a good estimation of  $t_w$  leads to a reasonable estimation of  $f$  for this case.

The average bubble growth time is overestimated by nearly a decade for low superheat and is better predicted for larger superheat. Its evolution seem coherent with a decrease up to 15 K and a stabilization afterwards. However, the experimental measurements show an increase in the growth time for large superheat which could be associated to bubble diameter increase with the wall Jakob number as previously observed in Section 5.6. This could be in partial contradiction with the single coalescence hypothesis for the lift-off since the average distance between bubbles is likely to decrease with wall superheat, thus decreasing the average growth time. On the other hand, the growth time overprediction may be associated to sliding length overestimation.

A very good approximation of the quenching time  $t_q$  is achieved using the time  $t^*$  (Eq. 6.56). This indicates that for this experimental case, the large value of the wait time implies that the transient conduction will be limited to a duration  $t^*$  and that the remaining wait time will be governed by forced convection.




Figure 7.2: Comparison of bubble nucleation frequency, wait time, average growth time and quenching time.

### 7.1.3 Single Bubble Area and Total Bubble Area

Figure 7.3 that the total area visited by a bubble is largely overestimated for the whole boiling curve. It only achieves a reasonable order of magnitude at high wall superheat ( $\Delta T_w > 23$  K). This could question the usual hypothesis that supposes a sliding length  $l_{sl}$  equal to the average distance between bubbles  $s_b = 0.5/\sqrt{N_b}$ . The sole projected area of the bubbles is in average better for the visited area, but underpredicts the largest values of  $A_{q,1b}$  when bubbles start sliding over significant lengths.

Moreover, both values do not reproduce the experimental trend where the visited area regularly increases with the wall superheat. Further experimental insights regarding the behavior of the bubble sliding length could allow a better modeling of  $l_{sl}$  depending on the bubble lift-off process as discussed in Section 5.6.

Those results naturally lead to an overprediction of the wall area fraction impacted by bubbles but shows an coherent increasing trend with wall superheat.

On Figure 7.4, we indicatively show the values of sliding length  $l_{sl}$ , departure diameter  $R_d$  and sliding diameter  $R_{sl}$  when sliding over  $l_{sl}$ . The small values of  $R_d$  are coherent with nearly immediate departure by sliding, with sliding radiiuses close to 0.1 mm.

### 7.1.4 Flux Proportions and Wall Superheat

Figure 7.5 finally compares the fraction of single-phase convection and quenching over the total heat flux  $\phi_w$  along with the boiling curve. The evolution of the single-phase flux reasonably agrees with the




Figure 7.3: Comparison of average area visited by a bubble and total wall fraction area impacted by bubbles (footprint or transient conduction).




Figure 7.4: Bubble radii, sliding length and distances between sites.

experiment and becomes 0 at a superheat similar to the measurement. However, the quenching heat flux is logically overestimated due to the significant overestimation of the area visited by a single bubble.

On the other hand, the boiling curve is pretty well predicted except for the last experimental measurement where an increase in wall temperature starts, which could correspond to conditions close to the CHF that can't yet be detected by the HFP model.




Figure 7.5: Comparison of the resulting heat flux partitioning along with the boiling curve.

## 7.2 WALL TEMPERATURE PREDICTIONS

In this section, we want to evaluate the model's capability to predict wall temperature in boiling regimes for different flow conditions. To do so, we gather boiling curves data from the literature for water that covers a large range of flow conditions as detailed in Table 7.1.

Author	$D_h$ [mm]	$P$ [bar]	$G_L$ [kg/m <sup>2</sup> /s]	$\Delta T_L$ [K]	$\phi_w$ [MW/m <sup>2</sup> ]	$\Delta T_w$ [K]	$N_{mes}$ [-]
Kossolapov [57] (2021)	11.78	1.12 - 75.8	500 - 2000	10	0.23 - 7.93	1.55 - 30.77	81
Jens-Lottes [48] (1951)	5.74	137.9	2617.5	53.3 - 92.2	2.15 - 3.63	1.81 - 4.16	38
Kennel [52] (1948)	4.3 - 13.2	2 - 6.2	284 - 10 577	11.1 - 83.3	0.053 - 6.35	1.64 - 49.7	172

Table 7.1: Experimental data range of wall temperature measurements in the boiling region.

The following sub-sections compare the results for wall superheat predictions obtained using four models: Kurul & Podowski (Section 4.2), Basu *et al.* (Section 4.3), Kommajosyula (Section 4.5) and the new formulation (Section 6.9).

In order to propose consistent choices required closing parameters for the new formulation, we will discuss the values attributed to the contact angle  $\theta$ , bubble inclination  $d\theta$  and constant value in bubble growth rate  $K$ .

### 7.2.1 Kossolapov Data

The boiling curves from Kossolapov's work [57] are among the most recent available data and notably include various operating pressures. The experimental setup consists of a heated flat plate of ITO in vertical flow boiling in a rectangular channel.

As stated by Kossolapov, the contact angle for water and ITO usually lies between 80° and 90° [57]. The bubble tilt is likely to be very low for high pressure cases (see Sec. 5.4) and the bubble growth rate coefficient  $K$  shall be closer to 1.5 / 2 at high pressure while it can be lower than 1 for low pressure cases. The chosen values are then:

- $\theta = 85^\circ$  ;
- $d\theta = 1^\circ$  for  $P > 5$  bar and  $d\theta = 5^\circ$  otherwise ;
- $K = 1.5$  for  $P > 5$  bar and  $K = 1.0$  otherwise.

Figure 7.6 shows two typical boiling curves along with the heat flux partitioning obtained using the new formulation for Kossolapov cases at 19.8 bar and 75.8 bar.

We can observe that experimental profiles are quite fairly reproduced in both cases. The model also shows different types of heat flux partitioning with the case at 75.8 bar starting to have a significant proportion of static coalescence evaporation flux. This is probably a consequence of both the high pressure and large wall superheat resulting in a very large nucleation site density and increasing the probability for two bubbles to coalesce early in their lifetime.

Figure 7.7 shows the wall temperature predictions achieved with the different HFP models.

We can note that the new formulation generally better agrees with experimental measurements but yields significant underestimation of low wall superheat values for low pressure cases. The predictions achieved by Kurul & Podowski and Kommajosyula models seem similar while Basu *et al.* formulation largely overestimates the wall temperature with an average error above 100 K.




Figure 7.6: Comparison with measured boiling curves from Kossolapov [57].  $\Delta T_L = 10^\circ\text{C}$  and  $G_L = 1000 \text{ kg/m}^2/\text{s}$ .




Figure 7.7: Wall temperature predictions achieved by the different HFP models on Kossolapov data.

### 7.2.2 Jens-Lottes Data

The data of Jens & Lottes are of particular interest for the HFP validation since they were obtained in conditions close to PWR ones, with an operating pressure of 138 bar, liquid mass flux above 2500 kg/m<sup>2</sup>/s

and high inlet liquid subcooling. The experiment consisted of an integrally heated metallic circular pipe. Precise evaluation of the contact angle in those conditions is tricky but, according to the work of Song & Fan [98], the water contact angle on metallic surfaces (*e.g.* stainless steel) at large pressure present a very large decrease when reaching surface temperatures above 200°C. Since saturation temperature of water at 138 bar if  $T_{sat} \approx 335^\circ\text{C}$ , the boiling measurements lie largely in the low contact angle zone. Therefore, we will assume:

- $\theta = 20^\circ$  ;
- $d\theta = 1^\circ$  (very high pressure leading to nearly non-tilted bubbles) ;
- $K = 2.0$  (very high pressure and low Jakob numbers).

Figure 7.8 shows a typical boiling curve obtained for an experimental case of Jens & Lottes. We can observe that in this region where wall superheat are low ( $\Delta T_w < 5$  K), the quasi-entirety of the wall heat flux is evacuated through liquid convection and transient conduction through quenching. This is likely to be a consequence of the very high pressure conditions under which nucleation site density is very large but bubbles become extremely small ( $R \sim \mu\text{m}$ ). Evaporation heat flux is then relatively small but the large number of bubbles and their sliding induce a strong quenching effect over the heater surface.




Figure 7.8: Comparison with measured boiling curve by Jens & Lottes [48].  $P = 138$  bar,  $G = 2600$  kg/m<sup>2</sup>/s,  $\Delta T_L = 64^\circ\text{C}$ .

Figure 7.9 shows the wall temperature predictions achieved with the different HFP models.

Both the new formulation and Kommajosyula model achieve good predictions of the wall temperature in those high pressure conditions. However, Kurul & Podowski and Basu models do not seem to capture properly the wall superheat evolution, with large relative overestimations ( $\sim 200\%$ ).

### 7.2.3 Kernel Data

Kernel measurements are of similar nature to those of Jens & Lottes since they were conducted for a uniformly heated vertical circular metallic pipe. However, the experiments were operated at pressures lower than 6 bar and various inlet liquid mass fluxes and subcoolings. In those conditions, the evaluation of the constant  $K$  in the bubble growth profile can be very tricky since the larger bubbles at low pressure are more impacted by the bulk flow, implying potentially large variations of  $K$  that can become much lower than 1. Regarding the contact angle, its value can also be roughly estimated using Song & Fan review [98] showing that metallic surfaces at low and moderate pressure also show a contact angle decrease with temperature, with values roughly lying between 40° and 60° when  $T_w \sim T_{sat}$ . Therefore, we assume:




Figure 7.9: Wall temperature predictions achieved by the different HFP models on Jens data.

- $\theta = 50^\circ$  ;
  - $d\theta = 5^\circ$  (larger and deformable bubbles at low pressure) ;
  - $K = 0.3$  (larger impact of bulk subcooling on bubble growth).

Figure 7.10 shows the wall temperature predictions achieved with the different HFP models.

Achieving a good quality of wall superheat predictions for the cases of Kennel appears more complicated. Indeed, the new formulation and Komma joysula model obtain the best results but still present an average underestimation of approximately 50%. The very large range of conditions associated to the low pressure may invalidate the assumption of constants values for  $\theta$ ,  $d\theta$  and  $K$ .

**Remark :** In his work, Kommajosyula [56] presented better wall temperature predictions on Kennel data with his model (average error between 3 K and 5 K). We only managed to achieve similar results using a much lower contact angle ( $\theta \leq 20^\circ$ ) which could be questioned regarding the operating conditions.




Figure 7.10: Wall temperature predictions achieved by the different HFP models on Kennel data.

### 7.3 VALIDATION FOR DEBORA EXPERIMENT

In order to try a further validation of the proposed HFP model, we will test it under conditions that are representative of the DEBORA cases for the G2P26W16 campaign (Chapter 2):

- R12 as operating fluid ;
- $P = 26.2$  bar ;
- $G_L = 2000 \text{ kg/m}^2/\text{s}$  ;
- $\Delta T_L \approx 0.1 \text{ K}$  (approaching liquid saturation near the wall);
- $\phi_w = 73.9 \text{ kW/m}^2$ .

Since refrigerant are usually known to have low contact angle, we suppose  $\theta = 10^\circ$ . The operating pressure being experimentally chosen to match high-pressure water similarity, we thus choose  $d\theta = 1^\circ$  and  $K = 2$  in accordance with the choices made for Jens & Lottes cases.

Applying the four different models yielded the results of Table 7.2.

Value	Experiment	Kurul & Podowski	Basu <i>et al.</i>	Kommajosyula	New model	NCFD reference
$\Delta T_w [\text{K}]$	2.15	0.37	17.9	4.0	3.9	6.9

Table 7.2: Wall superheat values obtained with different models versus the measurements on DEBORA case at 26.6 bar.

We see that the models perform in very different ways for the DEBORA conditions. Kurul & Podowski model finds a very low wall superheat while Basu *et al.* formulation largely overestimates the experimental value. The new formulation provides a result similar to Kommajosyula's model with an overestimation of approximately 2 K compared to the experiment.

**Remark :** The proximity in the results obtained by the new formulation and Kommajosyula's model might be related to their similar performance on the Jens & Lottes data (Subsection 7.2.2) since the DEBORA cases are supposed to mimic high pressure water boiling conditions, the physical formulations of the HFP models may then behave similarly in those conditions.

### 7.4 CONCLUSIONS

In this Chapter, we proposed different aspects of validation regarding the proposed Heat Flux Partitioning model developed in Section 6.9. All in all, we can conclude that:

- The evolution of most physical parameters included in the model are coherent with detailed measurements conducted by Kossolapov [57] (Section 7.1), namely the nucleation site density, the bubble departure frequency, waiting time and quenching time.
- The quenching seems overestimated with a probably too large sliding length. Meaning that the proposed modeling (*i. e.* average distance between two nucleating bubbles, Section 6.7) is likely to be an upper bound of the actual sliding length. Bubbles may actually slide over shorter length, which would require dedicated investigations when reaching boiling regimes with large bubble density on the wall.
- The formulation seems able to capture different nature of heat flux partition, with high-quenching regimes at high pressure and low superheats (Figure 7.8), regimes with both static and sliding coalescence at high pressure and high superheat (Figure 7.6), or mixed between quenching and sliding coalescence at low to moderate pressure and high superheat (Figure 7.6).
- Wall temperature predictions (Section 7.2) using the new formulation along with reasonable values for the closing parameters ( $\theta$ ,  $d\theta$ ,  $K$ ) yields better results in average compared to older models. In particular, it seems capable of enhancing the wall temperature predictions on the DEBORA case as shown on Table 7.2.

# 8

---

## PERSPECTIVES TOWARDS CRITICAL HEAT FLUX PREDICTION

---

Bibliography examples of CHF detection using HFP models !

Part III  
TOWARDS THE INDUSTRIAL GEOMETRY

---

PROMOTEUR

---

### 9.1 BOILING FREON IN A TUBE WITH MIXING VANES : DEBORA-PROMOTEUR EXPERIMENTS

In this section, we simulate upward boiling flows of R12 in a vertical tube equipped with mixing vanes and compare the outlet void fraction profile predicted by NEPTUNE\_CFD with measurements coming from the DEBORA-Promoteur experiment.

#### 9.1.1 Description of the experiment

In 2003, the wish to investigate boiling flows in complex geometries similar to those in PWR fuel assembly lead CEA and EDF to modify the DEBORA facility to introduce mixing vanes (MV) within the tube. This mixing device has been designed to have the same geometric properties as the mixing vanes attached to rod bundle grids (Figure 9.1).




Figure 9.1: Picture of the mixing device (left) and its fine meshing (right).

Two series of measurements were conducted on this geometry :

- Campaign 4800 : measurements of  $\alpha$  using two optical probes, mixing device placed  $0.455m \approx 23.5D_h$  upstream the end of the heating length
- Campaign 5200 : measurements of  $\alpha$  and  $U_{G,z}$  using two optical probes, mixing device placed  $0.192m \approx 10D_h$  upstream the end of the heating length

The goal of those tests was to observe the impact of the mixing device on the void fraction profile. The induced rotation is expected to gather the bubbles at the center of the tube and enhance condensation for highly subcooled cases. Those expectations are confirmed when looking at experimental  $\alpha$  profiles on Figure 9.8. The strong differences compared to simple tube profiles could explain the gain on the CHF value in PWR thanks to the mixing grids. Cases are named following the same nomenclature as presented in Section ??.

#### 9.1.2 Analysis of the Experimental Measurements

#### 9.1.3 NEPTUNE\_CFD simulations of DEBORA-Promoteur cases

We simulated 3 cases for each position of the mixing device, covering different local thermodynamic quality near the vanes ( $x_{eq,MV}$ ) :




Figure 9.2: Experimental results from the 48G3P26W23 series.




Figure 9.3: Experimental results from the 52G3P26W23 series.




Figure 9.4: Experimental results from the 52G3P26W27 series.

- 48G3P26W23Te65 & 52G3P26W23Te65 with  $x_{eq,MV} \approx -1\%$
- 48G3P26W23Te69 & 52G3P26W23Te69 with  $x_{eq,MV} \approx 4\%$
- 48G3P26W23Te75 & 52G3P26W23Te75 with  $x_{eq,MV} \approx 12\%$




Figure 9.5: Relative difference of interference frequency for the two probes.




Figure 9.6: Average relative importance of radial velocity to axial velocity in AGATE experiment




Figure 9.7: Estimation of bubble diameter on C5200 measurements series.

Computations are conducted using two meshes for Te69 cases : a large one (M1) with 444 703 cells and a fine one (M2) with 3 487 627 cells. Results for void fraction profiles are shown on Figure 9.8. Quantitatively speaking, it seems that NEPTUNE\_CFD reproduces the effect of vapor accumulation at the center thanks to the pressure gradient generated by the swirl induced by the mixing vanes. The radial position of the core void fraction peak correctly matches the experimental one.




Figure 9.8: NCFD (lines) vs. Exp. (circles) -  $\alpha$  profiles for two MV positions ( $23.5D_h$  in blue,  $10D_h$  in orange)  
-  $T_{in} = 65^\circ\text{C}$  (left),  $T_{in} = 69^\circ\text{C}$  (middle),  $T_{in} = 75^\circ\text{C}$  (right) - Simulations using two meshes M1  
(coarse) and M2 (fine) for  $T_{in} = 69^\circ\text{C}$ .

However, measured void fraction profiles are not predicted correctly. A particularly strong overestimation of the core void fraction is observed as well as close to the wall. The CMFD results tend to rapidly reach a core void fraction around 60% ( $T_{in} = 69^\circ\text{C}$  cases) and then flattens with increasing temperature ( $T_{in} = 75^\circ$  cases). This contradicts experimental observation where the void fraction profile globally rises when inlet temperature increases, except at the wall where no peak is observed due to bubble removing effect by the liquid's rotation. Moreover, the  $T_{in} = 75^\circ$  case with MV at  $10D_h$  experimentally shows local  $\alpha$  peaks at  $R \approx \pm 6\text{mm}$  which remain currently unexplained and not reproduced by the simulations.

To investigate what could be a potential origin for the core void fraction peak overestimation, we present in Section 9.2 single-phase flow simulations in the MV geometry.

## 9.2 LIQUID WATER FLOW IN A TUBE WITH MIXING VANES : AGATE-PROMOTEUR EXPERIMENT

In this penultimate section, we briefly investigate single-phase flow within the same geometry as Section 9.1.

### 9.2.1 Description of the experiment

In 2003, using the same experimental geometry as DEBORA-Promoteur cases (Section 9.1), Laser Doppler Velocimetry (LDV) measurements of velocity and turbulent fluctuations for an adiabatic single-phase flow of water were conducted. The outlet pressure was around  $P = 2$  bar with an inlet mass flux  $G \approx 3000 \text{ kg/m}^2/\text{s}$ . Measurements were conducted on 6 different diameters and repeated at various axial positions upstream and downstream the mixing vanes.

A first look at experimental measurements (Figure 9.9) shows that the vanes geometry induces significantly non-symmetric velocity profile. Moreover, we observe high turbulent fluctuations which maximum is located at the same radial position as the maximum radial velocity gradient.

### 9.2.2 NEPTUNE\_CFD simulations of AGATE-Promoteur case

On Figure 9.9, we present some of the results obtained with NEPTUNE\_CFD using the  $R_{ij} - \varepsilon$  SSG turbulence model on the M2 mesh, along with a smooth wall law and a rough wall law (roughness  $\epsilon = 0.01\text{mm}$ ). The turbulent fluctuations Root Mean Square (RMS) correspond, for instance, to  $\sqrt{\langle u_x'^2 \rangle}$  for the  $x$  direction where  $u_i'$  represents the fluctuating part of the velocity along component  $i$  and  $\langle \cdot \rangle$  the time-averaging operator. Subscripts  $R$  and  $A$  stand for radial and axial values ;  $U_0$  is the average inlet velocity.

Non-symmetric radial velocity profiles close to the MV are quite well reproduced by the simulations. However, far downstream the MV, it appears that the fluid's rotation is overestimated by the model with




Figure 9.9: NCFD vs. Exp. - Top & Middle : Radial velocity and turbulent RMS ( $z = 30\text{mm}$  &  $z = 440\text{mm}$ ) - Bottom : Axial velocity and turbulent RMS ( $z = 440\text{mm}$ ).

a smooth wall approach, while applying a roughness helps to reduce the magnitude of the swirl. Moreover, the radial turbulent fluctuations are better estimated by the rough wall approach at  $z = 440\text{ mm}$ . On the other hand, it seems that the rough wall approach deteriorates the axial velocity profile compared to the experiment. As shown on the bottom part of Figure 9.9, the smooth wall simulation returns a flat velocity profile closer to the experiment than the rough wall one which overestimates the core velocity peak.

Both simulations globally underestimate the turbulent fluctuations, which can have a significant influence over the observed discrepancies on velocity profiles since turbulence plays a key role to homogenize the fluid flow.

Those results finally highlight the fact that simulation of such rotating flows may need a particular wall approach to better capture the induced swirl and its dissipation. Correct prediction of turbulent fluctuations would be of significant interest to ensure liquid velocity validation. Further investigations on boiling cases could possibly be improved by a roughness approach, which is the current correction used for two-phase wall laws (Subsection 1.6).

%partConclusion

# 10

---

## CONCLUSION

---

To write big summary of all the work + lot of perspectives

Part IV  
APPENDIX

# A

---

## DETAILS ON THE BUBBLE GROWTH CALCULATION

---

To further study the bubble growth process, we will try to derive an analytic In this section, computations are conducted using the spherical coordinates  $(\bar{e}_r, \bar{e}_\theta, \bar{e}_\varphi)$  with coordinates  $(r, \theta, \phi)$ .




Figure A.1: Studied geometry

Geometrical definitions :

- $\Theta = \pi - \theta$  the angular portion of the truncated sphere in spherical coordinates ;
- $r_w = R\sin(\theta) = -R\sin(\Theta)$  the bubble foot radius ;
- $h = R\cos(\theta) = -R\cos(\Theta)$  the distance between the wall and the center of the bubble ( $> 0$  if  $\theta < \pi/2$ ,  $< 0$  otherwise) ;
- $R$  and  $V = \frac{4}{3}\pi R^3 f_V(\theta)$  the radius and the volume of the bubble ;
- $\bar{d}^2 S = R^2 \sin(\theta) d\theta d\varphi \bar{e}_r$  the surface vector in spherical coordinates ;
- $y = R\cos(\theta) + h = R(\cos(\theta) - \cos(\Theta))$  the distance to the wall in cartesian coordinates.

Thermal-hydraulics definitions :

- $\Delta T_L = T_{sat} - T_\infty$  et  $\Delta T_w = T_w - T_{sat}$  the subcooling of the liquid and the wall superheat respectively ;
- $\delta$  et  $\delta_b$  the flow boundary layer thickness and the bubble boundary layer thickness respectively ;
- $d^2 Q_b$  the heat received by the bubble between  $t$  and  $t + dt$  through the surface  $d^2 S$  ;
- $\lambda, \rho, c_p, \eta, h$  the thermal conductivity, density, heat capacity, thermal diffusivity and mass enthalpy respectively ( $l$  standing for liquid and  $g$  for gas) ;

- $\text{Ja}_w = \Delta T_w \rho_L c_{p,L} / (h_{LV} \rho_V)$  the wall superheat (or boiling) Jakob number and  $\text{Ja}_L = \Delta T_L \rho_L c_{p,L} / (h_{LV} \rho_V)$  the subcooled liquid (or condensation) one.

The thermal boundary layer of the flow is assumed to follow a linear profile, giving the expression :

$$T_l(y) = T_w + \frac{T_\infty - T_w}{\delta} y \quad (\text{A.1})$$

If we consider that the bubble stays at a temperature close to  $T_{sat}$ , the radial component of the temperature gradient at the bubble's interface yields :

$$\bar{\nabla}(T) \cdot \bar{er} = \frac{\partial T}{\partial r}(R, \theta, \phi) \approx \frac{T_l(y) - T_{sat}}{\delta_b} \quad (\text{A.2})$$

Applying Fourier's law to the liquid close to the bubble :  $\bar{j_Q} = -\lambda_l \bar{\nabla}(T)$ , then the bubble receives between  $t$  and  $t + dt$  through  $d^2S$  :

$$d^2Q_b = \bar{j_Q} \cdot (-\bar{d^2S}) \quad (\text{A.3})$$

$$= \lambda_l \frac{\partial T}{\partial r}(R, \theta, \varphi) R^2 \sin(\theta) d\theta d\varphi \quad (\text{A.4})$$

$$\approx \lambda_l \frac{T_l(y) - T_{sat}}{\delta_b} R^2 \sin(\theta) d\theta d\varphi \quad (\text{A.5})$$

$$= \lambda_l \frac{1}{\delta_b} \left[ T_w + \frac{T_\infty - T_w}{\delta} y - T_{sat} \right] R^2 \sin(\theta) d\theta d\varphi \quad (\text{A.6})$$

$$= \frac{\lambda_l}{\delta_b} \left[ \Delta T_w - \frac{\Delta T_w + \Delta T_l}{\delta} R [\cos(\theta) - \cos(\Theta)] \right] R^2 \sin(\theta) d\theta d\varphi \quad (\text{A.7})$$

$$= \frac{\lambda_l}{\delta_b} \left[ \Delta T_w R^2 \sin(\theta) - \frac{\Delta T_w + \Delta T_l}{\delta} R^3 [\cos(\theta) - \cos(\Theta)] \sin(\theta) \right] d\theta d\varphi \quad (\text{A.8})$$

The total heat flux received by the bubble can then be derived, supposing that  $\delta_b$  is constant all around the bubble between  $t$  and  $t + dt$  :

$$Q_b = \int_{\varphi=0}^{\varphi=2\pi} \int_{\theta=0}^{\Theta} d^2Q_b \quad (\text{A.9})$$

$$= \frac{2\pi\lambda_l}{\delta_b} \left[ \int_0^\Theta \Delta T_w R^2 \sin(\theta) d\theta + \int_0^\Theta \frac{\Delta T_w + \Delta T_l}{\delta} R^3 \cos(\Theta) \sin(\theta) d\theta - \int_0^\Theta \frac{\Delta T_w + \Delta T_l}{\delta} R^3 \cos(\theta) \sin(\theta) d\theta \right] \quad (\text{A.10})$$

$$= \frac{2\pi\lambda_l}{\delta_b} \left[ \Delta T_w R^2 (1 - \cos(\Theta)) + \frac{\Delta T_w + \Delta T_l}{\delta} R^3 \left[ \cos(\Theta) (1 - \cos(\Theta)) - \frac{1}{4} (1 - \cos(2\Theta)) \right] \right] \quad (\text{A.11})$$

$$= \frac{2\pi\lambda_l R^2}{\delta_b} \left[ \frac{-R}{2\delta} (\Delta T_w + \Delta T_l) (1 + 2\cos(\alpha) + \cos^2(\alpha)) + \Delta T_w (1 + \cos(\alpha)) \right] \quad (\text{A.12})$$

$$= \frac{2\pi\lambda_l R^2}{\delta_b} (1 + \cos(\alpha)) \left[ \Delta T_w - \frac{R}{2\delta} (\Delta T_w + \Delta T_l) (1 + \cos(\alpha)) \right] \quad (\text{A.13})$$

Between  $t$  and  $t + dt$ , the bubble receives a  $Q_b dt$  energy amount through thermal diffusion. Assuming this energy solely contributes to evaporation of the surrounding liquid, the resulting mass of generated vapor is :

$$dm_g = \rho_g dV = \frac{Q_b dt}{h_{lg}} \quad (\text{A.14})$$

$$\text{then } \frac{dV}{dt} = \frac{Q_b}{\rho_g h_{lg}} \quad (\text{A.15})$$

Since  $V = \frac{4}{3}\pi R^3 f_V(\alpha)$ , we can write :

$$\frac{dV}{dt} = \frac{4}{3}\pi f_V(\alpha) 3R^2 \frac{dR}{dt} \quad (\text{A.16})$$

Then :

$$\frac{dR}{dt} = \frac{1}{4\pi R^2 f_V(\alpha)} \frac{1}{\rho_g h_{lg}} \frac{2\pi \lambda_l R^2}{\delta_b} (1 + \cos(\alpha)) \left[ \Delta T_w - \frac{R}{2\delta} (\Delta T_w + \Delta T_l) (1 + \cos(\alpha)) \right] \quad (\text{A.17})$$

$$= \frac{1}{2f_V(\alpha)} \frac{\Delta T_w}{h_{lg} \rho_g} \frac{\lambda_l}{\delta_b} (1 + \cos(\alpha)) \left[ 1 - \frac{R}{2\delta} \left( 1 + \frac{\Delta T_l}{\Delta T_w} \right) (1 + \cos(\alpha)) \right] \quad (\text{A.18})$$

$$= \frac{\text{Ja}_w \eta_l}{2\delta_b f_V(\alpha)} (1 + \cos(\alpha)) \left[ 1 - \frac{R}{2\delta} \left( 1 + \frac{\text{Ja}_l}{\text{Ja}_w} \right) (1 + \cos(\alpha)) \right] \quad (\text{A.19})$$

If we define :

$$a = \frac{\text{Ja}_w \eta_l}{4\delta_b \delta f_V(\alpha)} \left( 1 + \frac{\text{Ja}_l}{\text{Ja}_w} \right) (1 + \cos(\alpha))^2 \quad \text{et} \quad b = \frac{\text{Ja}_w \eta_l}{2\delta_b f_V(\alpha)} (1 + \cos(\alpha)) \quad (\text{A.20})$$

Finally :

$$\frac{dR}{dt} + aR = b \quad (\text{A.21})$$

Solutions of this differential equation depend on the hypothesis over  $\delta$  and  $\delta_b$ . In a first approach, we will consider that  $\delta$  does not vary during the whole bubble growth. This thickness could be expressed using boundary layer thickness correlations for example (laminar or turbulent depending on the Reynolds number).

On the other hand, we will consider 3 different choices to model  $\delta_b$  :

#### A.0.1 Case 1 : $\delta_b$ is constant

This is a **strong assumption** since it means that  $\delta_b$  does not depend on the temperature and the flow shear rate facing the bubble. In this case,  $a$  and  $b$  are constant, giving :

$$\frac{dR}{dt} + aR = b \quad (\text{A.22})$$

With the initial condition  $R(t = 0) = 0$  the solution of this differential equation is :

$$R(t) = \frac{b}{a} (1 - e^{-at}) \quad \text{where} \quad \frac{b}{a} = \frac{2\delta}{\left( 1 + \frac{\text{Ja}_l}{\text{Ja}_w} \right) (1 + \cos(\alpha))} = R_\infty \quad \text{is the final bubble equilibrium radius.} \quad (\text{A.23})$$

#### A.0.2 Case 2 : $\delta_b = \sqrt{\eta_l t}$

This expression derives from the growth of a boundary layer through pure diffusion, as studied by LEGENDRE *et al.*

Such a boundary layer thickness is also used when one writes the quenching heat flux (see Section ?? and DEL VALLE & KENNING work).

In this case, this means that the boundary layer around the bubble interface grows through diffusion only.

Thus, it yields :

$$\frac{dR}{dt}(t) + a(t)R(t) = b(t) \quad (\text{A.24})$$

$$a(t) = \frac{\text{Ja}_w \sqrt{\eta_l}}{4\delta f_V(\alpha) \sqrt{t}} \left(1 + \frac{\text{Ja}_l}{\text{Ja}_w}\right) (1 + \cos(\alpha))^2 = K_a t^{-1/2} \text{ and } b(t) = \frac{\text{Ja}_w \sqrt{\eta_l}}{2f_V(\alpha) \sqrt{t}} (1 + \cos(\alpha)) = K_b t^{-1/2} \quad (\text{A.25})$$

With the initial condition  $R(t=0) = 0$ , the solution is given by :

$$R(t) = R_\infty \left(1 - e^{-2K_a \sqrt{t}}\right) \text{ avec } R_\infty = \frac{K_b}{K_a} \quad (\text{A.26})$$

### A.0.3 Case 3 : $\delta_b = CR$

In this last case, the bubble boundary layer is assumed to be proportional to the bubble radius  $R$ , through a constant coefficient  $C$ . This yields :

$$a(t) = \frac{\text{Ja}_w \eta_l}{4\delta f_V(\alpha) CR(t)} \left(1 + \frac{\text{Ja}_l}{\text{Ja}_w}\right) (1 + \cos(\alpha))^2 = K'_a \frac{1}{R(t)} \text{ et } b(t) = \frac{\text{Ja}_w \eta_l}{2f_V(\alpha) CR(t)} (1 + \cos(\alpha)) = K'_b \frac{1}{R(t)} \quad (\text{A.27})$$

Giving :

$$\frac{dR}{dt}(t) + K'_a R(t) = K'_b \frac{1}{R(t)} \quad (\text{A.28})$$

Which the solution with the initial condition  $R(t=0) = 0$  is :

$$R(t) = R_\infty \left(W\left(-e^{-tK'_a^2/K'_b - 1}\right) + 1\right) \quad (\text{A.29})$$

With  $W$  being the LAMBERT function defined as the reciprocal function of  $w \rightarrow we^w$  on  $\mathbb{C}$ .

# B

---

## DETAILS ON THE BUBBLE FORCE BALANCE

---

Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl. Etiam ac leo a risus tristique nonummy. Donec dignissim tincidunt nulla. Vestibulum rhoncus molestie odio. Sed lobortis, justo et pretium lobortis, mauris turpis condimentum augue, nec ultricies nibh arcu pretium enim. Nunc purus neque, placerat id, imperdiet sed, pellentesque nec, nisl. Vestibulum imperdiet neque non sem accumsan laoreet. In hac habitasse platea dictumst. Etiam condimentum facilisis libero. Suspendisse in elit quis nisl aliquam dapibus. Pellentesque auctor sapien. Sed egestas sapien nec lectus. Pellentesque vel dui vel neque bibendum viverra. Aliquam porttitor nisl nec pede. Proin mattis libero vel turpis. Donec rutrum mauris et libero. Proin euismod porta felis. Nam lobortis, metus quis elementum commodo, nunc lectus elementum mauris, eget vulputate ligula tellus eu neque. Vivamus eu dolor.

$$r_w = \frac{1}{2} (\sin(\theta_d) R + \sin(\theta_u) R) \quad (B.1)$$

$$= \frac{R}{2} (\sin(\theta_s + d\theta) + \sin(\theta - d\theta)) \quad (B.2)$$

$$= \frac{R}{2} \left[ 2\sin\left(\frac{\theta_s + d\theta + \theta_s - d\theta}{2}\right) \cos\left(\frac{\theta_s + d\theta - (\theta_s - d\theta)}{2}\right) \right] \quad (B.3)$$

$$= R\sin(\theta_s) \cos(d\theta) \quad (B.4)$$

$$\overline{F_{CP}} = \frac{2\sigma}{R_c} \frac{\pi d_w^2}{4} \overline{e_y} \quad (B.5)$$

$$= \frac{2\sigma}{R} \frac{\pi 4R^2}{4} \sin^2(\theta) \cos^2(d\theta) \overline{e_\perp} \quad (B.6)$$

$$= 2\sigma\pi R \underbrace{\sin^2(\theta) \cos^2(d\theta)}_{f_{cp}} \overline{e_\perp} \quad (B.7)$$

$$= 2\pi R\sigma f_{cp}(\theta, d\theta) \overline{e_\perp} \quad (B.8)$$

$$\overline{F_{CP}} \cdot \overline{e_\perp} = -d_w\sigma \frac{\pi}{\alpha_r - \alpha_u} (\cos(\alpha_a) - \cos(\alpha_r)) \quad (B.9)$$

$$= \pi 2R\sigma \frac{\sin(\alpha + d\alpha) + \sin(\alpha - d\alpha)}{2} \frac{\cos(\alpha + d\alpha) - \cos(\alpha - d\alpha)}{2d\alpha} \quad (B.10)$$

$$= 2\pi R\sigma \frac{2\sin(\alpha) \cos(d\alpha)}{2} \frac{(-2\sin(\alpha) \sin(d\alpha))}{2d\alpha} \quad (B.11)$$

$$= -2\pi R\sigma \underbrace{\sin^2(\alpha) \frac{\sin(2d\alpha)}{2d\alpha}}_{f_{s,\perp}} \quad (B.12)$$

$$= -2\pi R\sigma f_{s,\perp}(\alpha, d\alpha) \quad (B.13)$$

$$(B.14)$$

LABITUR BONORUM PRI NO	QUE VISTA	HUMAN
fastidii ea ius	germano	demonstratea
suscipit instructior	titulo	personas
quaestio philosophia	facto	demonstrated

Table B.1: Autem usu id.

$$\overline{F_s \cdot e_{\parallel}} = -1.215d_w\sigma \frac{\pi(\alpha_r - \alpha_u)}{\pi^2 - (\alpha_r - \alpha_u)^2} (\sin(\alpha_r) + \sin(\alpha_u)) \quad (B.15)$$

$$= -1.215d_w\sigma \frac{\pi 2d\alpha}{\pi^2 - 4d\alpha^2} (\sin(\alpha + d\alpha) + \sin(\alpha - d\alpha)) \quad (B.16)$$

$$= -1.215 2R\sigma \frac{\pi d\alpha}{\pi^2 - 4d\alpha^2} (\sin(\alpha + d\alpha) + \sin(\alpha - d\alpha))^2 \quad (B.17)$$

$$= -2\pi R\sigma \frac{1.215d\alpha}{\pi^2 - 4d\alpha^2} 4\sin^2(\alpha) \cos^2(d\alpha) \quad (B.18)$$

$$= -2\pi R\sigma \underbrace{1.215 \frac{d\alpha}{(\frac{\pi}{2})^2 - d\alpha^2} \sin^2(\alpha) \cos^2(d\alpha)}_{f_{s,\parallel}} \quad (B.19)$$

$$= -2\pi R\sigma f_{s,\parallel}(\alpha, d\alpha) \quad (B.20)$$

## B.1 APPENDIX SECTION TEST

Nulla in ipsum. Praesent eros nulla, congue vitae, euismod ut, commodo a, wisi. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Aenean nonummy magna non leo. Sed felis erat, ullamcorper in, dictum non, ultricies ut, lectus. Proin vel arcu a odio lobortis euismod. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Proin ut est. Aliquam odio. Pellentesque massa turpis, cursus eu, euismod nec, tempor congue, nulla. Duis viverra gravida mauris. Cras tincidunt. Curabitur eros ligula, varius ut, pulvinar in, cursus faucibus, augue. Nulla mattis luctus nulla. Duis commodo velit at leo. Aliquam vulputate magna et leo. Nam vestibulum ullamcorper leo. Vestibulum condimentum rutrum mauris. Donec id mauris. Morbi molestie justo et pede. Vivamus eget turpis sed nisl cursus tempor. Curabitur mollis sapien condimentum nunc. In wisi nisl, malesuada at, dignissim sit amet, lobortis in, odio. Aenean consequat arcu a ante. Pellentesque porta elit sit amet orci. Etiam at turpis nec elit ultricies imperdiet. Nulla facilisi. In hac habitasse platea dictumst. Suspendisse viverra aliquam risus. Nullam pede justo, molestie nonummy, scelerisque eu, facilisis vel, arcu.

## B.2 ANOTHER APPENDIX SECTION TEST

Curabitur tellus magna, porttitor a, commodo a, commodo in, tortor. Donec interdum. Praesent scelerisque. Maecenas posuere sodales odio. Vivamus metus lacus, varius quis, imperdiet quis, rhoncus a, turpis. Etiam ligula arcu, elementum a, venenatis quis, sollicitudin sed, metus. Donec nunc pede, tincidunt in, venenatis vitae, faucibus vel, nibh. Pellentesque wisi. Nullam malesuada. Morbi ut tellus ut pede tincidunt porta. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam congue neque id dolor. Donec et nisl at wisi luctus bibendum. Nam interdum tellus ac libero. Sed sem justo, laoreet vitae, fringilla at, adipiscing ut, nibh. Maecenas non sem quis tortor eleifend fermentum. Etiam id tortor ac mauris porta vulputate. Integer porta neque vitae massa. Maecenas tempus libero a libero posuere dictum. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Aenean quis mauris sed elit commodo placerat. Class aptent taciti sociosqu ad litora torquent per comubia nostra, per inceptos hymenaeos. Vivamus rhoncus tincidunt libero. Etiam elementum pretium justo. Vivamus est. Morbi a tellus eget pede tristique commodo. Nulla nisl. Vestibulum sed nisl eu sapien cursus rutrum.

There is also a useless Pascal listing below: [Listing B.1](#).

Listing B.1: A floating example (`listings` manual)

---

```
1 for i:=maxint downto 0 do
begin
{ do nothing }
end;
```

---

---

## BIBLIOGRAPHY

---

- [1] Rouhollah Ahmadi, Tatsuya Ueno, and Tomio Okawa. “Bubble dynamics at boiling incipience in subcooled upward flow boiling”. In: *International Journal of Heat and Mass Transfer* 55.1 (Jan. 15, 2012), pp. 488–497. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2011.09.050](https://doi.org/10.1016/j.ijheatmasstransfer.2011.09.050).
- [2] T. R. Auton. “The lift force on a spherical body in a rotational flow”. In: *Journal of Fluid Mechanics* 183 (Oct. 1987). Publisher: Cambridge University Press, pp. 199–218. ISSN: 1469-7645, 0022-1120. DOI: [10.1017/S002211208700260X](https://doi.org/10.1017/S002211208700260X).
- [3] Nilanjana Basu, Gopinath R. Warrier, and Vijay K. Dhir. “Wall Heat Flux Partitioning During Subcooled Flow Boiling: Part 1—Model Development”. In: *Journal of Heat Transfer* 127.2 (Mar. 15, 2005), pp. 131–140. ISSN: 0022-1481. DOI: [10.1115/1.1842784](https://doi.org/10.1115/1.1842784).
- [4] Nilanjana Basu, Gopinath R. Warrier, and Vijay K. Dhir. “Wall Heat Flux Partitioning During Subcooled Flow Boiling: Part II—Model Validation”. In: *Journal of Heat Transfer* 127.2 (Mar. 15, 2005), pp. 141–148. ISSN: 0022-1481. DOI: [10.1115/1.1842785](https://doi.org/10.1115/1.1842785).
- [5] V. M. Borishanskii, G. I. Bobrovich, and F. P. Minchenko. “Heat transfer from a tube to water and to ethanol in nucleate pool boiling”. In: *Problems of Heat Transfer and Hydraulics of Two-Phase Media*. Elsevier, 1969, pp. 85–106.
- [6] R. W. Bowring. *Physical model, based on bubble detachment, and calculation of steam voidage in the sub-cooled region of a heated channel*. HPR-10. Institutt for Atomenergi (Norway). OECD Halden Reaktor Prospekt, Dec. 1, 1962.
- [7] Mattia Bucci, Jacopo Buongiorno, and Matteo Bucci. “The not-so-subtle flaws of the force balance approach to predict the departure of bubbles in boiling heat transfer”. In: *Physics of Fluids* 33.1 (Jan. 2021). Publisher: American Institute of Physics, p. 017110. ISSN: 1070-6631. DOI: [10.1063/5.0036956](https://doi.org/10.1063/5.0036956).
- [8] Lubomír Bureš and Yohei Sato. “On the modelling of the transition between contact-line and microlayer evaporation regimes in nucleate boiling”. In: *Journal of Fluid Mechanics* 916 (June 2021). Publisher: Cambridge University Press. ISSN: 0022-1120, 1469-7645. DOI: [10.1017/jfm.2021.204](https://doi.org/10.1017/jfm.2021.204).
- [9] In-Cheol CHU, Hee Cheon NO, and Chul-Hwa SONG. “Bubble Lift-off Diameter and Nucleation Frequency in Vertical Subcooled Boiling Flow”. In: *Journal of Nuclear Science and Technology* 48.6 (June 1, 2011). Publisher: Taylor & Francis \_eprint: <https://www.tandfonline.com/doi/pdf/10.1080/18811248.2011.9711780>. ISSN: 0022-3131. DOI: [10.1080/18811248.2011.9711780](https://doi.org/10.1080/18811248.2011.9711780).
- [10] Deqi Chen, Liang-ming Pan, and Song Ren. “Prediction of bubble detachment diameter in flow boiling based on force analysis”. In: *Nuclear Engineering and Design* 243 (Feb. 1, 2012), pp. 263–271. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2011.11.022](https://doi.org/10.1016/j.nucengdes.2011.11.022).
- [11] J. C. Chen. “Correlation for Boiling Heat Transfer to Saturated Fluids in Convective Flow”. In: *Industrial & Engineering Chemistry Process Design and Development* 5.3 (July 1, 1966). Publisher: American Chemical Society, pp. 322–329. ISSN: 0196-4305. DOI: [10.1021/i260019a023](https://doi.org/10.1021/i260019a023).
- [12] Zhihao Chen, Atsushi Haginiwa, and Yoshio Utaka. “Detailed structure of microlayer in nucleate pool boiling for water measured by laser interferometric method”. In: *International Journal of Heat and Mass Transfer* 108 (May 1, 2017), pp. 1285–1291. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2017.01.003](https://doi.org/10.1016/j.ijheatmasstransfer.2017.01.003).
- [13] Zhihao Chen, Xiaocheng Hu, Kang Hu, Yoshio Utaka, and Shoji Mori. “Measurement of the microlayer characteristics in the whole range of nucleate boiling for water by laser interferometry”. In: *International Journal of Heat and Mass Transfer* 146 (Jan. 1, 2020), p. 118856. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2019.118856](https://doi.org/10.1016/j.ijheatmasstransfer.2019.118856).
- [14] Han Chi-Yeh and Peter Griffith. “The mechanism of heat transfer in nucleate pool boiling—Part I: Bubble initiation, growth and departure”. In: *International Journal of Heat and Mass Transfer* 8.6 (June 1, 1965), pp. 887–904. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(65\)90073-6](https://doi.org/10.1016/0017-9310(65)90073-6).

- [15] SW Churchill. "Friction Factor Spans All Fluid-Flow Regimes". In: *Chemical Engineering* 84 (1977), pp. 91–92.
- [16] Marco Colombo and Michael Fairweather. "Prediction of bubble departure in forced convection boiling: A mechanistic model". In: *International Journal of Heat and Mass Transfer* 85 (June 1, 2015), pp. 135–146. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2015.01.103](https://doi.org/10.1016/j.ijheatmasstransfer.2015.01.103).
- [17] M. G. Cooper and A. J. P. Lloyd. "The microlayer in nucleate pool boiling". In: *International Journal of Heat and Mass Transfer* 12.8 (Aug. 1, 1969), pp. 895–913. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(69\)90154-9](https://doi.org/10.1016/0017-9310(69)90154-9).
- [18] Géraud Cubizolles. "Etude stéréologique de la topologie des écoulements diphasiques à haute pression". These de doctorat. Ecully, Ecole centrale de Lyon, Jan. 1, 1996.
- [19] D. J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes*. Probability and its Applications. New York: Springer-Verlag, 2003. ISBN: 978-0-387-95541-4. DOI: [10.1007/b97277](https://doi.org/10.1007/b97277).
- [20] Victor H. Del Valle and D. B. R. Kenning. "Subcooled flow boiling at high heat flux". In: *International Journal of Heat and Mass Transfer* 28.10 (Oct. 1, 1985), pp. 1907–1920. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(85\)90213-3](https://doi.org/10.1016/0017-9310(85)90213-3).
- [21] Jean-Marc Delhaye. *Thermohydraulique des réacteurs*. Google-Books-ID: v8vL04U7Zt4C. EDP Sciences, Dec. 3, 2012. 527 pp. ISBN: 978-2-7598-0308-8.
- [22] Etienne Demarly. "A new approach to predicting departure from Nucleate Boiling (DNB) from direct representation of boiling heat transfer physics". Accepted: 2021-02-19T20:35:27Z ISBN: 9781237640528. Thesis. Massachusetts Institute of Technology, 2020.
- [23] F. W. Dittus and L. M. K. Boelter. "Heat transfer in automobile radiators of the tubular type". In: *International Communications in Heat and Mass Transfer* 12.1 (Jan. 1, 1985), pp. 3–22. ISSN: 0735-1933. DOI: [10.1016/0735-1933\(85\)90003-X](https://doi.org/10.1016/0735-1933(85)90003-X).
- [24] G. Duhar, G. Riboux, and C. Colin. "Vapour bubble growth and detachment at the wall of shear flow". In: *Heat and Mass Transfer* 45.7 (May 1, 2009), pp. 847–855. ISSN: 1432-1181. DOI: [10.1007/s00231-007-0287-y](https://doi.org/10.1007/s00231-007-0287-y).
- [25] Géraldine Duhar. "Croissance et détachement de bulles en paroi d'un écoulement cisaillé : étude expérimentale de l'injection et de l'ébullition nucléée". These de doctorat. Toulouse, INPT, Jan. 1, 2003.
- [26] Géraldine Duhar and Catherine Colin. "Dynamics of bubble growth and detachment in a viscous shear flow". In: *Physics of Fluids* 18.7 (July 2006). Publisher: American Institute of Physics, p. 077101. ISSN: 1070-6631. DOI: [10.1063/1.2213638](https://doi.org/10.1063/1.2213638).
- [27] Carlos E. Estrada-Pérez, Yassin A. Hassan, Bandar Alkhudhiri, and Junsoo Yoo. "Time-resolved measurements of liquid–vapor thermal interactions throughout the full life-cycle of sliding bubbles at subcooled flow boiling conditions". In: *International Journal of Multiphase Flow* 99 (Feb. 1, 2018), pp. 94–110. ISSN: 0301-9322. DOI: [10.1016/j.ijmultiphaseflow.2017.10.002](https://doi.org/10.1016/j.ijmultiphaseflow.2017.10.002).
- [28] H. K. Forster and N. Zuber. "Growth of a Vapor Bubble in a Superheated Liquid". In: *Journal of Applied Physics* 25.4 (Apr. 1954). Publisher: American Institute of Physics, pp. 474–478. ISSN: 0021-8979. DOI: [10.1063/1.1721664](https://doi.org/10.1063/1.1721664).
- [29] W Frost, G. S Dzakowic, and American Society of Mechanical Engineers. *An extension of the method for predicting incipient boiling on commercially finished surfaces*. OCLC: 459788171. New York, N.Y.: ASME, 1967.
- [30] R. F. Gaertner and J. W. Westwater. "Population of Active Sites in Nucleate Boiling Heat Transfer". In: *Chem. Eng. Progr.* Vol: 56: Symposium Ser. No. 30 (Jan. 1, 1960). Institution: General Electric Co., Schenectady, N.Y.
- [31] J. Garnier, E. Manon, and G. Cubizolles. "LOCAL MEASUREMENTS ON FLOW BOILING OF REFRIGERANT 12 IN A VERTICAL TUBE". In: *Multiphase Science and Technology* 13.1 (2001). Publisher: Begell House Inc. ISSN: 0276-1459, 1943-6181. DOI: [10.1615/MultScienTechn.v13.i1-2.10](https://doi.org/10.1615/MultScienTechn.v13.i1-2.10).
- [32] C. W. M. van der Geld. "The dynamics of a boiling bubble before and after detachment". In: *Heat and Mass Transfer* 45.7 (May 1, 2009), pp. 831–846. ISSN: 1432-1181. DOI: [10.1007/s00231-007-0254-7](https://doi.org/10.1007/s00231-007-0254-7).

- [33] Craig Douglas Gerardi. "Investigation of the pool boiling heat transfer enhancement of nano-engineered fluids by means of high-speed infrared thermography". Accepted: 2010-03-24T20:38:10Z. Thesis. Massachusetts Institute of Technology, 2009.
- [34] Craig Gerardi, Jacopo Buongiorno, Lin-wen Hu, and Thomas McKrell. "Study of bubble growth in water pool boiling through synchronized, infrared thermometry and high-speed video". In: *International Journal of Heat and Mass Transfer* 53.19 (Sept. 1, 2010), pp. 4185–4192. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2010.05.041](https://doi.org/10.1016/j.ijheatmasstransfer.2010.05.041).
- [35] Lindsey Anne Gilman. "Development of a general purpose subgrid wall boiling model from improved physical understanding for use in computational fluid dynamics". Accepted: 2014-12-08T18:48:48Z. Thesis. Massachusetts Institute of Technology, 2014.
- [36] Lindsey Gilman and Emilio Baglietto. "A self-consistent, physics-based boiling heat transfer modeling framework for use in computational fluid dynamics". In: *International Journal of Multiphase Flow* 95 (Oct. 1, 2017), pp. 35–53. ISSN: 0301-9322. DOI: [10.1016/j.ijmultiphaseflow.2017.04.018](https://doi.org/10.1016/j.ijmultiphaseflow.2017.04.018).
- [37] V. Gnielinski. "New equations for heat and mass transfer in the turbulent flow in pipes and channels". In: *NASA STI/Recon Technical Report A* 41 (Jan. 1, 1975). ADS Bibcode: 1975STIA...7522028G, pp. 8–16.
- [38] P. Griffith, J. A. Clark, and W. M. Rohsenow. *VOID VOLUMES IN SUBCOOLED BOILING SYSTEMS. Technical Report No. 12.* NP-6637. Massachusetts Inst. of Tech., Cambridge. Div. of Industrial Cooperation, Mar. 1, 1958.
- [39] Peng Guan, Li Jia, Liaoifei Yin, and Zetao Tan. "Bubble departure size in flow boiling". In: *Heat and Mass Transfer* 51.7 (July 1, 2015), pp. 921–930. ISSN: 1432-1181. DOI: [10.1007/s00231-014-1461-7](https://doi.org/10.1007/s00231-014-1461-7).
- [40] Jil Gueguen. "Contribution à la modélisation multidimensionnelle des écoulements bouillants convectifs en conduite haute pression pour l'application au cas des réacteurs à eau pressurisée". These de doctorat. Grenoble, Dec. 19, 2013.
- [41] Antoine Guelfi, Dominique Bestion, Marc Boucker, Pascal Boudier, Philippe Fillion, Marc Grandotto, Jean-Marc Hérard, Eric Hervieu, and Pierre Péturaud. "NEPTUNE: A New Software Platform for Advanced Nuclear Thermal Hydraulics". In: *Nuclear Science and Engineering* 156.3 (July 1, 2007). Publisher: Taylor & Francis \_eprint: <https://doi.org/10.13182/NSE05-98>, pp. 281–324. ISSN: 0029-5639. DOI: [10.13182/NSE05-98](https://doi.org/10.13182/NSE05-98).
- [42] Alexandre Guion, Shahriar Afkhami, Stéphane Zaleski, and Jacopo Buongiorno. "Simulations of microlayer formation in nucleate boiling". In: *International Journal of Heat and Mass Transfer* 127 (Dec. 1, 2018), pp. 1271–1284. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2018.06.041](https://doi.org/10.1016/j.ijheatmasstransfer.2018.06.041).
- [43] K. E. Gungor and R. H. S. Winterton. "A general correlation for flow boiling in tubes and annuli". In: *International Journal of Heat and Mass Transfer* 29.3 (Mar. 1, 1986), pp. 351–358. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(86\)90205-X](https://doi.org/10.1016/0017-9310(86)90205-X).
- [44] F. C. Gunther. "Photographic Study of Surface-Boiling Heat Transfer to Water With Forced Convection". In: *Transactions of the American Society of Mechanical Engineers* 73.2 (1951), pp. 115–123. ISSN: 0097-6822. DOI: [10.1115/1.4016160](https://doi.org/10.1115/1.4016160).
- [45] J. S. Hadamard. "Mouvement permanent lent d'une sphère liquide et visqueuse dans un liquide visqueux". In: *Comptes Rendus Hebdomadaires des Séances de l'Académie des Sciences* 155 (1911), pp. 1735–1738.
- [46] Takashi Hibiki and Mamoru Ishii. "Active nucleation site density in boiling systems". In: *International Journal of Heat and Mass Transfer* 46.14 (July 1, 2003), pp. 2587–2601. ISSN: 0017-9310. DOI: [10.1016/S0017-9310\(03\)00031-0](https://doi.org/10.1016/S0017-9310(03)00031-0).
- [47] M. Ishii. *One-dimensional drift-flux model and constitutive equations for relative motion between phases in various two-phase flow regimes.* ANL-77-47. Argonne National Lab., Ill. (USA), Oct. 1, 1977. DOI: [10.2172/6871478](https://doi.org/10.2172/6871478).
- [48] W. H. Jens and P. A. Lottes. *Analysis of Heat Transfer, Burnout, Pressure Drop and Density Data for High-Pressure Water.* ANL-4627. Argonne National Lab., May 1, 1951. DOI: [10.2172/4421630](https://doi.org/10.2172/4421630).

- [49] R. L. Judd and K. S. Hwang. "A Comprehensive Model for Nucleate Pool Boiling Heat Transfer Including Microlayer Evaporation". In: *Journal of Heat Transfer* 98.4 (Nov. 1, 1976), pp. 623–629. ISSN: 0022-1481. DOI: [10.1115/1.3450610](https://doi.org/10.1115/1.3450610).
- [50] B. A Kader and A. M Yaglom. "Heat and mass transfer laws for fully turbulent wall flows". In: *International Journal of Heat and Mass Transfer* 15.12 (Dec. 1, 1972), pp. 2329–2351. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(72\)90131-7](https://doi.org/10.1016/0017-9310(72)90131-7).
- [51] Satish G. Kandlikar and Mark E. Steinke. "Contact angles and interface behavior during rapid evaporation of liquid on a heated surface". In: *International Journal of Heat and Mass Transfer* 45.18 (Aug. 1, 2002), pp. 3771–3780. ISSN: 0017-9310. DOI: [10.1016/S0017-9310\(02\)00090-X](https://doi.org/10.1016/S0017-9310(02)00090-X).
- [52] William E. Kennel. "Local boiling of water and superheating of high pressure steam in annuli". Accepted: 2020-09-25T21:06:56Z ISSN: 2933-0025. Thesis. Massachusetts Institute of Technology, 1949.
- [53] J. F. Klausner, R. Mei, D. M. Bernhard, and L. Z. Zeng. "Vapor bubble departure in forced convection boiling". In: *International Journal of Heat and Mass Transfer* 36.3 (Feb. 1, 1993), pp. 651–662. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(93\)80041-R](https://doi.org/10.1016/0017-9310(93)80041-R).
- [54] G. Kocamustafaogullari. "Pressure dependence of bubble departure diameter for water". In: *International Communications in Heat and Mass Transfer* 10.6 (Nov. 1, 1983), pp. 501–509. ISSN: 0735-1933. DOI: [10.1016/0735-1933\(83\)90057-X](https://doi.org/10.1016/0735-1933(83)90057-X).
- [55] L. D. Koffman and M. S. Plesset. "Experimental Observations of the Microlayer in Vapor Bubble Growth on a Heated Solid". In: *Journal of Heat Transfer* 105.3 (Aug. 1, 1983), pp. 625–632. ISSN: 0022-1481. DOI: [10.1115/1.3245631](https://doi.org/10.1115/1.3245631).
- [56] Ravikishore Kommajosyula. "Development and assessment of a physics-based model for subcooled flow boiling with application to CFD". Accepted: 2021-01-05T23:15:30Z. Thesis. Massachusetts Institute of Technology, 2020.
- [57] Artyom Kossolapov. "Experimental Investigation of Subcooled Flow Boiling and CHF at Prototypical Pressures of Light Water Reactors". PhD thesis. Massachusetts Institute of Technology, 2021.
- [58] N. Kurul and Michael Z. Podowski. "MULTIDIMENSIONAL EFFECTS IN FORCED CONVECTION SUBCOOLED BOILING". In: International Heat Transfer Conference 9. Begel House Inc., 1990. ISBN: 0-89116-909-1. DOI: [10.1615/IHTC9.40](https://doi.org/10.1615/IHTC9.40).
- [59] Sir Horace Lamb. *Hydrodynamics*. Google-Books-ID: d\_AoAAAAYAAJ. University Press, 1895. 632 pp. ISBN: 978-1-4086-1332-0.
- [60] Dominique Legendre, Jacques Borée, and Jacques Magnaudet. "Thermal and dynamic evolution of a spherical bubble moving steadily in a superheated or subcooled liquid". In: *Physics of Fluids* 10.6 (June 1998). Publisher: American Institute of Physics, pp. 1256–1272. ISSN: 1070-6631. DOI: [10.1063/1.869654](https://doi.org/10.1063/1.869654).
- [61] Dominique Legendre and Jacques Magnaudet. "The lift force on a spherical bubble in a viscous linear shear flow". In: *Journal of Fluid Mechanics* 368 (Aug. 1998). Publisher: Cambridge University Press, pp. 81–126. ISSN: 1469-7645, 0022-1120. DOI: [10.1017/S0022112098001621](https://doi.org/10.1017/S0022112098001621).
- [62] M. Lemmert and J.M. Chawla. "Influence of flow velocity on surface boiling heat transfer coefficient". In: *Heat Transfer in Boiling*. Hemisphere. Washington D.C., 1977, pp. 236–246.
- [63] Octave Levenspiel. "Collapse of Steam Bubbles in Water". In: *Industrial & Engineering Chemistry* 51.6 (June 1, 1959). Publisher: American Chemical Society, pp. 787–790. ISSN: 0019-7866. DOI: [10.1021/ie50594a045](https://doi.org/10.1021/ie50594a045).
- [64] V. G. Levich. *Physicochemical hydrodynamics*. Prentice-Hall international series in the physical and chemical engineering sciences. OCLC: 1378432. Englewood Cliffs, N.J.: Prentice-Hall, 1962. 700 pp. ISBN: 978-0-13-674440-5.
- [65] Quan Li, Yongjun Jiao, Maria Avramova, Ping Chen, Junchong Yu, Jie Chen, and Jason Hou. "Development, verification and application of a new model for active nucleation site density in boiling systems". In: *Nuclear Engineering and Design* 328 (Mar. 1, 2018), pp. 1–9. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2017.12.027](https://doi.org/10.1016/j.nucengdes.2017.12.027).

- [66] Z. Liu and R. H. S. Winterton. "A general correlation for saturated and subcooled flow boiling in tubes and annuli, based on a nucleate pool boiling equation". In: *International Journal of Heat and Mass Transfer* 34.11 (Nov. 1, 1991), pp. 2759–2766. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(91\)90234-6](https://doi.org/10.1016/0017-9310(91)90234-6).
- [67] R.W. Lockhart and R.C. Martinelli. "Proposed Correlation of Data for Isothermal Two-Phase, Two-Component Flow in Pipes." In: *Chemical Engineering Progress* 45 (), pp. 38–48.
- [68] J. Magnaudet and I. Eames. "The Motion of High-Reynolds-Number Bubbles in Inhomogeneous Flows". In: *Annual Review of Fluid Mechanics* 32.1 (2000). \_eprint: <https://doi.org/10.1146/annurev.fluid.32.1.659>, pp. 659–708. DOI: [10.1146/annurev.fluid.32.1.659](https://doi.org/10.1146/annurev.fluid.32.1.659).
- [69] Sandipan Maity. "Effect of Velocity and Gravity on Bubble Dynamics". MSc Thesis. University of California Los Angeles, 2000.
- [70] Etienne Manon. "Contribution à l'analyse et à la modélisation locale des écoulements bouillants sous-saturés dans les conditions des réacteurs à eau sous pression". These de doctorat. Châtenay-Malabry, Ecole centrale de Paris, Jan. 1, 2000.
- [71] Philippe (1970 March. "Caractérisation et modélisation de l'environnement thermohydraulique et chimique des gaines de combustible des réacteurs à eau sous pression en présence d'ébullition". These de doctorat. Aix-Marseille 1, Jan. 1, 1999.
- [72] T. Mazzocco, W. Ambrosini, R. Kommajosyla, and E. Baglietto. "A reassessed model for mechanistic prediction of bubble departure and lift off diameters". In: *International Journal of Heat and Mass Transfer* 117 (Feb. 1, 2018), pp. 119–124. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2017.09.105](https://doi.org/10.1016/j.ijheatmasstransfer.2017.09.105).
- [73] William H McAdams. *Heat transmission*. OCLC: 683455. New York: McGraw-Hill, 1954.
- [74] Renwei Mei and J. F. Klausner. "Shear lift force on spherical bubbles". In: *International Journal of Heat and Fluid Flow* 15.1 (Feb. 1, 1994), pp. 62–65. ISSN: 0142-727X. DOI: [10.1016/0142-727X\(94\)90031-0](https://doi.org/10.1016/0142-727X(94)90031-0).
- [75] Renwei Mei and James F. Klausner. "Unsteady force on a spherical bubble at finite Reynolds number with small fluctuations in the free-stream velocity". In: *Physics of Fluids A: Fluid Dynamics* 4.1 (Jan. 1992). Publisher: American Institute of Physics, pp. 63–70. ISSN: 0899-8213. DOI: [10.1063/1.858501](https://doi.org/10.1063/1.858501).
- [76] B. B Mikic, W. M Rohsenow, and P Griffith. "On bubble growth rates". In: *International Journal of Heat and Mass Transfer* 13.4 (Apr. 1, 1970), pp. 657–666. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(70\)90040-2](https://doi.org/10.1016/0017-9310(70)90040-2).
- [77] Louis Melville Milne-Thomson. *Theoretical Hydrodynamics*. Google-Books-ID: A5hRAAAAMAAJ. Macmillan and Company, limited, 1938. 590 pp.
- [78] Michaël Montout. "Contribution au développement d'une Approche Prédictive Locale de la crise d'ébullition". These de doctorat. Toulouse, INPT, Jan. 21, 2009.
- [79] P. de. Munk. *Two-phase flow experiments in a 10 m long sodium heated steam generator test section*. AED-Conf-73-445-021 INIS Reference Number: 5098086. Germany, 1973, p. 2.
- [80] Tomio Okawa, Tatsuhiro Ishida, Isao Kataoka, and Michitsugu Mori. "Bubble rise characteristics after the departure from a nucleation site in vertical upflow boiling of subcooled water". In: *Nuclear Engineering and Design*. Festschrift Edition Celebrating the 65th Birthday of Prof. Richard T. Lahey, Jr. 235.10 (May 1, 2005), pp. 1149–1161. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2005.02.012](https://doi.org/10.1016/j.nucengdes.2005.02.012).
- [81] Tomio Okawa, Kazuhiro Kaiho, Shintaro Sakamoto, and Koji Enoki. "Observation and modelling of bubble dynamics in isolated bubble regime in subcooled flow boiling". In: *Nuclear Engineering and Design* 335 (Aug. 15, 2018), pp. 400–408. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2018.06.009](https://doi.org/10.1016/j.nucengdes.2018.06.009).
- [82] M. S. Plesset and S. A. Zwick. "The Growth of Vapor Bubbles in Superheated Liquids". In: *Journal of Applied Physics* 25.4 (Apr. 1954). Number: 4, pp. 493–450. ISSN: 0021-8979.
- [83] Michael Z. Podowski and Raf M. Podowski. "Mechanistic Multidimensional Modeling of Forced Convection Boiling Heat Transfer". In: *Science and Technology of Nuclear Installations* 2009 (Dec. 22, 2008). Publisher: Hindawi, e387020. ISSN: 1687-6075. DOI: [10.1155/2009/387020](https://doi.org/10.1155/2009/387020).

- [84] V Prodanovic, D Fraser, and M Salcudean. “Bubble behavior in subcooled flow boiling of water at low pressures and low flow rates”. In: *International Journal of Multiphase Flow* 28.1 (Jan. 1, 2002), pp. 1–19. ISSN: 0301-9322. DOI: [10.1016/S0301-9322\(01\)00058-1](https://doi.org/10.1016/S0301-9322(01)00058-1).
- [85] W. E. Ranz. “Evaporation from drops”. In: *Chemical Engineering Progress* (Jan. 1, 1952). ISSN: 0360-7275.
- [86] Lord Rayleigh. “VIII. On the pressure developed in a liquid during the collapse of a spherical cavity”. In: *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science* 34.200 (Aug. 1, 1917). Publisher: Taylor & Francis \_eprint: <https://doi.org/10.1080/14786440808635681>, pp. 94–98. ISSN: 1941-5982. DOI: [10.1080/14786440808635681](https://doi.org/10.1080/14786440808635681).
- [87] H. Reichardt. “Vollständige Darstellung der turbulenten Geschwindigkeitsverteilung in glatten Leitungen”. In: *Zeitschrift Angewandte Mathematik und Mechanik* 31 (Jan. 1, 1951). ADS Bibcode: 1951ZaMM...31..208R, pp. 208–219. ISSN: 0044-2267. DOI: [10.1002/zamm.19510310704](https://doi.org/10.1002/zamm.19510310704).
- [88] Tingting Ren, Zhiqiang Zhu, Rui Zhang, Jiangwu Shi, and Changqi Yan. “Development of force balance model for prediction of bubble departure diameter and lift-off diameter in subcooled flow boiling”. In: *International Journal of Heat and Mass Transfer* 161 (Nov. 1, 2020), p. 120245. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2020.120245](https://doi.org/10.1016/j.ijheatmasstransfer.2020.120245).
- [89] Andrew Jonathan Richenderfer. “Experimental study of heat flux partitioning in pressurized sub-cooled flow boiling”. Accepted: 2018-11-15T15:51:52Z. Thesis. Massachusetts Institute of Technology, 2018.
- [90] Andrew Richenderfer, Artyom Kossolapov, Jee Hyun Seong, Giacomo Saccone, Etienne Demarly, Ravikishore Kommajosyula, Emilio Baglietto, Jacopo Buongiorno, and Matteo Bucci. “Investigation of subcooled flow boiling and CHF using high-resolution diagnostics”. In: *Experimental Thermal and Fluid Science* 99 (Dec. 1, 2018), pp. 35–58. ISSN: 0894-1777. DOI: [10.1016/j.expthermflusci.2018.07.017](https://doi.org/10.1016/j.expthermflusci.2018.07.017).
- [91] E. Ruckenstein. “On mass transfer in the continuous phase from spherical bubbles or drops”. In: *Chemical Engineering Science* 19.2 (Feb. 1, 1964), pp. 131–146. ISSN: 0009-2509. DOI: [10.1016/0009-2509\(64\)85117-4](https://doi.org/10.1016/0009-2509(64)85117-4).
- [92] P. G. Saffman. “The lift on a small sphere in a slow shear flow”. In: *Journal of Fluid Mechanics* 22.2 (June 1965), pp. 385–400. ISSN: 0022-1120, 1469-7645. DOI: [10.1017/S0022112065000824](https://doi.org/10.1017/S0022112065000824).
- [93] V. Scheiff, F. Bergame, J. Sebilleau, P. Ruyer, and C. Colin. “Experimental study of steady and transient subcooled flow boiling”. In: *International Journal of Heat and Mass Transfer* 164 (Jan. 1, 2021), p. 120548. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2020.120548](https://doi.org/10.1016/j.ijheatmasstransfer.2020.120548).
- [94] Valentin Scheiff. “Etude expérimentale et modélisation du transfert de chaleur de l’écoulement transitoire”. These de doctorat. Toulouse, INPT, Dec. 13, 2018.
- [95] L. E. Scriven. “On the dynamics of phase growth”. In: *Chemical Engineering Science* 10.1 (Apr. 1, 1959), pp. 1–13. ISSN: 0009-2509. DOI: [10.1016/0009-2509\(59\)80019-1](https://doi.org/10.1016/0009-2509(59)80019-1).
- [96] Pengyu Shi, Roland Rzehak, Dirk Lucas, and Jacques Magnaudet. “Drag and lift forces on a rigid sphere immersed in a wall-bounded linear shear flow”. In: *Physical Review Fluids* 6.10 (Oct. 28, 2021). Number: 10 Publisher: American Physical Society, p. 104309. ISSN: 2469-990X.
- [97] Rong Situ, Takashi Hibiki, Mamoru Ishii, and Michitsugu Mori. “Bubble lift-off size in forced convective subcooled boiling flow”. In: *International Journal of Heat and Mass Transfer* 48.25 (Dec. 1, 2005), pp. 5536–5548. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2005.06.031](https://doi.org/10.1016/j.ijheatmasstransfer.2005.06.031).
- [98] Jia-Wen Song and Li-Wu Fan. “Temperature dependence of the contact angle of water: A review of research progress, theoretical understanding, and implications for boiling heat transfer”. In: *Advances in Colloid and Interface Science* 288 (Feb. 1, 2021), p. 102339. ISSN: 0001-8686. DOI: [10.1016/j.cis.2020.102339](https://doi.org/10.1016/j.cis.2020.102339).
- [99] R. Sugrue and J. Buongiorno. “A modified force-balance model for prediction of bubble departure diameter in subcooled flow boiling”. In: *Nuclear Engineering and Design* 305 (Aug. 15, 2016), pp. 717–722. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2016.04.017](https://doi.org/10.1016/j.nucengdes.2016.04.017).
- [100] R. Sugrue, J. Buongiorno, and T. McKrell. “An experimental study of bubble departure diameter in subcooled flow boiling including the effects of orientation angle, subcooling, mass flux, heat flux, and pressure”. In: *Nuclear Engineering and Design*. SI : CFD4NRS-4 279 (Nov. 1, 2014), pp. 182–188. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2014.08.009](https://doi.org/10.1016/j.nucengdes.2014.08.009).

- [101] Rosemary M. Sugrue. "The Effects of Orientation Angle, Subcooling, Heat Flux, Mass Flux, and Pressure on Bubble Growth and Detachment in Subcooled Flow Boiling". PhD thesis. Massachusetts Institute of Technology, 2012.
- [102] M. Sultan and R. L. Judd. "Spatial Distribution of Active Sites and Bubble Flux Density". In: *Journal of Heat Transfer* 100.1 (Feb. 1, 1978), pp. 56–62. ISSN: 0022-1481. DOI: [10.1115/1.3450504](https://doi.org/10.1115/1.3450504).
- [103] J. R. S. Thom, W. M. Walker, T. A. Fallon, and G. F. S. Reising. "Boiling In Sub-Cooled Water During Flow Up Heated Tubes or Annuli." In: *Proc. Inst. Mech. Eng. (London)*, 180: Pt 3C, 226-46(1965-66). (Oct. 31, 1967). Institution: Babcock and Wilcox Ltd., Renfrew, Eng.
- [104] G. E. Thorncroft, J. F. Klausner, and R. Mei. "An experimental investigation of bubble growth and detachment in vertical upflow and downflow boiling". In: *International Journal of Heat and Mass Transfer* 41.23 (Dec. 1, 1998), pp. 3857–3871. ISSN: 0017-9310. DOI: [10.1016/S0017-9310\(98\)00092-1](https://doi.org/10.1016/S0017-9310(98)00092-1).
- [105] G.E. Thorncroft, J.F. Klausner, and R. Mei. "Bubble forces and detachment models". In: *Multiphase Science and Technology* 13.3 (2001), pp. 35–76. ISSN: 0276-1459. DOI: [10.1615/multscientechn.v13.i3-4.20](https://doi.org/10.1615/multscientechn.v13.i3-4.20).
- [106] V. I. Tolubinsky and D. M. Kostanchuk. "VAPOUR BUBBLES GROWTH RATE AND HEAT TRANSFER INTENSITY AT SUBCOOLED WATER BOILING". In: International Heat Transfer Conference 4. Begel House Inc., 1970. DOI: [10.1615/IHTC4.250](https://doi.org/10.1615/IHTC4.250).
- [107] G. G. Treshchev. "The number of vapor-formation centers in surface boiling". In: *Convective Heat Transfer in Two-Phase and One-Phase Flows*. Borishanskii V.M. and Paleev I.I. Jerusalem: Israel Program for Scientific Translations, 1969, pp. 97–105.
- [108] A. Urbano, S. Tanguy, and C. Colin. "Direct numerical simulation of nucleate boiling in zero gravity conditions". In: *International Journal of Heat and Mass Transfer* 143 (Nov. 1, 2019), p. 118521. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2019.118521](https://doi.org/10.1016/j.ijheatmasstransfer.2019.118521).
- [109] A. Urbano, S. Tanguy, G. Huber, and C. Colin. "Direct numerical simulation of nucleate boiling in micro-layer regime". In: *International Journal of Heat and Mass Transfer* 123 (Aug. 1, 2018), pp. 1128–1137. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2018.02.104](https://doi.org/10.1016/j.ijheatmasstransfer.2018.02.104).
- [110] W. G. J. Van Helden, C. W. M. Van Der Geld, and P. G. M. Boot. "Forces on bubbles growing and detaching in flow along a vertical wall". In: *International Journal of Heat and Mass Transfer* 38.11 (July 1, 1995), pp. 2075–2088. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(94\)00319-Q](https://doi.org/10.1016/0017-9310(94)00319-Q).
- [111] L. Van Wijngaarden and D. J. Jeffrey. "Hydrodynamic interaction between gas bubbles in liquid". In: *Journal of Fluid Mechanics* 77.1 (Sept. 1976). Publisher: Cambridge University Press, pp. 27–44. ISSN: 1469-7645, 0022-1120. DOI: [10.1017/S0022112076001110](https://doi.org/10.1017/S0022112076001110).
- [112] G. H. Yeoh, Sherman C. P. Cheung, J. Y. Tu, and Mark K. M. Ho. "Fundamental consideration of wall heat partition of vertical subcooled boiling flows". In: *International Journal of Heat and Mass Transfer* 51.15 (July 15, 2008), pp. 3840–3853. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2007.11.047](https://doi.org/10.1016/j.ijheatmasstransfer.2007.11.047).
- [113] Junsoo Yoo, Carlos E. Estrada-Perez, and Yassin A. Hassan. "Experimental study on bubble dynamics and wall heat transfer arising from a single nucleation site at subcooled flow boiling conditions – Part 1: Experimental methods and data quality verification". In: *International Journal of Multiphase Flow* 84 (Sept. 1, 2016), pp. 315–324. ISSN: 0301-9322. DOI: [10.1016/j.ijmultiphaseflow.2016.04.018](https://doi.org/10.1016/j.ijmultiphaseflow.2016.04.018).
- [114] Junsoo Yoo, Carlos E. Estrada-Perez, and Yassin A. Hassan. "Experimental study on bubble dynamics and wall heat transfer arising from a single nucleation site at subcooled flow boiling conditions – Part 2: Data analysis on sliding bubble characteristics and associated wall heat transfer". In: *International Journal of Multiphase Flow* 84 (Sept. 1, 2016), pp. 292–314. ISSN: 0301-9322. DOI: [10.1016/j.ijmultiphaseflow.2016.04.019](https://doi.org/10.1016/j.ijmultiphaseflow.2016.04.019).
- [115] Junsoo Yoo, Carlos E. Estrada-Perez, and Yassin A. Hassan. "Area of bubble influence due to sliding bubbles in subcooled boiling flow". In: *International Journal of Heat and Mass Transfer* 125 (Oct. 1, 2018), pp. 43–52. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2018.04.058](https://doi.org/10.1016/j.ijheatmasstransfer.2018.04.058).

- [116] Junsoo Yoo, Carlos E. Estrada-Perez, and Yassin A. Hassan. "Development of a mechanistic model for sliding bubbles growth prediction in subcooled boiling flow". In: *Applied Thermal Engineering* 138 (June 25, 2018), pp. 657–667. ISSN: 1359-4311. DOI: [10.1016/j.applthermaleng.2018.04.096](https://doi.org/10.1016/j.applthermaleng.2018.04.096).
- [117] Byong-Jo Yun, Andrew Splawski, Simon Lo, and Chul-Hwa Song. "Prediction of a subcooled boiling flow with advanced two-phase flow models". In: *Nuclear Engineering and Design*. SI : CFD4NRS-3 253 (Dec. 1, 2012), pp. 351–359. ISSN: 0029-5493. DOI: [10.1016/j.nucengdes.2011.08.067](https://doi.org/10.1016/j.nucengdes.2011.08.067).
- [118] L. Z. Zeng, J. F. Klausner, D. M. Bernhard, and R. Mei. "A unified model for the prediction of bubble detachment diameters in boiling systems—II. Flow boiling". In: *International Journal of Heat and Mass Transfer* 36.9 (Jan. 1, 1993), pp. 2271–2279. ISSN: 0017-9310. DOI: [10.1016/S0017-9310\(05\)80112-7](https://doi.org/10.1016/S0017-9310(05)80112-7).
- [119] Lanying Zeng, Fady Najjar, S. Balachandar, and Paul Fischer. "Forces on a finite-sized particle located close to a wall in a linear shear flow". In: *Physics of Fluids* 21.3 (Mar. 2009). Publisher: American Institute of Physics, p. 033302. ISSN: 1070-6631. DOI: [10.1063/1.3082232](https://doi.org/10.1063/1.3082232).
- [120] Pei Zhou, Shiyang Hua, Cai Gao, Dongfang Sun, and Ronghua Huang. "A mechanistic model for wall heat flux partitioning based on bubble dynamics during subcooled flow boiling". In: *International Journal of Heat and Mass Transfer* 174 (Aug. 1, 2021), p. 121295. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2021.121295](https://doi.org/10.1016/j.ijheatmasstransfer.2021.121295).
- [121] Pei Zhou, Ronghua Huang, Sheng Huang, Yu Zhang, and Xiaoxuan Rao. "Experimental investigation on active nucleation site density and bubble departure frequency in subcooled flow boiling by using bubble tracking algorithm". In: *International Journal of Heat and Mass Transfer* 148 (Feb. 1, 2020), p. 119081. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2019.119081](https://doi.org/10.1016/j.ijheatmasstransfer.2019.119081).
- [122] Pei Zhou, Ronghua Huang, Sheng Huang, Yu Zhang, and Xiaoxuan Rao. "Experimental investigation on bubble contact diameter and bubble departure diameter in horizontal subcooled flow boiling". In: *International Journal of Heat and Mass Transfer* 149 (Mar. 1, 2020), p. 119105. ISSN: 0017-9310. DOI: [10.1016/j.ijheatmasstransfer.2019.119105](https://doi.org/10.1016/j.ijheatmasstransfer.2019.119105).
- [123] Novak Zuber. "The dynamics of vapor bubbles in nonuniform temperature fields". In: *International Journal of Heat and Mass Transfer* 2.1 (Mar. 1, 1961), pp. 83–98. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(61\)90016-3](https://doi.org/10.1016/0017-9310(61)90016-3).
- [124] H. C. Ünal. "Maximum bubble diameter, maximum bubble-growth time and bubble-growth rate during the subcooled nucleate flow boiling of water up to 17.7 MN/m<sup>2</sup>". In: *International Journal of Heat and Mass Transfer* 19.6 (June 1, 1976), pp. 643–649. ISSN: 0017-9310. DOI: [10.1016/0017-9310\(76\)90047-8](https://doi.org/10.1016/0017-9310(76)90047-8).

---

## DECLARATION

---

Put your declaration here.

*Paris, December 2022*

---

Luc Favre

## COLOPHON

This document was typeset using the typographical look-and-feel `classicthesis` developed by André Miede. The style was inspired by Robert Bringhurst's seminal book on typography "*The Elements of Typographic Style*". `classicthesis` is available for both L<sup>A</sup>T<sub>E</sub>X and LyX:

<https://bitbucket.org/amiede/classicthesis/>

Happy users of `classicthesis` usually send a real postcard to the author, a collection of postcards received so far is featured here:

<http://postcards.miede.de/>

