

# The guide to Pycle (**P**ython **C**ompressive **L**earning toolbox)

Vincent Schellekens

December 6, 2019

## Abstract

This is the guide to Pycle, a toolbox for Compressive Learning. It is structured as follows: first we shortly explain the theoretical methods this toolbox implements. Then, we explain how the toolbox is structured, and the main steps that a user should follow to use it. The detailed documentation of all the functionalities in the toolbox is then provided, followed by some practical examples to get started easily.

## 1 What is Compressive Learning?




Figure 1: Compressive learning .

$$z_X := \frac{1}{n} \sum_{i=1}^n \Phi(\mathbf{x}_i) \quad (1)$$

See [1] for a complete introduction to compressive learning.

## 2 An overview of Pycle

### 2.1 Requirements

The Pycle package builds on a set of standard Python libraries, that are required to run it:

- `numpy`
- `scipy`
- `matplotlib`

### 2.2 Typical workflow

A typical use of Pycle follows the following steps:

1. Design a sketch operator, then sketch the dataset using the `sketching.py` module.
2. Extract a model from the sketch by a compressive learning method contained in the `compressive_learning.py` module.




Figure 2: Flowchart of a typical compressive learning execution with Pycle.

## 3 A tutorial tour of pycle

We now explain the core features of `pycle`. I'll go over each of the submodules one by one and introduce, in a “tutorial style”, the most important tools they provide. Our focus being on understanding, this section is neither concise nor exhaustive (however, section 4 is a methodical list of all the toolbox features).

### 3.1 Sketching

To use the `sketching` submodule, you first need to import it (to spare me some typing, I personally like to use `sk` as shorthand). Usual sketching as defined in (1) can then be done by calling `sk.computeSketch` as follows.

---

```
import pycle.sketching as sk

X = ... # load a numpy array of dimension (n,d)
Phi = ... # sketch feature map, see later

z = sk.computeSketch(X,Phi)
```

---

As you might have guessed, `sk.computeSketch(dataset, featureMap)` requires two arguments: the dataset  $X$ , and the feature map  $\Phi$ . Let's start with the simplest one: the dataset  $X$  should be given as a 2d numpy array of dimensions  $(n, d)$ .

**Note: Matrix representation conventions.** We follow the same convention as most mainstream Python ML modules: the dataset, that we mathematically describe as  $X = (\mathbf{x}_i \in \mathbb{R}^d)_{i=1}^n \in \mathbb{R}^{d \times n}$ , is represented by a numpy array of shape  $(n, d)$ . In particular, `X[0]` references  $\mathbf{x}_1$ : note the awkward inversion of dimension order. For matrices that don't represent datasets (e.g.,  $\Omega$  in the examples below), we stick to the mathematical convention instead, i.e., a matrix of the type  $\mathbb{R}^{a \times b}$  is represented by a numpy array of shape  $(a, b)$ .

The feature map argument can be specified in one of the two following ways. Either—and this is the method I recommend—you give an instance of a `FeatureMap` object (explained below), or you directly provide a callable Python function (e.g., to compute the second-order moments for the sketch, write `Phi = lambda x: x**2`). Note that the second method is proposed for research purposes, in the case you want to construct a custom feature map that cannot be instantiated with the methods provided within the `FeatureMap` class.

**Note: FeatureMap objects.** Why do we use `FeatureMap` objects instead of (Python) functions to represent... well, (mathematical) functions? Because we often require additional metadata/methods about  $\Phi$  (e.g., target dimension  $m$ , jacobian  $\nabla\Phi, \dots$ ). All these parameters and methods are conveniently packaged inside `FeatureMap` objects.

*Voilà*, you know the basics of how the `sketching` submodule is used! Well, OK, all we saw was a function that computes an average, but hey, that's like, the essence of sketching, it's not my fault. Luckily for you, `sketching` has much more to offer. First and foremost, I'll demonstrate the whole zoo of feature maps that are readily available—I promise you, you'll construct your `FeatureMap` object  $\Phi$  in no more than two lines of code. After this comes more advanced methods of the toolbox that you may not need right away: I'll show how to automatically select the *scale hyper-parameter* in the aforementioned feature maps (which in practice can be hard to guess *a priori*); I'll then finally explain `pycles` functions for sketching with Differential Privacy guarantees.

#### 3.1.1 Painless instantiation of standard feature maps: the `SimpleFeatureMap` class

...

3.1.2 Designing the sampling pattern in the feature maps: the `estimateSigma` function

3.1.3 Guaranteeing the Differential Privacy of sketching: the `computeSketch_DP` function

3.2 Learning

3.3 Utilities

## 4 Documentation

4.1 Sketching methods

4.2 Learning tools

4.3 Utilities

## 5 Conclusion: going further

My primary goals for `pycle` are that it should be:

- **intuitive to use:** practitioners with no background knowledge in compressive learning and little experience in Python should be able to use it to implement compressive learning in their own projects;
- **flexible to new features:** researchers with interest in compressive learning (that want to try out new methods/techniques in CL) should be able to easily extend this code to suit their own needs, without having to re-write things from scratch (and eventually, suggesting to add some features to the toolbox);
- **efficient to run:** the main motivation of compressive learning is based on the fact that it can be much more memory- and time-efficient than traditional learning methods, so the performances of the toolbox should fulfill that promise (note: this goal is still a challenge for me, this item is rather wishful thinking).

With this in mind, if you have any suggestions to improve the toolbox, please don't hesitate to contact me!

## References

- [1] R. Gribonval, G. Blanchard, N. Keriven, and Y. Traonmilin, “Compressive statistical learning with random feature moments,” *arXiv preprint arXiv:1706.07180*, 2017.