

Documentation Guide

# Workspace - temp

# Índice

- 1. Settings
- 2. Connectors
  - 2.1 New Connector1111111111
  - 2.2 New Connector
- 3. Environment Variables
- 4. Forms
- 5. Open Telemetry
- 6. Gateway

# 1 - Settings

## General Settings

Description: Is workspace to temp

Container Image Name	Form Page Port	Enable Container Timeout	Container Timeout (minutes)
temp	8000	true	5

## Upload to Git

Repo URL: git@github.com:lucianasousa8/githubTestQscim.git

Upload to Git	Username	Email
true	lucianasousa8	lucianalopesdisc@gmail.com

## 2 - Connectors

### 2.2 - New Connector

ldap - port: 888

#### Configuration:

Edit connector configuration.

Key	Value
admin_user	admim
admin_password	123
user_base	raiUfopa
group_base	Ufopa2
user_attr	coimbra
group_attr	coimbra enterprise
user_classes	
0	rhgeth
group_classes	
0	etherh

## 2 - Connectors

### 2.2 - New Connector

ldap - port: 888

#### Mapping:

Map connector variables according to SCIM protocol.

Description:

#### Group mapping

Source	Destination	Type
dn	id	string
cn	displayName	string
member	members.value	array

## 2 - Connectors

### 2.2 - New Connector

ldap - port: 888

#### User mapping

Source	Destination	Type
dn	id	string
cn	userName	string
userAccountControl	active	boolean
userPassword	password	string
memberOf	groups.value	array
givenName	name.givenName	string
sn	name.familyName	string
displayName	name.formatted	string
title	title	string
mail	attributes.email.value	string
homePhone	phoneNumbers.home.value	string
postalCode	addresses.work.postalCode	string
streetAddress	addresses.work.streetAddress	string
l	addresses.work.locality	string
st	addresses.work.region	string
co	addresses.work.country	string
description	attributes.description.value	string
lastLogonTimestamp	attributes.lastLogonTimestamp.value	string
homeDirectory	attributes.homeDirectory.value	string
homeDrive	attributes.homeDrive.value	string
telephoneNumber	attributes.telephoneNumber.value	string
physicalDeliveryOfficeName	attributes.physicalDeliveryOfficeName.value	string

## 2 - Connectors

### 2.2 - New Connector

ldap - port: 888

#### Interceptors:

Create business rules or fetch data before reaching the connector.

Type: business-rule

Description: Define customized business rules to intercept and control requests.

Condition type: all

#### Condition table

Condition	Field	Type	Value
notEqual	userName	string	qriar

Type: business-rule

Description: Define customized business rules to intercept and control requests.

Condition type: all

#### Condition table

Condition	Field	Type	Value
equal		string	

Type: business-rule

Description: Define customized business rules to intercept and control requests.

Condition type: all

#### Condition table

Condition	Field	Type	Value
equal		string	

## 4 - Forms

Form Name	Method	Path	Connectors
My form	POST	/users	1
My form	POST	/users	1



# Environment Variables:

Name	Value
U*****	*****

## 5 - Open Telemetry

URL:http://localhost:9411/api/v2/spans

Name	Methods	Path
QSCIM Tracing	GET, POST, PUT, PATCH, DELETE	users, groups

### Headers

Key	Value
-----	-------

## 6 - Gateway

Enabled	Connectors	Port
true	1	5000