

Universidade de Aveiro

Mestrado em Engenharia de Computadores e Telemática Arquitecturas de Alto Desempenho

Memory

Academic year 2021/2022

- 1. Assume a memory subsystem with 23 address lines.
 - 1.1. How many bytes, half-words, words and double-words can be stored in it?
 - 1.2. Give examples of addresses (in hexadecimal form) for bytes, half-words, words and doublewords stored in the last quarter of its addressing space.
 - 1.3. Which of the following addresses are classified as *misaligned* if one intends to reference a byte, a half-word, a word and a double-word: 14902₁₀, 3710₁₀, 5555₁₀, 764₁₀ and 2760₁₀? Convert them first to hexadecimal form before giving your answer.
 - 1.4. Can the address 11899675₁₀ express a valid byte reference for the memory subsystem?
- 2. Consider a 128Mbit SDRAM chip organized in 8 banks of 4096 rows x 1024 columns of 4 bits.
 - 2.1. How many address lines are there? Justify clearly your answer.
 - 2.2. How many chips are needed to build a 64-bit data wide memory subsystem? Justify clearly your answer.
 - 2.3. What is the storage capacity of such subsystem? Justify clearly your answer.
 - 2.4. Sketch how the external address bus are mapped internally to make data access as efficient as possible. What is the main concern to be taken into account?