


#20 – Finding Similar Items (3)

Determine candidate pairs



Locality Sensitive Hashing

Locality-Sensitive Hashing:

LSH: General Idea

- **Goal:** Find documents with Jaccard similarity at least s
 - for some similarity threshold, e.g., $s=0.8$
- **LSH – General idea:**
 - Use a function $f(x,y)$ that tells whether x and y is a *candidate pair*:
 - a pair of elements whose similarity must be evaluated

LSH: General Idea

- **For Min-Hash matrices:**
 - Hash columns of **signature matrix M** to many buckets
 - Remember that columns represent documents
 - Each **pair of documents** that hashes into the **same bucket** is a **candidate pair**

Candidates from Min-Hash

- Pick a similarity threshold s ($0 < s < 1$)
- Columns \mathbf{x} and \mathbf{y} of \mathbf{M} are a **candidate pair** if their signatures agree on at least fraction s of their rows:
 $M(i, \mathbf{x}) = M(i, \mathbf{y})$ for at least frac. s values of i
- We expect documents \mathbf{x} and \mathbf{y} to have the same (Jaccard) similarity as their signatures

LSH for Min-Hash


- **Big idea:** Hash columns of signature matrix M several times
- Arrange that (only) **similar columns** are likely to **hash to the same bucket**, with high probability
- **Candidate pairs are those that hash to the same bucket**

Hash several times ...

- Divide matrix M into b bands of r rows
- For each band, hash its portion of each column to a hash table with k buckets
- Make k as large as possible




Partition M into b Bands



Partition M into Bands

- *Candidate* column **pairs** are those that hash to the same bucket for ≥ 1 band
- Tune *b* and *r*
 - to catch most similar pairs
 - but few non-similar pairs

Hashing Bands




Analysis of the Banding Technique

Simplifying Assumption

- IMPORTANT:
 - There are **enough buckets** that columns are unlikely to hash to the same bucket unless they are **identical** in a particular band
- Hereafter, we assume that “**same bucket**” means “**identical in that band**”
- Assumption needed only to simplify analysis, not for correctness of algorithm


b bands, r rows/band

- It is convenient to represent the bands in an abbreviated way
- Next example refers to 10 docs and 3 bands



b bands, r rows/band

- Consider the two blocks marked (with blue and green) in the figure:
- The probability of all elements of the blue block being equal to the corresponding elements of the green block is J^r
 - J is the Jaccard index/similarity of the two objects
 - Columns C_1 and C_2 have similarity J
 - r is the number of rows in each band



Probabilities

- Probability that not all elements in blue block and green block are equal:
 - $1 - J^r$
- Probability that not all elements are equal for the several bands is:
 - $(1 - J^r)^b$
 - Where b is the number of bands
- Probability of at least 1 band identical

$$P = 1 - (1 - J^r)^b$$



Example of application

Assume the following case:

- Suppose 100,000 columns of \mathbf{M} (100k docs)
- Signatures of 100 integers (rows)
- Therefore, signatures take 40Mb
- Choose $\mathbf{b} = 20$ bands of $\mathbf{r} = 5$ integers/band
- **Goal:** Find pairs of documents that are at least $\mathbf{s} = 0.8$ similar

Case 1: C_1, C_2 are 80% Similar

- Find pairs of $\geq s=0.8$ similarity, set $b=20, r=5$
- **Assume:** $\text{sim}(C_1, C_2) = 0.8$
 - Since $\text{sim}(C_1, C_2) \geq s$, we want C_1, C_2 to be a **candidate pair**:
 - We want them to **hash to at least 1 common bucket**
(at least one band identical)

Case 1 : 80 % similar

- Probability C_1, C_2 **identical in one particular band:**
 - $J^r = (0.8)^5 = 0.328$
- Probability C_1, C_2 are **not similar** in all of the 20 bands: $(1-0.328)^{20} = 0.00035$
 - i.e., about **1/3000th** of the 80%-similar column pairs are **false negatives**
- We would **find 99.965% pairs of truly similar documents**

Case 2: C_1, C_2 are 30% Similar

- Find pairs of $\geq s=0.8$ similarity, set $b=20, r=5$
- But now **Assume:** $\text{sim}(C_1, C_2) = 0.3$
- Since $\text{sim}(C_1, C_2) < s$ we want C_1, C_2 to hash to **NO common buckets**
 - all bands should be different

Case 2 (cont.): 30 % similar

- Probability C_1, C_2 **identical in one particular band:**
 - $(0.3)^5 = 0.00243$, as before
- Probability C_1, C_2 **identical in at least 1 of 20 bands:**
 - $1 - (1 - 0.00243)^{20} = 0.0474$
 - Approximately **4.74%** pairs of docs with similarity 0.3% end up becoming **candidate pairs**
- They are **false positives** since we will have to examine them (they are candidate pairs)
 - but then it will turn out their similarity is below threshold s

LSH Involves a Tradeoff

■ Pick:

- The number of Min-Hashes (rows of \mathbf{M})
- The number of bands \mathbf{b} , and
- The number of rows \mathbf{r} per band

to balance false positives and false negatives

Example (with less bands)

- Only 15 bands of 5 rows
- What happens to false positives ?
- And to false negatives ?

15 bands of 5 rows – False Positives

- Probability C_1, C_2 identical in one particular band: $(0.3)^5 = 0.00243$
- Probability C_1, C_2 identical in at least 1 of 15 bands: $1 - (1 - 0.00243)^{15} = 0.0358$
 - In other words, approximately 3.6% pairs of docs with similarity 0.3% end up becoming candidate pairs
 - They are false positives
- False positives decreased
 - It was 4.74 % for $b=20$


15 bands of 5 rows – false negatives

- **Probability C_1, C_2 identical in one particular band:** $(0.8)^5 = 0.328$
- Probability C_1, C_2 are **not** similar in all of the 15 bands: $(1-0.328)^{15} = 0.0026$
 - i.e., about **1/400th** of the 80%-similar column pairs are **false negatives** (we miss them)
- **We would find 99.74% pairs of truly similar documents**


Effect of decreasing bands

- The number of false positives goes down
- But the number of false negatives goes up
 - From 1/3000 to 1/400 (for similarity = 0.8)


LSH – What We Want



What 1 Band of 1 Row Gives You



What b Bands of r Rows Gives You




Similarity threshold s

- Example: $b = 20$; $r = 5$
- Prob. that at least 1 band is identical:

s	$1-(1-s^r)^b$
.2	.006
.3	.047
.4	.186
.5	.470
.6	.802
.7	.975
.8	.9996

Picking r and b : The S-curve

- Picking r and b to get the best S-curve
 - 50 hash-functions ($r=5$, $b=10$)




Blue area: False Negative rate
Green area: False Positive rate

Picking r and b : Example

- Imagine we want to select with probability < 0.01 all objects with Jaccard similarity $\leq 60\%$...
- AND we also want to select with probability > 0.99 all objects with Jaccard similarity $\geq 90\%$
- It is possible to solve the equations involving b and r to obtain their values
- The solution for our example:
 - b aprox. 20
 - r aprox. 15

Example (continuation)

- Confirming the results...
- Curve $P(J) = 1 - (1 - J^r)^b$
 - $r=15$
 - $b=20$





- Probability < 0.01 for Jaccard similarity ≤ 0.6
- $1 - (1 - 0.6^{15})^{20} \approx 0.0095 < 0.01$
 - OK
- Probability > 0.99 for Jaccard similarity ≥ 0.9
- $1 - (1 - 0.9^{15})^{20} \approx 0.9901 > 0.99$
 - OK

LSH Summary

- Tune M , b , r to get almost all pairs with similar signatures
 - but eliminate most pairs that do not have similar signatures
- Check in main memory that candidate pairs really do have similar signatures
- **Optional:** In another pass through data, check that the remaining candidate pairs really represent similar documents

Application to MovieLens

- Process the MinHash matrix (explained before)
 - They have been calculated previously
- Lets use $r=10$ $b = \text{NumHashFunctions} / r$



Note to other teachers and users of these slides: We would be delighted if you found this our material useful in giving your own lectures. Feel free to use these slides verbatim, or to modify them to fit your own needs. If you make use of a significant portion of these slides in your own lecture, please include this message, or a link to our web site: <http://www.mmds.org>

Part of the slides Adapted from: Finding Similar Items: Locality Sensitive Hashing

Mining of Massive Datasets

Jure Leskovec, Anand Rajaraman, Jeff Ullman

Stanford University

<http://www.mmds.org>

