PYTORCH CHEAT SHEET

Imports

General

```
import torch  # root package
from torch.utils.data import Dataset, DataLoader  # dataset representation and loading
```

Neural Network API

```
import torch.autograd as autograd  # computation graph
from torch import Tensor  # tensor node in the computation graph
import torch.nn as nn  # neural networks
import torch.nn.functional as F  # layers, activations and more
import torch.optim as optim  # optimizers e.g. gradient descent, ADAM, etc.
from torch.jit import script, trace  # hybrid frontend decorator and tracing jit
```

See autograd, nn, functional and optim

Torchscript and JIT

See Torchscript

ONNX

See onnx

Vision

```
from torchvision import datasets, models, transforms # vision datasets,
# architectures &
# transforms

import torchvision.transforms as transforms # composable transforms
```

See torchvision

Distributed Training

```
import torch.distributed as dist  # distributed communication
from torch.multiprocessing import Process  # memory sharing processes
```

· - - ·

See distributed and multiprocessing

Tensors

Creation

```
x = torch.randn(*size)  # tensor with independent N(0,1) entries
x = torch.[ones|zeros](*size)  # tensor with all 1's [or 0's]
x = torch.tensor(L)  # create tensor from [nested] list or ndarray L
y = x.clone()  # clone of x
with torch.no_grad():  # code wrap that stops autograd from tracking tensor history
requires_grad=True  # arg, when set to True, tracks computation
# history for future derivative calculations
```

See tensor

Dimensionality

```
# return tuple-like object of dimensions
x.size()
x = torch.cat(tensor_seq, dim=0)
                                           # concatenates tensors along dim
y = x.view(a,b,...)
                                           # reshapes x into size (a,b,...)
y = x.view(-1,a)
                                           # reshapes x into size (b,a) for some b
y = x.transpose(a,b)
                                           # swaps dimensions a and b
y = x.permute(*dims)
                                           # permutes dimensions
y = x.unsqueeze(dim)
                                           # tensor with added axis
y = x.unsqueeze(dim=2)
                                           # (a,b,c) tensor -> (a,b,1,c) tensor
                                           \# removes all dimensions of size 1 (a,1,b,1) \rightarrow (a,b)
y = x.squeeze()
y = x.squeeze(dim=1)
                                           # removes specified dimension of size 1 (a,1,b,1) -> (a,b,1)
```

See tensor

Algebra

```
ret = A.mm(B)  # matrix multiplication
ret = A.mv(x)  # matrix-vector multiplication
x = x.t()  # matrix transpose
```

See math operations

GPU Usage

```
torch.cuda.is_available
                                                             # check for cuda
x = x.cuda()
                                                             # move x's data from
                                                             # CPU to GPU and return new object
x = x.cpu()
                                                             # move x's data from GPU to CPU
                                                             # and return new object
if not args.disable_cuda and torch.cuda.is_available():
                                                             # device agnostic code
                                                             # and modularity
    args.device = torch.device('cuda')
                                                             #
    args.device = torch.device('cpu')
                                                             #
net.to(device)
                                                             # recursively convert their
                                                             # parameters and buffers to
                                                             # device specific tensors
x = x.to(device)
                                                             # copy your tensors to a device
                                                             # (gpu, cpu)
```

See cuda

Deep Learning

```
nn.Linear(m,n)
                                               # fully connected layer from
                                               # m to n units
nn.ConvXd(m,n,s)
                                               # X dimensional conv layer from
                                               # m to n channels where X \in \{1, 2, 3\}
                                               # and the kernel size is s
nn.MaxPoolXd(s)
                                               # X dimension pooling layer
                                               # (notation as above)
nn.BatchNormXd
                                               # batch norm layer
                                               # recurrent layers
nn.RNN/LSTM/GRU
nn.Dropout(p=0.5, inplace=False)
                                               # dropout layer for any dimensional input
nn.Dropout2d(p=0.5, inplace=False)
                                               # 2-dimensional channel-wise dropout
nn.Embedding(num_embeddings, embedding_dim)
                                               # (tensor-wise) mapping from
                                               # indices to embedding vectors
```

See nn

Loss Functions

```
mn.X

# where X is L1Loss, MSELoss, CrossEntropyLoss

# CTCLoss, NLLLoss, PoissonNLLLoss,

# KLDivLoss, BCELoss, BCEWithLogitsLoss,

# MarginRankingLoss, HingeEmbeddingLoss,

# MultiLabelMarginLoss, SmoothL1Loss,

# SoftMarginLoss, MultiLabelSoftMarginLoss,

# CosineEmbeddingLoss, MultiMarginLoss,

# or TripletMarginLoss
```

See loss functions

Activation Functions

```
nn.X

# where X is ReLU, ReLU6, ELU, SELU, PReLU, LeakyReLU,

# RReLu, CELU, GELU, Threshold, Hardshrink, HardTanh,

# Sigmoid, LogSigmoid, Softplus, SoftShrink,

# Softsign, Tanh, TanhShrink, Softmin, Softmax,

# Softmax2d, LogSoftmax or AdaptiveSoftmaxWithLoss
```

See activation functions

Optimizers

```
opt = optim.x(model.parameters(), ...)  # create optimizer
opt.step()  # update weights
optim.X  # where X is SGD, Adadelta, Adagrad, Adam,
# AdamW, SparseAdam, Adamax, ASGD,
# LBFGS, RMSprop or Rprop
```

See optimizers

Learning rate scheduling

See learning rate scheduler

Data Utilities

Datasets

Dataset# abstract class representing datasetTensorDataset# labelled dataset in the form of tensors

Concat Dataset # concatenation of Datasets

See datasets

Dataloaders and DataSamplers

DataLoader(dataset, batch_size=1, ...) # loads data batches agnostic

of structure of individual data points

sampler.Sampler(dataset,...) # abstract class dealing with

ways to sample from dataset

sampler.XSampler where ... # Sequential, Random, SubsetRandom,

WeightedRandom, Batch, Distributed

See dataloader

Also see

- Deep Learning with PyTorch: A 60 Minute Blitz (pytorch.org)
- PyTorch Forums (discuss.pytorch.org)
- PyTorch for Numpy users (github.com/wkentaro/pytorch-for-numpy-users)

Rate this Tutorial



© Copyright 2022, PyTorch.

Built with Sphinx using a theme provided by Read the Docs.

Docs

Access comprehensive developer documentation for PyTorch View Docs **Tutorials**

Get in-depth tutorials for beginners and advanced developers

View Tutorials

Resources

Find development resources and get your questions answered

View Resources

PyTorch Resources Stay up to date PyTorch Podcasts

Get Started **Tutorials** Facebook Spotify Features Docs Twitter Apple Ecosystem Discuss YouTube Google Blog Github Issues LinkedIn Amazon

Contributing Brand Guidelines

Terms | Privacy

[©] Copyright The Linux Foundation. The PyTorch Foundation is a project of The Linux Foundation. For web site terms of use, trademark policy and other policies applicable to The PyTorch Foundation please see www.linuxfoundation.org/policies/. The PyTorch Foundation supports the PyTorch open source project, which has been established as PyTorch Project a Series of LF Projects, LLC. For policies applicable to the PyTorch Project a Series of LF Projects, LLC, please see www.lfprojects.org/policies/.