



Leetcode.typ

Gabriel Wu (@lucifer1004)

December 31, 2025

Contents

0001. Two Sum	1
0002. Add Two Numbers	3
0003. Longest Substring Without Repeating Characters	4
0004. Median of Two Sorted Arrays	5
0005. Longest Palindromic Substring	6
0006. Zigzag Conversion	8
0007. Reverse Integer	9
0008. String to Integer (atoi)	11
0009. Palindrome Number	13
0010. Regular Expression Matching	14
0011. Container With Most Water	16
0012. Integer to Roman	17
0013. Roman to Integer	19
0014. Longest Common Prefix	21
0015. 3Sum	22
0016. 3Sum Closest	24
0017. Letter Combinations of a Phone Number	26
0018. 4Sum	28
0019. Remove Nth Node From End of List	29
0020. Valid Parentheses	30
0021. Merge Two Sorted Lists	32
0022. Generate Parentheses	33
0023. Merge k Sorted Lists	34
0024. Swap Nodes in Pairs	35
0025. N-Queens	36

0001. Two Sum

Given an array of integers `nums` and an integer `target`, return indices of the two numbers such that they add up to `target`.

You may assume that each input would have **exactly one solution**, and you may not use the same element twice.

You can return the answer in any order.

Test Results

Case 1

nums: [2, 7, 11, 15]

target: 9

Expected	Your Output
[0, 1]	none

Case 2

nums: [3, 2, 4]

target: 6

Expected	Your Output
[1, 2]	none

Case 3

nums: [3, 3]

target: 6

Expected	Your Output
[0, 1]	none

Case 4

nums: [0, 0]

target: 1

Expected	Your Output
[-1, -1]	none

Case 5

nums: [1, 4, 7, 10, 13, 16, 19, 22, 25, 28, 31, 34, 37, 40, 43, 46, 49, 52, 55, 58, 61, 64, 67, 70, 73, 76, 79, 82, 85, 88, 91, 94, 97]

target: 191

Expected	Your Output
[31, 32]	none

0002. Add Two Numbers

You are given two **non-empty** linked lists representing two non-negative integers. The digits are stored in **reverse order**, and each of their nodes contains a single digit. Add the two numbers and return the sum as a linked list.

You may assume the two numbers do not contain any leading zero, except the number 0 itself.

Test Results

Case 1

l1: 2→4→3

l2: 5→6→4

Expected
7→0→8

Your Output
none

Case 2

l1: 0

l2: 0

Expected
0

Your Output
none

Case 3

l1: 9→9→9→9→9→9→9

l2: 9→9→9→9

Expected
8→9→9→9→9→0→0→0→1

Your Output
none

Case 4

l1: 2→4→3

l2: 5→6→4→9

Expected
7→0→8→9

Your Output
none

0003. Longest Substring Without Repeating Characters

Given a string `s`, find the length of the **longest substring** without repeating characters.

Test Results

Case 1

`s: "abcabcbb"`

Expected
3

Your Output
none

Case 2

`s: "bbbbbb"`

Expected
1

Your Output
none

Case 3

`s: "pwwkew"`

Expected
3

Your Output
none

0004. Median of Two Sorted Arrays

Given two sorted arrays `nums1` and `nums2` of size `m` and `n` respectively, return the **median** of the two sorted arrays.

The overall run time complexity should be $\mathcal{O}(\log(m + n))$.

Test Results

Case 1

nums1: [1, 3]

nums2: [2]

Expected
2

Your Output
none

Case 2

nums1: [1, 2]

nums2: [3, 4]

Expected
2.5

Your Output
none

Case 3

nums1: [0, 3, 6, 9, 12, 15, 18, 21, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 54, 57, 60, 63, 66, 69, 72, 75, 78, 81, 84, 87, 90, 93, 96, 99]

nums2: [0, 6, 12, 18, 24, 30, 36, 42, 48, 54, 60, 66, 72, 78, 84, 90, 96, 102, 108, 114, 120, 126, 132, 138, 144, 150, 156, 162, 168, 174, 180, 186, 192, 198]

Expected
66.0

Your Output
none

0005. Longest Palindromic Substring

Given a string `s`, return the **longest palindromic substring** in `s`.

Test Results

Case 1

`s: "babad"`

Expected
"bab"

Your Output
none

Case 2

`s: "cbbd"`

Expected
"bb"

Your Output
none

Case 3

`s: "abcdefgfedcb"`

Expected
"bcdefgfedcb"

Your Output
none

Case 4

`s: "accc"`

Expected
"ccc"

Your Output
none

Case 5

`s: "a"`

Expected
"a"

Your Output
none

Case 6

s: "aa"

Expected
"aa"

Your Output
none

Case 7

s: "asasfsafdaasfsaasa"

Expected
"aasfsaa"

Your Output
none

0006. Zigzag Conversion

The string "PAYPALISHIRING" is written in a zigzag pattern on a given number of rows like this:

```
P   A   H   N
A P L S I I G
Y   I   R
```

And then read line by line: "PAHNAPLSIIGYIR"

Write the code that will take a string and make this conversion given a number of rows.

Test Results

Case 1

s: "PAYPALISHIRING"

numRows: 3

Expected	Your Output
"PAHNAPLSIIGYIR"	none

Case 2

s: "PAYPALISHIRING"

numRows: 4

Expected	Your Output
"PINALSIGYAHRPI"	none

Case 3

s: "A"

numRows: 1

Expected	Your Output
"A"	none

0007. Reverse Integer

Given a signed 32-bit integer x , return x with its digits reversed. If reversing x causes the value to go outside the signed 32-bit integer range $[-2^{31}, 2^{31} - 1]$, then return 0.

Assume the environment does not allow you to store 64-bit integers (signed or unsigned).

Test Results

Case 1

x: 123

Expected
321

Your Output
none

Case 2

x: -123

Expected
-321

Your Output
none

Case 3

x: 120

Expected
21

Your Output
none

Case 4

x: 0

Expected
0

Your Output
none

Case 5

x: 23498423

Expected

Your Output

32489432

none

Case 6

x: -213898800

Expected
-8898312

Your Output
none

Case 7

x: 1534236469

Expected
0

Your Output
none

Case 8

x: 2147483647

Expected
0

Your Output
none

Case 9

x: -2147483648

Expected
0

Your Output
none

0008. String to Integer (atoi)

Implement the `myAtoi(string s)` function, which converts a string to a 32-bit signed integer (similar to C/C++'s `atoi` function).

The algorithm for `myAtoi(string s)` is as follows:

1. Read in and ignore any leading whitespace.
2. Check if the next character (if not already at the end of the string) is '-' or '+'. Read this character in if it is either. This determines if the final result is negative or positive respectively. Assume the result is positive if neither is present.
3. Read in next the characters until the next non-digit character or the end of the input is reached. The rest of the string is ignored.
4. Convert these digits into an integer (i.e. "123" -> 123, "0032" -> 32). If no digits were read, then the integer is 0. Change the sign as necessary (from step 2).
5. If the integer is out of the 32-bit signed integer range $[-2^{31}, 2^{31} - 1]$, then clamp the integer so that it remains in the range. Specifically, integers less than -2^{31} should be clamped to -2^{31} , and integers greater than $2^{31} - 1$ should be clamped to $2^{31} - 1$.
6. Return the integer as the final result.

Note:

- Only the space character ' ' is considered a whitespace character.
- **Do not ignore** any characters other than the leading whitespace or the rest of the string after the digits.

Test Results

Case 1

s: "42"

Expected
42

Your Output
none

Case 2

s: " -42"

Expected
-42

Your Output
none

Case 3

s: "4193 with words"

Expected
4193

Your Output
none

0009. Palindrome Number

Given an integer `x`, return `true` if `x` is a **palindrome**, and `false` otherwise.

Test Results

Case 1

x: 121

Expected
true

Your Output
none

Case 2

x: -121

Expected
false

Your Output
none

Case 3

x: 10

Expected
false

Your Output
none

0010. Regular Expression Matching

Given an input string *s* and a pattern *p*, implement regular expression matching with support for '.' and '*' where:

- '.' Matches any single character.
- '*' Matches zero or more of the preceding element.

The matching should cover the **entire** input string (not partial).

Test Results

Case 1

s: "aa"

p: "a"

Expected	Your Output
false	none

Case 2

s: "aa"

p: "a*"

Expected	Your Output
true	none

Case 3

s: "ab"

p: ".*"

Expected	Your Output
true	none

Case 4

s: "aab"

p: "c*a*b"

Expected	Your Output
true	none

Case 5

s: "mississippi"

p: "mis*is*p*"

Expected
false

Your Output
none

Case 6

s: "ab"

p: ".*c"

Expected
false

Your Output
none

Case 7

s: "ab"

p: ".*c*"

Expected
true

Your Output
none

Case 8

s: "香蕉 x 牛奶"

p: "香*牛."

Expected
true

Your Output
none

0011. Container With Most Water

You are given an integer array `height` of length `n`. There are `n` vertical lines drawn such that the two endpoints of the i^{th} line are $(i, 0)$ and $(i, \text{height}[i])$.

Find two lines that together with the x-axis form a container, such that the container contains the most water.

Return the maximum amount of water a container can store.

Notice that you may not slant the container.

Test Results

Case 1

height: [1, 8, 6, 2, 5, 4, 8, 3, 7]

Expected
49

Your Output
none

Case 2

height: [1, 1]

Expected
1

Your Output
none

0012. Integer to Roman

Roman numerals are represented by seven different symbols: I, V, X, L, C, D and M.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two one's added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

- I can be placed before V (5) and X (10) to make 4 and 9.
- X can be placed before L (50) and C (100) to make 40 and 90.
- C can be placed before D (500) and M (1000) to make 400 and 900.

Given an integer, convert it to a roman numeral.

Test Results

Case 1

num: 3

Expected	Your Output
"III"	none

Case 2

num: 58

Expected	Your Output
"LVIII"	none

Case 3

num: 1994

Expected
"MCMXCIV"

Your Output
none

0013. Roman to Integer

Roman numerals are represented by seven different symbols: I, V, X, L, C, D and M.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two one's added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

- I can be placed before V (5) and X (10) to make 4 and 9.
- X can be placed before L (50) and C (100) to make 40 and 90.
- C can be placed before D (500) and M (1000) to make 400 and 900.

Given a roman numeral, convert it to an integer.

Test Results

Case 1

s: "III"

Expected	Your Output
3	none

Case 2

s: "LVIII"

Expected	Your Output
58	none

Case 3

s: "MCMXCIV"

Expected
1994

Your Output
none

0014. Longest Common Prefix

Write a function to find the longest common prefix string amongst an array of strings.

If there is no common prefix, return an empty string "".

Test Results

Case 1

strs: ["flower", "flow", "flight"]

Expected
"fl"

Your Output
none

Case 2

strs: ["dog", "racecar", "car"]

Expected
""

Your Output
none

0015. 3Sum

Given an integer array `nums`, return all the triplets `[nums[i], nums[j], nums[k]]` such that $i \neq j$, $i \neq k$, and $j \neq k$, and $nums[i] + nums[j] + nums[k] == 0$.

Notice that the solution set must not contain duplicate triplets.

Test Results

Case 1

nums: [-1, 0, 1, 2, -1, -4]

Expected	Your Output
<code>[[-1, -1, 2], [-1, 0, 1]]</code>	<code>none</code>

Case 2

nums: [0, 1, 1]

Expected	Your Output
<code>[]</code>	<code>none</code>

Case 3

nums: [0, 0, 0]

Expected	Your Output
<code>[[0, 0, 0]]</code>	<code>none</code>

Case 4

nums: [-10, -7, -4, -1, 2, 5, 8, 11, 14, 17]

Expected	Your Output
<code>[[-10, -7, 17], [-10, -4, 14], [-10, -1, 11], [-10, 2, 8], [-7, -4, 11], [-7, -1, 8], [-7, 2, 5], [-4, -1, 5]]</code>	<code>none</code>

Case 5

nums: [-10, -9, -8, -7, -6, -5, -4, -3, -2, -1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9]

Expected	Your Output
[[[-10, 1, 9], [-10, 2, 8], [-10, 3, 7], [-10, 4, 6], [-9, 0, 9], [-9, 1, 8], [-9, 2, 7], [-9, 3, 6], [-9, 4, 5], [-8, -1, 9], [-8, 0, 8], [-8, 1, 7], [-8, 2, 6], [-8, 3, 5], [-7, -2, 9], [-7, -1, 8], [-7, 0, 7], [-7, 1, 6], [-7, 2, 5], [-7, 3, 4], [-6, -3, 9], [-6, -2, 8], [-6, -1, 7], [-6, 0, 6], [-6, 1, 5], [-6, 2, 4], [-5, -4, 9], [-5, -3, 8], [-5, -2, 7], [-5, -1, 6], [-5, 0, 5], [-5, 1, 4], [-5, 2, 3], [-4, -3, 7], [-4, -2, 6], [-4, -1, 5], [-4, 0, 4], [-4, 1, 3], [-3, -2, 5], [-3, -1, 4], [-3, 0, 3], [-3, 1, 2], [-2, -1, 3], [-2, 0, 2], [-1, 0, 1]]	none

0016. 3Sum Closest

Given an integer array `nums` of length `n` and an integer `target`, find three integers in `nums` such that the sum is closest to `target`.

Return the sum of the three integers.

You may assume that each input would have exactly one solution.

Test Results

Case 1

nums: [-1, 2, 1, -4]

target: 1

Expected
2

Your Output
none

Case 2

nums: [0, 0, 0]

target: 1

Expected
0

Your Output
none

Case 3

nums: [0, 1, 1]

target: 2

Expected
2

Your Output
none

Case 4

nums: [-10, -7, -4, -1, 2, 5, 8, 11, 14, 17]

target: 20

Expected
21

Your Output
none

Case 5

nums: [-10, -9, -8, -7, -6, -5, -4, -3, -2, -1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9]

target: 30

Expected
24

Your Output
none

0017. Letter Combinations of a Phone Number

Given a string containing digits from 2-9 inclusive, return all possible letter combinations that the number could represent. Return the answer in **any order**.

A mapping of digits to letters (just like on the telephone buttons) is given below. Note that 1 does not map to any letters.



Test Results

Case 1

digits: "23"

Expected	Your Output
["ad", "bd", "cd", "ae", "be", "ce", "af", "bf", "cf"]	none

Case 2

digits: ""

Expected	Your Output
[]	none

Case 3

digits: "2"

Expected	Your Output
["a", "b", "c"]	none

0018. 4Sum

Given an array `nums` of `n` integers, return an array of all the unique quadruplets `[nums[a], nums[b], nums[c], nums[d]]` such that:

- $0 \leq a, b, c, d < n$
- `a, b, c, and d` are **distinct**.
- `nums[a] + nums[b] + nums[c] + nums[d] == target`

You may return the answer in **any order**.

Test Results

Case 1

nums: `[1, 0, -1, 0, -2, 2]`

target: `0`

Expected	Your Output
<code>[[-2, -1, 1, 2], [-2, 0, 0, 2], [-1, 0, 0, 1]]</code>	<code>none</code>

Case 2

nums: `[2, 2, 2, 2]`

target: `8`

Expected	Your Output
<code>[[2, 2, 2, 2]]</code>	<code>none</code>

Case 3

nums: `[-5, -4, -3, -2, -1, 0, 1, 2, 3, 4]`

target: `3`

Expected	Your Output
<code>[[-5, 1, 3, 4], [-4, 0, 3, 4], [-4, 1, 2, 4], [-3, -1, 3, 4], [-3, 0, 2, 4], [-3, 1, 2, 3], [-2, -1, 2, 4], [-2, 0, 1, 4], [-2, 0, 2, 3], [-1, 0, 1, 3]]</code>	<code>none</code>

0019. Remove Nth Node From End of List

Given the head of a linked list, remove the nth node from the end of the list and return its head.

Test Results

Case 1

head: 1→2→3→4→5

n: 2

Expected	Your Output
1→2→3→5	none

Case 2

head: 1

n: 1

Expected	Your Output
∅	none

Case 3

head: 1→2

n: 1

Expected	Your Output
1	none

0020. Valid Parentheses

Given a string *s* containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:

1. Open brackets must be closed by the same type of brackets.
 2. Open brackets must be closed in the correct order.
 3. Every close bracket has a corresponding open bracket of the same type.
- *s* consists of parentheses only '()[]{}'.

Test Results

Case 1

s: "()"

Expected
true

Your Output
none

Case 2

s: "()[{}]"

Expected
true

Your Output
none

Case 3

s: "[]"

Expected
false

Your Output
none

Case 4

s: "([)]"

Expected
true

Your Output
none

Case 5

s: "([])"

Expected
false

Your Output
none

0021. Merge Two Sorted Lists

You are given the heads of two sorted linked lists `list1` and `list2`.

Merge the two lists into one sorted list. The list should be made by splicing together the nodes of the first two lists.

Return the head of the merged linked list.

Test Results

Case 1

list1: 1→2→4

list2: 1→3→4

Expected	Your Output
1→1→2→2→3→4→4	none

Case 2

list1: ∅

list2: ∅

Expected	Your Output
∅	none

Case 3

list1: ∅

list2: 0

Expected	Your Output
0	none

0022. Generate Parentheses

Given n pairs of parentheses, write a function to generate all combinations of well-formed parentheses.

Test Results

Case 1

n: 1

Expected	Your Output
["()"]	none

Case 2

n: 3

Expected	Your Output
["((())", "(()())", "()()()", "()(())", "()()()"]	none

0023. Merge k Sorted Lists

You are given an array of k linked-lists `lists`, each linked-list is sorted in ascending order.

Merge all the linked-lists into one sorted linked-list and return it.

Test Results

Case 1

lists: `[1→4→5, 1→3→4, 2→6]`

Expected
<code>1→1→2→3→4→4→5→6</code>

Your Output
<code>none</code>

Case 2

lists: `[]`

Expected
<code>∅</code>

Your Output
<code>none</code>

Case 3

lists: `[∅]`

Expected
<code>∅</code>

Your Output
<code>none</code>

0024. Swap Nodes in Pairs

Given a linked list, swap every two adjacent nodes and return its head. You must solve the problem without modifying the values in the list's nodes (i.e., only nodes themselves may be changed.)

Test Results

Case 1

head: 1→2→3→4

Expected	Your Output
2→1→4→3	none

Case 2

head: ∅

Expected	Your Output
∅	none

Case 3

head: 1

Expected	Your Output
1	none

Case 4

head: 1→2→3

Expected	Your Output
2→1→3	none

0025. N-Queens

The **n-queens** puzzle is the problem of placing n queens on an $n \times n$ chessboard such that no two queens attack each other.

Given an integer n , return *all distinct solutions* to the **n-queens puzzle**. You may return the answer in **any order**.

Each solution contains a distinct board configuration of the n-queens' placement, where 'Q' and '.' both indicate a queen and an empty space, respectively.

Test Results

Case 1

n: 1

Expected	
<table border="1"><tr><td>Q</td></tr></table>	Q
Q	

Your Output
none

Case 2

n: 2

Expected
[]

Your Output
none

Case 3

n: 4

Expected

.	Q	.	.
.	.	.	Q
Q	.	.	.
.	.	Q	.

.	.	Q	.
Q	.	.	.
.	.	.	Q
.	Q	.	.

Your Output
none