

PRO POWER SERIES



PPS4042HCI 4GPM@4200PSI



67DX39G1PUMP

POWERED by

HONDA™ GX390 Engine

Standard Accessories

- ♦ Gun/wand assembly
 - ♦ 25' hose w/ couplers
 - ♦ Chemical injector
 - ♦ 3 color-coded QC spray nozzles
 - ♦ 1 color-coded QC chemical nozzle
- NOTE:** 2700-3300 PSI models include 22mm twist coupler socket hose ends; 4200 PSI models include 22mm twist socket x 3/8" QC plug hose ends.

Available Options

- ♦ Skid Mount – precede model with S/, Example: S/PPS4042LAI.
- ♦ 50' Hose Upgrade – add -50 suffix to model, Example: PPS2533HAI-50

Standard Features

- ♦ Revolutionary aircraft grade aluminum frame with dual handles (no welds to fail)
- ♦ Lifetime frame warranty
- ♦ 50 mesh inlet filter
- ♦ Adjustable pressure unloader
- ♦ Low oil shutdown Kohler, LCT & GX models only
- ♦ Pneumatic tires
- ♦ Dual padded shock absorbing feet
- ♦ 3/4" cold-rolled steel axle
- ♦ Kohler SH, Honda GC Series consumer grade & GX Series commercial grade engines are 50 state approved
- ♦ LCT Maxx Series commercial grade 49 state approved engines – **Not available in CA.**
- ♦ Thermo-sensor (prevents overheating in bypass mode)
- ♦ All models meet or exceed PWMA standards of +/- 10%.

Pressure-Pro®