### **PRO POWER SERIES**



PPS2533KAI

# 2.5GPM@3300PSI



RMV25G30D Pump

#### Standard Accessories

- Gun/wand assembly
- ♦ 25' hose w/ couplers
- Chemical injector
- ♦ 3 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle
  NOTE: 2700-3300 PSI models include
  22mm twist coupler socket hose ends;
  4200 PSI models include 22mm twist
  socket x 3/8" QC plug hose ends.

#### Available Options

- Skid Mount precede model with S/, Example: S/PPS4042LAI.
- 50' Hose Upgrade − add -50 suffix to model, Example: PPS2533HAI-50
- AVAILABLE OPTION-SH265, GC190, & GX200:ENGINE MODELS ONLY: UPS-Shipping Carton: No Extra Charge Includes: Specially designed protective carton and contractor grade two piece gun-wand assembly. Order standard model and add UPS suffix after model. Example: PPS2533HAI-UPS

## **KOHLER**. SH265 Engine

#### Standard Features

- Revolutionary aircraft grade aluminum frame with dual handles (no welds to fail)
- Lifetime frame warranty
- 50 mesh inlet filter
- Adjustable pressure unloader
- Low oil shutdown Kohler, LCT & GX models only
- Pneumatic tires
- Dual padded shock absorbing feet
- 3/4" cold-rolled steel axle
- Kohler SH, Honda GC Series consumer grade & GX Series commercial grade engines are 50 state approved
- LCT Maxx Series commercial grade 49 state approved engines – Not available in CA.
- Thermo-sensor (prevents overheating in bypass mode)
- ◆ All models meet or exceed PWMA standards of +/- 10%.