

# POST请求报文（给服务器看的） -- 通过form 表单发送的POST请求

```
POST http://localhost:3000/ HTTP/1.1
Host: localhost:3000
Connection: keep-alive
Content-Length: 22
Pragma: no-cache
Cache-Control: no-cache
Origin: http://localhost:63347
Upgrade-Insecure-Requests: 1
DNT: 1
Content-Type: application/x-www-form-urlencoded
User-Agent: Mozilla/5.0 (Windows NT 10.0; win64; x64) AppleWebKit/537.36 (KHTML,
like Gecko) Chrome/73.0.3683.75 Safari/537.36
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,image/apng,*/*;
q=0.8,application/signed-exchange;v=b3
Referer:
http://localhost:63347/0719_node/day04/5.http%E6%8A%A5%E6%96%87%E7%8A%B6%E6%80%
81%E7%A0%81/%E6%BC%94%E7%A4%BA%E9%98%B2%E7%9B%97%E9%93%BE.html?
_ijt=v73gogoe0uaatcie38ma6l7gso
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9,en-US;q=0.8,en;q=0.7
Cookie: webstorm-9af2238=09820128-3adb-43e4-8242-a6f65c9e523a
空行
name=kobe&password=123
```

## 请求报文首行

```
POST http://localhost:3000/ HTTP/1.1
```

## 请求报文头

```
Host: localhost:3000
Connection: keep-alive
【Content-Length: 22】
-- 发送数据的长度
Pragma: no-cache
Cache-Control: no-cache
【Origin: http://localhost:63347】
-- 精简版的Referer 1.防盗链。 2.广告计费
Upgrade-Insecure-Requests: 1
DNT: 1
【Content-Type: application/x-www-form-urlencoded】
--浏览器告诉服务器，发送数据的类型
User-Agent: Mozilla/5.0 (Windows NT 10.0; win64; x64) AppleWebKit/537.36 (KHTML,
like Gecko) Chrome/73.0.3683.75 Safari/537.36
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,image/apng,*/*;
q=0.8,
```

```
application/signed-exchange;v=b3
Referer: http://localhost:63347/0719_node/demo.html?
_ijt=r08g7l67qsmghv05cf7mphidka
-- “站”在哪里发出去的请求(源站) 1.防盗链。 2.广告计费
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9,en-US;q=0.8,en;q=0.7
Cookie: webstorm-9af2238=09820128-3adb-43e4-8242-a6f65c9e523a
```

## 空行

空行

## 请求报文体

name=kobe&password=123

## 备注：

- 1.form表单的 post请求和get请求 参数均以urlencoded形式进行编码
- 2.get请求将urlencoded编码的参数放入请求地址携带给服务器，所以称之为：查询字符串参数。
- 3.post请求将urlencoded编码的参数放入请求体，所以称之为：请求体参数。