

COPING COVER X 10'-0" LENGTH FINISH PER SPECIFICATIO			6" WIDE SPLICE PLATE AT EACH JOINT	_ V	8GA. ANCHO VITH SPRING NCHOR CHA	CLIP AND IR
"B"	FASTENERS		"A"			"C"
"A" DIMENSION :	3" DIMENS	SION:	"C" DIME	"C" DIMENSION:"		
ACTUAL WALL WIDTH	UTSIDE LE 5" STANDA	G RD - 6.5" MAXIMUM	_	INSIDE LEG 4" STANDARD - 6" MAXIMUM		
LINEAR FEET: OUTSIDE M		MITERS:	INSIDE MITERS:	END CAPS:	EXTEND	ER:Ift
		° TABBED	@ 90° TABBED		LATEIND	10'-0" LENGTHS
			WELDED OPTION	LEFT:	FACE SIZ	FACE SIZE:"
NOTES:						
ALUMINUM:	GALVA	GALVANIZED STEEL:		COPPER: ZINC:		
.040" ☐ Kynar® Color:	_ 24GA [24GA Kynar® Color:		.8mm		
.050" ☐ Kynar® Color:	Kynar® (20oz □ 1.0mm □		
.063" ☐ Kynar® Color:	_		Finish Opti	Finish Options:		

NOTES:

- CONCEALED SPLICE PLATES ARE PROVIDED TO INSTALL EVERY 10FT SECTION.
- UNLESS NOTED, STANDARD MITERS ARE FABRICATED AS A CUT+TAB, FIELD ASSEMBLED SYSTEM.
- WELDED MITERS AVAILABLE UPON REQUEST.

Contractor:	
Job Name:	
Signature:	

76-11 88th Street Glendale, NY 11385 [P] 718-846-0400 [F] 718-846-7803

[F] 718-846-7803 [E] info@litsco.com Lock-Tight Coping
ANSI/SPRI ES-1 coping system for Snap-On
installation

