GARD-N-EDGE

HEAVY DUTY GREEN ROOF EDGE RETENTION

OVERVIEW:

LITSCO's Gard-N-Edge is the ideal solution for garden roof projects where transition and soil retention is needed between the vegetation and hardscapes such as conventional roofing systems or pavers.

MATERIALS: *Actual colors may vary from this representation

KYNAR PAINTED ALUMINUM (AL) .063" / .080" / .125"

2 Coat Kynar Finish is Standard. A full list of all standard, premium colors, 3 coat, and custom colors is available upon request. Finish warranties of 20 years available. *Finish per specification

^{*}Popular colors are listed. Additional colors are available, see color charts.

SANDSTONE SR	DARK BRONZE	MATTE BLACK
BONE WHITE SR	SILVER METALLIC	CHARCOAL
COPPER (CP) 20 OZ		
COLD RED ROLLED 20 OZ	FREEDOM GRAY 20 OZ	

STAINLESS STEEL (SS) 22 GA / 20 GA

*Finish per specification

RHEINZINK-PATINA ZINC 1.0 MM





GRAPHITE-GRAY

FEATURES:

Fabricated in 10ft lengths with:

- Integrated Splice Plate means No additional pieces, Improves installation times.
- · Cut-Tab Corners allow for minor adjustments at corners. Just set and rivet to keep in place
- · Custom miters and profiles available.
- Drainage Outlets 3/8" wide x 1" high, spaced 1" O.C. to provide maximum drainage beneath the vegetative roof system.
- Height of slots accounts for the thickness of most drainage mats.

INSTALLATION:

EDGE RESTRAINT

Edge restraint is loosely laid on top of roofing system as specified and held in place by the weight of the growing media placed over it. Do not mechanically attach through roof system.

► STANDARD SIZES:

VERTICAL: HORIZONTAL:

5.5" 3" 7" 4" 8" 5.5"

Integrated Splice Plate

3/8" x 1" slotted holes at 1" o.c.

Gard-N-Edge per specifications

