

	FASCIA CO	OVER, 10'-0'	LENGTHS.	FINISH PER SPE	-CIFICATIO	NS		
			ESSION CLIP					
	6" L		EVERY 24" O. D IN SINGLE F	C. 2-1/2" ABO <sup>1</sup> PLY ROOF	VE ROOF LII	NE		
		FLASHING	S OVED SEALI	NG MASTIC				
-						ROOF MEMB		
"A"								
						++	+	
						$\perp$	$\blacksquare$	
			<del>\</del>				$\pm$	
			1					
			1			++	+	
4" WIDE CONCEALED SPLICE								
PLATE — .032" ALUMINUM	\	\	\	-1-1/4" GALVAN FASTEN 12" O		NAILS	3	
SPRING WATER DAM 24GA GALVANIZED STEEL	'		1" HEX WOOI 12" O.C.	O SCREWS				
STANDARD FACE SIZE: "A"								
PLYTIGHT 6-3/4" □		PLY	TIGHT 9"					
LINEAR FEET: OUTS	OUTSIDE MITERS: INSIDE		MITERS: END CAPS:		EXTENDER:			lft
10'-0" LENGTHS	@ 90°		. @ 90° RIGHT: LEFT:		10'-0" LENGTHS			
NOTES:			FACE SIZE:"					
ALUMINUM:  .040"	GALVANIZED STEEL		COPPER:	.018" (26ga	SS STEEL:		ZINC: BMM	
.050" or Baked Enamel  Kynar® Color		<u> </u>	20oz 🗆	24ga			.0MM	
See E Saked Ename.			Finish Optio				.0111111	<u> </u>
NOTES:			•					
CONCEALED SPLICE PLATES ARE PROV     INCLUDES ANCHOR CLEAT/WATER DAM	IDED TO INSTALL EVI	ERY 10FT SE	CTION.					
Contractor:								
Job Name:								
Signature:								

76-11 88th Street Glendale, NY 11385 [P] 718-846-0400 [F] 718-846-7803 [E] info@litsco.com Ply-Tight Fascia
FM rated fascia system for single ply roof systems

