

STREAMLINE® FLUSHWALL-TG

CONCEALED FASTENER, LAP SEAM METAL PANEL

OVERVIEW:

LITSCO's Flush TG panel is an ideal solution for exterior walls, parapets or soffits. The interlocking Tongue-n-Groove installation is fast and hides the fasteners making the 11" wide profile a clean, consistent appearance.

► MATERIALS: **Actual colors may vary from this representation*

KYNAR PAINTED ALUMINUM (AL) .040" & .050" OR GALVANIZED (GL) 24 GA & 22 GA

2 Coat Kynar Finish is Standard. A full list of all standard, premium colors, 3 coat, and custom colors is available upon request. Finish warranties of 20 years available.

**Popular colors are listed. Additional colors are available, see color charts.*

ALMOND SR
032/040/050 ALUMINUM
24 GA GALVANIZED

SANDSTONE SR
032/040/050 ALUMINUM
24 GA GALVANIZED

MATTE BLACK
032/040/050 ALUMINUM
24 GA GALVANIZED

BONE WHITE SR
032/040/050 ALUMINUM
24 GA GALVANIZED

SILVER METALLIC
040 ALUMINUM
24 GA GALVANIZED

SLATE GRAY
032/040/050 ALUMINUM
24 GA GALVANIZED

COPPER (CP)
20 OZ

RED ROLLED

FREEDOM GRAY

AURUBIS NORDIC PATINA

STAINLESS STEEL (SS)
24 GA

RHEINZINK-PATINA ZINC (ZN)
0.8 MM & 1.0 MM

BLUE-GRAY

GRAPHITE-GRAY

► TYPICAL STANDARD PANEL SIZE GUIDE:

KEY

STANDARD FLAT

V-REVEAL

AL, GL, CP, SS

11-1/4"

11"

ZN (0.8mm)

8-1/4"

8"

ZN (1.0mm)

14-7/8"

14-5/8"

► FEATURES:

8ft & 10ft lengths with the Baked Enamel Dark Bronze paint for immediate pickup or delivery. Custom lengths can be cut to order.

► INSTALLATION:

TRIM:

All flashing and trim will be fabricated by LITSCO or a qualified fabricator. Flashing shall be .032"-.040" aluminum or 24 GA steel.

SUBGIRTS:

Streamline Flush TG panels are intended to be installed directly onto 18 GA (1/2") deep galvanized steel subgirts. Maximum spacing is 30" O.C.

FASTENERS:

#12 pancake Phillips head, self-drilling stainless steel fastener. Fasteners to be installed 12" O.C.

**Always follow manufacturer's guidelines for proper storage and handling prior to install.*

