

					REWILL
COPING COVER X 10'-0" LENGTHS. FINISH PER SPECIFICATION.		6" WIDE SPLICE PLATE AT EACH JOINT	_ W	33" ALUMINUM ANCHOR P ITH SUPPORT CHAIR ND SPRING CLIP	LATE
A [$\overline{}$				1/2"
"B"		"A"		3/	"C"
"A" DIMENSION :" "B"	DIMENS	SION:	"C" DIMEI	NSION:	"
ACTUAL WALL WIDTH OUTSIDE LEG 4.5" STANDAR		G RD - 6.5" MAXIMUM	INSIDE LEG 4" STANDARD - 6" MAXIMUM		М
LINEAR FEET: OUTSIDE M	ITERS:	INSIDE MITERS:	END CAPS:	EXTENDER:	lft
10'-0" LENGTHS @ 90°	TABBED	@ 90° TABBED	RIGHT:)'-0" LENGTHS
WELDED OP		WELDED OPTION	LEFT:	FACE SIZE:	"
NOTES:					
ALUMINUM:	GALVA	GALVANIZED STEEL:		: ZINC:	
.040" Kynar® Color:	24GA □		16oz 🗆	16oz □ .8mm □	
050°□ Kynar® Color:	Kynar [®] Color:		2007 □	20oz 🗆 1 0mm 🗖	

.040" ☐ Kynar® Color: 24GA ☐ 16oz ☐ .8mm ☐	
	m 🔲
.050" Kynar® Color: Kynar® Color: 20oz 1.0mm	nm 🗆
.063" Kynar® Color: Finish Options:	

NOTES:

- CONCEALED SPLICE PLATES ARE PROVIDED TO INSTALL EVERY 10FT SECTION.
- UNLESS NOTED, STANDARD MITERS ARE FABRICATED AS A CUT+TAB, FIELD ASSEMBLED SYSTEM.
- WELDED MITERS AVAILABLE UPON REQUEST.

Contractor:	
Job Name:	
Signature:	

76-11 88th Street Glendale, NY 11385 [P] 718-846-0400

[F] 718-846-7803

[E] info@litsco.com

Lock-Tight Coping ANSI/SPRI ES-1 coping system for Snap-On installation

