



	l						
STANDARD FACE SIZE: "A	"						
FLASHDOWN 4-3/4" ☐ FLASHDOWN 4-3/4"		FLASHDOWN 6-3/4" □		FLASHDOWN 9" □			
LINEAR FEET:	OUTSIDE MI	TERS:	INSIDE MITERS:	END CAPS:	EXTENDER:	Ift	
10'-0" LENGTHS	@ 90	0°	@ 90°	RIGHT:	10'-0" LENGTHS		
				LEFT:	FACE SIZE:	"	
NOTES:							
A L L IN ALN II IN A	0.413.74	NUZED OTEEL	000000	OTAIN!! 500 03			
ALUMINUM:		GALVANIZED STEEL:		COPPER:	STAINLESS ST	EEL:	
.040" Kynar® Color:		Kynar® Color: 20		16oz 🔲	.018" (26ga) 🔲		
.050" ☐ Kynar® Color:				20oz 🗆	24ga □		
				Finish Options	sh Options:		
NOTES:							
CONCEALED SPLICE PLATES ARE PROVIDED TO INSTALL EVERY 10FT SECTION.							

- INCLUDES ANCHOR CLEAT/WATER DAM

Contractor:	
Job Name:	
Signature:	

76-11 88th Street Glendale, NY 11385 [P] 718-846-0400 [F] 718-846-7803

[E] info@litsco.com

Flashdown Fascia FM rated fascia system for single ply and modified roof systems

