



Statistical Machine Translation

Part I: Khalil Sima'an
Data and Models
Universiteit van Amsterdam

Part II: Trevor Cohn
Decoding and efficiency
University of Sheffield

Statistical Machine Translation: PART I

Dr. Khalil Sima'an
Statistical Language Processing and Learning
Institute for Logic, Language and Computation
Universiteit van Amsterdam

Some slides use figures from Philipp Koehn, Barry Haddow and Sophie Arnoult

Data and Models: Structure of lecture

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

- General statistical framework
- Word-based models: word alignments
- Phrase-based models: phrase-alignments
- Tree-based models: tree-alignments

Statistical Approach: Parallel Corpora

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Task: Translate a source sentence **f** to a target sentence **e**.
Data: Parallel corpus (source-target sentence pairs).



Source-Channel Approach: IBM Models (1990's)

Parallel Corpus Example

Parallel corpus **C** = a collection of text-chunks and their translations.

Parallel corpora are the by-product of *human translation*.
Every source chunk is paired with a target chunk.

Dutch	English
De prijs van het huis is gestegen.	The price of the house has risen.
Het huis kan worden verkocht.	The house can be sold.
Als het de marktprijs daalt zullen sommige gezinnen een zware tijd doormaken.	If the market price goes down, some families will go through difficult times.
.	.
.	.
.	.
.	.
.	.
.	.

- Hansards Canadian Parliament Proc. (English-French).
- European Parliament Proc. (23 languages).
- United Nations documents.
- Newspapers: Chinese-English; Arabic-English; Urdu-English.
- TAUS corpora.

Generative Source-Channel Framework

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Given source sentence \mathbf{f} , select target sentence \mathbf{e}

$$\arg \max_{\mathbf{e} \in E(\mathbf{f})} \{ P(\mathbf{e} | \mathbf{f}) \} = \arg \max_{\mathbf{e} \in E(\mathbf{f})} \{ \overbrace{P(\mathbf{e})}^{L.M.} \times \overbrace{P(\mathbf{f} | \mathbf{e})}^{T.M.} \}$$

Set $E(\mathbf{f})$ is the set of hypothesized translations of \mathbf{f} .

$P(\mathbf{f} | \mathbf{e})$: accounts for divergence in ...

- word order
- morphology
- syntactic relations
- idiomatic ways of expression
- :

How to estimate $P(\mathbf{e} | \mathbf{f})$? **Sparse-data problem!**

Inducing The Structure of Translation Data

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

e = Mary did not slap the green witch .


? ? ? ?

f = Maria no dio una bofetada a la bruja verde .



The latent structure of translation equivalence

Graphical representations Δ_f and Δ_e for **f** and **e**
Relation **a** between Δ_f and Δ_e



$$\arg \max_{\mathbf{e} \in E(\mathbf{f})} \{ P(\mathbf{e} \mid \mathbf{f}) \} =$$

$$\arg \max_{\mathbf{e} \in E(\mathbf{f})} \{ \sum_{\langle \Delta_f, \mathbf{a}, \Delta_e \rangle} P(\mathbf{e}, \Delta_f, \Delta_e, \mathbf{a} \mid \mathbf{f}) \}$$

The difficult question: Which $\Delta_{f/e}$ and **a** fit data best?

Structure in current models

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

$$\Delta_f \xrightarrow{a} \Delta_e$$

In most current models structure of **reordering**:

- $\Delta_{f/e}$ are structures over word positions.
- **a** is an **alignment** between groups of word positions in Δ_f and Δ_e .

Challenge: Number of permutations of n words is **$n!$**

Structure shows translation units **composing** together

- What are the atomic translation units?
- How these compose together **efficiently**?
- How to put probs. on these structures?

Structure helps combat sparsity and complexity

Structure in Existing Models: Sketch

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models


Alignment
Symmetriza-
tion

Phrase-Based
Models


Limitations of
PB Models

Syntax


Word-based



Phrase-based



Tree-based



Problem: No sufficient stats to estimate $P(\mathbf{e} \mid \mathbf{f})$ from data

Word-Based Models: Word Alignments

Some History and References

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Statistical models with word-alignments:

- Brown, Cocke, Della Pietra, Della Pietra, Jelinek, Lafferty, Mercer and Roossin. A statistical approach to machine translation. Computational Linguistics, 1990.
- Brown, Della Pietra, Della Pietra and Mercer. The mathematics of statistical machine translation: parameter estimation., Computational Linguistics, 1993.
- Och and Ney: A Systematic Comparison of Various Statistical Alignment Models. Computational Linguistics, 2003.

Word-Based Models and Word-Alignment

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models


Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

a is a mapping between word positions.



- Δ_f and Δ_e are sequences of word positions.

$$\mathbf{e} = \mathbf{e}_1^l = e_1 \dots e_l \text{ and } \mathbf{f} = \mathbf{f}_1^m = f_1 \dots f_m$$

- A hidden word-alignment **a**:

$$P(\mathbf{f} \mid \mathbf{e}) = \sum_{\mathbf{a}} P(\mathbf{a}, \mathbf{f} \mid \mathbf{e})$$

- Assume that a target word-position e_i translates into zero or more source word-positions

$$\mathbf{a} : \{pos_f\} \rightarrow (\{pos_e\} \cup \{0\})$$

- \mathbf{a}_i or $\mathbf{a}(i)$, i.e., word position in **e** with which \mathbf{f}_i is aligned.

Word Alignment Example

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



Word Alignment Example

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



Word Alignment Example: Not covered in this setting

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax




Word Alignment Matrix Example

Tutorial to Statistical Machine Translation

Dr Khalil
Sima'an

Word-Based Models

Limitations of PB Models



Translation model with word alignment

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

$$\arg \max_{\mathbf{e}} P(\mathbf{e} | \mathbf{f}) = \arg \max_{\mathbf{e}} P(\mathbf{e}) \times P(\mathbf{f} | \mathbf{e})$$

$$P(\mathbf{f} | \mathbf{e}) = \sum_{\mathbf{a}} P(\mathbf{a}, \mathbf{f} | \mathbf{e}) = \sum_{\mathbf{a}} P(\mathbf{a} | \mathbf{e}) \times P(\mathbf{f} | \mathbf{a}, \mathbf{e})$$

Questions

- How to parametrize the model?
How are \mathbf{e} , \mathbf{f} and \mathbf{a} composed from basic units?
- How to train the model?
How to acquire word alignment?
- How to translate with this model?
Decoding and computational issues (for second part)

Word-Alignment As Hidden Structure

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



We need to decompose

- The alignment \mathbf{a} and the length m : $P(\mathbf{a} \mid \mathbf{e})$
- "Translation dictionary" $P(\mathbf{f} \mid \mathbf{e}, \mathbf{a})$

Word Alignment Models: General Scheme

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Alignment of positions in **f** with positions in **e**:

$$\mathbf{a} = a_1^m = a_1 \dots a_m$$

Markov process over **a**

$$P(a_1^m, f_1^m \mid e_1^l) = P(m \mid \mathbf{e}) \times \prod_{j=1}^m P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) \times P(f_j \mid a_1^j, f_1^{j-1}, m, \mathbf{e})$$

In words: to generate alignment **a** and foreign sentence **f**

- 1 Choose a length m for **f**
- 2 Generate alignment a_j given the preceding alignments, words in **f**, m , and **e**
- 3 Generate word f_j conditioned on structure so far and **e**.

IBM models are obtained by simplifications of this formula.

IBM Model I

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

$$P(a_1^m, f_1^m \mid e_1 \dots e_l) = P(m \mid \mathbf{e}) \times \prod_{j=1}^m P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) \times P(f_j \mid a_1^j, f_1^{j-1}, m, \mathbf{e})$$

IBM Model I:

Length: $P(m \mid \mathbf{e}) \approx P(m \mid l) \approx \epsilon$ A **fixed** probability ϵ .

Align with **uniform** probability j with any a_j in \mathbf{e}_1^l or

NULL: $P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) \approx (l+1)^{-1}$

Note that a_j can be linked with l positions in \mathbf{e} or with NULL.

Lexicon: lexicon parameters $\pi_t(f \mid e)$

$$P(f_j \mid a_1^j, f_1^{j-1}, m, \mathbf{e}) \approx P(f_j \mid e_{a_j}) = \pi_t(f_j \mid e_{a_j})$$

Parameters: ϵ and $\{\pi_t(f \mid e) \mid \langle f, e \rangle \in \mathbf{C}\}$.

Sketch IBM Model I

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



IBM Model I Parameters and Data Likelihood

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Data Likelihood:

$$\begin{aligned} P(\mathbf{f} | \mathbf{e}) &= \sum_{a_1^m} P(a_1^m, f_1^m | \mathbf{e}_1 \dots \mathbf{e}_l) \\ &= \frac{\epsilon}{(I+1)^m} \times \sum_{a_1=0}^I \dots \sum_{a_m=0}^I \prod_{j=1}^m \pi_t(f_j | \mathbf{e}_{a_j}) \end{aligned}$$

Parameters: ϵ and $\{\pi_t(f | \mathbf{e}) \mid \langle f, \mathbf{e} \rangle \in \mathbf{C}\}$.

Fix ϵ , i.e., in practice put a uniform probability over a range $[1..m]$, for some natural number m .

Dilemma

To estimate these parameters we need word-alignment
To get word-alignment we need these parameters.

IBM Model II

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Extends IBM Model I at alignment probs:

$$P(a_1^m, f_1^m \mid e_1 \dots e_l) \approx \epsilon \times \prod_{j=1}^m \frac{P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) \times \pi_t(f_j \mid e_{a_j})}{P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e})}$$

IBM Model II: changes only one element in IBM Model I:

- IBM Model I does not take into account the position of words in both strings

$$P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) = P(a_j \mid j, l, m) := \pi_A(a_j \mid j, l, m)$$

Where $\pi_A(.|.)$ are parameters to be learned from data.

IBM Models III, IV and V concentrate on more complex alignments allowing, e.g., 1 – to – n (fertility)

IBM Model II Parameters

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

$$P(a_1^m, f_1^m \mid e_1 \dots e_l) \approx \epsilon \times \prod_{j=1}^m \pi_A(a_j \mid j, l, m) \times \pi_t(f_j \mid e_{a_j})$$

Parameters: $\{\pi_A(a_j \mid j, l, m)\}$ and $\{\pi_t(f_j \mid e_{a_j})\}$

Dilemma

To estimate these parameters we need word-alignment
To get word-alignment we need these parameters.

Estimating Model Parameters

Maximum-Likelihood Estimation of model M on parallel corpus \mathbf{C}

$$\arg \max_{m \in M} P(\mathbf{C} | m) = \arg \max_{m \in M} \prod_{\langle \mathbf{e}, \mathbf{f} \rangle \in \mathbf{C}} P_m(\mathbf{e} | \mathbf{f})$$

Example IBM Model I:

- Model M is defined by model parameters.
- Data is incomplete: no closed form solution.
- Expectation-Maximization (EM) sketch

Init: Set the parameters at some m_0 and let $i = 0$

Repeat until convergence (in perplexity)

$EM_i(\mathbf{C}) = \mathbf{C}$ completed using estimate m_i

$EM_i(\mathbf{C})$ contains m_i -expectations over $\langle \mathbf{e}, \mathbf{f}, \mathbf{a} \rangle$: $P(\mathbf{a} | \mathbf{f}, \mathbf{e})$

m_{i+1} = Relative Frequency Estimates from $EM_i(\mathbf{C})$.

EM for Lexicon and Word Alignment Probs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



EM for Lexicon and Word Alignment Probs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



EM for Lexicon and Word Alignment Probs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



EM for Lexicon and Word Alignment Probs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models


Syntax

... la maison ... la maison bleu ... la fleur ...
... the house ... the blue house ... the flower ...

Translation Using EM Estimates

- Lexicon probability estimates: $\{\hat{\pi}_t(f_j | e_{a_j})\}$
- Alignment probabilities: $\{\hat{\pi}_A(a_j | j, m, l)\}$
- Translation Model + Language Model + Decoder

$$\arg \max_{\mathbf{e}} P(\mathbf{e} | \mathbf{f}) = \arg \max_{\mathbf{e}} P(\mathbf{e}) \times \sum_{\mathbf{a}} P(\mathbf{a}, \mathbf{f} | \mathbf{e})$$



Viterbi Word-Alignment using EM estimates

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

After EM has stabilized on estimates

$$\{\hat{\pi}_t(f_j \mid e_{a_j})\} \quad \text{and} \quad \{\hat{\pi}_A(a_j \mid j, m, l)\}$$

For every $\langle \mathbf{f}, \mathbf{e} \rangle$ in \mathbf{C} apply the following

$$\arg \max_{a_1^m} P(a_1^m, f_1^m \mid e_1 \dots e_l) \approx$$
$$\arg \max_{a_1^m} \epsilon \times \prod_{j=1}^m \hat{\pi}_A(a_j \mid j, m, l) \times \hat{\pi}_t(f_j \mid e_{a_j})$$

HMM Alignment Model: General Form

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax


$$P(a_1^m, f_1^m \mid e_1 \dots e_l) \approx \epsilon \times \prod_{j=1}^m \frac{P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) \times \pi_t(f_j \mid e_{a_j})}{1}$$

- Words do not move independently of each other:
condition word movement on previous word movement

$$P(a_j \mid a_1^{j-1}, f_1^{j-1}, m, \mathbf{e}) \approx P(a_j \mid a_{j-1}, m)$$

IBM Model III (and IV): Example

- A hidden word-alignment \mathbf{a} : $P(\mathbf{f} | \mathbf{e}) = \sum_{\mathbf{a}} P(\mathbf{a}, \mathbf{f} | \mathbf{e})$



Estimate alignment + lexicon + reordering + fertility parameters.

Word-based Models (Och & Ney 2003)

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Table 1

Overview of the alignment models.

Model	Alignment model	Fertility model	E-step	Deficient
Model 1	uniform	no	exact	no
Model 2	zero-order	no	exact	no
HMM	first-order	no	exact	no
Model 3	zero-order	yes	approximative	yes
Model 4	first-order	yes	approximative	yes
Model 5	first-order	yes	approximative	no
Model 6	first-order	yes	approximative	yes

Word-Alignment As Hidden Structure: Sufficient?

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



We assumed alignment between words and dictionary:

- Alignment \mathbf{a} and the length m : $P(\mathbf{a} \mid \mathbf{e})$
- Dictionary $P(\mathbf{f} \mid \mathbf{e}, \mathbf{a})$

Limitations of Word-based Models

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Limitations of word-based translation:

- Many-to-one and many-to-many is common:
“Makes more difficult”/bemoeilijkt “Dat richtte (hen)
ten gronde”/”That destroyed (them)”
- Reordering takes place (often) by whole blocks.
Reordering individual words increases *ambiguity*.
“The (big heavy) cow/la vaca (pesada grande)”
- Translation works by “fixed expressions” (idiomatic).
Concatenating word-translations increases *ambiguity*.

Estimates of $P(\mathbf{f} \mid \mathbf{e})$ by word-based models are inaccurate.

Instead of words as basic events: multi-word events in
corpus.

Obtaining Symmetrized Word Alignments

Asymmetric Alignments: Limitations

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

- Word-based models presented so far are based on asymmetric word alignment.
Each position i in **f** is aligned with at most one position in **e**: \mathbf{a}_i
- What about such word alignments?




- Or when a word in **f** translated into two or more in **e**?

Symmetrization Heuristics

Obtain $A_{f \rightarrow e}$ and $A_{e \rightarrow f}$


From Intersection $A_{f \rightarrow e} \cap A_{e \rightarrow f}$ to Union $A_{f \rightarrow e} \cup A_{e \rightarrow f}$



Symmetrization Heursitics Algorithm

Obtain $A_{f \rightarrow e}$ and $A_{e \rightarrow f}$

From Intersection $A_{f \rightarrow e} \cap A_{e \rightarrow f}$ to Union $A_{f \rightarrow e} \cup A_{e \rightarrow f}$



- from intersection $A = A_{f \rightarrow e} \cap A_{f \rightarrow e}$ to union $A_{f \rightarrow e} \cup A_{f \rightarrow e}$
- step 1 (diagonal): add neighbouring points (f, e) in union
s.t. $\nexists (f, e') \in A$ or $\nexists (f', e) \in A$
- step 2 (finalize): add remaining points in union
s.t. $\nexists (f, e') \in A$ and $\nexists (f', e) \in A$

Phrase-based Models: Alignment between Phrases

Statistical “Memory-based” Translation

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

*Store arbitrary length source-target translation units
from training parallel corpus.*

*Translate new input by “covering” it with translation
units **replayed** from memory.*

Idiomatic = Tiling: Phrase-Based SMT

- Assume word-alignment **a** is given in parallel corpus.
- Phrase-pair = contiguous source-target $\langle n, m \rangle$ -grams that are *translational equivalents* under **a**.
- Estimate phrase-pair probabilities $\Theta(\bar{f}_i \mid \bar{e}_i)$
- Translate **f** by “tiling it with phrases with order permutation”

PBSMT some references

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models


Syntax

- Alignment-template Approach to Stat. Machine Translation (RWTH Aachen 1999)
- Phrase-based statistical machine translation (Zens, Och and Ney 2002)
- Phrase based SMT (Koehn, Och and Marcu 2003)
- Joint Phrase-based SMT (Wang and Marcu 2005)
- Statistical Machine Translation. (Ph. Koehn, Cambridge University Press 2010)

Relation to EBMT 1984; Data-Oriented Translation (2000).

Phrase-Based Models: Conceptual

Segment foreign sentence **f**
into l phrases \bar{f}_1^l



$$\arg \max_{\mathbf{e}} P(\mathbf{e} \mid \mathbf{f}) = \arg \max_{\mathbf{e}} P(\mathbf{e}) \times P(\mathbf{f} \mid \mathbf{e})$$

$$P(\mathbf{f} \mid \mathbf{e}) = \sum_{\langle \bar{f}_1^l, \bar{e}_1^l \rangle} P(\bar{f}_1^l, \bar{e}_1^l \mid \mathbf{e}) \prod_{i=1}^l P(\bar{f}_i \mid \bar{e}_i) \times d(\text{start}_i - \text{end}_{i-1} - 1)$$

$$\arg \max_{\mathbf{e}} P(\mathbf{f} \mid \mathbf{e}) \approx \arg \max_{\langle \bar{f}_1^l, \bar{e}_1^l \rangle} \overbrace{\prod_{i=1}^l \Theta(\bar{f}_i \mid \bar{e}_i)}^{\text{ph. table}} \times \overbrace{d(\text{start}_i - \text{end}_{i-1} - 1)}^{\text{Dist. reord.}}$$

$\text{start}_i/\text{end}_i$ are positions of first/last words of \bar{f}_i (translating to \bar{e}_i).

$d(x) = \alpha^x$ exponentially decaying in words skipped ($\alpha \in (0, 1]$).

Phrase-Based Models: Linear-interpolation

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models


Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Segment foreign sentence \mathbf{f}
into I phrases \bar{f}_1^I



Log-linear interpolation of factors:

$$\text{score}(\mathbf{e}|\mathbf{f}) = \sum_{\mathbf{f} \in F} \lambda_{\mathbf{f}} \times \log H_{\mathbf{f}}(\mathbf{e}, \mathbf{f})$$

Where set F consists of:

- Bag of phrases translation = $\prod_{i=1}^I \Theta(\bar{f}_i | \bar{e}_i)$
- d()** Phrases reordered with reordering model $d(\cdot)$
- lm** Language model (5-grams or even 7-grams).
- other** Smoothing + length penalty terms.

Topics to discuss

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

- Phrase table extraction
- Estimating $\{\Theta(\bar{f}_i \mid \bar{e}_i)\}$ and $\{\Theta(\bar{e}_i \mid \bar{f}_i)\}$
- Lexicalized and hierarchical phrase reordering models
- Other: phrase, length penalty ...
- Log-linear interpolation and minimum error-rate training
- Decoding and optimization

Extracting phrase pairs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

A phrase pair $\langle \bar{f}, \bar{e} \rangle$ is **consistent** with alignment \mathbf{a} iff

- Non-empty: at least one alignment pair from \mathbf{a} is in $\langle \bar{f}, \bar{e} \rangle$
- No foreign positions inside $\langle \bar{f}, \bar{e} \rangle$ aligned to positions outside it
- No english positions inside $\langle \bar{f}, \bar{e} \rangle$ aligned to positions outside it

Extracting phrase pairs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

					bofetada		bruja	
	Maria	no	daba	una	a	la	verde	
Mary								
did								
not								
slap								
the								
green								
witch								

Extracting phrase pairs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Word Alignment Induced Phrases (2)

	Maria no daba una				bofetada		a la		bruja		verde
Mary	■										
did		■									
not		■									
slap			■	■	■	■					
the							■	■			
green											■
witch									■		

(Maria, Mary), (no, did not), (slap, daba una bofetada), (a la, the), (bruja, witch),
(verde, green)

Extracting phrase pairs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Word Alignment Induced Phrases (3)

	Maria	no	daba	una	bofetada	a	la	bruja	verde
Mary	■	■							
did	■	■	■	■					
not		■	■						
slap			■	■	■	■			
the				■	■	■	■		
green								■	■
witch								■	■

(Maria, Mary), (no, did not), (slap, daba una bofetada), (a la, the), (bruja, witch),
(verde, green), (Maria no, Mary did not), (no daba una bofetada, did not slap),
(daba una bofetada a la, slap the), (bruja verde, green witch)

Extracting phrases from permutations

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an







Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



Phrase pair weights

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Extract phrase pairs from corpus into multiset

$$Tab = \{ \langle \bar{f}, \bar{e} \rangle, freq(\bar{f}, \bar{e}) \}$$

Weights for $\langle \bar{f}, \bar{e} \rangle$

$$\blacksquare \Theta(\bar{f} | \bar{e}) = \frac{freq(\bar{f}, \bar{e})}{\sum_{\langle \bar{f}', \bar{e} \rangle \in Tab} freq(\bar{f}', \bar{e})}$$

$$\blacksquare \Theta(\bar{e} | \bar{f}) = \frac{freq(\bar{e}, \bar{f})}{\sum_{\langle \bar{f}, \bar{e}' \rangle \in Tab} freq(\bar{f}, \bar{e}')}$$

- Smoothing with lexical word alignment estimates from IBM models

Distance-Based Reordering Sketch

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



Lexicalized Reordering Sketch (Tillmann 2004)

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



Limited generalization over parallel data (1)

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Non-productive Phrase Table: Phrase Variants?

Morphological e.g., changing inflection, agreement

<u>Al</u> \$arekat <u>Al</u> hindiyya	\$areka hindiyya
the-companies the-Indian	company Indian
the Indian companies	(an) Indian company

Syntactic e.g. adding adjective/proposition/adverbials

the fish <u>in the deep sea</u> swims	the fish swims
---------------------------------------	----------------

Reordering minor reordering of same words not allowed
In Arabic V-S-O and S-V-O are allowed.

Semantic e.g. synonyms, paraphrases

Non-productive Phrase Table = Data Sparseness

Limited generalization over parallel data (2)

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Reordering

Local, monotone, almost non-lexicalized reordering.

What about long range reordering?



Reordering target phrases with a coarse “source road map”?

Limitations: Data-Sparseness

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Non-productive phrase table + Local, *Uncharted* reordering



Data-sparseness: Shorter phrases will apply down to word level.



Shorter phrases combined assuming independence.



Target phrase selection hard due to large hypotheses lattice
Target Language Model = Only “GLUE” over target phrases.

The Shorter the Phrases, the Greater the Risk

Idiomatic Approach: GOOD, BAD and UGLY

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Phrases as atomic units

Good: Less ambiguity in lexical choice and reordering.
Match-Retrieve exactly is largely safe.

Bad: Weak generalization over data.
No phrase variants, weak reordering

Ugly: Fall-back on shorter phrases down to
word-to-word
LM as “glue” is insufficient.

Idiomatic approach does not alleviate data-sparseness

How Should We Translate Novel Phrases?

Towards the land of bi-trees

Alignments between Tree Pairs, ITG, Hierarchical Models and Syntax

Hidden Structure of Translation: Tree Pairs

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an


Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models


Limitations of
PB Models

Syntax



Reordering n words

- Permutations of n words: $n!$




- Surely **not all permutations** are needed! (Wu 1995)
- Use trees and allow permutations on the nodes?

There is an exponential number of trees in n



- ITG hypothesis (Wu 1995)

Assume binary trees with two operations



- Phrase-based forms of ITG (Chiang 2005; 2007): Hiero

Syntax-Driven Phrase Translation

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models

Alignment
Symmetriza-
tion


Phrase-Based
Models

Limitations of
PB Models


Syntax

Syntax-driven Re-Ordering

Hierarchical (ITG)



Linguistic Syntax



Is translation syntactically cohesive?

Reordering == Moving children in parse tree?

- Binary: monotone or inverted order at every node.
- Lexical elements can be phrase pairs.
- Covers word-alignments in parallel corpora?

Word order difference and syntax: Impression

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an




Word-Based
Models

Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax



Phrase-based Hierarchical Model: Hiero (Chiang 2005; 2007)

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models


Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

Extracting phrase-pairs with gaps (hierarchical trees):



$X \rightarrow X_1 \text{ dar una bufetada a } X_2 / X_1 \text{ slap } X_2$

$X \rightarrow \text{Maria no } X \text{ la bruja verde} / \text{Mary did not } X \text{ the green witch}$

ITG with syntactic labels

Tutorial to
Statistical
Machine
Translation

Dr Khalil
Sima'an

Word-Based
Models


Alignment
Symmetriza-
tion

Phrase-Based
Models

Limitations of
PB Models

Syntax

- $SBAR \rightarrow [WHNP\ SBAR\ WHNP]$ (a)
 $SBAR\ WHNP \rightarrow \langle VP/NP^L\ NP^R \rangle$ (b)
 $NP^R \rightarrow [NP\ PP]$ (c)
 $WHNP \rightarrow WHNP_P$ (d)
 $WHNP_P \rightarrow \text{which} / \text{der}$ (e)
 $VP/NP^L \rightarrow VP/NP_P^L$ (f)
 $VP/NP_P^L \rightarrow \text{is} / \text{ist}$ (g)
 $NP^R \rightarrow NP_P^R$ (h)
 $NP_P^R \rightarrow \text{the solution} / \text{die Lösung}$ (i)
 $NP \rightarrow NP_P$ (j)
 $NP_P \rightarrow \text{the solution} / \text{die Lösung}$ (k)
 $PP \rightarrow PP_P$ (l)
 $PP_P \rightarrow \text{to the problem} / \text{für das Problem}$ (m)



Part II: Trevor Cohn

Decoding algorithms and efficiency