

educative

Back To Course Home

Grokking the Coding Interview: Patterns for Coding Questions

13% completed

Search Course

'K' Closest Points to the Origin (easy)

We'll cover the following

Problem Statement

Try it yourself

Solution

Code

Time complexity

Space complexity

Problem Statement#

Given an array of points in a $2D$ plane, find 'K' closest points to the origin.

Example 1:

```
Input: points = [[1,2],[1,3]], K = 1
Output: [[1,2]]
Explanation: The Euclidean distance between (1, 2) and the origin is sqrt(5).
The Euclidean distance between (1, 3) and the origin is sqrt(10).
Since sqrt(5) < sqrt(10), therefore (1, 2) is closer to the origin.
```

Example 2:

```
Input: point = [[1, 3], [3, 4], [2, -1]], K = 2
Output: [[1, 3], [2, -1]]
```

Try it yourself#

Try solving this question here:

JavaPython3JS C++

```
1 class Point:
2
3     def __init__(self, x, y):
4         self.x = x
5         self.y = y
6
7     def print_point(self):
8         print "[" + str(self.x) + ", " + str(self.y) + "]" , end=''
9
10 def find_closest_points(points, k):
11     result = []
12     # TODO: Write your code here
13     return result
14
15
16 def main():
17
18     result = find_closest_points([Point(1, 3), Point(3, 4), Point(2, -1)], 2)
19     print("Here are the k points closest the origin: ", end='')
20     for point in result:
21         point.print_point()
22
23
24 main()
25
26
27
```

Run

SaveReset

Solution#

The [Euclidean distance](#) of a point P(x,y) from the origin can be calculated through the following formula:

$$\sqrt{x^2 + y^2}$$

This problem follows the [Top 'K' Numbers](#) pattern. The only difference in this problem is that we need to find the closest point (to the origin) as compared to finding the largest numbers.

Following a similar approach, we can use a **Max Heap** to find 'K' points closest to the origin. While iterating through all points, if a point (say 'P') is closer to the origin than the top point of the max-heap, we will remove that top point from the heap and add 'P' to always keep the closest points in the heap.

Code#

Here is what our algorithm will look like:

JavaPython3C++JS

```
1 from future import print_function
2 from heapq import *
3
4
5 class Point:
6
7     def __init__(self, x, y):
8         self.x = x
9         self.y = y
10
11     # used for max-heap
12     def __lt__(self, other):
13         return self.distance_from_origin() > other.distance_from_origin()
14
15     def distance_from_origin(self):
16         # ignoring sqrt to calculate the distance
17         return (self.x * self.x) + (self.y * self.y)
18
19     def print_point(self):
20         print "[" + str(self.x) + ", " + str(self.y) + "]" , end=''
21
22
23 def find_closest_points(points, k):
24     maxHeap = []
25     # put first 'k' points in the max heap
26     for i in range(k):
27         heappush(maxHeap, points[i])
28
29     # go through the remaining points of the input array, if a point is closer to the origin than the top point
30     # of the max-heap, remove the top point from heap and add the point from the input array
31     for i in range(k, len(points)):
```

Run

SaveReset

Time complexity#

The time complexity of this algorithm is $(N * \log K)$ as we iterating all points and pushing them into the heap.

Space complexity#

The space complexity will be $O(K)$ because we need to store 'K' point in the heap.