

educative

Back To Course Home

Grokking the Coding Interview: Patterns for Coding Questions

13% completed

Search Course

We'll cover the following

Problem Statement #

Try it yourself #

Solution #

Code #

Time complexity #

Space complexity #

Problem Statement ###

Given an array of numbers and a number 'k', find the median of all the 'k' sized sub-arrays (or windows) of the array.

**Example 1:**

Input: nums=[1, 2, -1, 3, 5], k = 2

Output: [1.5, 0.5, 1.0, 4.0]

Explanation: Lets consider all windows of size '2':

- [1, 2, -1, 3, 5] -> median is 1.5
- [1, 2, -1, 3, 5] -> median is 0.5
- [1, 2, -1, 3, 5] -> median is 1.0
- [1, 2, -1, 3, 5] -> median is 4.0

**Example 2:**

Input: nums=[1, 2, -1, 3, 5], k = 3

Output: [1.0, 2.0, 3.0]

Explanation: Lets consider all windows of size '3':

- [1, 2, -1, 3, 5] -> median is 1.0
- [1, 2, -1, 3, 5] -> median is 2.0
- [1, 2, -1, 3, 5] -> median is 3.0

Try it yourself ###

Try solving this question here:

Java

Python3

JS

C++

```
1 class SlidingWindowMedian:
2
3     def find_sliding_window_median(self, nums, k):
4         result = []
5         # TODO: Write your code here
6         return result
7
8     def main():
9
10        slidingWindowMedian = SlidingWindowMedian()
11        result = slidingWindowMedian.find_sliding_window_median(
12            [1, 2, -1, 3, 5], 2)
13        print("Sliding window medians are: " + str(result))
14
15        slidingWindowMedian = SlidingWindowMedian()
16        result = slidingWindowMedian.find_sliding_window_median(
17            [1, 2, -1, 3, 5], 3)
18        print("Sliding window medians are: " + str(result))
19
20
21    main()
22
```

Run

Save

Reset

Solution ###

This problem follows the **Two Heaps** pattern and share similarities with [Find the Median of a Number Stream](#). We can follow a similar approach of maintaining a max-heap and a min-heap for the list of numbers to find their median.

The only difference is that we need to keep track of a sliding window of 'k' numbers. This means, in each iteration, when we insert a new number in the heaps, we need to remove one number from the heaps which is going out of the sliding window. After the removal, we need to rebalance the heaps in the same way that we did while inserting.

Code ###

Here is what our algorithm will look like:

Java

Python3

C++

JS

```
1 from heapq import *
2 import heapq
3
4
5 class SlidingWindowMedian:
6     def __init__(self):
7         self.maxHeap, self.minHeap = [], []
8
9     def find_sliding_window_median(self, nums, k):
10        result = [0.0 for x in range(len(nums) - k + 1)]
11        for i in range(0, len(nums)):
12            if not self.maxHeap or nums[i] <= -self.maxHeap[0]:
13                heappush(self.maxHeap, -nums[i])
14            else:
15                heappush(self.minHeap, nums[i])
16
17            self.rebalance_heaps()
18
19            if i - k + 1 >= 0: # if we have at least 'k' elements in the sliding window
20                # add the median to the the result array
21                if len(self.maxHeap) == len(self.minHeap):
22                    # we have even number of elements, take the average of middle two elements
23                    result[i - k + 1] = -self.maxHeap[0] / \
24                        2.0 + self.minHeap[0] / 2.0
25                else: # because max-heap will have one more element than the min-heap
26                    result[i - k + 1] = -self.maxHeap[0] / 1.0
27
28                # remove the element going out of the sliding window
29                elementToBeRemoved = nums[i - k + 1]
30                if elementToBeRemoved <= -self.maxHeap[0]:
31                    self.remove(self.maxHeap, -elementToBeRemoved)
```

Run

Save

Reset

Time complexity ##

The time complexity of our algorithm is  $O(N * K)$  where 'N' is the total number of elements in the input array and 'K' is the size of the sliding window. This is due to the fact that we are going through all the 'N' numbers and, while doing so, we are doing two things:

- Inserting/removing numbers from heaps of size 'K'. This will take  $O(logK)$
- Removing the element going out of the sliding window. This will take  $O(K)$  as we will be searching this element in an array of size 'K' (i.e., a heap).

Space complexity ##

Ignoring the space needed for the output array, the space complexity will be  $O(K)$  because, at any time, we will be storing all the numbers within the sliding window.

Back

Next

Find the Median of a Number Stream (...)

Maximize Capital (hard)

Mark as Completed

Report an Issue

Ask a Question