Retrieval & RAG

Revisiting QA

Previously: SQuAD-like **reading comprehension** questions & answers

➔ Annotators read a passage and wrote questions with answers in mind

Avengers: Doomsday is an upcoming American superhero film based on the Marvel Comics superhero team the Avengers. … The return of the Russo brothers as directors and McFeely as co-writer, the casting of Downey as new villain Doctor Doom, and the new subtitle Doomsday were all announced in July 2024.

Q: “Who is the villain in *Avengers: Doomsday*?”


A: “Doctor Doom”

Open-domain QA


Today: More realistic questions posed by **information-seeking users**

Q: “Who’s the bad guy in avengers doomsday?”





A: “Doctor Doom”



Avengers: Doomsday

45 languages

Article Talk Read View source View history

From Wikipedia, the free encyclopedia

Avengers: Doomsday is an upcoming American superhero film based on the Marvel Comics superhero team the Avengers. Produced by Marvel Studios and distributed by Walt Disney Studios Motion Pictures, it is intended to be the sequel to *Avengers: Endgame* (2019) and the 39th film in the Marvel Cinematic Universe (MCU). Directed by Anthony and Joe Russo, and written by the writing team of Stephen McFeely and Michael Waldron, the film features an ensemble cast led by Robert Downey Jr. as Doctor Doom. In the film, the Avengers, Wakandans, New Avengers, Fantastic Four, and the X-Men converge from different universes to face Doom amidst the collapse of the multiverse.

Two new *Avengers* films, *The Kang Dynasty* and *Secret Wars*, were announced in July 2022 as the conclusion of the MCU's Phase Six and "The Multiverse Saga". Jonathan Majors was set to reprise his MCU role as the villain Kang the Conqueror, with Destin Daniel Cretton and Jeff Loveness hired to direct and write *The Kang Dynasty*, respectively. In November 2023, Cretton departed, Waldron replaced Loveness as writer, and Marvel was considering moving away from the Kang storyline, in part due to Majors's legal issues; Majors was fired the following month. The return of the Russo brothers as directors and McFeely as co-writer, the casting of Downey as new villain Doctor Doom, and the new subtitle *Doomsday* were all announced in July 2024. The

Avengers: Doomsday

Teaser poster

Directed by Anthony Russo, Joe Russo

Limitations of LMs

Hallucinations

Chong Zou, Zhipeng Wang, Ziyu Li, Nan Wu, Yuling Cai, Shan Shi, Jiawei Wei, Xia Sun, Jian Wang, and Yizhou Wang. Segment everything everywhere all at once. In Advances in Neural Information Processing Systems (NeurIPS), volume 36, 2023.

"This paper exists, but all authors are wrong."

Dinghuai Zhang, Yang Song, Inderjit Dhillon, and Eric Xing. Defense against adversarial attacks using spectral regularization. In International Conference on Learning Representations (ICLR), 2020.

"No Match"

ICLR 2026 paper citations

Limitations of LMs



Q: “Does the Scarlet Witch show up in Doomsday?”

(indecisive about going to the theaters, and asking on *Dec 20, 2026*)

Obsolete knowledge

< Models

6 astra

GPT-6 Astra `gpt-6-astra`

Our most capable model for the most demanding work.

1,050,000 context window

128,000 max output tokens


Apr 30, 2026 knowledge cutoff

Reasoning token support

Avengers: Doomsday is scheduled to be released in the United States on December 18, 2026, as part of Phase Six of the MCU. The sequel, *Avengers: Secret Wars*, is set to be released on December 17, 2027.

Retrieval-augmented LMs: intuitions

Q: “Who are the authors of the self-rag paper?”



A: “Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi”

Reduces hallucinations ✔

Parameter efficient ✔

Retrieval-augmented LMs: intuitions

Q: “what happened in episode 8 of visionquest”



1. Retrieve a small set of docs from a data store as evidence


A: “Vision meets Vigil Horton, the grandson of Phineus …”

2. Generate!

Update knowledge w/o retraining ✔

Improved verifiability ✔

Retrieval is now central to production LLMs



Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval



Augmentation

We'll conclude with **deep research agents**!

Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval




Augmentation

We'll conclude with **deep research agents**!

Scaling up the data store






MassiveDS paper

Scaling up the data store





MassiveDS paper

Preparing data for a datastore



Avengers: Doomsday

Article Talk


From Wikipedia, the free encyclopedia

Avengers: Doomsday is an upcoming American superhero film based on the Marvel Comics superhero team the Avengers. Produced by Marvel Studios and distributed by Walt Disney Studios Motion Pictures, it is intended to be the sequel to *Avengers: Endgame* (2019) and the 39th film in the Marvel Cinematic Universe (MCU). Directed by Anthony and Joe Russo, and written by the writing team of Stephen McFeely and Michael Waldron, the film features an ensemble cast led by Robert Downey Jr. as Doctor Doom. In the film, the Avengers, Wakandans, New Avengers, Fantastic Four, and the X-Men converge from different universes to face Doom amidst the collapse of the multiverse.

Two new *Avengers* films, *The Kang Dynasty* and *Secret Wars*, were announced in July 2022 as the conclusion of the MCU's Phase Six and "The Multiverse Saga". Jonathan Majors was set to reprise his MCU role as the villain Kang the Conqueror, with Destin Daniel Cretton and Jeff Loveness hired to direct and write *The Kang Dynasty*, respectively. In November 2023, Cretton departed, Waldron replaced Loveness as writer, and Marvel was considering moving away from the Kang storyline, in part due to Majors's legal issues; Majors was fired the following month. The return of the Russo brothers as directors and McFeely as co-writer, the casting of Downey as new villain Doctor Doom, and the new subtitle *Doomsday* were all announced in July 2024. The large cast features actors from previous MCU media and 20th Century Fox's *X-Men* film

```
Avengers: Doomsday is an
upcoming American
superhero film based on
the Marvel Comics …
```

```
Two new Avengers films,
The Kang Dynasty and
Secret Wars, were …
```



Curate & preprocess
e.g. linearization, normalization

Chunking
split docs into retrievable parts

Post-process
e.g. remove short docs, deduplication

Chunking

Fixed-size chunking

Segment based on size (e.g. 256 tokens)

Pick a size large enough to provide context & small enough to delineate topics

Chunking

Fixed-size chunking

```
… several unique marketing stunts were used for Doomsday. Many cast members were announced as part
```

```
of a nearly 5.5-hour-long livestream in March 2025, which became the most-viewed cross-platform livestream stunt …
```

Chunking

Fixed-size chunking

```
… several unique marketing stunts were used for Doomsday. Many cast members were announced as part
```

```
of a nearly 5.5-hour-long livestream in March 2025, which became the most-viewed cross-platform livestream stunt …
```

Fixed-size chunking w/ overlap

Avoid losing info at chunk boundaries

Chunking

Fixed-size chunking

… several unique marketing stunts were used for Doomsday. Many cast members were announced as part

of a nearly 5.5-hour-long livestream in March 2025, which became the most-viewed cross-platform livestream stunt …

Fixed-size chunking w/ overlap

… several unique marketing stunts were used for Doomsday. **Many cast members were announced as part**

Many cast members were announced as part of a nearly 5.5-hour-long livestream in March 2025, which became …

Chunking

Fixed-size chunking

… several unique marketing stunts were used for Doomsday. Many cast members were announced as part

of a nearly 5.5-hour-long livestream in March 2025, which became the most-viewed cross-platform livestream stunt …

Fixed-size chunking w/ overlap

… several unique marketing stunts were used for Doomsday. **Many cast members were announced as part**

Many cast members were announced as part of a nearly 5.5-hour-long livestream in March 2025, which became …

Semantic/structural chunking

Segment via logical boundaries, e.g. sentences, sections

May use LMs to detect natural breakpoints

Chunking

Fixed-size chunking

… several unique marketing stunts were used for Doomsday. Many cast members were announced as part

of a nearly 5.5-hour-long livestream in March 2025, which became the most-viewed cross-platform livestream stunt …

Fixed-size chunking w/ overlap

… several unique marketing stunts were used for Doomsday. **Many cast members were announced as part**

Many cast members were announced as part of a nearly 5.5-hour-long livestream in March 2025, which became …

Semantic/structural chunking

Music. In April 2024, Alan Silvestri indicated … returning as the composer for both Doomsday and Secret Wars.

Chris Evans as Steve Rogers: The former leader of the Avengers, a super soldier … to the comics.

Context-enriched chunking

Prepend chunk-specific explanatory context to each chunk to situate it in a doc.

```
<document>
{{WHOLE_DOCUMENT}}
</document>
Here is the chunk we want to situate within the whole document
<chunk>
{{CHUNK_CONTENT}}
</chunk>
Please give a short succinct context to situate this chunk within the overall
document for the purposes of improving search retrieval of the chunk. Answer only
with the succinct context and nothing else.
```

From Anthropic

Context-enriched chunking

Prepend chunk-specific explanatory context to each chunk to situate it in a doc.

Original

```
The company's revenue grew by 3% over the previous quarter.
```

Contextualized

```
This chunk is from an SEC filing on ACME corp's performance in Q2 2023; the previous quarter's revenue was $314 million. The company's revenue grew by 3% over the previous quarter.
```

Reduces the top-20-chunk retrieval failure rate by 49%!

From Anthropic

Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval



Augmentation

Summary: curate, chunk, filter, and scale data in datastores

Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval



Augmentation

Information retrieval (IR)

Input: A query & a datastore

Output: A small number of ranked text chunks, retrieved from the datastore, that are most similar or relevant to the input query

$$D \in \text{Top}_k \text{Sim}\left(\cdot \mid x\right)$$

Sparse retrievers

Term-frequency based embeddings e.g. TF-IDF, BM25

$, and performs ok

Dense retrievers

Dense embeddings encoded by a trained model, e.g. DPR

$$, but performs better!


Sparse retrievers

Naive approach: one-hot vectors

						nlp			
Query what is nlp?	(	…	1	0	0	0	1	0	0	…	)
Doc 1 Natural language processing (NLP) is …	(	…	1	1	0	0	1	0	0	…	)
Doc 2 Doctor Doom is a comic book character who …	(	…	1	0	1	0	0	0	1	…	)


Sparse retrievers

Naive approach: count-based vectors



Sparse retrievers


Naive approach: count-based vectors



Sparse retrievers

If **`nlp`** appears a lot, that's useful info! But if **`is`** appears a lot, it's not very informative...

Naive approach: count-based vectors



Word weighting: TF-IDF

$$\mathrm{TF}\,(t,d) = \begin{cases} 1 + \log_{10} \mathrm{count}\,(t,d) & \text{if count}\,(t,d) > 0 \\ 0 & \text{otherwise} \end{cases}$$

Count of token *t* in document *d*

$$\mathrm{IDF}\,(t) = \log_{10} \frac{N}{\mathrm{df}\,(t)}$$

Total number of docs


Number of docs containing *t*

$$\text{TF-IDF}\,(t,d) = \mathrm{TF}\,(t,\,d) \times \mathrm{IDF}\,(t)$$

Term frequency x inverse document frequency

Word weighting: BM25

Kinda like TF-IDF but stops giving extra points once a word appears enough times, and adjusts scores for doc length



Sparse retrievers


Consider lexical overlap b/t a query and a document

1. Assign words a score that penalizes common words, e.g. “is”, and rewards highly specific keywords, e.g. “nlp”
2. Compute **cosine similarity** between query and document vectors

Very strong baseline approach!


Can’t fully capture semantic similarities

Neural (dense) retrieval




Neural (dense) retrieval

May retrieve up to *k* top chunks



Dense retrievers: embeddings

Use output vector of [CLS] in masked LMs



Special tok added in front of every input

Load pre-trained sentence embeddings

README Apache-2.0 license Security

models license Apache-2.0 python 3.10 | 3.11 | 3.12 | 3.13 pypi v6.0.1 docs sentence-transformers

Sentence Transformers: Embeddings, Retrieval, and Reranking


```
from sentence_transformers import SentenceTransformer

model = SentenceTransformer("Qwen/Qwen3-Embedding-8B")
```

Dense passage retrieval (DPR)

For a long time, no good recipe for training the encoder…

Neural retrieval suddenly started to work in 2020! (Karpukhin et al. 2020)



Switched from lexical-based retrieval to dense retrieval

Switched from an RNN-based document reader to BERT-based

DPR: training a dense retriever

$$\text{sim}(x, z) = \text{Enc}(x)^\top \text{Enc}(z)$$

query | chunk

$$-\log \frac{e^{\text{sim}(x,z^+)}}{\sum_{i=1}^{N} e^{\text{sim}(x,z_i)}}$$

Get close to a positive gold chunk

Push back all the other chunks

Initialize encoder from BERT, then fine-tune on a labeled dataset of query and gold chunk pairs with **contrastive learning**

DPR: training a dense retriever

$$\text{sim}(x, z) = \text{Enc}(x)^\top \text{Enc}(z)$$

query | chunk

$$-\log \frac{e^{\text{sim}(x,z^+)}}{\sum_{i=1}^{N} e^{\text{sim}(x,z_i)}}$$

Get close to a positive gold chunk

Push back all the other chunks

A softmax probability distribution , or “out of all possible chunks, how likely is it that z^+ is the right one for x?”

DPR: training a dense retriever

Training data: tuples of $< x, z^+, z_1^-, z_2^-, \ldots, z_n^- >$

$$-\log \frac{e^{\text{sim}(x,z^+)}}{\sum_{i=1}^{N} e^{\text{sim}(x,z_i)}} \approx -\log \frac{e^{\text{sim}(x,z^+)}}{e^{\text{sim}(x,z^+)} + \sum_{i=1}^{n} e^{\text{sim}\left(x,z_i^-\right)}}$$

In-batch approximation

"Out of all possible chunks in this batch, how likely is it that z^+ is the right one for x?"

DPR: training a dense retriever


Training data: tuples of $< x, z^+, z_1^-, z_2^-, \ldots, z_n^- >$

$$-\log \frac{e^{\text{sim}(x,z^+)}}{\sum_{i=1}^{N} e^{\text{sim}(x,z_i)}} \approx -\log \frac{e^{\text{sim}(x,z^+)}}{e^{\text{sim}(x,z^+)} + \sum_{i=1}^{n} e^{\text{sim}(x,z_i^-)}}$$

In-batch approximation

Hard negatives in the batch that have high lexical overlap w/ *x* that challenge the model

DPR: results



Karpukhin et al. 2020

A little bit of history 🦕

Open-domain question answering

- Pre-2019: Retrieval-based models, w/ an external knowledge datastore and mostly lexical-based methods
- 2020: “Parametric-only LMs” might be better or enough?? Or do we need neural retrieval??
  - *Remember*: T5 beat its own human creators at trivia!
- Today: Most modern LMs use retrieval


Generally, the quality of retrieval-based LMs depends on the quality of **retrieval**

Reranking

A slow, post-retrieval “polishing” step that reranks retrieved results

Input pairs of <query, retrieved chunk> into a cross-encoder

Intuition: the initial retrieval might be high recall; this is high precision



FAISS: indexing & fast nearest neighbor search

Method	Class name	index_factory	Main parameters	Bytes/vector	Exhausti
Exact Search for L2	IndexFlatL2	"Flat"	d	4*d	yes
Exact Search for Inner Product	IndexFlatIP	"Flat"	d	4*d	yes
Hierarchical Navigable Small World graph exploration	IndexHNSWFlat	"HNSW,Flat"	d, M	4*d + x * M * 2 * 4	no
Inverted file with exact post-verification	IndexIVFFlat	"IVFx,Flat"	quantizer, d, nlists, metric	4*d + 8	no
Locality-Sensitive Hashing (binary flat index)	IndexLSH	-	d, nbits	ceil(nbits/8)	yes
Scalar quantizer (SQ) in flat mode	IndexScalarQuantizer	"SQ8"	d	d	yes
Product quantizer (PQ) in flat mode	IndexPQ	"PQx", "PQ"M"x"nbits	d, M, nbits	ceil(M * nbits / 8)	yes
IVF and scalar quantizer	IndexIVFScalarQuantizer	"IVFx,SQ4" "IVFx,SQ8"	quantizer, d, nlists, qtype	SQfp16: 2 * d + 8, SQ8: d + 8 or SQ4: d/2 + 8	no
IVFADC (coarse quantizer+PQ on residuals)	IndexIVFPQ	"IVFx,PQ"y"x"nbits	quantizer, d, nlists, M, nbits	ceil(M * nbits/8)+8	no
IVFADC+R (same as IVFADC with re-ranking based on codes)	IndexIVFPQR	"IVFx,PQy+z"	quantizer, d, nlists, M, nbits, M_refine, nbits_refine	M+M_refine+8	no

Exact search

Approximated search

Faster but some approaches are memory-heavy; can scale to ~1B vectors.

Some methods reduce index size w/ quantization; others are non-exhaustive.

Retrieval metrics

Evaluation of **unranked** retrieval sets

$$\text{Precision} = \frac{\#\left(\text{relevant items retrieved}\right)}{\#\left(\text{retrieved items}\right)} \qquad \text{Recall} = \frac{\#\left(\text{relevant items retrieved}\right)}{\#\left(\text{relevant items}\right)}$$

Can also calculate recall@K, or “coverage”

➔ Checks whether a gold doc appears in the top-K retrieved results

Retrieval metrics

Evaluation of **ranked** retrieval sets

Mean reciprocal rank (MRR)

of queries

Rank position of the first relevant doc for the *i*th query

$$\mathrm{MRR} = \frac{1}{|Q|}\sum_{i=1}^{|Q|}\frac{1}{\mathrm{rank}_i}$$

Normalized discounted cumulative gain (nDCG)

For the *j*th query

Graded relevance, e.g. *R* = 3 for "perfect" docs, *R* = 1 for "okay" docs

The top *k* results

For the *m*th result

$$\mathrm{nDCG}\,(Q,k) = \frac{1}{|Q|}\sum_{j=1}^{|Q|} Z_{kj}\sum_{m=1}^{k}\frac{2^{R(j,m)}-1}{\log_2\,(1+m)}$$

Retrieval metrics

Evaluation of **ranked** retrieval sets

Mean reciprocal rank (MRR)

of queries

Rank position of the first relevant doc for the *i*th query

$$\mathrm{MRR} = \frac{1}{|Q|}\sum_{i=1}^{|Q|}\frac{1}{\mathrm{rank}_i}$$

Normalized discounted cumulative gain (nDCG)

Average over all queries

DCG for one query

$$\mathrm{nDCG}\left(Q,k\right) = \frac{1}{|Q|}\sum_{j=1}^{|Q|} Z_{kj}\sum_{m=1}^{k}\frac{2^{R(j,m)}-1}{\log_2\left(1+m\right)}$$

Retrieval metrics

Evaluation of **ranked** retrieval sets

Mean reciprocal rank (MRR)

of queries

Rank position of the first relevant doc for the *i*th query

$$\mathrm{MRR} = \frac{1}{|Q|}\sum_{i=1}^{|Q|}\frac{1}{\mathrm{rank}_i}$$

Normalized discounted cumulative gain (nDCG)


Normalization, or 1 / the DCG of the best possible rank ordering. With this, a perfect ranking = 1.

Exponential, so better docs gain a lot more

Discount/penalize results further down the list


$$\mathrm{nDCG}\left(Q,k\right) = \frac{1}{|Q|}\sum_{j=1}^{|Q|} Z_{kj}\sum_{m=1}^{k}\frac{2^{R(j,m)}-1}{\log_2\left(1+m\right)}$$

Retrieval benchmark: BEIR



Thakur et al. 2021


Text representation benchmark: MTEB



Muennighoff et al. 2022

MTEB

https://leaderboard.mteb.org/



Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval



Augmentation

Summary: sparse vs. dense retrievers, the latter trained w/ contrastive loss

Various metrics and benchmarks for evaluating retrieval quality

Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval




Augmentation

Key early work: DrQA

Query



Document **retriever**; TF-IDF w/ bigrams



Document **reader**; an RNN


Answer

Chen et al. 2017

A precursor to DPR that used **sparse retrieval**, and demonstrated an entire pipeline where an LM is **augmented** w/ a retrieval module

Retrieval-augmented generation


The “RAG” paper introduced **end-to-end training**



Lewis et al. 2020

Retrieval-augmented generation

The “RAG” paper introduced **end-to-end training**



Lewis et al. 2020

In-context RAG

Can also just combine **retrieval w/ off-the-shelf LMs,** no additional training!

Retrieval results, ranked

In April 2023, 34 days before Elizabeth Holmes begins her 11-year prison sentence ...

In Season 2 of The Rehearsal, Fielder satirized use of ...

My name is Nathan Fielder, and I graduated from one of Canada's top business schools with really good grades.

In-context RAG

Can also just combine **retrieval w/ off-the-shelf LMs,** no additional training!

Retrieval results, ranked

In April 2023, 34 days before Elizabeth Holmes begins her 11-year prison sentence ...

In Season 2 of The Rehearsal, Fielder satirized use of ...

My name is Nathan Fielder, and I graduated from one of Canada's top business schools with really good grades.

Around when did Nathan Fielder start filming for his documentary?

In-context RAG


Can also just combine **retrieval w/ off-the-shelf LMs,** no additional training!

Retrieval results, ranked

In April 2023, 34 days before Elizabeth Holmes begins her 11-year prison sentence ...


In Season 2 of The Rehearsal, Fielder satirized use of ...

My name is Nathan Fielder, and I graduated from one of Canada's top business schools with really good grades.




Can concatenate multiple retrieved results together!

In-context RAG




Ram et al. 2023

In-context RAG (historically)




(a) RAG performance with e5 retriever



(b) RAG performance with BM25 retriever

Jin et al. 2024

Limitations of in-context RAG



Mallen et al. 2023

- **Mitigation**: some approaches, e.g. Self-RAG, are trained to *adaptively* call retrieval on demand
- ~2024: **LMs as search agents** that decide
  a. when to retrieve
  b. what to search for
  c. what results to include in response

Search-R1

Learn the search policy with RL. Template for generating rollouts:

```
Answer the given question. You must conduct reasoning inside <think> and
</think> first every time you get new information. After reasoning, if you
find you lack some knowledge, you can call a search engine by <search> query
</search>, and it will return the top searched results between <information>
and </information>. You can search as many times as you want. If you find no
further external knowledge needed, you can directly provide the answer inside
<answer> and </answer> without detailed illustrations. For example, <answer>
xxx </answer>. Question: question.
```

During training, use a **final outcome reward** that assesses correctness.

Search-R1 paper

Search-R1

Q: Curious is a women's fragrance by a singer born in what city and state?

<think> I need to find out which city and state a singer, by whom the women's fragrance "Curious" was created, was born in. </think>

<search> Curious fragrance information </search>

<information> Doc 1(Title: "Curious (fragrance)") Curious (fragrance) Curious is a women's fragrance by Britney Spears for Elizabeth Arden, and is the first perfume to be endorsed by Britney Spears, preceding ""Fantasy."" Spears reportedly earned $52 million from the endorsement. ""Curious"" was released in September 2004, and was very successful internationally. It was the number one fragrance of 2004 in department stores, ... </information>


<think> I need to find out which city and state Britney Spears, the singer behind "Curious" fragrance, was born in. </think>

<search> Britney Spears birthplace </search>

... ...


<answer> McComb, Mississippi </answer>

Search-R1




Search-R1 paper

Deep research agents (2025-present)



Deep research agents (2025-present)




Current effects of AI-generated papers

During this year's ICLR 2026 paper reviewing period:





Deep research agents (2025-present)



Deep research agents (2025-present)


Open-ended questions, that require long-form, complex, interleaved retrieval & reasoning workflows





Dr. Tulu blog post

Training deep research agents




Synthetic data plays a big role throughout!

Training deep research agents, with rubrics

Long-form responses are hard to verify!

One approach:

1. Build an initial rubric tailored to each question
2. During online RL, sample multiple rollouts from the current policy
3. Ask the rubric generator to propose new *positive* and *negative* criteria that compare these responses
4. Rubrics are filtered and ranked based on *discriminability*




DR Tulu blog post

Training deep research agents, with rubrics

A deep research agent, e.g. DR Tulu, must learn to decide actions:

- **think** for internal planning
- **call tool** to invoke search or browsing tools, e.g. `google_search`, `web_browse`, `paper_search`
- **answer** to produce a final response, and wrap claims in **citation tags**




[Dr. Tulu blog post]

Benchmarks for DR agents

BrowseComp: measure the ability of an agent to browse (Wei et al. 2025)

Difficult; not solvable with at least five Google searches, and should take a human 10+ minutes

Query: Please identify the fictional character who occasionally breaks the fourth wall with the audience, has a backstory involving help from selfless ascetics, is known for his humor, and had a TV show that aired between the 1960s and 1980s with fewer than 50 episodes.
Answer: Plastic Man



Benchmarks for DR agents

Many! MedBrowseComp, FinSearchComp, ScholarQABench, DeepResearchBench, ResearchQA, HealthBench

Some recurring themes:

A focus on expert, domain-specific, multi-step information work

Difficulty demonstrated based on whether frontier models struggle on the task at release

Evaluation metrics: accuracy on short answers, rubrics (auto-generated or expert-written) for long answers

Sometimes, models *outperform* human experts, or models agree with human annotators more than humans agree with each other!

Today


Retrieval-**A**ugmented **G**eneration



Data



Retrieval



Augmentation

Summary: LMs may be augmented w/ retrieval in an in-context manner or trained end-to-end. Eval of search and research can be *multi-dimensional*.

Logistics

Poster session will be in MH 6618


Guest lecture next week will be about RL and rubrics as rewards!

Logistics


In-class assignment on Nov 30

- Generation
- Reasoning
- Long Contexts & Experts
- Evaluation & Benchmarks
- Retrieval & RAG ← **we are here**
- Language Agents
- Interpretability

Logistics


r/popculture · 6d ago
u/Impossible-Yam3680
Top 1% Poster
Cardi B to Johns Hopkins University students: "Y'all better pass your semester exams and not ask ChatGPT for the answers"
😭😂😂

Review: Generation



We're doing beam search, w/ $n = 3$. **Which candidates are our next beams?**

Current candidate	Probability
the list of	0.004
the list goes	0.002
the list is	0.002
the look of	0.024
the lookout	0.016
the look on	0.008
and the two	0.024
and the creation	0.005
and the buildings	0.002

Review: Generation


Let's trim off our long tail!

Identify the set of *k* tokens that have the highest probabilities

Set the probabilities of all but these tokens to 0

Renormalize by dividing the remaining probs by the sum of these *k* tokens' probs

What is this decoding algo called?




Review: Generation

Add *n* tokens that have the highest probabilities to a set until their cumulative probability exceeds *p*

Set the probabilities of all but these *n* tokens to 0


Renormalize by dividing the remaining probs by the sum of these *n* tokens' probs

What is this decoding algo called?




Review: Generation

Once upon a time, there was a _____



Review: Generation

We're generating the next word in our output, and we're currently on *Das*. What is the boxed thing called?



Review: Generation

	y_1	y_2	y_3	y_4	y_5
	`cats`	`love`	`biting`	`your`	`toes`
p_i	0.8	0.7	0.9	0.8	0.7
q_i	0.9	0.8	0.8	0.3	0.8

We're running speculative decoding. **What do we do here?**

A) Accept the drafted word, B) Toss a weighted coin to decide, C) Reject it

Our sequence so far: `cats love`

Review: Generation

	y_1	y_2	y_3	y_4	y_5
	`cats`	`love`	`biting`	`your`	`toes`
$\boldsymbol{p_i}$	0.8	0.7	0.9	0.8	0.7
$\boldsymbol{q_i}$	0.9	0.8	0.8	0.3	0.8

If we reject this token, where do we sample a new token from?

A) $(q_i - p_i)_+$ B) $(p_i - q_i)_+$ C) p D) q

Our sequence so far: `cats love`