

Introduction to containers on HPC with the Sarus container engine

Summer School on Effective HPC for Climate and Weather Alberto Madonna, CSCS August 27, 2020

Table of Contents

- 1. Introduction to Sarus (30 min)
- 2. Tutorial / live demo (45 min)

Slides and code available at https://github.com/eth-cscs/containers-hands-on

 Disclaimer: This material reflects only the author's view and the EU-Commission is not responsible for any use that may be made of the information it contains







Docker and HPC: not a good fit

- Security model assumes root privileges
- No integration with workload managers
- Missing support for diskless nodes
- Very limited support for kernel bypassing devices (e.g. accelerators and NICs)
- No adequate parallel storage driver







Sarus container engine

- OCI-compatible container engine engineered by CSCS
- Designed for the requirements HPC
- Consistent UX with Docker: small learning curve
- Transparent native performance through hooks
- Enables use of standard, open, upstream components on HPC systems
- Extensible architecture encourages vendor engagement and improves maintainability







Typical user workflow at CSCS

2. Push to Docker Hub

3. Pull into storage at HPC center

FROM debian
RUN apt-get ...
RUN make ...

1. Create Docker image

4. Run at scale on HPC system





Highlights of Sarus from a user perspective

- Consistent experience
 - With Docker: closely resembling CLI
 - With host environment: env variables, uid/gid, file permissions
- Pull images from Docker registries (e.g. Docker Hub, NVIDIA NGC)
- Import images from local tar archives (no cloud upload required)
- Integration with the workload manager (Slurm)
- Native performance from GPUs and high-speed interconnects
- Access to parallel filesystems inside containers







Sarus CLI

Sarus

```
# pull image
$ sarus pull [options] <image>[<:tag>]
# load image
$ sarus load [options] <file> <image>
# show list of images
$ sarus images
# remove image
$ sarus rmi <image>[<:tag>]
# run container
$ sarus run [options] <image>[<:tag>]
<command> <args>
```

Docker

```
# pull image
$ docker pull [options] <image>[<:tag>]
# load image
$ docker load [options] -i <file>
# show list of images
$ docker images [options] [repo[<:tag>]]
# remove image
$ docker rmi [options] <image> [image...]
# run container
$ docker run [options] <image>[<:tag>]
<command> <args>
```











Live demo!

Piz Daint: our host for the demo



- Flagship system for the Swiss National HPC Service, installed at CSCS Lugano
- #10 in the June 2020 TOP500 list
- Hybrid Cray XC40/XC50 supercomputer
 - 5704 hybrid nodes: Intel Xeon E5-2690 v3 + NVIDIA Tesla P100
 - 1813 multicore nodes: 2 x Intel Xeon E5-2695 v4
- Cray Aries high-speed interconnect
- OS: Cray Linux Environment







Further reading

- Sarus user documentation: https://sarus.readthedocs.io/en/latest/user/user_guide.html
- Sarus on GitHub: https://github.com/eth-cscs/sarus

- Slides and Lab material: https://github.com/eth-cscs/containers-hands-on
- Lab intro video: https://youtu.be/dv74sFb3cVc
- Contact: <u>alberto.madonna@cscs.ch</u>







The ESiWACE1/2 projects have received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 675191 and No 823988





Disclaimer: This material reflects only the author's view and the EU-Commission is not responsible for any use that may be made of the information it contains
















Thank you for your attention.