

Formal Languages and Grammars

1 Formal Languages

Basic concepts of any formal language:

- Alphabet Σ = set of all possible symbols
- Sequence (or word) α = string of symbols
- Language = Particular set of sequences

Further concepts:

- Syntax: which sequences belong to the language
- Semantics: the meaning of these sequences

In the context of programming languages:

- Sequences in the formal language are all valid program codes

If a language L has a finite number of sequences it is described by listing all sequences

If it has an infinite number of sequences it is represented with more complex set notation or with a set of substitution rules

2 Formal Grammars

Definition: Formal Grammar

A finite way of describing an infinite number of strings
Given by a start symbol and a set of production rules

Definition: Grammar

A quadruple (V_T, V_N, P, S) where:

- V_T is a set of terminal symbols (or terminals)
- V_N is a set of non-terminal symbols (or terminals)
- P is a set of productions (or rules)
- S is the start symbol (which is a non-terminal)

$V = V_T \cup V_N$ is the set of all symbols where $V_T \cap V_N = \emptyset$

2.1 Notation

- Non terminals: Capital letters
- Terminals: Lower case letters
- Sequences (strings): Greek letters
- Productions have the form: $\alpha \rightarrow \beta$
 - α and β are strings of both terminals and non-terminals
 - α lies in VY^+ (it has at least one non-terminal)
 - β lies in V^* (i.e. can also be the empty string ϵ)
- Whenever we have two rules $\alpha \rightarrow \beta_1, \alpha \rightarrow \beta_2$ we write equivalently $\alpha \rightarrow \beta_1 | \beta_2$

2.2 Example

$$L_4 = \{a^m b^n | m, n \geq 0\}$$

Grammar for this language: $G_4 = \{\{a, b\}, \{S, A, B\}, P, S\}$ where P includes:

$$S \rightarrow AB$$

$$A \rightarrow aA$$

$$A \rightarrow \epsilon$$

$$B \rightarrow bB$$

$$B \rightarrow \epsilon$$

Or equivalently $S \rightarrow AB$

$$A \rightarrow aA | \epsilon$$

$$B \rightarrow bB | \epsilon$$

$$S \rightarrow AB \rightarrow aAB \rightarrow aaAB \rightarrow aaaAB \rightarrow aaaB \rightarrow aaabB \rightarrow aaabbB \rightarrow aaabb$$

Or in short:

$$S \xrightarrow[+]{G_4} aaabb$$

3 Language generated by a grammar

$$L(G) = \{\alpha \in V_T^* | S \xrightarrow[+]{G} \alpha\}$$

A non-terminal N is called

- **Left-recursive** if starting with N, we can produce a string that starts again with N
 - e.g. $N \rightarrow Nab$
- **Nullable** if starting with N, we can produce ϵ
 - e.g. $N \rightarrow aNb | \epsilon$
- **Useless** if starting with N, we can never produce a string consisting only of terminals
 - e.g. $N \rightarrow aN | bN$

4 The Chomsky Hierarchy

Definition: Chomsky Hierarchy

The classes of grammars we obtain by restricting the types of productions that can appear

Type 0 grammars - The set of all grammars

Type 1 (or context sensitive) grammars

- The grammars that have only productions of the form $\alpha \rightarrow \beta$, where $|\alpha| \geq |\beta|$

Type 2 (or context free) grammars

- The context free grammars, in which all productions have one of the forms:

$$A \rightarrow a$$

$$A \rightarrow aB$$