

PURE MATHEMATICS WITH MECHANICS • UPPER SIXTH

UPPER SIXTH — PURE MATHEMATICS WITH MECHANICS

CHAPTER 14

EQUILIBRIUM FORCES, MOMENTS AND COUPLES

SUGGESTED TIME: 15 PERIODS

IN THIS CHAPTER

This chapter studies how bodies remain at rest under the action of several forces: conditions of equilibrium, centres of gravity, resolution and composition of coplanar forces, and the elastic behaviour described by Hooke's law. It blends geometry, trigonometry and physical intuition into the core mechanics toolkit required at GCE Advanced Level.

- By the end of this chapter I can state and apply the conditions for equilibrium of a body under coplanar forces
- By the end of this chapter I can determine the centre of gravity of a lamina experimentally and by calculation
- By the end of this chapter I can represent forces as vectors and add them graphically and analytically
- By the end of this chapter I can resolve a force into components along chosen axes, including on an inclined plane
- By the end of this chapter I can draw a correct free-body diagram showing all forces acting on a body
- By the end of this chapter I can distinguish and compute resultant and equilibrant forces



DOWNLOAD ON- BUCH

Free • Google Play
AI tutor, past papers,
results



GO ONBUCH+

All signed courses, unlimited AI
tutor, PDF sheets — OnBuch+
tab in the app

THIS SIGNED COURSE CONTAINS

COURSE

complete, illustrated,
step by step

METHODS

and worked examples

EXERCISES

exam style + solutions

SUMMARY SHEET

the essentials to
remember



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+

CONTENTS

- | | |
|--|--|
| 1. Equilibrium and Centre of Gravity | ification |
| 2. Force as a Vector; Addition and Resolution | 7. Applications of Hooke's Law and Synthesis |
| 3. Types of Forces and Free-Body Diagrams | 8. Integration activity |
| 4. Resultant and Equilibrant; Graphical Methods | 9. Methods and worked examples |
| 5. Analytical Methods and Equilibrium Problems | 10. Exercises |
| 6. Hooke's Law and Its Experimental Verification | 11. Solutions to the exercises |
| | 12. Summary sheet |

CHAPTER OBJECTIVES

- By the end of this chapter I can state and apply the conditions for equilibrium of a body under coplanar forces
- By the end of this chapter I can determine the centre of gravity of a lamina experimentally and by calculation
- By the end of this chapter I can represent forces as vectors and add them graphically and analytically
- By the end of this chapter I can resolve a force into components along chosen axes, including on an inclined plane
- By the end of this chapter I can draw a correct free-body diagram showing all forces acting on a body
- By the end of this chapter I can distinguish and compute resultant and equilibrant forces
- By the end of this chapter I can use the triangle, parallelogram and polygon of forces to solve equilibrium problems
- By the end of this chapter I can state, verify experimentally and apply Hooke's law to springs and elastic strings
- By the end of this chapter I can solve GCE-style problems on suspended bodies, inclined planes and systems of springs

PREREQUISITES

- Trigonometric ratios (sine, cosine, tangent) and the sine and cosine rules from Lower Sixth pure mathematics
- Vector notation, magnitude and direction of a vector, and simple vector addition
- Basic kinematics and the concept of force, weight ($W = mg$) and Newton's laws from Lower Sixth mechanics
- Solving simultaneous linear equations in two unknowns
- Plotting and interpreting straight-line graphs (gradient, intercept)

1 EQUILIBRIUM AND CENTRE OF GRAVITY

1.1 The Market Trader's Pole: A Question of Balance

At Mokolo market in Yaoundé, a trader hangs a heavy sack of plantains on one end of a wooden balance pole and a small stone on the other — and the pole stays perfectly horizontal. Why does the small stone 'defeat' the heavy sack? On the Bamenda escarpment road, a loaded lorry parks on a steep slope without sliding, while a spring scale in a Douala hardware shop stretches exactly twice as much when the load is doubled. All these everyday situations obey the same mathematical laws: equilibrium of forces, moments, and Hooke's law. This chapter gives you the tools to explain and predict them — and to solve the GCE questions built on them.

1.2 Equilibrium of Forces

1.3 Moments and the Moment of a Force

1.4 The Plumb-Line Experiment

1.5 Equilibrium of Suspended Bodies

1.6 Applications: Stability and Toppling

2 EQUILIBRIUM AND CENTRE OF GRAVITY

3 EQUILIBRIUM AND CENTRE OF GRAVITY

4 EQUILIBRIUM AND CENTRE OF GRAVITY

5 EQUILIBRIUM AND CENTRE OF GRAVITY

6 FORCE AS A VECTOR; ADDITION AND RESOLUTION

In Section 1 we met bodies in equilibrium: a hanging picture frame, a ladder, a metre rule bal-

anced at its centre of gravity. In every case we spoke of forces balancing each other, but we treated them rather loosely, as if only their sizes mattered. A moment's thought shows this is not enough. If two porters at the Mokolo market push a stalled cart, it matters enormously whether they push in the same direction or against each other. To handle equilibrium properly we must treat force as what it truly is: a **vector**. That is the business of this section, and it will give us the tools — addition, resolution, and the geometry of coplanar systems — that we shall use for the rest of the chapter.

6.1 Force as a Vector Quantity

DEFINITION Force as a vector

A **force** is a vector quantity. To specify a force completely we must give four things:

- its **magnitude** (or size), measured in newtons (N);
- its **direction** (the angle it makes with a chosen reference line);
- its **line of action** (the infinite straight line along which it acts);
- its **point of application** (the point of the body where it acts).

A force is represented on paper by a directed line segment: the length of the segment (to a chosen scale) gives the magnitude, and the arrowhead gives the sense.

WARNING Point of application matters

Two forces with the same magnitude and direction but different lines of action do not have the same effect on a rigid body: pushing a door near the hinge and near the handle are very different experiences! For now, most of our bodies will be small enough to be treated as particles, so all forces act at one point; the line of action will become crucial when we study moments later in this chapter.

6.2 Addition of Forces: the Parallelogram and Triangle Laws

Suppose two forces $\vec{P}$ and $\vec{Q}$ act at the same point O of a body, with an angle θ between them. What single force would produce exactly the same effect?

DEFINITION Resultant

The **resultant** of a system of forces is the single force which, acting alone, has exactly the same effect on the body as the whole system acting together.

DEFINITION Equilibrant

The **equilibrant** of a system of forces is the single force which, when added to the system, brings the body into equilibrium. It is equal in magnitude to the resultant but opposite in direction: $\vec{E} = -\vec{R}$.

PROPERTY Parallelogram law of forces

If two forces acting at a point are represented in magnitude and direction by the adjacent sides of a parallelogram, then their resultant is represented in magnitude and direction by the diagonal of the parallelogram passing through their common point. (This law is an experimental fact of mechanics; its consequences must be derivable in the examination.)

Equivalently, the **triangle law**: draw $\vec{P}$, then draw $\vec{Q}$ starting from the head of $\vec{P}$; the resultant $\vec{R}$ is the segment joining the tail of $\vec{P}$ to the head of $\vec{Q}$. The two laws are the same statement, since opposite sides of a parallelogram are equal and parallel. Note that in the triangle construction, the angle between $\vec{P}$ and $\vec{Q}$ (placed head-to-tail) is $180^\circ - \theta$.



Parallelogram law (left) and triangle law (right) for the addition of two forces. In the triangle construction the interior angle is $180^\circ - \theta$.

Magnitude and direction of the resultant.

In the triangle, the angle between $\vec{P}$ and the reversed direction of $\vec{Q}$ is $180^\circ - \theta$. Applying the cosine rule:

$$R^2 = P^2 + Q^2 - 2PQ \cos(180^\circ - \theta) = P^2 + Q^2 + 2PQ \cos \theta.$$

The angle α that $\vec{R}$ makes with $\vec{P}$ follows from the sine rule or from components:

$$\tan \alpha = \frac{Q \sin \theta}{P + Q \cos \theta}.$$

KEY POINTS Key formulae

For two forces P and Q inclined at angle θ :

$$R = \sqrt{P^2 + Q^2 + 2PQ \cos \theta}, \quad \tan \alpha = \frac{Q \sin \theta}{P + Q \cos \theta}.$$

Special cases: forces in the same direction ($\theta = 0$): $R = P + Q$; opposite directions ($\theta = 180^\circ$): $R = |P - Q|$; perpendicular forces ($\theta = 90^\circ$): $R = \sqrt{P^2 + Q^2}$.

WORKED EXAMPLE 1 Resultant of two forces

Two forces of 5 N and 8 N act at a point O with an angle of 60° between them. Find the magnitude of their resultant and the angle it makes with the 8 N force.

SOLUTION

Solution. Take $P = 8$, $Q = 5$, $\theta = 60^\circ$.

$$R^2 = 8^2 + 5^2 + 2(8)(5) \cos 60^\circ = 64 + 25 + 80 \times 0.5 = 129,$$

so $R = \sqrt{129} \approx 11.36$ N. The angle α with the 8 N force satisfies

$$\tan \alpha = \frac{5 \sin 60^\circ}{8 + 5 \cos 60^\circ} = \frac{5 \times 0.8660}{8 + 2.5} = \frac{4.330}{10.5} = 0.4124,$$

giving $\alpha \approx 22.4^\circ$.

6.3 Resolution of a Force into Perpendicular Components

Addition combines two forces into one. **Resolution** does the reverse: it splits one force into two forces, called **components**, whose resultant is the original force. There are infinitely many ways to do this, but the useful one is resolution along two perpendicular axes.

If a force F makes an angle θ with the x -axis, then completing the rectangle (a parallelogram with perpendicular sides) gives immediately:

$$F_x = F \cos \theta, \quad F_y = F \sin \theta.$$

WARNING Sine or cosine?

The component adjacent to the angle θ takes $\cos \theta$; the component opposite to it takes $\sin \theta$. Mixing up sine and cosine is the single most common error at the GCE in this topic. Always draw the rectangle, mark the angle, and check: when $\theta = 0$ the whole force lies along the axis, so that component must be F (and $\cos 0 = 1$ — cosine confirmed).

METHOD Resolving a system of forces

1. Choose two perpendicular axes, placed so that as many forces as possible lie along them.

2. For each force, mark the angle it makes with an axis and write its two components.
3. Add the components along each axis to get $R_x = \sum F_x$ and $R_y = \sum F_y$.
4. Recombine if needed: $R = \sqrt{R_x^2 + R_y^2}$, $\tan \alpha = R_y / R_x$ (taking care with the quadrant of α).

6.4 Resolution on an Inclined Plane

A lorry parked on the sloping road up to Buea does not slide down, yet gravity pulls it vertically. How does the slope "share" the weight? This is the classic situation where wise choice of axes pays off.

METHOD Resolving weight on an inclined plane


For a body of mass m on a plane inclined at θ to the horizontal, take axes along the plane and perpendicular to the plane. The weight mg (vertically downward) then splits into:

- $mg \sin \theta$ acting down the slope;
- $mg \cos \theta$ acting perpendicularly into the plane.

Angle chasing: why the angle is θ (examinable proof).

Let the plane make angle θ with the horizontal. The weight $\vec{W}$ is vertical, i.e. perpendicular to the horizontal. The normal to the plane is perpendicular to the plane. Now use the geometric lemma: if two angles have their sides mutually perpendicular, the angles are equal. The sides of θ (horizontal, plane) are respectively perpendicular to the sides of the angle between the weight and the normal (vertical, normal). Hence the angle between the weight and the normal to the plane is exactly θ .

More elementarily: the plane makes θ with the horizontal, so the normal makes θ with the vertical (rotating both lines by 90° preserves the angle). Since the weight acts along the vertical, the angle between weight and normal is θ . Then, in the right-angled resolution rectangle, the component adjacent to θ (along the normal, into the plane) is $mg \cos \theta$, and the component opposite (down the slope) is $mg \sin \theta$.



Weight of a block on a plane inclined at $\theta = 30^\circ$ resolved into $mg \sin \theta$ down the slope and $mg \cos \theta$ into the plane. The angle between the weight (vertical) and the inward normal equals the inclination θ .

WORKED EXAMPLE 2 Components of weight on a slope

A block of mass 10 kg rests on a plane inclined at 30° to the horizontal. Find the components of its weight along and perpendicular to the plane. (Take $g = 9.81 \text{ m s}^{-2}$.)

SOLUTION

Solution. The weight is $W = mg = 10 \times 9.81 = 98.1 \text{ N}$.

$$\text{Down the slope: } W \sin 30^\circ = 98.1 \times 0.5 = 49.05 \text{ N,}$$

$$\text{Into the plane: } W \cos 30^\circ = 98.1 \times 0.8660 = 84.96 \text{ N.}$$

$$\text{Check: } \sqrt{49.05^2 + 84.96^2} \approx 98.1 = W. \quad \checkmark$$

6.5 Coplanar Forces

DEFINITION Coplanar forces

A system of forces is **coplanar** when all their lines of action lie in one and the same plane. Within coplanar systems we distinguish:

- **concurrent** systems: all lines of action pass through a single point (e.g. three ropes knotted together);
- **non-concurrent** systems: the lines of action do not all meet at one point (e.g. the forces on a ladder leaning against a wall).

Why restrict ourselves to coplanar forces? Because two perpendicular directions suffice to

describe every force in the plane: any coplanar force can be written $\vec{F} = F_x \vec{i} + F_y \vec{j}$, and the whole machinery of resolution above applies with just two axes. In three dimensions we would need a third component, vector products, and considerably heavier algebra — that belongs to Further Mathematics and to university mechanics. At Advanced Level, every equilibrium problem you will meet (hanging bodies, inclined planes, ladders, frameworks) can be arranged, by symmetry or by the geometry of the situation, as a coplanar problem.

EXAMPLE Recognising coplanar systems

- A picture hanging from a nail by two strings: the two tensions and the weight all lie in the vertical plane of the wall — concurrent and coplanar.
- A ladder against a wall: weight, two reactions and friction all act in the vertical plane perpendicular to the wall — coplanar but non-concurrent.
- A book on a sloping desk: weight, normal reaction and friction are coplanar in the vertical plane through the line of greatest slope.

EXERCISE 1 Practice

1. Two forces of 6 N and 10 N act at a point with an angle of 120° between them. Find the magnitude of their resultant.
2. A force of 20 N acts at 40° above the horizontal. Find its horizontal and vertical components.
3. A child of mass 35 kg sits on a slide inclined at 25° to the horizontal. Find the components of her weight along and perpendicular to the slide. ($g = 9.81 \text{ m s}^{-2}$)
4. Two perpendicular forces have a resultant of 13 N. If one force is 5 N, find the other and the angle the resultant makes with it.

SOLUTION Exercise 1

1. $R^2 = 6^2 + 10^2 + 2(6)(10) \cos 120^\circ = 36 + 100 - 60 = 76$, so $R = \sqrt{76} \approx 8.72 \text{ N}$.
2. $F_x = 20 \cos 40^\circ \approx 15.32 \text{ N}$; $F_y = 20 \sin 40^\circ \approx 12.86 \text{ N}$.
3. Along the slide: $35 \times 9.81 \times \sin 25^\circ \approx 145.1 \text{ N}$; perpendicular: $35 \times 9.81 \times \cos 25^\circ \approx 311.2 \text{ N}$.
4. Other force: $\sqrt{13^2 - 5^2} = \sqrt{144} = 12 \text{ N}$; angle with the 5 N force: $\tan \alpha = 12/5$, so $\alpha \approx 67.4^\circ$.

KEY POINTS To remember

- A force is a vector: magnitude, direction, line of action, point of application.
- Resultant of two forces: $R^2 = P^2 + Q^2 + 2PQ \cos \theta$ (where θ is the angle between them).
- Equilibrant: equal in magnitude to the resultant, opposite in direction ($\vec{E} = -\vec{R}$).
- Resolution: adjacent component takes cosine, opposite takes sine.
- On an inclined plane: $mg \sin \theta$ down the slope, $mg \cos \theta$ into the plane — because the angle between the weight and the normal equals θ .
- All our systems are coplanar: two perpendicular axes are enough.

With forces now added and resolved at will, we are ready in the next section to catalogue the types of forces that act on bodies — weight, reactions, tension, friction — and to draw the free-body diagrams that turn a physical situation into a solvable mathematical problem.

7 TYPES OF FORCES AND FREE-BODY DIAGRAMS

In the previous section we learnt that a force is a vector: it has a magnitude, a direction and a line of action, and we saw how to add forces and resolve them into components. But before we can add or resolve anything, we must answer a more basic question: which forces actually act on the body we are studying? A student who misses one force, or invents one that does not exist, will get the wrong answer no matter how good his vector algebra is. This section is therefore about **recognising forces** and about the single most important tool of mechanics: the **free-body diagram**. It covers Lessons 157 to 161 of the official syllabus: force as a vector, addition and resolution of forces, types of forces, free-body diagrams, resultant and equilibrant, and resolution on inclined planes.

7.1 The Main Types of Forces

Weight.

Every body near the Earth's surface is pulled towards the centre of the Earth. This pull is the **weight** of the body.

DEFINITION Weight

The **weight** of a body of mass m is the gravitational force exerted on it by the Earth:

$$W = mg,$$

where $g \approx 9.81 \text{ m s}^{-2}$ is the acceleration due to gravity. Weight is a force, measured in newtons (N), and it always acts vertically downward, through the centre of gravity of the

body, whatever the position or motion of the body.

WARNING Mass is not weight

Mass m is measured in kilograms; weight $W = mg$ is measured in newtons. A bag of rice of mass 25 kg has weight $W = 25 \times 9.81 \approx 245$ N. On an inclined plane the weight is still vertically downward — never “into the slope” and never “along the slope”.

Normal reaction.

Place a book on a table. The book does not fall through the table: the table pushes back on it. This push is the **normal reaction** (or contact reaction).

PROPERTY Direction of the normal reaction

The normal reaction $\vec{R}$ exerted by a surface on a body is always perpendicular (normal) to the surface of contact, directed away from the surface and into the body. It is never along the surface. (Proof not examinable; this is a modelling property of contact forces.)

The word “normal” here is the mathematical one: it means “at right angles”. On a horizontal floor, R is vertical; on a wall, R is horizontal; on a slope inclined at θ to the horizontal, R is inclined at θ to the vertical.

Tension.

When a string, rope, chain or cable is taut, it exerts a **tension** force on whatever is attached to its ends.

WARNING A string can only pull

The tension in a string always pulls on the body, along the string, directed away from the body towards the string. A string can never push: if you try to push with a rope, it simply goes slack and the tension becomes zero. For a light inextensible string passing over a smooth pulley, the tension has the same magnitude T throughout the string.

Friction.

Rub your hands together: you feel a resistance. When two rough surfaces are in contact, the force of **friction** acts along the surface of contact (tangentially), in the direction that **opposes relative motion** — or the tendency to move.

DEFINITION Friction

Friction is the tangential contact force between two rough surfaces. Its direction is opposite to the direction in which the body is sliding, or would slide if friction were absent. A surface described as **smooth** exerts no friction (only the normal reaction); a surface described as **rough** exerts friction F , whose maximum value, called limiting friction, will be studied in detail in a later chapter.

To find the direction of friction, always ask: "If this surface were smooth, which way would the body slide?" Friction points the opposite way. A crate pulled eastwards on rough ground experiences friction westwards; a block resting on a slope would slide down, so friction on it acts up the slope.

Thrust (compression) in rods.

Unlike a string, a rigid rod or strut can push. A rod in compression exerts a **thrust** on the body, directed along the rod, pushing the body away from the rod. A rod in tension pulls, exactly like a string. This is why scaffolding poles and the legs of a table can support loads that ropes cannot.

Applied forces and elastic (spring) forces.

An **applied force** is any push or pull given directly in the problem: a man pushing a trolley with 50 N, the wind on a signboard, the pull of a tractor. A **spring** (or elastic cord) exerts a force that depends on how much it is stretched or compressed: it pulls when stretched and pushes when compressed, always towards its natural length. We shall see in Section 6 that this force obeys Hooke's law, $T = kx$ — for now, simply treat it as a force acting along the spring.

DID YOU KNOW? Forces around us in Cameroon

When a bendskin (motorcycle taxi) climbs a hill in Bamenda, the friction between the tyres and the road pushes the motorcycle forward — friction is not always a nuisance! Without friction, wheels would spin uselessly and nobody could walk. Engineers choosing tyres for the rainy season on the Douala–Yaoundé road think constantly about friction. In the construction of the Kribi deep-sea port, cranes use steel cables (tension) and hydraulic rams (thrust) to lift containers; each force must be correctly identified for safe operation.

7.2 The Free-Body Diagram

When several forces act at once, the mind gets confused unless we draw a clean picture. Physicists and engineers use one universal tool.

DEFINITION Free-body diagram

A **free-body diagram** (FBD) is a sketch showing a single body, isolated from its surroundings, together with all the external forces acting on it — and nothing else. Every contact or


support is removed and replaced by the force it exerts on the body. Forces that the body exerts on other objects are never drawn.

METHOD Checklist for drawing a free-body diagram

1. Isolate the body: draw it alone (a simple dot or small box is enough).
2. Weight: draw $W = mg$ vertically downward from the centre of gravity.
3. Reactions at contacts: at each point of contact with a surface, draw the normal reaction R perpendicular to the surface.
4. Tensions and thrusts at attachments: along each string (pulling) or rod (pulling or pushing).
5. Applied forces: any push or pull stated in the problem.
6. Friction: if the contact is rough, draw F along the surface, opposing motion or the tendency to move.

WARNING The three classic errors

- Never add ma as a force. The quantity $m\vec{a}$ is the result of the forces ($\sum \vec{F} = m\vec{a}$), not an extra force. Drawing it on the FBD double-counts it.
- Never draw the reaction along the surface. R is perpendicular to the contact surface; the tangential component of contact is friction, a separate force.
- Never forget the weight. Even a body on a table, in the air, or on a slope always has $W = mg$ acting vertically downward.



Four free-body diagrams: hanging lamp, block on a rough slope, ladder against a wall, mass on a spring.

7.3 Worked Examples

EXAMPLE Hanging lamp

A lamp of mass 3 kg hangs at rest from a ceiling by a light string. Forces on the lamp: weight $W = 3 \times 9.81 = 29.4 \text{ N}$ downward, and tension T upward along the string. Since the lamp is in equilibrium, $T = W = 29.4 \text{ N}$. Note: the pull of the lamp on the string is not drawn — only forces on the lamp.

EXAMPLE Ladder against a wall

A ladder leans against a smooth vertical wall, its foot on rough horizontal ground. Forces on the ladder: weight W vertically down at its midpoint; normal reaction R_2 from the smooth wall, horizontal (perpendicular to the wall); at the rough ground, normal reaction R_1 vertically up and friction F along the ground towards the wall (the foot would slip away from the wall, so friction opposes this).

WORKED EXAMPLE 3 Block held on a slope by a string

A block of mass 5 kg rests on a rough plane inclined at 30° to the horizontal. It is held by a light string parallel to the slope, pulling up the slope. Draw the free-body diagram and identify every force.

SOLUTION

Solution. Isolate the block. Apply the checklist:

1. Weight: $W = mg = 5 \times 9.81 = 49.1 \text{ N}$, vertically downward.
2. Reaction: R , perpendicular to the slope (at 30° to the vertical), pointing away from the surface.
3. Tension: T , along the string, i.e. up the slope, pulling the block.
4. Applied force: none besides the string.
5. Friction: the plane is rough; without friction the block would slide down, so F acts up the slope, along the surface.

Four forces in total: W , R , T , F . Resolving (preview of Section 5): perpendicular to the plane, $R = W \cos 30^\circ$; parallel to the plane, $T + F = W \sin 30^\circ$.

WORKED EXAMPLE 4 Crate pulled on rough ground

A porter at a market pulls a crate of mass 40 kg along rough horizontal ground with a rope inclined at 25° above the horizontal, with tension $P = 120$ N. List the forces on the crate.

SOLUTION

Solution. Checklist on the crate:

1. Weight $W = 40 \times 9.81 = 392.4$ N, vertically downward.
2. Normal reaction R , vertically upward (perpendicular to the horizontal ground).
3. Tension $P = 120$ N along the rope, at 25° above the horizontal, pulling the crate.
4. Friction F along the ground, horizontal, opposing the motion (backwards).

Note that $R \neq W$ here: the rope has an upward component $P \sin 25^\circ$ which helps to support the crate, so $R = W - P \sin 25^\circ \approx 392.4 - 50.7 = 341.7$ N.

WORKED EXAMPLE 5 Particle on a smooth inclined plane with horizontal force

A particle of mass 2 kg rests in equilibrium on a smooth plane inclined at 40° to the horizontal, held by a horizontal force H acting towards the plane. Draw the free-body diagram and write the equilibrium equations.

SOLUTION


Solution. Forces on the particle:

1. Weight $W = 2 \times 9.81 = 19.62$ N, vertically downward.
2. Normal reaction R , perpendicular to the plane (at 40° to the vertical).
3. Applied horizontal force H , acting horizontally towards the plane.


No friction (smooth plane). Resolving perpendicular to the plane: $R = W \cos 40^\circ + H \sin 40^\circ$.
Resolving parallel to the plane (up the plane positive): $H \cos 40^\circ - W \sin 40^\circ = 0 \Rightarrow H = W \tan 40^\circ \approx 16.5$ N. Then $R = W \cos 40^\circ + W \tan 40^\circ \sin 40^\circ = W / \cos 40^\circ \approx 25.6$ N.

7.4 Wrong versus Right: a Typical Diagram Error

The figure below shows, for a block on an inclined plane, the most frequent wrong diagram seen in examinations, next to the correct one.



WRONG
R along slope,
W into slope



RIGHT
R perpendicular to slope,
W vertical, F along slope

Wrong versus right free-body diagram of a block on a rough inclined plane.

WARNING Examination traps

- The weight is vertical, not perpendicular to the slope. Only the components of W ($W \sin \theta$ along, $W \cos \theta$ perpendicular) may be drawn — and then W itself must be removed to avoid double-counting.
- Do not draw the force the block exerts on the plane: the FBD shows forces on the block only.
- On a smooth surface, there is no friction at all — do not invent it.
- For a system of coplanar forces (Lesson 162), all forces lie in one plane; the FBD must reflect this planarity.
- When resolving forces on an inclined plane (Lesson 161), choose axes parallel and perpendicular to the plane for simplicity.

KEY POINTS Key points

- Weight $W = mg$ always acts vertically downward through the centre of gravity.
- The normal reaction is always perpendicular to the contact surface; friction acts along it, opposing motion or its tendency.
- Tension pulls along the string; a string never pushes. A rod can push (thrust) or pull.
- A free-body diagram shows one isolated body with all external forces on it — weight, reactions, tensions/thrusts, applied forces, friction — and nothing else.
- Never draw ma as a force; never forget the weight.
- For equilibrium of coplanar forces, the vector sum is zero: $\sum \vec{F} = \vec{0}$, which gives two scalar equations $\sum F_x = 0$, $\sum F_y = 0$ (or resolved along/perpendicular to a plane).

EXERCISE 2 Forces on everyday objects

For each situation, list all the forces acting on the body in *italics* and sketch its free-body diagram:

1. a book resting on a horizontal table;
2. a picture frame hanging from a nail by a string over its top edge;
3. a box being pushed up a rough slope by a horizontal applied force;
4. a ball hanging from a spring fixed to the ceiling, pulled down and held at rest.

SOLUTION Exercise 1

1. Weight W downward; normal reaction R upward. Two forces.
2. Weight W downward; tension T upward along the string. Two forces.
3. Weight W vertically down; normal reaction R perpendicular to the slope; applied push P horizontal; friction F down the slope (opposing the upward motion). Four forces.
4. Weight W downward; spring tension T upward along the spring; applied downward pull P . Three forces.

In each case only forces acting on the italicised body are drawn.

With a correct free-body diagram in hand, we are ready for the next step: combining these forces to find their resultant, or showing that they balance — the subject of the following sections.

8**RESULTANT AND EQUILIBRANT; GRAPHICAL METHODS**

In the previous section we learnt how to identify every force acting on a body and how to display them on a **free-body diagram**. That picture immediately raises a practical question: when several forces act together, what is their combined effect? A loaded truck climbing the steep hill out of Bamenda is pulled forward by the engine's driving force, held back by friction and by the component of its weight parallel to the slope; whether it accelerates or moves at constant velocity depends on the single force equivalent to all of these. This section answers that question for coplanar forces acting at a point (concurrent forces), first by defining the **resultant** and the **equilibrant**, then by developing graphical methods — the parallelogram and the polygon of forces — which are quick, visual and fully accepted at the GCE Advanced Level when drawn accurately to scale.

8.1 The Resultant of a System of Forces

DEFINITION Resultant

The **resultant** of a system of forces is the single force which, acting alone on the body, produces exactly the same effect (the same tendency to translate and, where relevant, to rotate) as the whole system acting together. For a system of concurrent forces $\vec{F}_1, \vec{F}_2, \dots, \vec{F}_n$ acting at a point, the resultant $\vec{R}$ is their vector sum:

$$\vec{R} = \vec{F}_1 + \vec{F}_2 + \dots + \vec{F}_n.$$

The phrase “same effect” is essential. Two workers pushing a stalled vehicle with forces of 300 N and 400 N in the same direction achieve exactly what one person pushing with 700 N would achieve. The resultant is not an extra force added to the diagram; it is a replacement for the whole set.

WARNING The resultant is not an additional force

A very common error in free-body diagrams is to draw the real forces and then also the resultant $\vec{R}$. This double-counts the effect. Either you draw the individual forces, or you draw their resultant — never both on the same diagram.

8.2 The Equilibrant

Suppose the resultant of the forces on a body is $\vec{R}$. If we want the body to remain at rest (or in uniform motion), we must apply one more force that exactly cancels $\vec{R}$.

DEFINITION Equilibrant

The **equilibrant** $\vec{E}$ of a system of forces is the single force which, when added to the system, brings the body into equilibrium. It is:

- equal in magnitude to the resultant: $E = R$;
- opposite in direction to the resultant;
- collinear with the resultant (same line of action).

Hence $\vec{E} = -\vec{R}$, and $\vec{F}_1 + \vec{F}_2 + \dots + \vec{F}_n + \vec{E} = \vec{0}$.



$E = R$, opposite sense, same line of action through P

The resultant $\vec{R}$ and the equilibrant $\vec{E}$ of the same system: equal magnitudes, opposite directions, same line of action through P .

EXAMPLE Resultant versus equilibrant

Three tug-of-war teams pull a ring with a combined effect equivalent to a single force of 850 N directed due east. Then $R = 850$ N east. To keep the ring stationary, a fourth team must apply the equilibrant: $E = 850$ N due west, along the same line. Note that the equilibrant is not “the force that was missing” in any mysterious sense — it is simply $-\vec{R}$.

8.3 Graphical Method for Two Forces: the Parallelogram Law

PROPERTY Parallelogram of forces

If two forces $\vec{F}_1$ and $\vec{F}_2$ acting at a point O are represented in magnitude and direction by two adjacent sides of a parallelogram drawn from O , then their resultant $\vec{R}$ is represented in magnitude and direction by the diagonal of the parallelogram drawn from O . (This is the experimental law of vector addition; its analytical consequences are proved in the next section.)

METHOD Finding the resultant of two forces graphically

1. Choose a scale, e.g. $1 \text{ cm} \equiv 10 \text{ N}$, so that the drawing fits the page but stays large enough for accuracy.
2. From O , draw $\vec{F}_1$ to scale in its true direction (measure angles with a protractor).
3. From the same point O , draw $\vec{F}_2$ to scale in its true direction.
4. Complete the parallelogram with dashed lines parallel to the two forces.
5. Draw the diagonal from O : this is $\vec{R}$. Measure its length and convert back with the scale; measure its angle with the protractor.

WORKED EXAMPLE 6 Parallelogram construction

Two forces of 40 N and 30 N act at a point O , the angle between them being 60° . Find their resultant graphically.

SOLUTION

Scale: 1 cm $\equiv$ 10 N, so the forces are drawn as segments of 4.0 cm and 3.0 cm.

Construction: draw the 4.0 cm segment horizontally from O ; with a protractor draw the 3.0 cm segment at 60° to it; complete the parallelogram; draw the diagonal from O .

Measurement: the diagonal measures about 6.1 cm, giving $R \approx 61$ N, at an angle of about 25° to the 40 N force.

Check (analytical, for confidence):

$$R = \sqrt{40^2 + 30^2 + 2(40)(30)\cos 60^\circ} = \sqrt{1600 + 900 + 1200} = \sqrt{3700} \approx 60.8 \text{ N.}$$


The angle θ with the 40 N force satisfies $\tan \theta = \frac{30 \sin 60^\circ}{40 + 30 \cos 60^\circ} = \frac{25.98}{55} \approx 0.472$, so $\theta \approx 25.3^\circ$.
The graphical values 61 N and 25° agree within 0.5 % — excellent for a scale drawing.

8.4 The Polygon of Forces for Several Coplanar Forces

With three or more forces, completing parallelograms pairwise becomes clumsy. The **polygon of forces** generalises the idea: add the vectors head to tail.

METHOD Polygon of forces

1. Choose a suitable scale and record it on the diagram.
2. From a starting point A , draw the first force $\vec{F}_1$ to scale, in its true direction, ending at B .
3. From B (the head of $\vec{F}_1$), draw $\vec{F}_2$ to scale in its true direction, ending at C . Continue: each force starts where the previous one ends. Any order gives the same resultant.
4. When the last force ends at E , the vector from the start A to the finish E is the resultant $\vec{R}$. Measure its length and direction.
5. If the polygon closes (the last head returns to A), then $\vec{R} = \vec{0}$: the system is in equilibrium.



Polygon of forces for four coplanar forces drawn head-to-tail. The closing side $\vec{R}$ (orange), from the start A to the finish E, is the resultant.

WARNING Direction of the arrows

In the force polygon, all the given forces follow round in the same sense (head to tail, head to tail, ...). The resultant goes the opposite way: from the start of the first force to the end of the last. Never draw the resultant head-to-tail like the others — that would represent $\vec{R}$ added to the system, not equivalent to it. Likewise, the equilibrant, if drawn on the polygon, is the side that closes the polygon following the same sense as the other forces.

PROPERTY Graphical condition for equilibrium

A system of coplanar forces acting at a point is in equilibrium if and only if its force polygon closes (the head of the last force coincides with the tail of the first). Equivalently, $\vec{R} = \vec{0}$. (Proof: the polygon is exactly the geometrical addition of the vectors; closure means the vector sum is zero, which is the condition for equilibrium of a particle.)

This gives a powerful graphical test: to check whether given forces can hold a body in equilibrium, simply draw the polygon. If it closes, equilibrium is possible; the size of the “gap” otherwise gives the magnitude of the resultant, and the force needed to close the gap is the equilibrant.

8.5 Space Diagram, Force Diagram and Bow’s Notation

When forces act at different points of an extended body (a ladder, a beam), we need two drawings:

- the **space diagram**: a sketch of the body showing the lines of action of the forces and the angles between them;
- the **force diagram** (force polygon): the vectors drawn head-to-tail to scale, giving magnitudes and the resultant.

An exam-useful extra is **Bow’s notation**: in the space diagram, capital letters (A, B, C, ...) are

placed in the spaces between the lines of action, and each force is named by the two letters on either side of it (force AB , force BC , ...). In the force diagram the corresponding vertices are labelled with the matching small letters $a, b, c, \dots$, so the force AB is the vector from a to b . Bow's notation removes all ambiguity about which force is which and is appreciated by examiners in structured graphical questions.

EXAMPLE Bow's notation illustrated

A beam is supported at A and B and carries a load W at C . In the space diagram, label the spaces around the beam: A (left of left support), B (between supports), C (right of right support), D (above the beam). The forces are then: reaction at left support = DA , reaction at right support = AB , weight = BC , and any other force = CD . In the force diagram, draw vectors da, ab, bc, cd head-to-tail. The polygon closes if the beam is in equilibrium.

8.6 Accuracy of Graphical Work

Graphical methods are only as good as the drawing. Follow these rules:

- **Scale choice:** make the diagram as large as the paper allows while keeping every force on the page. A polygon spread over 20 cm is far more accurate than one squeezed into 5 cm.
- **Instruments:** sharp pencil, ruler with clear millimetre marks, good protractor. Measure lengths to the nearest millimetre and angles to the nearest degree.
- **Error estimate:** with a scale of 1 cm $\equiv$ 10 N, a ± 1 mm reading error gives ± 1 N uncertainty per measurement; for a resultant of 60 N this is roughly $\pm 2\%$. Always quote graphical answers sensibly, e.g. $R \approx 61$ N rather than 61.37 N.
- **State the scale** on your diagram — an unscaled drawing earns no marks.

WORKED EXAMPLE 7 Polygon of forces and the equilibrium test

Four forces act at a point O : $F_1 = 50$ N due east; $F_2 = 40$ N at 70° (measured anticlockwise from east); $F_3 = 45$ N at 150° ; $F_4 = 30$ N at 250° . Determine graphically whether the system is in equilibrium; if not, find the resultant and the equilibrant.

SOLUTION

Scale: 1 cm $\equiv$ 10 N; lengths 5.0, 4.0, 4.5, 3.0 cm.

Construction: from A draw $\vec{F}_1$ east to B ; from B draw $\vec{F}_2$ at 70° to C ; from C draw $\vec{F}_3$ at 150° to D ; from D draw $\vec{F}_4$ at 250° . The last head ends at E , which does not coincide with A : the system is not in equilibrium.

Measurement: $AE \approx 3.5$ cm, so $R \approx 35$ N, directed at about 66° anticlockwise from east.

Equilibrant: $E \approx 35$ N along the same line but in the opposite sense, i.e. at $66^\circ + 180^\circ = 246^\circ$ (or 66° below the westward axis). Adding this force would close the polygon.

Check (components):

$$\begin{aligned}\sum F_x &= 50 + 40 \cos 70^\circ + 45 \cos 150^\circ + 30 \cos 250^\circ \\ &= 50 + 13.68 - 38.97 - 10.26 = 14.45 \text{ N}, \\ \sum F_y &= 0 + 40 \sin 70^\circ + 45 \sin 150^\circ + 30 \sin 250^\circ \\ &= 37.59 + 22.5 - 28.19 = 31.90 \text{ N}, \\ R &= \sqrt{14.45^2 + 31.90^2} \approx 35.0 \text{ N}, \\ \theta &= \arctan\left(\frac{31.90}{14.45}\right) \approx 65.7^\circ \text{ from east}.\end{aligned}$$

The analytical result (35.0 N at 65.7°) agrees closely with the graphical measurement (35 N at 66°), the small difference coming from drawing tolerances.

WARNING Common traps in graphical questions

- Mixing up the space diagram and the force diagram: angles must be transferred correctly from one to the other.
- Drawing forces tail-to-tail (all from one point) in the polygon — that construction shows the forces but not their sum.
- Forgetting that the polygon may be drawn in any order; choosing a convenient order (e.g. nearly opposite forces together) reduces cumulative drawing error.
- Quoting the equilibrant in the same direction as the resultant. Remember: $\vec{E} = -\vec{R}$.
- Using a scale that is too small, leading to large percentage errors.

EXERCISE 3 Graphical practice

1. Two forces of 60 N and 80 N act at a point with an angle of 90° between them. Find the resultant graphically (scale 1 cm $\equiv$ 10 N) and check by calculation.
2. Three forces act at a point: 30 N east, 40 N at 120° , 35 N at 230° . Draw the force polygon, decide whether the system is in equilibrium, and if not find the resultant and the equilibrant.
3. A picture hangs from two strings making angles of 40° and 55° with the horizontal, the tensions being 25 N and 30 N. Using a polygon, find the single upward force (the equilibrant of the two tensions) that the nail must provide, and comment on the weight of the picture.

SOLUTION Exercise 1

1. Parallelogram (here a rectangle): diagonal measures 10.0 cm, so $R = 100 \text{ N}$ at $\arctan(80/60) \approx 53^\circ$ to the 60 N force. Check: $R = \sqrt{60^2 + 80^2} = 100 \text{ N}$. ✓
2. With scale 1 cm $\equiv$ 10 N, draw 3.0 cm east, then 4.0 cm at 120° , then 3.5 cm at 230° . The polygon does not close; the gap measures about 1.5 cm, so $R \approx 15 \text{ N}$ directed roughly 32° north of west; the equilibrant is 15 N in the opposite direction (32° south of east). (Component check: $\sum F_x = 30 + 40 \cos 120^\circ + 35 \cos 230^\circ = 30 - 20 - 22.5 = -12.5 \text{ N}$; $\sum F_y = 0 + 40 \sin 120^\circ + 35 \sin 230^\circ = 34.64 - 26.81 = 7.83 \text{ N}$; $R = \sqrt{12.5^2 + 7.83^2} \approx 14.7 \text{ N}$ at $\arctan(7.83/12.5) \approx 32^\circ$ above the negative x-axis, i.e. 148° from east. Graphical measurement improves with a larger scale such as 2 cm $\equiv$ 10 N.)
3. Draw the two tensions head-to-tail along their string directions; the closing side is vertical, of length corresponding to about 41 N upward. The nail's reaction (equilibrant of the tensions) is $\approx 41 \text{ N}$ upward; for the picture to hang at rest its weight must equal this, so the picture weighs about 41 N.

KEY POINTS Key points

- The **resultant** $\vec{R}$ is the single force equivalent to the whole system; the **equilibrant** $\vec{E} = -\vec{R}$ cancels it and produces equilibrium.
- Two forces: use the parallelogram; several coplanar forces: use the polygon of forces drawn head-to-tail to scale.
- In the polygon, the resultant runs from the start to the finish, against the sense of the other arrows.
- Equilibrium test: the force polygon closes $\iff \vec{R} = \vec{0} \iff$ equilibrium.
- Always state the scale, draw large, measure carefully, and quote answers to a sensible precision.
- Bow's notation links the space diagram and force diagram unambiguously.

Graphical methods give fast, visual answers, but their accuracy is limited by the drawing. In the next section we develop analytical methods — resolving forces into components — which give exact results and handle equilibrium problems algebraically.

9

ANALYTICAL METHODS AND EQUILIBRIUM PROBLEMS

In the previous section we explored graphical methods — the triangle and polygon of forces — which give an excellent visual understanding of resultants and equilibrium. However, graphical methods are limited by drawing accuracy and become cumbersome when many forces are in-

volved. In this section we develop the analytical (algebraic) approach: using trigonometry and vector components to compute resultants exactly and to solve equilibrium problems with precision. This is the method you will use in the vast majority of GCE Advanced Level examination questions.

9.1 Analytical Resultant of Two Forces

Consider two forces $\vec{P}$ and $\vec{Q}$ acting at a point O , with an angle θ between them ($0^\circ \leq \theta \leq 180^\circ$). Their resultant $\vec{R}$ is the diagonal of the parallelogram formed by $\vec{P}$ and $\vec{Q}$. Applying the cosine rule to the triangle formed by $\vec{P}$, $\vec{Q}$ and $\vec{R}$ gives the magnitude:

PROPERTY Magnitude of the Resultant of Two Forces

$$R = \sqrt{P^2 + Q^2 + 2PQ \cos \theta}$$

The direction of $\vec{R}$ relative to $\vec{P}$ is given by the angle α such that

$$\tan \alpha = \frac{Q \sin \theta}{P + Q \cos \theta}$$

This follows from the sine rule or by resolving $\vec{Q}$ into components parallel and perpendicular to $\vec{P}$.

EXAMPLE Resultant of two forces at 60°

Two forces of magnitudes $P = 30$ N and $Q = 40$ N act at a point with an angle of 60° between them. Find the magnitude and direction of their resultant.

Magnitude:

$$R = \sqrt{30^2 + 40^2 + 2 \cdot 30 \cdot 40 \cos 60^\circ} = \sqrt{900 + 1600 + 2400 \cdot 0.5} = \sqrt{3700} \approx 60.83 \text{ N}$$

Direction (angle α with the 30 N force):

$$\tan \alpha = \frac{40 \sin 60^\circ}{30 + 40 \cos 60^\circ} = \frac{40 \cdot \sqrt{3}/2}{30 + 40 \cdot 0.5} = \frac{20\sqrt{3}}{50} = \frac{2\sqrt{3}}{5} \approx 0.6928$$

$$\alpha \approx 34.7^\circ.$$

Special Cases

- **Forces at right angles** ($\theta = 90^\circ$): $\cos 90^\circ = 0$, so $R = \sqrt{P^2 + Q^2}$ and $\tan \alpha = Q/P$. This is simply Pythagoras' theorem.
- **Equal forces** ($P = Q$): $R = P\sqrt{2(1 + \cos \theta)} = 2P \cos \frac{\theta}{2}$, and the resultant bisects the angle between them ($\alpha = \theta/2$).
- **Same direction** ($\theta = 0^\circ$): $R = P + Q$, $\alpha = 0^\circ$.

- **Opposite directions** ($\theta = 180^\circ$): $R = |P - Q|$, direction is that of the larger force.

9.2 Component Method for Several Forces

When more than two forces act at a point, the parallelogram law becomes impractical. The systematic approach is to resolve each force into components along two perpendicular axes (usually horizontal x and vertical y).

METHOD Component Method for the Resultant of Several Coplanar Forces

1. Choose a coordinate system (usually x horizontal, y vertical).
2. For each force F_i making an angle θ_i with the positive x -axis, compute its components:

$$F_{ix} = F_i \cos \theta_i, \quad F_{iy} = F_i \sin \theta_i$$

3. Sum all x -components and all y -components:

$$\Sigma F_x = \Sigma F_{ix}, \quad \Sigma F_y = \Sigma F_{iy}$$

4. The resultant $\vec{R}$ has components $R_x = \Sigma F_x$, $R_y = \Sigma F_y$. Its magnitude and direction are:

$$R = \sqrt{(\Sigma F_x)^2 + (\Sigma F_y)^2}, \quad \tan \theta_R = \frac{\Sigma F_y}{\Sigma F_x}$$

(Determine the correct quadrant for θ_R from the signs of ΣF_x and ΣF_y .)

EXAMPLE Resultant of three forces by components

Three forces act at a point: $F_1 = 10 \text{ N}$ at 0° , $F_2 = 20 \text{ N}$ at 120° , $F_3 = 15 \text{ N}$ at 210° . Find the resultant.

Components:

$$\begin{aligned} F_{1x} &= 10 \cos 0^\circ = 10, & F_{1y} &= 10 \sin 0^\circ = 0 \\ F_{2x} &= 20 \cos 120^\circ = -10, & F_{2y} &= 20 \sin 120^\circ = 10\sqrt{3} \approx 17.32 \\ F_{3x} &= 15 \cos 210^\circ = -15 \frac{\sqrt{3}}{2} \approx -12.99, & F_{3y} &= 15 \sin 210^\circ = -7.5 \\ \Sigma F_x &= 10 - 10 - 12.99 = -12.99, & \Sigma F_y &= 0 + 17.32 - 7.5 = 9.82 \\ R &= \sqrt{(-12.99)^2 + 9.82^2} \approx \sqrt{168.7 + 96.4} \approx 16.28 \text{ N} \\ \tan \theta_R &= \frac{9.82}{-12.99} \approx -0.756 \Rightarrow \theta_R \approx 180^\circ - 37.1^\circ = 142.9^\circ \end{aligned}$$

(Second quadrant because $\Sigma F_x < 0$, $\Sigma F_y > 0$.)

9.3 Conditions of Equilibrium in Analytical Form

A particle (or a rigid body with no net moment) is in equilibrium under a system of coplanar forces if and only if the vector sum of the forces is zero. In components this gives two scalar equations:

PROPERTY Equilibrium Conditions for a Particle

$$\Sigma F_x = 0 \quad \text{and} \quad \Sigma F_y = 0$$

The force that balances a system of forces is called the **equilibrant**. It is equal in magnitude and opposite in direction to the resultant: $\vec{E} = -\vec{R}$. For a system in equilibrium, the equilibrant is the force that would need to be applied to maintain equilibrium if it were not already present.

For an extended rigid body, equilibrium also requires that the sum of moments about any point be zero:

$$\Sigma M_O = 0$$

This will be essential when we deal with beams, ladders, and other extended bodies in later chapters. For now, we concentrate on particles and concurrent force systems where the moment condition is automatically satisfied if the forces meet at a point.

9.4 Lami's Theorem for Three Concurrent Forces


When exactly three forces act at a point and the system is in equilibrium, the forces can be represented by the three sides of a triangle taken in order (the triangle of forces). Applying the sine rule to this triangle yields a powerful shortcut known as **Lami's Theorem**.

DEFINITION Lami's Theorem


If three forces P, Q, R acting at a point are in equilibrium, then each force is proportional to the sine of the angle between the other two forces:

$$\frac{P}{\sin \alpha} = \frac{Q}{\sin \beta} = \frac{R}{\sin \gamma}$$

where α is the angle between Q and R , β is the angle between R and P , and γ is the angle between P and Q .



Forces at Point



Force Triangle

Derivation of Lami's theorem: the angles α, β, γ between the forces at the point are the supplements of the interior angles of the force triangle. Since $\sin(180^\circ - \theta) = \sin \theta$, the sine rule on the triangle gives $P/\sin \alpha = Q/\sin \beta = R/\sin \gamma$.

PROPERTY Derivation of Lami's Theorem (Examinable)

The three forces in equilibrium form a closed triangle when placed head-to-tail. The interior angles of this triangle are $180^\circ - \alpha, 180^\circ - \beta, 180^\circ - \gamma$. By the sine rule:

$$\frac{P}{\sin(180^\circ - \alpha)} = \frac{Q}{\sin(180^\circ - \beta)} = \frac{R}{\sin(180^\circ - \gamma)}$$

Since $\sin(180^\circ - \theta) = \sin \theta$, we obtain Lami's theorem.

WARNING The Angle in Lami's Theorem

The angle used with each force is the angle between the other two forces, not the angle that force makes with the horizontal or vertical. In the diagram above, α is the angle between Q and R , β between R and P , γ between P and Q . Misidentifying these angles is the most common error when applying Lami's theorem.

9.5 Applications: Solving Equilibrium Problems

We now tackle typical examination problems: a body suspended by two strings, and a body on a smooth inclined plane held by a force. For three forces, you have a choice of method.

METHOD Choosing a Method for Three-Force Equilibrium

1. Lami's Theorem is fastest when the three forces are concurrent and you know (or can easily find) the angles between each pair of forces. Write the three ratios and solve for

the unknowns.

2. Resolution ($\Sigma F_x = 0$, $\Sigma F_y = 0$) is more versatile: it works for any number of forces, and is often simpler when forces are given with respect to horizontal/vertical axes (e.g. strings at known angles to the horizontal). It also avoids the supplement-angle confusion of Lami's theorem.
3. For more than three forces, you must use the component method; Lami's theorem does not apply.

WORKED EXAMPLE 8 Suspended Load — Two Strings

A load of weight $W = 50 \text{ N}$ is suspended by two light inextensible strings attached to the same horizontal ceiling. The strings make angles of 30° and 45° with the horizontal. Find the tension in each string.

SOLUTION

Method 1: Resolution (recommended) Let T_1 be the tension in the string at 30° , T_2 at 45° . The weight acts vertically downward. Resolve horizontally: $\Sigma F_x = 0 \Rightarrow T_1 \cos 30^\circ - T_2 \cos 45^\circ = 0$ Resolve vertically: $\Sigma F_y = 0 \Rightarrow T_1 \sin 30^\circ + T_2 \sin 45^\circ - 50 = 0$

From horizontal: $T_1 \frac{\sqrt{3}}{2} = T_2 \frac{\sqrt{2}}{2} \Rightarrow T_1 = T_2 \frac{\sqrt{2}}{\sqrt{3}}$.

Substitute into vertical:

$$T_2 \frac{\sqrt{2}}{\sqrt{3}} \cdot \frac{1}{2} + T_2 \frac{\sqrt{2}}{2} = 50$$

$$T_2 \frac{\sqrt{2}}{2} \left(\frac{1}{\sqrt{3}} + 1 \right) = 50$$

$$T_2 = \frac{100}{\sqrt{2} \left(1 + \frac{1}{\sqrt{3}} \right)} = \frac{100\sqrt{3}}{\sqrt{2}(\sqrt{3} + 1)} \approx 36.6 \text{ N}$$

Then $T_1 = T_2 \frac{\sqrt{2}}{\sqrt{3}} \approx 29.9 \text{ N}$.

Method 2: Lami's Theorem The three forces are T_1 , T_2 , and $W = 50 \text{ N}$. The angles between them: - Between T_1 and T_2 : $30^\circ + 45^\circ = 75^\circ$. - Between T_2 and W : $90^\circ + 45^\circ = 135^\circ$ (since W is vertical down, T_2 is 45° above horizontal). - Between W and T_1 : $90^\circ + 30^\circ = 120^\circ$.


Lami's theorem:

$$\frac{T_1}{\sin 135^\circ} = \frac{T_2}{\sin 120^\circ} = \frac{50}{\sin 75^\circ}$$

$$T_1 = 50 \frac{\sin 135^\circ}{\sin 75^\circ} = 50 \frac{\sqrt{2}/2}{\sin 75^\circ} \approx 29.9 \text{ N}$$

$$T_2 = 50 \frac{\sin 120^\circ}{\sin 75^\circ} = 50 \frac{\sqrt{3}/2}{\sin 75^\circ} \approx 36.6 \text{ N}$$

Both methods give the same result. Notice how Lami's theorem requires the angles between the forces (75° , 135° , 120°), not the angles to the horizontal.



Suspended load: physical configuration (left) and force triangle (right). The interior angles of the force triangle are the supplements of the angles between the forces at the point (75° , 135° , 120°).

EXAMPLE Body on a Smooth Inclined Plane

A body of weight $W = 100 \text{ N}$ rests on a smooth plane inclined at 30° to the horizontal. It is held in equilibrium by a force F acting up the plane at an angle of 20° to the plane. Find F and the reaction R of the plane.

Since the plane is smooth, the reaction R is perpendicular to the plane. Choose axes: x up the plane, y perpendicular to the plane (outward). Forces: – Weight W : components $W_x = -W \sin 30^\circ = -50 \text{ N}$, $W_y = -W \cos 30^\circ = -50\sqrt{3} \text{ N}$. – Applied force F : $F_x = F \cos 20^\circ$, $F_y = F \sin 20^\circ$. – Reaction R : $R_x = 0$, $R_y = R$.

Equilibrium:

$$\Sigma F_x = F \cos 20^\circ - 50 = 0 \Rightarrow F = \frac{50}{\cos 20^\circ} \approx 53.2 \text{ N}$$

$$\Sigma F_y = F \sin 20^\circ + R - 50\sqrt{3} = 0 \Rightarrow R = 50\sqrt{3} - F \sin 20^\circ \approx 86.6 - 18.2 = 68.4 \text{ N}$$

9.6 Summary and Key Points

KEY POINTS Key Points for Analytical Methods and Equilibrium

- Resultant of two forces: $R = \sqrt{P^2 + Q^2 + 2PQ \cos \theta}$, $\tan \alpha = \frac{Q \sin \theta}{P + Q \cos \theta}$.
- For several forces: resolve into x and y components, sum them, then $R =$

$$\sqrt{(\Sigma F_x)^2 + (\Sigma F_y)^2}, \tan \theta_R = \Sigma F_y / \Sigma F_x.$$

- Equilibrium of a particle: $\Sigma F_x = 0$ and $\Sigma F_y = 0$. The equilibrant $\vec{E} = -\vec{R}$.
- Lami's Theorem (three concurrent forces in equilibrium): $\frac{P}{\sin \alpha} = \frac{Q}{\sin \beta} = \frac{R}{\sin \gamma}$, where α, β, γ are the angles between the other two forces.
- For three forces, choose resolution (when angles to axes are given) or Lami's theorem (when angles between forces are given). For more than three forces, always use resolution.

EXERCISE 4 Practice Problems

- Two forces of 25 N and 40 N act at a point with an angle of 120° between them. Find the magnitude and direction of their resultant.
- A particle is in equilibrium under three forces: $F_1 = 10$ N horizontally to the right, $F_2 = 15$ N at 120° to the horizontal, and F_3 . Find F_3 by (a) resolution, (b) Lami's theorem.
- A weight of 80 N is suspended by two strings of lengths 3 m and 4 m attached to two points on a horizontal ceiling 5 m apart. Find the tension in each string. (Hint: the strings and the ceiling form a 3-4-5 triangle.)
- A block of weight W rests on a smooth plane inclined at α . A horizontal force H keeps it in equilibrium. Express H and the reaction R in terms of W and α .

SOLUTION Exercise 1

$$R = \sqrt{25^2 + 40^2 + 2 \cdot 25 \cdot 40 \cos 120^\circ} = \sqrt{625 + 1600 - 1000} = \sqrt{1225} = 35 \text{ N. } \tan \alpha = \frac{40 \sin 120^\circ}{25 + 40 \cos 120^\circ} = \frac{40 \cdot \sqrt{3}/2}{25 - 20} = 4\sqrt{3} \Rightarrow \alpha \approx 81.8^\circ \text{ from the 25 N force.}$$

SOLUTION Exercise 2

(a) Resolution: $\Sigma F_x = 10 + 15 \cos 120^\circ + F_{3x} = 10 - 7.5 + F_{3x} = 0 \Rightarrow F_{3x} = -2.5$. $\Sigma F_y = 0 + 15 \sin 120^\circ + F_{3y} = 12.99 + F_{3y} = 0 \Rightarrow F_{3y} = -12.99$. $F_3 = \sqrt{2.5^2 + 12.99^2} \approx 13.23$ N, angle $\approx -100.9^\circ$ (or 259.1°). (b) Lami's theorem: angles between forces: between F_1 and F_2 is 120° ; between F_2 and F_3 is β ; between F_3 and F_1 is γ . Since F_1 and F_2 are known, the force triangle gives $F_3 / \sin 120^\circ = 10 / \sin \beta = 15 / \sin \gamma$. With $\beta + \gamma = 240^\circ$, solving yields same F_3 .

SOLUTION Exercise 3

The geometry gives a right triangle (3–4–5). The strings are perpendicular to each other (angle 90°). Let T_3 be the tension in the 3 m string, T_4 in the 4 m string. The angles with the horizontal are $\sin^{-1}(4/5) \approx 53.1^\circ$ for the 3 m string and $\sin^{-1}(3/5) \approx 36.9^\circ$ for the 4 m string. At the point of suspension, the angles between the forces are: between the two tensions 90° ; between T_3 and W is 36.9° ; between T_4 and W is 53.1° . By Lami's theorem:

$$\frac{T_3}{\sin 53.1^\circ} = \frac{T_4}{\sin 36.9^\circ} = \frac{80}{\sin 90^\circ} = 80$$

$$T_3 = 80 \times 0.8 = 64 \text{ N}, \quad T_4 = 80 \times 0.6 = 48 \text{ N}.$$

SOLUTION Exercise 4

Axes along and perpendicular to plane. Weight components: $W \sin \alpha$ down plane, $W \cos \alpha$ into plane. Horizontal force H : component up plane $H \cos \alpha$, component out of plane $H \sin \alpha$. $\Sigma F_x = H \cos \alpha - W \sin \alpha = 0 \Rightarrow H = W \tan \alpha$. $\Sigma F_y = R - W \cos \alpha - H \sin \alpha = 0 \Rightarrow R = W \cos \alpha + W \tan \alpha \sin \alpha = W(\cos \alpha + \sin^2 \alpha / \cos \alpha) = W / \cos \alpha$.

10 HOOKE'S LAW AND ITS EXPERIMENTAL VERIFICATION

In the previous sections we learnt how to find the resultant of a system of coplanar forces analytically and how to use the conditions of equilibrium to solve problems. In most of those problems the forces were given to us directly: a weight of 50 N, a tension of 30 N, and so on. But where do such forces come from, and how can we measure a force that we cannot see? One of the oldest and most useful answers is: **use a spring**. A spring stretches when you pull it, and the amount it stretches tells you how hard you are pulling. The precise relationship between the pull and the stretch is the subject of this section: **Hooke's law**. It is the principle behind every spring balance used in the markets of Bamenda, Buea or Douala to weigh vegetables, fish and meat.

10.1 Elasticity, Springs and Elastic Strings

An introductory observation.

Take a spiral spring, hang it from a clamp, and pull its lower end gently. Two things happen:

- the spring gets longer while you pull;
- when you release it, the spring returns to its original length.

If you pull harder, it stretches more. But if you pull too hard, the spring no longer returns to its original length: it has been permanently damaged. This everyday behaviour contains all the

physics of this section.

DEFINITION Elasticity, natural length and extension

A body is said to be **elastic** if it returns to its original shape and size when the deforming force is removed. For a spring or an elastic string we define:

- the **natural length** (or unstretched length) l , sometimes written l_0 : the length of the spring when no load is applied;
- the **stretched length** L : the length of the spring when a load is applied;
- the **extension** x : the increase in length,

$$x = L - l.$$

The extension is measured in metres (m), or in millimetres (mm) in the laboratory.

WARNING Extension is NOT the total length

The most frequent mistake in this topic is to confuse the extension with the total length of the spring. Always subtract the natural length first:

$$x = \text{stretched length} - \text{natural length} = L - l.$$

For example, a spring of natural length $l = 20$ cm stretched to $L = 26$ cm has extension $x = 26 - 20 = 6$ cm, not 26 cm.

When a stretched spring is in equilibrium, it pulls back on the object stretching it. This inward pull is called the **tension** (or thrust, when a spring is compressed and pushes back). We denote it by T . For a body hanging at rest from a spring, equilibrium of the body gives $T = mg$: the tension in the spring equals the weight of the load.

DEFINITION Spring constant and modulus of elasticity

For a helical spring, the constant of proportionality in Hooke's law is called the **spring constant** (or stiffness) k , with unit N m^{-1} . For an elastic string or wire, it is more convenient to use the **modulus of elasticity** λ (lambda), measured in newtons (N), which is the force required to double the length of the string (theoretically). The two are related by

$$\lambda = kl,$$

where l is the natural length. Thus Hooke's law for a string is written

$$T = \frac{\lambda x}{l}.$$

10.2 Statement of Hooke's Law

Let us now make the observation quantitative. Hang masses of increasing weight F from a spring and measure the extension x each time. You will find results like these (typical school-laboratory values):

Load F (N)	0	1.0	2.0	3.0	4.0
Extension x (mm)	0	25	50	75	100

Each time the load doubles, the extension doubles; each time the load triples, the extension triples. The ratio $\frac{F}{x}$ is constant (here $\frac{F}{x} = 40 \text{ N/m}$). This is exactly the behaviour discovered by Robert Hooke in the seventeenth century.

PROPERTY Hooke's law

The **tension** T in an elastic spring (or string) is directly proportional to its **extension** x , provided the limit of proportionality is not exceeded:

$$T = kx,$$

where k is the **spring constant** (stiffness) of the spring.
An equivalent form, used for elastic strings and wires, is

$$T = \frac{\lambda x}{l},$$

where l is the natural length and λ is the **modulus of elasticity** of the string (measured in newtons).

KEY POINTS What Hooke's law really says

- $T = kx$ is a linear relationship: the graph of T against x is a straight line through the origin.
- It holds only within the limit of proportionality (often called the elastic limit at this level). Beyond that limit the spring is permanently deformed and the law fails.
- The same law applies to a spring in compression, with x the decrease in length and T the thrust.
- For an elastic string, $T = \lambda x / l$; a string, unlike a spring, cannot push — it goes slack when $x \leq 0$.
- The spring constant k is the force needed to produce a unit extension: $k = T/x$. Its SI unit is N m^{-1} . Physically, k measures the **stiffness**: the larger k , the harder the spring is to stretch.

DID YOU KNOW? Springs all around us


Robert Hooke announced his law in 1676 as a Latin anagram, *ceiilnossttuv*, which he later revealed as *ut tensio, sic vis* — “as the extension, so the force”. Today Hooke’s law is at work everywhere: in the suspension springs of the bendskins and taxis on Cameroonian roads, in spring balances at the market, in mattresses, ball-point pens and weighing scales. Engineers designing bridges and buildings must always check that materials stay within their elastic limit, so that structures spring back instead of collapsing.

10.3 Experimental Verification of Hooke’s Law**EXPERIMENT** Verifying Hooke’s law with a spiral spring

Aim. To verify that the extension of a spring is directly proportional to the applied load, and to determine the spring constant k .

Apparatus. A spiral spring, a retort stand with clamp, a set of slotted masses (each of known mass, e.g. 100 g), a millimetre ruler fixed vertically beside the spring, and a light pointer (a pin or a horizontal needle) attached to the bottom of the spring.

Setup. The spring is hung from the clamp with the ruler clamped vertically beside it, and the pointer moves in front of the scale (see figure below).



Experimental setup: a clamped spring with pointer, vertical millimetre scale and slotted masses. The extension x is the displacement of the pointer from its unloaded position.

Procedure.

1. With no load, record the pointer reading r_0 on the ruler.
2. Hang one slotted mass, wait for the spring to settle, and record the new pointer reading r . The extension is $x = r - r_0$.

3. Compute the load $F = mg$ (with $g = 9.81 \text{ m s}^{-2}$; for quick school work $g \approx 10 \text{ m s}^{-2}$ is often used).
4. Increase the load in equal steps, recording r each time, up to about ten readings.
5. Unload step by step and record the readings again; take the mean of the loading and unloading readings for each load.
6. Plot the load F (vertical axis) against the extension x (horizontal axis).

Precautions.

- Do not overload the spring: stay well below the elastic limit, otherwise the spring is permanently damaged and the results are useless.
- Fix the ruler vertically, close beside the spring, so that the pointer moves in front of the scale.
- Use a pointer and read the scale with the eye level with the pointer to avoid parallax error.
- Wait for the spring to stop oscillating before each reading, and repeat readings (loading and unloading) to average out random errors.
- Ensure the spring hangs freely without touching the ruler or the bench.


METHOD Verifying Hooke's law from the graph

1. Plot F (N) on the vertical axis against x (mm or m) on the horizontal axis.
2. If the points lie on a straight line through the origin, then $F \propto x$: Hooke's law is verified.
3. The gradient of the line is the spring constant:

$$k = \text{gradient} = \frac{\Delta F}{\Delta x}.$$

Choose two points on the line far apart (not necessarily data points) to compute it.

4. If x is in millimetres, convert: a gradient of $a \text{ N/mm}$ equals $1000a \text{ N/m}$.
5. If the line eventually curves and stops passing through the origin proportionally, the **limit of proportionality** (elastic limit) has been reached: beyond it the spring is permanently deformed.



Load against extension for a spring with $k = 40 \text{ N/m}$. Up to the limit of proportionality the graph is a straight line through the origin (gradient = k); beyond it the spring stretches more easily and is permanently deformed.

Reading the graph. In the figure above, the straight-line part has gradient

$$k = \frac{\Delta F}{\Delta x} = \frac{3 - 1}{75 - 25} = \frac{2 \text{ N}}{50 \text{ mm}} = 0.04 \text{ N/mm} = 40 \text{ N/m}.$$

The point where the line stops being straight (here at $F = 4 \text{ N}$, $x = 100 \text{ mm}$) is the **limit of proportionality**. Beyond it, equal increases of load produce ever larger extensions, and when the load is removed the spring does not return to its natural length: it has suffered a permanent (plastic) deformation.

WARNING Common traps in the experiment and the graph

- Plotting length instead of extension: the line then does not pass through the origin, and its gradient is still k but the proportionality is hidden. Always use $x = L - l$.

- Mixing units: if x is in mm, the gradient is in N/mm; multiply by 1000 to get N/m.
- Including points beyond the limit of proportionality when computing the gradient: use only the straight-line region.
- Forgetting that the load is the weight $F = mg$, not the mass m . A mass of 100 g gives a load of about 0.981 N, not 100 N.
- Not taking the mean of loading and unloading readings to reduce hysteresis errors.

10.4 Worked Examples

WORKED EXAMPLE 9 Using Hooke's law for a spring

A spring has natural length 25 cm. When a mass of 400 g is hung from it, its length becomes 33 cm. Taking $g = 10 \text{ m s}^{-2}$:

- Find the spring constant k , assuming the elastic limit is not exceeded.
- Find the length of the spring when a mass of 650 g is hung from it.
- Find the mass that must be hung from the spring to stretch it to a length of 40 cm.

SOLUTION

Solution. First convert to SI units: natural length $l = 0.25 \text{ m}$.

(a) The extension is

$$x = L - l = 0.33 - 0.25 = 0.08 \text{ m}.$$

The load is the weight of the mass:

$$T = mg = 0.400 \times 10 = 4 \text{ N}.$$

By Hooke's law $T = kx$:

$$k = \frac{T}{x} = \frac{4}{0.08} = 50 \text{ N/m}.$$

(b) The new tension is $T = 0.650 \times 10 = 6.5 \text{ N}$, so

$$x = \frac{T}{k} = \frac{6.5}{50} = 0.13 \text{ m} = 13 \text{ cm}.$$

The total length is $L = l + x = 25 + 13 = 38 \text{ cm}$.

(c) A length of 40 cm means an extension $x = 40 - 25 = 15 \text{ cm} = 0.15 \text{ m}$. Then

$$T = kx = 50 \times 0.15 = 7.5 \text{ N}, \quad m = \frac{T}{g} = \frac{7.5}{10} = 0.75 \text{ kg} = 750 \text{ g}.$$

WORKED EXAMPLE 10 Spring constant from a graph

In an experiment, a student plots the load F (N) against the extension x (mm) of a spring and obtains a straight line through the origin passing through the point (60 mm, 3 N).

- State what this result shows about the spring.
- Calculate the spring constant in N/m.
- The points stop being collinear beyond $F = 6$ N. Interpret this observation.

SOLUTION

Solution. (a) Since the graph of F against x is a straight line through the origin, F is directly proportional to x : the spring obeys **Hooke's law** within the range tested.

(b) The gradient of the line is the spring constant:

$$k = \frac{F}{x} = \frac{3 \text{ N}}{60 \text{ mm}} = 0.05 \text{ N/mm} = 0.05 \times 1000 = 50 \text{ N/m}.$$

(c) Beyond $F = 6$ N the spring has passed its **limit of proportionality**: Hooke's law no longer applies, the extension increases faster than the load, and the spring will not return to its natural length when unloaded (permanent deformation).

WORKED EXAMPLE 11 Equilibrium with a vertical spring

A light spring of natural length 0.40 m and spring constant 120 N/m hangs vertically. A block is attached to its lower end and rests in equilibrium with the spring stretched to a total length of 0.55 m. Taking $g = 9.81 \text{ m s}^{-2}$, find the mass of the block.

SOLUTION

Solution. The extension is

$$x = L - l = 0.55 - 0.40 = 0.15 \text{ m}.$$

By Hooke's law the tension in the spring is

$$T = kx = 120 \times 0.15 = 18 \text{ N}.$$

The block is in equilibrium under two vertical forces: its weight mg downwards and the tension T upwards. Hence

$$mg = T \quad \Rightarrow \quad m = \frac{18}{9.81} \approx 1.83 \text{ kg}.$$

Notice how this example links the present section with the equilibrium conditions of the previous sections: Hooke's law gives us the magnitude of one of the forces, and equilibrium does the rest.

WORKED EXAMPLE 12 Elastic string: modulus of elasticity

An elastic string has natural length 1.2 m and modulus of elasticity $\lambda = 60$ N.

- (a) Find the tension in the string when it is stretched to a length of 1.5 m.
 (b) What length corresponds to a tension of 20 N?
 (c) Find the spring constant k of this string.

SOLUTION

Solution. (a) Extension $x = 1.5 - 1.2 = 0.3$ m. Using $T = \frac{\lambda x}{l}$:

$$T = \frac{60 \times 0.3}{1.2} = 15 \text{ N.}$$

(b) For $T = 20$ N: $x = \frac{Tl}{\lambda} = \frac{20 \times 1.2}{60} = 0.4$ m, so the length is $L = l + x = 1.2 + 0.4 = 1.6$ m.

(c) The spring constant is $k = \frac{\lambda}{l} = \frac{60}{1.2} = 50$ N/m. Check: $T = kx = 50 \times 0.3 = 15$ N.

10.5 Consolidation Exercises**EXERCISE 5** Exercise 1

A spring of natural length 20 cm extends to 26 cm under a load of 3 N. Assuming Hooke's law applies, find (a) the spring constant in N/m; (b) the extension produced by a load of 7.5 N; (c) the total length of the spring under that load.

EXERCISE 6 Exercise 2

The table below gives the results of an experiment on a spring.

Load F (N)	0	1	2	3	4	5
Length L (cm)	12.0	14.5	17.0	19.5	22.0	24.5

- (a) Copy the table and add a row for the extension x .
 (b) Plot F against x and state, with a reason, whether the spring obeys Hooke's law.
 (c) Deduce the spring constant in N/m.

EXERCISE 7 Exercise 3

An elastic string has natural length 1.2 m and modulus of elasticity $\lambda = 60$ N. Find the tension in the string when it is stretched to a length of 1.5 m. What length corresponds to a tension of 20 N?

EXERCISE 8 Exercise 4

A light spring of natural length 30 cm and spring constant 200 N/m is compressed until its length is 24 cm. Calculate the thrust exerted by the spring.

EXERCISE 9 Exercise 5

Two identical springs, each of natural length 20 cm and spring constant 40 N/m, are joined end to end (in series). The combination is suspended vertically and a mass of 500 g is attached. Find the total extension of the combination. (Take $g = 10 \text{ m s}^{-2}$.)

SOLUTION Exercise 1

(a) $x = 26 - 20 = 6 \text{ cm} = 0.06 \text{ m}$; $k = \frac{T}{x} = \frac{3}{0.06} = 50 \text{ N/m}$. (b) $x = \frac{T}{k} = \frac{7.5}{50} = 0.15 \text{ m} = 15 \text{ cm}$.
(c) $L = l + x = 20 + 15 = 35 \text{ cm}$.

SOLUTION Exercise 2

(a) The natural length is $l = 12.0 \text{ cm}$ (length at zero load), so the extensions are 0, 2.5, 5.0, 7.5, 10.0, 12.5 cm. (b) The graph of F against x is a straight line through the origin (each extra newton adds exactly 2.5 cm), so $F \propto x$: the spring obeys Hooke's law.
(c) $k = \frac{F}{x} = \frac{1 \text{ N}}{0.025 \text{ m}} = 40 \text{ N/m}$.

SOLUTION Exercise 3

Extension $x = 1.5 - 1.2 = 0.3 \text{ m}$. Using $T = \frac{\lambda x}{l}$:

$$T = \frac{60 \times 0.3}{1.2} = 15 \text{ N}.$$

For $T = 20 \text{ N}$: $x = \frac{Tl}{\lambda} = \frac{20 \times 1.2}{60} = 0.4 \text{ m}$, so the length is $L = l + x = 1.2 + 0.4 = 1.6 \text{ m}$.

SOLUTION Exercise 4

Compression $x = 30 - 24 = 6 \text{ cm} = 0.06 \text{ m}$. Thrust $T = kx = 200 \times 0.06 = 12 \text{ N}$.

SOLUTION Exercise 5

For springs in series, the tension is the same in each spring. $T = mg = 0.5 \times 10 = 5 \text{ N}$. Extension of one spring: $x_1 = T/k = 5/40 = 0.125 \text{ m}$. Total extension $x = 2x_1 = 0.25 \text{ m} = 25 \text{ cm}$. (Equivalent spring constant $k_{\text{eq}} = k/2 = 20 \text{ N/m}$, then $x = T/k_{\text{eq}} = 5/20 = 0.25 \text{ m}$.)

KEY POINTS Key points of the section

- Extension: $x = L - l$ (stretched length minus natural length) — never the total length.
- Hooke's law: $T = kx$ (or $T = \lambda x/l$ for strings), valid only within the **limit of proportionality**.
- The spring constant k (unit N/m) is the force per unit extension; it measures stiffness.
- For an elastic string, modulus $\lambda = kl$ (unit N).
- Experimental verification: plot F against x ; a straight line through the origin confirms the law, and its gradient is k .
- Beyond the limit of proportionality the graph curves and the spring is permanently deformed.
- In equilibrium problems, Hooke's law supplies the tension, which is then combined with the conditions of equilibrium ($\sum F = 0$).

11 APPLICATIONS OF HOOKE'S LAW AND SYNTHESIS

This section brings together Hooke's law with the equilibrium of forces, moments and couples studied earlier. We solve problems where springs or elastic strings provide one or more of the forces acting on a body. We also examine combinations of springs.

11.1 Springs in Series and Parallel

PROPERTY Equivalent spring constant

- Springs in series: The tension is the same in each spring. The total extension is the sum of individual extensions.

$$\frac{1}{k_{\text{eq}}} = \frac{1}{k_1} + \frac{1}{k_2} + \dots \quad \text{or} \quad k_{\text{eq}} = \left(\sum \frac{1}{k_i} \right)^{-1}.$$

- Springs in parallel: The extension is the same for each spring. The total force is the sum of individual forces.

$$k_{\text{eq}} = k_1 + k_2 + \dots$$

WORKED EXAMPLE 13 Springs in parallel supporting a load

Two springs, A and B, are suspended side by side (in parallel) from a rigid support. Spring A has $k_A = 80 \text{ N/m}$, spring B has $k_B = 120 \text{ N/m}$. A load of 10 N is attached to a light cross-bar that connects the lower ends of the springs, so that both springs stretch by the same amount. Find (a) the equivalent spring constant; (b) the extension of each spring; (c) the tension in each spring.

SOLUTION

Solution. (a) $k_{\text{eq}} = k_A + k_B = 80 + 120 = 200 \text{ N/m}$. (b) Common extension $x = \frac{F}{k_{\text{eq}}} = \frac{10}{200} = 0.05 \text{ m} = 5 \text{ cm}$. (c) $T_A = k_A x = 80 \times 0.05 = 4 \text{ N}$; $T_B = k_B x = 120 \times 0.05 = 6 \text{ N}$. Check: $T_A + T_B = 10 \text{ N} = \text{load}$.

11.2 Equilibrium Problems Involving Springs

METHOD Solving equilibrium problems with springs

1. Draw a clear **free-body diagram** of the particle or rigid body.
2. Identify all forces: weights, tensions, thrusts, reactions, friction.
3. For each spring or elastic string, write Hooke's law: $T = kx$ or $T = \lambda x/l$. Express x in terms of the geometry (e.g., $x = L - l$).
4. Apply the equilibrium conditions:

- For a particle: $\sum F_x = 0$, $\sum F_y = 0$ (or resolve in two convenient directions).
 - For a rigid body: $\sum F = 0$ and $\sum M = 0$ about any point.
5. Solve the resulting equations for the unknowns.
 6. Check that extensions are positive (strings go slack if $x \leq 0$) and that the limit of proportionality is not exceeded.

WORKED EXAMPLE 14 Particle on a rough inclined plane held by a spring

A particle of mass 2 kg rests on a rough plane inclined at 30° to the horizontal. It is held in equilibrium by a light spring of natural length 0.5 m and spring constant 100 N/m, attached to a fixed point up the plane. The spring is stretched to a length of 0.7 m. The coefficient of friction between the particle and the plane is $\mu = 0.2$. Taking $g = 10 \text{ m s}^{-2}$, verify that the particle is in equilibrium and find the friction force.

SOLUTION

Solution. Extension of spring: $x = 0.7 - 0.5 = 0.2 \text{ m}$. Spring tension (up the plane): $T = kx = 100 \times 0.2 = 20 \text{ N}$. Weight component down the plane: $mg \sin 30^\circ = 2 \times 10 \times 0.5 = 10 \text{ N}$. Normal reaction: $R = mg \cos 30^\circ = 20 \times \frac{\sqrt{3}}{2} = 10\sqrt{3} \approx 17.32 \text{ N}$. Maximum friction: $F_{\max} = \mu R = 0.2 \times 17.32 = 3.46 \text{ N}$. For equilibrium up the plane: $T = mg \sin 30^\circ + F$. $20 = 10 + F \Rightarrow F = 10 \text{ N}$. But $F = 10 \text{ N} > F_{\max} = 3.46 \text{ N}$. Conclusion: The particle cannot be in equilibrium with the given data; it would accelerate up the plane. The problem as stated is inconsistent — either the spring is not that stretched, or μ is larger, or the mass is larger. This illustrates the importance of checking consistency!

WORKED EXAMPLE 15 Rigid body with a spring: moment equilibrium

A uniform rod AB of length 2 m and weight 50 N is hinged at A to a vertical wall. The rod is held horizontal by a light spring of natural length 0.8 m and spring constant 150 N/m, attached to the rod at B and to a fixed point C on the wall directly above A, with AC = 1.2 m. Find the extension of the spring and the reaction at the hinge.

SOLUTION

Solution. Geometry: Triangle ABC is right-angled at A. $AB = 2 \text{ m}$, $AC = 1.2 \text{ m}$. Length of spring $BC = \sqrt{2^2 + 1.2^2} = \sqrt{4 + 1.44} = \sqrt{5.44} \approx 2.332 \text{ m}$. Extension $x = BC - l = 2.332 - 0.8 = 1.532 \text{ m}$. Spring tension $T = kx = 150 \times 1.532 = 229.8 \text{ N}$. Angle of spring with horizontal: $\sin \theta = \frac{AC}{BC} = \frac{1.2}{2.332} \approx 0.5146$, $\theta \approx 31.0^\circ$. Take moments about A (hinge): Clockwise: $W \times 1 = 50 \times 1 = 50 \text{ N m}$. Anticlockwise: vertical component of T at B: $T \sin \theta \times 2 = 229.8 \times 0.5146 \times 2 \approx 236.5 \text{ N m}$. Not equal! The rod would rotate. Let's find the correct

extension for equilibrium. Let x be the extension. Then $BC = 0.8 + x$. By Pythagoras: $(0.8 + x)^2 = 2^2 + 1.2^2 = 5.44$. $0.8 + x = \sqrt{5.44} \approx 2.332 \Rightarrow x \approx 1.532$ m (fixed by geometry). But then moment equilibrium gives $T \sin \theta \times 2 = 50$. $T = kx = 150x$. $\sin \theta = \frac{1.2}{0.8+x}$. Equation: $150x \times \frac{1.2}{0.8+x} \times 2 = 50$. $360x = 50(0.8 + x) = 40 + 50x$. $310x = 40 \Rightarrow x = \frac{40}{310} \approx 0.129$ m. Then $BC = 0.8 + 0.129 = 0.929$ m. But Pythagoras requires $BC = \sqrt{5.44} \approx 2.332$ m. Contradiction. Interpretation: The geometry ($AC=1.2$, $AB=2$) fixes the length BC . The spring cannot have a different length. Therefore, with the given spring constant and natural length, equilibrium is impossible unless the hinge provides a moment (but it's a hinge, so no moment). The problem is over-constrained. In a real exam, the numbers would be consistent. This example shows how to set up the equations: geometry + Hooke's law + equilibrium.

WORKED EXAMPLE 16 Consistent rigid body problem

A uniform rod AB of length 1.5 m and weight 30 N is hinged at A. It is held at 30° above the horizontal by a light spring attached at B. The spring has natural length 0.5 m, spring constant 200 N/m, and its other end is fixed to a point C on the same horizontal level as A, with $AC = 1.0$ m. Find the extension of the spring and the hinge reaction.

SOLUTION

Solution. Coordinates: $A = (0, 0)$. Rod at 30° : $B = (1.5 \cos 30^\circ, 1.5 \sin 30^\circ) = (1.299, 0.75)$. $C = (1.0, 0)$. Length $BC = \sqrt{(1.299 - 1.0)^2 + (0.75 - 0)^2} = \sqrt{0.299^2 + 0.75^2} = \sqrt{0.0894 + 0.5625} = \sqrt{0.6519} \approx 0.807$ m. Extension $x = 0.807 - 0.5 = 0.307$ m. Tension $T = 200 \times 0.307 = 61.4$ N. Angle of spring: $\tan \phi = \frac{0.75}{0.299} \approx 2.508$, $\phi \approx 68.2^\circ$ above horizontal. Moments about A: Weight: $30 \times (0.75 \cos 30^\circ) = 30 \times 0.6495 = 19.485$ N m clockwise. Spring: vertical component $T \sin \phi = 61.4 \times \sin 68.2^\circ \approx 61.4 \times 0.928 = 57.0$ N. Moment arm = horizontal distance of B from A = 1.299 m. Anticlockwise moment = $57.0 \times 1.299 \approx 74.0$ N m. Not equal! Again, the geometry fixes BC . For equilibrium, we need $T \sin \phi \times 1.299 = 19.485$. But $T = k(BC - 0.5)$ and BC , ϕ are fixed by geometry. So this specific setup is not in equilibrium unless the spring constant or natural length is different. Correct approach for exam problems: Usually, the geometry is such that the spring is horizontal or vertical, or the angle is given, and you solve for the extension that satisfies equilibrium. Let's do a standard one.

WORKED EXAMPLE 17 Standard equilibrium: horizontal rod, vertical spring

A uniform rod AB of length 2 m and weight 40 N is hinged at A to a vertical wall. The rod is held horizontal by a vertical spring attached at B. The spring has natural length 0.4 m and spring constant 500 N/m. Its upper end is fixed to a point on the wall directly above B. Find the extension of the spring and the reaction at the hinge.

SOLUTION

Solution. Spring is vertical at B. Let extension be x . Tension $T = 500x$ (upwards at B). Moments about A: $T \times 2 = 40 \times 1$ (weight acts at centre, 1 m from A). $1000x = 40 \Rightarrow x = 0.04 \text{ m} = 4 \text{ cm}$. $T = 500 \times 0.04 = 20 \text{ N}$. Vertical equilibrium: $R_A + T = 40 \Rightarrow R_A = 20 \text{ N}$ (upwards). Horizontal equilibrium: $H_A = 0$. Hinge reaction: 20 N vertically upward.

11.3 Elastic Potential Energy (Brief Introduction)

Although the syllabus focuses on forces and equilibrium, it is useful to know that work is done in stretching a spring, and this work is stored as **elastic potential energy** (EPE).

PROPERTY Elastic potential energy

For a spring or string obeying Hooke's law, the elastic potential energy stored when the extension is x is

$$E = \frac{1}{2}kx^2 = \frac{1}{2}\frac{\lambda x^2}{l} = \frac{1}{2}Tx.$$

This is the area under the $F-x$ graph (a triangle).

WARNING EPE and equilibrium

In static equilibrium problems, we do not usually need energy methods; force balance is sufficient. Energy methods become essential in dynamics (oscillations, projectiles with springs). For GCE Mechanics, know the formula but apply forces for equilibrium.

11.4 Synthesis: Examination-Style Problems**WORKED EXAMPLE 18 GCE-style: Spring balance calibration**

A spring balance has a scale of length 15 cm corresponding to a maximum load of 50 N. The spring obeys Hooke's law.

- Calculate the spring constant.
- A load of unknown weight stretches the spring by 9 cm. Find the weight.
- The same spring is used in a different balance where the scale is 20 cm long for the same maximum load. Explain how this is possible.

SOLUTION

Solution. (a) Maximum extension $x_{\max} = 0.15$ m, $F_{\max} = 50$ N. $k = \frac{F_{\max}}{x_{\max}} = \frac{50}{0.15} = 333.3$ N/m.
 (b) $x = 0.09$ m. $F = kx = 333.3 \times 0.09 = 30$ N. (c) The spring constant is unchanged. A longer scale for the same maximum load means the pointer moves further for the same force. This is achieved by using a longer pointer (lever arm) or a different gearing mechanism, not by changing the spring. The spring itself still extends only 15 cm for 50 N.

WORKED EXAMPLE 19 GCE-style: Two springs and a mass

A mass of 0.5 kg is attached to the midpoint of a light elastic string of natural length 2 m and modulus $\lambda = 20$ N. The ends of the string are fixed to two points A and B on the same horizontal level, with $AB = 2.4$ m. The mass hangs in equilibrium below AB. Find the vertical distance of the mass below AB.

SOLUTION

Solution. Let the mass be at M, distance d below AB. By symmetry, $AM = BM$. Half the natural length of string = 1 m. Half the distance $AB = 1.2$ m. Each half of the string has natural length $l = 1$ m, modulus $\lambda = 20$ N (modulus is for the whole string; for half the string, the modulus is the same because λ is a material property, but the spring constant doubles. Better: use $T = \frac{\lambda x}{l}$ for each half with its own l and x). Length of half-string = $\sqrt{1.2^2 + d^2}$. Extension of half-string $x = \sqrt{1.44 + d^2} - 1$. Tension in each half: $T = \frac{\lambda x}{l} = \frac{20(\sqrt{1.44 + d^2} - 1)}{1} = 20(\sqrt{1.44 + d^2} - 1)$. Vertical equilibrium: $2T \sin \theta = mg = 5$ N. $\sin \theta = \frac{d}{\sqrt{1.44 + d^2}}$.
 $2 \times 20(\sqrt{1.44 + d^2} - 1) \times \frac{d}{\sqrt{1.44 + d^2}} = 5$. $40d \left(1 - \frac{1}{\sqrt{1.44 + d^2}}\right) = 5$. $8d \left(1 - \frac{1}{\sqrt{1.44 + d^2}}\right) = 1$. Solve for d . Try $d = 0.2$: $\sqrt{1.44 + 0.04} = \sqrt{1.48} = 1.2166$. $8 \times 0.2(1 - 1/1.2166) = 1.6(1 - 0.822) = 1.6 \times 0.178 = 0.285$ too small. Try $d = 0.5$: $\sqrt{1.44 + 0.25} = \sqrt{1.69} = 1.3$. $8 \times 0.5(1 - 1/1.3) = 4(1 - 0.769) = 4 \times 0.231 = 0.924$. Try $d = 0.55$: $\sqrt{1.44 + 0.3025} = \sqrt{1.7425} = 1.32$. $8 \times 0.55(1 - 1/1.32) = 4.4(1 - 0.7576) = 4.4 \times 0.2424 = 1.066$. Try $d = 0.53$: $\sqrt{1.44 + 0.2809} = \sqrt{1.7209} = 1.3118$. $8 \times 0.53(1 - 1/1.3118) = 4.24(1 - 0.7623) = 4.24 \times 0.2377 = 1.008 \approx 1$. So $d \approx 0.53$ m.

11.5 Consolidation Exercises (Applications)**EXERCISE 10** Exercise 6

Two springs, of spring constants $k_1 = 100$ N/m and $k_2 = 150$ N/m, are connected (a) in series, (b) in parallel. Find the equivalent spring constant in each case. If a load of 10 N is applied, find the total extension in each case.

EXERCISE 11 Exercise 7

A light elastic string of natural length 0.8 m and modulus 40 N has one end fixed. A particle of mass 0.5 kg is attached to the other end and hangs in equilibrium. Find the extension of the string. (Take $g = 10 \text{ m s}^{-2}$.)

EXERCISE 12 Exercise 8

A uniform rod AB of weight W and length $2a$ is freely hinged at A. It is held in equilibrium at an angle of 30° to the horizontal by a light elastic string attached at B. The string has natural length a and modulus λ . Its other end is fixed to a point C on the vertical line through A, with $AC = a$. Find λ in terms of W .

EXERCISE 13 Exercise 9

A spring balance is calibrated by hanging known masses. The pointer reads 0 with no load. With a mass of 200 g, the pointer reads 4 cm. With a mass of 500 g, the pointer reads 10 cm.

- Show that the spring obeys Hooke's law.
- Find the spring constant.
- What mass gives a reading of 7 cm?

EXERCISE 14 Exercise 10

A block of mass 2 kg rests on a smooth plane inclined at 30° . It is held in equilibrium by a spring of natural length 0.5 m and spring constant 200 N/m, attached to a fixed point up the plane. The spring is parallel to the plane. Find the stretched length of the spring. (Take $g = 10 \text{ m s}^{-2}$.)

SOLUTION Exercise 6

(a) Series: $\frac{1}{k_{\text{eq}}} = \frac{1}{100} + \frac{1}{150} = \frac{5}{300} = \frac{1}{60} \Rightarrow k_{\text{eq}} = 60 \text{ N/m}$. Extension $x = F/k_{\text{eq}} = 10/60 = 0.1667 \text{ m}$. (b) Parallel: $k_{\text{eq}} = 100 + 150 = 250 \text{ N/m}$. Extension $x = 10/250 = 0.04 \text{ m}$.

SOLUTION Exercise 7

$$T = mg = 5 \text{ N}. T = \frac{\lambda x}{l} \Rightarrow 5 = \frac{40x}{0.8} = 50x \Rightarrow x = 0.1 \text{ m} = 10 \text{ cm}.$$

SOLUTION Exercise 8

Geometry: $AC = a$, $AB = 2a$, angle at $A = 30^\circ$. By cosine rule in triangle ABC : $BC^2 = a^2 + (2a)^2 - 2(a)(2a)\cos 30^\circ = a^2 + 4a^2 - 4a^2(\sqrt{3}/2) = 5a^2 - 2\sqrt{3}a^2$. $BC = a\sqrt{5 - 2\sqrt{3}} \approx a\sqrt{5 - 3.464} = a\sqrt{1.536} \approx 1.239a$. Extension $x = BC - a = a(\sqrt{5 - 2\sqrt{3}} - 1)$. Tension $T = \frac{\lambda x}{a} = \lambda(\sqrt{5 - 2\sqrt{3}} - 1)$. Moments about A : $T \times (2a) \times \sin(\text{angle between string and rod}) = W \times a \cos 30^\circ$. Angle between string and rod: use sine rule or coordinates. Simpler: vertical component of T at B . Coordinates: $A=(0,0)$, $B=(2a \cos 30^\circ, 2a \sin 30^\circ) = (a\sqrt{3}, a)$. $C=(0, a)$. Vector $CB = (a\sqrt{3}, 0)$. So string is horizontal! Length $BC = a\sqrt{3} \approx 1.732a$. Extension $x = a\sqrt{3} - a = a(\sqrt{3} - 1)$. Tension $T = \frac{\lambda a(\sqrt{3}-1)}{a} = \lambda(\sqrt{3} - 1)$. Moments about A : $T \times (\text{vertical distance of } B \text{ from } A) = T \times a$. Weight moment: $W \times (\text{horizontal distance of centre from } A) = W \times a \cos 30^\circ = Wa \frac{\sqrt{3}}{2}$. Equilibrium: $Ta = Wa \frac{\sqrt{3}}{2} \Rightarrow \lambda(\sqrt{3} - 1) = \frac{\sqrt{3}}{2}W \Rightarrow \lambda = \frac{\sqrt{3}W}{2(\sqrt{3}-1)} = \frac{\sqrt{3}(\sqrt{3}+1)W}{2(3-1)} = \frac{(3+\sqrt{3})W}{4}$.

SOLUTION Exercise 9

(a) Load $F_1 = 0.2 \times 10 = 2 \text{ N}$, $x_1 = 0.04 \text{ m}$. $F_2 = 0.5 \times 10 = 5 \text{ N}$, $x_2 = 0.10 \text{ m}$. Ratio $F_1/x_1 = 2/0.04 = 50$. $F_2/x_2 = 5/0.10 = 50$. Constant ratio $\Rightarrow$ Hooke's law obeyed. (b) $k = 50 \text{ N/m}$. (c) $x = 0.07 \text{ m}$. $F = kx = 50 \times 0.07 = 3.5 \text{ N}$. $m = F/g = 3.5/10 = 0.35 \text{ kg} = 350 \text{ g}$.

SOLUTION Exercise 10

Equilibrium along plane: $T = mg \sin 30^\circ = 2 \times 10 \times 0.5 = 10 \text{ N}$. $T = kx \Rightarrow 10 = 200x \Rightarrow x = 0.05 \text{ m}$. Stretched length $L = l + x = 0.5 + 0.05 = 0.55 \text{ m}$.

KEY POINTS Key points for Applications and Synthesis

- Springs in series: $\frac{1}{k_{\text{eq}}} = \sum \frac{1}{k_i}$; same tension, extensions add.
- Springs in parallel: $k_{\text{eq}} = \sum k_i$; same extension, tensions add.
- For elastic strings: $T = \frac{\lambda x}{l}$, $\lambda = kl$. Strings go slack if $x \leq 0$.
- Equilibrium problems: combine Hooke's law ($T = kx$) with $\sum F = 0$ and/or $\sum M = 0$.


- Always find extension from geometry first, then tension, then apply equilibrium.
- Check consistency: extensions must be positive, tensions must not exceed the limit of proportionality.
- Elastic potential energy $E = \frac{1}{2}kx^2$ is stored energy; useful for dynamics, not usually for static equilibrium.

12 APPLICATIONS OF HOOKE'S LAW AND SYNTHESIS

In the previous section we established Hooke's law, $F = kx$, and verified it experimentally. We now extend its use to systems of springs, to elastic strings (which behave differently from springs when compressed), and to the energy stored in a stretched spring. Finally, we synthesise a universal strategy for solving any equilibrium problem — the skill that distinguishes a good candidate in the GCE Advanced Level examination.

12.1 Springs in Series and Parallel

When several springs support the same load, their combined effect can be replaced by a single equivalent spring of stiffness k_{eq} . The rule depends on how the springs are arranged.



Springs in series (left) and in parallel (right) carrying the same load W . Extensions add in series; loads share in parallel.

Series: The tension T is the same in both springs. If the extensions are x_1 and x_2 , the total extension is $x = x_1 + x_2$. By Hooke's law, $x_1 = T/k_1$, $x_2 = T/k_2$. Hence

$$x = T \left(\frac{1}{k_1} + \frac{1}{k_2} \right) \implies \frac{1}{k_{\text{eq}}} = \frac{1}{k_1} + \frac{1}{k_2}.$$

Parallel: The extension x is the same for both springs. The total load is shared: $W = T_1 + T_2 = k_1x + k_2x = (k_1 + k_2)x$. Hence

$$k_{\text{eq}} = k_1 + k_2.$$

PROPERTY Equivalent Stiffness of Springs

For two springs of stiffnesses k_1 and k_2 :

- In series: they share the same tension; the equivalent stiffness k_s satisfies $\frac{1}{k_s} = \frac{1}{k_1} + \frac{1}{k_2}$.
The combination is less stiff than either spring alone.
- In parallel: they share the same extension; the equivalent stiffness is $k_p = k_1 + k_2$. The combination is stiffer than either spring alone.

These formulae extend to any number of springs. Proof is examinable.

EXAMPLE Springs in Series

A load of 20 N is suspended from two light springs joined in series. The upper spring has stiffness 40 N/m and the lower 60 N/m. Find the total extension and the extension of each spring.

$$\frac{1}{k_s} = \frac{1}{40} + \frac{1}{60} = \frac{5}{120} = \frac{1}{24} \Rightarrow k_s = 24 \text{ N/m.}$$

$$x_{\text{total}} = \frac{W}{k_s} = \frac{20}{24} = 0.833 \text{ m.}$$

$$x_1 = \frac{T}{k_1} = \frac{20}{40} = 0.5 \text{ m,} \quad x_2 = \frac{20}{60} = 0.333 \text{ m.}$$

Check: $0.5 + 0.333 = 0.833 \text{ m.} \equiv$

WARNING Common Mistake

Do not confuse the formulas: series uses reciprocals, parallel uses direct sum. A quick mental check: two identical springs of stiffness k in series give $k/2$ (softer), in parallel give $2k$ (stiffer).

12.2 Elastic Strings and the “Slack” Condition

An elastic string obeys Hooke’s law only when stretched beyond its natural length. Unlike a spring, a string cannot push; it goes slack (tension = 0) if its length is less than or equal to its natural length l_0 .

DEFINITION Elastic String

A light elastic string of natural length l_0 and modulus of elasticity λ (or stiffness $k = \lambda/l_0$)

exerts a tension

$$T = \frac{\lambda x}{l_0} = kx \quad \text{when stretched by } x > 0,$$

and $T = 0$ when $x \leq 0$ (i.e. length $\leq l_0$).

WARNING String Goes Slack — Critical Check

In any problem involving an elastic string, always verify whether the string is actually taut. If the geometry forces the string length to be $\leq l_0$, the tension is zero and the string exerts no force. Many candidates lose marks by writing $T = kx$ with a negative x .

EXAMPLE Elastic String on a Smooth Table

A particle of mass 0.5 kg is attached to one end of a light elastic string of natural length 1.2 m and modulus $\lambda = 24$ N. The other end is fixed at point O on a smooth horizontal table. The particle is pulled to a distance 2 m from O and released from rest. Find the initial acceleration.

$$x = 2 - 1.2 = 0.8 \text{ m}, \quad T = \frac{\lambda x}{l_0} = \frac{24 \times 0.8}{1.2} = 16 \text{ N}.$$

By Newton's second law: $T = ma \Rightarrow a = \frac{16}{0.5} = 32 \text{ m/s}^2$ towards O .

12.3 Elastic Potential Energy in a Spring

When a spring (or elastic string) is stretched, work is done against the tension. This work is stored as elastic potential energy (EPE). Since the tension varies linearly from 0 to kx , the average force is $\frac{1}{2}kx$, and the work done is $\frac{1}{2}kx \cdot x$.

PROPERTY Elastic Potential Energy

The elastic potential energy stored in a spring (or string) of stiffness k stretched by an amount x is

$$E_{\text{el}} = \frac{1}{2}kx^2 = \frac{\lambda x^2}{2l_0}.$$

This formula is an extra link to the Work–Energy chapter and is very useful in GCE problems involving conservation of energy.

EXAMPLE Energy Approach

A 0.2 kg mass is attached to a spring of stiffness 50 N/m on a smooth horizontal surface. The mass is pulled 0.1 m from equilibrium and released. Find its maximum speed.

$$E_{\text{el}} = \frac{1}{2}kx^2 = \frac{1}{2} \times 50 \times (0.1)^2 = 0.25 \text{ J.}$$

At equilibrium, all EPE becomes kinetic energy: $\frac{1}{2}mv^2 = 0.25 \Rightarrow v = \sqrt{\frac{0.5}{0.2}} = 1.58 \text{ m/s.}$

12.4 Combined Equilibrium Problems: Strings and Springs Together

Real problems often mix inextensible strings, elastic strings, and springs. The solution always follows the same pattern: draw a free-body diagram, resolve forces, apply equilibrium conditions ($\sum F_x = 0$, $\sum F_y = 0$, and $\sum M = 0$ if moments are needed), and solve.

WORKED EXAMPLE 20 Mixed System: Inextensible and Elastic Strings

A particle of weight 50 N is suspended by two strings: an inextensible string AP of length 1.2 m attached to a fixed point A , and a light elastic string BP of natural length 0.6 m and modulus $\lambda = 80 \text{ N}$ attached to a fixed point B . Points A and B are 1.5 m apart horizontally. The particle hangs in equilibrium with both strings taut. Find the tension in each string and the extension of BP .

Solution:

1. Geometry: Let the horizontal distance from A to P be d . The vertical drop is h . Since $AP = 1.2 \text{ m}$,

$$d^2 + h^2 = 1.2^2 = 1.44. \quad (1)$$

The horizontal distance from P to B is $1.5 - d$. The length of BP is $l = 0.6 + x$, where x is the extension. Hence

$$(1.5 - d)^2 + h^2 = (0.6 + x)^2. \quad (2)$$

2. Tension in BP : By Hooke's law,

$$T_{BP} = \frac{\lambda x}{l_0} = \frac{80x}{0.6} = \frac{400}{3}x. \quad (3)$$

3. Horizontal equilibrium: The horizontal components of the tensions balance.

$$T_{AP} \frac{d}{1.2} = T_{BP} \frac{1.5 - d}{0.6 + x}. \quad (4)$$

4. Vertical equilibrium: The vertical components support the weight.

$$T_{AP} \frac{h}{1.2} + T_{BP} \frac{h}{0.6 + x} = 50. \quad (5)$$

5. Solving: Subtract (1) from (2):

$$(1.5 - d)^2 - d^2 = (0.6 + x)^2 - 1.44 \implies 2.25 - 3d = (0.6 + x)^2 - 1.44.$$

$$3.69 - 3d = (0.6 + x)^2. \quad (6)$$

From (4) and (5), eliminate T_{AP} . From (4): $T_{AP} = T_{BP} \frac{1.2(1.5-d)}{d(0.6+x)}$. Substitute into (5):

$$T_{BP} \frac{1.2(1.5-d)}{d(0.6+x)} \cdot \frac{h}{1.2} + T_{BP} \frac{h}{0.6+x} = 50$$

$$T_{BP} \frac{h}{0.6+x} \left(\frac{1.5-d}{d} + 1 \right) = 50$$

$$T_{BP} \frac{h}{0.6+x} \cdot \frac{1.5}{d} = 50 \implies T_{BP} h = \frac{50d(0.6+x)}{1.5} = \frac{100}{3}d(0.6+x). \quad (7)$$

Substitute T_{BP} from (3):

$$\frac{400}{3}xh = \frac{100}{3}d(0.6+x) \implies 4xh = d(0.6+x). \quad (8)$$

Now we have three equations (1), (6), (8) for d, h, x . From (1): $h = \sqrt{1.44 - d^2}$. From (6): $0.6 + x = \sqrt{3.69 - 3d}$ (positive root). Substitute into (8):

$$4x\sqrt{1.44 - d^2} = d\sqrt{3.69 - 3d}.$$

Also $x = \sqrt{3.69 - 3d} - 0.6$. This system can be solved numerically or by noticing a neat solution. Try $d = 0.96$: $h = \sqrt{1.44 - 0.9216} = \sqrt{0.5184} = 0.72$. $0.6 + x = \sqrt{3.69 - 2.88} = \sqrt{0.81} = 0.9 \implies x = 0.3$. Check (8): LHS = $4 \times 0.3 \times 0.72 = 0.864$; RHS = $0.96 \times 0.9 = 0.864$. $\equiv$

6. Results:

$$x = 0.3 \text{ m}, \quad T_{BP} = \frac{400}{3} \times 0.3 = 40 \text{ N}, \quad T_{AP} = \frac{T_{BP}(1.5-d)}{d} \cdot \frac{1.2}{0.6+x} = \frac{40 \times 0.54}{0.96} \times \frac{1.2}{0.9} = 30 \text{ N}.$$


12.5 Chapter Synthesis: A Complete Strategy for Equilibrium Problems

Every equilibrium problem in this chapter — whether it involves forces, moments, couples, Hooke's law, or a mixture — can be solved by following a disciplined, step-by-step method. Master this flowchart and you will avoid the common pitfalls that cost easy marks.

METHOD Universal Equilibrium Strategy

1. Diagram: Draw a clear, labelled free-body diagram. Show all forces (weights, tensions, reactions, friction, spring forces) with their directions. Indicate dimensions and angles.

2. Choose axes: For forces, pick perpendicular axes (usually horizontal/vertical or parallel/perpendicular to a plane). For moments, choose a convenient pivot (often where unknown forces act to eliminate them from the moment equation).
3. Resolve forces: Write $\sum F_x = 0$ and $\sum F_y = 0$ (or $\sum F_{\parallel} = 0$, $\sum F_{\perp} = 0$). If the body is a rigid body, also write $\sum M_{\text{pivot}} = 0$.
4. Apply constitutive laws: For springs/strings, use $T = kx$ or $T = \lambda x/l_0$. Remember: elastic strings go slack if $x \leq 0$.
5. Solve the equations: Solve simultaneously for the unknowns (tensions, reactions, extensions, angles). Keep exact fractions until the final step.
6. Verify: Check units (N, m, Nm). Check sense: are tensions positive? Are extensions positive? Does the geometry make sense? If a string is found to have negative extension, it is actually slack — re-solve with $T = 0$ for that string.



Flowchart for solving any equilibrium problem. Follow the loop until all checks pass.

KEY POINTS Key Points for the Examination

- Springs in series: $\frac{1}{k_{\text{eq}}} = \frac{1}{k_1} + \frac{1}{k_2}$ (same tension, softer).
- Springs in parallel: $k_{\text{eq}} = k_1 + k_2$ (same extension, stiffer).

- Elastic strings: tension only when stretched ($x > 0$); slack when $x \leq 0$.
- Elastic potential energy: $E = \frac{1}{2}kx^2$ (links to conservation of energy).
- The universal strategy (diagram $\rightarrow$ axes $\rightarrow$ resolve $\rightarrow$ laws $\rightarrow$ solve $\rightarrow$ verify) works for every equilibrium question.

DID YOU KNOW? Did You Know?

The modulus of elasticity λ (in newtons) is the force required to double the length of a string of unit natural length. In Cameroon's rubber industry, the elasticity of latex threads is tested by measuring λ to ensure quality for products like elastic bands and medical tubing.

EXERCISE 15 Practice Problems

- Two springs of stiffness 30 N/m and 50 N/m are joined in series and a 40 N weight is attached. Find the total extension and the extension of each spring.
- A light elastic string of natural length 2 m and modulus 100 N has its ends fixed to two points 1.5 m apart on a horizontal line. A particle of weight 40 N is attached to the midpoint and hangs in equilibrium. Find the extension of each half of the string.
- A block of mass 2 kg rests on a rough plane inclined at 30° . It is held in equilibrium by a spring of stiffness 100 N/m fixed up the plane. The spring's natural length is 0.5 m and its length in equilibrium is 0.7 m. Find the coefficient of friction.
- (Synthesis) A uniform rod AB of length 2 m and weight 20 N is hinged at A . It is held horizontal by a light elastic string attached at B and to a point C vertically above A with $AC = 1.5$ m. The string has natural length 1.5 m and modulus 25 N. Find the angle the string makes with the horizontal and the reaction at the hinge.

SOLUTION Exercise 1

Series: $1/k_s = 1/30 + 1/50 = 8/150 = 4/75 \Rightarrow k_s = 18.75$ N/m. $x_{\text{total}} = 40/18.75 = 2.133$ m.
 $x_1 = 40/30 = 1.333$ m, $x_2 = 40/50 = 0.8$ m.

SOLUTION Exercise 2

Each half has natural length $l_0 = 1$ m. Horizontal distance from midpoint to each support

= 0.75 m. Let extension be x . Length of each half $l = 1+x$. Vertical drop $h = \sqrt{(1+x)^2 - 0.75^2} = \sqrt{x^2 + 2x + 0.4375}$. Tension $T = \frac{\lambda x}{l_0} = 100x$. Vertical equilibrium: $2T \frac{h}{l} = 40 \Rightarrow 200x \frac{h}{1+x} = 40 \Rightarrow 5xh = 1+x$. Substitute h : $5x\sqrt{x^2 + 2x + 0.4375} = 1+x$. Square: $25x^2(x^2 + 2x + 0.4375) = (1+x)^2$. This simplifies to $25x^4 + 50x^3 + 10.9375x^2 = x^2 + 2x + 1$. By inspection, $x = 0.25$ is a solution: LHS = $25(0.00390625) + 50(0.015625) + 10.9375(0.0625) = 0.09766 + 0.78125 + 0.68359 = 1.5625$; RHS = $(1.25)^2 = 1.5625$. Thus $x = 0.25$ m.

SOLUTION Exercise 3

Spring extension $x = 0.7 - 0.5 = 0.2$ m. Spring force $F_s = kx = 100 \times 0.2 = 20$ N up the plane. Weight component down plane = $mg \sin 30^\circ = 2 \times 9.8 \times 0.5 = 9.8$ N. Friction F_r acts down the plane (since spring pulls up). Equilibrium up plane: $F_s = mg \sin 30^\circ + F_r \Rightarrow 20 = 9.8 + F_r \Rightarrow F_r = 10.2$ N. Normal reaction $R = mg \cos 30^\circ = 19.6 \times \sqrt{3}/2 \approx 16.97$ N. $\mu = F_r/R = 10.2/16.97 \approx 0.60$.

SOLUTION Exercise 4

Geometry: $AC = 1.5$, $AB = 2$, angle at A is 90° (rod horizontal, AC vertical). So $BC = \sqrt{1.5^2 + 2^2} = 2.5$ m. String natural length = 1.5 m, so extension $x = 1.0$ m. Tension $T = \lambda x/l_0 = 25 \times 1.0/1.5 = 16.67$ N. Angle of string with horizontal: $\tan \theta = AC/AB = 1.5/2 = 0.75 \Rightarrow \theta \approx 36.87^\circ$. Moments about A: $T \sin \theta \times 2 = W \times 1 \Rightarrow 16.67 \times \sin 36.87^\circ \times 2 = 20 \times 1$. $\sin 36.87^\circ = 0.6$, LHS = $16.67 \times 0.6 \times 2 = 20.0$, RHS = 20. Equilibrium satisfied. Reaction at hinge: Horizontal $R_H = T \cos \theta = 16.67 \times 0.8 = 13.33$ N (towards C). Vertical $R_V = W - T \sin \theta = 20 - 10 = 10$ N (upwards). Magnitude $R = \sqrt{13.33^2 + 10^2} \approx 16.67$ N at angle $\tan^{-1}(10/13.33) \approx 36.87^\circ$ above horizontal.

13 INTEGRATION ACTIVITY

13.1 Aims of the activity

By the end of this integrative task, you should be able to:

- locate the **centre of gravity** of an irregular lamina experimentally by the plumb-line method and use it to choose a suspension point;
- apply the **conditions of equilibrium** of a particle (closed triangle of forces, Lami's theorem, resolution into components) to a real two-string suspension;
- use a **graphical method** (scale triangle of forces) to check an analytical result and comment on the accuracy of each approach;
- calibrate a spring, verify **Hooke's law** graphically, extract the spring constant from a gradient and graduate a scale in kilograms;
- communicate technical results in the form of a short user manual, as a technician or engineer would.

13.2 Situation

EXPERIMENT The weighing station of the Mokolo market

A women's cooperative that sells rice, groundnuts and dried fish at Mokolo market (Yaoundé) wants a cheap, reliable weighing station. The committee has asked your Upper Sixth class to design it. The station consists of:

- a flat tray cut from a sheet of cardboard (an irregular quadrilateral $ABCD$), of mass 2 kg, which must hang horizontally so that goods do not slide off;
- two light inextensible strings attached to the tray at two points and joined at a ring O fixed to a beam; when loaded, the strings make angles of 40° and 55° with the horizontal;
- a spring scale: a steel spring suspended from the beam, to be calibrated with standard masses and graduated up to 20 kg.

The heaviest single item sold is a 15 kg bag of rice. Take $g = 9.81 \text{ m s}^{-2}$. The cooperative also wants to know the greatest mass the spring can measure without being permanently damaged.

For the calibration, your group uses standard masses and a millimetre ruler. The unloaded spring has length $L_0 = 12.0 \text{ cm}$. The measurements are:

Mass m (kg)	0.5	1.0	1.5	2.0	2.5	3.0
Length L (cm)	13.0	14.0	15.1	16.0	17.1	18.0

Beyond an extension of 50 cm the spring does not return to its original length: this is its **elastic limit**.

13.3 Tasks

- Centre of gravity.** Describe, with a labelled diagram, the plumb-line experiment you would perform on the cardboard tray to locate its centre of gravity G . Explain why two pin-holes are enough in principle, and why a third is a good idea. Where should the two strings be attached (relative to G) for the tray to hang level?
- Equilibrium of the loaded tray.** The tray (2 kg) carries the 15 kg bag of rice placed so that the whole system hangs symmetrically; the junction ring O is then in equilibrium under three forces: the tensions T_1 (at 40° to the horizontal) and T_2 (at 55°), and the total weight W .
 - Compute W .
 - Draw the free-body diagram of the ring O .
 - Use **Lami's theorem** to find T_1 and T_2 .
 - Check your answers by **resolving** horizontally and vertically.
- Graphical verification.** Using a scale of 1 cm : 20 N, draw the triangle of forces for the three concurrent forces at O . Measure T_1 and T_2 and compare with Task 2. Comment on the agreement and on the sources of error of the graphical method.
- Calibrating the spring.** For each mass compute the load $F = mg$ and the extension $x = L - L_0$. Plot F (vertical axis) against x (horizontal axis). Is Hooke's law verified over this range? Determine the spring constant k from the gradient, giving its unit.
- Graduating the scale.** Using your value of k , compute the extension for loads of 5, 10, 15 and 20 kg, and explain how you would mark the scale in kilograms. Why are the graduations equally spaced?
- Safety limit.** The elastic limit corresponds to $x = 50$ cm. Find the greatest mass that may be hung without permanently deforming the spring. Is the requested 20 kg range safe?
- User manual.** Write a one-page manual for the trader: how to hang the tray, where to place the goods, how to read the spring scale, and the two safety warnings (maximum load, elastic limit).

13.4 Model answer


Task 1. Locating the centre of gravity.

Punch a small hole near a corner A of the tray and suspend the tray freely from a horizontal nail through the hole, so that it can turn without sticking. Hang a plumb line (a string with a small mass) from the same nail. When the tray is completely at rest, it is in equilibrium under exactly two forces: its **weight**, acting vertically downwards through G , and the **reaction** of the nail at the hole. Two forces in equilibrium must be equal, opposite and collinear; therefore G lies on

the vertical line through the nail, which is exactly the line of the plumb line. Draw this line on the cardboard with a pencil.

Repeat the experiment from a second hole near corner B : G also lies on the new plumb line. The intersection of the two lines is G . Two holes are enough in principle because two distinct lines meet in exactly one point. A third hole is a good idea as a check: the three lines should be concurrent. If they are not, the experiment was careless (friction at the nail, tray not perfectly still, plumb line swinging, pencil line drawn too thickly).

For the loaded tray to hang level, the strings must be attached at points such that the vertical through the junction ring O passes through the centre of gravity G of the loaded system (tray plus goods); otherwise the tray would tilt until this condition is met. In practice the strings are fixed at points placed symmetrically about G , and the goods are placed at the centre of the tray.




Plumb-line method: G lies on the vertical line drawn from the suspension hole.

Task 2. Equilibrium of the loaded tray.

(a) Total mass $M = 2 + 15 = 17$ kg, so

$$W = Mg = 17 \times 9.81 = 166.77 \text{ N} \approx 166.8 \text{ N}.$$

(b) The ring O is modelled as a particle in equilibrium under three concurrent forces: T_1 along the left string, T_2 along the right string, and W vertically downwards (the strings are light, so each tension is transmitted unchanged).



Free-body diagram of the loaded tray suspended by two strings.

(c) **Lami's theorem.** The angle between the two strings is $180^\circ - 40^\circ - 55^\circ = 85^\circ$; the angle between T_1 and the downward vertical is $90^\circ + 40^\circ = 130^\circ$; the angle between T_2 and the downward vertical is $90^\circ + 55^\circ = 145^\circ$. Lami's theorem states that each force is proportional to the sine of the angle between the other two:

$$\frac{T_1}{\sin 145^\circ} = \frac{T_2}{\sin 130^\circ} = \frac{W}{\sin 85^\circ}.$$

Hence

$$T_1 = \frac{166.77 \times \sin 145^\circ}{\sin 85^\circ} = \frac{166.77 \times 0.5736}{0.9962} \approx 96.0 \text{ N},$$

$$T_2 = \frac{166.77 \times \sin 130^\circ}{\sin 85^\circ} = \frac{166.77 \times 0.7660}{0.9962} \approx 128.2 \text{ N}.$$

(d) **Resolution check.** Horizontally, the components must cancel:

$$T_2 \cos 55^\circ = 128.2 \times 0.5736 \approx 73.5 \text{ N}, \quad T_1 \cos 40^\circ = 96.0 \times 0.7660 \approx 73.5 \text{ N}.$$

They balance. Vertically, the upward components must support the weight:

$$T_1 \sin 40^\circ + T_2 \sin 55^\circ = 96.0 \times 0.6428 + 128.2 \times 0.8192 \approx 61.7 + 105.0 = 166.7 \text{ N} \approx W.$$

Both conditions of equilibrium are satisfied, which confirms the Lami calculation.

WARNING Choosing the angles in Lami's theorem

The angle used with each force is the angle between the other two forces, measured at the point of concurrence. A very common error is to use 40° and 55° directly instead of 130° , 145° and 85° . Always draw the three forces meeting at one point and read off the three angles between them.

Task 3. Graphical verification.

Draw $W = 166.8 \text{ N}$ vertically downward as a segment of length $\frac{166.8}{20} = 8.34 \text{ cm}$. From its upper end draw a line at 40° to the horizontal (direction of T_1) and from its lower end a line at 55° to

the horizontal (direction of T_2); their intersection closes the triangle of forces. Measuring the two unknown sides gives about 4.8 cm and 6.4 cm, i.e. $T_1 \approx 96$ N and $T_2 \approx 128$ N, in excellent agreement with Task 2.




Closed triangle of forces at O (not to scale): the three vectors add to zero.

Small discrepancies come from protractor and ruler reading errors (about $\pm 0.5^\circ$ and ± 0.5 mm). The analytical method is more precise; the graphical method is faster and gives an immediate visual check that the triangle closes.

Task 4. Calibrating the spring.

With $L_0 = 12.0$ cm, $F = mg$ and $x = L - L_0$:

$F = mg$ (N)	4.91	9.81	14.72	19.62	24.53	29.43
x (cm)	1.0	2.0	3.1	4.0	5.1	6.0



Load against extension: the points lie on a straight line through the origin.

The points lie on a straight line through the origin, so F is proportional to x : **Hooke's law** $F = kx$ is verified over this range. Using two well-separated points on the best-fit line, the gradient is

$$k = \frac{\Delta F}{\Delta x} = \frac{29.43 - 4.91}{(6.0 - 1.0) \times 10^{-2}} = \frac{24.52}{0.05} \approx 490 \text{ N m}^{-1}.$$

The unit is the newton per metre, since $k = F/x$.

WARNING Units in the gradient

Convert the extension to metres before dividing: using centimetres would give $k = 4.9 \text{ N cm}^{-1}$, which is the same constant but not the SI value expected at the GCE. State $k \approx 490 \text{ N m}^{-1}$.

Task 5. Graduating the scale.

With $k = 490 \text{ N m}^{-1}$, the extension for a mass m is $x = \frac{mg}{k}$:

Mass (kg)	5	10	15	20
F (N)	49.05	98.1	147.2	196.2
x (cm)	10.0	20.0	30.0	40.0

Fix a strip of card behind the spring, mark the pointer positions corresponding to these extensions and label them 5, 10, 15, 20 kg. Because x is proportional to m (Hooke's law), equal steps of mass produce equal steps of extension: the graduations are equally spaced, here 2 cm per kilogram, so intermediate marks (every kilogram, or every 500 g) can be added by simple division of the intervals.

Task 6. Safety limit.

At the elastic limit, $x_{\max} = 50 \text{ cm} = 0.50 \text{ m}$, so

$$F_{\max} = kx_{\max} = 490 \times 0.50 = 245 \text{ N}, \quad m_{\max} = \frac{F_{\max}}{g} = \frac{245}{9.81} \approx 25.0 \text{ kg}.$$

The requested 20 kg range is safe, with a margin of about 5 kg before the elastic limit is reached. Beyond 25 kg the spring would be permanently stretched and every subsequent reading would be wrong.

Task 7. User manual (model content).

METHOD Weighing station: instructions for the trader

1. Hanging the tray. Suspend the tray by its two strings so that the vertical line through the ring O passes through the centre mark G painted on the tray; the tray then hangs level.
2. Placing the goods. Always place the goods at the centre of the tray, directly above G , so that the tray stays horizontal and the strings share the load as designed.
3. Reading the scale. Hang the item on the spring hook, wait until the pointer is still, and read it at eye level to avoid parallax error.
4. Safety warning 1. Never put more than 20 kg on the scale: the graduations stop there.
5. Safety warning 2. Never load the spring beyond 25 kg: the spring would pass its elastic limit, stay permanently stretched, and all readings would become false.

KEY POINTS What this activity mobilises

Locating a centre of gravity experimentally by the plumb-line method; the conditions of equilibrium of a particle (zero resultant, closed triangle of forces); Lami's theorem and resolution into components as two equivalent analytical tools; the scale triangle of forces as a graphical check; Hooke's law $F = kx$, its graphical verification and the reading of a gradient to obtain k ; and the practical meaning of the elastic limit as the greatest load an instrument can bear without permanent damage.

14 METHODS AND WORKED EXAMPLES

15 EQUILIBRIUM, FORCES, MOMENTS AND COUPLES

15.1 Introduction and Learning Outcomes

KEY POINTS What you will master in this chapter

- The concept of **equilibrium** for particles and rigid bodies: translational and rotational equilibrium.
- The **centre of gravity** (or centre of mass) of a body and how to locate it experimentally and by calculation.
- Forces as vectors: addition by the parallelogram/triangle rule, resolution into components, and the use of free-body diagrams.
- The **resultant** and **equilibrant** of a system of coplanar forces; graphical and analytical methods.
- The **moment of a force** and the **couple**; the principle of moments and conditions for equilibrium of a rigid body.
- **Hooke's law** for elastic springs and strings: experimental verification, spring constant, energy stored, and combinations of springs (series and parallel).
- Solving complete equilibrium problems involving suspended bodies, bodies on inclined planes, and systems of springs.

DID YOU KNOW? Why this matters

From the roof trusses of a house in Douala to the suspension cables of the Wouri Bridge, every structure that stands still obeys the same two conditions: the vector sum of the forces is zero, and the sum of the moments about any point is zero. Mastering these ideas lets you analyse and design safe, stable systems — a core skill for any engineer or physicist.

16 EQUILIBRIUM AND CENTRE OF GRAVITY

DEFINITION Equilibrium of a particle and a rigid body

A particle is in equilibrium if the vector sum of all forces acting on it is zero:

$$\sum \vec{F} = \vec{0}.$$

A rigid body is in complete equilibrium if two conditions hold simultaneously:

1. Translational equilibrium: $\sum \vec{F} = \vec{0}$ (no net force, centre of mass does not accelerate).
2. Rotational equilibrium: $\sum \vec{M} = \vec{0}$ about any point (no net moment, body does not rotate).

For coplanar forces these give three independent scalar equations:

$$\sum F_x = 0, \quad \sum F_y = 0, \quad \sum M_O = 0 \quad (\text{about any point } O).$$

PROPERTY Centre of gravity (centre of mass)

The **centre of gravity** G of a body is the point through which the resultant of the gravitational forces on all its particles (the weight $W = mg$) acts, for any orientation of the body. For a uniform body in a uniform gravitational field, G coincides with the geometric centre (centroid).

- Uniform rod: midpoint.
- Uniform rectangular lamina: intersection of diagonals.
- Uniform triangular lamina: centroid (intersection of medians), at $\frac{1}{3}$ of the median from the base.
- Uniform solid hemisphere: $3R/8$ from the flat face on the axis of symmetry.

PROPERTY Equilibrium of a suspended body

A body suspended from a fixed point O by a string or a smooth hinge comes to rest with its centre of gravity G vertically below O . The line of action of the weight passes through O , so the moment of the weight about O is zero. If the body is slightly displaced, the weight produces a restoring moment (stable equilibrium).

METHOD Testing the equilibrium of a suspended body

1. Identify all forces: weight $W = mg$ acting vertically downward through G , and the ten-

sion(s) or reaction(s) at the support(s).

2. Apply the first condition: $\sum \vec{F} = \vec{0}$.
3. For a body hanging from one point: at equilibrium G is vertically below the suspension point.
4. For a body supported by two strings: the three forces are concurrent (lines of action meet at one point).
5. If the body can rotate, apply the second condition: $\sum M = 0$ about any convenient point (often the suspension point).

Reflex: always sketch the body slightly displaced; the weight must produce a restoring moment for stable equilibrium.

WORKED EXAMPLE 21 A hanging signboard in Buea

A uniform rectangular signboard $ABCD$ of mass 12 kg hangs from a nail at the midpoint O of its top edge AB . The board is 1.2 m wide and 0.8 m high. (a) Describe the position of the board at equilibrium. (b) A horizontal wind force of 20 N acts at the centre of the board. Through what angle does the board turn? Take $g = 9.81 \text{ m s}^{-2}$.

SOLUTION

Solution.

1. Forces. Weight $W = mg = 12 \times 9.81 = 117.72 \text{ N}$ acts at G , the geometric centre of the uniform board; the reaction of the nail acts at O .
2. (a) With no wind, the only two forces are W and the reaction at O . For equilibrium they must be collinear, so G hangs vertically below O : the board hangs straight, with AB horizontal.
3. (b) With the wind force $F = 20 \text{ N}$ horizontal through G , take moments about O when the board has turned through an angle θ . The perpendicular distance from O to the line of action of F is $OG \cos \theta$; the perpendicular distance to the line of action of W is $OG \sin \theta$, where $OG = 0.4 \text{ m}$ (half the height).
4. Moment balance about O (clockwise positive):

$$F \cdot OG \cos \theta = W \cdot OG \sin \theta \implies \tan \theta = \frac{F}{W} = \frac{20}{117.72} = 0.1699.$$

5. Hence $\theta = \tan^{-1}(0.1699) \approx 9.65^\circ$.

Answer: (a) G vertically below O ; (b) the board tilts through about 9.7° .

EXPERIMENT Locating the centre of gravity of an irregular lamina (plumb-line method)

1. Cut the lamina (cardboard, thin plywood) to shape. Make three small holes A, B, C near the edge.
2. Suspend the lamina freely from a pin through hole A . Hang a **plumb line** (string with a small bob) from the same pin.
3. When oscillations cease, mark the vertical line of the plumb line on the lamina. The centre of gravity G lies on this line.
4. Repeat from holes B and C , drawing the plumb line each time.
5. The three lines should intersect at a single point — that point is G .
6. Verification: balance the lamina horizontally on a sharp point (e.g. a needle) placed under G ; it should remain horizontal.

Precautions: the lamina must swing freely (no friction at the pin), the plumb line must be still before marking, holes must be small so as not to shift G appreciably, and the lamina must be uniform in thickness and density.

WORKED EXAMPLE 22 Locating G of a triangular lamina

A student cuts a triangular lamina with vertices $A(0, 0)$, $B(12, 0)$, $C(0, 9)$ (coordinates in cm) from uniform cardboard. (a) State how she would locate G experimentally. (b) Compute the exact position of G and compare. (c) The lamina is suspended from A ; find the angle that AB makes with the vertical at equilibrium.

SOLUTION

Solution.

1. (a) She suspends the lamina from a pin through a hole near A , marks the plumb line; repeats from a hole near B ; the intersection of the two lines gives G . A third suspension from C serves as a check.
2. (b) For a uniform triangular lamina, G is at the centroid:

$$x_G = \frac{0 + 12 + 0}{3} = 4 \text{ cm}, \quad y_G = \frac{0 + 0 + 9}{3} = 3 \text{ cm}.$$

So $G = (4, 3)$ cm, which should coincide with the experimental intersection.

3. (c) Suspended from A , G hangs vertically below A . The line AG has slope $\frac{3}{4}$ to the horizontal, so it makes $\tan^{-1}(3/4) = 36.87^\circ$ with the horizontal, hence $90^\circ - 36.87^\circ = 53.13^\circ$ with the vertical. Since AB is along the x -axis (horizontal), at equilibrium AG is vertical, so AB makes 53.13° with the vertical (or 36.87° with the horizontal).

Answer: $G = (4, 3)$ cm; AB makes 53.1° with the vertical.

17 FORCE AS A VECTOR; ADDITION AND RESOLUTION

DEFINITION Force as a vector

A **force** is a vector quantity: it has magnitude (in newtons, N), direction, and sense. It is represented by an arrow whose length is proportional to the magnitude (according to a chosen scale) and whose direction and sense match the force. Forces obey the parallelogram law of addition.

PROPERTY Addition of forces — resultant

The **resultant** $\vec{R}$ of two forces $\vec{F}_1$ and $\vec{F}_2$ is the single force that has the same effect as the two acting together. It is the diagonal of the parallelogram constructed on $\vec{F}_1$ and $\vec{F}_2$:

$$\vec{R} = \vec{F}_1 + \vec{F}_2.$$

Magnitude: $R = \sqrt{F_1^2 + F_2^2 + 2F_1F_2 \cos \theta}$, where θ is the angle between $\vec{F}_1$ and $\vec{F}_2$. Direction: $\tan \alpha = \frac{F_2 \sin \theta}{F_1 + F_2 \cos \theta}$ (angle with $\vec{F}_1$).

PROPERTY Resolution of a force into components

Any force $\vec{F}$ can be replaced by two (or more) component forces whose vector sum is $\vec{F}$. For perpendicular axes Ox and Oy , if $\vec{F}$ makes an angle θ with Ox :

$$F_x = F \cos \theta, \quad F_y = F \sin \theta.$$

Memory aid: the component adjacent to the angle uses cos; the component opposite uses sin.

METHOD Resolving a force — inclined plane reflex

1. Draw the force $\vec{F}$ and choose two perpendicular axes (often along and perpendicular

to a plane).

- If F makes an angle θ with an axis, the component along that axis is $F \cos \theta$ and the component perpendicular to it is $F \sin \theta$.
- Replace $\vec{F}$ by its components and work with each axis separately.
- Inclined plane: for a body of weight W on a plane inclined at α to the horizontal, resolve the weight:

$$W_{\parallel} = W \sin \alpha \text{ (down the slope),} \quad W_{\perp} = W \cos \alpha \text{ (into the plane).}$$

- Equilibrium: sum of components along each axis equals zero. On a smooth plane, the normal reaction is $R = W \cos \alpha$.

WORKED EXAMPLE 23 Crate on a smooth ramp

A crate of mass 50 kg rests on a smooth plank inclined at 25° to the horizontal, held at rest by a rope parallel to the plank. Find (a) the tension in the rope, (b) the normal reaction of the plank. Take $g = 9.81 \text{ m s}^{-2}$.

SOLUTION

Solution.


- Forces: weight $W = mg = 50 \times 9.81 = 490.5 \text{ N}$ vertically down; normal reaction R perpendicular to the plank; tension T up the plank.
- Resolve W : along the plane $W \sin 25^\circ$ (down-slope); perpendicular $W \cos 25^\circ$ (into the plane).
- (a) Equilibrium along the plane (up positive):

$$T - W \sin 25^\circ = 0 \implies T = 490.5 \times \sin 25^\circ = 490.5 \times 0.4226 = 207.3 \text{ N.}$$

- (b) Equilibrium perpendicular to the plane (outward positive):

$$R - W \cos 25^\circ = 0 \implies R = 490.5 \times \cos 25^\circ = 490.5 \times 0.9063 = 444.5 \text{ N.}$$

Answer: $T \approx 207 \text{ N}$, $R \approx 445 \text{ N}$.



18 TYPES OF FORCES AND FREE-BODY DIAGRAMS

DEFINITION Common forces in mechanics

- Weight $W = mg$: acts vertically downward through the centre of gravity.
- Normal reaction R (or N): perpendicular to the contact surface, pushes away from the surface.
- Friction F_f : parallel to the contact surface, opposes relative motion (or tendency). Maximum static friction $F_{\max} = \mu_s R$; kinetic friction $F_k = \mu_k R$.
- Tension T : in a taut string/rope, pulls along the string away from the body.
- Thrust/Compression: in a rod/strut, pushes along the rod toward the body.
- Applied forces: pushes, pulls, wind, etc., specified in the problem.

METHOD Drawing a free-body diagram (FBD)

1. Isolate the body of interest (imagine it cut free from its surroundings).
2. Draw the body as a simple shape (dot, box, outline).
3. Show all external forces acting on the body, with arrows starting on the body. Label each force clearly (W , R , T_1 , F , etc.).
4. Do not show forces exerted by the body on other objects, nor internal forces.
5. Indicate known angles and dimensions; choose coordinate axes.

Golden rule: if you miss a force, your equations will be wrong. Check: gravity? contact? strings? applied?


WORKED EXAMPLE 24 Free-body diagrams practice

Draw the FBD for: (a) a block at rest on a rough inclined plane; (b) a picture frame hanging from two strings attached to its top corners; (c) a uniform ladder leaning against a smooth wall on rough ground.

SOLUTION

Solution.

1. (a) Block on rough incline: weight W vertically down; normal reaction R perpendicular to plane; friction F up the plane (opposing tendency to slide down).
2. (b) Picture frame: weight W down at centre; tensions T_1, T_2 along strings, pulling upward and inward at the corners.
3. (c) Ladder: weight W down at midpoint; at top (smooth wall) normal reaction R_W horizontal; at bottom (rough ground) normal reaction R_G vertical and friction F_G horizontal (toward wall to prevent slipping out).



19 RESULTANT AND EQUILIBRANT; GRAPHICAL METHODS

DEFINITION Resultant and equilibrant

The **resultant** $\vec{R}$ of a system of forces is the single force that produces the same effect as the whole system. The **equilibrant** $\vec{E}$ is the single force that, when added to the system, brings it into equilibrium:

$$\vec{E} = -\vec{R}.$$

The equilibrant has the same magnitude as the resultant but the opposite direction.

METHOD Graphical determination of resultant — parallelogram and polygon rules

Two forces (parallelogram rule):

1. Choose a suitable **scale** (e.g. $1 \text{ cm} \equiv 10 \text{ N}$).
2. From a point O , draw the two forces to scale with the correct angle between them.
3. Complete the parallelogram; the diagonal from O is the resultant. Measure its length and convert with the scale; measure its direction with a protractor.

Several forces (polygon rule):

1. Draw the forces head-to-tail in any order, each to scale and in the correct direction.
2. The resultant is the vector from the start of the first to the end of the last.
3. If the polygon closes, the resultant is zero: the forces are in equilibrium (the closing side, drawn in the opposite sense, is the equilibrant).

Reflex: the equilibrant is equal in magnitude to the resultant but opposite in direction.

WORKED EXAMPLE 25 Two tug-of-war teams

Two teams pull a tyre at a school sports day in Bamenda with forces $F_1 = 300$ N due east and $F_2 = 400$ N at 60° north of east. (a) Find the resultant graphically. (b) Confirm the result by calculation. (c) State the equilibrant.

SOLUTION

Solution.

1. (a) Graphical: scale $1 \text{ cm} \equiv 50 \text{ N}$. Draw $\vec{F}_1$ as 6 cm east; from its head draw $\vec{F}_2$ as 8 cm at 60° to the east direction. The closing vector from the start measures about 12.2 cm, i.e. $R \approx 610$ N, at about 35° north of east.
2. (b) Analytical check. Components (east = x , north = y):

$$R_x = 300 + 400 \cos 60^\circ = 300 + 200 = 500 \text{ N},$$

$$R_y = 400 \sin 60^\circ = 346.4 \text{ N}.$$

$$R = \sqrt{500^2 + 346.4^2} = \sqrt{250000 + 120000} = \sqrt{370000} = 608.3 \text{ N}.$$

$$\tan \theta = \frac{346.4}{500} = 0.6928 \implies \theta = 34.7^\circ.$$

The graphical and analytical results agree (small differences come from drawing accuracy).

3. (c) Equilibrant: $E = 608.3$ N directed at 34.7° south of west (opposite to $\vec{R}$).

Answer: $R \approx 608$ N at 34.7° north of east; equilibrant equal and opposite.

20 ANALYTICAL METHODS AND EQUILIBRIUM PROBLEMS

METHOD Component method for concurrent coplanar forces

1. Draw a clear **free-body diagram**: isolate the body and show only the external forces on it.
2. Choose axes Ox, Oy (horizontal/vertical, or along/perpendicular to a plane).
3. Resolve every force: $F_x = F \cos \theta, F_y = F \sin \theta$, with careful signs.
4. Sum components: $R_x = \sum F_x, R_y = \sum F_y$.
5. Resultant: $R = \sqrt{R_x^2 + R_y^2}$, direction $\tan \theta = \left| \frac{R_y}{R_x} \right|$ (fix the quadrant from the signs of R_x, R_y).
6. Equilibrium: $R_x = 0$ and $R_y = 0$ — two scalar equations, enough to find two unknowns.

WORKED EXAMPLE 26 Picture frame on two strings

A picture frame of weight 60 N hangs from a nail by two strings attached to its top corners. The left string makes 30° with the vertical and the right string 45° with the vertical. Find the tensions T_1 and T_2 in the strings.

SOLUTION

Solution.

1. Free-body diagram: three concurrent forces on the frame: T_1 at 30° left of vertical, T_2 at 45° right of vertical, $W = 60$ N downward.
2. Horizontal equilibrium ($\sum F_x = 0$), right positive:

$$T_2 \sin 45^\circ - T_1 \sin 30^\circ = 0 \implies 0.7071 T_2 = 0.5 T_1 \implies T_1 = 1.4142 T_2.$$

3. Vertical equilibrium ($\sum F_y = 0$), up positive:

$$T_1 \cos 30^\circ + T_2 \cos 45^\circ - 60 = 0 \implies 0.8660 T_1 + 0.7071 T_2 = 60.$$

4. Substitute $T_1 = 1.4142 T_2$:

$$0.8660(1.4142 T_2) + 0.7071 T_2 = 60 \implies 1.2247 T_2 + 0.7071 T_2 = 60,$$

$$1.9319 T_2 = 60 \implies T_2 = 31.06 \text{ N}.$$

5. Then $T_1 = 1.4142 \times 31.06 = 43.92$ N.

6. Check: vertical: $43.92 \cos 30^\circ + 31.06 \cos 45^\circ = 38.03 + 21.97 = 60.00$ N. ✓

Answer: $T_1 \approx 43.9$ N, $T_2 \approx 31.1$ N.

PROPERTY Moment of a force and couple

The **moment** (or torque) of a force $\vec{F}$ about a point O is $M_O = F \times d$, where d is the perpendicular distance from O to the line of action of $\vec{F}$. Units: N m. Sign convention: anticlockwise positive. A **couple** consists of two equal and opposite parallel forces F and $-F$ separated by a perpendicular distance d . Its moment is Fd (same about any point) and it produces pure rotation without translation.

PROPERTY Principle of moments

For a body in rotational equilibrium under coplanar forces, the sum of the clockwise moments about any point equals the sum of the anticlockwise moments about that point:

$$\sum M_{\text{clockwise}} = \sum M_{\text{anticlockwise}}$$

Equivalently, $\sum M_O = 0$ for any point O .

METHOD Solving rigid-body equilibrium problems

1. Draw a complete free-body diagram showing all forces (weights, reactions, tensions, applied forces) with their points of application.
2. Choose a point to take moments about — ideally a point where unknown forces act (their moments are then zero).
3. Write the moment equation $\sum M = 0$.
4. Write the two force-component equations $\sum F_x = 0$, $\sum F_y = 0$.
5. Solve the system (up to three equations for three unknowns).
6. Check: do the forces balance? Do the moments balance about a different point?

WORKED EXAMPLE 27 Uniform beam on two supports

A uniform beam AB of length 4.0 m and mass 20 kg rests on two supports at A and C , where C is 1.0 m from B . A load of mass 30 kg is placed at B . Find the reactions at A and C . Take $g = 9.81 \text{ m s}^{-2}$.

SOLUTION

Solution.

1. Forces: $W_{\text{beam}} = 20g = 196.2 \text{ N}$ at midpoint (2.0 m from A); $W_{\text{load}} = 30g = 294.3 \text{ N}$ at B (4.0 m from A); reactions R_A at A, R_C at C (3.0 m from A). All vertical.

2. Moments about A (anticlockwise +):

$$R_C \times 3.0 - 196.2 \times 2.0 - 294.3 \times 4.0 = 0$$

$$3R_C = 392.4 + 1177.2 = 1569.6 \Rightarrow R_C = 523.2 \text{ N}.$$

3. Vertical equilibrium:

$$R_A + R_C = 196.2 + 294.3 = 490.5 \Rightarrow R_A = 490.5 - 523.2 = -32.7 \text{ N}.$$

4. Interpretation: R_A is negative, meaning the beam would lift off support A; the beam is not in equilibrium on both supports with this load at B — it would tip about C. (If the problem insists both supports are in contact, the load position must be changed.)

Answer: With the given data, R_A is negative, so the beam tips about C; A loses contact.

WORKED EXAMPLE 28 Ladder against a smooth wall

A uniform ladder of length 5.0 m and mass 15 kg leans against a smooth vertical wall with its foot on rough horizontal ground. The ladder makes an angle of 60° with the horizontal. Find (a) the normal reaction of the wall, (b) the frictional force at the ground, (c) the minimum coefficient of friction to prevent slipping. Take $g = 9.81 \text{ m s}^{-2}$.

SOLUTION

Solution.

1. Forces: $W = 15g = 147.15 \text{ N}$ at midpoint (2.5 m from foot); R_W horizontal at top (smooth wall); R_G vertical at foot; F horizontal at foot (friction, toward wall).

2. Moments about foot O (anticlockwise +):

$$R_W \times (5 \sin 60^\circ) - W \times (2.5 \cos 60^\circ) = 0$$

$$R_W \times 4.330 - 147.15 \times 1.25 = 0 \Rightarrow R_W = \frac{183.94}{4.330} = 42.5 \text{ N}.$$

3. Horizontal equilibrium: $F = R_W = 42.5 \text{ N}$.

4. Vertical equilibrium: $R_G = W = 147.15 \text{ N}$.

5. Minimum μ : $F \leq \mu R_G \Rightarrow \mu_{\min} = \frac{F}{R_G} = \frac{42.5}{147.15} = 0.289$.

Answer: (a) $R_W = 42.5 \text{ N}$; (b) $F = 42.5 \text{ N}$; (c) $\mu_{\min} = 0.289$.

21 HOOKE'S LAW AND ITS EXPERIMENTAL VERIFICATION

PROPERTY Hooke's law

Within the **elastic limit**, the extension e of a spring (or elastic string) is directly proportional to the stretching force F :

$$F = ke,$$

where k is the **spring constant** (stiffness) in N m^{-1} . The force exerted by the spring is $\vec{F}_{\text{spring}} = -k\vec{e}$ (restoring force).

METHOD Experimental verification of Hooke's law

1. Hang a **spring** vertically from a clamp with a pointer and a millimetre ruler beside it. Record the pointer reading x_0 with no load (unstretched position).
2. Add a known mass m , wait until the spring is still, and record the new reading x . The extension is $e = x - x_0$ and the stretching force is $F = mg$.
3. Increase the load in equal steps, recording x each time; unload step by step and check the readings repeat (no permanent stretch).
4. Never exceed the elastic limit: stop if the spring does not return to x_0 when unloaded.
5. Plot F (y-axis) against e (x-axis). Hooke's law is verified if the points lie on a straight line through the origin.
6. The gradient of the line is the spring constant: $k = \frac{F}{e}$, in N m^{-1} .

WORKED EXAMPLE 29 Analysing a Hooke's law experiment

A Form Upper Sixth student in Yaoundé obtains the following results for a spring:

Load m (g)	0	50	100	150	200
Reading x (cm)	20.0	22.5	25.0	27.4	30.1

(a) Compute the extensions and the forces. (b) Determine the spring constant k . (c) Estimate the extension for a load of 120 g. (d) The reading for 200 g seems off the line: comment. Take $g = 9.81 \text{ m s}^{-2}$.

SOLUTION

Solution.

1. (a) Extensions $e = x - 20.0$ cm and forces $F = mg$:

e (cm)	0	2.5	5.0	7.4	10.1
F (N)	0	0.4905	0.981	1.4715	1.962

2. (b) Using the point (5.0 cm, 0.981 N) on the line:

$$k = \frac{F}{e} = \frac{0.981}{0.050} = 19.62 \text{ N m}^{-1}.$$

(Each 50 g gives about 2.5 cm, confirming proportionality.)

3. (c) For $m = 120$ g: $F = 0.120 \times 9.81 = 1.1772$ N, so

$$e = \frac{F}{k} = \frac{1.1772}{19.62} = 0.0600 \text{ m} = 6.00 \text{ cm}.$$

4. (d) The last point gives $e = 10.1$ cm where 10.0 cm is expected; the small excess (0.1 cm) may be reading error, but if the spring no longer returns to 20.0 cm on unloading, the elastic limit is being approached and the load should not be increased further.

Answer: $k \approx 19.6 \text{ N m}^{-1}$; $e \approx 6.0$ cm for 120 g.

22 APPLICATIONS OF HOOKE'S LAW AND SYNTHESIS

PROPERTY Elastic potential energy

The work done in stretching (or compressing) a spring from extension 0 to e is stored as **elastic potential energy**:

$$E_p = \frac{1}{2}ke^2 = \frac{1}{2}Fe = \frac{F^2}{2k}.$$

This is the area under the F - e graph (a triangle).

METHOD Springs in series and in parallel

1. Series (springs end to end): the tension F is the same in each spring; extensions add:

$$e = e_1 + e_2 = \frac{F}{k_1} + \frac{F}{k_2}, \text{ so}$$

$$\frac{1}{k_{\text{eq}}} = \frac{1}{k_1} + \frac{1}{k_2}.$$

2. Parallel (springs side by side, sharing the load): the extension e is the same for each; forces add: $F = k_1 e + k_2 e$, so

$$k_{\text{eq}} = k_1 + k_2.$$

3. Strategy: write $F = ke$ for each spring, use the geometry (which quantities are equal), then solve.

WORKED EXAMPLE 30 Two springs supporting a platform

A light platform is supported horizontally by two identical springs in parallel, each of stiffness $k = 800 \text{ N m}^{-1}$. (a) A bag of cement of mass 40 kg is placed at the centre; find the compression of each spring. (b) The same two springs are now connected in series and the bag is hung from the lower end; find the total extension. (c) Compute the elastic energy stored in case (a). Take $g = 9.81 \text{ m s}^{-2}$.

SOLUTION

Solution.

1. Load: $W = mg = 40 \times 9.81 = 392.4 \text{ N}$.

2. (a) Parallel: $k_{\text{eq}} = k_1 + k_2 = 1600 \text{ N m}^{-1}$.

$$e = \frac{W}{k_{\text{eq}}} = \frac{392.4}{1600} = 0.24525 \text{ m} = 24.5 \text{ cm}.$$

Each spring compresses by 24.5 cm (and carries half the load, 196.2 N : check $800 \times 0.24525 = 196.2 \text{ N}$ ✓).

3. (b) Series: $\frac{1}{k_{\text{eq}}} = \frac{1}{800} + \frac{1}{800} = \frac{2}{800}$, so $k_{\text{eq}} = 400 \text{ N m}^{-1}$.

$$e_{\text{total}} = \frac{W}{k_{\text{eq}}} = \frac{392.4}{400} = 0.981 \text{ m} = 98.1 \text{ cm}.$$

(Each spring stretches 49.05 cm ; the full tension passes through both.)

4. (c) Energy in (a): for the two springs together,

$$E_p = 2 \times \frac{1}{2} ke^2 = 800 \times (0.24525)^2 = 800 \times 0.06015 = 48.1 \text{ J}.$$

Answer: (a) 24.5 cm each; (b) 98.1 cm total; (c) $E_p \approx 48.1 \text{ J}$.

WORKED EXAMPLE 31 Synthesis: suspended body with spring

A uniform rod AB of length 1.2 m and mass 4 kg is hinged at A to a vertical wall. A light spring of natural length 0.5 m and stiffness $k = 200\text{ N m}^{-1}$ is attached to B and to a point C on the wall 1.3 m directly above A . The rod is held horizontal and released. Find the extension of the spring when the rod comes to rest in equilibrium. Take $g = 9.81\text{ m s}^{-2}$.

SOLUTION

Solution.

1. Geometry: when the rod is horizontal, B is 1.2 m horizontally from A . C is 1.3 m vertically above A . So $BC = \sqrt{1.2^2 + 1.3^2} = \sqrt{1.44 + 1.69} = \sqrt{3.13} = 1.769\text{ m}$.
2. Extension $e = BC - l_0 = 1.769 - 0.5 = 1.269\text{ m}$.
3. Spring force $F_s = ke = 200 \times 1.269 = 253.8\text{ N}$ along BC (toward C).
4. Moments about A : Weight $W = 4g = 39.24\text{ N}$ acts at midpoint (0.6 m from A), vertically down. The spring force at B has a vertical component $F_s \sin \theta$ and horizontal component $F_s \cos \theta$, where $\sin \theta = 1.3/1.769 = 0.735$, $\cos \theta = 1.2/1.769 = 0.678$.
5. Only vertical forces contribute moment about A (horizontal force at B passes through A ? No, A is at $(0, 0)$, B at $(1.2, 0)$, horizontal force at B has moment arm 0 vertically? Wait: horizontal force at B is perpendicular to vertical distance from A ? Actually, moment of a force about A is force $\times$ perpendicular distance. The horizontal component of spring force acts along the rod (horizontal), so its line of action passes through A ? No, A is at the hinge, the rod is horizontal. A horizontal force at B is along the rod, so its line of action passes through A — moment zero. The vertical component of spring force at B is upward, perpendicular distance 1.2 m .
6. Moment equilibrium about A (anticlockwise +):

$$F_s \sin \theta \times 1.2 - W \times 0.6 = 0$$

$$253.8 \times 0.735 \times 1.2 - 39.24 \times 0.6 = 223.7 - 23.5 = 200.2 \neq 0.$$

7. Contradiction: the rod is not in equilibrium in the horizontal position with this spring extension. The problem asks for the extension when the rod comes to rest in equilibrium — so the rod will settle at some angle α below horizontal. We must solve for the equilibrium angle.
8. Let the rod make angle α below horizontal. Then coordinates: $A = (0, 0)$, $B = (1.2 \cos \alpha, -1.2 \sin \alpha)$, $C = (0, 1.3)$.
9. Length $BC = \sqrt{(1.2 \cos \alpha)^2 + (1.3 + 1.2 \sin \alpha)^2}$.
10. Extension $e = BC - 0.5$.
11. Spring force magnitude $F_s = ke = 200(BC - 0.5)$.

12. Direction of spring force: from B to C, vector $\vec{BC} = (-1.2 \cos \alpha, 1.3 + 1.2 \sin \alpha)$.
13. Moment of spring force about A: $\vec{r}_B \times \vec{F}_s \cdot \vec{r}_B = (1.2 \cos \alpha, -1.2 \sin \alpha) \cdot \vec{F}_s = F_s \frac{\vec{BC}}{BC}$.
14. Moment (scalar, out of plane): $M_s = x_B F_{s,y} - y_B F_{s,x}$.
15. $F_{s,y} = F_s \frac{1.3+1.2 \sin \alpha}{BC}$, $F_{s,x} = F_s \frac{-1.2 \cos \alpha}{BC}$.
16. $M_s = (1.2 \cos \alpha) F_s \frac{1.3+1.2 \sin \alpha}{BC} - (-1.2 \sin \alpha) F_s \frac{-1.2 \cos \alpha}{BC} = \frac{1.2 F_s \cos \alpha}{BC} [1.3 + 1.2 \sin \alpha - 1.2 \sin \alpha] = \frac{1.2 F_s \cos \alpha \times 1.3}{BC}$.
17. Moment of weight about A: $W \times (0.6 \cos \alpha)$ clockwise (negative).
18. Equilibrium: $M_s - 0.6W \cos \alpha = 0 \Rightarrow \frac{1.2 \times 1.3 F_s}{BC} = 0.6W \Rightarrow \frac{2.6 F_s}{BC} = W$.
19. But $F_s = 200(BC - 0.5)$, so $\frac{2.6 \times 200(BC - 0.5)}{BC} = 39.24$.
20. $520 \frac{BC - 0.5}{BC} = 39.24 \Rightarrow \frac{BC - 0.5}{BC} = 0.07546 \Rightarrow 1 - \frac{0.5}{BC} = 0.07546 \Rightarrow \frac{0.5}{BC} = 0.92454 \Rightarrow BC = 0.5408 \text{ m}$.
21. Then $e = BC - 0.5 = 0.0408 \text{ m} = 4.08 \text{ cm}$.
22. Check: $BC = 0.5408$, but BC must be at least the vertical distance 1.3 m? Wait, C is at (0, 1.3), B is at $(1.2 \cos \alpha, -1.2 \sin \alpha)$. The vertical distance is $1.3 + 1.2 \sin \alpha \geq 1.3$. So $BC \geq 1.3$. Our computed $BC = 0.54$ is impossible.
23. Error: The spring is attached to C which is 1.3 m above A. If the rod is horizontal, B is at (1.2, 0), so $BC = \sqrt{1.2^2 + 1.3^2} = 1.769 > 1.3$. The spring is stretched. But the moment calculation gave a huge anticlockwise moment from the spring. The weight moment is small. The spring would pull the rod up, not down. So the equilibrium position is with the rod above horizontal? Let's re-read: "hinged at A to a vertical wall. A light spring ... attached to B and to a point C on the wall 1.3 m directly above A." If the rod is held horizontal and released, the spring pulls upward on B, lifting the rod. The rod will rise until the spring force moment balances the weight moment. The angle α should be measured above horizontal.
24. Let α be angle above horizontal. Then $B = (1.2 \cos \alpha, 1.2 \sin \alpha)$. $C = (0, 1.3)$. Vertical distance = $1.3 - 1.2 \sin \alpha$. This must be positive, so $\sin \alpha < 1.3/1.2$ (always true). $BC = \sqrt{(1.2 \cos \alpha)^2 + (1.3 - 1.2 \sin \alpha)^2}$.
25. Moment of spring force about A: similar derivation gives $M_s = \frac{1.2 F_s \cos \alpha \times 1.3}{BC}$ (anticlockwise? Let's check sign). $\vec{r}_B = (1.2 \cos \alpha, 1.2 \sin \alpha)$. $\vec{BC} = (-1.2 \cos \alpha, 1.3 - 1.2 \sin \alpha)$. $M_s = x_B F_{s,y} - y_B F_{s,x} = (1.2 \cos \alpha) F_s \frac{1.3 - 1.2 \sin \alpha}{BC} - (1.2 \sin \alpha) F_s \frac{-1.2 \cos \alpha}{BC} = \frac{1.2 F_s \cos \alpha}{BC} [1.3 - 1.2 \sin \alpha + 1.2 \sin \alpha] = \frac{1.56 F_s \cos \alpha}{BC}$. This is positive (anticlockwise).
26. Weight moment: $W \times (0.6 \cos \alpha)$ clockwise (negative).

27. Equilibrium: $\frac{1.56F_s \cos \alpha}{BC} - 0.6W \cos \alpha = 0$. If $\cos \alpha \neq 0$, $\frac{1.56F_s}{BC} = 0.6W = 23.544$.
28. $F_s = 200(BC - 0.5)$. So $\frac{1.56 \times 200(BC - 0.5)}{BC} = 23.544 \Rightarrow 312 \frac{BC - 0.5}{BC} = 23.544 \Rightarrow \frac{BC - 0.5}{BC} = 0.07546$.
29. Same equation! $BC = 0.5408$ m. But $BC \geq |1.3 - 1.2| = 0.1$? Actually minimum BC is when B is closest to C . B moves on circle radius 1.2. C is at distance 1.3 from A . Minimum $BC = 1.3 - 1.2 = 0.1$ m. Maximum $BC = 2.5$ m. So $BC = 0.5408$ is possible! It corresponds to the rod pointing somewhat upward, with B close to C .
30. Then $e = 0.5408 - 0.5 = 0.0408$ m = 4.08 cm.
31. Find α : $BC^2 = 1.2^2 + 1.3^2 - 2 \times 1.2 \times 1.3 \sin \alpha = 3.13 - 3.12 \sin \alpha$.
32. $0.5408^2 = 0.2925 = 3.13 - 3.12 \sin \alpha \Rightarrow 3.12 \sin \alpha = 2.8375 \Rightarrow \sin \alpha = 0.9095 \Rightarrow \alpha = 65.4^\circ$ above horizontal.

Answer: The spring extends by 4.1 cm when the rod rests at 65.4° above the horizontal.

WARNING Frequent errors in this chapter

- Confusing resultant and equilibrant: the equilibrant has the same magnitude but the opposite direction.
- Resolving with sin and cos interchanged: the component adjacent to the given angle uses cos.
- On an inclined plane, resolving the weight into $W \sin \alpha$ and $W \cos \alpha$ along the wrong directions — always draw the angle first.
- Measuring the extension of a spring from the top instead of from the unstretched length: $e = x - x_0$.
- Applying $F = ke$ beyond the elastic limit, where the graph is no longer linear.
- Forgetting that in equilibrium problems you may write two independent scalar equations ($\sum F_x = 0$, $\sum F_y = 0$) — and a moment equation if the body can rotate.
- Taking moments about a point where an unknown force acts, but forgetting that force's moment is zero only if its line of action passes through the point.
- Sign errors in moment equations: define a clear convention (e.g. anticlockwise +) and stick to it.
- In series/parallel springs: confusing which quantity is the same (force in series, extension in parallel).

EXERCISE 16 Practice problems

1. A uniform rod AB of length 2 m and weight 50 N is suspended by two vertical strings attached at A and B . A weight of 30 N is hung from the rod at a point 0.5 m from A . Find the tension in each string.
2. A force of 100 N acts at 30° to the horizontal. Find its horizontal and vertical components.
3. Three coplanar forces act at a point: 20 N at 0° , 30 N at 120° , 40 N at 240° . Find the resultant analytically.
4. A spring of natural length 0.3 m and stiffness 150 N m^{-1} is stretched to 0.5 m. Find the force and the energy stored.
5. Two springs of stiffness 200 N m^{-1} and 300 N m^{-1} are connected (a) in series, (b) in parallel. Find the equivalent stiffness in each case.
6. A uniform ladder of length 6 m and mass 20 kg leans against a smooth wall at 60° to the horizontal. A man of mass 70 kg climbs 4 m up the ladder. Find the friction force at the ground and the minimum coefficient of friction. ($g = 9.81 \text{ m s}^{-2}$)
7. A triangular lamina of mass 2 kg has vertices at $(0, 0)$, $(0.3, 0)$, $(0, 0.4)$ (in metres). It is suspended from the vertex at $(0, 0)$. Find the angle the side on the x -axis makes with the vertical at equilibrium.

SOLUTION Exercise 1

Let tensions be T_A at A and T_B at B . Moments about A : $T_B \times 2 - 50 \times 1 - 30 \times 0.5 = 0 \Rightarrow 2T_B = 50 + 15 = 65 \Rightarrow T_B = 32.5 \text{ N}$. Vertical equilibrium: $T_A + T_B = 80 \Rightarrow T_A = 47.5 \text{ N}$.

SOLUTION Exercise 2

$F_x = 100 \cos 30^\circ = 86.6 \text{ N}$, $F_y = 100 \sin 30^\circ = 50 \text{ N}$.

SOLUTION Exercise 3

$R_x = 20 + 30 \cos 120^\circ + 40 \cos 240^\circ = 20 - 15 - 20 = -15 \text{ N}$. $R_y = 0 + 30 \sin 120^\circ + 40 \sin 240^\circ = 25.98 - 34.64 = -8.66 \text{ N}$. $R = \sqrt{15^2 + 8.66^2} = 17.3 \text{ N}$ at $\tan^{-1}(8.66/15) = 30^\circ$ south of west (i.e. 210°).

SOLUTION Exercise 4

$$e = 0.5 - 0.3 = 0.2 \text{ m. } F = 150 \times 0.2 = 30 \text{ N. } E_p = \frac{1}{2} \times 150 \times 0.2^2 = 3 \text{ J.}$$

SOLUTION Exercise 5

(a) Series: $1/k_{\text{eq}} = 1/200 + 1/300 = 5/600 \Rightarrow k_{\text{eq}} = 120 \text{ N m}^{-1}$. (b) Parallel: $k_{\text{eq}} = 200 + 300 = 500 \text{ N m}^{-1}$.

SOLUTION Exercise 6

Forces: $W_L = 196.2 \text{ N}$ at 3 m from foot; $W_M = 686.7 \text{ N}$ at 4 m from foot; R_W at top ($6 \sin 60^\circ = 5.196 \text{ m}$ up); F and R_G at foot. Moments about foot: $R_W \times 5.196 - 196.2 \times 3 \cos 60^\circ - 686.7 \times 4 \cos 60^\circ = 0$. $R_W \times 5.196 = 196.2 \times 1.5 + 686.7 \times 2 = 294.3 + 1373.4 = 1667.7 \Rightarrow R_W = 321.0 \text{ N}$. $F = R_W = 321.0 \text{ N}$. $R_G = 196.2 + 686.7 = 882.9 \text{ N}$. $\mu_{\text{min}} = 321.0/882.9 = 0.364$.

SOLUTION Exercise 7

Centroid $G = (0.1, 0.1333) \text{ m}$. Suspended from $(0, 0)$, G hangs vertically below. Line OG has slope $0.1333/0.1 = 1.333$, angle with horizontal $= \tan^{-1}(1.333) = 53.13^\circ$. The side on x -axis is horizontal, so it makes $90^\circ - 53.13^\circ = 36.87^\circ$ with the vertical.

23 EXERCISES

23.1 I check my knowledge

EXERCISE 17 MCQ: resultant of two forces

Two forces of magnitudes 6 N and 8 N act at a point O at right angles to each other. The magnitude of their resultant is:

- (a) 2 N (b) 10 N (c) 14 N (d) 48 N

Choose the correct answer and justify your choice with a calculation.

EXERCISE 18 True or false

For each of the following statements, say whether it is true or false and justify your answer briefly.

1. A body is in equilibrium whenever the sum of the magnitudes of the forces acting on it is zero.
2. The centre of gravity of a uniform body always lies inside the material of the body.
3. When three non-parallel coplanar forces keep a body in equilibrium, their lines of action are concurrent.
4. Hooke's law states that the extension of a spring is proportional to the load, whatever the load may be.

EXERCISE 19 Definitions

Define each of the following terms, giving one example in each case:

1. the **resultant** of a system of coplanar forces;
2. the **equilibrant** of a system of coplanar forces;
3. a **couple** of forces;
4. the **centre of gravity** of a body.

EXERCISE 20 Direct calculation

A force of 20 N acts at an angle of 40° above the horizontal.

1. Resolve the force into horizontal and vertical components.
2. A spring of stiffness $k = 150 \text{ N m}^{-1}$ is stretched by a force of 12 N. Assuming Hooke's law holds, calculate the extension in centimetres.

23.2 I practise**EXERCISE 21** Resultant of two forces

Two forces of 8 N and 12 N act at a point O with an angle of 60° between them.

1. Using the cosine rule (parallelogram of forces), calculate the magnitude of the resultant.
2. Calculate the angle the resultant makes with the 12 N force.
3. Verify your answers with an accurate scale drawing (state the scale used).

EXERCISE 22 Block on an inclined plane

A block of weight 100 N rests on a smooth plane inclined at 30° to the horizontal. It is held in equilibrium by a force P acting parallel to the plane.

1. Draw a clearly labelled free-body diagram of the block.
2. By resolving parallel and perpendicular to the plane, find P and the normal reaction R .

EXERCISE 23 Springs in series and in parallel

Two identical springs, each of stiffness $k = 50 \text{ N m}^{-1}$, support a load of 10 N.

1. The springs are connected in series. Find the extension of each spring and the total extension.
2. The springs are connected in parallel, sharing the load equally. Find the total extension.
3. Explain, in terms of Hooke's law, why the two arrangements give different total extensions.

EXERCISE 24 Hanging picture

A picture of weight 40 N is hung by a string passing over a nail. The two parts of the string make angles of 50° and 70° with the vertical.

1. Draw the free-body diagram of the picture.
2. Using Lami's theorem, find the tension in each part of the string.
3. Check your answers by resolving horizontally and vertically.

23.3 I prepare for the GCE**EXERCISE 25** GCE-style: string and spring in equilibrium

A body of mass 5 kg hangs in equilibrium. It is supported by a light inextensible string inclined at 35° to the vertical and by a horizontal spring of stiffness 200 N m^{-1} attached to a wall. Take $g = 9.81 \text{ m s}^{-2}$.

1. Draw a free-body diagram of the body, showing all the forces acting on it. (3 marks)
2. Write down the equations obtained by resolving the forces horizontally and vertically. (4 marks)
3. Calculate the tension in the string. (3 marks)
4. Calculate the extension of the spring, giving your answer in centimetres. State clearly the law you use and the assumption made. (5 marks)

EXERCISE 26 GCE-style: experimental verification of Hooke's law

In an experiment to investigate Hooke's law, a student suspends a spring vertically and records the extension e for increasing loads W :

Load W (N)	1	2	3	4	5
Extension e (cm)	2.1	4.0	6.2	8.1	10.3

1. Describe briefly how the student should carry out this experiment, including the precautions taken to obtain accurate readings. (4 marks)
2. Plot the graph of e against W on graph paper, using suitable scales. (4 marks)
3. Explain how the graph verifies Hooke's law, and use it to determine the stiffness k of the spring in N m^{-1} . (4 marks)

4. The reading at $W = 5 \text{ N}$ lies slightly off the line. Suggest two possible reasons for this and state what the student should check before concluding that the elastic limit has been reached. (3 marks)

EXERCISE 27 GCE-style: centre of gravity and stability

1. A uniform lamina in the shape of a rectangle with a triangular notch cut from one side is suspended freely from a corner. Describe, with the aid of a diagram, the experiment you would perform to locate its centre of gravity, and explain why the lamina hangs so that the line from the point of suspension through the centre of gravity is vertical. (6 marks)
2. A loaded wheelbarrow is modelled as a rigid body resting on the ground. Using the position of the centre of gravity and the base of support, explain why the wheelbarrow topples forward when the load is placed too far in front of the wheel. Illustrate your answer with a diagram showing the line of action of the weight in the stable and in the toppling cases. (6 marks)
3. Three coplanar forces act at a point and keep a body in equilibrium. Two of the forces are 10 N due east and 15 N at 120° measured anticlockwise from east. Find, by resolving, the magnitude and direction of the third force, and explain how the same result could be obtained graphically by the polygon of forces. (8 marks)

24 SOLUTIONS TO THE EXERCISES**SOLUTION Exercise 1 — MCQ: resultant of two forces**

The correct answer is (b) 10 N.

Justification. The two forces are perpendicular, so by the parallelogram rule (here a rectangle), the magnitude of the resultant is given by Pythagoras' theorem:

$$R = \sqrt{6^2 + 8^2} = \sqrt{36 + 64} = \sqrt{100} = 10 \text{ N.}$$

The other options correspond to common errors: 14 N (adding the magnitudes arithmetically), 2 N (subtracting them), 48 N (multiplying them). Forces are vectors: only the vector sum is physically meaningful.

SOLUTION Exercise 2 — True or false

1. False. Equilibrium requires the vector sum of the forces to be zero, $\sum \vec{F} = \vec{0}$, not the sum of the magnitudes. For example, two forces of 5 N and 3 N acting in opposite directions have magnitudes summing to 8 N, yet their vector sum has magnitude 2 N $\neq 0$, so the body is not in equilibrium. The correct condition is that the resultant vector vanishes (and, for an extended body, that the total moment about any point is also zero).
2. False. The centre of gravity may lie outside the material of the body: for a uniform ring it is at the centre of the hole; for a boomerang or an L-shaped lamina it can lie in empty space. What matters is that the line of action of the total weight always passes through it.
3. True. If three non-parallel coplanar forces are in equilibrium, the resultant of any two of them must balance the third. This resultant acts through the point of intersection of the first two lines of action, so the third force must pass through the same point: the three lines of action are **concurrent**. (This is the three-force principle, very useful for locating unknown forces in GCE problems.)
4. False. Hooke's law ($F = ke$) holds only provided the elastic limit is not exceeded. Beyond the elastic limit the extension is no longer proportional to the load and the spring suffers permanent deformation: it does not return to its original length when unloaded.

SOLUTION Exercise 3 — Definitions

1. The **resultant** of a system of coplanar forces is the single force, acting at the same point, which has the same effect as all the forces together; it is their vector sum $\vec{R} = \sum \vec{F}_i$. Example: forces of 3 N due east and 4 N due north have a resultant of 5 N in the direction $\arctan(4/3) \approx 53.1^\circ$ north of east.
2. The **equilibrant** is the single force which, added to the system, produces equilibrium; it is equal in magnitude to the resultant, acts along the same line, but in the opposite direction: $\vec{E} = -\vec{R}$. Example: for the system above, the equilibrant is 5 N directed 53.1° south of west.
3. A **couple** is a pair of equal, parallel, oppositely directed forces whose lines of action are distinct. Its resultant force is zero, but it produces a pure turning effect (moment) $\tau = Fd$, where d is the perpendicular distance between the lines of action. Example: the two forces applied by the hands on a steering wheel, or the fingers turning a tap.
4. The **centre of gravity** of a body is the point through which the line of action of its total weight always passes, whatever the orientation of the body; equivalently, it is the point about which the weights of all the particles of the body have zero total moment. Example: the centre of gravity of a uniform metre rule is at the 50 cm mark.

SOLUTION Exercise 4 — Direct calculation

1. Let $\vec{F}$ have magnitude $F = 20$ N at 40° above the horizontal. The component adjacent to the angle uses cosine, the component opposite uses sine:

$$F_x = F \cos 40^\circ = 20 \times 0.7660 \approx 15.3 \text{ N}, \quad F_y = F \sin 40^\circ = 20 \times 0.6428 \approx 12.9 \text{ N}.$$

The horizontal component is about 15.3 N and the vertical component about 12.9 N (upwards). Check: $\sqrt{15.3^2 + 12.9^2} \approx 20.0$ N. ✓

2. By Hooke's law, $F = ke$, so

$$e = \frac{F}{k} = \frac{12}{150} = 0.08 \text{ m} = 8 \text{ cm}.$$

The extension is 8 cm (assuming the elastic limit is not exceeded).

SOLUTION Exercise 5 — Resultant of two forces

1. By the cosine rule applied to the parallelogram (triangle) of forces, with the angle between the forces $\theta = 60^\circ$:

$$R^2 = 8^2 + 12^2 + 2(8)(12) \cos 60^\circ = 64 + 144 + 192 \times 0.5 = 208 + 96 = 304.$$

$$R = \sqrt{304} \approx 17.4 \text{ N.}$$

2. Let α be the angle between the resultant and the 12 N force. Resolving the 8 N force parallel and perpendicular to the 12 N force:


$$\tan \alpha = \frac{8 \sin 60^\circ}{12 + 8 \cos 60^\circ} = \frac{8 \times 0.8660}{12 + 4} = \frac{6.928}{16} = 0.4330, \quad \alpha \approx 23.4^\circ.$$

The resultant makes an angle of about 23.4° with the 12 N force.

3. Scale drawing. Choose the scale 1 cm : 1 N. From a point O draw a segment of 12 cm (the 12 N force) along a reference line; using a protractor, draw from O a segment of 8 cm at 60° to it. Complete the parallelogram and draw the diagonal from O . Measuring the diagonal gives about 17.4 cm, i.e. $R \approx 17.4 \text{ N}$, and measuring the angle between the diagonal and the 12 cm side gives about 23° . This confirms the calculation.

SOLUTION Exercise 6 — Block on an inclined plane

1. Free-body diagram. Three forces act on the block: the weight $W = 100 \text{ N}$ vertically downwards, the normal reaction R perpendicular to the plane, and the applied force P parallel to the plane, directed up the slope.



Free-body diagram of the block on the smooth inclined plane.

2. The plane is smooth, so there is no friction. Resolve the weight: the component parallel to the plane (down the slope) is $W \sin 30^\circ$; the component perpendicular to the plane (into the plane) is $W \cos 30^\circ$. (The angle between the weight and the normal to the plane equals the angle of inclination, 30° .)

Equilibrium parallel to the plane:

$$P = W \sin 30^\circ = 100 \times 0.5 = 50 \text{ N.}$$

Equilibrium perpendicular to the plane:

$$R = W \cos 30^\circ = 100 \times \frac{\sqrt{3}}{2} \approx 86.6 \text{ N.}$$

Hence $P = 50 \text{ N}$ up the plane and $R \approx 86.6 \text{ N}$. Note that $R < W$: on an incline the plane supports only part of the weight.

SOLUTION Exercise 7 — Springs in series and in parallel

1. Series. In series, the same tension $T = 10 \text{ N}$ acts in each spring. By Hooke's law, the extension of each spring is

$$e = \frac{T}{k} = \frac{10}{50} = 0.2 \text{ m} = 20 \text{ cm.}$$

The total extension is the sum:

$$e_{\text{total}} = 0.2 + 0.2 = 0.4 \text{ m} = 40 \text{ cm.}$$

2. Parallel. The load is shared equally between the two identical springs, so each carries $\frac{10}{2} = 5 \text{ N}$. Each spring (and hence the combination, since both ends move together) extends by


$$e = \frac{5}{50} = 0.1 \text{ m} = 10 \text{ cm.}$$

The total extension is $0.1 \text{ m} = 10 \text{ cm}$.

3. Explanation. In series, the full load passes through each spring, so each stretches by F/k and the extensions add: the combination is softer (effective stiffness $k_{\text{eff}} = k/2 = 25 \text{ N m}^{-1}$, since $e_{\text{total}} = 2F/k$). In parallel, each spring carries only half the load, so each stretches less and the extensions do not add: the combination is stiffer (effective stiffness $k_{\text{eff}} = 2k = 100 \text{ N m}^{-1}$, since the total force $2ke$ is shared). In both cases the result follows directly from $e = F/k$ applied to the force actually carried by each spring.

SOLUTION Exercise 8 — Hanging picture

1. Free-body diagram. Three forces act on the picture: its weight $W = 40 \text{ N}$ vertically downwards, and the tensions T_1 and T_2 along the two parts of the string, at 50° and 70° to the vertical respectively (on opposite sides of the vertical).



2. Lami's theorem. Since the two strings lie on opposite sides of the vertical, the angle between T_1 and T_2 is $50^\circ + 70^\circ = 120^\circ$; the angle between T_1 and W is $180^\circ - 50^\circ = 130^\circ$; the angle between T_2 and W is $180^\circ - 70^\circ = 110^\circ$. (Check: $120^\circ + 130^\circ + 110^\circ = 360^\circ$. ✓) Lami's theorem states that each force is proportional to the sine of the angle between the other two:

$$\frac{T_1}{\sin 110^\circ} = \frac{T_2}{\sin 130^\circ} = \frac{W}{\sin 120^\circ} = \frac{40}{0.8660} = 46.19 \text{ N.}$$

$$T_1 = 46.19 \sin 110^\circ = 46.19 \times 0.9397 \approx 43.4 \text{ N,}$$

$$T_2 = 46.19 \sin 130^\circ = 46.19 \times 0.7660 \approx 35.4 \text{ N.}$$

3. Check by resolution. Horizontally (taking components of the tensions measured from the vertical):

$$T_1 \sin 50^\circ = 43.4 \times 0.7660 \approx 33.2 \text{ N,} \quad T_2 \sin 70^\circ = 35.4 \times 0.9397 \approx 33.3 \text{ N,}$$


which balance (the small difference is due to rounding). Vertically:

$$T_1 \cos 50^\circ + T_2 \cos 70^\circ = 43.4 \times 0.6428 + 35.4 \times 0.3420 \approx 27.9 + 12.1 = 40.0 \text{ N} = W. \quad \checkmark$$

SOLUTION**Exercise 9 — GCE-style: string and spring in equilibrium**

1. Free-body diagram (3 marks: one for each correctly drawn and labelled force)

Three forces act on the body: the weight $W = mg = 5 \times 9.81 = 49.05 \text{ N}$ vertically downwards; the tension T along the string, at 35° to the vertical, pulling up and away from the wall; the spring force F horizontal, pulling the body towards the wall.



Free-body diagram: weight, tension, spring force.

2. Equations of equilibrium (4 marks: 2 per equation)

Resolving horizontally (F to the right balancing the horizontal component of T):

$$F = T \sin 35^\circ.$$

Resolving vertically:

$$T \cos 35^\circ = W = mg = 49.05 \text{ N}.$$

3. Tension (3 marks: method, substitution, answer)

$$T = \frac{49.05}{\cos 35^\circ} = \frac{49.05}{0.8192} \approx 59.9 \text{ N}.$$

4. Extension of the spring (5 marks: value of F , statement of Hooke's law, assumption, calculation, answer in cm)

$$\text{First, } F = T \sin 35^\circ = 59.9 \times 0.5736 \approx 34.3 \text{ N}.$$

Law used: Hooke's law, $F = ke$; assumption: the elastic limit of the spring is not exceeded, so the extension is proportional to the applied force.

$$e = \frac{F}{k} = \frac{34.3}{200} = 0.172 \text{ m} \approx 17.2 \text{ cm}.$$

Examiner's expectations: a clear diagram with three forces only; correct resolution of T (sine horizontal, cosine vertical, since the angle is measured from the vertical); explicit mention of Hooke's law and of the elastic-limit condition; final answer in centimetres with correct conversion.


SOLUTION Exercise 10 — GCE-style: experimental verification of Hooke's law

1. Procedure and precautions (4 marks)

Suspend the spring vertically from a firm retort stand beside a vertical metre rule. Attach a pointer (e.g. a horizontal pin) to the lower end of the spring. Record the pointer reading with no load, then add slotted masses one at a time, recording the pointer reading for each load; the extension is the difference from the unloaded reading. Precautions: read the scale at eye level to avoid parallax error; wait until the spring is at rest before reading; avoid overloading the spring beyond its elastic limit; check that the spring returns to its original length when the load is removed; use small, regular load increments.

2. Graph (4 marks: axes labelled with units, suitable scale, correct plotting, best straight line)

Plot e (cm) on the vertical axis against W (N) on the horizontal axis, e.g. 2 cm : 1 N horizontally and 1 cm : 1 cm of extension vertically. The points (1, 2.1), (2, 4.0), (3, 6.2), (4, 8.1), (5, 10.3) lie almost on a straight line through the origin; draw the best-fit straight line.



Extension against load: points and best-fit line through the origin.

3. Verification and stiffness (4 marks)

The graph is a straight line through the origin, so $e \propto W$: the extension is proportional to the load, which is exactly Hooke's law. The stiffness is the inverse of the gradient (with e converted to metres):

$$\text{gradient} = \frac{\Delta e}{\Delta W} \approx \frac{10.0 \text{ cm}}{5.0 \text{ N}} = 2.0 \text{ cm N}^{-1} = 0.020 \text{ m N}^{-1}, \quad k = \frac{1}{0.020} \approx 50 \text{ N m}^{-1}.$$


4. Anomalous point at $W = 5 \text{ N}$ (3 marks)

Possible reasons: (i) a reading error, e.g. parallax or reading the pointer while the spring was still oscillating; (ii) the load was not exactly 5 N (worn or mislabelled mass), or the spring was beginning to be stretched beyond its elastic limit. Before concluding that the elastic limit has been reached, the student should repeat the reading, then remove the load and check whether the spring returns to its original unstretched length: if it does, the elastic limit has not been exceeded and the point is simply an experimental error.

SOLUTION Exercise 11 — GCE-style: centre of gravity and stability**1. Locating the centre of gravity** (6 marks)

Make a small hole near the corner of the lamina and suspend it freely from a horizontal pin (or nail) so that it can swing without friction. Hang a plumb line from the same pin. When the lamina is at rest, draw the line of the plumb line on the lamina: the centre of gravity lies on this line. Repeat from a second hole at a different edge; the intersection of the two lines is the centre of gravity G (a third suspension checks the result).


Explanation: in equilibrium under gravity, the weight acts through G and the reaction at the pin acts at the point of suspension. Two forces in equilibrium must be equal, opposite and collinear, so G must lie vertically below the point of suspension; hence the line from the suspension point through G is vertical. (Equivalently, the weight exerts a moment about the pin until G comes to rest directly below it.)



Plumb-line method: G lies vertically below the point of suspension.

2. Stability of the wheelbarrow (6 marks)

A rigid body resting on the ground is stable as long as the vertical line of action of its weight (the line through G) falls inside the base of support (the region bounded by the contact points with the ground). If the load is placed too far in front of the wheel, G moves forward; when the line of action of W passes beyond the front edge of the base of support, the weight produces an unbalanced moment about that edge and the wheelbarrow topples forward. Moving the load back brings the line of action inside the base again and restores stability.



Left: line of action of W inside the base (stable). Right: outside the base (toppling).

3. Third force by resolution

(8 marks)

Take axes: x due east, y due north. Force 1: $\vec{F}_1 = (10, 0)$. Force 2: magnitude 15 N at 120° anticlockwise from east:

$$F_{2x} = 15 \cos 120^\circ = -7.5 \text{ N}, \quad F_{2y} = 15 \sin 120^\circ = 7.5\sqrt{3} \approx 12.99 \text{ N}.$$

Equilibrium requires $\vec{F}_3 = -(\vec{F}_1 + \vec{F}_2)$:

$$F_{3x} = -(10 - 7.5) = -2.5 \text{ N}, \quad F_{3y} = -(0 + 12.99) = -12.99 \text{ N}.$$

Magnitude:


$$F_3 = \sqrt{2.5^2 + 12.99^2} = \sqrt{6.25 + 168.75} = \sqrt{175} \approx 13.2 \text{ N}.$$

Direction: $\tan \theta = \frac{12.99}{2.5} = 5.196$, so $\theta \approx 79.1^\circ$; with both components negative, $\vec{F}_3$ points into the third quadrant (south-west), i.e. 79.1° south of west. Equivalently, the direction is 259.1° measured anticlockwise from east, or a bearing of about 190.9° (almost due south, slightly west).

Graphical check (polygon of forces): to a suitable scale (e.g. 1 cm : 2 N), draw the 10 N force eastwards, then from its head draw the 15 N force at 120° . For equilibrium the triangle must close: the closing side, drawn from the head of the second force back to the start, is the third force. Measuring gives about 6.6 cm, i.e. 13.2 N, at about 79° south of west — confirming the calculation.

Examiner's expectations: correct components with signs; use of $\sum F_x = 0$, $\sum F_y = 0$; magnitude from Pythagoras; direction stated unambiguously (angle with a named direction); clear description of the closing side of the force triangle.

25 SUMMARY SHEET



Mind map of Chapter PMM14: Equilibrium Forces, Moments and Couples

FICHE BILAN L'essentiel à connaître pour l'examen

Key Definitions

- **Equilibrium:** A body is in equilibrium if the resultant force and resultant moment acting on it are both zero.
- **Centre of Gravity (CG):** The point where the whole weight of a body can be considered to act.
- **Force as a Vector:** A force has magnitude, direction, and point of application; represented by a vector.
- **Resultant Force:** The single force that has the same effect as a system of forces.
- **Equilibrant Force:** The force that brings a system into equilibrium; equal in magnitude, opposite in direction to the resultant.
- **Moment of a Force:** $M = F \times d$, where d is the perpendicular distance from the pivot to

the line of action.

- **Couple:** Two equal and opposite parallel forces separated by a distance; produces pure rotation.
- **Hooke's Law:** For an elastic material, extension x is proportional to the applied force F : $F = kx$, where k is the stiffness.

Laws, Formulas & Theorems

- **Conditions for Equilibrium (Coplanar Forces):** $\sum F_x = 0$, $\sum F_y = 0$, $\sum M_O = 0$ (about any point O).
- **Triangle of Forces:** If three forces are in equilibrium, they can be represented in magnitude and direction by the sides of a triangle taken in order.
- **Polygon of Forces:** For any number of coplanar forces in equilibrium, the force polygon closes.
- **Resolution of Forces:** $F_x = F \cos \theta$, $F_y = F \sin \theta$.
- **Resultant of Two Forces:** $R = \sqrt{F_1^2 + F_2^2 + 2F_1F_2 \cos \theta}$.
- **Moment of a Couple:** $M = F \times d$ (independent of the point about which moments are taken).
- **Hooke's Law:** $F = kx$; Elastic potential energy $E = \frac{1}{2}kx^2$.
- **Experimental Verification:** Plot F vs x ; gradient gives k ; linear region confirms Hooke's law.

Methods

1. **Free-Body Diagram:** Isolate the body; show all external forces (weight, reactions, tensions, friction) with correct directions and points of application.
2. **Graphical Method:** Draw force vectors to scale; use triangle/polygon law; measure resultant/equilibrant.
3. **Analytical Method:** Resolve forces into perpendicular components; apply $\sum F_x = 0$, $\sum F_y = 0$; take moments about a convenient point to eliminate unknowns.
4. **Centre of Gravity Experiment:** Suspend a lamina from different points; draw vertical lines; intersection gives CG.
5. **Hooke's Law Experiment:** Hang known masses on a spring; measure extensions; plot F vs x ; determine k from slope.

Common Mistakes

- Forgetting to include the weight of the body or the reaction at a support in the free-body diagram.
- Confusing resultant and equilibrant: equilibrant is opposite to resultant.

- Taking moments about a point where an unknown force acts, but forgetting that the moment of that force is zero only if its line of action passes through the point.
- Using the wrong perpendicular distance for moments (must be perpendicular to the line of action).
- Assuming Hooke's law holds beyond the elastic limit; the graph becomes non-linear.
- Mixing units (e.g., cm vs m) in moment calculations.
- In graphical methods, not drawing to scale or not maintaining the correct order of vectors.

GCE Tips

- Always start with a clear free-body diagram; it earns marks and prevents missing forces.
- For equilibrium problems, choose the point for moments that eliminates as many unknowns as possible (often a hinge or support).
- Show all steps: resolve forces, write equilibrium equations, solve simultaneously.
- In graphical questions, use a sharp pencil, ruler, and protractor; state the scale used.
- For Hooke's law, remember to convert mass to force ($F = mg$) and extension to metres.
- The centre of gravity of a uniform lamina is at its geometric centre; for composite bodies, use the principle of moments: $\sum m_i x_i = M\bar{x}$.
- Practice past GCE questions on ladder problems, suspended bodies, and spring systems.



Signed • OnBuch+

ONBUCH+ TEACHING TEAM

FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+