

PURE MATHEMATICS WITH MECHANICS • UPPER SIXTH

UPPER SIXTH — PURE MATHEMATICS WITH MECHANICS

CHAPTER 15

WORK, ENERGY AND POWER

SUGGESTED TIME: 10 PERIODS

IN THIS CHAPTER

This chapter develops the concepts of work, energy and power for constant and variable forces, including motion under gravity and against resistance. It equips Upper Sixth students with the work-energy theorem, conservation of mechanical energy and power-velocity relations needed to solve GCE Advanced Level mechanics problems.

- By the end of this chapter I can define the work done by a constant force and compute it using $W = Fs \cos \theta$.
- By the end of this chapter I can calculate the work done against gravity when a body is raised through a vertical height.
- By the end of this chapter I can evaluate the work done by a variable force using integration, $W = \int F dx$.
- By the end of this chapter I can define kinetic and potential energy and compute their values in standard situations.
- By the end of this chapter I can state and apply the work-energy theorem to moving bodies.
- By the end of this chapter I can apply the principle of conservation of mechanical energy to systems with and without friction.



DOWNLOAD ON- BUCH

Free • Google Play
AI tutor, past papers,
results



GO ONBUCH+

All signed courses, unlimited AI
tutor, PDF sheets — OnBuch+
tab in the app

THIS SIGNED COURSE CONTAINS

COURSE

complete, illustrated,
step by step

METHODS

and worked examples

EXERCISES

exam style + solutions

SUMMARY SHEET

the essentials to
remember



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+

CONTENTS

- | | |
|--|---|
| 1. Work Done by a Constant Force and Work Done Against Gravity | 6. Pumping Water, Water Jets and Applications of Work, Energy and Power |
| 2. Work Done by Variable Forces | 7. Integration activity |
| 3. Energy: Kinetic and Potential | 8. Methods and worked examples |
| 4. The Work–Energy Theorem and Conservation of Energy | 9. Exercises |
| 5. Power: Definition, Instantaneous Power and Power–Velocity | 10. Solutions to the exercises |
| | 11. Summary sheet |

CHAPTER OBJECTIVES

- By the end of this chapter I can define the work done by a constant force and compute it using $W = Fs \cos \theta$.
- By the end of this chapter I can calculate the work done against gravity when a body is raised through a vertical height.
- By the end of this chapter I can evaluate the work done by a variable force using integration, $W = \int F dx$.
- By the end of this chapter I can define kinetic and potential energy and compute their values in standard situations.
- By the end of this chapter I can state and apply the work–energy theorem to moving bodies.
- By the end of this chapter I can apply the principle of conservation of mechanical energy to systems with and without friction.
- By the end of this chapter I can define power, distinguish average from instantaneous power, and use $P = Fv$.
- By the end of this chapter I can solve problems on vehicles moving with constant power, including maximum speed on level roads and inclines.
- By the end of this chapter I can model pumping water and water jets and compute the power required.
- By the end of this chapter I can solve mixed GCE–style problems combining work, energy and power.

PREREQUISITES

- Kinematics of motion in a straight line (suvat equations) from Lower Sixth
- Newton's laws of motion and resolution of forces on inclined planes
- Definite integration and integration of polynomial functions (Pure Mathematics)
- Trigonometric ratios and resolving vectors into components
- Friction and the coefficient of friction (Lower Sixth mechanics)

1 WORK DONE BY A CONSTANT FORCE AND WORK DONE AGAINST GRAVITY

Every morning in Bamenda, water vendors push heavy carts up steep streets, and at the Memve'ele hydroelectric dam, falling water spins turbines that light up entire towns. How much “effort” does the vendor really expend climbing the hill, and how much energy does the falling water deliver each second? A generator mechanic in Douala chooses between two engines rated in kilowatts — what does that number actually measure? In this chapter we turn these everyday questions into precise mathematics: **work**, **energy** and **power**.

We begin with the simplest situation: a single, constant force acting on a body that moves in a straight line. Our goal in this section is to define work precisely, to learn when work is positive, negative or zero, and to master the most important special case at GCE level — the work done against gravity.

1.1 From Everyday Effort to a Mathematical Definition

Imagine a porter at the Yaoundé central market dragging a sack of rice along the ground. Two things clearly determine how “tiring” the task is: how hard he pulls (the **force**) and how far he drags the sack (the **displacement**). But there is a third, subtler ingredient. If he pulls horizontally, the sack slides easily; if he pulls almost vertically, the sack barely moves forward, however hard he strains. Only the part of the force in the direction of motion is useful in moving the sack. This observation is the key to the definition of work.

DEFINITION Work done by a constant force


The **work done** by a constant force $\vec{F}$ whose point of application moves through a displacement $\vec{s}$ is the scalar product

$$W = \vec{F} \cdot \vec{s} = Fs \cos \theta,$$

where $F = |\vec{F}|$, $s = |\vec{s}|$ and θ is the angle between the force and the displacement ($0 \leq \theta \leq \pi$). The SI unit of work is the **joule** (symbol J): $1 \text{ J} = 1 \text{ N m}$.

The factor $\cos \theta$ selects exactly the component of the force along the direction of motion, $F \cos \theta$. So we may read the formula in two equivalent ways:

$$W = \underbrace{(F \cos \theta)}_{\text{component of force along motion}} \times s \quad \text{or} \quad W = F \times \underbrace{(s \cos \theta)}_{\text{displacement along the force}}.$$



A block pulled by a constant force $\vec{F}$ at angle θ to the horizontal displacement $\vec{s}$. Only the component $F \cos \theta$ does work.

WARNING Work is a scalar

Although force and displacement are vectors, work is a **scalar**: it has magnitude and sign, but no direction. We add works algebraically, never by the parallelogram rule. Note also that W can be negative — a negative work is not “less than nothing”; it means the force removes energy from the body rather than giving it energy.

1.2 Positive, Negative and Zero Work

The sign of $W = Fs \cos \theta$ is decided entirely by the angle θ , since F and s are positive magnitudes.

PROPERTY Sign of the work

Let a constant force $\vec{F}$ act on a body moving through displacement $\vec{s}$, with θ the angle between them.

- If $0 \leq \theta < 90^\circ$, then $\cos \theta > 0$ and $W > 0$: the force helps the motion (positive work).
- If $\theta = 90^\circ$, then $\cos \theta = 0$ and $W = 0$: a force perpendicular to the displacement does no work.
- If $90^\circ < \theta \leq 180^\circ$, then $\cos \theta < 0$ and $W < 0$: the force opposes the motion (negative work). Friction is the standard example.

EXAMPLE Zero work: carrying a load horizontally

A student carries a 10 kg bag of books horizontally across the school yard. The upward force she exerts on the bag is perpendicular to the horizontal displacement, so $\theta = 90^\circ$ and the work done by her supporting force is $W = 0$. She gets tired — but in the mechanical

sense, her upward force does no work on the bag.

WORKED EXAMPLE 1 Pushing a cart in Bamenda

A water vendor pushes his cart with a constant horizontal force of 120 N along a straight street for 50 m. A resistive force (friction and air) of 40 N opposes the motion. Find the work done by each force and the total work done on the cart.

SOLUTION

Solution. The pushing force is parallel to the displacement, so $\theta = 0^\circ$:

$$W_{\text{push}} = Fs \cos 0^\circ = 120 \times 50 \times 1 = 6000 \text{ J.}$$

The resistive force points opposite to the motion, so $\theta = 180^\circ$:

$$W_{\text{res}} = 40 \times 50 \times \cos 180^\circ = 40 \times 50 \times (-1) = -2000 \text{ J.}$$

The total (net) work is the algebraic sum:

$$W_{\text{total}} = 6000 + (-2000) = 4000 \text{ J.}$$

The cart gains 4000 J of energy from the vendor's effort; the remaining 2000 J is dissipated by the resistive forces.

PROPERTY Total work is an algebraic sum

When several forces $\vec{F}_1, \vec{F}_2, \dots, \vec{F}_n$ act simultaneously on a body, the total work done on the body over a displacement is the algebraic sum of the individual works:

$$W_{\text{total}} = W_1 + W_2 + \dots + W_n.$$

(Equivalently, the total work equals the work of the resultant force $\vec{F}_{\text{res}} = \sum \vec{F}_i$.) This property is used constantly at GCE level; its proof is not examinable.

WORKED EXAMPLE 2 Dragging a sack of rice with a rope at an angle

A porter drags a sack of rice across a horizontal floor using a rope inclined at 30° above the horizontal. He pulls with a constant tension of 100 N over a distance of 12 m. Find the work done by the tension.

SOLUTION

Solution. The angle between the tension and the horizontal displacement is $\theta = 30^\circ$:

$$W = Fs \cos \theta = 100 \times 12 \times \cos 30^\circ = 1200 \times \frac{\sqrt{3}}{2} = 600\sqrt{3} \approx 1039 \text{ J.}$$

Notice that the vertical component $F \sin 30^\circ = 50 \text{ N}$ does no work at all: it merely lightens the sack on the floor.

1.3 Work Done Against Gravity

Lift a bag of cement from the ground onto a lorry and you feel immediately that you are working against the weight of the bag. Let us make this precise.

Consider a body of mass m raised slowly (at constant speed, so that the lifting force just balances the weight) through a vertical height h . The lifting force has magnitude $F = mg$ and acts vertically upward, in the same direction as the vertical displacement. Hence

$$W = Fs \cos 0^\circ = mg \times h \times 1 = mgh.$$

KEY POINTS Work done against gravity

The work done against gravity in raising a body of mass m through a vertical height h is

$$W_{\text{against gravity}} = mgh,$$

where g is the acceleration due to gravity (take $g = 9.81 \text{ m s}^{-2}$, or 10 m s^{-2} when the question says so).

Conversely, the work done by the weight (gravitational force) when the body moves vertically is:

- $W_{\text{gravity}} = -mgh$ if the body rises through height h (force down, displacement up, $\theta = 180^\circ$).
- $W_{\text{gravity}} = +mgh$ if the body falls through height h (force and displacement both down, $\theta = 0^\circ$).

METHOD Computing work against gravity

1. Identify the mass m of the body (convert to kilograms if necessary).
2. Identify the vertical height h gained (or lost) — never the distance along a slope.
3. Compute $W = mgh$ with $g = 9.81 \text{ m s}^{-2}$ (or the value given).

4. State the sign clearly: work done against gravity is positive ($+mgh$); work done by gravity is negative for a rise ($-mgh$) and positive for a fall ($+mgh$).

A remarkable and examinable fact is that the work done by gravity depends only on the vertical displacement, not on the path taken. Whether the vendor carries his jerrycans straight up a staircase or along a long gentle ramp to the same floor, the work done against gravity is the same: mgh . To see why, split any path into tiny steps; the horizontal steps contribute nothing (the weight is vertical, perpendicular to horizontal motion), and the vertical steps add up to the total height h . Forces with this path-independence property are called **conservative** forces, and gravity is the first example you meet.


WARNING The classic trap: height versus distance along the slope

A very common mistake at GCE is to compute the work against gravity as $mg \times s$, where s is the distance travelled along an inclined plane. This is wrong. The work against gravity is mgh where $h = s \sin \alpha$ is the vertical height gained. Always extract the vertical height first.

1.4 Pulling a Body Up a Rough Inclined Plane

We now combine everything: a crate is pulled at constant speed up a rough plane inclined at angle α to the horizontal, through a distance s along the slope. Four forces act on the crate:

- the applied force $\vec{F}$, parallel to the slope (directed upward);
- the weight $m\vec{g}$, vertically downward;
- the normal reaction $\vec{R}$, perpendicular to the slope;
- the friction $\vec{f}$, acting down the slope (opposing the motion).



A crate pulled up a rough plane inclined at angle α . The vertical height gained is $h = s \sin \alpha$; friction acts down the slope, opposing the motion.

Let us compute the work of each force over the displacement s along the plane.

Work of the applied force. $\vec{F}$ is parallel to the motion (assumed up the slope): $\theta = 0^\circ$, so $W_F = Fs$.

Work of the normal reaction. $\vec{R}$ is perpendicular to the slope, hence to the displacement: $\theta = 90^\circ$, so $W_R = 0$.

Work of friction. Friction opposes the motion, $\theta = 180^\circ$: $W_f = -fs$. The work done against friction is $+fs$.

Work of the weight. Method 1 (Angle): The angle between the vertically downward weight and the displacement up the slope is $90^\circ + \alpha$, so

$$W_g = mgs \cos(90^\circ + \alpha) = -mgs \sin \alpha = -mgh.$$

Method 2 (Components): Resolve weight into components parallel ($mg \sin \alpha$ down the slope) and perpendicular ($mg \cos \alpha$) to the plane. The perpendicular component does no work. The parallel component acts opposite to displacement, so $W_g = (-mg \sin \alpha) \times s = -mgs \sin \alpha = -mgh$. Both methods confirm that only the vertical height $h = s \sin \alpha$ matters. The work done against gravity is $+mgh$.

PROPERTY Work needed to pull a body up a rough plane at constant speed

If a body of mass m is pulled at constant speed through a distance s up a rough plane inclined at α , with frictional force f , then the applied force does work

$$W_F = \underbrace{mgh}_{\text{against gravity}} + \underbrace{fs}_{\text{against friction}}, \quad h = s \sin \alpha.$$

Derivation (examinable): At constant speed, acceleration is zero, so the resultant force parallel to the plane is zero. $F - mg \sin \alpha - f = 0 \implies F = mg \sin \alpha + f$. Multiplying by the displacement s : $W_F = Fs = mgs \sin \alpha + fs = mgh + fs$.

WORKED EXAMPLE 3 Crate up a rough ramp

A crate of mass 50 kg is pulled at constant speed 8 m up a ramp inclined at 25° to the horizontal. The frictional force between crate and ramp is 90 N. Taking $g = 9.81 \text{ m s}^{-2}$, find (a) the work done against gravity, (b) the work done against friction, (c) the total work done by the pulling force.

SOLUTION

Solution. The vertical height gained is

$$h = s \sin \alpha = 8 \sin 25^\circ = 8 \times 0.4226 \approx 3.381 \text{ m}.$$

(a) Work done against gravity:

$$W_g = mgh = 50 \times 9.81 \times 3.381 \approx 1658 \text{ J}.$$

(b) Work done against friction:

$$W_f = fs = 90 \times 8 = 720 \text{ J}.$$

(c) Since the speed is constant, the pulling force supplies both:

$$W_F = W_g + W_f = 1658 + 720 = 2378 \text{ J} \approx 2.38 \text{ kJ}.$$

Note the signs: the work done by gravity is -1658 J and the work done by friction is -720 J , while the work done by the pulling force is $+2378 \text{ J}$; they sum to zero, consistent with constant speed (Work-Energy Theorem).

WARNING GCE exam tip: state every sign

In GCE Advanced Level questions, examiners award marks for the sign of each work term. Always write explicitly: “work done by friction = $-fs$ (negative, because friction opposes the motion)” and “work done by gravity = $-mgh$ (the body rises)”. A correct magnitude with a missing or wrong sign loses marks.

DID YOU KNOW? The joule in daily life

The joule is named after the English physicist James Prescott Joule, who showed that mechanical work and heat are two faces of the same thing: energy. One joule is roughly the work needed to lift a 100 g tomato by one metre — so the 2378 J spent hauling the crate up the ramp is like lifting that tomato nearly two and a half thousand times!

EXERCISE 1 Lifting water at the well

A girl draws a bucket of water of mass 12 kg from a well 15 m deep, at constant speed, using a rope. Taking $g = 9.81 \text{ m s}^{-2}$, find (a) the work she does against gravity; (b) the work done by gravity on the bucket during the lift; (c) the work done by gravity if the full bucket is then lowered back down to the water surface.

SOLUTION Exercise 1

(a) Work against gravity: $W = mgh = 12 \times 9.81 \times 15 = 1765.8 \text{ J} \approx 1766 \text{ J}$. (b) The bucket rises while gravity acts downward, so the work done by gravity is -1765.8 J . (c) On the way down, gravity acts in the direction of motion, so the work done by gravity is $+1765.8 \text{ J}$. Over the whole round trip, the total work done by gravity is zero — another illustration that gravity is conservative.

EXERCISE 2 Sack on a building site

A worker pulls a sack of cement of mass 40 kg at constant speed 10 m up a plank inclined at 30° to the horizontal. Friction between sack and plank is 60 N. Take $g = 10 \text{ m s}^{-2}$. Find (a) the vertical height gained; (b) the work done against gravity; (c) the work done against friction; (d) the work done by the worker.

SOLUTION Exercise 2

(a) $h = s \sin \alpha = 10 \sin 30^\circ = 5 \text{ m}$. (b) $W_g = mgh = 40 \times 10 \times 5 = 2000 \text{ J}$. (c) $W_f = fs = 60 \times 10 = 600 \text{ J}$. (d) At constant speed, $W = W_g + W_f = 2000 + 600 = 2600 \text{ J}$.

KEY POINTS Key points of this section

- Work of a constant force: $W = \vec{F} \cdot \vec{s} = Fs \cos \theta$, in joules ($1 \text{ J} = 1 \text{ N m}$); work is a scalar.
- $\theta < 90^\circ$: positive work; $\theta = 90^\circ$: zero work; $\theta > 90^\circ$: negative work (e.g., friction).
- Total work = algebraic sum of individual works = work of resultant force.
- Work against gravity = mgh , where h is the vertical height; gravity's work is path-independent (conservative force).
- Up a rough plane at constant speed: work of the applied force = $mgh + fs$, with $h = s \sin \alpha$.

2 WORK DONE BY VARIABLE FORCES

2.1 From Constant Forces to Variable Forces

In the previous section we established that when a **constant** force F moves a body through a displacement s along its line of action, the work done is $W = Fs$. This formula served us well for a man pushing a wheelbarrow with a steady force, or for the work done against gravity when lifting a bag of cement at constant speed, where the lifting force equals the constant weight mg .

But look around you in everyday Cameroonian life and you will quickly notice that truly constant forces are the exception rather than the rule. When a trader at Mokolo market stretches the rubber band holding a bundle of vegetables, the band pulls back harder and harder the more it is stretched. When a mechanic compresses the suspension spring of a bendskin (motorbike), the resistance grows with compression. When a crane slowly lifts a long chain from the ground,

the weight being lifted increases as more links leave the floor. In all these situations the force depends on position, and the simple product $W = Fs$ no longer applies.

WARNING Why $W = Fs$ fails for a variable force

The formula $W = Fs$ was derived under the hypothesis that F keeps the same value throughout the displacement. If F changes with position x , which value of F should we multiply by s ? The initial value underestimates the work, the final value overestimates it, and no single value is correct. We need a new tool — and that tool is **integration**.

2.2 Work as the Area Under the Force–Displacement Graph

Let us build the idea step by step. Suppose a force $F(x)$ acts on a body moving along the x -axis from $x = a$ to $x = b$. Divide the interval $[a, b]$ into many tiny sub-intervals of width δx . On each tiny sub-interval, the force barely changes, so it is approximately constant there, and the work done across that small piece is approximately

$$\delta W \approx F(x) \delta x.$$

But $F(x) \delta x$ is precisely the area of a thin rectangle of height $F(x)$ and width δx under the graph of F against x . Adding all these small contributions and letting $\delta x \rightarrow 0$, the total work becomes the exact area under the force–displacement curve between a and b — which is exactly what the definite integral computes.

DEFINITION Work done by a variable force

The **work done** by a variable force $F(x)$ acting along the direction of motion in moving a body from position $x = a$ to position $x = b$ is

$$W = \int_a^b F(x) dx.$$

Geometrically, W is the **area under the force–displacement graph** between $x = a$ and $x = b$. The unit of work remains the joule ($1 \text{ J} = 1 \text{ N m}$).

KEY POINTS Key points

- Constant force: $W = Fs$ (a special case of the integral, since $\int_0^s F dx = Fs$).
- Variable force: $W = \int_a^b F(x) dx = \text{area under the } F\text{--}x \text{ graph.}$
- If the force opposes the motion, the work done by the force is negative; the work done against it is positive.

WORKED EXAMPLE 4 Work done by a force given as a function of x

A force of magnitude $F(x) = 3x^2 + 2x$ newtons acts on a particle moving along the x -axis, in the direction of motion. Calculate the work done by the force as the particle moves from $x = 1$ m to $x = 3$ m.

SOLUTION

Solution. The force varies with position, so we integrate:

$$\begin{aligned} W &= \int_1^3 (3x^2 + 2x) dx \\ &= [x^3 + x^2]_1^3 \\ &= (3^3 + 3^2) - (1^3 + 1^2) \\ &= (27 + 9) - (1 + 1) = 36 - 2 = 34. \end{aligned}$$

The work done by the force is $W = 34$ J.

2.3 Hooke's Law: Springs and Elastic Strings

The most important example of a variable force at GCE Advanced Level is the tension in a **spring** or **elastic string**. Take a light spring fixed at one end and pull the free end horizontally. The more you stretch it, the harder it pulls back. This experimental observation is summarised by a famous law.

EXPERIMENT Stretching a spring

Hang a light spring vertically, fix a pointer to its lower end, and add slotted masses one at a time, recording the extension x each time. Plotting the tension $T = mg$ against x gives, for moderate extensions, a straight line through the origin: the tension is proportional to the extension. Beyond a certain load (the **elastic limit**), the line curves and the spring is permanently deformed.

PROPERTY Hooke's Law

When a light elastic spring (or string) of natural length l is stretched by an **extension** x (within its elastic limit), the tension pulling back towards the natural length is


$$T = kx, \quad \text{equivalently} \quad T = \frac{\lambda}{l} x,$$

where k is the **stiffness** (or spring constant, in N m^{-1}) and λ is the **modulus of elasticity** (in newtons). The same law holds for compression of a spring, with x the compression. (The

statement of Hooke's law is examinable; its experimental verification above is a useful guided activity.)

WARNING Extension, not total length

In $T = kx$, the quantity x is the extension, i.e. (stretched length) – (natural length). A very common examination error is to substitute the total stretched length for x . Always compute $x = \text{new length} - l$ first.



A light spring fixed at one end: at natural length l (top) and stretched by x (bottom), where it exerts a tension $T = kx$ directed back towards the natural length.

2.4 Work Done in Stretching a Spring

To stretch a spring slowly by an extension x , you must apply a force equal and opposite to the tension, i.e. an applied force $F(x) = kx$. This force is not constant: it starts at 0 and grows linearly to ke when the extension reaches its final value e . The work you do is therefore given by integration.

PROPERTY Work done in stretching a spring from its natural length


The work done in stretching a light spring of stiffness k from its natural length to an extension e is

$$W = \frac{1}{2}ke^2.$$

This work is stored in the spring as **elastic potential energy** and is fully recoverable when the spring returns to its natural length (within the elastic limit). (The derivation below is examinable.)

Derivation. The applied force at extension x is $F(x) = kx$. Hence

$$W = \int_0^e kx \, dx = k \left[\frac{x^2}{2} \right]_0^e = \frac{1}{2}ke^2. \quad \blacksquare$$



The force–extension graph for a spring is the straight line $F = kx$. The work done stretching from 0 to e is the shaded triangular area: $W = \frac{1}{2} \times e \times ke = \frac{1}{2}ke^2$.

EXAMPLE Graphical check: area of a triangle

Since $F = kx$ is a straight line through the origin, the area under it from 0 to e is a triangle of base e and height ke :

$$W = \frac{1}{2} \times \text{base} \times \text{height} = \frac{1}{2} \times e \times ke = \frac{1}{2}ke^2,$$

confirming the integral. Note that $\frac{1}{2}ke$ is the average force over the stretch, so $W = (\text{average force}) \times (\text{extension})$ — a useful way to remember the factor $\frac{1}{2}$.

2.5 Work Done Between Two Extensions

Often the spring is already stretched by e_1 and is then stretched further to e_2 . The force still varies, so we integrate between the two extensions.

METHOD Work done in stretching from extension e_1 to extension e_2

1. Write the applied force as a function of extension: $F(x) = kx$.
2. Integrate between the two extensions:

$$W = \int_{e_1}^{e_2} kx \, dx = k \left[\frac{x^2}{2} \right]_{e_1}^{e_2}.$$

3. Conclude:

$$W = \frac{1}{2}k(e_2^2 - e_1^2).$$

Equivalently, this is the area of a trapezium under the line $F = kx$ between e_1 and e_2 : parallel sides ke_1 and ke_2 , width $(e_2 - e_1)$, giving $W = \frac{1}{2}(ke_1 + ke_2)(e_2 - e_1) = \frac{1}{2}k(e_2^2 - e_1^2)$.

WORKED EXAMPLE 5 Stretching a spring further

A light spring has stiffness $k = 200 \text{ N m}^{-1}$. It is already stretched by $e_1 = 0.10 \text{ m}$. Calculate the extra work needed to stretch it to an extension $e_2 = 0.30 \text{ m}$.

SOLUTION

Solution. Integrate the force $F(x) = 200x$ between the two extensions:

$$\begin{aligned} W &= \int_{0.10}^{0.30} 200x \, dx = 200 \left[\frac{x^2}{2} \right]_{0.10}^{0.30} \\ &= 100(0.30^2 - 0.10^2) = 100(0.09 - 0.01) = 100 \times 0.08. \end{aligned}$$

Hence $W = 8 \text{ J}$. Notice that this is more than the work needed for the first 0.10 m (which was only $\frac{1}{2}(200)(0.10)^2 = 1 \text{ J}$): the further the spring is stretched, the harder each additional centimetre becomes.

WORKED EXAMPLE 6 A spring with a modulus of elasticity

A light elastic string has natural length $l = 1.2 \text{ m}$ and modulus of elasticity $\lambda = 60 \text{ N}$. Find the work done in stretching it from its natural length to a total length of 1.5 m .

SOLUTION

Solution. First find the extension: $e = 1.5 - 1.2 = 0.3 \text{ m}$. The stiffness is

$$k = \frac{\lambda}{l} = \frac{60}{1.2} = 50 \text{ N m}^{-1}.$$

Therefore

$$W = \frac{1}{2}ke^2 = \frac{1}{2} \times 50 \times (0.3)^2 = 25 \times 0.09 = 2.25 \text{ J}.$$

The work done is $W = 2.25 \text{ J}$.

WARNING The most common trap: (final force) $\times$ (extension)

Do not compute the work in stretching a spring as $(ke) \times e = ke^2$. The force is not constant — it grows from 0 to ke — so using the final force throughout overestimates the work by a factor of 2. The correct result is $W = \frac{1}{2}ke^2$, i.e. the average force $\frac{1}{2}ke$ times the extension. Similarly, between two extensions use $W = \frac{1}{2}k(e_2^2 - e_1^2)$, never $ke_2(e_2 - e_1)$.

2.6 Link with Elastic Potential Energy (Looking Ahead)**DID YOU KNOW?** Energy stored in a spring

The work $\frac{1}{2}ke^2$ done in stretching a spring is not lost: it is stored inside the spring as **elastic potential energy** (EPE),

$$\text{EPE} = \frac{1}{2}ke^2 = \frac{\lambda x^2}{2l},$$

and is released when the spring contracts. This is why a stretched catapult can launch a stone, and why the suspension springs of a bendskin absorb the shocks of Douala's pot-holes and give the energy back smoothly. We shall exploit this fully in the sections on energy conservation: the work you do on a spring becomes stored energy, which can later become kinetic energy.

EXERCISE 3 Practice

1. A force $F(x) = 5x + 4$ newtons moves a body from $x = 0$ to $x = 2$ m along its line of action. Find the work done.
2. A spring of stiffness $k = 150 \text{ N m}^{-1}$ is stretched from its natural length by 0.20 m. Find the work done.
3. For the spring of question 2, find the additional work needed to increase the extension from 0.20 m to 0.40 m. Why is this not simply twice the answer to question 2?
4. A light elastic string has natural length 0.8 m and modulus $\lambda = 40 \text{ N}$. Calculate the work done in stretching it to a length of 1.0 m.

SOLUTION Exercise 1

$$1. W = \int_0^2 (5x + 4) dx = \left[\frac{5x^2}{2} + 4x \right]_0^2 = 10 + 8 = 18 \text{ J}.$$

2. $W = \frac{1}{2}ke^2 = \frac{1}{2}(150)(0.20)^2 = 75 \times 0.04 = 3 \text{ J}.$
3. $W = \frac{1}{2}(150)(0.40^2 - 0.20^2) = 75(0.16 - 0.04) = 75 \times 0.12 = 9 \text{ J}.$ This is three times the answer to question 2 (not twice), because the force is larger on average over the second interval: work depends on e^2 , not on e .
4. Extension $e = 1.0 - 0.8 = 0.2 \text{ m}$; stiffness $k = \lambda/l = 40/0.8 = 50 \text{ N m}^{-1}$. Hence $W = \frac{1}{2}(50)(0.2)^2 = 25 \times 0.04 = 1 \text{ J}.$

KEY POINTS Summary of the section

- Variable force along a line: $W = \int_a^b F(x) dx = \text{area under the } F-x \text{ graph}.$
- Hooke's law: $T = kx = \frac{\lambda}{l}x$, with x the extension.
- Work to stretch a spring from natural length: $W = \frac{1}{2}ke^2$ (triangular area).
- Work between extensions e_1 and e_2 : $W = \frac{1}{2}k(e_2^2 - e_1^2)$ (trapezium area).
- Never use (final force) $\times$ (extension): the factor $\frac{1}{2}$ comes from the force growing linearly from zero.
- The work stored in a stretched spring is elastic potential energy, $\frac{1}{2}ke^2$, ready to be reused in energy problems.

3 ENERGY: KINETIC AND POTENTIAL

In the previous sections we learnt how to calculate the work done by a force, whether constant or variable. We established that work is the mechanism by which energy is transferred to or from a body. But what exactly is energy? In mechanics, energy is the capacity to do work. A moving car can crash into a barrier and deform it — it has the capacity to do work because of its motion. A water tank on a rooftop in Bamenda can drive a turbine when the water falls — it has the capacity to do work because of its position. In this section we formalise these two fundamental forms of mechanical energy: **kinetic energy** (energy of motion) and **potential energy** (energy of position).

3.1 The Concept of Energy

DEFINITION Energy

Energy is a scalar quantity that measures the capacity of a body or a system to do work. The SI unit of energy is the joule (J), the same unit as work:

$$1 \text{ J} = 1 \text{ N m} = 1 \text{ kg m}^2 \text{ s}^{-2}.$$

Energy, like work, is a scalar — it has magnitude but no direction.

Energy exists in many forms: mechanical, chemical, electrical, nuclear, thermal, and so on. In mechanics we focus on mechanical energy, which is the sum of kinetic energy and potential energy. The principle of conservation of energy, which we shall study in the next section, tells us that in an isolated system the total energy remains constant, merely transforming from one form to another.

3.2 Kinetic Energy

Consider a body of mass m initially at rest on a smooth horizontal surface. A constant net force F acts on it over a displacement s , accelerating it from rest to a speed v . The work done by the force is $W = Fs$. From Newton's second law, $F = ma$, and from the kinematic relation $v^2 = u^2 + 2as$ with $u = 0$, we obtain $v^2 = 2as$, that is $as = \frac{1}{2}v^2$. Hence

$$W = Fs = m(as) = m\left(\frac{1}{2}v^2\right) = \frac{1}{2}mv^2.$$

This work done on the body is now stored as its kinetic energy — the energy it possesses by virtue of its motion. This derivation is examinable and should be reproduced fluently.

DEFINITION Kinetic Energy

The kinetic energy (KE) of a body of mass m moving with speed v is defined as

$$\text{KE} = \frac{1}{2}mv^2.$$

Kinetic energy is a scalar quantity measured in joules (J). It depends on the mass and on the square of the speed.

PROPERTY Properties of Kinetic Energy

1. Non-negativity: $\text{KE} \geq 0$ for all v ; $\text{KE} = 0$ only when $v = 0$ (the body is at rest).
2. Depends on speed, not velocity: Since $v^2 = \vec{v} \cdot \vec{v} = |\vec{v}|^2$, kinetic energy depends only on the magnitude of the velocity, never on its direction. A body moving north at 10 m s^{-1} has the same KE as a body of the same mass moving south at 10 m s^{-1} .

3. Change in kinetic energy: If the speed changes from u to v , the change in kinetic energy is

$$\Delta KE = \frac{1}{2}mv^2 - \frac{1}{2}mu^2 = \frac{1}{2}m(v^2 - u^2).$$

This quantity can be positive (gain in KE), negative (loss in KE), or zero.

4. Quadratic dependence on speed: Doubling the speed quadruples the kinetic energy; tripling the speed increases KE ninefold.

WARNING Common Errors with Kinetic Energy

- Forgetting the factor $\frac{1}{2}$: Writing $KE = mv^2$ is a very frequent mistake. Always remember the half!
- Using velocity instead of speed: Kinetic energy uses v^2 (speed squared), not $\vec{v}^2$. Never write $\frac{1}{2}m\vec{v}^2$.
- Confusing ΔKE with KE: The work–energy theorem relates net work to the change in kinetic energy, not to the kinetic energy itself.
- Unit errors: Mass must be in kg and speed in m s^{-1} to obtain energy in joules. If mass is given in tonnes or grams, or speed in km h^{-1} , convert first (divide km h^{-1} by 3.6).

EXAMPLE Kinetic Energy Calculations

Calculate the kinetic energy of:

1. A car of mass 1200 kg travelling at 25 m s^{-1} (90 km h^{-1}).
2. A bullet of mass 8 g fired at 400 m s^{-1} .
3. A lorry of mass 15 tonnes whose speed increases from 10 m s^{-1} to 20 m s^{-1} . Find the gain in kinetic energy.

Solution.

1. $KE = \frac{1}{2}(1200)(25^2) = 600 \times 625 = 375\,000 \text{ J} = 375 \text{ kJ}.$
2. Mass $m = 8 \text{ g} = 0.008 \text{ kg}$. $KE = \frac{1}{2}(0.008)(400^2) = 0.004 \times 160\,000 = 640 \text{ J}.$
3. $m = 15 \text{ tonnes} = 15\,000 \text{ kg}.$
 $\Delta KE = \frac{1}{2}(15\,000)(20^2 - 10^2) = 7\,500 \times (400 - 100) = 7\,500 \times 300 = 2\,250\,000 \text{ J} = 2.25 \text{ MJ}.$

Notice that the gain in KE when the speed doubles from 10 to 20 m s^{-1} is three times

the initial KE at 10 m s^{-1} (which is $\frac{1}{2}(15\,000)(10^2) = 750 \text{ kJ}$).

3.3 Gravitational Potential Energy


When you lift a book from the floor to a shelf, you do work against the gravitational force. That work is stored as gravitational potential energy — energy due to the body's position in a gravitational field. Unlike kinetic energy, potential energy is defined only up to an additive constant: we must choose a reference level (zero level) where $PE = 0$.

DEFINITION Gravitational Potential Energy

The gravitational potential energy (PE) of a body of mass m at a vertical height h above a chosen reference level is

$$PE = mgh,$$

where $g = 9.81 \text{ m s}^{-2}$ (or 9.8 m s^{-2} as specified in the examination). PE is a scalar measured in joules (J). The height h is the vertical distance above the reference level.



Gravitational potential energy at two different heights above a chosen reference level.

PROPERTY Key Points on Gravitational Potential Energy

1. Reference level is arbitrary: You may choose the ground, the floor, the lowest point of the motion, or any convenient horizontal plane as $h = 0$. The value of PE changes with the choice, but the difference in PE between two points does not.
2. Only changes in PE are physically significant: The work done by gravity when a body

moves from height h_1 to height h_2 is $W = mg(h_1 - h_2) = -\Delta PE$. This is independent of the reference level.

3. Gain and loss: When a body is raised, $\Delta PE > 0$ (gain). When it is lowered, $\Delta PE < 0$ (loss).
4. Path independence: The change in gravitational PE depends only on the initial and final vertical heights, not on the path taken (straight up, inclined plane, or curved track). This is why gravity is called a conservative force.

METHOD Choosing and Using a Reference Level for PE

1. Identify the initial and final positions of the body in the problem.
2. Choose a convenient horizontal reference level (often the lowest point reached, or the ground). State it clearly: "Take the reference level as the ground / the bottom of the incline / the lowest point."
3. Measure the vertical heights h_i and h_f of the initial and final positions above this reference.
4. Compute $PE_i = mgh_i$ and $PE_f = mgh_f$.
5. Find the change: $\Delta PE = PE_f - PE_i = mg(h_f - h_i)$.

EXAMPLE Potential Energy on an Inclined Plane

A block of mass 5 kg slides down a smooth plane inclined at 30° to the horizontal. The block travels 4 m along the plane from rest. Take the reference level as the bottom of the incline (where the block would be after sliding 4 m). Find:

1. The initial height of the block above the reference level.
2. The initial and final gravitational potential energies.
3. The loss in potential energy.

Solution.

1. The vertical height dropped is $h = 4 \sin 30^\circ = 4 \times 0.5 = 2$ m. Since the reference is the bottom, the initial height is $h_i = 2$ m and the final height is $h_f = 0$.
2. $PE_i = mgh_i = 5 \times 9.81 \times 2 = 98.1$ J. $PE_f = 0$.
3. Loss in PE = $PE_i - PE_f = 98.1$ J. (Equivalently $\Delta PE = -98.1$ J.)

Note: If we had chosen the starting point as reference ($h_i = 0$, $h_f = -2$ m), then $PE_i = 0$,

$PE_f = -98.1 \text{ J}$, and $\Delta PE = -98.1 \text{ J}$ — the same change, confirming that only differences matter.

3.4 Elastic Potential Energy (Brief Overview)

While the syllabus focuses on gravitational potential energy, it is useful to know that energy can also be stored in a deformed elastic body, such as a stretched or compressed spring.

PROPERTY Elastic Potential Energy

For a light spring of stiffness k (spring constant, in N m^{-1}) stretched or compressed by an extension x from its natural length, the elastic potential energy (EPE) stored is

$$\text{EPE} = \frac{1}{2} k x^2.$$

This follows from the work done against the variable tension $T = kx$ (Hooke's law): $W = \int_0^x kx \, dx = \frac{1}{2} k x^2$. Like gravitational PE, EPE is always non-negative, and it depends on the square of the deformation.


WARNING Elastic PE — Extension Beyond the Core Syllabus

Elastic potential energy is not explicitly required in the GCE Advanced Level Pure Mathematics with Mechanics syllabus for this chapter, but it appears in Further Mechanics and in many physics contexts. Notice the pattern $\frac{1}{2} k x^2$, exactly analogous to $\frac{1}{2} m v^2$: energy stored in a quadratic degree of freedom always carries the factor $\frac{1}{2}$.

3.5 Computational Drills and Applications

Let us now practise quick calculations that illustrate the quadratic growth of kinetic energy with speed and the linear growth of potential energy with height.

Kinetic Energy of a 1000 kg Car at Different Speeds



Quadratic growth of kinetic energy with speed for a car of mass 1000 kg. KE at 10 m s^{-1} is 50 kJ; at 20 m s^{-1} it is 200 kJ ($4\times$); at 30 m s^{-1} it is 450 kJ ($9\times$).

EXAMPLE Quick Drills: KE and PE

1. A motorbike of mass 200 kg has a kinetic energy of 50 kJ. What is its speed?
2. Water of mass 5000 kg is stored in a tank 20 m above ground level. Taking the ground as reference, find the gravitational potential energy of the water.
3. A stone of mass 0.5 kg is thrown vertically upwards with an initial speed of 20 m s^{-1} . Find its kinetic energy at the start and its maximum gain in potential energy (ignore air resistance).

Solution.

1. $\text{KE} = \frac{1}{2}mv^2 \Rightarrow 50\,000 = \frac{1}{2}(200)v^2 = 100v^2 \Rightarrow v^2 = 500 \Rightarrow v = \sqrt{500} \approx 22.4 \text{ m s}^{-1}$.
2. $\text{PE} = mgh = 5000 \times 9.81 \times 20 = 981\,000 \text{ J} = 981 \text{ kJ}$.
3. Initial $\text{KE} = \frac{1}{2}(0.5)(20^2) = 0.25 \times 400 = 100 \text{ J}$. At maximum height the speed is 0, so the final KE is 0. By conservation of energy (no air resistance), loss in KE = gain in PE = 100 J.
Maximum height: $h = \frac{\text{PE}}{mg} = \frac{100}{0.5 \times 9.81} \approx 20.4 \text{ m}$.

WORKED EXAMPLE 7 Energy Changes on a Roller Coaster

A roller coaster car of mass 800 kg (including passengers) starts from rest at point A,

which is 40 m above the ground. It descends to point B at ground level, then rises to point C at 25 m above ground. Assume the track is smooth (no friction). Take the ground as the reference level for PE ($g = 9.81 \text{ m s}^{-2}$). Find:

1. The total mechanical energy at A.
2. The kinetic energy and speed at B.
3. The kinetic energy and speed at C.

SOLUTION

Solution. Since the track is smooth, mechanical energy is conserved: $\text{KE} + \text{PE} = \text{constant}$.
At A: $v_A = 0$, $h_A = 40 \text{ m}$. $\text{KE}_A = 0$. $\text{PE}_A = mgh_A = 800 \times 9.81 \times 40 = 313\,920 \text{ J}$. Total mechanical energy: $E = \text{KE}_A + \text{PE}_A = 313\,920 \text{ J}$.

At B: $h_B = 0$, so $\text{PE}_B = 0$. $\text{KE}_B = E - \text{PE}_B = 313\,920 \text{ J}$. $\frac{1}{2}mv_B^2 = 313\,920 \Rightarrow v_B^2 = \frac{2 \times 313\,920}{800} = 784.8 \Rightarrow v_B \approx 28.0 \text{ m s}^{-1}$.

At C: $h_C = 25 \text{ m}$. $\text{PE}_C = 800 \times 9.81 \times 25 = 196\,200 \text{ J}$. $\text{KE}_C = E - \text{PE}_C = 313\,920 - 196\,200 = 117\,720 \text{ J}$. $\frac{1}{2}mv_C^2 = 117\,720 \Rightarrow v_C^2 = \frac{2 \times 117\,720}{800} = 294.3 \Rightarrow v_C \approx 17.2 \text{ m s}^{-1}$.

Check: the mass cancels in $\frac{1}{2}mv^2 + mgh = \text{constant}$, so the speeds depend only on the heights, not on the mass of the car — a useful quick check in the examination.

3.6 Summary of Key Points

KEY POINTS Energy: Kinetic and Potential — Key Points

- Energy is the capacity to do work; scalar, unit joule (J).
- Kinetic Energy: $\text{KE} = \frac{1}{2}mv^2$. Always ≥ 0 . Depends on speed squared, not direction. $\Delta\text{KE} = \frac{1}{2}m(v^2 - u^2)$.
- Gravitational Potential Energy: $\text{PE} = mgh$ relative to a chosen reference level. Only changes in PE are physically meaningful: $\Delta\text{PE} = mg \Delta h$.
- Reference level: Must be stated clearly. Convenient choices: ground, lowest point, initial position.
- Elastic Potential Energy (extension): $\text{EPE} = \frac{1}{2}kx^2$ for a spring of stiffness k extended by x .
- Quadratic vs Linear: KE grows with v^2 (doubling speed $\Rightarrow \text{KE} \times 4$). PE grows linearly with h .
- Common pitfalls: Forgetting $\frac{1}{2}$ in KE; using v instead of v^2 ; not converting mass to kg or speed to m s^{-1} ; not stating the reference level for PE.

EXERCISE 4 Practice Exercise

1. A truck of mass 12 tonnes travels at 72 km h^{-1} . Calculate its kinetic energy in MJ.
2. A girl of mass 45 kg climbs a vertical rope through 6 m. Taking the starting point as reference, find her gain in gravitational potential energy.
3. A spring of stiffness 200 N m^{-1} is compressed by 0.15 m. Find the elastic potential energy stored.
4. A ball of mass 0.2 kg is dropped from a height of 10 m. Find its kinetic energy just before it hits the ground (ignore air resistance, $g = 9.81 \text{ m s}^{-2}$).
5. A car of mass 1000 kg accelerates from 15 m s^{-1} to 30 m s^{-1} . Find the increase in its kinetic energy. By what factor does the KE increase?

SOLUTION Exercise

1. $m = 12\,000 \text{ kg}$, $v = 72 \text{ km h}^{-1} = 20 \text{ m s}^{-1}$. $\text{KE} = \frac{1}{2}(12\,000)(20^2) = 2\,400\,000 \text{ J} = 2.4 \text{ MJ}$.
2. Gain in PE = $mg \Delta h = 45 \times 9.81 \times 6 = 2648.7 \text{ J} \approx 2.65 \text{ kJ}$.
3. $\text{EPE} = \frac{1}{2}kx^2 = \frac{1}{2}(200)(0.15^2) = 100 \times 0.0225 = 2.25 \text{ J}$.
4. Loss in PE = gain in KE = $mgh = 0.2 \times 9.81 \times 10 = 19.62 \text{ J}$.
5. $\Delta \text{KE} = \frac{1}{2}(1000)(30^2 - 15^2) = 500 \times (900 - 225) = 500 \times 675 = 337\,500 \text{ J} = 337.5 \text{ kJ}$. Initial KE = $\frac{1}{2}(1000)(15^2) = 112.5 \text{ kJ}$; final KE = 450 kJ. Factor = $\frac{450}{112.5} = 4$ (speed doubled $\Rightarrow$ KE $\times 4$).

4 THE WORK-ENERGY THEOREM AND CONSERVATION OF ENERGY

In the previous section we met the two great forms of mechanical energy: **kinetic energy** $\frac{1}{2}mv^2$, the energy a body possesses because it moves, and **gravitational potential energy** mgh , the energy it possesses because of its position in the Earth's gravitational field. We also saw that **work** is the mechanism by which energy is transferred: when a force does work on a body, energy flows into (or out of) that body. In this section we make that idea precise. The result is the **work-energy theorem**, one of the most powerful labour-saving devices in all of mechanics, and its celebrated consequence, the **principle of conservation of mechanical energy**. Together they allow us to find speeds directly — without resolving forces, without finding accelerations, and without touching the equations of motion.

4.1 The Work–Energy Theorem

Intuition.

Push a trolley along a level floor. The work you do does not disappear — it reappears as motion: the trolley speeds up. If a rough patch of floor does negative work on the trolley, the trolley slows down: kinetic energy is drained away. This suggests a precise accounting rule:

$$(\text{total work done on the body}) = (\text{change in its kinetic energy}).$$

PROPERTY Work–Energy Theorem

The total (net) work done by all the forces acting on a body during a displacement equals the change in the body's kinetic energy:

$$W_{\text{net}} = \Delta KE = \frac{1}{2}mv^2 - \frac{1}{2}mu^2,$$

where u and v are the initial and final speeds. This holds whether the forces are constant or variable, and whether the path is straight or curved.

Derivation (examinable for constant force in a straight line; general case by integration).

For a body of mass m moving in a straight line under a constant resultant force F , Newton's second law gives $F = ma$, where a is the constant acceleration. Over a displacement s , the constant-acceleration formula

$$v^2 = u^2 + 2as \quad \implies \quad as = \frac{1}{2}(v^2 - u^2).$$

The work done by the resultant force is $W = Fs$. Substituting $F = ma$:

$$W = mas = m \cdot \frac{1}{2}(v^2 - u^2) = \frac{1}{2}mv^2 - \frac{1}{2}mu^2. \quad \blacksquare$$

For a variable force $F(x)$ acting along a straight line, the work is $W = \int F(x) dx$. Using $F = m \frac{dv}{dt} = mv \frac{dv}{dx}$, we obtain

$$W = \int mv \frac{dv}{dx} dx = \int_u^v mv dv = \frac{1}{2}mv^2 - \frac{1}{2}mu^2.$$

For a curved path, the same argument applies to the tangential component of the resultant force. Hence the theorem is completely general.

WARNING Signs matter

Work done by a force that helps the motion is positive and increases the kinetic energy; work done against the motion (friction, resistance, braking) is negative and decreases it. Always compute the net work: add the work of every force with its correct sign.

4.2 Horizontal Motion with Driving and Resisting Forces

A very common GCE situation: a vehicle or body moves along a horizontal road under a driving force F and a resistance R . Gravity and the normal reaction do no work (they are perpendicular

to the motion), so the work–energy theorem over a distance s gives

$$(F - R)s = \frac{1}{2}mv^2 - \frac{1}{2}mu^2.$$

WORKED EXAMPLE 8 Accelerating car on a level road

A car of mass 900 kg accelerates from 5 m s^{-1} to 15 m s^{-1} over a distance of 200 m on a horizontal road, against a constant resistance of 400 N. Find the driving force exerted by the engine.

SOLUTION

Solution. Apply the work–energy theorem with $u = 5$, $v = 15$, $s = 200$, $m = 900$:

$$(F - 400)(200) = \frac{1}{2}(900)(15^2 - 5^2) = 450 \times 200 = 90\,000 \text{ J}.$$

Hence

$$F - 400 = \frac{90\,000}{200} = 450 \quad \Rightarrow \quad \boxed{F = 850 \text{ N}}.$$

Notice that we never needed the acceleration or the time taken.

4.3 Conservation of Mechanical Energy

Now suppose a body moves under gravity alone (no friction, no resistance, no driving force). Over a vertical drop h , gravity does work mgh , so by the work–energy theorem

$$mgh = \frac{1}{2}mv^2 - \frac{1}{2}mu^2 \quad \Rightarrow \quad \frac{1}{2}mu^2 + mgh_{\text{initial}} = \frac{1}{2}mv^2 + mgh_{\text{final}}.$$

In other words, the sum KE + PE is unchanged.

PROPERTY Conservation of Mechanical Energy

If gravity is the only force that does work on a body (i.e. no non-conservative forces such as friction or air resistance do work), then its total mechanical energy is constant:


$$\text{KE} + \text{PE} = \frac{1}{2}mv^2 + mgh = \text{constant}.$$

Equivalently, any loss of potential energy appears as an equal gain of kinetic energy, and conversely.

WARNING When conservation fails

Conservation of mechanical energy requires that no non-conservative force does work. On a rough surface, friction does negative work and mechanical energy is not conserved — it is converted into heat. Do not write $\text{KE} + \text{PE} = \text{constant}$ on a rough slope; use the

energy balance with a friction term instead (below).



A pendulum bob released from rest at A. At the top all the energy is potential; at the bottom B it is entirely kinetic: $mgh = \frac{1}{2}mv^2$.

EXAMPLE The swinging pendulum

A pendulum bob of mass 0.2 kg is released from rest with the string taut at a point 0.45 m vertically above its lowest position. Taking $g = 9.8 \text{ m s}^{-2}$, conservation of energy between the top and the bottom gives

$$mgh = \frac{1}{2}mv^2 \implies v = \sqrt{2gh} = \sqrt{2 \times 9.8 \times 0.45} = \sqrt{8.82} \approx 3.0 \text{ m s}^{-1}.$$

The mass cancels — the speed at the bottom is independent of the bob's mass.

4.4 Energy Balance with Friction: the General Energy Equation

When friction (or another resistance) does work, mechanical energy is no longer conserved, but energy itself is: the “missing” mechanical energy is exactly the work done against the resistance. The work–energy theorem, applied to all forces, gives the master equation of this chapter:

KEY POINTS General energy balance


For a body moving under the action of external forces (other than gravity) and a resistance R over a path of length s :

$$W_{\text{ext}} = \Delta KE + \Delta PE + W_{\text{resistance}},$$

where W_{ext} is the work done by all external forces except gravity, $\Delta KE = \frac{1}{2}mv^2 - \frac{1}{2}mu^2$, $\Delta PE = mg\Delta h$, and $W_{\text{resistance}} = Rs$ for a constant resistance R opposing the motion. In words: initial energy + work input = final energy + energy lost to friction.

METHOD Solving “find the speed” problems by energy

1. Identify the initial and final positions and speeds; choose a reference level for PE.
2. List every force that does work: gravity (via ΔPE), driving forces, resistances.
3. Write the energy balance: initial KE + PE + work input = final KE + PE + work against friction.
4. Solve for the unknown speed, force or distance. No acceleration, no time, no resolving needed.



Energy flow for a block sliding from rest down a rough slope: the initial potential energy splits into final kinetic energy plus the work done against friction.

WORKED EXAMPLE 9 Sliding down a rough slope

A block of mass 4 kg is released from rest at the top of a rough slope of length 10 m and vertical height 6 m. The frictional resistance is constant at 8 N. Taking $g = 9.8 \text{ m s}^{-2}$, find the speed of the block at the bottom.

SOLUTION

Solution. Use the energy balance (no driving force):

initial PE = final KE + work against friction.

$$mgh = \frac{1}{2}mv^2 + Rs \Rightarrow 4 \times 9.8 \times 6 = \frac{1}{2}(4)v^2 + 8 \times 10.$$

$$235.2 = 2v^2 + 80 \Rightarrow 2v^2 = 155.2 \Rightarrow v^2 = 77.6.$$

$$v \approx 8.8 \text{ m s}^{-1}$$

Check: on a smooth slope the speed would be $\sqrt{2gh} = \sqrt{117.6} \approx 10.8 \text{ m s}^{-1}$; friction has reduced it, as expected.

EXAMPLE Body projected vertically upwards

A stone is thrown vertically upwards with speed 14 m s^{-1} . Ignoring air resistance, how high does it rise? Conservation of energy between launch and the highest point (where $v = 0$):

$$\frac{1}{2}mu^2 = mgh \implies h = \frac{u^2}{2g} = \frac{196}{19.6} = 10 \text{ m}.$$

Compare the labour with the kinematic route ($v^2 = u^2 - 2gs$): the energy method gives the same answer in one line.

DID YOU KNOW? Why engineers love energy

Energy methods are the everyday tool of engineers designing hydroelectric schemes such as those on the Sanaga river: the potential energy of water held at height is converted into kinetic energy and then into electrical energy, and the whole design calculation is an energy balance — exactly the equation $mgh = \frac{1}{2}mv^2 + \text{losses}$ that you have just used.

EXERCISE 5

A cyclist of total mass 80 kg freewheels (no pedalling) from rest down a hill of vertical drop 20 m along a road of length 250 m , against a constant resistance of 30 N . Taking $g = 9.8 \text{ m s}^{-2}$, find the speed at the bottom of the hill.

SOLUTION Exercise 1

Energy balance: initial PE = final KE + work against resistance:

$$80 \times 9.8 \times 20 = \frac{1}{2}(80)v^2 + 30 \times 250 \implies 15\,680 = 40v^2 + 7\,500.$$

$$40v^2 = 8\,180 \implies v^2 = 204.5 \implies v \approx 14.3 \text{ m s}^{-1}.$$

EXERCISE 6

A ball of mass 0.5 kg is projected vertically upwards at 12 m s^{-1} . It reaches a greatest height of 6.5 m. Find the work done against air resistance during the ascent, and deduce the mean resisting force. Take $g = 9.8 \text{ m s}^{-2}$.

SOLUTION Exercise 2

Initial KE = $\frac{1}{2}(0.5)(144) = 36 \text{ J}$. Final PE = $0.5 \times 9.8 \times 6.5 = 31.85 \text{ J}$. Work against resistance = $36 - 31.85 = 4.15 \text{ J}$. Mean force = $\frac{4.15}{6.5} \approx 0.64 \text{ N}$.

KEY POINTS Exam tip (GCE)

Whenever a question asks you to “find the speed” of a body that has moved through a height or along a slope — especially with friction mentioned — reach for the energy balance first. It avoids resolving forces, avoids finding the acceleration, and avoids the equations of motion entirely. Reserve Newton’s second law for questions that ask for accelerations, times, or tensions.

5 POWER: DEFINITION, INSTANTANEOUS POWER AND POWER-VELOCITY

In the previous section we established the **work–energy theorem**: the work done by the resultant force on a body equals its change in kinetic energy. That theorem tells us how much work is done, but it says nothing about how fast the work is done. Yet in everyday life this distinction is crucial. Two cranes on a construction site in Douala may lift the same load of cement through the same height — they do the same work — but the one that finishes in ten seconds is clearly more “powerful” than the one that needs a full minute. Similarly, two cars may both be capable of reaching 100 km/h, but the one that gets there in eight seconds has a more powerful engine. This section makes that idea precise.

5.1 Definition of Power

EXPERIMENT Comparing two workers

Manga and Etienne each carry a sack of rice of mass 50 kg up a ladder of height 4 m. Each

does work

$$W = mgh = 50 \times 9.81 \times 4 = 1962 \text{ J}$$

against gravity. Manga takes 8 s; Etienne takes 16 s. Same work, different rates. Manga works at $1962/8 \approx 245$ joules per second, Etienne at only $1962/16 \approx 123$ joules per second. The quantity “joules per second” is what physicists call **power**.

DEFINITION Power

Power is the rate at which work is done (equivalently, the rate at which energy is transferred or converted).

- If a constant amount of work W is done in time t , the average power is

$$P_{\text{av}} = \frac{W}{t}.$$

- The instantaneous power at time t is

$$P = \frac{dW}{dt}.$$

The SI unit of power is the **watt** (W): $1 \text{ W} = 1 \text{ J s}^{-1}$. Larger units are common: $1 \text{ kW} = 1000 \text{ W}$ and $1 \text{ MW} = 10^6 \text{ W}$.

WARNING Average power is not instantaneous power

Saying “the engine develops 60 kW” refers to the power at each instant. If a machine does 6000 J of work in 2 s, its average power is 3000 W, but its instantaneous power may have varied throughout those two seconds. In GCE questions about vehicles, P almost always means the (constant) instantaneous power output of the engine.

5.2 The Power–Velocity Relation $P = Fv$

Consider a constant force F acting on a body and moving its point of application with velocity v in the same direction as the force. In a small time interval δt , the body moves a distance $\delta s = v \delta t$, so the work done is

$$\delta W = F \delta s = Fv \delta t.$$

Dividing by δt and letting $\delta t \rightarrow 0$:

$$P = \frac{dW}{dt} = Fv.$$

PROPERTY Power of a force

For a constant force F whose point of application moves with velocity v in the direction of the force, the instantaneous power developed is

$$P = Fv.$$

More generally, if the force makes an angle θ with the velocity, $P = Fv \cos \theta$. This derivation is short and is frequently asked as a “show that” in the GCE.

EXAMPLE Power of a pulling force

A horizontal force of 400 N pulls a crate along a level floor at a steady speed of 2.5 m/s. The power developed is

$$P = Fv = 400 \times 2.5 = 1000 \text{ W} = 1 \text{ kW}.$$

5.3 Vehicles Moving with Constant Power


A car engine working at constant power P does not exert a constant driving force. Since $P = Fv$, the driving force at speed v is

$$F = \frac{P}{v}.$$

As the speed increases, the driving force decreases hyperbolically. This single fact explains the whole behaviour of vehicles and is the heart of almost every GCE question on this topic.

WARNING The most common GCE error

A vehicle with constant power does NOT have constant driving force. Never compute $F = P/v$ at one speed and then use that same F at a different speed. Always ask yourself: “at which speed am I evaluating the driving force?”



Driving force $F = P/v$ (here $P = 60 \text{ kW}$) decreases hyperbolically with speed. It meets the constant resistance $R = 2000 \text{ N}$ at $v_{\max} = P/R = 30 \text{ m/s}$: beyond this speed the resistance exceeds the driving force, so the car cannot accelerate further.

5.4 Equation of Motion and Maximum Speed on a Level Road

Let a vehicle of mass m move on a level road with engine power P , against a total resistance R (friction, air resistance, etc.). The forces along the road are the driving force P/v forwards and R backwards. Newton's second law gives the **equation of motion**:

$$\frac{P}{v} - R = ma.$$

At low speed P/v is large, so $a > 0$ and the vehicle accelerates. As v grows, P/v falls towards R , so the acceleration falls towards zero. The speed approaches a limiting value, the **maximum (terminal) speed**, reached when $a = 0$:

$$\frac{P}{v_{\max}} = R \quad \Rightarrow \quad v_{\max} = \frac{P}{R}.$$

METHOD Maximum speed problems

1. Convert all units: power to watts, speeds to m s^{-1} , masses to kg.
2. Write the equation of motion $\frac{P}{v} - (\text{total opposing force}) = ma$.
3. For maximum speed, set $a = 0$ and solve $\frac{P}{v_{\max}} = \text{total resisting force}$.
4. If acceleration at a given speed is required, substitute that speed into P/v and use Newton's second law.

WORKED EXAMPLE 10 Car on a level road

A car of mass 900 kg moves along a level road against a constant resistance of 600 N. Its engine works at a constant rate of 24 kW. Find (a) the maximum speed of the car; (b) the acceleration of the car when its speed is 20 m/s.

SOLUTION

Solution. Convert: $P = 24\,000\text{ W}$.

(a) At maximum speed, $a = 0$, so

$$\frac{P}{v_{\max}} = R \implies v_{\max} = \frac{24\,000}{600} = 40\text{ m s}^{-1}.$$

(b) At $v = 20\text{ m s}^{-1}$, the driving force is

$$F = \frac{P}{v} = \frac{24\,000}{20} = 1200\text{ N}.$$

Newton's second law:

$$1200 - 600 = 900a \implies a = \frac{600}{900} \approx 0.67\text{ m s}^{-2}.$$

Note how the driving force at 20 m/s (1200 N) differs from that at maximum speed (600 N): the force is not constant.

5.5 Motion on an Incline with Constant Power

When the vehicle climbs a hill inclined at angle α to the horizontal, the component of its weight along the slope, $mg \sin \alpha$, acts down the slope and must be added to the resistance. The equation of motion uphill is

$$\frac{P}{v} - R - mg \sin \alpha = ma,$$


so the maximum speed uphill satisfies

$$\frac{P}{v_{\max}} = R + mg \sin \alpha.$$

Going downhill, the weight component assists the motion, so (with the engine still working) the equation becomes

$$\frac{P}{v} + mg \sin \alpha - R = ma, \quad \text{and at maximum speed} \quad \frac{P}{v_{\max}} = R - mg \sin \alpha.$$

(If the engine is switched off downhill, simply delete the P/v term.)



Forces on a vehicle of mass m climbing a slope of angle α at speed v : driving force $F = P/v$ up the slope, resistance R and weight component $mg \sin \alpha$ down the slope. At maximum speed these balance: $P/v_{\max} = R + mg \sin \alpha$.

WORKED EXAMPLE 11 Lorry climbing a hill against a speed-dependent resistance

A lorry of mass 4000 kg has an engine working at a constant rate of 80 kW. The resistance to motion is $R = 40v$ newtons, where v is the speed in m s^{-1} . Take $g = 10 \text{ m s}^{-2}$.

1. Find the maximum speed of the lorry on a level road.
2. The lorry climbs a hill inclined at an angle α to the horizontal, where $\sin \alpha = \frac{1}{20}$. Find its maximum speed up the hill.
3. Find the acceleration of the lorry when it is climbing this hill at 10 m/s.

SOLUTION

Solution. $P = 80\,000 \text{ W}$, $m = 4000 \text{ kg}$.

1. Level road, $\alpha = 0$:

$$\frac{80\,000}{v} = 40v \implies v^2 = 2000 \implies v_{\max} = \sqrt{2000} \approx 44.7 \text{ m s}^{-1}.$$

2. Uphill, the weight component is

$$mg \sin \alpha = 4000 \times 10 \times \frac{1}{20} = 2000 \text{ N}.$$

At maximum speed:

$$\frac{80\,000}{v} = 40v + 2000 \implies 40v^2 + 2000v - 80\,000 = 0 \implies v^2 + 50v - 2000 = 0.$$

By the quadratic formula:

$$v = \frac{-50 + \sqrt{2500 + 8000}}{2} = \frac{-50 + \sqrt{10\,500}}{2} \approx \frac{-50 + 102.5}{2} \approx 26.2 \text{ m s}^{-1}.$$

(The negative root is rejected since $v > 0$.)

3. At $v = 10 \text{ m s}^{-1}$ uphill, the driving force is $P/v = 80\,000/10 = 8000 \text{ N}$ and the resistance is $R = 40 \times 10 = 400 \text{ N}$. Newton's second law:

$$8000 - 400 - 2000 = 4000a \implies a = \frac{5600}{4000} = 1.4 \text{ m s}^{-2}.$$

WARNING Exam tip — units first

Before substituting anything, convert: power to watts (multiply kW by 1000), speeds to m s^{-1} (divide km/h by 3.6), masses to kg. Mixing kW with N and m/s is the fastest way to lose marks in this topic.

KEY POINTS Key points

- Power is the rate of doing work: $P_{\text{av}} = W/t$ (average), $P = dW/dt$ (instantaneous); unit the watt, $1 \text{ kW} = 1000 \text{ W}$.
- For a force F moving its point of application at velocity v in the same direction: $P = Fv$.
- A vehicle at constant power has driving force $F = P/v$, which decreases as speed increases.
- Equation of motion: $\frac{P}{v} - R = ma$ (level road); add $mg \sin \alpha$ to the opposing forces uphill, subtract it downhill.
- Maximum speed occurs when $a = 0$: on level ground $v_{\text{max}} = P/R$; uphill $\frac{P}{v_{\text{max}}} = R + mg \sin \alpha$; downhill $\frac{P}{v_{\text{max}}} = R - mg \sin \alpha$.

EXERCISE 7 Maximum speed with speed-dependent resistance

A car of mass 1200 kg works at a constant rate of 48 kW . The total resistance to motion is $R = 30v$ newtons on a level road, where v is in m s^{-1} . Take $g = 10 \text{ m s}^{-2}$.

1. Find the maximum speed of the car on the level road.
2. Find the acceleration when the car is travelling at 20 m/s on the level road.
3. The car now descends a hill with $\sin \alpha = \frac{1}{40}$, with the engine still working at 48 kW . Show that the maximum speed downhill v satisfies $v^2 - 10v - 1600 = 0$, and find it.

SOLUTION Exercise 1

$P = 48\,000\text{ W}$. 1. At maximum speed on the level road, $\frac{48\,000}{v} = 30v \Rightarrow v^2 = 1600 \Rightarrow v_{\max} = 40\text{ m s}^{-1}$. 2. At $v = 20\text{ m s}^{-1}$: driving force $F = 48\,000/20 = 2400\text{ N}$, resistance $R = 30 \times 20 = 600\text{ N}$, so

$$a = \frac{2400 - 600}{1200} = 1.5\text{ m s}^{-2}.$$

3. Downhill, $mg \sin \alpha = 1200 \times 10 \times \frac{1}{40} = 300\text{ N}$ assists the motion. At maximum speed, driving force plus weight component balance resistance:

$$\frac{48\,000}{v} + 300 = 30v \Rightarrow 48\,000 + 300v = 30v^2 \Rightarrow v^2 - 10v - 1600 = 0,$$

as required. Solving:

$$v = \frac{10 + \sqrt{100 + 6400}}{2} = \frac{10 + \sqrt{6500}}{2} \approx \frac{10 + 80.6}{2} \approx 45.3\text{ m s}^{-1}.$$

(The negative root is rejected.) Note that the maximum speed downhill exceeds that on the level road, as expected.

DID YOU KNOW? Why lorries slow down on hills

The relation $F = P/v$ explains a familiar sight on the road from Yaoundé to Bafoussam: heavy lorries crawling uphill at a fraction of their speed on the flat. The engine's power is fixed, so to produce the large driving force needed against gravity and resistance, the speed $v = P/F$ must be small — which is exactly why drivers change down to a lower gear before a steep climb: lower gears let the wheels turn slowly while the engine keeps delivering its full power.

6 PUMPING WATER, WATER JETS AND APPLICATIONS OF WORK, ENERGY AND POWER

In the previous section we discovered that power is the rate of doing work, and that a force F moving its point of application at velocity v delivers the instantaneous power $P = Fv$. We now apply these ideas to one of the most frequent families of GCE Advanced Level problems: **pumps** raising water, **water jets** and fire hoses, and engines working against gravity and resistance. These problems look different from block-and-slope questions, but they are governed by exactly the same principle: power is the energy given to the system each second.

6.1 Modelling a Pump Raising Water

From a static load to a continuous flow.

Until now, the objects we lifted were rigid bodies of fixed mass m : raising them through a height h required the work $W = mgh$, done once and for all. A pump is different: it does not lift one mass, it lifts a continuous stream of water. Every second, a certain mass of water arrives at the pump and is delivered, higher up or faster, at the outlet. The natural quantity is therefore not the mass but the **mass flow rate**.


DEFINITION Mass flow rate

The **mass flow rate** $\dot{m}$ of a fluid in motion is the mass of fluid passing a given cross-section per unit time:

$$\dot{m} = \frac{\Delta m}{\Delta t}, \quad \text{unit: kg s}^{-1}.$$

For a jet or pipe of cross-sectional area A in which water of density ρ moves at speed v , the volume crossing a section in one second is Av (a cylinder of length v), so

$$\dot{m} = \rho Av.$$



A pump raises water from a ground reservoir to an overhead tank at height h ; the water leaves the pipe of cross-section A at speed v .

Energy given to each kilogram of water.

Consider what the pump must do for each kilogram of water passing through it:

- raise it through the height h : this costs gh joules of gravitational potential energy per kilogram;
- if the water leaves the pipe at speed v (having started essentially at rest in the reservoir), give it kinetic energy $\frac{1}{2}v^2$ joules per kilogram.

Hence the energy supplied per kilogram is $gh + \frac{1}{2}v^2$. Since $\dot{m}$ kilograms pass each second, the energy supplied per second — that is, the power — follows immediately.

PROPERTY Power of a pump and of a water jet

A pump handling a mass flow rate $\dot{m}$ (in kg s^{-1}) delivers a useful power

$$P = \dot{m}gh + \frac{1}{2}\dot{m}v^2$$

where h is the height through which the water is raised and v the speed at which it leaves. In particular:

- water merely lifted through h (delivered at negligible speed): $P = \dot{m}gh$;
- a water jet of cross-section A , density ρ , speed v (no lifting): with $\dot{m} = \rho Av$,

$$P = \frac{1}{2}\dot{m}v^2 = \frac{1}{2}\rho Av^3.$$

(Proof examinable as a derivation: it is a direct application of the work–energy theorem per unit time.)

METHOD Solving a pumping or jet problem

1. Find the mass flow rate. For a jet or pipe, $\dot{m} = \rho Av$; for a tank filled in time t , $\dot{m} = \rho V/t$. Remember $\rho_{\text{water}} = 1000 \text{ kg m}^{-3}$ and convert areas to m^2 .
2. Energy per kilogram. Add gh (lifting) and $\frac{1}{2}v^2$ (speed given), each only if present.
3. Multiply. Useful power $P = \dot{m}(gh + \frac{1}{2}v^2)$.
4. Account for efficiency if given: $P_{\text{input}} = P_{\text{useful}}/\eta$.

WARNING Do not forget the kinetic energy term

When water leaves a pipe or hose at speed, the pump (or the fire engine) supplies both potential and kinetic energy. Using only $\dot{m}gh$ underestimates the power. Conversely, if the water is simply poured gently into the tank, the term $\frac{1}{2}\dot{m}v^2$ must not be invented. Read the statement carefully: “the water issues from the pipe at 6 m s^{-1} ” means the kinetic term is required.

WORKED EXAMPLE 12 Pump filling an overhead tank

A pump raises water from a ground-level reservoir to an overhead tank whose inlet is 12 m above the reservoir surface. The water flows through a pipe of cross-sectional area $8.0 \times$

10^{-3} m^2 and leaves the pipe at 5.0 m s^{-1} . Take $\rho = 1000 \text{ kg m}^{-3}$ and $g = 9.81 \text{ m s}^{-2}$. Find the useful power of the pump.

SOLUTION

Step 1: mass flow rate.

$$\dot{m} = \rho Av = 1000 \times 8.0 \times 10^{-3} \times 5.0 = 40 \text{ kg s}^{-1}.$$

Step 2: energy per kilogram. Lifting: $gh = 9.81 \times 12 = 117.72 \text{ J kg}^{-1}$. Kinetic: $\frac{1}{2}v^2 = \frac{1}{2}(5.0)^2 = 12.5 \text{ J kg}^{-1}$. Step 3: power.

$$P = \dot{m} \left(gh + \frac{1}{2}v^2 \right) = 40 (117.72 + 12.5) = 40 \times 130.22 \approx 5.21 \times 10^3 \text{ W}.$$

The pump delivers a useful power of about **5.2 kW**, of which $40 \times 12.5 = 500 \text{ W}$ (about 10%) goes into the kinetic energy of the jet.

WORKED EXAMPLE 13 Power of a fire-hose jet

Water issues horizontally from a hose nozzle of diameter 7.0 cm at a speed of 25 m s^{-1} . Find the kinetic power of the jet. ($\rho = 1000 \text{ kg m}^{-3}$.)

SOLUTION

The cross-sectional area is

$$A = \pi r^2 = \pi (0.035)^2 = 3.848 \times 10^{-3} \text{ m}^2.$$

Hence $\dot{m} = \rho Av = 1000 \times 3.848 \times 10^{-3} \times 25 = 96.2 \text{ kg s}^{-1}$, and

$$P = \frac{1}{2} \dot{m} v^2 = \frac{1}{2} \rho A v^3 = \frac{1}{2} \times 1000 \times 3.848 \times 10^{-3} \times 25^3 \approx 3.0 \times 10^4 \text{ W}.$$

The jet carries about **30 kW** of kinetic power. Note the v^3 dependence: doubling the speed multiplies the power by 8.

6.2 Efficiency of Pumps and Engines

No real machine converts all the energy it consumes into useful work: friction in bearings, turbulence in pipes and heat losses all take their share. This is quantified by the **efficiency**.

DEFINITION Efficiency

The **efficiency** η of a machine is

$$\eta = \frac{\text{useful power output}}{\text{power input}} = \frac{\text{useful energy output}}{\text{energy input}},$$

usually expressed as a percentage. Consequently $P_{\text{useful}} = \eta P_{\text{input}}$, i.e. the input power required is $P_{\text{input}} = P_{\text{useful}} / \eta$.

EXAMPLE Motor driving a pump

The pump of the first worked example is driven by an electric motor of efficiency 80%. The electrical power consumed is

$$P_{\text{in}} = \frac{5.21 \text{ kW}}{0.80} \approx 6.5 \text{ kW}.$$

The missing 1.3 kW is dissipated as heat and sound in the motor and pump.

6.3 Choosing Between Energy and Power Methods

By now you have two toolboxes that overlap: the work–energy theorem (and conservation of energy) on one side, power ($P = Fv$, $P = \dot{W}$) on the other. Choosing the right one saves precious exam minutes.

METHOD Which method for which problem?

- Speeds and displacements, no time involved (“find the speed at the bottom”, “how far does it slide”): use the work–energy theorem or conservation of energy.
- Rates, times, continuous flow (“how long to fill the tank”, “power developed”, “mass per second”): use power.
- Constant speed against resistance (vehicle at steady speed): the driving force balances resistance, and $P = Fv$ links them directly.
- Acceleration at a given instant (vehicle speeding up): write $P = Fv$ for the tractive force, then Newton’s second law $F - R = ma$.

WARNING GCE exam tip

In structured questions, later parts almost always reuse earlier results. Keep exact values (fractions, surds, unrounded decimals) throughout your working and round only the

final answer to the accuracy requested. A premature rounding in part (a) can cost all the accuracy marks of parts (b) and (c).

6.4 GCE–Style Structured Problems

WORKED EXAMPLE 14 Vehicle on a hill with resistance

A car of mass 1200 kg climbs a hill inclined at an angle α to the horizontal, where $\sin \alpha = \frac{1}{14}$. A constant resistance to motion of 600 N acts on the car. Take $g = 9.8 \text{ m s}^{-2}$.

- (a) The car climbs at a steady speed of 20 m s^{-1} . Find the power developed by the engine.
- (b) With the engine now developing 45 kW, find the acceleration of the car at the instant its speed is 20 m s^{-1} up the hill.

SOLUTION

(a) At steady speed the tractive force F balances the total opposing force:

$$F = R + mg \sin \alpha = 600 + 1200 \times 9.8 \times \frac{1}{14} = 600 + 840 = 1440 \text{ N.}$$

Then

$$P = Fv = 1440 \times 20 = 28\,800 \text{ W} = 28.8 \text{ kW.}$$

(b) With $P = 45\,000 \text{ W}$ at $v = 20 \text{ m s}^{-1}$, the new tractive force is

$$F' = \frac{P}{v} = \frac{45\,000}{20} = 2250 \text{ N.}$$

Newton's second law up the slope:

$$F' - R - mg \sin \alpha = ma \implies 2250 - 1440 = 1200 a,$$

$$\text{so } a = \frac{810}{1200} = 0.675 \text{ m s}^{-2}.$$

WORKED EXAMPLE 15 Pump, tank and time

A small water pump of useful power 1.5 kW fills an empty tank of capacity 2.4 m^3 situated 8.0 m above the water source. The water enters the tank at negligible speed. Taking $\rho = 1000 \text{ kg m}^{-3}$ and $g = 9.81 \text{ m s}^{-2}$, find the time needed to fill the tank.

SOLUTION

The total potential energy to supply is

$$E = mgh = \rho Vgh = 1000 \times 2.4 \times 9.81 \times 8.0 = 188\,352 \text{ J.}$$

Since $P = \frac{E}{t}$,

$$t = \frac{E}{P} = \frac{188\,352}{1500} \approx 125.6 \text{ s} \approx 2 \text{ min } 6 \text{ s.}$$

WORKED EXAMPLE 16 Springs and energy combined

A light spring of natural length 0.50 m and modulus of elasticity 60 N hangs vertically. A mass of 0.80 kg is attached to its lower end and released from rest with the spring just unstretched. Take $g = 9.8 \text{ m s}^{-2}$ and $\lambda = 60 \text{ N}$, natural length $l = 0.50 \text{ m}$.

- (a) Using energy, find the extension of the spring when the mass first comes momentarily to rest.
- (b) Find the speed of the mass when it has fallen 0.20 m.

SOLUTION

(a) Let x be the maximum extension. The gravitational potential energy lost equals the elastic energy stored (kinetic energy is zero at both ends):

$$mgx = \frac{\lambda x^2}{2l} \implies x = \frac{2mgl}{\lambda} = \frac{2 \times 0.80 \times 9.8 \times 0.50}{60} = 0.1307 \text{ m} \approx 0.13 \text{ m.}$$

(b) The maximum extension is 0.13 m, so the mass never reaches a fall of 0.20 m; the question likely contains a misprint. We illustrate the method for a fall of $y = 0.10 \text{ m}$:

$$mgy = \frac{1}{2}mv^2 + \frac{\lambda y^2}{2l} \implies 0.80 \times 9.8 \times 0.10 = \frac{1}{2}(0.80)v^2 + \frac{60(0.10)^2}{2 \times 0.50},$$

$$0.784 = 0.40v^2 + 0.60 \implies v^2 = 0.46, \quad v \approx 0.68 \text{ m s}^{-1}.$$

This illustrates the exam tip: energy methods handle springs and gravity in one line, and checking consistency of data is part of the exercise.

EXERCISE 8 Fire pump in Yaounde


A pump draws water from a well 6.0 m below ground and delivers it through a nozzle of cross-section $2.0 \times 10^{-3} \text{ m}^2$ at 12 m s^{-1} . The pump-motor unit has efficiency 70%. Find (a) the mass flow rate, (b) the useful power, (c) the electrical power consumed. ($\rho = 1000 \text{ kg m}^{-3}$, $g = 9.81 \text{ m s}^{-2}$.)

SOLUTION Exercise 1

(a) $\dot{m} = \rho Av = 1000 \times 2.0 \times 10^{-3} \times 12 = 24 \text{ kg s}^{-1}$. (b) $P_{\text{useful}} = \dot{m}gh + \frac{1}{2}\dot{m}v^2 = 24(9.81 \times 6.0) + \frac{1}{2}(24)(144) = 1412.6 + 1728 = 3140.6 \text{ W} \approx 3.1 \text{ kW}$. (c) $P_{\text{in}} = \frac{3140.6}{0.70} \approx 4.5 \text{ kW}$.

6.5 Revision Grid of the Chapter

Quantity / Law	Formula	Conditions of validity
Work of a constant force	$W = Fs \cos \theta$	Force constant; θ angle between $\vec{F}$ and displacement
Work against gravity	$W = mgh$	Near Earth's surface, g constant; h vertical rise
Work of a variable force	$W = \int_{x_1}^{x_2} F(x) dx$	Force depends on position; area under F - x graph
Elastic potential energy	$E_e = \frac{\lambda x^2}{2l}$	Spring of modulus λ , natural length l , extension x
Kinetic energy	$E_k = \frac{1}{2}mv^2$	Translation of a particle of mass m
Gravitational potential energy	$E_p = mgh$	Measured from a chosen reference level
Work-energy theorem	$W_{\text{all forces}} = \Delta E_k$	Always valid (resultant work)
Conservation of energy	$E_k + E_p = \text{const}$	Only conservative forces do work
Power	$P = \frac{dW}{dt} = Fv$	$P = Fv$ for force F at speed v in its direction
Pump / jet power	$P = \dot{m}gh + \frac{1}{2}\dot{m}v^2, \dot{m} = \rho Av$	Steady flow; include each term only when present
Efficiency	$\eta = \frac{P_{\text{useful}}}{P_{\text{input}}}$	Usually quoted as a percentage



The logical chain of the chapter: work leads, through the work–energy theorem, to energy, power and their applications.

KEY POINTS Key points of the section

- For continuous flow, work with the **mass flow rate** $\dot{m} = \rho Av$ and the energy given to each kilogram.
- Pump power: $P = \dot{m}gh + \frac{1}{2}\dot{m}v^2$; a pure jet has $P = \frac{1}{2}\rho Av^3$ — note the v^3 .
- Efficiency links input and output: $P_{\text{input}} = P_{\text{useful}}/\eta$.
- Energy methods for speeds and displacements; power methods for rates and times; $P = Fv$ with Newton's second law for vehicles.
- Keep exact values until the final line of a structured question.

DID YOU KNOW? Water power in Cameroon

Cameroon's great hydroelectric dams — Song Loulou and Edea on the Sanaga river — are giant, perfected versions of the pump problems of this section, run in reverse: instead of spending power to raise water, they collect the power $\dot{m}gh$ released by water falling through the height of the dam. The same formula you have just used for a domestic pump governs the electricity supply of entire cities — a beautiful illustration that the physics of the GCE classroom is the physics of the nation.

7 INTEGRATION ACTIVITY

7.1 Aims of the activity

By the end of this group activity, each student should be able to:

- compute a **mass flow rate** from a volume delivered per unit time;
- calculate the **work done against gravity** when a mass is raised through a given height;
- calculate the **kinetic energy** communicated to a moving fluid;
- apply the **work–energy theorem** and the **conservation of energy** to obtain a total energy balance;
- deduce a **minimum power**, then correct it for the **efficiency** of a real machine;
- make and justify an engineering choice from a catalogue, and verify a design by an independent calculation;
- present and defend a scientific argument in front of the class.

7.2 Situation

The Mfoundi neighbourhood, in the heart of Yaoundé, is supplied with water from a community well. The water level in the well is 12 m below the point where the delivery pipe discharges into an overhead tank. The neighbourhood committee wants to install an electric pump that satisfies the following requirements:

- the pump must deliver 600 litres of water per hour;
- the water must leave the delivery pipe with a speed of 2 m s^{-1} ;
- the overall efficiency of the pump and its motor is 70%;
- the overhead storage tank has a capacity of 2000 litres.

Take $g = 9.81 \text{ m s}^{-2}$ and the density of water $\rho = 1000 \text{ kg m}^{-3}$. Recall that $1 \text{ litre} = 10^{-3} \text{ m}^3$, so that 1 litre of water has a mass of 1 kg.

The local dealer proposes the following catalogue of motors:

Model	Rated power (W)	Price (FCFA)
M1	120	45 000
M2	150	58 000
M3	200	72 000
M4	250	85 000

Working in groups, you are the engineering team of the committee. You must determine the energy the pump must supply every second, choose the cheapest motor that can do the job,

and verify your design. Each group will present its complete **energy balance** on a poster, and the class will compare the designs.

7.3 Tasks

1. **Mass flow rate.** Convert the delivery of 600 litres per hour into a mass of water pumped per second. Denote this mass flow rate by q (in kg s^{-1}).
2. **Work against gravity.** Each kilogram of water must be raised through 12 m. Write down the work done against gravity to raise a mass m through a height h , and deduce the work done against gravity per second (i.e. the potential energy gained by the water each second).
3. **Kinetic energy.** The water arrives at the top with speed $v = 2 \text{ m s}^{-1}$. Write down the kinetic energy of a mass m moving at speed v , and deduce the kinetic energy given to the water per second.
4. **Minimum pump power.** Using the work–energy theorem, explain why the minimum useful power of the pump is the sum of the two quantities found in questions 2 and 3. Compute this minimum power $P_{\min}$.
5. **Choice of motor.** The pump–motor set has an efficiency of 70%. Explain why the electrical power required is $P_{\text{elec}} = \frac{P_{\min}}{0.7}$. Compute P_{elec} and choose, from the catalogue, the cheapest motor whose rated power is sufficient. Justify your choice.
6. **Verification.** Compute the time needed to fill the 2000–litre tank at the delivery rate of 600 litres per hour. Give your answer in hours and minutes.
7. **Poster.** Present your full energy balance (mass flow rate, potential energy per second, kinetic energy per second, minimum power, electrical power, chosen motor, filling time) on a poster, with one sentence justifying each step.

7.4 Model answer

1. **Mass flow rate.** Since 1 litre of water has a mass of 1 kg, a delivery of 600 litres per hour corresponds to 600 kg per hour. Hence

$$q = \frac{600}{3600} = \frac{1}{6} \approx 0.1667 \text{ kg s}^{-1}.$$

2. **Work done against gravity per second.** The work needed to raise a mass m through a height h is $W = mgh$. In one second the mass raised is $q = \frac{1}{6} \text{ kg}$, so the potential energy gained per second is

$$\dot{E}_p = q g h = \frac{1}{6} \times 9.81 \times 12 = 19.62 \text{ W}.$$

3. **Kinetic energy per second.** The kinetic energy of a mass m at speed v is $E_k = \frac{1}{2}mv^2$. In one second a mass q is given the speed $v = 2 \text{ m s}^{-1}$, so the kinetic energy supplied per second is

$$\dot{E}_k = \frac{1}{2} q v^2 = \frac{1}{2} \times \frac{1}{6} \times 2^2 = \frac{1}{3} \approx 0.333 \text{ W}.$$

4. Minimum pump power. By the work–energy theorem, the total work done by the pump on each kilogram of water equals the change in its mechanical energy, namely the gain in gravitational potential energy plus the gain in kinetic energy. Therefore the minimum useful power is

$$P_{\min} = \dot{E}_p + \dot{E}_k = 19.62 + 0.333 \approx 19.95 \text{ W}.$$

5. Choice of motor. Only 70% of the electrical power consumed is converted into useful mechanical work on the water, so

$$P_{\text{elec}} = \frac{P_{\min}}{0.7} = \frac{19.95}{0.7} \approx 28.5 \text{ W}.$$

Every motor in the catalogue has a rated power greater than 28.5 W; the cheapest adequate model is therefore **M1** (120 W, 45 000 FCFA). Its rated power is comfortably above the requirement, which also gives a safety margin for friction in the pipes.

6. Verification. At 600 litres per hour, the time to fill the 2000-litre tank is

$$t = \frac{2000}{600} = \frac{10}{3} \text{ h} \approx 3 \text{ h } 20 \text{ min}.$$

7. Conclusion. The design is consistent: a 120 W motor (model M1) pumps 600 litres per hour to a height of 12 m with an exit speed of 2 m s^{-1} , and fills the 2000-litre tank in about 3 h 20 min.

WARNING Common errors to avoid

- Forgetting to convert hours into seconds: the mass flow rate must be in kg s^{-1} , not kg h^{-1} .
- Omitting the kinetic energy term: the water does not only rise, it also leaves the pipe moving.
- Dividing by the efficiency instead of multiplying: since the machine wastes energy, the electrical power must be larger than the useful power, so we divide $P_{\min}$ by 0.7.

8 METHODS AND WORKED EXAMPLES

9 WORK, ENERGY AND POWER

9.1 Work Done by a Constant Force and Work Done Against Gravity

DEFINITION Work of a constant force

Let a constant force $\vec{F}$ act on a particle. If the point of application of the force undergoes a displacement $\vec{d}$ (from point A to point B), the work done by the force is the scalar quantity

$$W = \vec{F} \cdot \vec{d} = F d \cos \theta,$$

where $F = \|\vec{F}\|$, $d = \|\vec{d}\| = AB$ and θ is the angle between the directions of $\vec{F}$ and $\vec{d}$ ($0 \leq \theta \leq \pi$). The SI unit of work is the joule (J): $1 \text{ J} = 1 \text{ N m}$.

PROPERTY Sign of the work

- $W > 0$ (driving work) if $0 \leq \theta < 90^\circ$: the force has a component in the direction of motion.
- $W = 0$ if $\theta = 90^\circ$: the force is perpendicular to the displacement.
- $W < 0$ (resisting work) if $90^\circ < \theta \leq 180^\circ$: the force has a component opposite to the motion.


Work is a scalar; the total work of several forces is the algebraic sum of their individual works.

METHOD Computing the work of a constant force

1. Draw a clear diagram showing the force $\vec{F}$, the displacement $\vec{d}$ (or the path), and mark the angle θ between them.
2. Identify the magnitude F of the force and the distance d travelled.
3. Apply $W = Fd \cos \theta$.
4. Decide the sign from the value of $\cos \theta$ (or from the physical sense: driving or resist-)

ing).

5. For the weight $\vec{W} = m\vec{g}$: if the body rises vertically by h , the work done by the weight is $W_{\text{weight}} = -mgh$; the work done against gravity is $W_{\text{against}} = +mgh$. This depends only on the vertical height change, not on the path.
6. State the answer in joules with its sign and a brief physical interpretation.



Work of a constant force: only the component $F \cos \theta$ along the displacement contributes.

EXAMPLE Work on an inclined plane

A block of mass 5 kg is pulled a distance of 8 m up a rough plane inclined at 30° to the horizontal. The pulling force of 50 N acts parallel to the plane, up the slope. The coefficient of friction is 0.2. Take $g = 10 \text{ m s}^{-2}$. Find the work done by (a) the pulling force, (b) the weight, (c) the friction, (d) the normal reaction, (e) the total work.

Diagram and data: $d = 8 \text{ m}$, $\alpha = 30^\circ$, $F = 50 \text{ N}$ (up the plane), $mg = 50 \text{ N}$, $R = \mu N = \mu mg \cos \alpha = 0.2 \times 50 \times \cos 30^\circ = 10 \times \frac{\sqrt{3}}{2} = 5\sqrt{3} \text{ N}$.

(a) Pulling force: $\theta = 0^\circ$, $W_F = 50 \times 8 \times \cos 0^\circ = 400 \text{ J}$.

(b) Weight: The weight mg acts vertically downwards. The angle between $m\vec{g}$ and the displacement (up the plane) is $90^\circ + \alpha = 120^\circ$.

$$W_{mg} = mg d \cos(90^\circ + \alpha) = 50 \times 8 \times \cos 120^\circ = 400 \times \left(-\frac{1}{2}\right) = -200 \text{ J}.$$

Check: vertical rise $h = d \sin \alpha = 8 \times \frac{1}{2} = 4 \text{ m}$, so work against gravity $= mgh = 5 \times 10 \times 4 = 200 \text{ J}$; work by gravity $= -200 \text{ J}$. Consistent.

(c) Friction: Acts down the plane, opposite to displacement: $\theta = 180^\circ$.

$$W_f = R d \cos 180^\circ = 5\sqrt{3} \times 8 \times (-1) = -40\sqrt{3} \approx -69.3 \text{ J}.$$

(d) Normal reaction: Perpendicular to displacement: $\theta = 90^\circ$, $W_N = 0$.

(e) Total work:

$$W_{\text{total}} = 400 - 200 - 40\sqrt{3} + 0 = 200 - 40\sqrt{3} \approx 130.7 \text{ J}.$$

The positive total work means the block gains kinetic energy.

WARNING Choosing the angle θ

The most frequent error is confusing the angle of the slope with the angle between the force and the displacement. Always draw the two vectors tail-to-tail and measure the angle between them. For the weight on an incline, $\theta = 90^\circ + \alpha$ (if moving up) or $\theta = 90^\circ - \alpha$ (if moving down). Remember: work against gravity depends only on the vertical height gained, never on the length or shape of the path.

9.2 Work Done by Variable Forces**DEFINITION** Work of a variable force along a straight line

If a force $F(x)$ varies with position x and acts along the x -axis (or along a straight line taken as the x -axis), the work done in moving from $x = a$ to $x = b$ is

$$W = \int_a^b F(x) dx.$$

Geometrically, W is the signed area between the graph of $F(x)$ and the x -axis from a to b .


METHOD Work of a variable force by integration

1. Choose an origin and a positive direction along the line of motion. Express the force as a function $F(x)$ of the position x .
2. Write the elementary work $\delta W = F(x) \delta x$ for a small displacement δx .
3. Integrate between the initial and final positions: $W = \int_{x_1}^{x_2} F(x) dx$.
4. For an elastic string or spring obeying Hooke's law: tension $T = \frac{\lambda}{l}x$, where λ is the modulus of elasticity, l the natural length, and x the extension. The work done in stretching from extension x_1 to x_2 is

$$W = \int_{x_1}^{x_2} \frac{\lambda}{l} x dx = \frac{\lambda}{2l} (x_2^2 - x_1^2).$$

This work is stored as elastic potential energy $E_{el} = \frac{\lambda x^2}{2l}$.

5. Check the sign: if the force acts in the direction of increasing x , the work is positive; if opposite, negative.



Work of a variable force $F(x)$ from x_1 to x_2 equals the area under the curve.

WORKED EXAMPLE 17 Stretching an elastic string

An elastic string of natural length 0.8 m and modulus of elasticity 60 N is fixed at one end. Find the work done in stretching it slowly from a length of 1.0 m to a length of 1.4 m.

SOLUTION

Step 1 — Hooke's law. Natural length $l = 0.8$ m, modulus $\lambda = 60$ N. Tension at extension x :

$$F(x) = T(x) = \frac{\lambda}{l}x = \frac{60}{0.8}x = 75x \text{ N.}$$

Step 2 — Limits of integration. Length 1.0 m $\Rightarrow$ extension $x_1 = 1.0 - 0.8 = 0.2$ m. Length 1.4 m $\Rightarrow$ extension $x_2 = 1.4 - 0.8 = 0.6$ m.

Step 3 — Integrate.

$$W = \int_{0.2}^{0.6} 75x \, dx = 75 \left[\frac{x^2}{2} \right]_{0.2}^{0.6} = \frac{75}{2} (0.36 - 0.04) = 37.5 \times 0.32 = 12 \text{ J.}$$

Step 4 — Check via elastic potential energy.

$$E_{\text{el}} = \frac{\lambda x^2}{2l} \Rightarrow \Delta E_{\text{el}} = \frac{60}{2(0.8)} (0.6^2 - 0.2^2) = 37.5 \times 0.32 = 12 \text{ J.}$$

The work done equals the gain in elastic potential energy, as expected for a slow (quasi-static) stretch with no kinetic energy change.

WORKED EXAMPLE 18 Work from a force–displacement graph

A force $F(x)$ acts on a body moving along the x -axis. The graph of F against x consists of: a straight line from $(0, 0)$ to $(2, 10)$, a horizontal segment from $(2, 10)$ to $(4, 10)$, and a straight line from $(4, 10)$ to $(6, 0)$. Find the total work done from $x = 0$ to $x = 6$.

SOLUTION

The work is the area under the graph. We compute it as the sum of three areas:

- Triangle $0 \leq x \leq 2$: $\frac{1}{2} \times 2 \times 10 = 10 \text{ J}$.
 - Rectangle $2 \leq x \leq 4$: $2 \times 10 = 20 \text{ J}$.
 - Triangle $4 \leq x \leq 6$: $\frac{1}{2} \times 2 \times 10 = 10 \text{ J}$.
- Total work $W = 10 + 20 + 10 = 40 \text{ J}$.

9.3 Energy: Kinetic and Potential

DEFINITION Kinetic energy

The kinetic energy of a body of mass m moving with speed v is

$$E_k = \frac{1}{2}mv^2.$$

It is a scalar, always non-negative, measured in joules (J). It depends only on the speed, not on the direction of motion.

DEFINITION Gravitational potential energy

Near the Earth's surface, the gravitational potential energy of a body of mass m at a height h above a chosen reference level is

$$E_p = mgh.$$

Only changes in potential energy are physically meaningful; the reference level (where $E_p = 0$) can be chosen arbitrarily for convenience.

DEFINITION Elastic potential energy

For an elastic string or spring of natural length l and modulus λ , stretched (or compressed) by an amount x , the elastic potential energy stored is

$$E_{\text{el}} = \frac{\lambda x^2}{2l}.$$

PROPERTY Conservative forces

A force is conservative if the work it does depends only on the initial and final positions, not on the path taken. Gravity and elastic forces are conservative. For a conservative

force, one can define a potential energy E_p such that the work done by the force equals the negative change in potential energy: $W = -\Delta E_p$. Friction and air resistance are non-conservative (dissipative) forces.

KEY POINTS Key energy formulas

Quantity	Formula
Kinetic energy	$E_k = \frac{1}{2}mv^2$
Gravitational potential energy	$E_p = mgh$ (relative to a reference level)
Elastic potential energy	$E_{el} = \frac{\lambda x^2}{2l}$
Work by gravity (vertical rise h)	$W_{\text{grav}} = -mgh$
Work against gravity	$W_{\text{against}} = +mgh$
Work by elastic force (extension $x_1 \rightarrow x_2$)	$W = -\frac{\lambda}{2l}(x_2^2 - x_1^2)$

9.4 The Work–Energy Theorem and Conservation of Energy

PROPERTY Work–Energy Theorem

The total work done by all forces acting on a particle (or a rigid body in translation) equals the change in its kinetic energy:

$$W_{\text{total}} = \Delta E_k = \frac{1}{2}mv^2 - \frac{1}{2}mu^2.$$

This theorem holds whether the forces are conservative or not. It is a scalar equation, often simpler than using Newton's second law when only speeds and distances are involved.

METHOD Applying the work–energy theorem

1. Identify the body, its mass m , initial speed u and final speed v .
2. Compute $\Delta E_k = \frac{1}{2}m(v^2 - u^2)$.
3. List all forces that do work on the body (weight, tension, friction, driving force, normal reaction does no work if perpendicular to motion, etc.).

4. Compute the work done by each force over the displacement. For constant forces: $W = Fd \cos \theta$. For variable forces: integrate.
5. Sum the works algebraically to get W_{total} .
6. Set $W_{\text{total}} = \Delta E_k$ and solve for the unknown.

WORKED EXAMPLE 19 Lorry braking downhill

A lorry of mass 3000 kg travels at 20 m s^{-1} down a hill inclined at $\sin^{-1}(0.1)$ to the horizontal. The brakes apply a constant resisting force of 9000 N. Using the work–energy theorem, find the distance travelled before the speed falls to 8 m s^{-1} . Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

Step 1 — Change in kinetic energy.

$$\Delta E_k = \frac{1}{2}(3000)(8^2 - 20^2) = 1500(64 - 400) = -504\,000 \text{ J.}$$

Step 2 — Works over distance d . Component of weight down the slope: $mg \sin \alpha = 3000 \times 10 \times 0.1 = 3000 \text{ N}$ (driving).

$$W_{\text{weight}} = +3000 d.$$

Braking force opposes motion:

$$W_{\text{brake}} = -9000 d.$$

Normal reaction does no work.

Step 3 — Apply the theorem.

$$\begin{aligned} W_{\text{total}} &= \Delta E_k \\ 3000d - 9000d &= -504\,000 \\ -6000d &= -504\,000 \\ d &= 84 \text{ m.} \end{aligned}$$

The lorry travels 84 m before its speed drops to 8 m s^{-1} . Note that gravity supplies energy (positive work), so the brakes must dissipate both the initial kinetic energy and the work done by gravity.

PROPERTY Conservation of mechanical energy

If only conservative forces (gravity, elastic forces) do work on a system, the total me-

mechanical energy $E = E_k + E_p$ (including elastic potential energy if present) remains constant:

$$E_{\text{initial}} = E_{\text{final}} \iff \frac{1}{2}mu^2 + mgh_1 + \frac{\lambda x_1^2}{2l} = \frac{1}{2}mv^2 + mgh_2 + \frac{\lambda x_2^2}{2l}.$$

If non-conservative forces (friction, resistance, driving force) do work, mechanical energy is not conserved; use the work-energy theorem instead, or write

$$E_{\text{final}} = E_{\text{initial}} + W_{\text{non-conservative}}.$$

METHOD Applying conservation of mechanical energy

1. Verify that no non-conservative forces do work (smooth surfaces, no engine, no resistance). If they do, use the work-energy theorem.
2. Choose a reference level for gravitational potential energy (usually the lowest point).
3. Write the total mechanical energy at the initial state: $E_i = \frac{1}{2}mu^2 + mgh_i (+E_{\text{el},i})$.
4. Write it at the final state: $E_f = \frac{1}{2}mv^2 + mgh_f (+E_{\text{el},f})$.
5. Set $E_i = E_f$ and solve. The mass m often cancels.
6. If a constant resistance R acts over a distance s , the energy lost is Rs : $E_i - E_f = Rs$.

WORKED EXAMPLE 20 Bead on a smooth vertical wire

A small bead of mass 0.5 kg slides from rest at the top A of a smooth curved wire. Point A is 5 m vertically above the lowest point B , and point C is 2 m above B . Find the speed of the bead (a) at B , (b) at C . Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

The wire is smooth $\Rightarrow$ reaction does no work $\Rightarrow$ mechanical energy conserved. Choose B as reference level ($h = 0$).

(a) Speed at B . At A : $v_A = 0$, $h_A = 5 \text{ m}$. $E_A = 0 + mg(5) = 5mg$. At B : $h_B = 0$, $E_B = \frac{1}{2}mv_B^2$.

$$\frac{1}{2}mv_B^2 = 5mg \implies v_B^2 = 10g = 100 \implies v_B = 10 \text{ m s}^{-1}.$$

(b) Speed at C . $h_C = 2 \text{ m}$, $E_C = \frac{1}{2}mv_C^2 + mg(2)$.

$$\frac{1}{2}mv_C^2 + 2mg = 5mg \implies \frac{1}{2}v_C^2 = 3g = 30 \implies v_C = \sqrt{60} = 2\sqrt{15} \approx 7.75 \text{ m s}^{-1}.$$

Remark. The mass cancels: any bead would have the same speeds. The shape of the wire is irrelevant — only the vertical heights matter because gravity is conservative.

WORKED EXAMPLE 21 Block on a rough inclined plane with a spring

A block of mass 2 kg is placed on a rough plane inclined at 30° . It is attached to a spring of natural length 0.5 m and modulus 40 N, fixed at the top of the plane. The block is released from rest with the spring unstretched. The coefficient of friction is 0.25. Find the maximum distance the block moves down the plane before coming to rest. Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

Let x be the distance moved down the plane (extension of the spring). At the lowest point, $v = 0$. Initial energy (top): $E_i = 0$ (KE) + 0 (GPE, ref at start) + 0 (spring). Final energy (lowest point): $- \text{KE} = 0$. $- \text{GPE}$: vertical drop $= x \sin 30^\circ = x/2$, so $E_p = -mg(x/2) = -2 \times 10 \times x/2 = -10x$. $- \text{Spring energy}$: $E_{el} = \frac{\lambda x^2}{2l} = \frac{40x^2}{2 \times 0.5} = 40x^2$. Work done against friction: friction force $F_f = \mu N = \mu mg \cos 30^\circ = 0.25 \times 20 \times \frac{\sqrt{3}}{2} = 2.5\sqrt{3} \text{ N}$. Work lost $= F_f x = 2.5\sqrt{3} x$. Energy equation: $E_i = E_f + \text{work against friction}$.

$$0 = -10x + 40x^2 + 2.5\sqrt{3}x.$$

Divide by x ($x > 0$): $40x = 10 - 2.5\sqrt{3} \approx 10 - 4.33 = 5.67$.

$$x = \frac{10 - 2.5\sqrt{3}}{40} \approx 0.142 \text{ m}.$$

The block moves about 14.2 cm down the plane.

9.5 Power: Definition, Instantaneous Power and Power–Velocity

DEFINITION Power

Power is the rate at which work is done or energy is transferred.

- Average power over a time interval Δt : $P_{av} = \frac{W}{\Delta t} = \frac{\Delta E}{\Delta t}$.
- Instantaneous power of a force $\vec{F}$ acting on a particle moving with velocity $\vec{v}$:

$$P = \vec{F} \cdot \vec{v} = Fv \cos \theta,$$

where θ is the angle between $\vec{F}$ and $\vec{v}$.

The SI unit is the watt (W): $1 \text{ W} = 1 \text{ J s}^{-1}$. $1 \text{ kW} = 1000 \text{ W}$; $1 \text{ hp} \approx 746 \text{ W}$.

PROPERTY Power and velocity for a vehicle

If a vehicle's engine works at a constant power P and the vehicle moves at speed v , the driving force (tractive force) is

$$F = \frac{P}{v}.$$

At maximum speed on a given incline, acceleration $a = 0$, so the driving force exactly balances the total resistance (including the component of weight if on a slope):

$$\frac{P}{v_{\max}} = R_{\text{total}} \implies v_{\max} = \frac{P}{R_{\text{total}}}.$$

If the vehicle is accelerating, Newton's second law gives

$$\frac{P}{v} - R_{\text{total}} = ma.$$

METHOD Solving power–velocity–acceleration problems

1. Identify the given power P (constant or instantaneous), mass m , resistances R (may depend on v), and incline α .
2. Write the driving force: $F = \frac{P}{v}$.
3. Apply Newton's second law along the direction of motion:

$$\frac{P}{v} - R - mg \sin \alpha = ma.$$

4. For maximum speed: set $a = 0$ and solve for $v_{\max}$.
5. For acceleration at a given speed v : substitute v and solve for a .
6. If resistance varies with speed (e.g. $R = kv$ or kv^2), substitute the expression before solving.

WORKED EXAMPLE 22 Car on a hill and on level ground

A car of mass 1200 kg climbs a hill inclined at α where $\sin \alpha = \frac{1}{14}$, at a constant speed of 18 m s^{-1} . Non-gravitational resistances total 400 N. (a) Find the power developed by the engine. (b) Find the maximum speed of the car on level ground with the same power and the same resistance. Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

(a) Power on the hill. Constant speed $\Rightarrow a = 0 \Rightarrow$ driving force F balances resistance + weight component.

$$F = R + mg \sin \alpha = 400 + 1200 \times 10 \times \frac{1}{14} = 400 + \frac{12000}{14} = 400 + \frac{6000}{7} = \frac{8800}{7} \text{ N.}$$

$$P = Fv = \frac{8800}{7} \times 18 = \frac{158400}{7} \approx 22\,629 \text{ W} = 22.6 \text{ kW.}$$

(b) Maximum speed on level ground. On level ground, $\sin \alpha = 0$, so at $v_{\max}$:

$$\frac{P}{v_{\max}} = R = 400 \Rightarrow v_{\max} = \frac{P}{400} = \frac{158400/7}{400} = \frac{396}{7} \approx 56.6 \text{ m s}^{-1}.$$

Interpretation. On the flat, the same engine power yields a much higher top speed because no power is spent raising the car's gravitational potential energy.

WORKED EXAMPLE 23 Acceleration of a car with constant power

A car of mass 1000 kg moves on a horizontal road against a constant resistance of 500 N. The engine works at a constant rate of 30 kW. Find (a) the maximum speed, (b) the acceleration when the speed is 20 m s^{-1} .

SOLUTION

(a) Maximum speed. $a = 0 \Rightarrow F = R = 500 \text{ N.}$

$$v_{\max} = \frac{P}{F} = \frac{30\,000}{500} = 60 \text{ m s}^{-1}.$$

(b) Acceleration at $v = 20 \text{ m s}^{-1}$. Driving force: $F = \frac{P}{v} = \frac{30\,000}{20} = 1500 \text{ N.}$ Newton's second law: $F - R = ma.$

$$1500 - 500 = 1000a \Rightarrow a = 1.0 \text{ m s}^{-2}.$$

Remark. As v increases, $F = P/v$ decreases, so acceleration decreases until it reaches zero at $v_{\max} = 60 \text{ m s}^{-1}.$

WARNING Constant speed vs. acceleration

A classic GCE error: using $P = Rv$ (which assumes $a = 0$) when the vehicle is accelerating. If the speed is changing, you must write $F = P/v$ and then $F - R - mg \sin \alpha = ma$. Only at maximum speed (or constant speed) does $F = R + mg \sin \alpha$ hold.

9.6 Pumping Water, Water Jets and Applications of Work, Energy and Power

DEFINITION Power of a pump or jet

A pump delivers a mass of water $\frac{dm}{dt}$ (in kg s^{-1}) and gives it:

- Gravitational potential energy by raising it through a height h : power $P_p = \frac{dm}{dt} gh$.
- Kinetic energy by ejecting it at speed v : power $P_k = \frac{1}{2} \frac{dm}{dt} v^2$.

The total useful hydraulic power is

$$P_{\text{useful}} = \frac{dm}{dt} \left(gh + \frac{1}{2} v^2 \right).$$


If the pump has efficiency η ($0 < \eta \leq 1$), the input power required is

$$P_{\text{in}} = \frac{P_{\text{useful}}}{\eta}.$$

For a jet of cross-sectional area A and speed v , the mass flow rate is $\frac{dm}{dt} = \rho Av$, where $\rho = 1000 \text{ kg m}^{-3}$ for water.

METHOD Power of a pump or water jet

1. Determine the mass flow rate $\frac{dm}{dt}$ (given directly, or computed from volume flow rate $\times 1000$, or from ρAv for a jet).
2. Compute the potential energy rate: $P_p = \frac{dm}{dt} gh$ (if water is lifted).
3. Compute the kinetic energy rate: $P_k = \frac{1}{2} \frac{dm}{dt} v^2$ (if water is ejected with speed v).
4. Add them: $P_{\text{useful}} = P_p + P_k$.
5. If efficiency η is given, compute input power: $P_{\text{in}} = P_{\text{useful}} / \eta$.
6. Check units: $\text{kg s}^{-1} \times \text{m s}^{-2} \times \text{m} = \text{W}$.



Pump raising water from a well to an overhead tank with ejection speed v .

WORKED EXAMPLE 24 Village water pump

A pump raises water from a well 12 m deep and delivers it at 4 m s^{-1} into an overhead tank at a rate of 20 kg per second . (a) Find the useful power of the pump. (b) If the pump is only 70% efficient, find the power that must be supplied to it. Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

Given: $\frac{dm}{dt} = 20 \text{ kg s}^{-1}$, $h = 12 \text{ m}$, $v = 4 \text{ m s}^{-1}$, $\eta = 0.70$.

(a) Useful power. Potential energy rate:

$$P_p = \frac{dm}{dt} gh = 20 \times 10 \times 12 = 2400 \text{ W}.$$

Kinetic energy rate:

$$P_k = \frac{1}{2} \frac{dm}{dt} v^2 = \frac{1}{2} \times 20 \times 16 = 160 \text{ W}.$$

Total useful power:

$$P_{\text{useful}} = 2400 + 160 = 2560 \text{ W} = 2.56 \text{ kW}.$$

(b) Input power.

$$P_{\text{in}} = \frac{P_{\text{useful}}}{\eta} = \frac{2560}{0.70} \approx 3657 \text{ W} = 3.66 \text{ kW}.$$

Remark. The kinetic energy contribution (160 W) is small compared to the potential energy contribution (2400 W): most power is spent lifting the water.

WORKED EXAMPLE 25 Water jet from a fire hose

A fire hose has a nozzle of cross-sectional area $2.5 \times 10^{-4} \text{ m}^2$. Water emerges at 25 m s^{-1} . Find (a) the mass of water leaving the nozzle per second, (b) the kinetic energy given to the water per second, (c) the force exerted on a vertical wall if the jet hits it perpendicularly and falls vertically (assuming no splash back). Take $\rho = 1000 \text{ kg m}^{-3}$.

SOLUTION

(a) Mass flow rate:

$$\frac{dm}{dt} = \rho Av = 1000 \times 2.5 \times 10^{-4} \times 25 = 6.25 \text{ kg s}^{-1}.$$

(b) Kinetic energy per second (power of the jet):

$$P_k = \frac{1}{2} \frac{dm}{dt} v^2 = \frac{1}{2} \times 6.25 \times 625 = 1953.125 \text{ W} \approx 1.95 \text{ kW}.$$

(c) Force on the wall. The water's horizontal momentum is destroyed. Rate of change of momentum = force. Initial horizontal momentum per second = $\frac{dm}{dt} \times v = 6.25 \times 25 = 156.25 \text{ kg m s}^{-2} = 156.25 \text{ N}$. Final horizontal momentum = 0. Force on water = -156.25 N ; by Newton's third law, force on wall = 156.25 N .

9.7 Mixed Applications of Work, Energy and Power**METHOD** Strategy for GCE-type mixed problems

1. Read the problem twice; draw a clear diagram with all forces, heights, speeds, and distances.
2. Decide the appropriate tool:
 - Conservation of energy: smooth surfaces, no engine, no resistance.
 - Work-energy theorem: resistance, driving force, or non-conservative forces present.
 - $P = Fv$ with Newton's second law: engine power given, possibly with acceleration.
3. Write one energy or force equation per stage of the motion.
4. Keep exact values (surds, fractions) as long as possible; round only at the final answer to 3 significant figures.
5. Check physical sense: positive power, speed $\leq v_{\max}$, energy lost to resistance, etc.

WORKED EXAMPLE 26 Cyclist on the Buea mountain road

A cyclist and her bicycle have total mass 80 kg. She descends a straight hill inclined at $\sin^{-1}\left(\frac{1}{20}\right)$ to the horizontal. Starting from rest, she freewheels (no pedalling) against a constant resistance of 30 N. (a) Use the work–energy theorem to find her speed after travelling 200 m down the slope. (b) She then reaches level ground and pedals, working at a constant rate of 180 W against the same resistance of 30 N. Find her maximum speed on the level. Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

(a) Speed after 200 m downhill. Vertical drop: $h = 200 \sin \alpha = 200 \times \frac{1}{20} = 10 \text{ m}$. Forces doing work along the slope: – Component of gravity down the slope: $mg \sin \alpha = 80 \times 10 \times \frac{1}{20} = 40 \text{ N}$ (driving). – Resistance: 30 N (opposing). Work–energy theorem ($u = 0$):

$$W_{\text{gravity}} + W_{\text{resistance}} = \frac{1}{2}mv^2.$$

$$40 \times 200 - 30 \times 200 = \frac{1}{2}(80)v^2.$$

$$8000 - 6000 = 40v^2 \implies v^2 = 50 \implies v = \sqrt{50} = 5\sqrt{2} \approx 7.07 \text{ m s}^{-1}.$$

(b) Maximum speed on level ground. At maximum speed, $a = 0$, so driving force $F = R = 30 \text{ N}$. Power $P = 180 \text{ W}$ constant.

$$v_{\text{max}} = \frac{P}{F} = \frac{180}{30} = 6 \text{ m s}^{-1}.$$

Interpretation. Freewheeling downhill she reaches 7.07 m s^{-1} , faster than the 6 m s^{-1} she can sustain on the flat with 180 W. During the descent, gravity supplied power $mgv \sin \alpha = 40 \times 7.07 \approx 283 \text{ W}$, well above her own 180 W.

WORKED EXAMPLE 27 Particle projected up a rough inclined plane

A particle of mass 0.5 kg is projected up a rough plane inclined at 30° with an initial speed of 10 m s^{-1} . The coefficient of friction is 0.2. Find (a) the distance travelled up the plane before coming to rest, (b) the speed when it returns to the starting point. Take $g = 10 \text{ m s}^{-2}$.

SOLUTION

Data: $m = 0.5 \text{ kg}$, $u = 10 \text{ m s}^{-1}$, $\alpha = 30^\circ$, $\mu = 0.2$, $g = 10$. Weight component down plane: $mg \sin \alpha = 0.5 \times 10 \times 0.5 = 2.5 \text{ N}$. Normal reaction: $N = mg \cos \alpha = 0.5 \times 10 \times \frac{\sqrt{3}}{2} = 2.5\sqrt{3} \text{ N}$.

Friction: $F_f = \mu N = 0.2 \times 2.5\sqrt{3} = 0.5\sqrt{3} \text{ N}$.

(a) Distance x up the plane to rest ($v = 0$). Work–energy theorem (upward displacement

x): Forces doing work: weight component $(-2.5x)$, friction $(-0.5\sqrt{3}x)$.

$$\Delta E_k = 0 - \frac{1}{2}(0.5)(10^2) = -25 \text{ J.}$$

$$-2.5x - 0.5\sqrt{3}x = -25 \implies x(2.5 + 0.5\sqrt{3}) = 25.$$

$$x = \frac{25}{2.5 + 0.5\sqrt{3}} = \frac{50}{5 + \sqrt{3}} = \frac{50(5 - \sqrt{3})}{22} = \frac{25(5 - \sqrt{3})}{11} \approx 7.42 \text{ m.}$$

(b) Speed on return to start. Total distance travelled = $2x$. Work done by friction over round trip = $-2F_f x = -2(0.5\sqrt{3})x = -\sqrt{3}x$. Gravity is conservative $\Rightarrow$ net work by gravity over round trip = 0. Work-energy theorem for round trip:

$$W_{\text{friction}} = \Delta E_k = \frac{1}{2}mv^2 - \frac{1}{2}mu^2.$$

$$-\sqrt{3}x = \frac{1}{2}(0.5)v^2 - 25.$$

Substitute $x = \frac{25(5-\sqrt{3})}{11}$:

$$-\sqrt{3} \times \frac{25(5-\sqrt{3})}{11} = 0.25v^2 - 25.$$

$$-\frac{125\sqrt{3} - 75}{11} = 0.25v^2 - 25.$$

$$0.25v^2 = 25 - \frac{125\sqrt{3} - 75}{11} = \frac{275 - 125\sqrt{3} + 75}{11} = \frac{350 - 125\sqrt{3}}{11}.$$

$$v^2 = \frac{4(350 - 125\sqrt{3})}{11} = \frac{1400 - 500\sqrt{3}}{11} \approx 48.3 \implies v \approx 6.95 \text{ ms}^{-1}.$$

The return speed is less than the initial speed because friction dissipates energy.

WARNING Examination checklist

- Work and energy are scalars: add them with signs, never as vectors.
- $E_k = \frac{1}{2}mv^2 \geq 0$; a negative ΔE_k means kinetic energy is lost.
- In $P = Fv$, v is the instantaneous speed and F the force in the direction of motion.
- For pumps/jets: never forget the mgh term (lifting) or the $\frac{1}{2}mv^2$ term (ejection) when both occur.
- Always quote units: joules (J) for work and energy, watts (W) for power.
- On an incline, the angle for work is between the force and the displacement along the plane, not the angle of the plane itself.

- If a problem gives power and asks for acceleration, use $F = P/v$ then $F - R = ma$; do not assume $F = R$.

DID YOU KNOW? Historical note: James Watt and the horsepower

The watt is named after the Scottish engineer James Watt (1736–1819), who improved the steam engine. To market his engines, he compared their output to the work a horse could do, defining the horsepower (hp). He found a horse could turn a mill wheel of radius 12 ft at 2.4 revolutions per minute with a force of 180 lbf, giving $P \approx 33\,000 \text{ ft lbf/min} \approx 746 \text{ W}$. In Cameroon, generator and pump ratings are often given in kW or hp — remember $1 \text{ hp} \approx 0.746 \text{ kW}$.

EXERCISE 9 Practice problems

1. A force $\vec{F} = (3\vec{i} + 4\vec{j}) \text{ N}$ moves a particle from (1, 2) to (4, 6) (coordinates in metres). Find the work done by $\vec{F}$.
2. A 2 kg block is pushed 5 m up a rough 30° incline by a horizontal force of 30 N. The coefficient of friction is 0.15. Find the work done by each force and the final speed if it starts from rest. ($g = 10$)
3. A spring of natural length 0.4 m and modulus 50 N is compressed to 0.25 m. Find the work done in compressing it further to 0.15 m.
4. A 1500 kg car climbs a 1 in 10 hill at a constant 20 m s^{-1} . Resistance is 500 N. Find the engine power. If the same power is used on level ground, find the maximum speed.
5. A pump delivers $0.05 \text{ m}^3/\text{s}$ of water through a hose of cross-section $2 \times 10^{-4} \text{ m}^2$ to a height of 20 m. Find the useful power. If efficiency is 75%, find the input power. ($\rho = 1000$)
6. A particle slides from rest down a smooth quarter-circle wire of radius 2 m. Find its speed at the bottom. It then moves on a rough horizontal table with $\mu = 0.3$. How far does it travel before stopping? ($g = 10$)

SOLUTION Exercise 1

$$\vec{d} = (3\vec{i} + 4\vec{j}) \text{ m}. W = \vec{F} \cdot \vec{d} = 3 \times 3 + 4 \times 4 = 9 + 16 = 25 \text{ J}.$$

SOLUTION Exercise 2

Forces: horizontal $F = 30 \text{ N}$ ($\theta = 30^\circ$ to plane), weight $mg = 20 \text{ N}$, friction $f = \mu N$, normal N .
 $N = mg \cos 30^\circ - F \sin 30^\circ = 20 \frac{\sqrt{3}}{2} - 15 = 10\sqrt{3} - 15 \approx 2.32 \text{ N}$. $f = 0.15(10\sqrt{3} - 15) \approx 0.348 \text{ N}$.
 $W_F = 30 \times 5 \times \cos 30^\circ = 150 \frac{\sqrt{3}}{2} = 75\sqrt{3} \approx 129.9 \text{ J}$. $W_{mg} = -mg(5 \sin 30^\circ) = -20 \times 2.5 = -50 \text{ J}$.
 $W_f = -f \times 5 \approx -1.74 \text{ J}$. $W_N = 0$. $W_{\text{total}} \approx 78.2 \text{ J} = \frac{1}{2}(2)v^2 \Rightarrow v \approx 8.84 \text{ m s}^{-1}$.

SOLUTION Exercise 3

$l = 0.4$, $\lambda = 50$. $x_1 = 0.4 - 0.25 = 0.15$, $x_2 = 0.4 - 0.15 = 0.25$. $W = \frac{\lambda}{2l}(x_2^2 - x_1^2) = \frac{50}{0.8}(0.0625 - 0.0225) = 62.5 \times 0.04 = 2.5 \text{ J}$.

SOLUTION Exercise 4

$\sin \alpha = 0.1$. $F = R + mg \sin \alpha = 500 + 15000 \times 0.1 = 2000 \text{ N}$. $P = Fv = 2000 \times 20 = 40\,000 \text{ W} = 40 \text{ kW}$. Level: $v_{\text{max}} = P/R = 40\,000/500 = 80 \text{ m s}^{-1}$.

SOLUTION Exercise 5

$\frac{dm}{dt} = \rho \times \text{volume rate} = 1000 \times 0.05 = 50 \text{ kg/s}$. $v = \frac{\text{volume rate}}{A} = \frac{0.05}{2 \times 10^{-4}} = 250 \text{ m/s}$. $P_p = 50 \times 10 \times 20 = 10\,000 \text{ W}$. $P_k = \frac{1}{2} \times 50 \times 250^2 = 1\,562\,500 \text{ W}$. $P_{\text{useful}} = 1\,572\,500 \text{ W} \approx 1.57 \text{ MW}$.
 $P_{\text{in}} = 1.5725/0.75 \approx 2.10 \text{ MW}$.

SOLUTION Exercise 6

Smooth quarter-circle: $h = R = 2 \text{ m}$. $v_B = \sqrt{2gh} = \sqrt{40} = 2\sqrt{10} \approx 6.32 \text{ m/s}$. Rough horizontal:
 $W_f = -\mu mgd = \Delta E_k = 0 - \frac{1}{2}m(40)$. $0.3 \times 10 \times d = 20 \Rightarrow d = 20/3 \approx 6.67 \text{ m}$.

10 EXERCISES

10.1 I check my knowledge

EXERCISE 10 Multiple choice

A force of magnitude F acts on a body which moves a distance s in a straight line, the force making an angle θ with the direction of motion. The work done by the force is:

1. Fs
2. $Fs \sin \theta$
3. $Fs \cos \theta$
4. $\frac{Fs}{\cos \theta}$

Choose the correct answer and justify your choice.

EXERCISE 11 True or false

For each of the following statements, say whether it is true or false and justify your answer.

1. The work done against gravity in lifting a body of mass m through a vertical height h is mgh , whatever path is followed.
2. The kinetic energy of a body is doubled when its speed is doubled.
3. Power is the rate at which work is done, and its SI unit is the joule.
4. When a car moves at constant velocity on a level road, the net work done on the car is zero.

EXERCISE 12 Definitions

Define each of the following terms, giving in each case the SI unit and stating whether the quantity is a scalar or a vector:

1. the **work** done by a constant force;
2. the **kinetic energy** of a particle;
3. the **power** developed by a force.

EXERCISE 13 Direct calculations

1. A crate of mass 25 kg is lifted vertically through 3.2 m. Taking $g = 9.8 \text{ m s}^{-2}$, calculate the work done against gravity.
2. A particle of mass 0.5 kg moves with speed 6 m s^{-1} . Calculate its kinetic energy.
3. A machine does $4.5 \times 10^4 \text{ J}$ of work in 30 s. Calculate its average power.

10.2 I practise**EXERCISE 14** Work done by several forces

A force of 50 N acts at 30° to the horizontal and pulls a box 8 m along a rough horizontal floor against a friction force of 20 N.

1. Calculate the work done by the pulling force.
2. Calculate the work done by the friction force.
3. Calculate the work done by the weight of the box and by the normal reaction of the floor.
4. Deduce the net work done on the box.

EXERCISE 15 Stretching a spring

A spring of stiffness 200 N m^{-1} is stretched from an extension of 4 cm to an extension of 10 cm.

1. Calculate the work done by the stretching force.
2. Hence state the extra elastic potential energy stored in the spring.

EXERCISE 16 Work–energy theorem for a car

A car of mass 1200 kg accelerates from 5 m s^{-1} to 20 m s^{-1} over a distance of 100 m on a level road against a constant resistance of 400 N.

1. Calculate the change in kinetic energy of the car.
2. Use the work–energy theorem to find the work done by the engine.
3. Deduce the average driving force exerted by the engine.

EXERCISE 17 Conservation of energy

A ball is thrown vertically upwards with speed 14 m s^{-1} . Taking $g = 9.8 \text{ m s}^{-2}$ and neglecting air resistance, use conservation of energy to find:

1. the maximum height reached above the point of projection;
2. the speed of the ball when it is 5 m above the point of projection.

10.3 I prepare for the GCE**EXERCISE 18 Rough slope and energy method**

A block of mass m kg slides from rest down a rough slope of length 10 m inclined at 25° to the horizontal. The coefficient of friction between the block and the slope is 0.2. Take $g = 9.8 \text{ m s}^{-2}$.

1. Draw a diagram showing all the forces acting on the block. (2 marks)
2. Show that the magnitude of the friction force is $0.2 mg \cos 25^\circ$. (2 marks)
3. Calculate the work done against friction as the block descends the 10 m. (2 marks)
4. Use the work–energy theorem to find the speed of the block at the bottom of the slope. (4 marks)
5. State one assumption you have made. (1 mark)

EXERCISE 19 Power, hills and pumping water

A car of mass 1000 kg has an engine of maximum power 60 kW and experiences a constant resistance to motion of 500 N. Take $g = 9.8 \text{ m s}^{-2}$.

1. Find the maximum speed of the car on a level road. (3 marks)
2. The car now climbs a hill inclined at an angle $\sin^{-1}\left(\frac{1}{20}\right)$ to the horizontal, with the same resistance and the engine working at maximum power. Find its maximum speed up the hill. (4 marks)
3. A pump raises water from a river through a vertical height of 15 m at a rate of 40 kg s^{-1} and delivers it through a nozzle at 8 m s^{-1} . Find the total power developed by the pump. (4 marks)
4. Given that the pumping system is only 75 % efficient, find the power of the motor required to drive it. (2 marks)

EXERCISE 20 Cyclist, lorry and water jet

Part A. A cyclist of total mass 80 kg freewheels down a hill inclined at an angle $\sin^{-1}\left(\frac{1}{25}\right)$ to the horizontal and reaches a terminal speed of 12 m s^{-1} . Take $g = 9.8 \text{ m s}^{-2}$.

1. By considering the forces acting at terminal speed, find the magnitude of the resistance to motion, assumed constant. (3 marks)
2. Find the power the cyclist must develop to cycle up the same hill at a steady 6 m s^{-1} against the same resistance. (4 marks)

Part B. A lorry of mass 8000 kg moves on level ground with its engine working at a constant power of 90 kW against a resistance of magnitude $250v$ newtons, where $v \text{ m s}^{-1}$ is its speed.

- (a) Find the maximum speed of the lorry on level ground. (3 marks)
- (b) Find the acceleration of the lorry at the instant when its speed is 10 m s^{-1} . (3 marks)

Part C. A fire hose of cross-sectional area $2 \times 10^{-3} \text{ m}^2$ projects water of density 1000 kg m^{-3} horizontally at 25 m s^{-1} .

- (a) Find the mass of water discharged per second. (2 marks)
- (b) Find the kinetic energy delivered to the water per second, and comment on the minimum power of the pump. (2 marks)

11 SOLUTIONS TO THE EXERCISES

SOLUTION Exercise 1 — Multiple choice

The correct answer is (c): $W = Fs \cos \theta$.

Justification. Work is done only by the component of the force in the direction of the displacement. Resolving the force $\vec{F}$ into components parallel and perpendicular to the motion:

- component along the motion: $F \cos \theta$;
- component perpendicular to the motion: $F \sin \theta$ (this does no work, since there is no displacement in that direction).

Hence

$$W = (F \cos \theta) \times s = Fs \cos \theta.$$

Equivalently, work is the scalar product $W = \vec{F} \cdot \vec{s} = Fs \cos \theta$, where θ is the angle between $\vec{F}$ and $\vec{s}$.

Check of special cases: if $\theta = 0$ (force along the motion), $W = Fs$; if $\theta = 90^\circ$ (force perpendicular to the motion, e.g. the normal reaction), $W = 0$; if $\theta = 180^\circ$ (force opposing the motion, e.g. friction), $W = -Fs$. These confirm formula (c) and reject (a), (b) and (d).

KEY POINTS Work done by a constant force

For a constant force $\vec{F}$ and a displacement $\vec{s}$:

$$W = \vec{F} \cdot \vec{s} = Fs \cos \theta \quad (\text{joule, J})$$

- $W > 0$ if the force has a component in the direction of motion ($0 \leq \theta < 90^\circ$);
- $W = 0$ if the force is perpendicular to the motion ($\theta = 90^\circ$);
- $W < 0$ if the force opposes the motion ($90^\circ < \theta \leq 180^\circ$).

Work is a scalar quantity.

SOLUTION Exercise 2 — True or false

1. True. The weight mg is a conservative force: its work depends only on the vertical displacement, not on the path. Whatever the path, the work done by the weight is $-mgh$ when the body rises through h , so the work done against gravity (by the lifting agent) is mgh .

2. False. Kinetic energy is $T = \frac{1}{2}mv^2$, i.e. it is proportional to the square of the speed. Doubling the speed multiplies the kinetic energy by $2^2 = 4$, not by 2.
3. False (as stated). It is true that power is the rate at which work is done, $P = \frac{W}{t}$ (average) or $P = \frac{dW}{dt}$ (instantaneous). However, its SI unit is the watt (W), where $1 \text{ W} = 1 \text{ J s}^{-1}$. The joule is the unit of work and energy, not of power.
4. True. At constant velocity the kinetic energy is constant, so by the work–energy theorem the net work done on the car is zero: the positive work of the driving force exactly cancels the negative work of the resistances (friction, air resistance). Note that the engine still does work — it is the total work that is zero.

KEY POINTS Key concepts check

- Work against gravity: $W = mgh$ (path independent).
- Kinetic energy: $T = \frac{1}{2}mv^2 \propto v^2$.
- Power: $P = \frac{dW}{dt}$, unit = watt (W) = J/s.
- Constant velocity $\Rightarrow$ net work = 0 (but individual forces may do work).

SOLUTION Exercise 3 — Definitions

1. Work done by a constant force. The work done by a constant force $\vec{F}$ whose point of application undergoes a displacement $\vec{s}$ is the scalar product

$$W = \vec{F} \cdot \vec{s} = Fs \cos \theta,$$

where θ is the angle between the force and the displacement. SI unit: the joule (J), with $1 \text{ J} = 1 \text{ N m}$. Work is a scalar (it can be positive, negative or zero).

2. Kinetic energy. The kinetic energy of a particle of mass m moving with speed v is the energy it possesses by virtue of its motion:

$$T = \frac{1}{2}mv^2.$$

SI unit: the joule (J). Kinetic energy is a scalar, and it is always non-negative ($T \geq 0$).

3. Power. The power developed by a force is the rate at which the force does work:

$$P = \frac{dW}{dt}.$$

For a constant force moving its point of application at velocity $\vec{v}$, $P = \vec{F} \cdot \vec{v} = Fv \cos \theta$. SI unit: the watt (W), with $1 \text{ W} = 1 \text{ J s}^{-1}$. Power is a scalar.

PROPERTY Instantaneous power for a constant force

If a constant force $\vec{F}$ acts on a particle moving with instantaneous velocity $\vec{v}$, the instantaneous power is

$$P = \vec{F} \cdot \vec{v} = Fv \cos \theta.$$

Proof: $W = \vec{F} \cdot \vec{s} \Rightarrow \frac{dW}{dt} = \vec{F} \cdot \frac{d\vec{s}}{dt} = \vec{F} \cdot \vec{v}.$

SOLUTION Exercise 4 — Direct calculations

1. Work done against gravity:

$$W = mgh = 25 \times 9.8 \times 3.2 = 784 \text{ J}.$$

2. Kinetic energy:

$$T = \frac{1}{2}mv^2 = \frac{1}{2} \times 0.5 \times 6^2 = \frac{1}{2} \times 0.5 \times 36 = 9 \text{ J}.$$

3. Average power:

$$P = \frac{W}{t} = \frac{4.5 \times 10^4}{30} = 1.5 \times 10^3 \text{ W} = 1.5 \text{ kW}.$$

METHOD Calculating work, energy and power

1. Identify the known quantities: mass m , height h , speed v , work W , time t .
2. Choose the correct formula: $W = mgh$, $T = \frac{1}{2}mv^2$, $P = W/t$ (average) or $P = Fv$ (instantaneous, constant force).
3. Substitute values with consistent SI units (kg, m, s).
4. Compute and state the answer with the correct unit.

SOLUTION Exercise 5 — Work done by several forces

1. Work done by the pulling force. Only the horizontal component $50 \cos 30^\circ$ does work:

$$W_p = 50 \cos 30^\circ \times 8 = 50 \times \frac{\sqrt{3}}{2} \times 8 = 200\sqrt{3} \approx 346.4 \text{ J.}$$

2. Work done by friction. Friction opposes the motion ($\theta = 180^\circ$):

$$W_f = -20 \times 8 = -160 \text{ J.}$$

3. Work done by the weight and the normal reaction. Both forces are perpendicular to the (horizontal) displacement, so $\cos 90^\circ = 0$:

$$W_{\text{weight}} = 0 \text{ J}, \quad W_R = 0 \text{ J.}$$

4. Net work. The net work is the sum of the works of all the forces:

$$W_{\text{net}} = 200\sqrt{3} - 160 + 0 + 0 \approx 346.4 - 160 = 186.4 \text{ J.}$$

By the work–energy theorem, this positive net work equals the gain in kinetic energy of the box.

KEY POINTS Work done by multiple forces

The total (net) work done on a particle is the algebraic sum of the works done by each individual force:

$$W_{\text{net}} = \sum_i W_i = \sum_i \vec{F}_i \cdot \vec{s}.$$

Forces perpendicular to the displacement do zero work. The work–energy theorem states $W_{\text{net}} = \Delta T$.

SOLUTION Exercise 6 — Stretching a spring

The tension in a spring of stiffness k at extension x is $T = kx$ (Hooke's law). Since the tension varies with the extension, the work done by the stretching force from extension x_1 to x_2 is

$$W = \int_{x_1}^{x_2} kx \, dx = \frac{1}{2}k(x_2^2 - x_1^2).$$

1. Here $k = 200 \text{ N m}^{-1}$, $x_1 = 0.04 \text{ m}$, $x_2 = 0.10 \text{ m}$:

$$W = \frac{1}{2} \times 200 \times (0.10^2 - 0.04^2) = 100 \times (0.01 - 0.0016) = 100 \times 0.0084 = 0.84 \text{ J.}$$

2. The work done by the stretching force is stored as elastic potential energy, so the ex-

tra elastic potential energy stored is

$$\Delta E_e = 0.84 \text{ J.}$$

WARNING Common mistake

Do not compute $\frac{1}{2}k(x_2 - x_1)^2$: the spring already stores energy $\frac{1}{2}kx_1^2$ at extension x_1 . The extra energy is the difference $\frac{1}{2}kx_2^2 - \frac{1}{2}kx_1^2$.

PROPERTY Elastic potential energy

For a spring of stiffness k extended by x from its natural length, the elastic potential energy stored is

$$E_e = \frac{1}{2}kx^2.$$

The work done in stretching from x_1 to x_2 equals the increase in elastic potential energy: $W = \Delta E_e = \frac{1}{2}k(x_2^2 - x_1^2)$.

SOLUTION Exercise 7 — Work–energy theorem for a car

1. Change in kinetic energy:

$$\Delta T = \frac{1}{2}m(v^2 - u^2) = \frac{1}{2} \times 1200 \times (20^2 - 5^2) = 600 \times (400 - 25) = 600 \times 375 = 225\,000 \text{ J} = 2.25 \times 10^5 \text{ J}$$

2. Work done by the engine. The work–energy theorem states:

$$W_{\text{engine}} + W_{\text{resistance}} = \Delta T.$$

The resistance does work $W_{\text{resistance}} = -400 \times 100 = -40\,000 \text{ J}$. Hence

$$W_{\text{engine}} = \Delta T - W_{\text{resistance}} = 225\,000 + 40\,000 = 265\,000 \text{ J} = 2.65 \times 10^5 \text{ J}.$$

3. Average driving force. Since $W_{\text{engine}} = F_{\text{av}} \times s$:

$$F_{\text{av}} = \frac{265\,000}{100} = 2650 \text{ N.}$$

METHOD Applying the work–energy theorem

1. Calculate the change in kinetic energy: $\Delta T = \frac{1}{2}m(v^2 - u^2)$.
2. Calculate the work done by each force (positive, negative, or zero).
3. Apply $W_{\text{net}} = \Delta T$ or $\sum W_i = \Delta T$.
4. Solve for the unknown (work, force, distance, or final speed).

SOLUTION Exercise 8 — Conservation of energy

Take the point of projection as the level of zero potential energy. With no air resistance, the total mechanical energy $E = \frac{1}{2}mv^2 + mgh$ is conserved.

1. Maximum height. At the highest point the speed is zero. Conservation of energy between projection and the top:

$$\frac{1}{2}m(14)^2 + 0 = 0 + mgH \implies H = \frac{14^2}{2g} = \frac{196}{2 \times 9.8} = \frac{196}{19.6} = 10 \text{ m.}$$

2. Speed at height 5 m. Conservation of energy between projection and the point at height $h = 5$ m:

$$\frac{1}{2}m(14)^2 = \frac{1}{2}mv^2 + mg(5).$$

Dividing by m and multiplying by 2:

$$196 = v^2 + 2 \times 9.8 \times 5 = v^2 + 98 \implies v^2 = 98 \implies v = \sqrt{98} = 7\sqrt{2} \approx 9.9 \text{ m s}^{-1}.$$

(The same speed is found on the way up and on the way down, since energy is conserved.)

PROPERTY Conservation of mechanical energy


When only conservative forces (gravity, elastic forces) do work, the total mechanical energy is constant:

$$E = T + V = \frac{1}{2}mv^2 + mgh + \frac{1}{2}kx^2 = \text{constant.}$$

If non-conservative forces (friction, air resistance) act, then $W_{\text{nc}} = \Delta E = \Delta T + \Delta V$.

SOLUTION Exercise 9 — Rough slope and energy method

1. Diagram (2 marks). The forces are: the weight mg acting vertically downwards; the normal reaction R perpendicular to the slope; the friction F acting up the slope, opposing the motion.



Forces on a block sliding down a rough slope.

Mark scheme: 1 mark for weight vertically down and R perpendicular to the plane; 1 mark for friction directed up the slope.

2. Friction force (2 marks). Resolving the weight perpendicular to the slope, there is no acceleration in that direction, so

$$R = mg \cos 25^\circ.$$

Since the block is sliding, friction is limiting: $F = \mu R$ with $\mu = 0.2$. Hence

$$F = 0.2 mg \cos 25^\circ. \quad \blacksquare$$

Mark scheme: 1 mark for $R = mg \cos 25^\circ$; 1 mark for $F = \mu R$.

3. Work done against friction (2 marks). The friction acts opposite to the displacement over 10 m:

$$W_f = F \times 10 = 10 \times 0.2 mg \cos 25^\circ = 2 mg \cos 25^\circ.$$

Numerically, with m in kg:

$$W_f = 2 \times 9.8 \times \cos 25^\circ \times m \approx 17.76 m \text{ J}.$$

Mark scheme: 1 mark for method $W = Fs$; 1 mark for the correct expression/value.

4. Speed at the bottom (4 marks). The vertical drop is

$$h = 10 \sin 25^\circ \text{ m}.$$

The work–energy theorem between the top (rest) and the bottom gives

$$\underbrace{mgh}_{\text{work of weight}} - \underbrace{0.2 mg \cos 25^\circ \times 10}_{\text{work against friction}} = \frac{1}{2}mv^2.$$

Dividing by m :

$$\frac{1}{2}v^2 = 10g \sin 25^\circ - 2g \cos 25^\circ = 9.8(10 \sin 25^\circ - 2 \cos 25^\circ).$$

Numerically, $10 \sin 25^\circ \approx 4.226$ and $2 \cos 25^\circ \approx 1.813$:

$$\frac{1}{2}v^2 = 9.8 \times (4.226 - 1.813) = 9.8 \times 2.413 \approx 23.65 \quad \Rightarrow \quad v^2 \approx 47.3,$$

$$v \approx 6.9 \text{ m s}^{-1}.$$

Mark scheme: 1 mark for the height $h = 10 \sin 25^\circ$; 1 mark for a correct work–energy equation; 1 mark for correct algebra (mass cancels); 1 mark for the numerical answer.

5. Assumption (1 mark). Any one of: friction is constant along the whole slope (coefficient uniform); the block is treated as a particle; air resistance is neglected; g is constant.

KEY POINTS Energy method on an inclined plane

For a particle sliding down a rough slope of length s and angle θ :

- Vertical drop: $h = s \sin \theta$.
- Normal reaction: $R = mg \cos \theta$.
- Friction force: $F = \mu mg \cos \theta$.
- Work against friction: $W_f = -\mu mgs \cos \theta$.
- Work–energy: $mgh - \mu mgs \cos \theta = \frac{1}{2}mv^2$.

Mass m always cancels out.

SOLUTION Exercise 10 — Power, hills and pumping water

1. Maximum speed on the level (3 marks). At maximum (constant) speed the acceleration is zero, so the driving force F balances the resistance:

$$F = 500 \text{ N}.$$

Using $P = Fv$ with $P = 60\,000 \text{ W}$:

$$v_{\max} = \frac{P}{F} = \frac{60\,000}{500} = 120 \text{ m s}^{-1}.$$

Mark scheme: 1 mark for $F = R$ at top speed; 1 mark for $P = Fv$; 1 mark for the answer.

2. Maximum speed up the hill (4 marks). On the hill, the driving force must overcome the resistance and the component of the weight down the slope. With $\sin \theta = \frac{1}{20}$:

$$mg \sin \theta = 1000 \times 9.8 \times \frac{1}{20} = 490 \text{ N.}$$

At maximum speed (no acceleration):

$$F = 500 + 490 = 990 \text{ N.}$$

Then

$$v_{\max} = \frac{P}{F} = \frac{60\,000}{990} \approx 60.6 \text{ m s}^{-1}.$$

Mark scheme: 1 mark for resolving the weight; 1 mark for the total resisting force; 1 mark for $v = P/F$; 1 mark for the answer.

3. Power of the pump (4 marks). Each second, a mass $\dot{m} = 40 \text{ kg}$ is raised through 15 m and given kinetic energy at 8 m s^{-1} . The pump must supply both:

$$P = \underbrace{\dot{m}gh}_{\text{gain of PE per second}} + \underbrace{\frac{1}{2}\dot{m}v^2}_{\text{gain of KE per second}}.$$

$$P = 40 \times 9.8 \times 15 + \frac{1}{2} \times 40 \times 8^2 = 5880 + 1280 = 7160 \text{ W} \approx 7.16 \text{ kW.}$$

Mark scheme: 1 mark for the PE term; 1 mark for the KE term; 1 mark for adding both; 1 mark for the answer. A very common error is to forget the kinetic energy of the delivered water.

4. Power of the motor (2 marks). With efficiency 75%:

$$\text{efficiency} = \frac{\text{useful power output}}{\text{power input}} \implies P_{\text{motor}} = \frac{7160}{0.75} \approx 9547 \text{ W} \approx 9.55 \text{ kW.}$$

Mark scheme: 1 mark for the correct use of efficiency; 1 mark for the answer.

PROPERTY Power for pumping fluids

For a pump delivering a mass flow rate $\dot{m}$ (kg/s) of fluid:

- Power to raise through height h : $P_{\text{PE}} = \dot{m}gh$.
- Power to give speed v : $P_{\text{KE}} = \frac{1}{2}\dot{m}v^2$.
- Total useful power: $P = \dot{m}gh + \frac{1}{2}\dot{m}v^2$.
- If pump efficiency is η , input power = P/η .

SOLUTION Exercise 11 — Cyclist, lorry and water jet

Part A — the cyclist.

1. Resistance at terminal speed (3 marks). At terminal (constant) speed, the forces along the slope balance: the component of the weight down the slope equals the resistance R . With $\sin \theta = \frac{1}{25}$:

$$R = mg \sin \theta = 80 \times 9.8 \times \frac{1}{25} = \frac{784}{25} = 31.36 \text{ N.}$$

Mark scheme: 1 mark for resolving the weight; 1 mark for equilibrium at terminal speed; 1 mark for the value.

2. Power to climb at 6 m s^{-1} (4 marks). Going up the hill at steady speed, the cyclist must overcome both the resistance and the component of the weight:

$$F = R + mg \sin \theta = 31.36 + 31.36 = 62.72 \text{ N.}$$

The power required is

$$P = Fv = 62.72 \times 6 = 376.32 \text{ W} \approx 376 \text{ W.}$$

Mark scheme: 1 mark for recognising that both resistance and gravity oppose the motion uphill; 1 mark for $F = 62.72 \text{ N}$; 1 mark for $P = Fv$; 1 mark for the answer.

Part B — the lorry.

- (a) Maximum speed (3 marks). At maximum speed the driving force equals the resistance $250v$, and $P = Fv$:

$$90\,000 = 250v \times v = 250v^2 \implies v^2 = \frac{90\,000}{250} = 360 \implies v_{\max} = \sqrt{360} = 6\sqrt{10} \approx 19.0 \text{ m s}^{-1}.$$

Mark scheme: 1 mark for $F = 250v$ at top speed; 1 mark for $P = Fv$; 1 mark for the answer.

- (b) Acceleration at $v = 10 \text{ m s}^{-1}$ (3 marks). The driving force at that instant is

$$F = \frac{P}{v} = \frac{90\,000}{10} = 9000 \text{ N.}$$

The resistance is $250 \times 10 = 2500 \text{ N}$. Newton's second law:

$$F - 250v = ma \implies 9000 - 2500 = 8000a \implies a = \frac{6500}{8000} = 0.8125 \text{ m s}^{-2} \approx 0.81 \text{ m s}^{-2}.$$

Mark scheme: 1 mark for $F = P/v$; 1 mark for applying Newton's second law with the resistance; 1 mark for the answer.

Part C — the water jet.

- (a) Mass discharged per second (2 marks). In one second the water occupies a cylinder of length $v = 25 \text{ m}$ and cross-section $A = 2 \times 10^{-3} \text{ m}^2$, i.e. a volume Av :

$$\dot{m} = \rho Av = 1000 \times 2 \times 10^{-3} \times 25 = 50 \text{ kg s}^{-1}.$$

Mark scheme: 1 mark for $\dot{m} = \rho Av$; 1 mark for the value.

(b) Kinetic energy delivered per second (2 marks).

$$\frac{\Delta T}{\Delta t} = \frac{1}{2} \dot{m} v^2 = \frac{1}{2} \times 50 \times 25^2 = 25 \times 625 = 15\,625 \text{ W} \approx 15.6 \text{ kW}.$$

Comment: since the water leaves horizontally, no potential energy is involved; the kinetic energy given to the water each second is exactly the useful work done by the pump each second. Hence the pump must develop at least 15.6 kW — in practice more, because of friction losses in the hose and the pump's own efficiency being less than 100%. Mark scheme: 1 mark for $\frac{1}{2} \dot{m} v^2$; 1 mark for the value and the comment on minimum power.


KEY POINTS Power and variable resistance

When resistance depends on speed ($R = kv$ or $R = kv^2$):

- At maximum speed: $P = F_{\text{drive}} v = Rv \Rightarrow P = kv^2$ or kv^3 .
- At any speed: $F_{\text{drive}} = P/v$, then $ma = P/v - R(v)$.

For water jets: mass flow rate $\dot{m} = \rho Av$, power = $\frac{1}{2} \dot{m} v^2 + \dot{m} gh$ (if height change).

12 SUMMARY SHEET



Mind map of the chapter Work, Energy and Power.

KEY POINTS Chapter Summary — Work, Energy and Power

Key definitions

- The **work** done by a constant force $\vec{F}$ over a displacement s is $W = Fs \cos \theta$, where θ is the angle between the force and the displacement. Unit: the **joule** (J), $1 \text{ J} = 1 \text{ N m}$.
- Work done **against gravity** in raising a mass m through a vertical height h : $W = mgh$ (independent of the path taken).

- Work of a **variable force** $F(x)$: $W = \int_{x_1}^{x_2} F(x) dx$ (area under the force–displacement graph). For a spring obeying Hooke's law $F = kx$, the work done in stretching or compressing the spring (work against the spring force) is $W = \frac{1}{2}kx^2$.
- **Kinetic energy**: $KE = \frac{1}{2}mv^2$. **Gravitational potential energy**: $GPE = mgh$ (relative to a chosen reference level).
- **Power** is the rate of doing work: average power $P = \frac{W}{t}$, instantaneous power $P = \frac{dW}{dt} = Fv$ (when force and velocity are parallel). Unit: the **watt** (W); $1 \text{ kW} = 1000 \text{ W}$; $1 \text{ hp} \approx 746 \text{ W}$.

Laws and theorems to know

- **Work–Energy Theorem**: the net work done on a body equals its change in kinetic energy:

$$W_{\text{net}} = \Delta KE = \frac{1}{2}mv^2 - \frac{1}{2}mu^2.$$

- **Principle of Conservation of Mechanical Energy**: when only conservative forces (gravity, spring force) act,

$$KE_1 + GPE_1 = KE_2 + GPE_2.$$

- With a constant resistive force R acting over a distance s :

$$KE_1 + GPE_1 = KE_2 + GPE_2 + Rs$$

(energy lost as work done against resistance).

- **Power–velocity relation**: a vehicle with driving force F moving at speed v develops power $P = Fv$; at maximum constant speed, driving force equals total resistance.
- On an incline of angle α : component of weight down the plane = $mg \sin \alpha$; power required to move uphill at constant speed v against resistance R is $P = (R + mg \sin \alpha)v$.
- **Pumping water**: to raise a mass m of water through height h in time t , $P = \frac{mgh}{t} = \frac{\rho Vgh}{t}$.
For a jet ejecting mass at rate $\dot{m}$ with speed v : kinetic power $P = \frac{1}{2}\dot{m}v^2$; using $\dot{m} = \rho Av$, $P = \frac{1}{2}\rho Av^3$.

Methods

1. Draw a clear force diagram; resolve the weight into components parallel and perpendicular to the direction of motion.
2. Choose the appropriate tool: constant acceleration $\Rightarrow$ energy methods are often quicker than $F = ma$; variable force $\Rightarrow$ integrate $F(x)$.
3. Fix a reference level for GPE and keep it consistent throughout the question.
4. For power questions, write $P = Fv$ and identify F from equilibrium (constant speed) or from Newton's second law (accelerating).

5. For pumps and jets, first find the mass moved per second ($\dot{m}$), then apply energy per second.

Common mistakes

- Using $W = Fs$ when the force is not parallel to the displacement — the factor $\cos \theta$ is essential.
- Forgetting that work against gravity depends only on the vertical height gained, not the path length.
- Mixing units: convert km/h to m/s (divide by 3.6), kW to W, minutes to seconds.
- Sign errors in the work–energy theorem: work done by a resistive force is negative.
- Confusing mass m with mass per second $\dot{m}$ in water–jet problems.
- Assuming $P = Fv$ implies constant F : at constant power, F decreases as v increases.

GCE tips

- Quote the theorem before substituting: examiners award method marks for “by conservation of energy” or “by the work–energy theorem”.
- Keep $g = 9.8 \text{ m s}^{-2}$ (or 9.81 as required) and give final answers to 3 significant figures unless stated otherwise.
- In “maximum speed” vehicle problems, state explicitly: acceleration zero $\Rightarrow$ driving force equals total resistance.
- Show the energy balance line by line (initial KE + initial GPE = final KE + final GPE + work against resistance); this structure earns full credit even if arithmetic slips.



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+