

ICT • UPPER SIXTH

UPPER SIXTH — ICT

CHAPTER 17

REVIEWING THE HISTORY OF THE INTERNET

SUGGESTED TIME: 2 PERIODS

IN THIS CHAPTER

This chapter traces the Internet from its military–research origins to the global, high-speed network we use today, and examines the connectivity technologies and technical requirements that make access possible. Mastery of these topics is essential for the GCE Advanced Level ICT examination and for understanding Cameroon’s digital development.

- Explain the key milestones in the history and development of the Internet (ARPANET, TCP/IP, World Wide Web).
- Describe the transition from a research network to a commercial, public infrastructure.
- Identify and compare major Internet connectivity technologies (dial-up, DSL, cable, fibre, wireless, satellite).
- Analyse the hardware, software and protocol requirements for establishing an Internet connection.
- Differentiate IPv4 and IPv6 addressing schemes and their relevance to address exhaustion.
- Evaluate the impact of bandwidth, latency and reliability on user experience.



DOWNLOAD ON- BUCH

Free • Google Play
AI tutor, past papers, results



GO ONBUCH+

All signed courses, unlimited AI tutor, PDF sheets — OnBuch+ tab in the app

THIS SIGNED COURSE CONTAINS

COURSE

complete, illustrated, step by step

METHODS

and worked examples

EXERCISES

exam style + solutions

SUMMARY SHEET

the essentials to remember



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+

CONTENTS

- | | |
|--|--------------------------------------|
| 1. 1. Origins and Early Development of the Internet | ing and Security for Internet Access |
| 2. 2. Expansion, Commercialisation and the Modern Internet | 5. Integration activity |
| 3. 3. Internet Connectivity Technologies and Media | 6. Methods and worked examples |
| 4. 4. Technical Requirements, Address- | 7. Exercises |
| | 8. Solutions to the exercises |
| | 9. Summary sheet |

CHAPTER OBJECTIVES

- Explain the key milestones in the history and development of the Internet (ARPANET, TCP/IP, World Wide Web).
- Describe the transition from a research network to a commercial, public infrastructure.
- Identify and compare major Internet connectivity technologies (dial-up, DSL, cable, fibre, wireless, satellite).
- Analyse the hardware, software and protocol requirements for establishing an Internet connection.
- Differentiate IPv4 and IPv6 addressing schemes and their relevance to address exhaustion.
- Evaluate the impact of bandwidth, latency and reliability on user experience.
- Apply knowledge to propose suitable connectivity solutions for specific Cameroonian contexts (urban, peri-urban, rural).
- Critically assess common misconceptions about Internet speed, bandwidth and security.

PREREQUISITES

- Basic understanding of computer networks (LAN, WAN, OSI model) from Lower Sixth.
- Familiarity with binary numbering and data representation.

- Knowledge of common telecommunications terms (modem, router, ISP).
- Awareness of Cameroon's geography and existing telecom operators (MTN, Orange, Camtel).
- Ability to interpret simple diagrams and tables.

1 ORIGINS AND EARLY DEVELOPMENT OF THE INTERNET

Imagine a student in Yaoundé downloading a 2 GB video lesson over a 4G connection while a peer in a remote village in the East Region struggles with a 56 kbps dial-up line. The stark contrast illustrates how the Internet's history and the technologies that connect us shape everyday learning opportunities across Cameroon. This section traces the remarkable journey from a Cold-War research project to the global network that now underpins education, commerce and communication.

1.1 Cold-War Context and the Birth of ARPANET

In the late 1950s, the Soviet launch of Sputnik (1957) spurred the United States to create the Advanced Research Projects Agency (ARPA) in 1958. ARPA's mandate was to maintain technological superiority, particularly in command-and-control systems that could survive a nuclear strike. The prevailing telephone network used circuit switching — a dedicated physical path is reserved for the entire call — which is vulnerable because destroying a single switch disconnects all calls passing through it.


DEFINITION Packet Switching

Packet switching breaks data into small, self-contained units called **packets**. Each packet carries a destination address and is routed independently through the network. Packets may follow different paths and are reassembled at the destination. This provides robustness: if one link fails, packets are rerouted automatically.

WARNING Circuit Switching vs Packet Switching

Do not confuse the two. Circuit switching (traditional telephone) reserves bandwidth end-to-end for the session duration; packet switching (Internet) shares links statistically. In exams, you may be asked to compare latency, efficiency and fault tolerance.

ARPA funded research at UCLA, Stanford Research Institute (SRI), UC Santa Barbara and the University of Utah. On **29 October 1969**, the first ARPANET message — “LO” (intended “LOGIN”) — was sent from UCLA to SRI. By December 1969, the four-node network was operational, using the Network Control Protocol (NCP) over 50 kbps leased lines.



The four-node ARPANET in December 1969.

1.2 From NCP to TCP/IP — The Protocol Suite that United Networks

By the early 1970s, multiple packet-switching networks existed (ARPANET, SATNET, PRNET, CYCLADES in France). They could not interoperate because each used its own host-to-host protocol. Vint Cerf and Bob Kahn solved this with the **Transmission Control Program** (1974, RFC 675), later split into two layers: **TCP** (reliable end-to-end delivery) and **IP** (addressing and routing).

PROPERTY TCP/IP Layered Architecture (DoD Model)

The TCP/IP model comprises four layers:

1. Application Layer — user-level protocols (HTTP, FTP, SMTP, DNS).
2. Transport Layer — TCP (reliable, connection-oriented) and UDP (unreliable, datagram).
3. Internet Layer — IP (routing, fragmentation, addressing), ICMP, ARP.
4. Link Layer — Ethernet, Wi-Fi, PPP, etc. (physical and data-link combined).

Each layer adds its own header (encapsulation). This modularity allows innovation at one layer without disturbing others.

On **1 January 1983** (Flag Day), ARPANET switched from NCP to TCP/IP, marking the birth of the **Internet** as a network of networks. The decision to make TCP/IP open and royalty-free was pivotal for global adoption.

METHOD Tracing Protocol Evolution via RFC Numbers

1. Identify the protocol (e.g., TCP, IP, HTTP).

2. Visit the RFC Editor website (<https://www.rfc-editor.org/>).
3. Search by keyword or number. Key RFCs:
 - RFC 791 (IP), RFC 793 (TCP) — 1981 standards.
 - RFC 1122/1123 — Host/Application requirements.
 - RFC 2616 (HTTP/1.1), RFC 7540 (HTTP/2).
4. Note Obsoletes and Updated by fields to follow the lineage.
5. For exam purposes, memorise the seminal RFC numbers for TCP, IP, DNS, HTTP.

1.3 Naming the Network — The Domain Name System (DNS)

As the network grew, the central `HOSTS.TXT` file maintained at SRI became unmanageable. In 1983, Paul Mockapetris designed the **Domain Name System (DNS)**, a distributed, hierarchical database (RFC 882, RFC 883).

DEFINITION Domain Name System (DNS)

DNS maps human-readable domain names (e.g., `www.antic.cm`) to IP addresses (e.g., `196.201.216.10`). It uses a tree of domains delegated to authoritative name servers. The root zone is served by 13 logical root server clusters (A–M) distributed worldwide.

The first top-level domains (TLDs) created in 1984–1985 were:

TLD	Purpose	Year
.arpa	Infrastructure (reverse DNS)	1984
.com	Commercial organisations	1985
.edu	Educational institutions (US)	1985
.gov	US government	1985
.mil	US military	1985
.org	Non-profit organisations	1985
.net	Network infrastructure	1985

Country-code TLDs (ccTLDs) like `.cm` (Cameroon, delegated in 1995 and managed by ANTIC) followed ISO 3166-1 alpha-2 codes. The `.int` TLD for international organisations was created later (1988).

DID YOU KNOW? Cameroon's .cm Domain

The `.cm` ccTLD is administered by the Agence Nationale des Technologies de l'Information

et de la Communication (ANTIC). It became active in 1995, enabling Cameroonian entities to have a distinct online identity. Today, .cm domains are widely used by government (gov.cm), education (edu.cm), and businesses.

1.4 The World Wide Web — A Service on Top of the Internet

By 1989, the Internet supported email, FTP, Usenet, Telnet — but information was scattered and hard to navigate. At CERN, Tim Berners-Lee proposed a hypertext system to link documents across the network. By Christmas 1990 he had implemented:

- **HTML** (HyperText Markup Language) — document structure.
- **HTTP** (HyperText Transfer Protocol) — application-layer transfer (port 80).
- **URL** (Uniform Resource Locator) — global addressing scheme (`scheme://host/path`).
- The first web browser/editor (`WorldWideWeb`) and server (`httpd`).

WARNING Internet vs World Wide Web

The Internet is the global infrastructure (routers, cables, TCP/IP). The World Wide Web is a service (HTTP + HTML + URLs) that runs on top of the Internet. Confusing them is a classic exam trap. Other Internet services: email (SMTP/IMAP/POP), file transfer (FTP/SFTP), remote login (SSH), VoIP (SIP/RTP).


The release of **Mosaic** (1993), the first popular graphical browser, and **Netscape Navigator** (1994) triggered explosive growth.

1.5 Expansion, Commercialisation and the Rise of ISPs

The US National Science Foundation built **NSFNET** (1986) as a 56 kbps backbone connecting supercomputer centres. It upgraded to T1 (1.544 Mbps) in 1988 and T3 (45 Mbps) in 1991, linking regional networks and universities. Crucially, NSFNET's Acceptable Use Policy initially restricted commercial traffic.

In 1991, the Commercial Internet eXchange (CIX) allowed commercial networks to interconnect. By 1995, NSFNET was decommissioned; the Internet backbone was fully privatized. **Internet Service Providers (ISPs)** emerged to sell connectivity to businesses and homes — first via dial-up (modems over PSTN), then ISDN, DSL, cable, fibre and mobile.

In Cameroon, the first ISP licences were granted in the late 1990s (CAMTEL, then private operators). MTN Cameroon and Orange Cameroon later deployed 2G/3G/4G, making mobile the primary Internet access mode for most citizens.



Key milestones from ARPANET to the commercial Internet (1969–1995).

1.6 Worked Example: Analysing a Historical Scenario

WORKED EXAMPLE 1 Question

A 1992 internal memo at a Cameroonian university states: “We will connect to the Internet via NSFNET to access the World Wide Web for research.” Identify three technical or policy inaccuracies in this statement for the year 1992.

SOLUTION

Solution.

1. **NSFNET Access Policy:** In 1992, NSFNET’s Acceptable Use Policy still restricted traffic to research and education. A university could connect, but commercial use (e.g., consulting for a private firm) was prohibited. The memo implies unrestricted “Internet” access.
2. **World Wide Web Availability:** The WWW was publicly released in August 1991, but in 1992 it was still extremely niche — only a handful of servers existed (mostly at CERN and a few universities). Graphical browsers (Mosaic) appeared in 1993. Most Internet traffic in 1992 was email, FTP, Gopher, Telnet. Expecting routine “Web access” is anachronistic.
3. **Terminology — Internet vs NSFNET:** NSFNET was a backbone funded by NSF; the “Internet” was the collection of interconnected networks (including ARPANET until 1990, CSNET, BITNET gateways, etc.). Saying “connect to the Internet via NSFNET” conflates a backbone with the whole network of networks. A more accurate phrasing: “connect to the Internet through our regional network which peers with NSFNET.”

1.7 Key Points to Retain

KEY POINTS Summary of Section 1

- 1969: ARPANET (4 nodes) demonstrates packet switching — robust, decentralized.
- 1974: Cerf & Kahn publish TCP/IP design (RFC 675, later RFC 791/793).
- 1 Jan 1983: Flag Day — ARPANET adopts TCP/IP; the Internet is born.
- 1984–85: DNS introduced; first TLDs (.arpa, .com, .edu, .gov, .mil, .org, .net).
- 1989–1991: Tim Berners-Lee invents the WWW (HTML, HTTP, URL) at CERN.
- 1993: Mosaic browser popularises the Web.
- 1995: NSFNET decommissioned; Internet backbone fully commercial; ISPs proliferate.
- Distinction: Internet = infrastructure (TCP/IP); Web = application service (HTTP/HTML).

EXERCISE 1 Exercise 1

1. Explain why packet switching is more resilient than circuit switching for a military command network.
2. List the four layers of the TCP/IP model and give one protocol example per layer.
3. What problem did DNS solve, and why was a hierarchical design chosen?
4. Distinguish between the Internet and the World Wide Web. Give two examples of Internet services that are not the Web.
5. In what year did the NSFNET backbone cease operation, and what did this signify for Internet governance?

SOLUTION Exercise 1

1. Packet switching does not reserve a dedicated path; packets are routed independently. If a switch or link is destroyed, subsequent packets find alternative routes. Circuit switching fails completely if any link in the dedicated circuit is broken.
2. Application (HTTP), Transport (TCP), Internet (IP), Link (Ethernet).
3. DNS replaced the centrally maintained `HOSTS.TXT` which did not scale. Hierarchy allows delegation: each zone manages its own subdomains, enabling distributed administration and caching.

4. Internet = global network of networks running TCP/IP. Web = information system using HTTP/HTML/URLs over the Internet. Other services: Email (SMTP), File Transfer (FTP), Remote Login (SSH).
5. 1995. It marked the transition from a US government-funded research backbone to a fully privatized, commercially operated Internet infrastructure.

2 THE WEB REVOLUTION AND THE MODERN INTERNET

In the previous section we saw how the **internet** grew from the military-academic network ARPANET (1969) into a worldwide infrastructure unified by the TCP/IP protocol suite (1983). By the end of the 1980s, the internet existed and worked well — but it was used almost exclusively by scientists and engineers typing cryptic commands on text terminals. Sending a file required FTP commands; reading news required Usenet; there was no simple way to jump from one document to another. The revolution that transformed this expert tool into the everyday medium we know today was not a new network: it was a new service built on top of the existing network. That service is the **World Wide Web**, and understanding the difference between the two is one of the most frequently tested points at the GCE Advanced Level.


2.1 The Internet Is Not the Web

Imagine the road network of Cameroon: the tarred roads from Douala to Yaoundé and Bamenda existed before any particular business was built along them. The roads are the infrastructure; the banks, restaurants and delivery services built beside them are services that use the roads. Closing one restaurant does not destroy the road, and the road can carry many different kinds of traffic.

The same logic applies here. The **internet** is the global infrastructure: millions of interconnected networks, routers, cables and protocols (TCP/IP) that transport packets of data. The **World Wide Web** is only one service among several that travel over this infrastructure, exactly as e-mail, file transfer (FTP) or video streaming do.

DEFINITION The World Wide Web

The **World Wide Web** (WWW or simply “the Web”) is a system of interlinked **hypertext** documents and resources, identified by addresses called URLs and accessed via the internet using application programs called **browsers**. It was invented by the British computer scientist **Tim Berners-Lee** at CERN in 1989. The Web is a service that runs on the internet; it is not the internet itself.



Layered view: the internet is the transport infrastructure; the Web, e-mail, FTP and streaming are services running on top of it.

WARNING The classic exam trap

A very common mistake in GCE scripts is to write: “The internet was invented in 1989 by Tim Berners-Lee.” This is wrong. What Tim Berners-Lee invented in 1989 is the World Wide Web. The internet is much older: ARPANET dates from 1969, and the modern internet based on TCP/IP dates from 1983. Always write “the Web” when you mean 1989, and “the internet” when you mean 1969/1983. Confusing the two can cost you the full mark of a definition question.

2.2 1989–1991: Tim Berners-Lee Invents the Web at CERN

CERN, the European Organisation for Nuclear Research near Geneva, hosted thousands of physicists from different countries, each with different computers and incompatible document systems. Tim Berners-Lee observed that scientists wasted enormous time simply finding information scattered across machines. His idea, proposed in March 1989, was elegant: let any document contain **hyperlinks** — clickable references that jump directly to another document, wherever it is stored in the world.

To make this work, he created three technologies that remain the foundation of the Web today:

- **HTML** (HyperText Markup Language): the language used to write web pages, marking titles, paragraphs, images and, above all, hyperlinks.
- **HTTP** (HyperText Transfer Protocol): the set of rules by which a browser requests a page from a web server and the server delivers it.
- **URL** (Uniform Resource Locator): the unique address of every resource on the Web, for example an address beginning with `http://` followed by a server name and a file path.

By 1990–1991 Berners-Lee had also written the first web server and the first browser, which he named WorldWideWeb — a program that could both read and edit pages. The first website, hosted at CERN, simply explained what the Web was. Crucially, CERN decided in 1993 to make

the Web technology freely available to everyone, without royalties. This open decision is a major reason the Web spread so fast.

DID YOU KNOW? Key persons to remember for the exam

- **Tim Berners-Lee**: invented the World Wide Web (HTML, HTTP, URL) at CERN in 1989.
- **Ray Tomlinson**: sent the first networked **e-mail** in 1971 and chose the @ symbol to separate the user name from the machine name.
- **Marc Andreessen**: co-author of the **Mosaic** browser (1993) and co-founder of **Netscape** (1994), which brought the Web to the general public.

2.3 1993–1998: Browsers for Everyone, Commercialisation and Search Engines

The early Web was still text-based and known only in universities. Two events opened it to the public. In **1993**, Marc Andreessen and Eric Bina at the University of Illinois released **Mosaic**, the first popular graphical browser: it displayed images inside pages and could be driven with a mouse, making the Web attractive to non-specialists. In **1994** Andreessen co-founded **Netscape**, whose Navigator browser dominated the market and triggered an explosion of websites. Microsoft answered with Internet Explorer (1995), launching the “browser wars”.

Businesses quickly understood that a website was a shop window open to the whole planet. The late 1990s saw the **dot-com boom**: investors poured money into any company whose name ended in “.com”, stock values soared, and thousands of online businesses were created. Many had no realistic revenue, and the bubble burst around 2000–2001 — but the commercial Web survived and matured (Amazon and Google, founded in the 1990s, are famous survivors).

As the number of pages grew into the millions, finding information became a problem, solved by **search engines**: Yahoo! (1994, initially a human-edited directory), AltaVista, and then **Google** (1998), whose PageRank algorithm ranked pages by the links pointing to them and quickly became the world reference.

2.4 The 2000s: Web 2.0 — the User Becomes a Producer

The first Web was largely read-only: a few organisations published pages and everyone else consumed them. From the mid-2000s, a new generation of sites inverted this relationship. Ordinary users could publish, comment, share and collaborate without knowing HTML. This transformation is called **Web 2.0**.

DEFINITION Web 2.0


Web 2.0 designates the participatory or social Web, in which users are no longer passive readers but active **content producers**: they publish articles and photos, edit shared documents, comment and interact. Typical Web 2.0 services include **blogs**, **wikis** (e.g. Wikipedia), **social networks** (Facebook, launched 2004), video-sharing platforms (YouTube, 2005) and messaging applications (WhatsApp, 2009).

EXAMPLE Web 1.0 versus Web 2.0 in daily life

Reading an online newspaper article in 1999 was Web 1.0: you could only read. Today a student in Buea can write a blog post about local agriculture, upload a tutorial video to YouTube, contribute to the Wikipedia article on Mount Cameroon, and discuss it all in a WhatsApp group — that is Web 2.0. The same infrastructure (the internet) carries both; what changed is who produces the content.

2.5 The Mobile Internet: the Web in Your Pocket

The next revolution was mobility. Early mobile phones offered only voice and SMS. The arrival of **3G** networks (2000s) and then **4G** (2010s) provided data rates high enough for comfortable browsing, e-mail and video on the move. The launch of Apple's iPhone (2007) and of Android phones popularised the **smartphone**: a pocket computer with a touch screen, a real browser and **apps** — small dedicated applications for banking, maps, messaging or social media. The internet ceased to be a place you “went to” at a cybercafé; it became something permanently in your pocket. In Cameroon, as in most of Africa, the majority of people experience the internet primarily through a mobile phone, often using mobile money services such as MTN Mobile Money or Orange Money that rely entirely on this connectivity.



Timeline 1989–2012: the Web revolution worldwide (blue, above) and milestones of the internet in Cameroon (orange, below).

2.6 A Brief History of the Internet in Cameroon

Cameroon's first internet connections appeared in the **1990s**, initially through slow and expensive satellite links and dial-up telephone lines, mostly serving universities, NGOs and a few companies in Douala and Yaoundé. The state operator **CAMTEL** (Cameroon Telecommunications), created in 1998, inherited the national telephone network and progressively built the national fibre-optic **backbone** that carries traffic between cities and to the coast.

A decisive step was the landing of submarine fibre-optic cables, which connect Cameroon to the global internet at high capacity and lower cost than satellites:

- **SAT-3/WASC/SAFE** (around 2002): the first submarine cable serving Cameroon, landing at Douala.
- **WACS** (West Africa Cable System, 2012) and **ACE** (Africa Coast to Europe, 2012): newer, higher-capacity cables that multiplied available bandwidth and helped reduce prices.

On the retail side, mobile operators **MTN** and **Orange** (from 1999–2000), later joined by **Nexttel** (2014), democratised access: first through 2G/EDGE, then 3G and 4G, making mobile internet the dominant mode of access for Cameroonians. The regulator (ART) and the security agency **ANTIC** supervise the sector, while e-government services (online tax declarations, exam results) progressively move public services onto the Web.

2.7 Current Trends: Internet of Things and Web 3.0 (Exam Extra)

DID YOU KNOW? Beyond the syllabus — short awareness

Two trends are frequently mentioned in exam “open” questions:

- The **Internet of Things** (IoT): everyday objects — meters, vehicles, farm sensors, televisions — are connected to the internet and exchange data without human intervention.
- **Web 3.0**: an evolving term for a more intelligent and decentralised Web, combining the semantic web (data understandable by machines), artificial intelligence and, in some visions, blockchain technologies.

A single well-phrased sentence on each is enough to earn the bonus mark; do not develop them at length.

2.8 Worked Example and Examination Method

WORKED EXAMPLE 2 Distinguishing internet and Web in a GCE question

Statement. (a) Define the World Wide Web. (b) A candidate writes: “The internet was created in 1989 at CERN.” Identify and correct the two errors in this statement.

SOLUTION

Solution. (a) The World Wide Web is a system of interlinked hypertext documents and resources, identified by URLs and accessed through the internet using browsers; it was invented by Tim Berners-Lee at CERN in 1989. (b) First error: what was created in 1989 at CERN is the Web, a service, not the internet. Second error: the internet is far older — it descends from ARPANET (1969) and took its modern form with the adoption of TCP/IP in 1983. Corrected sentence: “The World Wide Web was created in 1989 at CERN by Tim Berners-Lee; it runs on the internet, whose origins go back to ARPANET in 1969.”

METHOD Structuring a “history of the internet” essay for the GCE

When a question asks you to trace the history of the internet, organise your answer in three clearly labelled eras:

1. ARPANET era (1969–1982): military and academic packet-switching network in the USA; first e-mail (Tomlinson, 1971).
2. TCP/IP and NSFNET era (1983–1990): adoption of the TCP/IP protocols (1983), the internet becomes a network of networks open to universities.
3. Web era (1989 to today): Berners-Lee invents the Web (1989); Mosaic/Netscape open it to the public (1993–94); commercialisation and search engines (late 1990s); Web 2.0 and mobile internet (2000s); in Cameroon, CAMTEL backbone, SAT-3/WACS/ACE cables and mobile operators.

Finish with one sentence on current trends (IoT, Web 3.0). This chronological skeleton guarantees full coverage and impresses the examiner.

KEY POINTS Key points of this section

- The **internet** is the infrastructure (1969/1983); the **Web** is a service on top of it, invented by **Tim Berners-Lee** at CERN in **1989** using HTML, HTTP and URLs.
- **Mosaic** (1993) and **Netscape** (1994, Marc Andreessen) made the Web graphical and public; the late 1990s brought commercialisation, the dot-com boom and search engines (Google, 1998).
- **Web 2.0** (2000s) turned users into content producers (blogs, wikis, Facebook, YouTube, WhatsApp); smartphones, 3G/4G and apps made the internet mobile.
- In Cameroon: first links in the 1990s, CAMTEL backbone, submarine cables SAT-3 (2002), WACS and ACE (2012), and mobile internet through MTN, Orange and Next-tel.
- Current trends to mention briefly: the Internet of Things and Web 3.0.

EXERCISE 2 Check your understanding

1. Give two services, other than the Web, that run on the internet, and name the protocol associated with each.
2. Explain, in three sentences, why the statement “Google invented the internet” contains two mistakes.
3. Construct a table with two columns (Web 1.0, Web 2.0) and three rows (role of the user, example services, approximate period).
4. Describe the role of submarine cables in the development of the internet in

Cameroon, naming at least two of them.

3 INTERNET CONNECTIVITY TECHNOLOGIES

In the previous section we saw how the World Wide Web transformed the internet from a tool for researchers into a global public space. But a web browser is useless if the computer cannot actually reach the network. Between your laptop in Bamenda and a web server in London, there must be a physical path for data: a telephone line, a fibre optic cable, a radio wave to a satellite, or a signal from a mobile phone mast. The technologies that provide this path are called **internet connectivity technologies**. Choosing between them is a daily practical question in Cameroon: should a cybercafé in Ngaoundéré invest in fibre, in a 4G router, or in a satellite dish? This section gives you the knowledge to answer such questions rigorously.

3.1 Classification of Connection Types

Internet connection technologies are usually classified into four broad families:

- **Dial-up** connections: narrowband, established on demand over the ordinary telephone line.
- **Broadband wired** connections: high-speed, permanent connections over telephone lines (ADSL), TV cables, or fibre optics.
- **Wireless** connections: local wireless access (Wi-Fi hotspots, fixed wireless) and satellite links.
- **Mobile** connections: internet through the cellular phone network (2G, 3G, 4G, 5G).

DEFINITION Broadband

Broadband is a high-speed, always-on internet connection, as opposed to dial-up, which is slow and must be established (“dialled”) each time it is used. With broadband, the connection is permanent: the moment you open your browser, you are online.

DEFINITION Bandwidth

The **bandwidth** of a connection is the maximum rate at which data can be transferred through it. It is measured in bits per second (bps) and its multiples: kilobits per second (kbps), megabits per second (Mbps) and gigabits per second (Gbps). A higher bandwidth means web pages load faster, videos play smoothly, and files download quickly.

DEFINITION Latency

The **latency** of a connection is the time taken for a small piece of data to travel from the sender to the receiver and back (round-trip time), usually measured in milliseconds (ms). Low latency is essential for real-time applications such as video calls and online games; high latency is tolerable for e-mail and ordinary browsing.

WARNING Bandwidth is not “speed” in the everyday sense

Students often say a connection is “fast” when they mean it has high bandwidth. Strictly, bandwidth measures how much data passes per second, not how quickly a single bit travels. Also note the units: internet speeds are given in bits per second (Mbps), while file sizes are in Bytes (1 Byte = 8 bits). A 10 MB file on an 8 Mbps line takes about 10 seconds ($10 \times 8 = 80$ megabits, divided by 8 megabits per second), not 1.25 seconds.

3.2 Dial-up: the Historical Connection

The earliest home internet connections used the ordinary telephone network. A **dial-up modem** (the word comes from MOdulator–DEModulator) converts the computer’s digital signals into audio tones that travel over the telephone line, and back again at the other end. To connect, the modem literally telephoned the Internet Service Provider (ISP), which is why old modems made characteristic beeping and hissing sounds.

The fastest dial-up modems reached only **56 kbps** (0.056 Mbps). Two serious limitations followed:

- The telephone line was occupied: nobody could make or receive a phone call while the computer was online.
- Speeds were so low that loading a single photograph could take a minute; video was impossible.

Despite this, dial-up has enormous historical importance: it carried the internet into homes and schools during the 1990s, and in Cameroon the first cybercafés of the early 2000s often ran on dial-up or similar low-speed links.

3.3 ADSL: Broadband over the Telephone Line

ADSL (Asymmetric Digital Subscriber Line) is a broadband technology that reuses the same copper telephone line as dial-up, but in a clever way: it transmits data on high frequencies that the human voice does not use. A small device called a **splitter** (or filter) separates the voice frequencies from the data frequencies, so the telephone and the internet can be used at the same time.

The word asymmetric means the download speed (from the internet to you) is much higher than the upload speed (from you to the internet). Typical ADSL offers 8 to 24 Mbps download and about 1 Mbps upload. This suits most home users, who download far more than they upload.

WARNING Distance matters with ADSL

ADSL speed decreases strongly with the length of the copper line between the subscriber and the telephone exchange. A customer 5 km from the exchange may get only a fraction of the advertised speed. In exams, do not quote the “advertised” speed as guaranteed.

3.4 Cable and Fibre Optics (FTTH)

Cable internet delivers broadband through the same coaxial cable used for cable television, typically reaching tens to a few hundred Mbps. It is common in some countries but little deployed in Cameroon.

Fibre optics goes much further. In a fibre optic cable, data is encoded as pulses of light travelling inside a very thin glass fibre, kept inside by total internal reflection. When fibre reaches the subscriber’s home, the service is called **FTTH** (Fibre To The Home).

PROPERTY Advantages of fibre optics


Fibre optics offers the highest speeds (commonly 100 Mbps to 1 Gbps and beyond) and the lowest interference of all wired technologies, because data travels as light pulses in glass fibres: light is immune to the electromagnetic interference that disturbs electrical signals in copper wires, and signal loss over distance is very small.

In Cameroon, fibre is deployed mainly in Yaoundé and Douala, where operators such as CAMTEL and MTN offer FTTH to homes and businesses. The national fibre backbone also links major towns, but extending fibre to every quarter remains costly.

3.5 Satellite Internet

Where no cable or telephone line reaches — a village in the Far North, a forest camp in the East — **satellite internet** may be the only option. The principle is simple to picture:

1. The user installs a small dish antenna pointed at a geostationary satellite fixed high above the equator.
2. The dish sends the user’s requests up to the satellite, which relays them down to the ISP’s ground station connected to the internet.
3. Replies travel back along the reverse path: ground station → satellite → dish → computer.



Schematic of a satellite internet link: the user's dish communicates with a geostationary satellite, which relays traffic to the ISP's ground station connected to the internet.

The great advantage of satellite is coverage: a single satellite can serve an entire country, including the most remote rural zones. The great drawback is **latency**: a geostationary satellite orbits about 36 000 km above the Earth, so the signal must travel roughly 72 000 km up and down, adding a noticeable delay (often 500 ms or more). Web browsing still works, but real-time applications such as video calls or online games suffer. Equipment and subscriptions are also relatively expensive.

3.6 Wireless Local Access: Wi-Fi and Fixed Wireless

Wi-Fi is a local wireless technology: a wireless router connected to a wired line (ADSL, fibre) shares the connection over radio waves within a home, school or cybercafé, typically over a few tens of metres. A public Wi-Fi access point is called a **hotspot** (found in airports, hotels, some university campuses).

Fixed wireless extends the same idea over longer distances: an ISP installs an antenna on a mast and the customer has a small antenna on the roof, giving broadband without laying cables to each building.

WARNING Wi-Fi is not the internet connection

A very common mistake is to confuse **Wi-Fi** with the internet connection itself. Wi-Fi is only the last few metres: the wireless link between your device and the router. The router itself must still be connected to the internet by ADSL, fibre, 4G or another technology. A laptop can show “connected to Wi-Fi” and still have no internet access if the router's own connection is down.

3.7 Mobile Networks: from 2G to 5G


Mobile networks bring internet access through the same cellular masts that carry phone calls. Each generation has brought a leap in speed and services:

Generation	Technology	Typical speed	Main services
2G	GPRS / EDGE	up to about 0.2 Mbps	Text-based browsing, e-mail, basic mobile money
3G	UMTS / HSPA	1–10 Mbps	Web browsing, social media, small downloads
4G / LTE	LTE	10–100 Mbps	HD video streaming, video calls, fast downloads
5G	NR	100 Mbps–1 Gbps+	Very high speed, very low latency, connected objects

In Cameroon, mobile internet is by far the dominant way people get online: MTN and Orange provide 3G and 4G coverage in towns and along main roads, and most Cameroonians experience the internet through a smartphone. Mobile money services (MTN MoMo, Orange Money) run over these same networks. 5G is at an early stage of deployment, concentrated in the largest cities.

3.8 Comparing the Technologies

The chart below compares typical maximum download speeds on a logarithmic scale, because the values differ enormously.



Typical maximum download speeds (logarithmic scale): dial-up 0.056 Mbps, ADSL up to 24 Mbps, 4G up to about 100 Mbps, fibre up to 1000 Mbps (1 Gbps).

Speed is not the only criterion. A good comparison uses five criteria: **bandwidth**, **availability**, **cost**, **latency** and **mobility**.

Technology	Advantage	Disadvantage	Best suited for
Dial-up	Works on any phone line	Extremely slow; blocks the line	(Historical interest only)
ADSL	Cheap; uses existing lines	Speed falls with distance	Homes near an exchange
Fibre (FTTH)	Highest speed, very reliable	Costly to deploy; limited coverage	Cities, businesses, schools
Satellite	Covers remote areas	High latency; expensive	Rural and isolated zones
Mobile 3G/4G	Mobility; wide coverage	Data bundles costly; coverage gaps	Smartphones, users on the move

METHOD Choosing an internet connection

1. Identify the need: required speed (simple e-mail or video streaming?), number of users, mobility (fixed office or on the move?).
2. Check availability at the location: is there fibre in the quarter? 4G coverage? Only satellite?
3. Compare costs: equipment, installation, and monthly subscription or data bundles.
4. Match the technology to the need: e.g. fibre for a city cybercafé, 4G router for a mobile worker, satellite for a rural health centre.
5. Verify with a real test (speed test) before committing to a long contract.

WORKED EXAMPLE 3 Choosing a connection for a school

A secondary school in a rural district of the North West Region wants internet for its computer laboratory of 40 machines. There is no telephone line and no fibre; 3G coverage exists but is weak and unstable. Propose a solution and justify it.

SOLUTION

Solution. Apply the method: (1) Need: 40 simultaneous users require high bandwidth and stability; the school is fixed, so mobility is irrelevant. (2) Availability: no ADSL, no fibre; 3G is present but weak. (3) Cost: satellite equipment is expensive but is a one-off investment plus subscription. (4) Match: a satellite link (dish + router) distributing the connection to the laboratory through Wi-Fi or a wired network is the most suitable option, because it is the only technology offering stable, adequate bandwidth at this location. The weak 3G can serve as a backup. The known drawback of satellite — latency — is acceptable for teaching (browsing, e-mail, downloads), though less ideal for video conferencing.

EXERCISE 3 Comparing two offers

A trader in Douala hesitates between a 4G router (advertised up to 100 Mbps, paid per data bundle) and an FTTH fibre subscription (up to 50 Mbps, flat monthly rate). She uses the internet heavily all day for her online shop. Advise her, giving one argument based on cost and one based on quality of service.

SOLUTION Exercise 1

Cost argument: with heavy daily use, paying per data bundle on 4G quickly becomes more expensive than a flat-rate fibre subscription, which allows unlimited (or very large) usage for a fixed monthly price. Quality argument: although 4G advertises a higher peak speed (100 Mbps vs 50 Mbps), fibre delivers a more stable, consistent speed with lower latency and no dependence on mobile network congestion — important for a shop that must stay online all day. Conclusion: the FTTH subscription is the better choice for her fixed, intensive usage; the 4G router could remain as a mobile backup.

WARNING Exam tip

For the GCE, learn at least one advantage and one disadvantage of each connectivity technology (dial-up, ADSL, cable/fibre, satellite, Wi-Fi, mobile 2G–5G). Questions frequently ask you to “compare two technologies” or “justify a choice for a given situation” — always argue from the criteria: **bandwidth**, **availability**, **cost**, **latency** and **mobility**.

DID YOU KNOW? Internet in Cameroon

Cameroon illustrates perfectly why several technologies must coexist. Mobile internet (3G/4G) dominates because smartphones are the main device and mobile masts reach far beyond the wired network. Fibre concentrates in Yaoundé and Douala, where CAMTEL, MTN and Orange compete on FTTH offers. And for rural schools, health centres and administrative posts far from any cable, satellite remains the technology of last resort — which is why national digital-inclusion programmes study all three solutions together.

KEY POINTS Key points

- Connections are classified as **dial-up**, **broadband wired**, **wireless** and **mobile**.
- **Bandwidth** (in bps, kbps, Mbps, Gbps) measures the maximum data rate; **latency**

measures the round-trip delay.

- Dial-up (56 kbps) is historically important but obsolete; ADSL reuses the telephone line with a splitter and offers asymmetric broadband (8–24 Mbps).
- Fibre optics (FTTH) carries data as light pulses: the highest speeds (up to 1 Gbps) and lowest interference.
- Satellite covers remote areas but suffers from high latency (about 500 ms).
- Wi-Fi is only the local wireless link, not the internet connection itself.
- Mobile networks evolved from 2G (GPRS/EDGE) to 5G, multiplying speeds by thousands; in Cameroon, mobile internet dominates.
- Compare technologies using bandwidth, availability, cost, latency and mobility.

4 TECHNICAL REQUIREMENTS, ADDRESSING AND SECURITY FOR INTERNET ACCESS

In the previous section we examined the physical ways a home, school or business in Cameroon can reach the Internet: ADSL over telephone lines, fibre to the home, 4G/5G mobile networks, satellite links, and the media (copper, fibre, radio) that carry the signals. But owning a cable or a SIM card is not enough. Between your computer and a web server in Douala or abroad, a whole chain of equipment, software, addresses and protocols must work together – and the whole chain must be protected. This final section completes the picture: we study what a host needs to connect, how machines are identified on the Internet, which protocols make communication possible, how to manage traffic quality, and how to keep the connection fast and safe. We close with the Cameroonian regulatory framework that governs Internet service provision.

4.1 Hardware and Software Requirements

Observation. A student in Buea buys a laptop and a 4G subscription, yet cannot connect her old desktop computer at home. Why? The laptop has a built-in wireless network card; the old desktop has none. Connecting to the Internet begins with the right **hardware**.

DEFINITION Hardware requirements for Internet access

The essential hardware for connecting a host to the Internet comprises:

- a **Network Interface Card** (NIC): the circuit (Ethernet, Wi-Fi, or mobile broadband) that physically connects the computer to a network medium and handles frames at the data link layer;
- a **modem** (modulator–demodulator) or **ONT** (Optical Network Terminal): converts

digital data into signals suitable for the transmission line (telephone line for ADSL, radio for 4G/5G, light for fibre via an ONT);

- a **router**: forwards packets between the local network (LAN) and the Internet (WAN), and usually combines modem/ONT interface, switch, Wi-Fi access point and firewall in one box (the “box” supplied by CAMTEL, MTN or Orange);
- **cabling**: UTP (Unshielded Twisted Pair, e.g. Cat5e/Cat6) for Ethernet up to 100 m, or optical fibre for long distances and very high speeds;
- a **power backup** (UPS, inverter or generator): essential in Cameroon where power cuts can interrupt connectivity and damage equipment.

Software requirements. Hardware alone is mute; it needs software to speak the language of the Internet.

- The **operating system network stack**: every modern OS (Windows, Linux, macOS, Android) implements the TCP/IP model — drivers for the NIC, then IP, then TCP/UDP, then applications.
- **TCP/IP configuration**: each host needs an IP address, a subnet mask, a default gateway and DNS server addresses. These can be assigned automatically by **DHCP** (Dynamic Host Configuration Protocol) or typed in manually (static addressing).
- The **DNS client** (resolver): built into the OS, it translates names such as `www.minesec.gov.cm` into IP addresses.

WARNING Static or dynamic?

A common mistake in school computer labs is to assign a static IP address that is already used by another machine or that lies inside the DHCP server’s pool. The result is an IP address conflict: both machines lose connectivity intermittently. Reserve static addresses for servers and printers, and keep them outside the DHCP range.

4.2 IP Addressing: IPv4

Intuition. To send a letter you need the recipient’s address; to send a packet you need the recipient’s **IP address**. IPv4, designed in the early 1980s, writes each address as 32 bits, presented as four decimal numbers separated by dots, e.g. `192.168.1.10`. Each number is one octet (0–255).

DEFINITION IPv4 address and subnet mask

An **IPv4 address** is a 32-bit identifier split by a **subnet mask** into a network part and a host part. With mask `255.255.255.0` (or prefix `/24`), the first 24 bits identify the network and the

last 8 bits identify hosts, giving $2^8 - 2 = 254$ usable host addresses (the all-zeros address names the network, the all-ones address is the broadcast).

Private versus public addresses. Because $2^{32} \approx 4.3$ billion addresses are not enough for the world's devices, three ranges are private (usable freely inside organisations, never routed on the public Internet): 10.0.0.0/8, 172.16.0.0/12 and 192.168.0.0/16. Your home router gives your phone a private address such as 192.168.1.10; on the Internet, all your devices appear under one public address owned by your ISP.

DEFINITION NAT

NAT (Network Address Translation) is a router mechanism that rewrites the source address and port of outgoing packets so that many devices with private addresses share a single public IP address. The router keeps a translation table (private IP + port $\leftrightarrow$ public IP + port) so that replies return to the correct internal device.

EXAMPLE NAT at work in a Yaoundé household

Three phones (192.168.1.10, .11, .12) browse the web through a router whose public address is 102.244.x.x (assigned by the ISP). The router replaces each private source address with the public one, using a different source port for each phone. When the web server replies, the router consults its table and delivers the page to the right phone. NAT also hides the internal structure of the network, a modest security side-effect.

METHOD Subnetting an IPv4 network (examinable procedure)

Goal: Divide a given network into N subnets.

1. Determine the number of bits b to borrow from the host part: smallest b such that $2^b \geq N$.
2. New prefix length = original prefix + b . New mask: set the borrowed bits to 1.
3. Number of hosts per subnet = $2^{\text{remaining host bits}} - 2$.
4. List subnets: increment the network address by the block size (value of the last borrowed bit).
5. For each subnet: network address (first), broadcast address (last), usable range (network+1 to broadcast-1).

WORKED EXAMPLE 4 Subnetting a school network

A school in Bamenda receives the network 192.168.10.0/24. It needs subnets for four departments (Administration, Staff room, Computer lab, Students' Wi-Fi). Propose a subnetting plan and give, for the lab subnet, the mask, the network address, the broadcast address and the usable range.

SOLUTION

We need at least 4 subnets, so we borrow $b = 2$ bits ($2^2 = 4$ subnets). The new prefix is $24 + 2 = 26$, i.e. mask 255.255.255.192 (binary 11111111.11111111.11111111.11000000). Each subnet has $2^6 = 64$ addresses, of which 62 are usable.

- Administration: 192.168.10.0/26, usable .1–.62, broadcast .63;
- Staff room: 192.168.10.64/26, usable .65–.126, broadcast .127;
- Computer lab: 192.168.10.128/26, usable .129–.190, broadcast .191;
- Students' Wi-Fi: 192.168.10.192/26, usable .193–.254, broadcast .255.

For the lab: mask 255.255.255.192, network 192.168.10.128, broadcast 192.168.10.191, usable hosts 192.168.10.129 to 192.168.10.190 — enough for 62 computers.

4.3 IPv6: The New Generation

Observation. With billions of phones, vehicles and sensors, IPv4 addresses ran out: the last blocks were distributed to regional registries in the 2010s. The long-term answer is **IPv6**.

DEFINITION IPv6 address

An **IPv6 address** is a 128-bit identifier written as eight groups of four hexadecimal digits separated by colons, e.g. 2001:0db8:0000:0000:0000:ff00:0042:8329. Leading zeros in a group may be omitted, and one run of consecutive all-zero groups may be compressed with ::, giving 2001:db8::ff00:42:8329.

PROPERTY Size of the IPv6 address space

IPv6 provides $2^{128} \approx 3.4 \times 10^{38}$ addresses — about 7.9×10^{28} times more than IPv4. Every device can therefore own a globally unique public address, which eliminates the need for NAT and restores true end-to-end connectivity. (Statement to know; no proof is examinable.)

IPv6 address types.

- Unicast (one interface): includes global unicast (routable on Internet, prefix 2000::/3), link-

local (valid only on the local link, prefix `fe80::/10`, auto-configured), and unique local (private, prefix `fc00::/7`).

- Multicast (one-to-many, prefix `ff00::/8`) replaces broadcast.
- Anycast (one-to-nearest): same address assigned to multiple interfaces; packet goes to the nearest.

Note: IPv6 has no broadcast address.

Transition mechanisms. Since the Internet cannot switch overnight, IPv4 and IPv6 coexist through:

- **Dual stack:** hosts and routers run both protocols simultaneously (most common).
- **Tunnelling:** IPv6 packets encapsulated inside IPv4 packets (e.g. 6to4, Teredo, ISATAP).
- **Translation:** NAT64/DNS64, converting between the two formats for IPv6-only clients accessing IPv4 servers.

IPv4	IPv6
Size: 32 bits (4 octets)	Size: 128 bits (16 octets)
Notation: dotted decimal 192.168.1.10	Notation: hex + colons 2001:db8::ff00:42:8329
Addresses: $2^{32} \approx 4.3 \times 10^9$	Addresses: $2^{128} \approx 3.4 \times 10^{38}$
Header: 13 fields, variable length (20–60 bytes)	Header: 8 fields, fixed 40 bytes (faster routing)
Broadcast: yes	Broadcast: no (multicast)
Config: DHCPv4 or manual	Config: SLAAC or DHCPv6
NAT: indispensable	NAT: not needed

Comparison of IPv4 and IPv6: address space, notation, header and transition.

METHOD Configuring a host: static IPv4 and DHCPv6

On Windows (static IPv4):

1. Open Settings → Network & Internet → Advanced network settings → Change adapter options, right-click the interface, choose Properties.
2. Select Internet Protocol Version 4 (TCP/IPv4) → Properties → Use the following IP address.
3. Enter the IP address (e.g. 192.168.10.130), mask (255.255.255.192), default gateway (the router, e.g. 192.168.10.129) and DNS servers; validate and test with ping and a browser.

On Linux (static IPv4, command line, non-persistent): `sudo ip addr add 192.168.10.130/26 dev eth0` then `sudo ip route add default via 192.168.10.129`, and write the DNS server in `/etc/resolv.conf` (or use `nmcli` / `Netplan` for persistence).

DHCPv6 client: on Windows, in Internet Protocol Version 6 (TCP/IPv6) properties, choose Obtain an IPv6 address automatically and Obtain DNS server address automatically. On Linux, enable DHCPv6 in NetworkManager (`nmcli con mod id "Wired connection 1" ipv6.method dhcp`) or run `sudo dhclient -6 eth0`. Verify with `ipconfig /all` (Windows) or `ip -6 addr` (Linux).

4.4 Key Protocols for Internet Access

Protocol	Role	Port / Layer
HTTP	Transfers web pages in plain text (no confidentiality)	80 / Application
HTTPS	HTTP encrypted with TLS/SSL: confidentiality, integrity, server authentication (padlock)	443 / Application
DNS	Translates domain names into IP addresses (and reverse)	53 / Application
DHCPv4 / DHCPv6	Automatically assigns IP address, mask, gateway, DNS to hosts	67/68 (v4), 546/547 (v6) / Application
PPPoE	PPP over Ethernet: authenticates a subscriber (login/password) on an ISP access link, common on ADSL/FTTH	— / Data Link
VPN	Creates an encrypted tunnel through the public Internet (e.g. IPsec, OpenVPN, WireGuard)	Various / Network/Application
TLS/SSL	Cryptographic layer securing HTTP, SMTP, IMAP, etc. (SSL is the obsolete ancestor of TLS)	Transport

DID YOU KNOW? The padlock and mobile money

When you pay a bill by mobile money (MTN MoMo, Orange Money) or check examination results on www.gceboard.cm in Cameroon, HTTPS/TLS encrypts the exchange so that an eavesdropper on the same Wi-Fi network cannot read your PIN or password. ANTIC, the national agency for ICT security, regularly reminds users to check for the padlock and the correct domain name before entering credentials.

4.5 Quality of Service (QoS)

Observation. During a video call, if someone in the house starts a large download, the voice becomes choppy. Web pages can wait half a second; a voice packet cannot. **QoS** mechanisms manage this.

DEFINITION Quality of Service

QoS is the set of techniques that guarantee measurable performance (bandwidth, delay, jitter, packet loss) to different traffic classes. Two main tools:

- **Traffic shaping** (or policing): smoothing and limiting the rate of traffic flows so that one user or application cannot saturate the link.
- **Prioritisation** (queueing): classifying packets into queues (e.g. using DSCP – Differentiated Services Code Point in the IP header) and serving delay-sensitive traffic (VoIP, video conferencing, gaming) before elastic traffic (downloads, e-mail, updates).

Routers and switches mark packets and apply queueing disciplines (e.g. HTB, FQ_CoDel). ISPs also use QoS to differentiate subscription offers (e.g. guaranteed minimum bandwidth).

4.6 Security Basics

DEFINITION Essential protection mechanisms

- A **firewall** (packet filter / stateful inspection / next-generation) filters incoming and outgoing traffic according to rules (by address, port, protocol, application, user). It may be a dedicated appliance, a router function, or host-based software.
- An **IDS** (Intrusion Detection System) monitors traffic and logs suspicious patterns; an **IPS** (Intrusion Prevention System) additionally blocks them in real time.
- **Secure Wi-Fi**: WPA3 (SAE – Simultaneous Authentication of Equals) encrypts the radio link with strong authentication and forward secrecy; WPA2 (AES-CCMP) remains acceptable. The obsolete WEP and WPA (TKIP) are trivially broken and must never be used.
- **Phishing awareness**: most intrusions start with a fraudulent e-mail or SMS imitating a bank, a ministry (MINESUP, MINFI) or a mobile-money operator, inviting the victim to a fake page. Always verify the address (HTTPS, correct spelling), never share a PIN or one-time code (OTP).
- **Updates**: keep OS, browser, router firmware and applications patched against known vulnerabilities.

WARNING Default passwords and open Wi-Fi

Routers are delivered with default administrator credentials (often `admin/admin` or printed on a label) that are publicly known. Keeping them, or running an open (unencrypted) Wi-Fi network, lets anyone nearby reconfigure the router, intercept traffic or use the connection for illegal acts — for which the subscriber may be held legally responsible. First actions on any new router: change the admin password, enable WPA2/WPA3 with a strong passphrase (12+ characters), disable WPS, and update the firmware.

4.7 The Cameroonian Regulatory Framework

In Cameroon, the electronic communications sector is regulated by the **ART** (Agence de Régulation des Télécommunications), established by Law No. 98/014 of 14 July 1998 and reorganised by Law No. 2010/013 of 21 December 2010. Its main missions relevant to the Internet are:

- **Licensing of ISPs:** any operator wishing to provide Internet access (CAMTEL, MTN Cameroon, Orange Cameroon, Nexttel, and others) must obtain a licence or authorisation from ART and comply with its conditions (coverage, quality of service, tariffs, interconnection).
- **Universal service obligations:** operators contribute to a Universal Service Access Fund intended to extend connectivity to rural and underserved areas, so that Internet access is not limited to Douala and Yaoundé.
- **Consumer protection and quality control:** ART monitors advertised versus actual quality of service (throughput, latency, availability) and can sanction operators for non-compliance.
- **Management of national resources:** the `.cm` country-code top-level domain (ccTLD) and numbering resources fall under national regulation; cybersecurity and critical infrastructure protection are supervised by **ANTIC** (Agence Nationale des Technologies de l'Information et de la Communication), created by Decree No. 2002/053 of 26 March 2002 and reinforced by Law No. 2010/012 on cybersecurity and cybercrime.

KEY POINTS Key points of Section 4

- Connecting a host requires hardware (NIC, modem/ONT, router, cabling, power backup) and software (TCP/IP stack, DHCP/DNS client).
- IPv4: 32 bits, dotted decimal; private ranges + NAT allow many devices to share one public address. Subnetting borrows host bits to create subnets (examinable calculation).
- IPv6: 128 bits, hexadecimal, 2^{128} addresses, no NAT, no broadcast (multicast instead); coexistence via dual stack, tunnelling, translation.
- Essential protocols: HTTP/HTTPS, DNS, DHCP, PPPoE, VPN, TLS/SSL.
- QoS (shaping, prioritisation/DSCP) protects real-time traffic; security rests on fire-

walls, IDS/IPS, WPA3, updates and user vigilance against phishing.

- In Cameroon, ART licenses ISPs and imposes universal service obligations; ANTIC oversees ICT security and the .cm domain.

EXERCISE 4 Addresses, protocols and security

1. A host has address 172.20.5.44 with mask 255.255.0.0. Is this address private or public? Justify using the RFC 1918 ranges.
2. Compress the IPv6 address 2001:0db8:0000:0000:0000:0000:0000:0001 following the standard rules.
3. Explain why NAT complicates hosting a public web server at home, and how IPv6 solves the problem without compromising security.
4. List four concrete measures to secure the Wi-Fi network of a cybercafé in Douala.
5. A small business has the network 192.168.50.0/24. It needs 6 subnets. Determine the new mask, the number of usable hosts per subnet, and the network/broadcast addresses of the 3rd subnet.

SOLUTION Exercise 1

1. 172.20.5.44 belongs to the range 172.16.0.0–172.31.255.255 (the 172.16.0.0/12 private block defined in RFC 1918), so it is a private address, not routable on the public Internet.
2. 2001:db8::1 (leading zeros removed in each group; the five consecutive all-zero groups compressed with a single ::).
3. With NAT, internal machines have private addresses unreachable from outside; hosting a server requires manual port forwarding (DNAT) on the router, which is fragile, limited to one server per port, and breaks end-to-end connectivity. IPv6 gives every device a global unicast address, so the server is directly reachable from the Internet; access is controlled by a stateful firewall on the router (allow inbound TCP/80,443 to that specific IPv6 address) — security is maintained without address translation.
4. Enable WPA2/WPA3 (AES) with a strong passphrase (changed periodically); change the router's default administrator password; update firmware regularly; disable WPS; enable client isolation (AP isolation) so clients cannot talk to each other; optionally use a captive portal with RADIUS authentication for accountability.

5. Need 6 subnets → borrow $b = 3$ bits ($2^3 = 8$ subnets). New prefix = $24 + 3 = 27$. Mask 255.255.255.224. Block size = 32 addresses. Usable hosts = $32 - 2 = 30$. Subnets: 0: .0, 1: .32, 2: .64, 3: .96, 4: .128, 5: .160, 6: .192, 7: .224. 3rd subnet (index 2 if 0-based, but usually "3rd" means index 2 or 3? Standard wording: 1st=.0, 2nd=.32, 3rd=.64). Let's assume 1st = .0/27. 3rd = .64/27. Network: 192.168.50.64, Broadcast: 192.168.50.95, Usable: .65–.94.

5 INTEGRATION ACTIVITY

5.1 Aims of the activity

This integration activity closes the chapter Reviewing the History of the Internet. It asks you to act as an ICT consultant: you will use everything learned about the **history of the Internet** (Lesson 36) and about **connectivity technologies and requirements** (Lesson 37) to solve a realistic Cameroonian problem. By the end of the activity, you should be able to:

- mobilise your knowledge of the **historical development** of the Internet (from ARPANET to the modern commercial Internet) to understand why certain technologies dominate today;
- compare **Internet connectivity technologies** (fibre optic, 4G mobile broadband, satellite, ADSL) and justify a choice in terms of bandwidth, latency, availability and cost;
- calculate the **bandwidth requirements** of a real institution from usage scenarios;
- design a simple **Local Area Network** (LAN) with an Internet gateway, including redundancy (backup link);
- propose an **IPv4/IPv6 addressing plan** and **basic security measures** (firewall, authentication, filtering);
- communicate a technical solution clearly in a short oral presentation, as an ICT professional would.

The activity is done in **groups of 4** and is assessed with a rubric covering technical justification (40%), bandwidth and cost analysis (30%), and clarity of the diagram and the 5-minute pitch (30%).

5.2 Situation

Connecting Collège Bilingue de Mandjou (East Region)

Collège Bilingue de Mandjou is a government secondary school located on the outskirts of Bertoua, capital of the East Region of Cameroon. The school has **300 students** and **20 teachers**. Thanks to a donation, it now owns a **computer laboratory of 30 PCs**, but none of them is connected to the Internet. The principal wants to use the lab for ICT practical lessons, online research, and simultaneous video lessons streamed from the Ministry's distance-education platform, especially for subjects where qualified teachers are scarce.

A feasibility visit reveals the following facts:

- A **CAMTEL fibre optic backbone** passes along the main road, about 800 m from the school. CAMTEL quotes a one-off installation fee of CFA 1 500 000 and a monthly subscription of CFA 150 000 for a dedicated 100 Mbps link.
- **MTN 4G** coverage in the area is good (measured average: 20 Mbps download, 5 Mbps upload, latency about 60 ms). A 4G router costs CFA 60 000; data bundles cost about CFA 10 000 for 50 GB.
- **Satellite Internet** (VSAT) is available everywhere but costs CFA 2 500 000 for equipment

plus CFA 200 000 per month, with a high latency of about 600 ms and a fair-use data cap.

- The school's total budget for the project (equipment + installation + one year of subscription) is **CFA 5 000 000**.
- The lab is a single hall; the administration block (5 offices) is 40 m away. Teachers should also get Wi-Fi access in the staff room.
- The principal insists: "If the main link fails during an examination session, we must still be able to go online."

WARNING Budget discipline

The CFA 5 000 000 must cover everything: the primary link installation, one year of subscription, the backup link, the router, switch, Wi-Fi access points, cabling and a small firewall. A solution that exceeds the budget is rejected, however brilliant it may be technically. Always draw up the full budget table before finalising your technical choices.

5.3 Tasks

Task 1 — Choosing the primary connectivity technology.

For each of the three options (CAMTEL fibre, MTN 4G, satellite VSAT), identify its strengths and weaknesses in terms of bandwidth, latency, reliability and cost. Then choose the primary link and the backup link, justifying your choice with at least three technical arguments. Recall from the history of the Internet why fibre has become the dominant fixed-access medium.

Task 2 — Calculating the required bandwidth.

The school wants up to **30 simultaneous video streams** (one per PC), each requiring 2 Mbps. Additionally, allow 10 Mbps for administration, messaging and background traffic.

1. Compute the total bandwidth needed.
2. Check whether your chosen primary link satisfies this need, with a safety margin.
3. Estimate the monthly data volume if the lab streams video 4 hours per day, 20 days per month (1 hour of a 2 Mbps stream $\approx$ 0.9 GB). Comment on whether a 4G-only solution would be viable.

Task 3 — Drafting the network diagram.

Draw a labelled diagram of the school network showing: the primary link, the backup link, a router/gateway, a firewall, a central switch in the lab, the 30 PCs, at least two Wi-Fi access points (lab and staff room) and the administration block. Indicate the transmission medium used between buildings and justify it.

Task 4 — Addressing and security plan.

1. Propose a private IPv4 addressing plan (network address, subnet mask, ranges for PCs, servers, Wi-Fi users) using CIDR notation, and explain the role of NAT and DHCP.
2. Explain briefly why the school should also be ready for IPv6.

- List at least four basic security measures (e.g. firewall rules, WPA2/WPA3 Wi-Fi authentication, content filtering, user accounts, updates) and state what threat each one addresses.

Task 5 — The 5-minute pitch.

Prepare a 5-minute group presentation for the principal and the Parent-Teacher Association: one slide on the chosen technology, one on the bandwidth calculation, one on the diagram, and one on the budget table. Every group member must speak.

5.4 Model answer

Task 1 — Choice of technology.

The comparison table summarises the three options. First-year costs are computed as: installation (or equipment) + 12 × monthly subscription.

Criterion	CAMTEL fibre	MTN 4G	Satellite VSAT
Bandwidth	100 Mbps dedicated	≈ 20 Mbps, shared	10–30 Mbps, capped
Latency	Very low (< 10 ms)	≈ 60 ms	≈ 600 ms
Reliability	High, stable	Variable (congestion, signal quality)	Affected by heavy rain
Data limit	Unlimited	Pay per bundle (50 GB)	Fair-use cap
Cost (year 1)	1.5 M + 12 × 150 k = 3.3 M FCFA	Router 60 k + bundles	2.5 M + 12 × 200 k = 4.9 M FCFA

Decision: the **primary link** is the **CAMTEL fibre**, for three main reasons: (1) it offers 100 Mbps dedicated, enough for the 30 simultaneous video streams; (2) its latency is very low, which is essential for interactive video lessons; (3) its data is unlimited and its total first-year cost (3.3 M FCFA) fits the budget. The **backup link** is an **MTN 4G router**: cheap, quick to activate, and sufficient for emergency text-based work (e-mail, result submission) if the fibre is cut. Satellite is rejected: it is the most expensive option (4.9 M FCFA in year one, almost the whole budget), has the highest latency (about 600 ms, poor for interactive video) and a data cap.

Historically, fibre dominates fixed access because, from the 1990s onwards, the explosive growth of Internet traffic — the Web, then audio and video streaming — demanded capacities that copper telephone lines (ADSL) could not offer, while the cost of optical fibre and optical equipment fell steadily. This is the same evolution that carried the Internet from the low-speed ARPANET links of the 1970s to today's broadband networks.

Task 2 — Bandwidth calculation.

The total bandwidth is the sum of the simultaneous needs:

$$\text{Video streams} = 30 \times 2 \text{ Mbps} = 60 \text{ Mbps}$$

$$\text{Other traffic} = 10 \text{ Mbps}$$

$$\text{Total required} = 60 + 10 = 70 \text{ Mbps}$$

The fibre link offers 100 Mbps. The safety margin is

$$\frac{100 - 70}{100} = 0.30 = 30\%$$

of spare capacity: the link is **acceptable**, even if usage grows slightly.

For the data volume, note first where the given figure comes from: a 2 Mbps stream transfers $2 \text{ Mbit/s} \div 8 = 0.25 \text{ MB/s}$, i.e. $0.25 \times 3600 = 900 \text{ MB} \approx 0.9 \text{ GB}$ per hour. Hence:


$$30 \text{ PCs} \times 0.9 \text{ GB/h} \times 4 \text{ h/day} \times 20 \text{ days} = 2160 \text{ GB} \approx 2.2 \text{ TB per month.}$$

On 4G at CFA 10 000 per 50 GB bundle, this would cost

$$\frac{2160}{50} \times 10\,000 \approx \text{CFA } 432\,000 \text{ per month,}$$

nearly three times the fibre subscription, for a slower, shared link with higher latency. A 4G-only solution is therefore not viable as the primary link — but it remains excellent as an occasional backup.

Task 3 — Network diagram.



Proposed network for Collège Bilingue de Mandjou. Both Internet links enter the router/firewall; the switch distributes the connection inside the lab. The inter-building link uses outdoor fibre to avoid interference and signal loss over 40 m.

The two links (fibre and 4G) both connect to the **router/gateway**, which can switch to the backup automatically if the fibre fails. Inside the lab, PCs are wired to the switch with Ethernet cable (cheaper and more stable than Wi-Fi for fixed machines). The link to the administration block, 40 m away, uses **outdoor optical fibre**: copper Ethernet is limited to about 100 m and is sensitive to electromagnetic interference and lightning, whereas fibre is immune and future-proof.

Task 4 — Addressing and security.

IPv4 plan. We use the private range 192.168.10.0/24 (mask 255.255.255.0, giving $2^8 - 2 = 254$ usable host addresses). The router performs **NAT** and a **DHCP** server assigns addresses automatically.

Element	Value	Remark
Network address	192.168.10.0/24	Mask 255.255.255.0, 254 usable hosts
Router / gateway	192.168.10.1	Static
Switch, APs, server	192.168.10.2 – 192.168.10.10	Static (reserved, outside DHCP pool)
Lab PCs (DHCP pool)	192.168.10.50 – 192.168.10.100	30 PCs + spares
Wi-Fi users (DHCP pool)	192.168.10.150 – 192.168.10.220	Staff and students

NAT (Network Address Translation) hides all the private addresses behind the single public address provided by CAMTEL, saving public addresses and adding a first layer of protection. **DHCP** (Dynamic Host Configuration Protocol) automates the configuration of each machine (address, mask, gateway, DNS) and avoids address conflicts and typing errors.

IPv6 readiness: the global pool of IPv4 addresses is exhausted, and ISPs (including Cameroonian operators) progressively deploy IPv6. The school should therefore buy dual-stack equipment (supporting IPv4 and IPv6) so that no replacement is needed when IPv6 becomes standard.

Security measures (at least four; each is matched to the threat it addresses):

1. **Firewall** on the router: blocks unsolicited incoming connections (threat: intrusions, port scans from the Internet).
2. **WPA2/WPA3** with a strong password on the Wi-Fi access points (threat: unauthorised access, bandwidth theft, eavesdropping).
3. **Content filtering** at the gateway (threat: inappropriate sites for students, phishing and malware sites).
4. **Individual user accounts** with passwords and limited rights on the PCs (threat: data deletion, installation of unwanted software, misuse).
5. **Regular updates and antivirus** on all PCs (threat: viruses, ransomware exploiting known flaws).

Task 5 — Budget summary for the pitch.

Item	Cost (FCFA)
Fibre installation + 1 year subscription (1.5 M + 12 × 150 000)	3 300 000
4G backup router + 1 year of bundles (60 000 + 12 × 10 000)	180 000
Router/firewall, switch, 2 access points, cabling	1 200 000
Contingency (about 5%)	250 000
Total	4 930 000

The project fits the CFA 5 000 000 budget (with CFA 70 000 to spare), delivers 100 Mbps with a 30% safety margin, includes the backup link demanded by the principal, and secures the network. The pitch concludes: “Fibre for performance, 4G for safety, security for trust.”

WARNING Common mistakes to avoid

- Forgetting the backup link, or the one-year subscription, in the budget.
- Confusing Mbps (megabits per second, used for links) with MB (megabytes, used for storage): 1 byte = 8 bits, so a 2 Mbps stream downloads only 0.25 MB per second.
- Assigning public addresses inside the LAN, omitting the subnet mask, or placing static addresses inside the DHCP pool (risk of conflicts).
- Drawing a diagram without labelling the transmission media, or without the firewall between the Internet links and the LAN.
- Choosing a technology on bandwidth alone, without checking latency, data caps and total cost over one year.

6 METHODS AND WORKED EXAMPLES

7 ORIGINS AND EARLY DEVELOPMENT OF THE INTERNET

7.1 Skill 1 — Placing Key Events in the History of the Internet (Timeline Questions)

DEFINITION Internet

The **Internet** is a global network of interconnected computer networks that communicate using a common set of protocols, the TCP/IP protocol suite, allowing users worldwide to share information and services.

DEFINITION World Wide Web

The **World Wide Web** (WWW or Web) is an information system of interlinked hypertext documents accessed via the Internet. It uses URLs to identify resources, HTTP to transfer them, and HTML to format them.

KEY POINTS Internet vs. Web — The Distinction That Earns Marks

- The Internet is the infrastructure (hardware + protocols): a network of networks born in 1969 (ARPANET) / 1983 (TCP/IP).
- The Web is a service that runs on top of the Internet, invented in 1989–1991 by Tim Berners-Lee at CERN.
- Never write “the Internet was invented in 1989” — that date belongs to the Web.

METHOD How to answer a GCE question on the history of the Internet

1. Identify the period asked. The GCE typically asks about one of four eras: the pre-Internet era (before 1969), the ARPANET era (1969–1982), the TCP/IP era (1983–1990), and the Web era (1990 to today).
2. Recall the anchor dates. Memorise the short list: 1969 (ARPANET first nodes), 1973–1974 (TCP designed by Cerf and Kahn), 1983 (ARPANET switches to TCP/IP, 1 January),

1989–1991 (Tim Berners-Lee invents the World Wide Web at CERN), 1993 (Mosaic, the first popular graphical browser).

3. Distinguish Internet from Web. The **Internet** is the global network of networks (hardware + protocols); the **World Wide Web** is a service (hypertext pages linked by URLs, transferred with HTTP) that runs on the Internet.
4. Structure the answer. For an essay question, use chronological order, give the date, the event, the key people or organisations, and the consequence of each step.
5. Link to Cameroon when asked. Mention that Cameroon connected progressively in the late 1990s, with CAMTEL as the historic operator and ANTIC created later to regulate and secure the digital space.

DID YOU KNOW? Cameroon's Early Internet

Cameroon's first Internet connection was established in the late 1990s via CAMTEL. The **ANTIC** (Agence Nationale des Technologies de l'Information et de la Communication) was created in 2002 to regulate, promote and secure ICT usage. Today, the country is served by submarine cables (WACS, SAT-3, ACE) landing at Kribi and Limbe, feeding the national fibre backbone operated by CAMTEL.

WORKED EXAMPLE 5 Timeline of the Internet

Statement (GCE A-Level style).

- (a) Define the term Internet. (2 marks)
- (b) Arrange the following events in chronological order and give the approximate year of each: invention of the World Wide Web; adoption of TCP/IP by ARPANET; creation of ARPANET; release of the Mosaic browser. (4 marks)
- (c) State two differences between the Internet and the World Wide Web. (4 marks)

SOLUTION

Detailed solution.

(a) Definition. The Internet is a global network of interconnected computer networks that communicate using a common set of protocols, the TCP/IP protocol suite, allowing users worldwide to share information and services. (1 mark for "network of networks", 1 mark for the common protocols / global communication.)

(b) Chronological order.

1. 1969 — Creation of ARPANET. Funded by the US Department of Defense (ARPA), the first nodes connected four American universities (UCLA, Stanford, UC Santa Barbara, Utah); it used packet switching.

2. 1983 — Adoption of TCP/IP by ARPANET. On 1 January 1983 ARPANET switched from the NCP protocol to TCP/IP, designed by Vinton Cerf and Robert Kahn; this date is often considered the “birth” of the modern Internet.
3. 1989–1991 — Invention of the World Wide Web. Tim Berners-Lee, at CERN in Geneva, proposed and built the Web: URLs, HTTP and HTML, plus the first browser/editor.
4. 1993 — Release of Mosaic. The first widely used graphical web browser, developed at NCSA, which made the Web accessible to the general public and triggered its explosive growth.

(c) Two differences.

Criterion	Internet	World Wide Web
Nature	Physical/logical infrastructure: a network of networks (cables, routers, protocols)	A service: a collection of interlinked hypertext documents accessed via browsers
Birth	1969 (ARPANET) / 1983 (TCP/IP)	1989–1991 (Tim Berners-Lee at CERN)
Key technologies	TCP/IP, routers, DNS	HTTP, HTML, URLs, browsers

Any two well-expressed differences earn the marks. The classic trap — saying the Web and the Internet are the same thing — must be avoided.

7.2 Skill 2 — Explaining Packet Switching and the Role of TCP/IP

DEFINITION Packet Switching

Packet switching is a data transmission technique in which a message is divided into small units called **packets**; each packet carries a header with source and destination addresses; packets travel independently through the network (possibly by different routes) and are reassembled in the correct order at the destination.

PROPERTY Advantages of Packet Switching over Circuit Switching

- Efficiency: transmission links are shared between many users (statistical multiplexing); bandwidth is not wasted during silent periods.
- Robustness: if a router or link fails, packets are rerouted along another path; the communication survives partial network failures (a design goal of ARPANET).
- No dedicated circuit: no need to establish and reserve an end-to-end line before

communicating, unlike the classical telephone network (PSTN).

DEFINITION TCP and IP

- **IP** (Internet Protocol): handles addressing and routing of packets. Every host has an IP address; routers forward packets based on the destination IP.
- **TCP** (Transmission Control Protocol): handles reliable delivery. It numbers packets, detects losses, requests retransmission, and reassembles them in order.

METHOD How to explain why the Internet works: packet switching + TCP/IP

1. Define packet splitting. A message is split into small blocks called packets; each packet carries a header with source and destination addresses.
2. Explain independent routing. Packets may travel by different routes through the network; routers read the destination address and forward each packet along the best available path.
3. Describe reassembly. At the destination, TCP checks that all packets arrived, requests retransmission of any lost or corrupted packet, and reorders them.
4. Give the advantages. Efficient use of links (sharing), robustness (rerouting), no dedicated line needed.
5. Use an analogy. Sending a book as several numbered parcels through a postal network: each parcel may take a different road, but the numbering lets the receiver rebuild the book.
6. Conclude. TCP/IP became the standard in 1983 and is the reason networks of different types can intercommunicate — hence “inter-net”.

WORKED EXAMPLE 6 Packet switching and TCP/IP

Statement.

- (a) What is packet switching? (2 marks)
- (b) Give two advantages of packet switching over circuit switching. (2 marks)
- (c) A school in Bamenda sends a 4 MB photo by email to a school in Buea. Explain, in four steps, what happens to the photo from the moment it leaves the sender’s computer until it is displayed on the receiver’s screen. (4 marks)

SOLUTION

Detailed solution.

(a) Packet switching is a data transmission technique in which a message is divided into small units called packets; each packet is labelled with the destination address, travels independently through the network (possibly by different routes), and all packets are re-assembled in the correct order at the destination.

(b) Advantages (any two).

- Efficiency: transmission links are shared between many users instead of being reserved for a single conversation, so bandwidth is not wasted.
- Robustness: if a router or link fails, packets are simply rerouted along another path; the communication survives partial network failures.
- No dedicated circuit: there is no need to establish and reserve an end-to-end line before communicating, unlike the classical telephone network.

(c) The four steps.

1. Segmentation: the sender's computer (TCP layer) splits the 4 MB photo into numbered packets and adds headers containing the destination IP address of the Buea computer.
2. Routing: each packet travels across the network (through the ISP's routers, e.g. via CAMTEL's backbone); routers read the destination address and forward each packet along the best available path — packets may take different routes.
3. Reassembly and checking: the receiver's TCP layer checks that all packets arrived, requests retransmission of any lost or corrupted packet, and reorders them.
4. Delivery: the complete photo is reconstructed and handed to the email application, which displays it on the screen.

8 EXPANSION, COMMERCIALISATION AND THE MODERN INTERNET

8.1 Skill 3 — Identifying and Comparing Internet Connectivity Technologies

KEY POINTS Main Families of Internet Access

- Wired: Dial-up (PSTN), ADSL, Fibre optic (FTTH), Cable (DOCSIS).

- Wireless: Mobile networks (2G/3G/4G/5G), Wi-Fi (local), Satellite (VSAT, LEO constellations), WiMAX.

METHOD How to choose or compare an Internet access technology

1. List the main families. Wired: dial-up (PSTN), ADSL, fibre optic (FTTH), cable. Wireless: mobile networks (2G/3G/4G/5G), Wi-Fi, satellite, WiMAX.
2. Compare with fixed criteria. Always compare using: maximum bandwidth (speed), coverage/availability, cost, mobility, and reliability (sensitivity to weather, distance, congestion).
3. Know the orders of magnitude. Dial-up: up to 56 kbit/s. ADSL: a few Mbit/s (degrades with distance from the exchange). Fibre: tens to hundreds of Mbit/s and more (symmetric possible). 4G: tens of Mbit/s in practice. Satellite: wide coverage but high latency (GEO) or lower latency (LEO).
4. Match technology to context. A rural village without a telephone line → mobile network or satellite; a bank in Douala needing high speed and stability → fibre; a home user → ADSL or 4G router.
5. In the exam, justify. A mark is earned only if the choice is justified with a criterion (speed, cost, coverage), not merely named.

WARNING Common Trap: Confusing Local and Access Technologies

Wi-Fi is a local wireless technology (last few metres). It is not an Internet access technology by itself — it connects your device to a router that uses ADSL, fibre, or 4G for the actual Internet link. Do not list “Wi-Fi” as an ISP access type in a comparison table.

WORKED EXAMPLE 7 Choosing a connectivity technology

Statement.

A cybercafé owner in Ngaoundéré asks for advice. The town has a CAMTEL telephone line and good 4G coverage from MTN and Orange, but no fibre yet.

(a) Copy and complete the comparison table below.

(4 marks)

Criterion	ADSL	4G (mobile)
Transmission medium		
Typical speed		
One advantage		
One limitation		

(b) Recommend one technology for the cybercafé and justify your choice with two arguments. (3 marks)

SOLUTION

Detailed solution.

(a) Completed table.

Criterion	ADSL	4G (mobile)
Transmission medium	Existing copper telephone line (PSTN)	Radio waves via a mobile base station (antenna)
Typical speed	A few Mbit/s (e.g. 1–20 Mbit/s), decreasing with distance from the exchange	Tens of Mbit/s in good coverage, shared between users of the cell
One advantage	Stable, dedicated bandwidth; flat-rate (unlimited) subscriptions common	Quick to deploy, no line works needed; usable on the move
One limitation	Requires a telephone line; speed drops far from the exchange	Speed varies with congestion and signal strength; data bundles can be expensive

(b) Recommendation. For a cybercafé, ADSL is recommended (with a 4G router as backup).

- Argument 1 — Cost model: a cybercafé consumes large volumes of data all day; ADSL flat-rate subscriptions allow unlimited usage, whereas 4G pay-per-gigabyte bundles would be very costly for many simultaneous customers.
- Argument 2 — Stability: ADSL offers a dedicated line whose bandwidth is not shared with neighbouring users, unlike a 4G cell whose speed collapses at peak hours when many subscribers are connected.

(A reasoned answer choosing 4G — e.g. if the telephone line is unreliable — can also earn marks provided two valid criteria are given.)

9 INTERNET CONNECTIVITY TECHNOLOGIES AND MEDIA

9.1 Skill 4 — Listing the Requirements for an Internet Connection

KEY POINTS Four Categories of Requirements

To connect a computer to the Internet, you need:

1. Hardware: computer/smartphone, network interface (Ethernet/Wi-Fi), modem/router (ADSL modem, 4G router, ONT for fibre), transmission medium (telephone line, fibre, SIM card).
2. An ISP subscription: contract with an **Internet Service Provider** (CAMTEL, MTN Cameroon, Orange Cameroon, etc.) supplying the link and an IP address.
3. Software: OS with TCP/IP stack configured, applications (web browser, email client).
4. Authentication: username/password or activated SIM with data plan.

METHOD How to answer “State the requirements for connecting a computer to the Internet”

1. Think in four categories. (i) Hardware, (ii) an access provider, (iii) software, (iv) a subscription/account.
2. Hardware. A computer (or smartphone), a **modem** or router (ADSL modem, 4G router, ONT for fibre) or a network interface (Ethernet/Wi-Fi card), and the transmission medium (telephone line, fibre, SIM card for mobile data).
3. Provider. A subscription with an **ISP** (Internet Service Provider) — e.g. CAMTEL, MTN Cameroon, Orange Cameroon — which supplies the connection and assigns an IP address.
4. Software. An operating system with the TCP/IP protocol stack configured, plus application software: a web browser (Chrome, Firefox), an email client, etc.
5. Account. Login credentials (username/password or an activated SIM with a data plan) to authenticate on the ISP's network.
6. Exam tip. If the question says “four requirements”, give exactly four, one per category, and name real examples to secure full marks.

WORKED EXAMPLE 8 Equipping a school computer room

Statement.

GBHS Kumba has just received 20 computers and wants to connect them to the Internet.

- (a) State four requirements the school must fulfil to obtain an Internet connection. (4 marks)
- (b) The school subscribes to an ISP. Define the acronym ISP and give two examples of ISPs operating in Cameroon. (3 marks)
- (c) Explain the role of the modem in the connection. (2 marks)

SOLUTION

Detailed solution.

(a) Four requirements.

1. Hardware: the computers, each with a network interface (Ethernet/Wi-Fi), plus a modem-router (e.g. an ADSL router) and the linking medium (telephone line or SIM-equipped 4G router).
2. An ISP subscription: a contract with an Internet Service Provider that supplies the access and an IP address.
3. Software: an operating system with TCP/IP configured and a web browser installed on each machine.
4. An account / authentication: the username and password (or activated data SIM) used to log on to the ISP's network.

(b) ISP means Internet Service Provider: a company that provides individuals and organisations with access to the Internet, usually for a subscription fee. Examples in Cameroon: CAMTEL (the historic fixed-line operator), MTN Cameroon and Orange Cameroon (mobile Internet), also Ringo or YooMee-type operators. (1 mark for the definition, 1 mark per example, up to 2.)

(c) Role of the modem. The modem (modulator-demodulator) converts the digital signals of the computer into signals suitable for the transmission line (modulation) when sending, and converts the incoming line signals back into digital data (demodulation) when receiving. It is the indispensable interface between the local equipment and the ISP's line.

9.2 Skill 5 — Distinguishing Dial-up, ADSL and Fibre; Understanding Bandwidth**DEFINITION** Bandwidth / Bit Rate

Bandwidth (or bit rate) is the maximum amount of data that can be transmitted per unit of time. Units: bit/s, kbit/s = 10^3 bit/s, Mbit/s = 10^6 bit/s, Gbit/s = 10^9 bit/s.

PROPERTY Generations of Fixed-Line Access

- Dial-up (PSTN): analogue modem, up to 56 kbit/s, occupies the voice band → blocks phone calls.
- ADSL (Asymmetric Digital Subscriber Line): digital, uses higher frequencies on the same copper pair, allows simultaneous voice + Internet (splitter/filter), asymmetric: downstream > upstream.
- Fibre (FTTH – Fibre To The Home): light pulses in glass fibre, very high speed (100 Mbit/s – 10 Gbit/s+), symmetric options, immune to electromagnetic interference, distance-insensitive.

METHOD How to handle questions on access speeds and media

1. Recall the units. Bit rate in bit/s: 1 kbit/s = 10^3 bit/s, 1 Mbit/s = 10^6 bit/s, 1 Gbit/s = 10^9 bit/s.
2. Know the generations. Dial-up (analogue, 56 kbit/s, blocks phone) → ADSL (digital, same copper, simultaneous phone+Internet, asymmetric) → Fibre (light, very high speed, symmetric possible).
3. Convert when needed. Download time $t = \frac{\text{file size in bits}}{\text{bit rate in bit/s}}$. Remember 1 byte = 8 bits.
4. Interpret “asymmetric”. In ADSL, the A means the downstream (download) rate exceeds the upstream (upload) rate — suitable for home users who download more than they send.

WORKED EXAMPLE 9 From dial-up to fibre — bandwidth calculation

Statement.

- (a) Explain why ADSL allows a subscriber to make a phone call and browse the Internet at the same time on the same line, unlike a dial-up connection. (2 marks)
- (b) What does the “A” in ADSL stand for, and what does it mean for the user? (2 marks)
- (c) A student downloads a 60 MB video file. Calculate the theoretical download time (i) on a 2 Mbit/s ADSL line and (ii) on a 100 Mbit/s fibre connection. (Take 1 MB = 8×10^6 bits.) (4 marks)

SOLUTION

Detailed solution.

- (a) Simultaneous use. A dial-up modem transmits data by occupying the same fre-

quency band as the voice, so the line is busy and calls are impossible during a connection. ADSL, on the contrary, splits the copper line into separate frequency bands (using a splitter/filter): one band for voice (0–4 kHz), others for data. Voice and data travel simultaneously without interfering.

(b) Meaning of “A”. “A” stands for Asymmetric. It means the download (downstream) bit rate is higher than the upload (upstream) bit rate. For the user, web pages, videos and downloads arrive fast, but sending large files (e.g. uploading a video) is noticeably slower.

(c) Download times.

File size in bits: $60 \text{ MB} \times 8 \times 10^6 = 4.8 \times 10^8 \text{ bits}$.

$$(i) \text{ ADSL: } t = \frac{4.8 \times 10^8 \text{ bits}}{2 \times 10^6 \text{ bit/s}} = 240 \text{ s} = 4 \text{ minutes.}$$

$$(ii) \text{ Fibre: } t = \frac{4.8 \times 10^8 \text{ bits}}{100 \times 10^6 \text{ bit/s}} = 4.8 \text{ s.}$$

Comment. The fibre link is 50 times faster here, which matches the ratio of the bit rates ($100/2 = 50$). In practice, times are slightly longer because of protocol overheads and congestion.

9.3 Skill 6 — Analysing Mobile and Satellite Connectivity (Cameroonian Context)

DEFINITION Mobile Network Generations

- 2G (GSM): voice + SMS, slow data (GPRS/EDGE ≈ 100 – 200 kbit/s).
- 3G (UMTS/HSPA): mobile Internet, few Mbit/s.
- 4G / LTE: fast mobile broadband, tens of Mbit/s ($100+$ Mbit/s peak).
- 5G (NR): very high speed (Gbit/s), low latency ($<10 \text{ ms}$), massive IoT.

DEFINITION Satellite Internet (VSAT)

A **VSAT** (Very Small Aperture Terminal) dish communicates with a geostationary satellite (GEO, $\approx 36\,000 \text{ km}$ altitude) or a low-earth-orbit (LEO) constellation. The satellite relays traffic to a ground station (teleport) connected to the Internet backbone.

KEY POINTS Mobile vs Satellite — Key Trade-offs

Criterion	Mobile (3G/4G/5G)	Satellite (VSAT)
Coverage	Good in towns, weak/absent in remote rural areas	Everywhere with sky view (including remote villages, sea)
Equipment cost	Low (modem/router + SIM, few thousand FCFA)	High (dish, transceiver, modem, installation)
Latency	Low (10–50 ms)	High for GEO (500–700 ms), lower for LEO (20–40 ms)
Weather sensitivity	Low	Rain fade (heavy rain degrades signal, especially Ku/Ka band)
Typical use	General public, smartphones, 4G routers	Backup links, remote sites, maritime, emergency

METHOD How to discuss wireless connectivity in an essay

1. Mobile networks. Describe the principle: the phone/router communicates by radio with the nearest base station (cell), which is linked to the operator's core network and then to the Internet. Generations: 2G (voice + SMS, slow data), 3G (mobile Internet), 4G/LTE (fast mobile broadband), 5G (very high speed, low latency).
2. Satellite. A dish (VSAT) communicates with a satellite that relays to a ground station connected to the Internet. Advantage: coverage everywhere, even remote villages. Limitations: high cost of equipment, latency (signal travels to orbit and back), sensitivity to heavy rain.
3. Structure an essay. Introduction (define connectivity) → body (one paragraph per technology with advantages + limitations) → conclusion (match to need, e.g. bridging the digital divide in rural Cameroon).
4. Use local colour accurately. MTN and Orange provide 3G/4G in most Cameroonian towns; CAMTEL operates the fibre backbone; ANTIC regulates and promotes secure use of ICTs.

WORKED EXAMPLE 10 Connecting a rural health centre

Statement.

A health centre in a village of the Far North Region has no telephone line, no fibre, and weak but usable 3G coverage. The Ministry of Health wants to connect it to the Internet so that patient records can be sent to the regional hospital.

(a) Name two technologies that could provide the connection. (2 marks)

- (b) For each technology, give one advantage and one limitation in this context. (4 marks)
 (c) Which technology do you recommend if the budget is very limited? Justify. (2 marks)

SOLUTION

Detailed solution.

(a) Two possible technologies. (i) The mobile network (3G/4G) via a data SIM and a 3G/4G router or modem; (ii) a satellite (VSAT) connection with a dish.

(b) Advantages and limitations.

Technology	Advantage	Limitation
Mobile 3G/4G	Cheap equipment (a simple modem/router and SIM); quick to install	Weak coverage means slow, unstable speeds; data bundles costly for heavy use
Satellite (VSAT)	Works everywhere, independent of local infrastructure; stable bandwidth	Expensive dish and subscription; noticeable latency (GEO); performance can degrade in heavy rain

(c) Recommendation. With a very limited budget, the 3G/4G mobile connection is recommended: the equipment costs only a few thousand FCFA (a modem and SIM from MTN or Orange), installation is immediate, and the weak signal can be improved with an external directional antenna. Satellite would give better quality but its equipment and subscription costs are far beyond a small budget.

10 TECHNICAL REQUIREMENTS, ADDRESSING AND SECURITY FOR INTERNET ACCESS

10.1 Skill 7 — Drawing and Interpreting a Connection Diagram

METHOD How to sketch the path from a home computer to a web server

1. Place the elements in order. Computer → (router/switch) → modem → transmission medium (copper line, fibre, radio) → ISP's network → Internet backbone → destination server.
2. Label each link with the technology used (Ethernet/Wi-Fi at home, ADSL/4G/fibre on the access link, fibre on the backbone).
3. Mark the roles. The modem adapts the signal; the router directs packets; the

ISP assigns the IP address and routes traffic; DNS servers translate names (e.g. `www.minesec.gov.cm`) into IP addresses.

4. In an exam, a clear, labelled diagram with these five or six elements earns full marks; arrows must show the direction of the data flow.


WORKED EXAMPLE 11 Diagram of a home connection

Statement.

Draw a labelled diagram showing how a student's laptop in Yaoundé, connected to a 4G router, reaches a web server hosted in Europe. Identify four elements of the diagram and state the role of each. (6 marks)

SOLUTION

Detailed solution.



Roles of four elements (any four).

1. 4G router/modem: adapts the laptop's data to the radio link (modulation) and shares the connection with local devices (Wi-Fi AP + router).
2. Base station (BTS): receives the radio signal from the router and forwards the traffic into the operator's core network via fibre/ microwave backhaul.
3. ISP core network: authenticates the subscriber (AAA), assigns an IP address (dynamic or static), routes packets towards the Internet; DNS servers translate the website name into an IP address.
4. Internet backbone: high-capacity fibre links (including submarine cables landing on the Cameroonian coast: WACS, SAT-3, ACE) that carry the traffic across continents to the destination server.

Marking guide: 2 marks for a correct, ordered, labelled diagram; 1 mark per correctly stated role (maximum 4).

EXPERIMENT Guided Activity: Trace Your Own Connection

Objective: Understand the path your data takes.

1. Open a terminal (Command Prompt on Windows, Terminal on Linux/macOS).
2. Run `tracert www.google.com` (Windows) or `traceroute www.google.com` (Linux/macOS).
3. Observe the list of hops (routers). The first hop is your router, the next few belong to your ISP (CAMTEL, MTN, Orange), then you see backbone routers, possibly international ones.
4. Note the round-trip times (RTT) in milliseconds. A jump in RTT often indicates a long-distance link (e.g., submarine cable).

Reflection: Why do some hops show “* * *”? (Answer: routers configured not to respond to ICMP TTL-exceeded messages for security.)

WARNING Security Basics for Internet Access

- Change default router passwords. Many attacks exploit unchanged admin credentials on home routers.
- Use WPA2/WPA3 encryption on Wi-Fi, never WEP or open networks.
- Keep firmware updated. ISPs (CAMTEL, MTN, Orange) push updates to CPE (Customer Premises Equipment); do not block them.
- Beware of public Wi-Fi. Use a VPN when accessing sensitive services (banking, school portal) on open hotspots.
- ANTIC’s role. In Cameroon, ANTIC operates the **CERT** (Computer Emergency Response Team) and promotes cybersecurity awareness; report incidents to cert@antic.cm.

EXERCISE 5 Chapter Review Questions

1. History. (a) State the year ARPANET adopted TCP/IP. (b) Who invented the World Wide Web and where? (c) Explain why the Internet and the Web are not the same thing.
2. Packet switching. A 10 MB file is sent over a packet-switched network. (a) What happens to the file at the sender’s TCP layer? (b) If packets arrive out of order, how does TCP handle it?

3. **Connectivity.** A small business in Douala needs a stable 50 Mbit/s symmetric connection for video conferencing and cloud backups. The building has a telephone line and is covered by 4G and fibre. Recommend the best technology and justify with three technical arguments.
4. **Requirements.** List the four categories of requirements for a standalone PC to access the Internet. For each, give a concrete example (hardware model, ISP name, software name, credential type).
5. **Bandwidth calculation.** A 250 MB file is downloaded on a 20 Mbit/s link. Calculate the theoretical minimum download time in seconds. (Use 1 MB = 8×10^6 bits.)
6. **Mobile vs Satellite.** Compare 4G and GEO satellite for a remote school in the East Region. Use a table with four criteria.
7. **Diagram.** Draw the connection path for a smartphone in Bafoussam using mobile data to access a server in South Africa. Label five elements and state the role of the base station and the ISP core network.

SOLUTION Chapter Review Questions

1. (a) 1983 (1 January). (b) Tim Berners-Lee at CERN, Geneva (1989–1991). (c) Internet = infrastructure (network of networks, TCP/IP); Web = service (HTTP/HTML/URLs) running on the Internet.
2. (a) TCP segments the file into numbered packets, adds headers with destination IP. (b) TCP buffers packets, reorders them by sequence number, requests retransmission of missing ones, then delivers the reassembled file to the application.
3. **Recommendation:** Fibre (FTTH). **Arguments:** (1) Symmetric 50+ Mbit/s easily available; (2) Dedicated, stable bandwidth not shared with neighbours; (3) Low latency (<5 ms) essential for video conferencing; (4) Unlimited data plans common, unlike 4G bundles.
4. (1) **Hardware:** PC + Ethernet card + fibre ONT (e.g., Huawei HG8245). (2) **ISP:** CAMTEL fibre subscription. (3) **Software:** Windows 11 (TCP/IP stack) + Firefox browser. (4) **Authentication:** PPPoE username/password provided by CAMTEL.
5. $\text{File} = 250 \times 8 \times 10^6 = 2 \times 10^9 \text{ bits}$. $\text{Rate} = 20 \times 10^6 \text{ bit/s}$. $t = 2 \times 10^9 / 20 \times 10^6 = 100 \text{ seconds}$.
6. **Table:** Coverage (4G: town only; Satellite: everywhere), Cost (4G: low; Satellite: high), Latency (4G: low; Satellite: high $\approx 600 \text{ ms}$), Weather (4G: robust; Satellite: rain fade).
7. **Diagram:** Smartphone $\rightarrow$ (radio) $\rightarrow$ BTS $\rightarrow$ (fibre/microwave) $\rightarrow$ ISP Core $\rightarrow$ (backbone/submarine cable) $\rightarrow$ Server (ZA). **Roles:** BTS = radio access + backhaul; ISP Core

= authentication, IP assignment, routing, DNS.

11 EXERCISES

11.1 I check my knowledge

EXERCISE 6 Multiple-choice questions

For each question, choose the single correct answer.

1. The protocol suite that replaced NCP on ARPANET on 1 January 1983 is:
 - (a) HTTP/HTTPS
 - (b) TCP/IP
 - (c) FTP/SMTP
 - (d) OSI/RM
2. The World Wide Web was invented in 1989–1991 by:
 - (a) Vint Cerf
 - (b) Tim Berners-Lee
 - (c) Leonard Kleinrock
 - (d) Paul Baran
3. Which technology typically offers the lowest latency for a home connection in Yaoundé?
 - (a) Satellite (GEO)
 - (b) Dial-up
 - (c) Fibre to the home (FTTH)
 - (d) 2G mobile data
4. NAT (Network Address Translation) is normally performed by:
 - (a) the switch
 - (b) the router
 - (c) the repeater
 - (d) the web browser

EXERCISE 7 True or false — justify

State whether each statement is true or false, and justify your answer in one or two sentences.

1. ARPANET used circuit switching to guarantee a dedicated path for every message.
2. A private IP address such as 192.168.1.10 can be routed directly on the public Internet.
3. Doubling bandwidth always halves the time needed to load a web page.
4. The landing of submarine cables such as ACE and 2Africa on the Cameroonian coast can improve both redundancy and affordability of Internet access.

EXERCISE 8 Definitions

Define each of the following terms in one or two clear sentences, giving an example where appropriate:

1. packet switching;
2. bandwidth;
3. latency;
4. ISP (Internet Service Provider);
5. IP address.

EXERCISE 9 Direct calculations

1. A file of 600 MB is downloaded over a link with an effective throughput of 40 Mbps. Calculate the download time in seconds, then in minutes (recall: 1 byte = 8 bits).
2. A video-conference application requires a round-trip latency below 150 ms. A GEO satellite link has a round-trip latency of about 600 ms. State, with justification, whether this link is suitable.

11.2 I practise**EXERCISE 10 Sizing a school connection**

A secondary school in Bafoussam plans to stream 5 concurrent 720p video lessons, each

requiring 3 Mbps.

1. Calculate the total bandwidth needed for the streams.
2. Add 20 % overhead for protocol traffic and other uses, and determine the minimum symmetric fibre plan (in Mbps) the school should subscribe to.
3. Explain why a symmetric plan is recommended if teachers must also upload recorded lessons.

EXERCISE 11 Labelling a home network

Draw (or copy from your course) the schematic of a typical home network: the ISP line enters the house and serves a desktop PC by cable, plus a laptop and two smartphones wirelessly.

1. Label the following devices: modem, router, switch, Wi-Fi access point.
2. Indicate clearly where NAT occurs and justify your answer.
3. State one advantage of connecting the desktop PC by cable rather than Wi-Fi.

EXERCISE 12 Comparing connectivity technologies

Copy and complete the following comparison table for a cybercafé owner in Bamenda choosing an Internet connection. Use the terms low / medium / high for cost and latency, and give a typical bandwidth range.

Technology	Typical bandwidth	Latency	Installation cost
ADSL			
4G mobile			
FTTH (fibre)			
VSAT satellite			

Then recommend one technology for the cybercafé, justifying your choice with two arguments.

EXERCISE 13 Bandwidth versus latency

1. Explain, in your own words, the difference between bandwidth and latency, using the analogy of a road between Douala and Yaoundé.

2. Give one real-world example of an application where a connection with high bandwidth but high latency still degrades performance, and explain why.
3. Name one application for which high latency matters little but high bandwidth is essential.

11.3 I prepare for the GCE

EXERCISE 14 Essay: submarine cables and Cameroon

(20 marks)

“The landing of submarine fibre-optic cables such as ACE and 2Africa on the Cameroonian coast transforms the national Internet landscape.” Discuss this statement. Your essay should:

1. briefly recall the historical development of the Internet from ARPANET to the commercial Web; (4 marks)
2. explain the role of submarine cables in international connectivity and in redundancy (what happens when a country depends on a single cable?); (6 marks)
3. analyse the expected effects on affordability, quality of service and the digital economy in Cameroon (e-government, mobile money, online education); (6 marks)
4. identify two remaining obstacles that prevent all Cameroonians from benefiting fully, and propose a solution for each. (4 marks)

EXERCISE 15 Case study: a business in Douala

(15 marks)

A small import-export business in Bonabéri, Douala, uses an ADSL line to connect its 8 employees. The accountant complains that the VPN connection to the bank’s server drops several times per day, especially when it rains, and that large file uploads are very slow.

1. State three structured troubleshooting steps the technician should perform first, and explain what each step can reveal. (6 marks)
2. Give two technical reasons why ADSL can suffer from instability and low upload speed. (4 marks)
3. Propose a long-term upgrade path (technology, equipment, and a redundancy solution), justifying each choice. (5 marks)

EXERCISE 16 Structured problem: connecting a new school**(20 marks)**

A new Government High School in a rural divisional headquarters must be connected to the Internet for its computer laboratory of 40 machines. The town has 4G mobile coverage but no fibre; the national electricity supply is unstable.

1. List the hardware and software requirements needed to connect the laboratory and share the connection among the 40 machines. (5 marks)
2. Compare two candidate access technologies (4G router vs. VSAT satellite) in terms of bandwidth, latency, cost and reliability, and make a justified recommendation. (6 marks)
3. Explain how IP addressing should be organised inside the laboratory (private addresses, DHCP, NAT). (5 marks)
4. Propose two security measures to protect students and the school's data, and one measure to cope with power cuts. (4 marks)

12 SOLUTIONS TO THE EXERCISES

SOLUTION Exercise 1 — Multiple-choice questions

1. Answer: b) TCP/IP. On 1 January 1983, ARPANET switched from the NCP protocol to the TCP/IP suite, an event often called the “flag day”. This date is considered the birth of the modern Internet. HTTP (a) is a Web application protocol (1991), FTP/SMTP (c) are application protocols that run on top of TCP/IP, and OSI/RM (d) is a theoretical reference model, never deployed on ARPANET.
2. Answer: b) Tim Berners-Lee. Working at CERN, he proposed the Web in 1989 and implemented HTML, HTTP and the first browser/server around 1990–1991. Vint Cerf co-designed TCP/IP, Kleinrock developed the theory of packet switching, and Baran invented the concept of distributed packet-switched networks.
3. Answer: c) Fibre to the home (FTTH). Light propagates in fibre with very low delay (typically a few ms to the ISP). GEO satellite (a) imposes about 500–600 ms round trip, dial-up (b) has high latency and tiny bandwidth, and 2G (d) is slow with high latency.
4. Answer: b) the router. NAT translates private addresses (e.g. 192.168.1.x) into the single public address assigned by the ISP; this is a Layer-3 function performed by the router (often integrated in the ISP box). A switch works at Layer 2, a repeater at Layer 1, and the browser is application software.

SOLUTION Exercise 2 — True or false

1. False. ARPANET was precisely the first large network to use **packet switching**: messages are cut into packets routed independently, with no dedicated path. Circuit switching (like the old telephone network) was exactly what Baran and Kleinrock wanted to avoid.
2. False. Addresses in the private ranges (10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16) are not routable on the public Internet; Internet routers drop them. They reach the Internet only through NAT on the router, which substitutes a public address.
3. False. Doubling bandwidth halves the transfer time of the data volume, but the total loading time also includes latency, DNS resolution, server response time and processing, which do not depend on bandwidth. Hence the gain is real but never exactly a factor of two.
4. True. Each additional submarine cable provides an alternative international route:

if one cable is cut, traffic can be rerouted (redundancy), and increased competition/capacity between cable systems tends to lower wholesale bandwidth prices, which can translate into cheaper retail access.

SOLUTION Exercise 3 — Definitions

1. Packet switching: a data-transmission technique in which a message is divided into small blocks called **packets**, each carrying addressing information and routed independently through the network, then reassembled at the destination. Example: an e-mail sent from Douala to Bamenda is split into packets that may follow different paths.
2. Bandwidth: the maximum quantity of data a link can carry per unit of time, measured in bits per second (bps, Mbps, Gbps). Example: a 20 Mbps FTTH subscription.
3. Latency: the time delay for a data unit to travel from source to destination (often measured as round-trip time), expressed in milliseconds. Example: about 600 ms round trip on a GEO satellite link.
4. ISP (Internet Service Provider): a company that sells Internet access to customers and routes their traffic to the global Internet. Examples in Cameroon: MTN Cameroon, Orange Cameroon, CAMTEL, Nexttel.
5. IP address: a unique numerical identifier assigned to a device on an IP network, used to address and route packets to it. Example: 192.168.1.10 (IPv4 private address).

SOLUTION Exercise 4 — Direct calculations

1. Convert the file size to bits:

$$600 \text{ MB} = 600 \times 8 = 4800 \text{ Mb (megabits).}$$

The download time is

$$t = \frac{4800 \text{ Mb}}{40 \text{ Mbps}} = 120 \text{ s} = \frac{120}{60} = 2 \text{ min.}$$

2. The GEO link is not suitable. Its round-trip latency (about 600 ms) is four times the maximum tolerated (150 ms): $600 > 150$. Even with abundant bandwidth, the delay would cause awkward pauses and echoes in the conversation, making interactive video-conferencing unusable. A terrestrial link (fibre, 4G) with latency below 150 ms must be used.

SOLUTION Exercise 5 — Sizing a school connection

1. Total bandwidth for the streams:

$$5 \times 3 \text{ Mbps} = 15 \text{ Mbps.}$$

2. Adding 20 % overhead:


$$15 \times 1.20 = 18 \text{ Mbps.}$$

The school should therefore subscribe to a symmetric fibre plan of at least 18 Mbps; in practice the next commercial tier, e.g. 20 Mbps symmetric, would be chosen.

3. Streaming only consumes downstream bandwidth, but uploading recorded lessons consumes upstream bandwidth. An asymmetric plan (e.g. ADSL) typically offers an upload rate 5 to 10 times lower than the download rate, so publishing videos would be painfully slow and could saturate the uplink, degrading the whole connection (acknowledgements of downloads also use the uplink). A symmetric plan guarantees the same capacity in both directions, so teachers can upload lessons while students stream without congestion.

SOLUTION Exercise 6 — Labelling a home network

1. Schematic of the typical home network:



In most real installations the modem, router, switch and access point are combined in a single box supplied by the ISP.

2. NAT occurs in the router. The router is the boundary between the private LAN (addresses such as 192.168.1.x) and the public Internet: it translates each private source

address into its own public address (with port numbers to distinguish the devices) before forwarding packets to the ISP, and performs the reverse translation for replies.

3. Advantage of the cable for the desktop PC: a more stable and faster connection, immune to radio interference, walls and distance, with lower latency than Wi-Fi (also slightly more secure against eavesdropping).

SOLUTION Exercise 7 — Comparing connectivity technologies

Completed table (typical values, to be adapted to local offers):

Technology	Typical bandwidth	Latency	Installation cost
ADSL	1–20 Mbps	low to medium	low
4G mobile	5–50 Mbps	medium	low
FTTH (fibre)	20 Mbps–1 Gbps	low	medium to high
VSAT satellite	2–30 Mbps	high (500–700 ms)	high

Recommendation: FTTH (fibre) if it is available at the cybercafé's location in Bamenda, for two reasons:

1. Quality of service: fibre offers the highest bandwidth and the lowest latency, so many customers can browse, stream and make video calls simultaneously without congestion — essential for a business whose revenue depends on connection quality.
2. Reliability and cost per Mbps: once installed, fibre is stable (unaffected by weather, unlike satellite or radio) and its cost per Mbps is the lowest, which improves the profitability of the cybercafé.

(If fibre is not yet available in the neighbourhood, a 4G router with a generous data plan is the acceptable fallback; VSAT is the last resort because of its high latency and cost.)

SOLUTION Exercise 8 — Bandwidth versus latency

1. Imagine the Douala–Yaoundé road. Bandwidth is the number of lanes: the more lanes, the more vehicles (data) can travel at the same time. Latency is the time a single vehicle needs to go from Douala to Yaoundé: even a six-lane motorway does not reduce the travel time of one car. Similarly, a link can carry huge volumes per second (high bandwidth) while each individual packet still takes a long time to arrive (high latency).
2. Example: an online video-conference or VoIP call over a GEO satellite link with high bandwidth but high latency (≈ 600 ms round trip). The link can carry the video stream easily, but every reply arrives with a noticeable delay, so speakers constantly talk over

each other: interactivity is destroyed because latency, not bandwidth, governs the responsiveness of the conversation.

3. Downloading or streaming a large video file (e.g. watching a recorded film): the user only cares that the whole file arrives quickly, so high bandwidth is essential, while a latency of a few hundred milliseconds at the start is barely noticeable.

SOLUTION Exercise 9 — Essay: submarine cables and Cameroon (20 marks)

Indicative mark scheme and expected content.

(a) Historical development (4 marks). Award 1 mark per correct idea, up to 4:

- 1960s: packet switching theorised (Baran, Kleinrock); 1969: ARPANET connects its first nodes (universities/research in the USA).
- 1974: TCP/IP designed by Cerf and Kahn; 1 January 1983: ARPANET adopts TCP/IP — birth of the Internet; interconnection of networks (NSFNET, etc.).
- 1989–1991: Tim Berners-Lee invents the Web (HTML, HTTP, URL) at CERN; 1993: Mosaic browser popularises it.
- 1990s: commercialisation, ISPs, browsers, search engines; 2000s–today: broadband, mobile Internet, social networks, cloud.

(b) Role of submarine cables (6 marks). Expected: submarine fibre-optic cables carry the overwhelming majority of intercontinental Internet traffic (1–2 marks); they land at coastal stations (e.g. near Douala/Limbé/Kribi) and connect the national backbone to the world (1 mark); each additional cable adds capacity and redundancy (1 mark). A country depending on a single cable suffers total or severe international disconnection when that cable is cut (ship anchors, fishing, earthquakes), as has happened to several African countries (2 marks); multiple cables allow automatic rerouting and continuity of service (1 mark).

(c) Expected effects for Cameroon (6 marks). Any three well-developed effects, 2 marks each:

- Affordability: more capacity and competition lower wholesale prices, which can reduce retail subscription and data costs.
- Quality of service: higher speeds, lower congestion, better streaming and video-conferencing.
- Digital economy: growth of e-government services, mobile money (MTN MoMo, Orange Money), online education, e-commerce, outsourcing and start-ups; attraction of data centres and investment.

(d) Two remaining obstacles + solutions (4 marks). 1 mark per obstacle and 1 per coherent solution, e.g.:

- Last-mile gap: cables land on the coast but fibre does not reach rural areas → invest in the national fibre backbone, mobile broadband (4G/5G) and community access points.
- Cost of devices and data / digital illiteracy: many households cannot afford smart-phones or lack skills → subsidise devices, reduce taxes on ICT equipment, digital literacy programmes in schools.
- (Also acceptable: unstable electricity supply → solar-powered infrastructure; weak competition → regulatory enforcement.)

Examiner's expectations: structured essay (introduction, development, conclusion), correct technical vocabulary, Cameroonian examples, and balanced discussion (benefits and limits), not a mere list.

SOLUTION Exercise 10 — Case study: a business in Douala (15 marks)

(a) Three structured troubleshooting steps (6 marks — 2 each: step + what it reveals).

1. Check the physical layer: inspect cables, connectors, the ADSL splitter/filter and the modem's synchronisation LED; test with another modem if possible. Reveals: corroded or loose connectors, water ingress in outdoor joints (consistent with drops when it rains), or a faulty modem.
2. Test the line quality: read the modem's diagnostic values (SNR — signal-to-noise ratio, line attenuation, error counts) and ask the ISP for a line test. Reveals: a degraded copper pair, excessive distance from the exchange, or interference — typical causes of instability.
3. Isolate the internal network: connect a single PC directly to the modem, run ping/traceroute to the bank's server and monitor packet loss over time. Reveals: whether the problem is inside the company (switch, cabling, overloaded Wi-Fi, mis-configured VPN client) or on the ISP side.

(b) Two technical reasons for ADSL instability and low upload speed (4 marks — 2 each).

- Copper sensitivity: ADSL uses the old telephone copper pair, whose signal attenuates with distance from the exchange and is vulnerable to moisture, corrosion and electromagnetic interference — hence synchronisation losses, especially when it rains.
- Asymmetry by design: the "A" in ADSL means most of the frequency band is allocated to the downstream; the upstream band is narrow, so upload throughput is typically 5–10 times lower than download, making large file uploads very slow.

(c) Long-term upgrade path (5 marks).

- Technology: migrate to FTTH fibre (or a 4G/5G business router if fibre is unavailable in Bonabéri) — symmetric bandwidth, low latency, immunity to weather on the access

line (2 marks).

- **Equipment:** a business-grade router/firewall with VPN support (hardware VPN acceleration), a manageable switch, and a UPS for the modem/router (1 mark).
- **Redundancy:** keep a 4G failover connection as backup: the router switches automatically to 4G when the fibre fails, guaranteeing continuity of the VPN to the bank (2 marks).

Examiner's expectations: methodical reasoning (physical → line → network), correct use of terms (SNR, attenuation, asymmetry, failover), and realistic proposals for the Douala context.

SOLUTION Exercise 11 — Structured problem: connecting a new school (20 marks)

(a) Hardware and software requirements (5 marks — 1 per item, any five).

- An Internet access device: 4G router (or VSAT terminal) with an active ISP subscription/SIM.
- A switch (48 ports or two 24-port switches) and Ethernet cabling to connect the 40 machines.
- Optionally one or more Wi-Fi access points for mobile devices.
- A router/firewall function (often integrated in the 4G router) to share the connection (NAT) and filter content.
- A DHCP service (usually on the router) to distribute IP addresses automatically.
- Software: operating systems updated, antivirus, a web browser, and optionally a proxy/filtering software; a server is optional.
- Electrical protection: UPS or inverter (may be credited here or in (d)).

(b) 4G router vs VSAT (6 marks).

Criterion	4G router	VSAT satellite
Bandwidth	5–50 Mbps, shared with other users	2–30 Mbps, more stable per contract
Latency	medium (30–80 ms), fine for Web/video	high (500–700 ms), poor for inter-activity
Cost	low equipment, affordable data plans	expensive dish + installation + subscription
Reliability	depends on coverage/congestion; weather-sensitive	works anywhere; degraded by heavy rain

Recommendation (2 marks): choose the 4G router, because the town already has 4G coverage: it is far cheaper to install and operate, offers lower latency suitable for educational browsing and video, and requires no specialised maintenance. VSAT would only be justified if 4G coverage were absent or unusable.

(c) IP addressing organisation (5 marks).


- Use a private address range, e.g. 192.168.1.0/24, which supports up to 254 hosts — more than enough for 40 machines (1 mark).
- Configure the router as a DHCP server distributing addresses (e.g. 192.168.1.100–192.168.1.200), the default gateway (192.168.1.1) and DNS servers automatically, avoiding manual configuration errors (2 marks).
- The router performs NAT: all 40 private addresses are translated to the single public address provided by the ISP, so one subscription serves the whole laboratory (2 marks).

(d) Security and power measures (4 marks).

- Security (any two, 1 mark each): a firewall with content filtering to block inappropriate sites and protect students; antivirus software on all machines with regular updates; strong passwords/WPA2 or WPA3 on the Wi-Fi; user accounts with limited rights for students.
- Power (2 marks): install a UPS/inverter with batteries (possibly solar-backed) to keep the router, switch and machines running during cuts and to protect equipment from surges.

Examiner's expectations: a complete, coherent and cost-aware solution; correct use of the terms DHCP, NAT, private addressing; and justification of each choice in the rural Cameroonian context (coverage, budget, electricity).

13 SUMMARY SHEET



Mind map of Chapter ICT17: from ARPANET to today's connection technologies.

FICHE BILAN L'essentiel à connaître pour l'examen

Key definitions.

- **Internet**: a global network of interconnected networks communicating through common protocols (TCP/IP); a network of networks.
- **ARPANET**: the ancestor of the Internet, launched in 1969 by ARPA (US Department of Defense), linking four university computers.
- **Packet switching**: data is split into small addressed packets routed independently

and reassembled at destination (concept by Baran and Davies).

- **TCP/IP**: the protocol suite adopted on 1 January 1983; **IP** addresses and routes packets, **TCP** guarantees ordered, reliable delivery.
- **World Wide Web**: system of hypertext documents invented by Tim Berners-Lee at CERN (1989–1991), based on **HTML**, **URL** and **HTTP**. The Web is a service of the Internet, not the Internet itself.
- **ISP** (Internet Service Provider): company that sells Internet access (e.g. CAMTEL, MTN Cameroon, Orange, Nexttel).
- **Modem**: device that modulates/demodulates signals between the user's equipment and the ISP's line.
- **Bandwidth**: maximum data rate of a link, measured in bits per second (kbit/s, Mbit/s, Gbit/s).

Key dates and facts to memorise.

- 1969: ARPANET connects UCLA, Stanford, UCSB and Utah; first message "LO" (crash during "LOGIN").
- 1971: Ray Tomlinson sends the first networked e-mail and introduces the @ symbol.
- 1974: Vinton Cerf and Bob Kahn publish the TCP design; 1983: ARPANET switches to TCP/IP; DNS follows in 1984.
- 1989–1991: Berners-Lee creates the Web; 1993: Mosaic, the first popular graphical browser; 1995: commercial Internet boom.
- 2000s: broadband (ADSL, fibre), Web 2.0, social networks; 2010s: mobile Internet (3G/4G) dominates, including in Cameroon.

Connectivity technologies (know advantages/limits).

Technology	Medium	Remark
Dial-up	Telephone line	Slow ($\approx$ 56 kbit/s), obsolete
ADSL	Telephone copper pair	Broadband, asymmetric speeds
Fibre optic	Glass fibre	Very high speed, low latency
Mobile 3G/4G/5G	Radio waves	Dominant access mode in Cameroon
Satellite	Radio via satellite	Covers remote rural areas
Wi-Fi / WiMAX	Local radio	Wireless local/metropolitan access

Requirements for an Internet connection (method).

1. Subscribe to an **ISP** and obtain an account/SIM.

2. Hardware: computer or smartphone, **NIC** or wireless adapter, **modem**/router.
3. Software: operating system with TCP/IP stack, **browser** (Chrome, Firefox).
4. Configuration: obtain an **IP address** (static or via DHCP), DNS server addresses.
5. Test the connection (open a web page, use ping).

Common mistakes to avoid.

- Confusing the **Internet** (infrastructure, 1969/1983) with the **Web** (service, 1989).
- Saying Berners-Lee “invented the Internet” — he invented the Web.
- Confusing bandwidth (capacity) with actual speed; forgetting units (bit/s, not byte/s).
- Forgetting that a modem alone is not enough: an ISP subscription and IP configuration are required.

GCE tips.

- Learn the timeline as a chain: ARPANET → TCP/IP → DNS → Web → broad-band/mobile.
- In essays, define terms first, then compare technologies in a table (speed, cost, availability in Cameroon).
- Cite local examples (CAMTEL fibre, MTN/Orange 4G, mobile money over the Internet) to earn application marks.



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+