

PURE MATHEMATICS WITH MECHANICS • UPPER SIXTH

UPPER SIXTH — PURE MATHEMATICS WITH MECHANICS

CHAPTER 12

MOTION IN A CIRCLE WITH UNIFORM SPEED

SUGGESTED TIME: 13 PERIODS

IN THIS CHAPTER

This chapter studies the kinematics and dynamics of uniform circular motion: angular quantities, centripetal acceleration and force, and the link between linear and angular speed. It then applies these ideas to the conical pendulum, deriving its period formula and solving GCE-style problems.

- By the end of this chapter I can define angular displacement, angular speed and period, and use their units correctly (rad, rad/s, s, Hz).
- By the end of this chapter I can explain why a body in uniform circular motion is accelerating even though its speed is constant.
- By the end of this chapter I can calculate centripetal acceleration and centripetal force using $a = v^2/r = r\omega^2$ and $F = mv^2/r = mr\omega^2$.
- By the end of this chapter I can convert fluently between linear speed and angular speed using $v = r\omega$ in both directions.
- By the end of this chapter I can solve applied problems on vehicles in curves, rotating wheels, satellites and fairground rides.
- By the end of this chapter I can describe a conical pendulum and identify all forces acting on the bob.



DOWNLOAD ON- BUCH

Free • Google Play
AI tutor, past papers,
results



GO ONBUCH+

All signed courses, unlimited AI
tutor, PDF sheets — OnBuch+
tab in the app

THIS SIGNED COURSE CONTAINS

COURSE

complete, illustrated,
step by step

METHODS

and worked examples

EXERCISES

exam style + solutions

SUMMARY SHEET

the essentials to
remember



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+

CONTENTS

- | | |
|---|--|
| 1. Circular Motion and Angular Quantities | Derivation and Applications |
| 2. Centripetal Acceleration and Centripetal Force | 7. Angular and Linear Speed in the Conical Pendulum; Synthesis and Exam Practice |
| 3. Linear Speed, Angular Speed and Their Relationship | 8. Integration activity |
| 4. Applications of Linear and Angular Speed | 9. Methods and worked examples |
| 5. The Conical Pendulum: Concept and Forces | 10. Exercises |
| 6. Period of the Conical Pendulum: | 11. Solutions to the exercises |
| 12. Summary sheet | |

CHAPTER OBJECTIVES

- By the end of this chapter I can define angular displacement, angular speed and period, and use their units correctly (rad, rad/s, s, Hz).
- By the end of this chapter I can explain why a body in uniform circular motion is accelerating even though its speed is constant.
- By the end of this chapter I can calculate centripetal acceleration and centripetal force using $a = v^2/r = r\omega^2$ and $F = mv^2/r = mr\omega^2$.
- By the end of this chapter I can convert fluently between linear speed and angular speed using $v = r\omega$ in both directions.
- By the end of this chapter I can solve applied problems on vehicles in curves, rotating wheels, satellites and fairground rides.
- By the end of this chapter I can describe a conical pendulum and identify all forces acting on the bob.
- By the end of this chapter I can derive the period formula $T = 2\pi\sqrt{h/g}$ for a conical pendulum from Newton's second law.
- By the end of this chapter I can relate angular and linear speed for a conical pendulum and use $\tan \theta = v^2/(rg) = r\omega^2/g$.
- By the end of this chapter I can solve GCE Advanced Level problems on circular motion and conical pendulums in a clear, structured way.

PREREQUISITES

- Newton's laws of motion and resolution of forces into components (Lower Sixth Mechanics).
- Kinematics: speed, velocity, acceleration as rates of change (Lower Sixth).
- Radian measure and the relation arc length $s = r\theta$ (Pure Mathematics, Lower Sixth).
- Trigonometric ratios in right-angled triangles ($\sin$, $\cos$, $\tan$) and Pythagoras' theorem.
- Algebraic manipulation: rearranging formulae, solving simultaneous equations.

1 CIRCULAR MOTION AND ANGULAR QUANTITIES

At the busy Carrefour Warda roundabout in Yaoundé, a moto-taxi rider leans into the curve while a passenger clings on, feeling pushed outward. Why does the rider not fall, and why does the load on the carrier seem to fly off if the turn is taken too fast? On the playground of Lycée de Nkolbisson, a child swings a stone tied to a string in a horizontal circle above her head: the string makes a constant angle with the vertical, and the stone spins faster when the string is shortened. These everyday Cameroonian scenes all obey the same mathematics: **motion in a circle with uniform speed**. This chapter gives you the tools to explain, predict and calculate them.

Before we can talk about forces (why the rider leans, why the string tilts), we must first learn the language of circular motion: how to describe position, rotation and rate of rotation. That is the work of this first section.

1.1 What is circular motion? Everyday observations

Look around you and circular motion is everywhere:

- the wheels of a bendskin (bicycle taxi) rolling through Bamenda;
- the blades of a ceiling fan turning in a classroom in Buea;
- a merry-go-round at a Christmas fairground;
- the hands of the clock on the wall of your examination hall;
- the Earth travelling around the Sun, and the Moon around the Earth;
- a stone whirled on the end of a string.

In each case, some point of the object moves along a **circle** (or very nearly one). In this chapter we idealise the moving object as a particle P travelling on a circle of fixed centre O and fixed radius r .

DEFINITION Circular motion and uniform circular motion

A particle is in **circular motion** when its path is a circle of centre O and radius r . The motion is called **uniform circular motion** when the speed of the particle along the circle is constant.

WARNING Constant speed does not mean constant velocity

Speed is a scalar; velocity is a vector. Even when the speed v is constant, the direction of the velocity changes continuously, because the velocity vector is always tangent to the circle and the tangent direction turns as the particle moves. Since velocity changes, the particle is accelerating — this surprising fact is the key to the whole chapter and will be made precise in the next section (centripetal acceleration). For now, keep the slogan:

uniform circular motion = constant speed, changing velocity.

1.2 Angular displacement and the radian

To locate a particle on a circle, distances along a straight axis are clumsy. The natural coordinate is an **angle**.

DEFINITION Angular displacement

Let a particle move on a circle of centre O from position A to position B . The **angular displacement** is the angle $\theta = \angle AOB$ swept out by the radius OP . It is measured in **radians** (symbol rad).


Why invent a new unit, the radian, when degrees exist? Because the radian makes the geometry of the circle collapse into one beautiful formula. Measure the arc length s from A to B along the circle. If you double the radius while keeping the same angle, the arc doubles: arc length is proportional to radius. The radian is defined so that the constant of proportionality is exactly 1.

DEFINITION The radian

One **radian** is the angle subtended at the centre of a circle by an arc whose length equals the radius. Consequently, for any angle θ in radians,

$$s = r\theta$$

where s is the arc length and r the radius. A full revolution corresponds to $\theta = 2\pi$ rad, since the full circumference is $s = 2\pi r$. The radian is a dimensionless unit (it is a ratio of two lengths), but we keep the symbol “rad” for clarity.



A particle moves from A to B on a circle of radius r . The angular displacement is θ (in radians) and the arc travelled is $s = r\theta$.

PROPERTY Conversion between degrees and radians

Since 360° corresponds to 2π rad,

$$180^\circ = \pi \text{ rad}, \quad 1^\circ = \frac{\pi}{180} \text{ rad}, \quad 1 \text{ rad} = \frac{180}{\pi} \text{ degrees} \approx 57.3^\circ.$$

To convert degrees to radians, multiply by $\frac{\pi}{180}$; to convert radians to degrees, multiply by $\frac{180}{\pi}$.

EXAMPLE Converting angles

$$60^\circ = 60 \times \frac{\pi}{180} = \frac{\pi}{3} \text{ rad}; \quad 135^\circ = \frac{3\pi}{4} \text{ rad}; \quad \frac{5\pi}{6} \text{ rad} = \frac{5\pi}{6} \times \frac{180}{\pi} = 150^\circ.$$

1.3 Angular speed

A degree or a radian tells us how far the radius has turned. We now ask how fast it turns.

DEFINITION Angular speed

If the radius OP sweeps an angular displacement $\Delta\theta$ in a time interval Δt , the **angular speed** is

$$\omega = \frac{\Delta\theta}{\Delta t}$$

with $\Delta\theta$ in radians and Δt in seconds. The SI unit of ω is the radian per second, written rad s^{-1} (or rad/s). For uniform circular motion, ω is constant: equal angles are swept in equal times. (One can also define an angular velocity vector $\vec{\omega}$ pointing along the axis of rotation; at GCE Advanced Level we only need its magnitude ω .)

1.4 Period and frequency

Two more everyday words describe rotation, and examiners love converting between them.

DEFINITION Period and frequency

The **period** T is the time for one complete revolution; its SI unit is the second (s). The **frequency** f is the number of complete revolutions per second; its SI unit is the hertz (Hz), with $1 \text{ Hz} = 1 \text{ s}^{-1}$. Clearly

$$f = \frac{1}{T} \quad \text{and} \quad T = \frac{1}{f}.$$

Now connect these to ω . In one period T , the radius sweeps exactly one full turn, i.e. $\Delta\theta = 2\pi$ rad. Hence:

PROPERTY Fundamental relations for uniform circular motion

$$\omega = \frac{2\pi}{T} = 2\pi f$$

This follows directly from $\omega = \Delta\theta/\Delta t$ with one revolution: $\omega = \frac{2\pi}{T}$, and substituting $T = 1/f$ gives $\omega = 2\pi f$. (The derivation is examinable and takes two lines — learn it.)

WORKED EXAMPLE 1 The second hand of a clock

The second hand of the clock in your examination hall makes one revolution per minute. Find (a) its period, (b) its frequency, (c) its angular speed.

SOLUTION


Solution.

1. One revolution takes 60 s, so $T = 60$ s.

$$2. f = \frac{1}{T} = \frac{1}{60} \text{ Hz} \approx 0.0167 \text{ Hz}.$$

$$3. \omega = \frac{2\pi}{T} = \frac{2\pi}{60} = \frac{\pi}{30} \text{ rad s}^{-1} \approx 0.105 \text{ rad s}^{-1}.$$

Check: in 15 s the hand sweeps $\theta = \omega t = \frac{\pi}{30} \times 15 = \frac{\pi}{2} \text{ rad} = 90^\circ$ — exactly a quarter turn, as expected.



$$T = 60 \text{ s}, \quad \omega = \frac{2\pi}{T} = \frac{\pi}{30} \text{ rad s}^{-1}$$

The second hand of a clock: period $T = 60$ s, angular speed $\omega = 2\pi/T$. In time t it sweeps $\theta = \omega t$.

1.5 Revolutions per minute (rpm)

Machines rarely quote ω in rad s^{-1} . Grinding wheels, fans, engines and DJ turntables are rated in **revolutions per minute** (rpm). If a wheel makes N revolutions in one minute, then each revolution is 2π rad and one minute is 60 s, so

$$\omega = \frac{N \times 2\pi \text{ rad}}{60 \text{ s}} = \frac{2\pi N}{60} \text{ rad s}^{-1}.$$

METHOD Converting rpm to rad/s

To convert a rotation rate of N rpm to an angular speed in rad s^{-1} :

1. Multiply N by 2π to get the angle swept per minute, in radians.
2. Divide by 60 to convert “per minute” to “per second”.
3. Write the result with the unit rad s^{-1} , keeping π symbolic unless a decimal is requested.

In short: $\omega = \frac{2\pi N}{60} = \frac{\pi N}{30} \text{ rad s}^{-1}$.

WORKED EXAMPLE 2 The grinding wheel in Douala

A grinding wheel in a workshop in Douala spins at 1200 rpm. Find (a) its angular speed in rad s^{-1} , (b) its frequency in Hz, (c) its period.

SOLUTION

Solution.

$$1. \quad \omega = \frac{2\pi N}{60} = \frac{2\pi \times 1200}{60} = 40\pi \text{ rad s}^{-1} \approx 125.7 \text{ rad s}^{-1}.$$

$$2. \quad f = \frac{\omega}{2\pi} = \frac{40\pi}{2\pi} = 20 \text{ Hz (equivalently, } 1200/60 = 20 \text{ revolutions per second).}$$

$$3. \quad T = \frac{1}{f} = \frac{1}{20} = 0.05 \text{ s.}$$

So the wheel completes a full turn every fiftieth of a second — no wonder a slipping work-piece is dangerous!

WARNING Never mix degrees and radians

The formulas $s = r\theta$, $\omega = \Delta\theta/\Delta t$ and $\omega = 2\pi/T$ are valid only when angles are in radians. If a problem gives an angle in degrees, convert first: multiply by $\pi/180$. A candidate who writes “ $\omega = 360/60 = 6 \text{ rad s}^{-1}$ ” for the second hand of a clock has mixed degrees with radians and loses the marks — the correct value is $\pi/30 \text{ rad s}^{-1}$.

EXAMPLE A fairground merry-go-round

A merry-go-round completes one revolution every 8.0 s. Its angular speed is

$$\omega = \frac{2\pi}{T} = \frac{2\pi}{8.0} = \frac{\pi}{4} \text{ rad s}^{-1} \approx 0.785 \text{ rad s}^{-1},$$

and its frequency is $f = 1/8.0 = 0.125 \text{ Hz}$. In 20 s a child on it sweeps $\theta = \omega t = \frac{\pi}{4} \times 20 = 5\pi$ rad, i.e. two and a half turns.

KEY POINTS Key points of this section

- Uniform circular motion: constant speed, continuously changing velocity (direction).
- Angular displacement θ in radians; 1 rad is the angle for which arc = radius; $s = r\theta$; $360^\circ = 2\pi$ rad.
- Angular speed $\omega = \frac{\Delta\theta}{\Delta t}$, unit rad s^{-1} .
- Period T (s per revolution), frequency $f = \frac{1}{T}$ (Hz).
- $\omega = \frac{2\pi}{T} = 2\pi f$; from N rpm: $\omega = \frac{2\pi N}{60}$.

METHOD Exam tip: units earn marks

GCE Advanced Level examiners expect the unit written at every final answer: rad s^{-1} for ω , Hz for f , s for T , rad for θ . A correct numerical answer with a missing or wrong unit routinely loses the final mark. Make it a habit now: no unit, no full credit.

EXERCISE 1 Consolidation

1. Convert to radians: 45° , 210° , 300° . Convert to degrees: $\frac{\pi}{6}$ rad, $\frac{7\pi}{4}$ rad.
2. The minute hand of a clock: find its period, frequency and angular speed.
3. A ceiling fan rotates at 300 rpm. Find ω in rad s^{-1} and the angle swept in 0.5 s.
4. A wheel has angular speed $10\pi \text{ rad s}^{-1}$. How many revolutions does it make in one minute?

SOLUTION Exercise 1

1. $45^\circ = \frac{\pi}{4}$ rad; $210^\circ = \frac{7\pi}{6}$ rad; $300^\circ = \frac{5\pi}{3}$ rad. $\frac{\pi}{6}$ rad = 30° ; $\frac{7\pi}{4}$ rad = 315° .
2. $T = 3600$ s; $f = \frac{1}{3600}$ Hz $\approx 2.78 \times 10^{-4}$ Hz; $\omega = \frac{2\pi}{3600} = \frac{\pi}{1800}$ $\text{rad s}^{-1} \approx 1.75 \times 10^{-3}$ rad s^{-1} .
3. $\omega = \frac{2\pi \times 300}{60} = 10\pi \text{ rad s}^{-1} \approx 31.4 \text{ rad s}^{-1}$; $\theta = \omega t = 10\pi \times 0.5 = 5\pi$ rad (two and a half turns).
4. $f = \frac{\omega}{2\pi} = 5$ Hz, so in 60 s the wheel makes $5 \times 60 = 300$ revolutions (i.e. 300 rpm).

DID YOU KNOW? Why radians rule the sciences

The radian is not an arbitrary convention: it is the only angle unit for which $\frac{d}{d\theta}(\sin \theta) = \cos \theta$ holds without extra factors, and the only one for which $s = r\theta$ is exactly true. That is why every formula in this chapter — and later in simple harmonic motion, waves and electromagnetism — silently assumes radians. Your calculator should live in RAD mode during mechanics papers!

We can now describe how fast anything rotates, from a clock hand to a grinding wheel. But description is not explanation: the moto-taxi at Carrefour Warda leans because something must pull him towards the centre of the curve. In the next section we quantify that something: the centripetal acceleration $a = \omega^2 r$ and the centripetal force that produces it.

2 CENTRIPETAL ACCELERATION AND CENTRIPETAL FORCE

In the previous section we described uniform circular motion with the angular quantities θ , ω and the period T , and we saw that the linear speed $v = r\omega$ stays constant. It is tempting to conclude that “constant speed” means “no acceleration”. That conclusion is wrong, and understanding why it is wrong is the heart of this section. We shall show that a body moving in a circle is permanently accelerated towards the centre, derive the famous formula $a = \frac{v^2}{r}$, and then apply Newton’s second law to obtain the **centripetal force** $F = \frac{mv^2}{r}$.

2.1 Uniform circular motion is accelerated motion

EXPERIMENT Swinging a stone on a string

Tie a small stone to a string about 1 m long and whirl it in a horizontal circle above your head. Two observations are immediate:

1. You must keep pulling on the string the whole time. The instant you let go, the stone flies away.
2. Your hand feels a continuous pull outwards from the stone — the stone is “trying” to go straight while you force it to turn.

A force is needed to keep the stone on its circle. By Newton’s second law, a force means an acceleration. So the stone is accelerating, even though its speed never changes.

The key is the vector nature of velocity. Acceleration is defined by

$$\vec{a} = \frac{d\vec{v}}{dt},$$


and the velocity vector $\vec{v}$ has **both a magnitude and a direction**. In uniform circular motion the magnitude v is constant, but the direction of $\vec{v}$ changes continuously: at every instant $\vec{v}$ is tangent to the circle, and the tangent direction rotates as the body moves. A changing velocity vector — even with constant magnitude — means a non-zero acceleration.

WARNING Constant speed does not mean zero acceleration

In circular motion, “uniform” refers to the speed (the magnitude of $\vec{v}$), not to the velocity vector. Because the direction of $\vec{v}$ changes all the time, the acceleration is never zero. Writing “ v constant $\Rightarrow a = 0$ ” is one of the most frequent errors at the GCE Advanced Level.

2.2 Direction of the acceleration: towards the centre

Consider a particle moving with constant speed v on a circle of radius r centred at O . Let it pass through point P at time t and through a nearby point Q at time $t + \Delta t$, where the radius has turned through a small angle $\Delta\theta$.



Velocity vectors at two nearby points P and Q ; the change $\Delta\vec{v}$ points towards the interior of the circle, i.e. towards the centre as $\Delta\theta \rightarrow 0$.

To find the acceleration we must examine the change of velocity $\Delta\vec{v} = \vec{v}_Q - \vec{v}_P$. Place the two velocity vectors tail to tail (right-hand part of the figure). Since the motion is uniform, $|\vec{v}_P| = |\vec{v}_Q| = v$, so the velocity triangle is isosceles, and the angle between $\vec{v}_P$ and $\vec{v}_Q$ equals the angle $\Delta\theta$ between the radii (each velocity is perpendicular to its radius). As $\Delta\theta \rightarrow 0$, the vector $\Delta\vec{v}$ becomes perpendicular to $\vec{v}_P$ and points inwards, along the radius, **towards the centre** O . This is why the acceleration is called **centripetal**, from the Latin petere: “seeking the centre”.

2.3 Derivation of $a = \frac{v^2}{r}$

This derivation is instructive and its steps can be asked for at the examination.

Step 1: magnitude of $\Delta\vec{v}$. In the isosceles velocity triangle with sides v , v and small angle $\Delta\theta$ between them, the chord gives

$$|\Delta\vec{v}| = 2v \sin\left(\frac{\Delta\theta}{2}\right) \approx v \Delta\theta \quad (\Delta\theta \text{ small, in radians}).$$

Step 2: time taken. The body moves along the arc from P to Q with speed v , and the arc length is $r\Delta\theta$, so

$$\Delta t = \frac{r\Delta\theta}{v}.$$

Step 3: magnitude of the acceleration.

$$a = \lim_{\Delta t \rightarrow 0} \frac{|\Delta\vec{v}|}{\Delta t} = \frac{v\Delta\theta}{r\Delta\theta/v} = \frac{v^2}{r}.$$

Since $v = r\omega$, we obtain the equivalent form $a = \frac{(r\omega)^2}{r} = r\omega^2$.

DEFINITION Centripetal acceleration

A body in uniform circular motion of radius r with speed v and angular speed ω has an acceleration of magnitude

$$a = \frac{v^2}{r} = r\omega^2$$

directed at every instant along the radius towards the centre of the circle. It is called the **centripetal acceleration**. Its SI unit is the m s^{-2} .

WARNING Two traps with the formula

- a is inversely proportional to r at fixed v , but directly proportional to r at fixed ω (use $a = r\omega^2$). Always ask which quantity is held constant before comparing.
- The acceleration points towards the centre, not along the tangent. The velocity points along the tangent; velocity and acceleration are perpendicular in uniform circular motion.

2.4 Centripetal force: Newton's second law for circular motion

Acceleration never appears by magic: it is produced by a resultant force. Applying Newton's second law $\vec{F} = m\vec{a}$ to the centripetal acceleration gives the central law of this chapter.

PROPERTY Centripetal force (Newton's second law for circular motion)

To keep a body of mass m in uniform circular motion of radius r at speed v (angular speed ω), the resultant of all the forces acting on it must have magnitude

$$F = \frac{mv^2}{r} = mr\omega^2$$

and must be directed towards the centre of the circle. This resultant is called the **centripetal force**.

KEY POINTS Centripetal force is NOT a new force

The centripetal force is not an extra force to be added to the list of forces. It is the role played by the resultant of real, identifiable forces:

- the tension of a string (stone whirled in a circle);
- the friction between tyres and road (car rounding a bend);
- the gravitational attraction of the Earth (satellite or the Moon in orbit);
- the normal reaction of a wall or banked track (wall of death, velodrome).

In each problem, your first task is to identify which real force(s) supply the required $\frac{mv^2}{r}$.

WARNING There is no “centrifugal force” on the body

You may feel “thrown outwards” in a turning car, but no real force pushes the moving body away from the centre. The so-called centrifugal force is only the tendency of the body to continue in a straight line (inertia), felt in the rotating frame. Never draw a centrifugal force on a free-body diagram — it is a classic error that costs marks.

METHOD Finding the required centripetal force

1. Draw the free-body diagram: list all real forces (weight, tension, friction, reaction, ...).
2. Choose the radial direction (towards the centre) and resolve every force along it.
3. Set the resultant towards the centre equal to $\frac{mv^2}{r}$ (or $mr\omega^2$).
4. Solve for the unknown (tension, friction, speed, ...) and check the units.

2.5 Worked examples


EXAMPLE Stone on a string (horizontal circle)

A stone of mass $m = 0.50$ kg is whirled in a horizontal circle of radius $r = 1.0$ m on a frictionless table, at speed $v = 4.0$ m s⁻¹. Find the tension in the string.

Solution. On the smooth table the weight is balanced by the normal reaction of the table; the only horizontal force is the tension T , which points towards the centre. Hence the tension alone provides the centripetal force:

$$T = \frac{mv^2}{r} = \frac{0.50 \times (4.0)^2}{1.0} = 8.0 \text{ N.}$$

If the string can bear at most 8.0 N, it is exactly at breaking point: any increase of speed snaps it.



Free-body diagram (view from above) of a stone on a horizontal string: the tension $\vec{T}$ points towards the centre O and provides the centripetal force; the velocity $\vec{v}$ is tangential.

WORKED EXAMPLE 3 Car rounding a bend

A car of mass $m = 1200$ kg rounds a flat, unbanked bend of radius $r = 50$ m at $v = 20$ m s⁻¹. (a) What centripetal force is required, and what provides it? (b) If the maximum friction available between tyres and road is $F_{\text{max}} = 9600$ N, what is the greatest safe speed?

SOLUTION

(a) On a flat road the weight and the normal reaction cancel vertically. Horizontally, only the friction $\vec{f}$ of the road on the tyres points towards the centre of the bend, so friction is

the centripetal force:

$$f = \frac{mv^2}{r} = \frac{1200 \times 20^2}{50} = \frac{1200 \times 400}{50} = 9600 \text{ N.}$$

(b) The greatest safe speed corresponds to friction at its maximum:

$$\frac{mv_{\max}^2}{r} = F_{\max} \implies v_{\max} = \sqrt{\frac{F_{\max} r}{m}} = \sqrt{\frac{9600 \times 50}{1200}} = \sqrt{400} = 20 \text{ m s}^{-1}.$$

So at 20 m s^{-1} (about 72 km h^{-1}) the car is exactly at the limit of grip — on a wet Douala-Yaoundé road, where $F_{\max}$ is smaller, the safe speed drops accordingly.

EXAMPLE Satellite in orbit

A satellite of mass $m = 800 \text{ kg}$ moves in a circular orbit of radius $r = 7.0 \times 10^6 \text{ m}$ around the Earth, where the gravitational pull on it is $F = 6.4 \times 10^3 \text{ N}$. Find its orbital speed.

Solution. The Earth's gravitational attraction is the only force on the satellite, so it plays the role of centripetal force:

$$\frac{mv^2}{r} = F \implies v = \sqrt{\frac{Fr}{m}} = \sqrt{\frac{6.4 \times 10^3 \times 7.0 \times 10^6}{800}} = \sqrt{5.6 \times 10^7} \approx 7.5 \times 10^3 \text{ m s}^{-1}.$$

The satellite falls towards the Earth continuously — that fall is its centripetal acceleration — yet its tangential speed keeps it on the circle.

2.6 What happens if the centripetal force is removed?

Suppose the string of the whirling stone suddenly breaks. From that instant, no horizontal force acts on the stone. By **Newton's first law**, the stone continues in a straight line at constant velocity — the velocity it had at the moment of release, which is tangent to the circle. The stone therefore flies off **along the tangent**, never radially outwards. This is why sparks from a grinding wheel and mud from a bicycle tyre leave tangentially, and why a hammer thrower releases the hammer so that its tangent line points at the target.

DID YOU KNOW? Why the Moon does not fall on us

The Moon is permanently “falling” towards the Earth: gravity gives it the centripetal acceleration $a = v^2/r$ of its (nearly) circular orbit. It never gets closer because its tangential speed continually carries it sideways as it falls. Newton himself used this idea to show that the same gravity that makes an apple fall also holds the Moon in orbit.

EXERCISE 2 Practice

1. A particle moves uniformly on a circle of radius 2.0 m with angular speed $\omega = 3.0 \text{ rad s}^{-1}$. Calculate its centripetal acceleration.
2. A child of mass 30 kg sits 4.0 m from the axis of a merry-go-round making one revolution every 6.0 s. Find the centripetal force the seat must exert on the child.
3. A bucket of water is whirled in a vertical circle. Explain, using the ideas of this section, why the water does not fall out at the top if the speed is large enough, and identify what provides the centripetal force on the water at the top.

SOLUTION Exercise 1

$a = r\omega^2 = 2.0 \times (3.0)^2 = 18 \text{ m s}^{-2}$, directed towards the centre.

SOLUTION Exercise 2

$\omega = \frac{2\pi}{T} = \frac{2\pi}{6.0} = \frac{\pi}{3} \text{ rad s}^{-1}$. Then $F = mr\omega^2 = 30 \times 4.0 \times \left(\frac{\pi}{3}\right)^2 = \frac{120\pi^2}{9} \approx 132 \text{ N}$, directed towards the axis.

SOLUTION Exercise 3

At the top of the circle, both the weight mg of the water and the reaction of the bucket bottom point downwards, i.e. towards the centre: together they supply the centripetal force, $mg + R = \frac{mv^2}{r}$. If v is large enough that $\frac{mv^2}{r} \geq mg$, the required force exceeds the weight, so $R \geq 0$: the bucket keeps pushing on the water and the water stays in. The minimum speed is given by $R = 0$, i.e. $v_{\min} = \sqrt{gr}$.

KEY POINTS Summary of the section

- Uniform circular motion is accelerated motion, because the direction of $\vec{v}$ changes continuously.
- The acceleration is centripetal: $a = \frac{v^2}{r} = r\omega^2$, towards the centre.

- Newton's second law gives the centripetal force: $F = \frac{mv^2}{r} = mr\omega^2$, supplied by real forces (tension, friction, gravity, reaction).
- No centrifugal force acts on the body; if the centripetal force vanishes, the body leaves along the tangent (Newton's first law).

3 LINEAR SPEED, ANGULAR SPEED AND THEIR RELATIONSHIP

In the previous section we discovered that a particle moving in a circle, even at constant speed, is permanently accelerated towards the centre, with centripetal acceleration $a = \frac{v^2}{r}$, and that a **centripetal force** $F = \frac{mv^2}{r}$ is needed to bend its path. But we left one question open: how exactly are the linear speed v (in metres per second) and the angular speed ω (in radians per second) connected? A cyclist in Bamenda, a grinding wheel in a Douala workshop, and the Earth itself all rotate — yet different points of the same rotating object move at different linear speeds. This section makes the link precise: it is the celebrated relation $v = r\omega$, one of the most frequently used formulas of the whole mechanics syllabus.

3.1 Linear (Tangential) Speed: Intuition

Imagine tying a stone to a string and whirling it horizontally above your head. If the string suddenly snaps, the stone does not fly radially outwards — it flies off along the **tangent** to the circle at the point of release. This everyday observation tells us two things:

- the stone possesses a **linear speed** v , measured as arc length covered per unit time, in m s^{-1} ;
- at each instant, the velocity vector $\vec{v}$ is directed along the **tangent** to the circle, perpendicular to the radius.

DEFINITION Linear (tangential) speed

The **linear speed** (or tangential speed) of a particle in uniform circular motion is the distance travelled along the arc per unit time:

$$v = \frac{\text{arc length}}{\text{time}} = \frac{s}{t}.$$

The velocity vector $\vec{v}$ is tangent to the circular path at the position of the particle, and its magnitude v is constant in uniform circular motion (only its direction changes).

Recall also the angular quantities from Section 1: the angular position θ (in radians), and the an-

gular speed

$$\omega = \frac{d\theta}{dt}, \quad \text{in rad s}^{-1},$$

with $\omega = \frac{2\pi}{T} = 2\pi f$, where T is the period and f the frequency.

3.2 Derivation of $v = r\omega$

This derivation is short, instructive, and **examinable** — learn it line by line.

For a particle moving on a circle of radius r , the arc length s corresponding to an angle θ (in radians) is, by the very definition of the radian:

$$s = r\theta.$$

Since the radius r is constant, differentiate both sides with respect to time t :

$$\frac{ds}{dt} = \frac{d}{dt}(r\theta) = r \frac{d\theta}{dt}.$$

Now $\frac{ds}{dt}$ is the rate at which arc length is covered, i.e. the linear speed v , and $\frac{d\theta}{dt}$ is the angular speed ω . Therefore:

$$v = r\omega$$

PROPERTY Linking linear and angular speed

For a particle in uniform circular motion of radius r , period T and frequency f :

$$v = r\omega = \frac{2\pi r}{T} = 2\pi r f.$$


The two last forms follow immediately from $\omega = \frac{2\pi}{T} = 2\pi f$. (The derivation of $v = r\omega$ from $s = r\theta$ is examinable.)

WARNING Units are not optional

The formula $v = r\omega$ is valid only when θ and ω are in radians (radians and radians per second). If a problem gives the rotation in revolutions per minute (rpm) or in degrees, convert first:

$$\omega (\text{rad s}^{-1}) = \frac{2\pi \times N (\text{rpm})}{60}.$$

Using rpm directly in $v = r\omega$ is one of the most common errors at the GCE.



$$v = r\omega, \vec{v} \perp \text{radius}$$

Uniform circular motion: the velocity $\vec{v}$ is tangent to the circle, perpendicular to the radius OP , with $v = r\omega$.

3.3 Same ω , Different v : Points of a Rigid Rotating Body

Here is the key conceptual point of the whole section. Consider a rigid body rotating about a fixed axis — a grinding wheel, a turntable, a ceiling fan. In a time t , every radius of the body sweeps through the same angle θ : the body rotates “as one block”. Hence all points of the body share the **same angular speed** ω .


But their linear speeds differ, because $v = r\omega$ grows in proportion to the distance r from the axis: a point twice as far from the centre moves twice as fast. A point on the axis ($r = 0$) does not move at all.

WARNING The classic trap: v depends on r , ω does not

Two points A and B on the same rotating wheel, with $r_A < r_B$:

- have the same angular speed: $\omega_A = \omega_B$;
- have different linear speeds: $v_B = \frac{r_B}{r_A} v_A > v_A$;
- have different centripetal accelerations: $a = r\omega^2$ is larger for the outer point.

Saying “all points of the wheel have the same speed” is false; only the angular speed is common.



$$\text{Same } \omega; v_2 = \frac{r_2}{r_1} v_1 > v_1$$

A rotating disc: points A and B share the same angular speed ω , but the outer point B has the larger tangential velocity since $v = r\omega$.

3.4 Choosing Between $a = \frac{v^2}{r}$ and $a = r\omega^2$

Since $v = r\omega$, the centripetal acceleration of Section 2 can be written in two equivalent ways:

$$a = \frac{v^2}{r} = r\omega^2 \quad \left(\text{also } a = \frac{4\pi^2 r}{T^2} = 4\pi^2 r f^2 \right).$$

Both formulas describe the same acceleration; the art is to pick the one that uses the data actually given, avoiding unnecessary intermediate calculations.

METHOD Which centripetal acceleration formula?

1. Read the data. List what is given: v ? ω ? T or f ? r ?
2. Given v and r : use $a = \frac{v^2}{r}$ directly.
3. Given ω and r : use $a = r\omega^2$ directly.
4. Given T or f : convert first, $\omega = \frac{2\pi}{T} = 2\pi f$, then use $a = r\omega^2$.
5. Comparing two points of the same rigid body (same ω): use $a = r\omega^2$, so $a \propto r$.
6. Comparing motions at the same linear speed (e.g. a belt driving two pulleys): use $a = \frac{v^2}{r}$, so $a \propto \frac{1}{r}$.

WARNING A subtle comparison trap

For two points on the same wheel, $a = r\omega^2$ shows the outer point has the larger acceleration. But for a car taking a tighter bend at the same speed v , $a = \frac{v^2}{r}$ shows the smaller radius gives the larger acceleration. There is no contradiction: in the first case ω is fixed, in the second v is fixed. Always ask: which quantity is common to the two situations?

3.5 Worked Examples**WORKED EXAMPLE 4** Points on a grinding wheel

A grinding wheel in a workshop rotates at 1200 rpm. Two grains of the wheel, A and B, are at distances $r_A = 4.0$ cm and $r_B = 10.0$ cm from the axis. Find (a) the angular speed of the wheel; (b) the linear speed of each grain; (c) the centripetal acceleration of grain B.

SOLUTION

Solution. (a) Convert the rotation rate to rad s^{-1} :

$$\omega = \frac{2\pi \times 1200}{60} = 40\pi \approx 125.7 \text{ rad s}^{-1}.$$

This angular speed is the same for both grains.

(b) Apply $v = r\omega$ to each grain:

$$v_A = r_A \omega = 0.040 \times 40\pi = 1.6\pi \approx 5.0 \text{ m s}^{-1},$$

$$v_B = r_B \omega = 0.100 \times 40\pi = 4\pi \approx 12.6 \text{ m s}^{-1}.$$

Note that $\frac{v_B}{v_A} = \frac{r_B}{r_A} = 2.5$, as expected.

(c) Since ω and r are known, use $a = r\omega^2$:

$$a_B = 0.100 \times (40\pi)^2 = 160\pi^2 \approx 1.58 \times 10^3 \text{ m s}^{-2}.$$

That is more than 160 times g — which is why a cracked grinding wheel is so dangerous.

WORKED EXAMPLE 5 A record turntable

A turntable rotates at $33\frac{1}{3}$ rpm. A speck of dust sits on a record at $r = 12$ cm from the centre. Calculate (a) the period T ; (b) the linear speed of the speck; (c) its centripetal acceleration.

SOLUTION

Solution. (a) One revolution takes

$$T = \frac{60}{33\frac{1}{3}} = \frac{60 \times 3}{100} = 1.8 \text{ s.}$$

(b) Using $v = \frac{2\pi r}{T}$:

$$v = \frac{2\pi \times 0.12}{1.8} = \frac{0.24\pi}{1.8} \approx 0.42 \text{ m s}^{-1}.$$

(c) With $\omega = \frac{2\pi}{T} = \frac{2\pi}{1.8} \approx 3.49 \text{ rad s}^{-1}$:

$$a = r\omega^2 = 0.12 \times (3.49)^2 \approx 1.46 \text{ m s}^{-2}.$$

WORKED EXAMPLE 6 Speed of a point on the Equator

The Earth completes one rotation about its axis in 24 hours, and its radius is $R \approx 6.4 \times 10^6 \text{ m}$. Estimate the linear speed, due to the Earth's rotation, of a person standing on the Equator (e.g. near the coast of the South-West Region).

SOLUTION

Solution. The period is $T = 24 \times 3600 = 8.64 \times 10^4 \text{ s}$. Then

$$v = \frac{2\pi R}{T} = \frac{2\pi \times 6.4 \times 10^6}{8.64 \times 10^4} \approx 4.65 \times 10^2 \text{ m s}^{-1}.$$

A person on the Equator is therefore travelling at roughly 465 m s^{-1} — faster than the speed of sound in air — without feeling it, because the motion is perfectly uniform and everything around moves together. (Points away from the Equator move on smaller circles of radius $R \cos \lambda$, where λ is the latitude, so their speed is smaller while ω is the same for the whole planet.)

3.6 Inverse Problems: Finding ω or r

The relation $v = r\omega$ contains three quantities; given any two, the third follows:

$$\omega = \frac{v}{r}, \quad r = \frac{v}{\omega}, \quad v = r\omega.$$

Combined with $\omega = \frac{2\pi}{T} = 2\pi f$ and $a = \frac{v^2}{r} = r\omega^2$, this solves a wide family of GCE problems.

WORKED EXAMPLE 7 Finding ω from v and r

The tip of the minute hand of a large clock moves at $v = 2.0 \text{ mm s}^{-1}$. The hand is $r = 15 \text{ cm}$ long. (a) Find the angular speed of the tip. (b) Deduce the period of the minute hand and comment.

SOLUTION

Solution. (a) Convert units: $v = 2.0 \times 10^{-3} \text{ m s}^{-1}$, $r = 0.15 \text{ m}$.

$$\omega = \frac{v}{r} = \frac{2.0 \times 10^{-3}}{0.15} \approx 1.33 \times 10^{-2} \text{ rad s}^{-1}.$$

(b) $T = \frac{2\pi}{\omega} = \frac{2\pi}{1.33 \times 10^{-2}} \approx 4.7 \times 10^2 \text{ s}$? Let us check: $\frac{2\pi}{0.0133} \approx 472 \text{ s}$. Hmm — a minute hand should take 3600 s! The discrepancy tells us the stated tip speed was too large; a real 15 cm minute hand has $\omega = \frac{2\pi}{3600} \approx 1.75 \times 10^{-3} \text{ rad s}^{-1}$ and tip speed $v = r\omega \approx 0.26 \text{ mm s}^{-1}$. Lesson: always check the physical plausibility of a numerical answer — examiners reward this reflex.

WORKED EXAMPLE 8 Finding r from v and T

A satellite moves in a circular orbit with period $T = 5.6 \times 10^3 \text{ s}$ at a constant speed $v = 7.6 \times 10^3 \text{ m s}^{-1}$. Find the radius of its orbit.

SOLUTION

Solution. From $v = \frac{2\pi r}{T}$ we isolate r :

$$r = \frac{vT}{2\pi} = \frac{7.6 \times 10^3 \times 5.6 \times 10^3}{2\pi} \approx 6.8 \times 10^6 \text{ m}.$$

The orbit radius is about $6.8 \times 10^6 \text{ m}$, i.e. roughly 400 km above the Earth's surface.

METHOD Exam strategy: period or frequency given

When a question gives the period T or the frequency f (or a rotation rate in rpm):

1. Convert immediately to angular speed: $\omega = \frac{2\pi}{T} = 2\pi f = \frac{2\pi N}{60}$.
2. Then use $v = r\omega$ and, if required, $a = r\omega^2$ or $F = mr\omega^2$.
3. Keep π symbolic until the final line, then approximate ($\pi \approx 3.1416$, $\pi^2 \approx 9.87$).
4. Check units: r in metres, ω in rad s^{-1} , v in m s^{-1} .

KEY POINTS Key points of the section

- Linear speed: $v = \frac{s}{t}$ along the arc; $\vec{v}$ is tangent to the circle.
- Fundamental link (derivable from $s = r\theta$): $v = r\omega = \frac{2\pi r}{T} = 2\pi r f$.
- All points of a rigid rotating body share the same ω ; their linear speeds satisfy $v \propto r$.
- Centripetal acceleration: $a = \frac{v^2}{r} = r\omega^2$ — choose the form matching the given data.
- Inverse problems: $\omega = \frac{v}{r}$, $r = \frac{v}{\omega} = \frac{vT}{2\pi}$.
- Always convert rpm, periods and frequencies to ω in rad s^{-1} before computing.

EXERCISE 3 Practice

1. A ceiling fan rotates at 300 rpm. Find (a) its angular speed in rad s^{-1} ; (b) the linear speed of a point on a blade 60 cm from the axis; (c) the centripetal acceleration of that point.
2. Two points P and Q of a rotating platform are at 0.20 m and 0.50 m from the axis. If $v_P = 1.5 \text{ m s}^{-1}$, find ω and v_Q .
3. A car wheel of radius 0.30 m rolls so that its centre moves at 24 m s^{-1} . Assuming no slipping, find the angular speed of the wheel and its rotation frequency in rpm.

SOLUTION Exercise 1

1. (a) $\omega = \frac{2\pi \times 300}{60} = 10\pi \approx 31.4 \text{ rad s}^{-1}$. (b) $v = r\omega = 0.60 \times 10\pi = 6\pi \approx 18.8 \text{ m s}^{-1}$. (c) $a = r\omega^2 = 0.60 \times (10\pi)^2 = 60\pi^2 \approx 5.9 \times 10^2 \text{ m s}^{-2}$.
2. $\omega = \frac{v_P}{r_P} = \frac{1.5}{0.20} = 7.5 \text{ rad s}^{-1}$ (same for the whole platform); $v_Q = r_Q\omega = 0.50 \times 7.5 = 3.75 \text{ m s}^{-1}$.
3. $\omega = \frac{v}{r} = \frac{24}{0.30} = 80 \text{ rad s}^{-1}$; $N = \frac{60\omega}{2\pi} = \frac{60 \times 80}{2\pi} \approx 764 \text{ rpm}$.

DID YOU KNOW? Why this matters beyond the classroom

The relation $v = r\omega$ explains why the teeth at the rim of a circular saw must be made of harder material than the disc itself: they travel fastest and do all the cutting. It also governs the

design of the turbines at the Song Loulou and Memve'ele hydroelectric stations: for a given rotational speed imposed by the alternator, the engineer chooses the rotor radius so that the tangential speed of the blades stays within safe mechanical limits — too large an r at fixed ω means destructive centripetal stresses.

4 APPLICATIONS OF LINEAR AND ANGULAR SPEED

In the previous sections we established the fundamental bridge between the two descriptions of uniform circular motion: the **linear speed** v of a particle on its circular path and the **angular speed** ω of the radius vector, linked by the relation $v = r\omega$. We also proved that any body moving in a circle of radius r at constant speed v experiences a **centripetal acceleration** $a = \frac{v^2}{r} = r\omega^2$ directed towards the centre, and therefore requires a **centripetal force** $F = \frac{mv^2}{r} = mr\omega^2$.

A natural question now arises: where does this centripetal force come from in real situations? A force never appears from nowhere — it must be supplied by a concrete physical interaction: friction between tyres and road, tension in a string or belt, the normal reaction of a surface, or the pull of gravity. In this section we tour the most important applications. For each, we follow the same three-step method that GCE examiners expect:

1. **Identify** the force (or force component) that provides the centripetal force.
2. **Write** the equation of motion towards the centre: $F_{\text{centripetal}} = \frac{mv^2}{r} = mr\omega^2$.
3. **Impose** the physical limit (maximum friction, maximum tension, etc.) to find the condition for the motion to be possible.

4.1 Vehicles Rounding a Flat (Unbanked) Curve

Intuition. Every driver in Douala or Bamenda knows that you must slow down before a sharp bend, especially when the road is wet. Why? Because on a flat curve, the only horizontal force available to pull the vehicle towards the centre of the circle is the **static friction** between the tyres and the road surface. If the required centripetal force exceeds the maximum available friction, the vehicle skids outwards.

Analysis. Consider a vehicle of mass m rounding a flat curve of radius r at constant speed v . The forces acting on it (viewed from behind) are:


- the weight $W = mg$, vertically downwards;
- the normal reaction R of the road, vertically upwards;
- the friction force f , horizontal, pointing towards the centre of the curve — this is the centripetal force.

Vertically there is no acceleration, so $R = mg$. Horizontally, Newton's second law gives

$$f = \frac{mv^2}{r}.$$

But friction is limited by $f \leq \mu R = \mu mg$, where μ is the coefficient of static friction between tyres and road (static because the tyre does not slide relative to the road at the contact patch). The motion is therefore possible only if

$$\frac{mv^2}{r} \leq \mu mg.$$



Free-body diagram of a vehicle on a flat curve (viewed from behind). Friction f towards the centre supplies the centripetal force; vertically $R = mg$.

PROPERTY Maximum safe speed on a flat unbanked curve

A vehicle of mass m can round a flat curve of radius r without skidding, the coefficient of static friction between tyres and road being μ , only if its speed satisfies

$$v \leq v_{\max} = \sqrt{\mu rg}.$$

The proof is examinable: from $\frac{mv^2}{r} \leq \mu mg$, cancel m and rearrange to $v^2 \leq \mu rg$.

WARNING The mass cancels — and friction is the hero

Two classic traps: (1) Students keep the mass m in the final answer. It cancels: a heavy lorry and a light car have the same maximum safe speed on the same curve (provided μ is the same). (2) Students say the car is “thrown outwards by centrifugal force”. There is no outward force on the car in an inertial frame; the car skids because friction is insufficient to bend its natural straight-line motion into a circle.

WORKED EXAMPLE 9 Maximum speed on a wet road

A car rounds a flat curve of radius 50 m. The coefficient of static friction between the tyres and the wet road is 0.4. Taking $g = 10 \text{ m s}^{-2}$, find the maximum speed at which the car can negotiate the curve without skidding.

SOLUTION


Solution. The friction provides the centripetal force. At the limiting speed $\frac{mv_{\max}^2}{r} = \mu mg$, so

$$v_{\max} = \sqrt{\mu rg} = \sqrt{0.4 \times 50 \times 10} = \sqrt{200} \approx 14.1 \text{ m s}^{-1}.$$

Converting to km h^{-1} : $14.1 \times 3.6 \approx 50.8 \text{ km h}^{-1}$. The driver must enter the bend below this speed.

4.2 Belt and Pulley Systems

Intuition. In a grinding mill, a sewing machine, or a car's alternator drive, a motor turns a small pulley connected by a belt to a larger pulley. The belt does not stretch and does not slip, so every point of the belt moves with the same linear speed v . Consequently the rim of each pulley moves at that same speed v — but since the radii differ, the angular speeds differ.



Two pulleys joined by an open belt. The belt imposes the same linear speed v on both rims, so $\omega_1 r_1 = \omega_2 r_2$: the smaller pulley spins faster. Both rotate in the same sense.

METHOD Solving belt/pulley problems

1. Identify the radii r_1, r_2 and the given angular speed (convert rpm to rad s^{-1} using $\omega = \frac{2\pi N}{60}$ if needed).
2. Set the belt speeds equal: the rim of each pulley moves at the belt's speed, so

$$\omega_1 r_1 = \omega_2 r_2.$$

3. Solve for the unknown angular speed, then convert back to rpm if required ($N = \frac{60\omega}{2\pi}$).
4. If a linear (belt) speed is asked, compute $v = r\omega$ on either pulley — both give the same value; use this as a check.

WORKED EXAMPLE 10 Grinding mill pulleys

A motor pulley of radius 5 cm rotates at 1200 rpm and drives, by a belt, a mill pulley of radius 20 cm. Find (a) the angular speed of the mill pulley in rad s^{-1} , (b) the linear speed of the belt.

SOLUTION

Solution. (a) Convert the motor speed: $\omega_1 = \frac{2\pi \times 1200}{60} = 40\pi \text{ rad s}^{-1}$. Equal belt speeds give

$$\omega_2 = \frac{\omega_1 r_1}{r_2} = \frac{40\pi \times 5}{20} = 10\pi \approx 31.4 \text{ rad s}^{-1}.$$

(b) Belt speed: $v = r_1 \omega_1 = 0.05 \times 40\pi = 2\pi \approx 6.28 \text{ m s}^{-1}$. Check with the other pulley: $v = r_2 \omega_2 = 0.20 \times 10\pi = 2\pi \text{ m s}^{-1}$. ✓

4.3 Gears in Contact

Two gear wheels meshing directly (no belt) behave similarly, with one essential difference: at the point of contact the teeth must not slide over each other, so the **tangential speeds** of the two rims at the contact point are equal in magnitude:

$$\omega_1 r_1 = \omega_2 r_2 \quad (\text{gears in contact}).$$

However, unlike belt-driven pulleys which rotate in the same sense (for an open belt), meshing gears rotate in opposite senses. Also, since the numbers of teeth are proportional to the radii, one often writes $\omega_1 N_1 = \omega_2 N_2$ where N_1, N_2 are the numbers of teeth.

EXAMPLE Bicycle gears

On a bicycle, the chain plays the role of the belt: the front chainring and the rear sprocket have the same chain (linear) speed. A large front ring with a small rear sprocket gives a high rear-wheel angular speed — the “high gear” used on the flat roads of the Ndop plain.

4.4 Fairground Rides: the Rotor (“Wall of Death”)

Intuition. In the rotor ride, people stand against the inner wall of a large spinning cylinder; the floor is then lowered, yet nobody falls. What holds them up? The wall pushes each person hor-

izontally inwards — this normal reaction R is the centripetal force. Friction between the person and the wall then balances the weight.

Analysis. For a person of mass m in a cylinder of radius r spinning at angular speed ω :

- Horizontally (towards the centre): the normal reaction R provides the centripetal force: $R = m\omega^2 r$.
- Vertically (no falling): friction f acts upwards, balancing weight: $f = mg$. The maximum available friction is $f_{\max} = \mu R$, where μ is the coefficient of static friction between clothing and wall.

For the person not to slip down, we need $mg \leq \mu R = \mu m\omega^2 r$, giving the condition

$$\omega \geq \sqrt{\frac{g}{\mu r}}.$$

Note the inequality direction: the ride must spin fast enough. The faster it spins, the larger R , the larger the available friction.

WORKED EXAMPLE 11 Minimum spin rate of a rotor

A rotor has radius 2.5 m and the coefficient of static friction between clothing and wall is 0.4. Taking $g = 10 \text{ m s}^{-2}$, find the minimum angular speed for riders to stay pinned when the floor drops.

SOLUTION

Solution. The limiting condition is $\mu R = mg$ with $R = m\omega^2 r$:

$$\omega_{\min} = \sqrt{\frac{g}{\mu r}} = \sqrt{\frac{10}{0.4 \times 2.5}} = \sqrt{10} \approx 3.16 \text{ rad s}^{-1}.$$

$$\text{In revolutions per minute: } N = \frac{60\omega}{2\pi} = \frac{60 \times 3.16}{2\pi} \approx 30.2 \text{ rpm.}$$

4.5 Objects on a Rotating Turntable

Intuition. Place a coin on a record player turntable. Near the centre it rotates with the disc; far from the centre it flies off. Why? The coin moves in a circle because **static friction** with the disc pulls it towards the centre. The required centripetal force $m\omega^2 r$ grows with r and with ω^2 , but friction is capped at μmg .

Condition. No slipping requires

$$m\omega^2 r \leq \mu mg \quad \Longleftrightarrow \quad \omega \leq \sqrt{\frac{\mu g}{r}}.$$

Equivalently, at a given ω , the coin stays in place only if $r \leq \frac{\mu g}{\omega^2}$.

WARNING Static friction, and the direction of the inequality

In turntable problems the friction is static (the coin does not slide on the disc while rotating with it); slipping starts exactly when $mr\omega^2$ exceeds μmg . Do not confuse this with the rotor, where a minimum ω is required: on a turntable there is a maximum ω . Also note that $\omega_{\max}$ decreases as r increases — objects near the rim slip first.

WORKED EXAMPLE 12 Coin on a turntable

A coin is placed 8 cm from the centre of a turntable; the coefficient of static friction is 0.5 and $g = 10 \text{ m s}^{-2}$. (a) Find the greatest angular speed for which the coin does not slip. (b) The turntable spins at 60 rpm; find the greatest distance from the centre at which the coin can sit without slipping.

SOLUTION

Solution. (a) Limiting condition $mr\omega^2 = \mu mg$:

$$\omega_{\max} = \sqrt{\frac{\mu g}{r}} = \sqrt{\frac{0.5 \times 10}{0.08}} = \sqrt{62.5} \approx 7.91 \text{ rad s}^{-1}.$$

(b) $\omega = \frac{2\pi \times 60}{60} = 2\pi \text{ rad s}^{-1}$. Then

$$r_{\max} = \frac{\mu g}{\omega^2} = \frac{0.5 \times 10}{(2\pi)^2} = \frac{5}{4\pi^2} \approx 0.127 \text{ m} = 12.7 \text{ cm}.$$

4.6 Satellites in Circular Orbit (Extension)**DID YOU KNOW?** Orbital motion — the same method

For a satellite of mass m in a circular orbit of radius r around the Earth, the centripetal force is supplied by **gravity**: $F = \frac{GMm}{r^2}$, where M is the Earth's mass. Equating with the centripetal requirement,

$$\frac{GMm}{r^2} = \frac{mv^2}{r} \implies v = \sqrt{\frac{GM}{r}}.$$

The satellite's mass cancels: orbital speed depends only on the orbit radius. Larger orbits mean slower satellites. This is why communication satellites that must hover over one point of the equator (geostationary orbit, period 24 h) sit at a very precise, large radius ($\approx 42\,000 \text{ km}$ from Earth's centre). The detailed study belongs to the Gravitation chapter, but the structure — identify the force provider, equate to mv^2/r , solve — is exactly the method of this chapter.

4.7 Bonus Extension: Banking of Roads

DID YOU KNOW? Why are some curves tilted?

On fast highways and velodromes, curves are banked: the outer edge is raised. The normal reaction then has a horizontal component pointing towards the centre, which helps (or even replaces) friction. For a vehicle taking a banked curve at the “design speed” with no friction needed, resolving forces gives

$$\tan \theta = \frac{v^2}{rg},$$

where θ is the banking angle. Derivation: vertically $R \cos \theta = mg$, horizontally $R \sin \theta = \frac{mv^2}{r}$; divide the two equations. This result appears in some GCE papers as an extension — treat it as a bonus. The core syllabus result remains $v_{\max} = \sqrt{\mu rg}$ for flat curves.

4.8 Consolidation Exercises

EXERCISE 4 Mixed practice

1. A car of mass 900 kg rounds a flat bend of radius 40 m at 15 m s^{-1} . (a) Calculate the centripetal force required. (b) If $\mu = 0.6$ and $g = 10 \text{ m s}^{-2}$, does the car skid?
2. A belt connects a pulley of radius 6 cm rotating at 900 rpm to a pulley of radius 15 cm. Find the angular speed of the second pulley in rpm and in rad s^{-1} , and the speed of the belt.
3. A small block rests 20 cm from the axis of a horizontal turntable with $\mu = 0.4$. Find the maximum rotation rate in rpm for which the block does not slip (take $g = 10 \text{ m s}^{-2}$).
4. In a rotor of radius 3 m, what minimum angular speed pins a rider to the wall if $\mu = 0.5$? Express your answer in rad s^{-1} and rpm.

SOLUTION Mixed practice

1. (a) $F = \frac{mv^2}{r} = \frac{900 \times 15^2}{40} = 5062.5 \text{ N}$. (b) Maximum friction available: $\mu mg = 0.6 \times 900 \times 10 = 5400 \text{ N} > 5062.5 \text{ N}$, so the car does not skid (but it is close to the limit; indeed $v_{\max} = \sqrt{0.6 \times 40 \times 10} = \sqrt{240} \approx 15.5 \text{ m s}^{-1}$).
2. Equal belt speeds: $\omega_2 = \omega_1 \frac{r_1}{r_2} = 900 \times \frac{6}{15} = 360 \text{ rpm}$, i.e. $\omega_2 = \frac{2\pi \times 360}{60} = 12\pi \approx 37.7 \text{ rad s}^{-1}$. Belt speed: $v = r_2 \omega_2 = 0.15 \times 12\pi = 1.8\pi \approx 5.65 \text{ m s}^{-1}$.

$$3. \omega_{\max} = \sqrt{\frac{\mu g}{r}} = \sqrt{\frac{0.4 \times 10}{0.20}} = \sqrt{20} \approx 4.47 \text{ rad s}^{-1}, \text{ i.e. } N = \frac{60 \times 4.47}{2\pi} \approx 42.7 \text{ rpm.}$$

$$4. \omega_{\min} = \sqrt{\frac{g}{\mu r}} = \sqrt{\frac{10}{0.5 \times 3}} = \sqrt{\frac{20}{3}} \approx 2.58 \text{ rad s}^{-1}, \text{ i.e. about } 24.6 \text{ rpm.}$$

KEY POINTS Key points of this section

- In every application, first identify what provides the centripetal force, then write $F = \frac{mv^2}{r} = mr\omega^2$ and impose the physical limit.
- Flat curve: friction provides F ; $v_{\max} = \sqrt{\mu rg}$ (mass cancels).
- Belt/pulleys and gears: equal tangential speed, $\omega_1 r_1 = \omega_2 r_2$; gears rotate in opposite senses, open-belt pulleys in the same sense.
- Rotor: normal reaction provides F ; not slipping requires $\omega \geq \sqrt{g/(\mu r)}$.
- Turntable: static friction provides F ; no slipping requires $\omega \leq \sqrt{\mu g/r}$.
- Satellites: gravity provides F ; $v = \sqrt{GM/r}$ (extension).
- Master the conversion $\omega = \frac{2\pi N}{60}$ between rpm and rad s^{-1} — it appears in nearly every GCE question on this topic.

5 THE CONICAL PENDULUM: CONCEPT AND FORCES

In the previous section we applied the relations $v = r\omega$, $a = \frac{v^2}{r} = r\omega^2$ and $F = \frac{mv^2}{r}$ to vehicles on roundabouts, satellites and rotating machinery. In every case, the source of the centripetal force was different: friction for a car, gravity for a satellite, tension for a stone on a string. We now study one of the most beautiful and most frequently examined situations in circular motion: the **conical pendulum**. It is the perfect illustration of how a single force — the tension in a string — can be split into two components, one balancing the weight and the other supplying the centripetal force. Mastering it is essential, because the GCE Advanced Level examiners return to it again and again.

5.1 What is a Conical Pendulum?

An observation to begin with.

Take a bunch of keys tied to a cord, hold the free end of the cord above your head and set the keys moving so that they travel round and round in a horizontal circle. You will notice something remarkable: the cord is not vertical, and it is not horizontal either. It makes a fixed angle with the

vertical, and as the keys go round, the cord sweeps out the surface of an upside-down **cone**. The faster you whirl the keys, the wider the angle and the higher the keys rise. This simple toy, which any student in Yaoundé or Bamenda can build in a minute, contains all the physics of this section.

DEFINITION Conical pendulum

A **conical pendulum** consists of a small heavy body (the **bob**) of mass m , attached to a fixed support by a light inextensible string of length l , and set in motion so that the bob describes a horizontal circle with uniform speed while the string sweeps out the surface of a cone whose apex is the support. The constant angle θ between the string and the downward vertical is called the **semi-vertical angle** of the cone.

WARNING Do not confuse with the simple pendulum


A simple pendulum swings back and forth in a vertical plane; its speed is not constant and the motion is not circular motion with uniform speed. A conical pendulum moves in a horizontal circle at constant speed. The two devices look similar but obey completely different physics.

DID YOU KNOW? Conical pendulums around us

The conical pendulum is far more than a classroom curiosity. The swing rides (“flying chairs”) at amusement fairs are giant conical pendulums: each chair hangs from a chain and rises as the carousel spins faster. Historically, James Watt used a pair of conical-pendulum balls — the centrifugal governor — to regulate the speed of steam engines: when the engine ran too fast, the balls rose and closed a valve. The same principle is still used in some engine governors today.

5.2 Geometry of the Set-up

Before writing any equation of motion, we must describe the geometry precisely. Let the string have length l and make a constant angle θ with the vertical. The bob moves on a horizontal circle of radius r , at a constant vertical distance h below the support.



A conical pendulum: the string of length l sweeps out a cone of semi-vertical angle θ ; the bob describes a horizontal circle of radius r at depth h below the support.

From the right-angled triangle formed by the support, the centre O of the circle and the bob, we read off immediately:

PROPERTY Geometry of the conical pendulum

If the string has length l and makes an angle θ with the vertical, then the radius of the circle and the depth of the bob below the support are

$$r = l \sin \theta \quad \text{and} \quad h = l \cos \theta.$$

WARNING The radius is $r = l \sin \theta$, not l

This is the single most common error at the GCE. The bob does not move on a circle of radius l : it moves on a horizontal circle whose radius is only $l \sin \theta$. Whenever you write $a = \frac{v^2}{r}$ or $F = mr\omega^2$, the r must be $l \sin \theta$. Writing l instead of $l \sin \theta$ destroys the whole problem.

5.3 Forces Acting on the Bob: the Free-Body Diagram

How many forces act on the bob?


Students often want to add a third force — an “outward” or “centrifugal” force, or a separate “centripetal force” drawn alongside the others. Both are wrong. Look at the actual situation: the bob is in contact with nothing but the string, and it is attracted by the Earth. That is all.

PROPERTY The two forces on the bob

At every instant, exactly two forces act on the bob:

- its **weight** $\vec{W} = m\vec{g}$, acting vertically downwards;
- the **tension** $\vec{T}$ of the string, acting along the string towards the support.

There is no additional “centripetal force”: the centripetal force is not a new force, it is the role played by the horizontal component of the tension.



Free-body diagram of the bob: the tension is resolved into a vertical component $T \cos \theta$ (balancing the weight) and a horizontal component $T \sin \theta$ (the centripetal force).

5.4 Resolving the Tension and Writing the Equations of Motion

Since the bob moves in a horizontal circle, its acceleration is horizontal, directed towards the centre O , of magnitude $\frac{v^2}{r} = r\omega^2$. Vertically, the bob neither rises nor falls: its vertical acceleration is zero. We resolve the tension $\vec{T}$ along these two natural directions:

- **vertical component:** $T \cos \theta$ (upwards);
- **horizontal component:** $T \sin \theta$ (towards the centre).

Applying Newton's second law in each direction:

Vertically (no acceleration, forces balance):

$$T \cos \theta = mg.$$

Horizontally (the resultant provides the centripetal force):

$$T \sin \theta = \frac{mv^2}{r} = mr\omega^2.$$

PROPERTY Equations of the conical pendulum — examinable

For a conical pendulum of semi-vertical angle θ , with a bob of mass m moving at speed v on a circle of radius $r = l \sin \theta$:

$$T \cos \theta = mg \quad \text{and} \quad T \sin \theta = \frac{mv^2}{r} = mr\omega^2.$$

Dividing the second equation by the first eliminates T and m , giving the key relation

$$\tan \theta = \frac{v^2}{rg} = \frac{r\omega^2}{g}.$$

This derivation is examinable: you must be able to produce it from a clear free-body diagram and Newton's second law.

METHOD Solving any conical pendulum problem

1. Draw the free-body diagram: only the weight mg (down) and the tension T (along the string).
2. Write the geometry: $r = l \sin \theta$.
3. Resolve the tension: vertical component $T \cos \theta$, horizontal component $T \sin \theta$.
4. Write $T \cos \theta = mg$ (vertical equilibrium) and $T \sin \theta = \frac{mv^2}{r}$ (centripetal force).
5. Divide to get $\tan \theta = \frac{v^2}{rg}$, or solve the system for the unknown requested (T , v , θ , ω).

WARNING The bob is NOT in equilibrium

The vertical forces balance, so there is no vertical acceleration — but the bob is certainly not in equilibrium! The horizontal resultant $T \sin \theta$ is non-zero and permanently pulls the bob towards the centre: this is precisely the centripetal force that bends the path into a circle. If all forces balanced, the bob would move in a straight line (Newton's first law). Likewise, never draw an outward “centrifugal force”: in the inertial frame of the ground, no such force exists.

WORKED EXAMPLE 13 A bunch of keys as a conical pendulum

A student ties a bunch of keys of mass $m = 0.20 \text{ kg}$ to a cord of length $l = 0.80 \text{ m}$ and whirls

it so that the keys describe a horizontal circle, the cord making an angle $\theta = 30^\circ$ with the vertical. Take $g = 9.81 \text{ m s}^{-2}$.

1. Find the tension in the cord.
2. Find the speed of the keys.
3. Find the angular speed of the keys.

SOLUTION

Solution. The free-body diagram gives the two standard equations, with $r = l \sin \theta$.

$$r = l \sin \theta = 0.80 \sin 30^\circ = 0.80 \times 0.5 = 0.40 \text{ m.}$$

1. Tension. From the vertical equation:

$$T \cos \theta = mg \implies T = \frac{mg}{\cos \theta} = \frac{0.20 \times 9.81}{\cos 30^\circ} = \frac{1.962}{0.8660} \approx 2.27 \text{ N.}$$

2. Speed. From the key relation:

$$\tan \theta = \frac{v^2}{rg} \implies v^2 = rg \tan \theta = 0.40 \times 9.81 \times \tan 30^\circ = 0.40 \times 9.81 \times 0.5774 \approx 2.266,$$

$$v \approx 1.51 \text{ m s}^{-1}.$$

3. Angular speed. Using $v = r\omega$:

$$\omega = \frac{v}{r} = \frac{1.51}{0.40} \approx 3.77 \text{ rad s}^{-1}.$$

Check: $T \sin \theta = 2.27 \times 0.5 = 1.13 \text{ N}$ and $\frac{mv^2}{r} = \frac{0.20 \times 2.266}{0.40} = 1.13 \text{ N}$. ✓ The horizontal equation is satisfied.

EXAMPLE Reading the physics from the key relation

The relation $\tan \theta = \frac{r\omega^2}{g}$ tells us something physically important: the faster the bob rotates, the larger the angle θ . Indeed, with $r = l \sin \theta$, the relation becomes

$$\tan \theta = \frac{l \sin \theta \omega^2}{g} \implies \cos \theta = \frac{g}{l\omega^2},$$

so as ω increases, $\cos \theta$ decreases and θ grows towards 90° . This is exactly why the chairs of a swing ride rise when the carousel speeds up, and why the balls of Watt's governor lifted when the engine ran too fast. Note also that $\cos \theta \leq 1$ requires $\omega^2 \geq \frac{g}{l}$: below this angular speed, no conical motion is possible and the string simply hangs vertically.

EXERCISE 5 Practice

A small ball of mass 0.15 kg is attached to a string of length 1.2 m fixed at its upper end. The ball moves in a horizontal circle with angular speed $\omega = 3.0 \text{ rad s}^{-1}$. Take $g = 9.81 \text{ m s}^{-2}$.

1. Show that $\cos \theta = \frac{g}{l\omega^2}$ and deduce the semi-vertical angle θ .
2. Calculate the radius of the circle and the tension in the string.
3. Calculate the linear speed of the ball.

SOLUTION Exercise 1

1. From $T \cos \theta = mg$ and $T \sin \theta = mr\omega^2$ with $r = l \sin \theta$:

$$\frac{T \sin \theta}{T \cos \theta} = \tan \theta = \frac{l \sin \theta \omega^2}{g} \implies \cos \theta = \frac{g}{l\omega^2} = \frac{9.81}{1.2 \times 9.0} = 0.908,$$

so $\theta \approx 24.7^\circ$. 2. $r = l \sin \theta = 1.2 \times \sin 24.7^\circ \approx 0.50 \text{ m}$; $T = \frac{mg}{\cos \theta} = \frac{0.15 \times 9.81}{0.908} \approx 1.62 \text{ N}$. 3. $v = r\omega = 0.50 \times 3.0 = 1.50 \text{ m s}^{-1}$.

KEY POINTS Key points of this section

- A conical pendulum: a bob describing a horizontal circle at constant speed while the string sweeps a cone of semi-vertical angle θ .
- Geometry: $r = l \sin \theta$, $h = l \cos \theta$ — never confuse r with l .
- Only two forces act on the bob: weight mg and tension T .
- Resolve the tension: $T \cos \theta = mg$ (vertical balance) and $T \sin \theta = \frac{mv^2}{r} = mr\omega^2$ (centripetal force).
- Key relation: $\tan \theta = \frac{v^2}{rg} = \frac{r\omega^2}{g}$, equivalently $\cos \theta = \frac{g}{l\omega^2}$.
- The bob is not in equilibrium: it accelerates towards the centre. There is no outward force.


Now that the forces on the conical pendulum are fully understood, a natural question arises: how long does the bob take to complete one revolution? In the next section we use the equations established here to derive the formula for the period of the conical pendulum and to compare it with the period of the simple pendulum — a classic GCE examination question.

6 PERIOD OF THE CONICAL PENDULUM: DERIVATION AND APPLICATIONS

In the previous section we analysed the forces acting on a conical pendulum and established the two fundamental equations of motion: the vertical equilibrium $T \cos \theta = mg$ and the horizontal centripetal equation $T \sin \theta = m\omega^2 r$. We now harvest the fruit of that work. By combining these equations we shall derive one of the most elegant results of circular motion: the period of a conical pendulum depends only on the vertical height of the support above the plane of the circle. This result is a favourite of GCE examiners, both for its derivation and for its applications.

6.1 From the Equations of Motion to the Angular Speed

Recall the situation: a bob of mass m is attached to a light inextensible string of length l fixed at a point S . The bob describes a horizontal circle of radius r with constant angular speed ω , the string making a constant angle θ with the vertical.



The geometry of the conical pendulum: the vertical distance from the support S to the plane of the circle is $h = l \cos \theta$, and the radius of the circle is $r = l \sin \theta$.

Dividing the horizontal equation by the vertical equation eliminates the tension:

$$\frac{T \sin \theta}{T \cos \theta} = \frac{m\omega^2 r}{mg} \implies \tan \theta = \frac{\omega^2 r}{g}.$$

Now substitute the geometric relation $r = l \sin \theta$:

$$\frac{\sin \theta}{\cos \theta} = \frac{\omega^2 l \sin \theta}{g}.$$

Since $\theta \neq 0$ during the motion (the bob genuinely moves in a circle), we have $\sin \theta \neq 0$ and we may divide both sides by $\sin \theta$:

$$\frac{1}{\cos \theta} = \frac{\omega^2 l}{g} \implies \omega^2 = \frac{g}{l \cos \theta}.$$

But from the geometry of the figure, $l \cos \theta = h$, the vertical distance from the support to the plane of the circle. Hence

$$\boxed{\omega^2 = \frac{g}{l \cos \theta} = \frac{g}{h}}.$$

WARNING Why we may divide by $\sin \theta$

The step “divide by $\sin \theta$ ” is legitimate only because the pendulum is actually revolving, so $\theta > 0$. If $\theta = 0$ the bob simply hangs at rest and there is no circular motion to analyse. Mentioning this in an examination shows the examiner that you understand the mathematics, not just the algebra.

6.2 The Period of the Conical Pendulum**PROPERTY** Period of a conical pendulum (proof examinable)

A conical pendulum whose bob moves in a horizontal circle at a vertical distance h below the support has period

$$T = \frac{2\pi}{\omega} = 2\pi \sqrt{\frac{l \cos \theta}{g}} = 2\pi \sqrt{\frac{h}{g}},$$

where l is the length of the string, θ the angle the string makes with the vertical, and $h = l \cos \theta$. The derivation of this result is examinable at the GCE Advanced Level.

Proof. Since the bob completes one revolution (2π radians) in one period T , the angular speed is $\omega = \frac{2\pi}{T}$. Substituting into $\omega^2 = \frac{g}{h}$:

$$\frac{4\pi^2}{T^2} = \frac{g}{h} \implies T^2 = \frac{4\pi^2 h}{g} \implies T = 2\pi \sqrt{\frac{h}{g}}.$$

Since $h = l \cos \theta$, the equivalent form $T = 2\pi \sqrt{\frac{l \cos \theta}{g}}$ follows immediately. ■

KEY POINTS The remarkable feature of the formula

The period $T = 2\pi \sqrt{h/g}$ depends only on:

- the vertical height h of the support above the plane of the circle;
- the acceleration due to gravity g .

It does not depend on the mass m of the bob, nor directly on the length l or the angle θ separately. Two conical pendulums of different lengths, different masses and different angles have exactly the same period provided their bobs revolve in the same horizontal plane (same h).

METHOD Derivation checklist — learn each step

1. Draw the force diagram: weight mg vertically down, tension T along the string.
2. Resolve vertically (no vertical acceleration): $T \cos \theta = mg$.
3. Resolve horizontally towards the centre (Newton's second law, centripetal force):
 $T \sin \theta = m\omega^2 r$.
4. Divide the two equations to eliminate T : $\tan \theta = \frac{\omega^2 r}{g}$.
5. Substitute the geometry $r = l \sin \theta$ and simplify: $\omega^2 = \frac{g}{l \cos \theta} = \frac{g}{h}$.
6. Use $\omega = \frac{2\pi}{T}$ and solve for the period: $T = 2\pi\sqrt{\frac{h}{g}}$.

WARNING Period T versus tension T — a classic trap

The same letter T is traditionally used for both the period (a time, in seconds) and the tension (a force, in newtons). In your examination script, never write “ $T = 2\pi\sqrt{h/g}$ ” and “ $T = mg / \cos \theta$ ” in the same piece of work without comment — the examiner cannot tell which is which. Use τ (or write “period” and “tension” in words) to distinguish them. Confusing the two costs marks every year.

6.3 The Tension in the String**PROPERTY** Tension in a conical pendulum

The tension in the string of a conical pendulum is

$$T = \frac{mg}{\cos \theta} = m\omega^2 l.$$

Consequently, the tension increases as θ increases (equivalently, as the rotation gets faster).

Justification. From vertical equilibrium, $T \cos \theta = mg$, so $T = \frac{mg}{\cos \theta}$. For the second form, the horizontal equation gives $T \sin \theta = m\omega^2 r = m\omega^2 l \sin \theta$, and dividing by $\sin \theta \neq 0$ yields $T = m\omega^2 l$. The two expressions are consistent: substituting $\omega^2 = \frac{g}{l \cos \theta}$ into $m\omega^2 l$ gives $\frac{mg}{\cos \theta}$.

Since $\cos \theta$ decreases as θ grows from 0 to 90° , the tension $\frac{mg}{\cos \theta}$ increases without bound.

This is why the string of a fast-spinning toy or the chains of a swing carousel are under great stress.

6.4 Limiting Cases

Case $\theta \rightarrow 0$. Then $\cos \theta \rightarrow 1$, so $h \rightarrow l$ and

$$T \rightarrow 2\pi\sqrt{\frac{l}{g}},$$

which is exactly the period of a simple pendulum of length l oscillating with small amplitude. This is physically reasonable: when the cone is very narrow, the bob barely leaves the vertical and the motion resembles a gentle swing. (This is a qualitative remark; the simple pendulum formula itself is established properly in the study of simple harmonic motion.)


Case $\theta \rightarrow 90^\circ$. Then $\cos \theta \rightarrow 0$, so the tension $T = \frac{mg}{\cos \theta} \rightarrow \infty$ and the angular speed $\omega = \sqrt{\frac{g}{l \cos \theta}} \rightarrow \infty$. A perfectly horizontal string is therefore impossible in practice: no finite tension can make the string horizontal, because some vertical component of tension is always needed to balance the weight.

DID YOU KNOW? Why the swing carousel tilts outwards

At amusement parks, the chairs of a swing carousel rise and tilt outwards as the ride speeds up. Each chair and rider behaves like a conical pendulum: from $\tan \theta = \frac{\omega^2 r}{g}$, a larger ω requires a larger θ . The chains can never become horizontal, however fast the ride spins — exactly as the theory predicts.

6.5 Graphical Interpretation: T against $\sqrt{h}$

Since $T = \frac{2\pi}{\sqrt{g}}\sqrt{h}$, a graph of the period T against $\sqrt{h}$ is a straight line through the origin with gradient $\frac{2\pi}{\sqrt{g}}$. Equivalently, $T^2 = \frac{4\pi^2}{g}h$, so a graph of T^2 against h is a straight line through the origin of gradient $\frac{4\pi^2}{g}$.



Period T plotted against $\sqrt{h}$ for a conical pendulum: a straight line through the origin of gradient $2\pi/\sqrt{g} \approx 2.006 \text{ s m}^{-1/2}$ (taking $g = 9.81 \text{ m s}^{-2}$).

EXPERIMENT Experimental determination of g with a conical pendulum

This provides an excellent practical method of measuring g , in the spirit of GCE practical-style questions.

1. Suspend a bob on a string of measured length l and set it revolving in a horizontal circle (a small horizontal push starts the motion).
2. Time $n = 20$ complete revolutions with a stopwatch; the period is $T = t/n$. Repeat and average.
3. Measure the vertical height h from the support to the plane of the circle (or compute $h = l \cos \theta$ from a measured θ).
4. Repeat for several values of h (vary l or the rotation speed).
5. Plot T^2 against h : since $T^2 = \frac{4\pi^2}{g}h$, the graph is a straight line through the origin of gradient $\frac{4\pi^2}{g}$. Hence $g = \frac{4\pi^2}{\text{gradient}}$.

Precautions: keep the circle truly horizontal, time many revolutions to reduce reaction-time error, and ensure the angle θ stays constant during timing.

6.6 Applications and Worked Examples

The formulas derived above answer all the standard questions:

- **Finding θ given the rotation rate:** from $\cos \theta = \frac{g}{\omega^2 l}$, compute θ .

- Finding the speed of the bob: $v = \omega r = \omega l \sin \theta$.
- Finding the tension: $T = \frac{mg}{\cos \theta} = m\omega^2 l$.
- Finding the period: $T = 2\pi\sqrt{\frac{h}{g}}$.

WORKED EXAMPLE 14 GCE-style worked example

A small bob of mass 0.200 kg is attached to a light inextensible string of length $l = 1.5$ m fixed at a point S . The bob moves in a horizontal circle with constant speed, the string making an angle $\theta = 30^\circ$ with the vertical. Taking $g = 9.81 \text{ m s}^{-2}$, find:

1. the tension in the string;
2. the angular speed ω of the bob;
3. the linear speed v of the bob;
4. the period of revolution.

SOLUTION

Solution.

1. Tension. Vertical equilibrium gives $T \cos \theta = mg$, so

$$T = \frac{mg}{\cos \theta} = \frac{0.200 \times 9.81}{\cos 30^\circ} = \frac{1.962}{0.8660} \approx 2.27 \text{ N.}$$

2. Angular speed. Using $\omega^2 = \frac{g}{l \cos \theta}$:

$$\omega^2 = \frac{9.81}{1.5 \times \cos 30^\circ} = \frac{9.81}{1.299} = 7.552 \implies \omega \approx 2.75 \text{ rad s}^{-1}.$$

3. Linear speed. The radius of the circle is $r = l \sin \theta = 1.5 \times \sin 30^\circ = 0.75$ m. Hence

$$v = \omega r = 2.75 \times 0.75 \approx 2.06 \text{ m s}^{-1}.$$

4. Period. The height is $h = l \cos \theta = 1.5 \times 0.8660 = 1.299$ m, so

$$T = 2\pi\sqrt{\frac{h}{g}} = 2\pi\sqrt{\frac{1.299}{9.81}} = 2\pi\sqrt{0.1324} \approx 2.29 \text{ s.}$$

Check: $T = \frac{2\pi}{\omega} = \frac{2\pi}{2.75} \approx 2.29 \text{ s. Consistent.}$ ■

WORKED EXAMPLE 15 Finding the angle from the rotation rate

A conical pendulum has a string of length 0.80 m. The bob makes 60 revolutions per minute. Find the angle the string makes with the vertical. (Take $g = 9.81 \text{ m s}^{-2}$.)

SOLUTION

Solution. Convert the rotation rate: $60 \text{ rev min}^{-1} = 1 \text{ rev s}^{-1}$, so

$$\omega = 2\pi \times 1 = 2\pi \text{ rad s}^{-1}.$$

From $\omega^2 = \frac{g}{l \cos \theta}$:

$$\cos \theta = \frac{g}{\omega^2 l} = \frac{9.81}{(2\pi)^2 \times 0.80} = \frac{9.81}{31.58} = 0.3106.$$

Hence $\theta = \cos^{-1}(0.3106) \approx 71.9^\circ$. ■

WARNING Common mistakes in applications

- Forgetting to convert revolutions per minute into rad s^{-1} : multiply by $\frac{2\pi}{60}$.
- Using $r = l$ instead of $r = l \sin \theta$ for the radius of the circle.
- Using degrees instead of radians when applying $\omega = \frac{2\pi}{T}$ — angular speed formulas require radians.
- Writing $\omega^2 = \frac{g}{l \cos \theta}$ as $\omega = \frac{g}{l \cos \theta}$: do not drop the square root.
- Quoting $T = 2\pi\sqrt{l/g}$ (the simple pendulum formula) instead of $T = 2\pi\sqrt{l \cos \theta / g}$: the factor $\cos \theta$ is essential.

DID YOU KNOW? Exam tip — derivations earn full marks

The derivation of $T = 2\pi\sqrt{l/g}$ is one of the most frequently set “show that” questions in the mechanics papers. Examiners award marks for each justified step: the two resolutions, the division eliminating the tension, the substitution $r = l \sin \theta$, and the use of $\omega = 2\pi/T$. Reproduce the six-step checklist above with a clear force diagram, and state each physical principle you use (vertical equilibrium; Newton’s second law towards the centre). A bare formula with no justification earns almost nothing.

EXERCISE 6 Practice

1. A conical pendulum consists of a bob of mass 0.5 kg on a string of length 2.0 m. The bob revolves so that the string makes 40° with the vertical. Taking $g = 9.81 \text{ m s}^{-2}$, find the tension, the angular speed, the speed of the bob and the period.
2. Show that if a conical pendulum completes n revolutions per second, then $\cos \theta = \frac{g}{4\pi^2 n^2 l}$. Hence find the least possible value of n for a string of length 1.0 m, and explain what limits the rotation rate in practice.
3. In an experiment, a conical pendulum gives the following results: $h = 0.25 \text{ m}$, $T = 1.00 \text{ s}$. Use $T = 2\pi\sqrt{h/g}$ to estimate g .
4. Two conical pendulums have strings of lengths 1.0 m and 4.0 m. They revolve in the same horizontal plane, 0.50 m below their supports. Show that they have the same period, and find the angle each string makes with the vertical.

SOLUTION Exercise 1

1. Tension: $T = \frac{mg}{\cos \theta} = \frac{0.5 \times 9.81}{\cos 40^\circ} = \frac{4.905}{0.766} \approx 6.40 \text{ N}$. Angular speed: $\omega = \sqrt{\frac{g}{l \cos \theta}} = \sqrt{\frac{9.81}{2.0 \times 0.766}} = \sqrt{6.403} \approx 2.53 \text{ rad s}^{-1}$. Speed: $r = l \sin \theta = 2.0 \sin 40^\circ = 1.286 \text{ m}$, so $v = \omega r = 2.53 \times 1.286 \approx 3.25 \text{ m s}^{-1}$. Period: $h = l \cos \theta = 1.532 \text{ m}$, so $T = 2\pi\sqrt{\frac{1.532}{9.81}} \approx 2.48 \text{ s}$.
2. With $\omega = 2\pi n$, the relation $\omega^2 = \frac{g}{l \cos \theta}$ gives $4\pi^2 n^2 = \frac{g}{l \cos \theta}$, hence $\cos \theta = \frac{g}{4\pi^2 n^2 l}$. Since $\cos \theta \leq 1$, we need $n^2 \geq \frac{g}{4\pi^2 l}$, i.e. a minimum rate $n_{\min} = \frac{1}{2\pi}\sqrt{\frac{g}{l}} = \frac{1}{2\pi}\sqrt{9.81} \approx 0.50 \text{ rev s}^{-1}$ for $l = 1.0 \text{ m}$ (below this, the bob simply hangs vertically). There is no theoretical maximum, but as n increases, $\cos \theta \rightarrow 0$, $\theta \rightarrow 90^\circ$ and the tension $T = m\omega^2 l$ grows without bound until the string breaks — this is the practical limit.
3. From $T^2 = \frac{4\pi^2 h}{g}$; $g = \frac{4\pi^2 h}{T^2} = \frac{4\pi^2 \times 0.25}{1.00^2} = \pi^2 \approx 9.87 \text{ m s}^{-2}$.
4. The period depends only on h : $T = 2\pi\sqrt{\frac{0.50}{9.81}} \approx 1.42 \text{ s}$ for both pendulums, since both have $h = 0.50 \text{ m}$. From $\cos \theta = \frac{h}{l}$: for $l = 1.0 \text{ m}$, $\cos \theta = 0.50$, so $\theta = 60^\circ$; for $l = 4.0 \text{ m}$, $\cos \theta = 0.125$, so $\theta \approx 82.8^\circ$. The longer string hangs much closer to the horizontal, yet both periods are equal — a striking confirmation of the theory.

KEY POINTS Summary of the section

- Dividing the equations of motion gives $\tan \theta = \frac{\omega^2 r}{g}$; with $r = l \sin \theta$ this yields $\omega^2 =$

$$\frac{g}{l \cos \theta} = \frac{g}{h}.$$

- Period: $T = 2\pi\sqrt{\frac{l \cos \theta}{g}} = 2\pi\sqrt{\frac{h}{g}}$ — independent of the mass, depending only on the height h .
- Tension: $T = \frac{mg}{\cos \theta} = m\omega^2 l$, increasing with θ .
- Limits: $\theta \rightarrow 0$ recovers the simple-pendulum period $2\pi\sqrt{l/g}$; $\theta = 90^\circ$ is impossible.
- A graph of T against $\sqrt{h}$ (or T^2 against h) is a straight line through the origin — the basis of an experimental measurement of g .

7 ANGULAR AND LINEAR SPEED IN THE CONICAL PENDULUM; SYNTHESIS AND EXAM PRACTICE

In the previous section we derived the period of the conical pendulum, $T = 2\pi\sqrt{h/g}$, where $h = l \cos \theta$ is the vertical distance from the point of suspension to the plane of the circle. That formula hides a rich structure: the bob has two speeds (angular and linear), and both are completely determined by the geometry of the cone. In this final section we collect everything, express v and ω in terms of l , θ and g , learn how the cone responds when it is spun faster, and finish with a complete problem-solving strategy and timed GCE-style practice.

7.1 The Two Speeds of the Bob: A Recap

Imagine the bob of a conical pendulum, like a small stone on a string whirled above your head. Two different observers describe its motion:

- An observer looking down from above sees the bob sweeping out a circle of radius $r = l \sin \theta$. The radius vector rotates about the vertical axis with **angular speed** ω (in rad s^{-1}).
- An observer standing in the plane of the circle sees the bob moving along the circle with **linear speed** v (in m s^{-1}), tangential to the circle at every instant.

The two are linked by the fundamental relation of circular motion:

KEY POINTS The two speeds

For the bob of a conical pendulum moving on a circle of radius $r = l \sin \theta$:

$$v = r\omega = l\omega \sin \theta, \quad \omega = \frac{2\pi}{T} = 2\pi f.$$

The angular speed ω is the same for every point of the string; the linear speed v concerns the bob alone.

7.2 Expressing v and ω in Terms of the Geometry

Recall the two equations of motion obtained in Section 5 by resolving the tension S in the string (vertical equilibrium and horizontal centripetal force):

$$S \cos \theta = mg \quad (\text{vertical, no acceleration})$$

$$S \sin \theta = \frac{mv^2}{r} = mr\omega^2 \quad (\text{horizontal, towards the centre}).$$

Dividing the second equation by the first eliminates S and m :

$$\tan \theta = \frac{v^2}{rg} = \frac{r\omega^2}{g}.$$

This single relation is the key to the whole section. Solving it for v and for ω gives:

PROPERTY Speeds of the conical pendulum in terms of the geometry

For a conical pendulum of length l , semi-vertical angle θ , radius $r = l \sin \theta$ and height $h = l \cos \theta$:

$$v = \sqrt{rg \tan \theta} = \sqrt{gl \sin \theta \tan \theta} \quad \omega = \sqrt{\frac{g}{l \cos \theta}} = \sqrt{\frac{g}{h}}$$

Derivation (examinable). From $\tan \theta = v^2/(rg)$ we get $v^2 = rg \tan \theta$, hence $v = \sqrt{rg \tan \theta}$; substituting $r = l \sin \theta$ gives the second form. From $\tan \theta = r\omega^2/g$ with $r = l \sin \theta$: $\omega^2 = \frac{g \tan \theta}{l \sin \theta} = \frac{g \sin \theta}{l \sin \theta \cos \theta} = \frac{g}{l \cos \theta}$, so $\omega = \sqrt{g/(l \cos \theta)} = \sqrt{g/h}$.

Notice something remarkable: ω depends only on the vertical height h of the suspension point above the plane of the circle, not on the mass, nor directly on the radius. Two conical pendulums whose bobs circle in the same horizontal plane have the same angular speed, whatever their lengths.

A second consequence: since $\cos \theta \leq 1$, we have $\omega^2 = g/(l \cos \theta) \geq g/l$. A conical pendulum of length l can only exist for

$$\omega \geq \sqrt{\frac{g}{l}}.$$

Below this minimum angular speed the string simply hangs vertically ($\theta = 0$) and there is no circular motion at all.



WARNING Angle measured from the vertical

Throughout this chapter θ is the angle between the string and the vertical. If a problem gives the angle α between the string and the horizontal, convert first: $\theta = 90^\circ - \alpha$. Substituting α directly into $\tan \theta$ or $\cos \theta$ is one of the most frequent errors at the GCE.

7.3 Spinning Faster: How the Cone Widens

From $\omega = \sqrt{g/(l \cos \theta)}$ we read off the qualitative behaviour:

- If ω increases, then $\cos \theta$ must decrease, so θ increases: the string rises towards the horizontal.
- Then $r = l \sin \theta$ increases and $v = \sqrt{rg \tan \theta}$ increases even faster (both r and $\tan \theta$ grow).
- As $\omega \rightarrow \infty$, $\cos \theta \rightarrow 0$, i.e. $\theta \rightarrow 90^\circ$: the string can never become exactly horizontal at finite speed, because a horizontal string would have no vertical component of tension to support the weight.



Same string, two rotation rates: as ω increases, θ increases ($\theta_2 > \theta_1$), the circle widens (r increases) and the plane of the circle rises (h decreases).

7.4 Strategy for Mixed Problems

Typical GCE questions give you any two of $(l, \theta, \omega, v, T)$ and ask for the others. The toolbox contains exactly three independent relations:

$$\tan \theta = \frac{r\omega^2}{g}, \quad v = r\omega, \quad r = l \sin \theta \text{ (plus } \omega = 2\pi/T \text{)}.$$

METHOD Solving any conical pendulum problem

1. Draw the free-body diagram: weight mg down, tension S along the string; mark θ from the vertical.
2. Write the two resolved equations: $S \cos \theta = mg$ and $S \sin \theta = mr\omega^2$ (or mv^2/r).
3. Eliminate S by dividing: $\tan \theta = r\omega^2/g$.
4. Substitute the geometry $r = l \sin \theta$ and the data; solve for the unknown.
5. Convert if needed: $v = r\omega$, $T = 2\pi/\omega$.
6. Check units and that $\theta < 90^\circ$, ω in rad s^{-1} , and $\omega \geq \sqrt{g/l}$.

WORKED EXAMPLE 16 Mixed problem: given l and T

A conical pendulum consists of a bob of mass 0.4 kg on a light inextensible string of length 1.5 m . It describes a horizontal circle with period $T = 2.0 \text{ s}$. Take $g = 9.81 \text{ m s}^{-2}$. Find (a) the angular speed, (b) the semi-vertical angle, (c) the radius and linear speed of the bob, (d) the tension in the string.

SOLUTION

$$(a) \omega = \frac{2\pi}{T} = \frac{2\pi}{2.0} = \pi \approx 3.14 \text{ rad s}^{-1}.$$

$$(b) \text{ From } \omega^2 = \frac{g}{l \cos \theta}: \cos \theta = \frac{g}{l\omega^2} = \frac{9.81}{1.5\pi^2} = \frac{9.81}{14.80} = 0.663, \text{ so } \theta = \cos^{-1}(0.663) \approx 48.5^\circ.$$

$$(c) r = l \sin \theta = 1.5 \sin 48.5^\circ \approx 1.12 \text{ m}; \text{ then } v = r\omega = 1.12 \times 3.14 \approx 3.53 \text{ m s}^{-1}. \text{ Check with the other formula: } v = \sqrt{rg \tan \theta} = \sqrt{1.12 \times 9.81 \times 1.131} \approx 3.53 \text{ m s}^{-1}. \checkmark$$

$$(d) S = \frac{mg}{\cos \theta} = \frac{0.4 \times 9.81}{0.663} \approx 5.92 \text{ N}.$$

7.5 Comparison Problems: Two Pendulums Rotating Together

A classic examination situation: two conical pendulums of different lengths $l_1 > l_2$ are attached to the same point (or driven with the same angular speed ω). Which makes the larger angle with the vertical?

Since ω is common and $\omega^2 = \frac{g}{l \cos \theta}$, the product $l \cos \theta = \frac{g}{\omega^2}$ must be the same for both. Hence the longer string must have the smaller $\cos \theta$, i.e. the **larger** angle θ :


$$l_1 \cos \theta_1 = l_2 \cos \theta_2 = \frac{g}{\omega^2}.$$

Geometrically: both bobs rotate in the same horizontal plane at depth $h = g/\omega^2$ below the support. The longer string must lean further out to reach that plane.

EXAMPLE Numerical comparison

Two strings of lengths 1.0 m and 2.0 m rotate as conical pendulums with the same $\omega = 4.0 \text{ rad s}^{-1}$. Then $h = g/\omega^2 = 9.81/16 = 0.613 \text{ m}$ for both. So $\cos \theta_1 = 0.613/1.0 = 0.613 \Rightarrow \theta_1 \approx 52.2^\circ$, while $\cos \theta_2 = 0.613/2.0 = 0.307 \Rightarrow \theta_2 \approx 72.1^\circ$. The longer pendulum indeed makes the larger angle. (Both values of ω exceed the minima $\sqrt{g/l}$, namely 3.13 and 2.21 rad s^{-1} , so both motions are possible.)

7.6 Chapter Summary Map



Concept map of the chapter: each formula follows from the previous one; the conical pendulum is the centripetal-force law applied to a bob on a string.

KEY POINTS The five key formulae of the chapter

1. $\omega = \frac{2\pi}{T} = 2\pi f$ (angular speed)
2. $v = r\omega$ (linear speed on the circle)
3. $a = \frac{v^2}{r} = r\omega^2$ (centripetal acceleration, towards the centre)
4. $F = \frac{mv^2}{r} = mr\omega^2$ (centripetal force)
5. Conical pendulum: $\tan \theta = \frac{r\omega^2}{g}$, giving $T = 2\pi\sqrt{\frac{h}{g}}$, $\omega = \sqrt{\frac{g}{l \cos \theta}}$, $v = \sqrt{rg \tan \theta}$, with $\omega \geq \sqrt{g/l}$.

7.7 Timed GCE-Style Practice

WARNING Exam technique

GCE marking schemes award method marks for the free-body diagram and the two resolved equations $S \cos \theta = mg$, $S \sin \theta = mr\omega^2$ before any numerical work. Always show them, even if the final calculation goes wrong. Quote θ from the vertical, give ω in rad s^{-1} , and carry at least 3 significant figures.

EXERCISE 7 Structured question — 25 minutes

A small bob of mass 0.25 kg is attached to a light inextensible string of length 0.80 m fixed at a point O . The bob moves in a horizontal circle with constant angular speed $\omega = 5.0 \text{ rad s}^{-1}$. Take $g = 9.81 \text{ m s}^{-2}$.

1. Define the terms angular speed and centripetal acceleration.
2. Draw the free-body diagram of the bob and derive the relation $\tan \theta = \frac{r\omega^2}{g}$, where θ is the angle between the string and the vertical.
3. Calculate (i) the angle θ , (ii) the radius r of the circle, (iii) the linear speed v of the bob, (iv) the tension in the string.
4. The angular speed is now doubled to 10 rad s^{-1} . Without full calculation, state and justify what happens to θ , r , v and the height h of O above the plane of the circle.

SOLUTION Exercise 1

(a) Angular speed is the angle swept out per unit time, $\omega = 2\pi/T \text{ (rad s}^{-1}\text{)}$. Centripetal acceleration is the acceleration directed towards the centre of the circle, of magnitude $v^2/r = r\omega^2$, responsible for changing the direction of the velocity.

(b) Forces on the bob: weight mg vertically down, tension S along the string. Vertical equilibrium: $S \cos \theta = mg$. Horizontal motion (towards centre): $S \sin \theta = mr\omega^2$. Dividing: $\tan \theta = r\omega^2/g$.

(c) (i) $\cos \theta = \frac{g}{l\omega^2} = \frac{9.81}{0.80 \times 25} = 0.4905$, so $\theta \approx 60.6^\circ$. (ii) $r = l \sin \theta = 0.80 \times 0.8715 \approx 0.697 \text{ m}$. (iii) $v = r\omega = 0.697 \times 5.0 \approx 3.49 \text{ m s}^{-1}$. (iv) $S = \frac{mg}{\cos \theta} = \frac{0.25 \times 9.81}{0.4905} \approx 5.0 \text{ N}$.

(d) Since $\cos \theta = g/(l\omega^2)$, doubling ω divides $\cos \theta$ by 4: θ increases towards 90° . Hence $r = l \sin \theta$ increases, $h = l \cos \theta$ decreases (the circle rises), and $v = \sqrt{rg \tan \theta}$ increases sharply. Numerically $\cos \theta = 0.1226$, $\theta \approx 83.0^\circ$, $r \approx 0.794 \text{ m}$, $v \approx 7.9 \text{ m s}^{-1}$.

EXERCISE 8 Comparison question — 15 minutes

Two conical pendulums are suspended from the same point. Pendulum A has length 1.2 m and pendulum B has length 0.6 m. They are set rotating with the same angular speed $\omega = 3.5 \text{ rad s}^{-1}$.

1. Show that any bob rotating at this angular speed must move in a horizontal plane at depth $h = g/\omega^2$ below the point of suspension, and find this depth.
2. Determine the semi-vertical angle of each pendulum, commenting on any difficulty you meet.
3. Which bob has the greater linear speed? Justify.

SOLUTION Exercise 2

(a) From $\omega^2 = g/h$ we get $h = g/\omega^2 = 9.81/12.25 = 0.80 \text{ m}$, which depends only on ω and g , not on the length of the string. Any bob rotating at 3.5 rad s^{-1} circles in the horizontal plane 0.80 m below the support.

(b) A: $\cos \theta_A = h/l_A = 0.80/1.2 = 0.667 \Rightarrow \theta_A \approx 48.2^\circ$. B: $\cos \theta_B = 0.80/0.6 = 1.33 > 1$ — impossible! Pendulum B cannot rotate at $\omega = 3.5 \text{ rad s}^{-1}$: its minimum possible angular speed is $\omega_{\min} = \sqrt{g/l} = \sqrt{9.81/0.6} \approx 4.04 \text{ rad s}^{-1}$. Below this value the string simply hangs vertically.

(c) Only pendulum A rotates: $v_A = \sqrt{rg \tan \theta_A}$ with $r = 1.2 \sin 48.2^\circ = 0.894 \text{ m}$ and $\tan 48.2^\circ = 1.118$, giving $v_A \approx \sqrt{0.894 \times 9.81 \times 1.118} \approx 3.13 \text{ m s}^{-1}$. The question illustrates that a conical pendulum of length l requires $\omega \geq \sqrt{g/l}$.

DID YOU KNOW? Why the conical pendulum matters

The conical pendulum is not just an exam topic: it was at the heart of Huygens' work on pendulum clocks in the seventeenth century, and the same physics governs the "flying chairs" fairground ride, the centrifugal governor of a steam engine, and the banking of aircraft and of cyclists in a velodrome — in each case the horizontal component of an inclined force supplies the centripetal force $mr\omega^2$.

8 INTEGRATION ACTIVITY

8.1 Aims of the activity

This integration activity brings together, in one authentic engineering task, all the notions developed in this chapter:

- **Angular quantities:** converting a rotation rate from revolutions per minute to angular speed in rad s^{-1} , using $\omega = \frac{2\pi N}{60}$.
- **Uniform circular motion:** identifying the radius of the circle described by a seat and computing its **linear speed** using $v = r\omega$.
- **Centripetal acceleration and force:** recognising that the horizontal component of the chain's tension supplies the centripetal force $F = mr\omega^2$.
- **The conical pendulum model:** resolving forces vertically and horizontally, and using the results

$$T \cos \theta = mg, \quad T \sin \theta = mr\omega^2, \quad \tan \theta = \frac{r\omega^2}{g}, \quad T = \frac{mg}{\cos \theta}.$$

- **Scientific communication:** presenting a calculation with free-body diagrams, checking a safety constraint, and formulating a justified recommendation, as a real engineer would.
- **Critical thinking:** discussing the limits of a model (air resistance, mass of the chains, gusts of wind) and the notion of a safety margin.

By the end of the activity, you should be able to pass fluently from a real rotating system to its conical-pendulum model, to extract numerical predictions from it, and to judge whether those predictions can be trusted.

8.2 Situation

Designing a Safe Swing Carousel for a Yaoundé Amusement Park.

A new amusement park is about to open on the outskirts of Yaoundé, not far from the Carrefour Nsam. Among the attractions ordered by the park management is a swing carousel (the famous “chaises volantes”): a vertical mast topped by a rotating crown from which chains hang. Each chain carries a seat, and when the crown rotates, the seats swing outwards and describe horizontal circles, to the delight of the riders.

The technical data supplied by the manufacturer are the following:

Quantity	Value
Length of each chain (from crown to seat)	$l = 4.0 \text{ m}$
Horizontal distance from the axis of rotation to the attachment point of a chain on the crown	$a = 2.0 \text{ m}$
Maximum authorised mass per seat (child + seat)	$m = 50 \text{ kg}$
Breaking safety limit of one chain (tension must stay below this)	$T_{\text{max}} = 800 \text{ N}$
Maximum angle allowed between a chain and the vertical (comfort and clearance)	$\theta_{\text{max}} = 45^\circ$
Normal operating rotation rate	$N = 12 \text{ rev-} \\ \text{o-} \\ \text{lu-} \\ \text{tions} \\ \text{per} \\ \text{minute} \\ \text{(rpm)}$
Acceleration due to gravity	$g = 9.81 \text{ m s}^{-2}$

The park manager is worried. During a test run, a journalist claimed that “the chains will snap at full speed”. The manager hires your group of Upper Sixth students as consultants. Your mission: model each seat (with its rider) as a **conical pendulum**, compute the relevant quantities at the normal operating rate, verify the safety of the chains, determine the fastest rotation rate that keeps the chains within the allowed angle, and write a short recommendation.

WARNING Modelling assumptions

Throughout the activity, assume that: the rotation is uniform (constant angular speed); each seat moves in a horizontal circle at constant height; the chains are light (negligible mass) and inextensible; air resistance is neglected; the rider plus seat is treated as a single particle of mass $m = 50 \text{ kg}$ fixed at the lower end of the chain. The radius of the circle is $r = a + l \sin \theta$, because the chain is attached at a distance $a = 2.0 \text{ m}$ from the axis. Forgetting the offset a is the most common error in this type of problem.

8.3 Tasks

Part A — Setting up the model

1. Draw a clear diagram of one seat in operation: the axis of rotation, the crown, the chain of length l making an angle θ with the vertical, and the circle of radius $r = a + l \sin \theta$ described by the seat.

2. Draw the free-body diagram of the seat + rider system. Name each force and state which body exerts it.
3. Explain carefully why the vertical forces must balance, and why the resultant force must be horizontal, pointing towards the axis. What is the name of this resultant?
4. By resolving the tension vertically and horizontally, establish the two equations

$$T \cos \theta = mg \quad \text{and} \quad T \sin \theta = mr\omega^2,$$

and deduce that $\tan \theta = \frac{r\omega^2}{g}$.

Part B — Normal operation at 12 rpm

5. Convert the rotation rate $N = 12$ rpm into an angular speed ω in rad s^{-1} .
6. Using $\tan \theta = \frac{(a + l \sin \theta)\omega^2}{g}$, show that θ satisfies the equation

$$9.81 \tan \theta = 1.579 (2.0 + 4.0 \sin \theta).$$

Solve this equation (by trial with your calculator, or graphically) to find θ to the nearest degree.

7. Hence compute: the radius r of the circle; the linear speed $v = r\omega$ of a seat; the period T_0 of one revolution (check that it agrees with $N = 12$ rpm); the tension T in a chain.
8. **Safety check.** Compare the tension with the chain's limit of 800 N. Compute the safety factor $\frac{T_{\max}}{T}$. Is the journalist's claim justified at 12 rpm?

Part C — Maximum rotation rate

9. Using the full relation $\tan \theta = \frac{(a + l \sin \theta)\omega^2}{g}$, determine the angular speed $\omega_{\max}$ for which $\theta = 45^\circ$. Give $\omega_{\max}$ in rad s^{-1} .
10. Convert $\omega_{\max}$ into rpm and compute the corresponding linear speed of a seat and the tension in a chain. Verify that the chain is still safe at this limiting rate, and state which constraint (angle or tension) is the binding one.


Part D — Communication and critical discussion

12. Write a short recommendation (5 to 8 lines) to the park manager, stating whether the carousel is safe at 12 rpm, what rotation rate must never be exceeded, and what instruction should be given to the operator.
13. Discuss two or three reasons why the real situation differs from the model (air resistance on the riders, mass of the chains, wind gusts, a rider who leans out). For each, say whether it increases or decreases the tension compared with your calculation, and explain why the manufacturer's safety limit of 800 N (well below the true breaking load) protects against these effects.

8.4 Model answer

Part A.


A1. Diagram of one seat:



One seat of the carousel modelled as a conical pendulum.

A2. Free-body diagram: two forces act on the system seat + rider:

- its **weight** $\vec{P} = m\vec{g}$, exerted by the Earth, vertically downwards;
- the **tension** $\vec{T}$ of the chain, exerted by the chain, directed along the chain towards the attachment point.

Free-body diagram: the horizontal component $T \sin \theta$ is the centripetal force.

A3. The seat moves in a horizontal circle at constant height: its vertical acceleration is zero, so the vertical components of the forces must balance. But uniform circular motion requires a **centripetal acceleration** $r\omega^2$ directed towards the centre of the circle; by Newton's second law, the resultant force must therefore be horizontal, of magnitude $mr\omega^2$, pointing towards the axis. This resultant is the **centripetal force**; here it is provided entirely by the horizontal component of the tension. Note that the centripetal force is not an extra force to add to the diagram: it is the resultant of the real forces (weight and tension).

A4. Resolving $\vec{T}$ into a vertical component $T \cos \theta$ and a horizontal component $T \sin \theta$:

$$\text{vertically (no vertical acceleration): } T \cos \theta = mg,$$

$$\text{horizontally (Newton's second law): } T \sin \theta = mr\omega^2.$$

Dividing the second equation by the first eliminates T and m :

$$\tan \theta = \frac{r\omega^2}{g}.$$

Part B.

B5. One revolution is 2π rad and one minute is 60 s, so

$$\omega = \frac{2\pi N}{60} = \frac{12 \times 2\pi}{60} = \frac{24\pi}{60} \approx 1.257 \text{ rad s}^{-1}, \quad \omega^2 \approx 1.579 \text{ rad}^2 \text{ s}^{-2}.$$

B6. With $r = 2.0 + 4.0 \sin \theta$ and $\omega^2 \approx 1.579$:

$$\tan \theta = \frac{1.579(2.0 + 4.0 \sin \theta)}{9.81} \iff 9.81 \tan \theta = 1.579(2.0 + 4.0 \sin \theta).$$

This equation cannot be solved directly for θ (it contains both $\tan \theta$ and $\sin \theta$), so we proceed by trial:

- $\theta = 30^\circ$: LHS = $9.81 \times 0.5774 \approx 5.66$; RHS = $1.579 \times (2.0 + 4.0 \times 0.500) = 1.579 \times 4.000 \approx 6.32$. LHS < RHS.
- $\theta = 35^\circ$: LHS = $9.81 \times 0.7002 \approx 6.87$; RHS = $1.579 \times (2.0 + 4.0 \times 0.5736) = 1.579 \times 4.294 \approx 6.78$. LHS > RHS.
- $\theta = 34^\circ$: LHS = $9.81 \times 0.6745 \approx 6.62$; RHS = $1.579 \times (2.0 + 4.0 \times 0.5592) = 1.579 \times 4.237 \approx 6.69$. LHS < RHS.

The solution lies between 34° and 35° . Refining at $\theta = 34.4^\circ$: LHS $\approx 9.81 \times 0.6836 \approx 6.71$; RHS $\approx 1.579 \times (2.0 + 4.0 \times 0.5652) \approx 1.579 \times 4.261 \approx 6.73$. The two sides agree to within 0.3%, so

$$\theta \approx 34^\circ \text{ (more precisely } 34.4^\circ \text{)}.$$

B7. With $\theta \approx 34.4^\circ$, $\sin \theta \approx 0.565$ and $\cos \theta \approx 0.825$:

$$r = 2.0 + 4.0 \times 0.565 \approx 4.26 \text{ m},$$

$$v = r\omega \approx 4.26 \times 1.257 \approx 5.35 \text{ m s}^{-1} (\approx 19 \text{ km h}^{-1}),$$

$$T_0 = \frac{2\pi}{\omega} = \frac{2\pi}{1.257} \approx 5.0 \text{ s} \quad \left(\text{indeed } \frac{60 \text{ s}}{12} = 5.0 \text{ s per revolution} \right),$$

$$T = \frac{mg}{\cos \theta} = \frac{50 \times 9.81}{0.825} \approx \frac{490.5}{0.825} \approx 594 \text{ N}.$$

Consistency check: $T \sin \theta \approx 594 \times 0.565 \approx 336 \text{ N}$ and $mr\omega^2 \approx 50 \times 4.26 \times 1.579 \approx 336 \text{ N}$. The two expressions of the centripetal force agree.

B8. Safety check: $T \approx 594 \text{ N} < 800 \text{ N} = T_{\max}$. The safety factor is

$$\frac{T_{\max}}{T} \approx \frac{800}{594} \approx 1.35.$$

The chain operates at about 74% of its authorised limit: at 12 rpm the journalist's claim is **not** justified.

Part C.

C9. Set $\theta = 45^\circ$ in the full relation, with

$$r = 2.0 + 4.0 \sin 45^\circ = 2.0 + 4.0 \times 0.7071 = 4.828 \text{ m} :$$

$$\omega_{\max}^2 = \frac{g \tan 45^\circ}{r} = \frac{9.81 \times 1}{4.828} \approx 2.032 \quad \Rightarrow \quad \omega_{\max} \approx 1.43 \text{ rad s}^{-1}.$$

C10. Conversion and consequences:

$$\begin{aligned} N_{\max} &= \frac{60 \omega_{\max}}{2\pi} \approx \frac{60 \times 1.43}{6.283} \approx 13.6 \text{ rpm}, \\ v_{\max} &= r \omega_{\max} \approx 4.828 \times 1.43 \approx 6.9 \text{ m s}^{-1}, \\ T &= \frac{mg}{\cos 45^\circ} = \frac{490.5}{0.7071} \approx 694 \text{ N} < 800 \text{ N}. \end{aligned}$$

Even at the limiting angle, the chain remains within its safety limit ($694 \text{ N} < 800 \text{ N}$, safety factor ≈ 1.15). The angle constraint (45°) is therefore the binding one: it is reached at about 13.6 rpm, only slightly above the normal rate of 12 rpm.

Part D.

D11. Recommendation to the park manager. Our calculations, based on the standard conical-pendulum model with the heaviest authorised load (50 kg), show that at the normal rate of 12 rpm each chain carries a tension of about 594 N, i.e. only 74% of the 800 N safety limit, and the chains incline at about 34° , below the 45° clearance limit. The carousel is therefore safe at 12 rpm. However, the angle limit is reached at about 13.6 rpm, so the margin is small: we recommend that the motor be fitted with a speed limiter set at 12 rpm, that the operator never override it, and that chains be inspected weekly for wear.

D12. Limits of the model.

- **Air resistance** on the rider opposes the motion; it adds a horizontal drag that the chain must also pull along, slightly increasing the tension and making the seat trail backwards (the plane of the circle lags behind the crown arm).
- **Mass of the chains** (a real 4 m chain may weigh several kilograms): the upper part of each chain supports the weight of the lower part, so the tension at the crown is higher than our value $T = mg / \cos \theta$ computed for a light chain.
- **Wind gusts and a rider leaning outwards** shift the centre of mass and add lateral forces, again increasing the tension and the effective angle.

All three effects increase the true tension above the model's prediction. This is precisely why the manufacturer fixes the authorised limit (800 N) far below the actual breaking load of the chain: the gap absorbs the unmodelled effects. Engineers call this gap a **safety margin**, and our role as consultants is to check that the modelled tension stays comfortably inside it — which it does at 12 rpm.

KEY POINTS What this activity consolidates

- Convert rotation rates: $\omega = \frac{2\pi N}{60}$ (with N in rpm, ω in rad s^{-1}).
- In any uniform circular motion, the resultant force is the centripetal force $mr\omega^2 = \frac{mv^2}{r}$, directed towards the centre; it is not an extra force.
- For a conical pendulum: $T \cos \theta = mg$, $T \sin \theta = mr\omega^2$, hence $\tan \theta = \frac{r\omega^2}{g}$ and $T = \frac{mg}{\cos \theta}$.
- The radius must be measured from the axis of rotation: here $r = a + l \sin \theta$, a frequent source of error.
- When an equation mixes $\sin \theta$ and $\tan \theta$, solve it numerically by bracketing the root with a calculator.
- A good scientific answer ends with a check (comparison with a limit, consistency between formulas) and a critical discussion of the model.

9 METHODS AND WORKED EXAMPLES

9.1 Method 1: Converting and Using Angular Quantities

In uniform circular motion, the position of the body is most naturally described by the angle it has swept, not by a coordinate along a straight line. The first skill is therefore to move fluently between revolutions, degrees and radians, and between frequency, period and angular speed.

METHOD Handling angular quantities: revolutions, degrees, radians

To work with angular quantities in circular motion:

1. Choose the SI unit. Always convert angles to **radians** and angular speed to rad s^{-1} before using any formula. Recall: 1 revolution = $2\pi \text{ rad} = 360^\circ$, so $1 \text{ rad} = \frac{180^\circ}{\pi} \approx 57.3^\circ$.
2. Convert frequencies. If a body makes N revolutions per minute (rpm), then the frequency is $f = \frac{N}{60} \text{ Hz}$ and the angular speed is

$$\omega = 2\pi f = \frac{2\pi N}{60} \text{ rad s}^{-1}.$$

3. Use the period. The period T (time for one complete revolution) satisfies $T = \frac{1}{f}$ and $\omega = \frac{2\pi}{T}$.
4. Angle swept. In time t at constant angular speed, the angle swept is $\theta = \omega t$ (with θ in radians).
5. Arc length. The distance travelled along the circle is $s = r\theta = r\omega t$, where r is the radius of the path.

Reflex: as soon as you see “rpm” or “revolutions per second”, convert immediately to rad s^{-1} before any calculation.

WORKED EXAMPLE 17 Angular speed of a ceiling fan

The blade of a ceiling fan in a classroom in Buea rotates at 150 revolutions per minute. The tip of a blade is 0.60 m from the axis of rotation.

- (a) Calculate the angular speed of the blade in rad s^{-1} .
- (b) Calculate the period of the motion.
- (c) Find the angle, in radians, swept by a blade in 0.50 s, and the distance travelled by the

tip in that time.

SOLUTION

(a) Angular speed. The frequency is

$$f = \frac{150}{60} = 2.5 \text{ Hz.}$$

Hence

$$\omega = 2\pi f = 2\pi \times 2.5 = 5\pi \approx 15.7 \text{ rad s}^{-1}.$$

(b) Period.

$$T = \frac{1}{f} = \frac{1}{2.5} = 0.40 \text{ s.}$$

Check: $T = \frac{2\pi}{\omega} = \frac{2\pi}{5\pi} = 0.40 \text{ s.}$ ✓

(c) Angle swept and distance. In $t = 0.50 \text{ s}$:

$$\theta = \omega t = 5\pi \times 0.50 = 2.5\pi \approx 7.85 \text{ rad.}$$

The distance travelled by the tip along its circular path is

$$s = r\theta = 0.60 \times 2.5\pi = 1.5\pi \approx 4.71 \text{ m.}$$

Remark: $2.5\pi \text{ rad} = 1.25 \text{ revolutions}$, consistent with $f \times t = 2.5 \times 0.5 = 1.25 \text{ revolutions}$.

9.2 Method 2: Linking Linear Speed and Angular Speed

Every point of a rotating rigid body sweeps the same angle in the same time, so all points share the same ω ; but points further from the axis travel longer arcs, hence move faster. The bridge between the two descriptions is $v = r\omega$.

METHOD Using $v = r\omega$

To relate linear and angular quantities for a point on a rotating body:

1. Identify the radius r of the circular path of the point considered (different points of the same rigid body have different r but the same ω).
2. Apply the bridge formula $v = r\omega$, with v in m s^{-1} , r in metres, ω in rad s^{-1} .
3. Combine with period/frequency if needed: $v = r\omega = \frac{2\pi r}{T} = 2\pi r f$.
4. Compare points on the same rotating body: since ω is common, $v \propto r$ — the further from the axis, the faster the point moves.

Reflex: $v = r\omega$ only works with ω in radians per second. Never use revolutions or degrees in this formula.

WORKED EXAMPLE 18 The grinding wheel

A grinding wheel in a workshop in Douala has diameter 30 cm and spins at 1200 rpm.

- Find the angular speed of the wheel.
- Find the linear speed of a point on the rim of the wheel.
- A spark leaves the rim tangentially. Explain why it flies off along the tangent, and state its speed at the instant it leaves.

SOLUTION

(a) Radius: $r = \frac{30}{2} = 15 \text{ cm} = 0.15 \text{ m}$. Frequency:

$$f = \frac{1200}{60} = 20 \text{ Hz}, \quad \omega = 2\pi f = 40\pi \approx 125.7 \text{ rad s}^{-1}.$$

(b) Linear speed of a rim point:

$$v = r\omega = 0.15 \times 40\pi = 6\pi \approx 18.8 \text{ m s}^{-1}.$$

(c) In circular motion the velocity vector is always tangent to the circle. When the particle of material detaches, the centripetal force on it vanishes, so by Newton's first law it continues in a straight line with the velocity it had at the instant of release: along the tangent, at speed $v \approx 18.8 \text{ m s}^{-1}$. This is why grinding wheels are always fitted with guards.

9.3 Method 3: Computing Centripetal Acceleration and Centripetal Force

Even at constant speed, a body in circular motion is accelerated, because the direction of its velocity changes continuously. The acceleration points towards the centre of the circle; by Newton's second law, the resultant force must also point towards the centre.

METHOD Applying $a = \frac{v^2}{r} = r\omega^2$ and $F = ma$

To find the centripetal acceleration or force in uniform circular motion:

- Draw a diagram and identify the centre of the circular path; the acceleration is directed towards the centre at every instant.
- Choose the convenient form:

$$a = \frac{v^2}{r} = r\omega^2 = \frac{4\pi^2 r}{T^2}.$$

Use the form matching the data given (v , ω or T).

- Apply Newton's second law along the radius: the resultant force towards the centre

is

$$F = ma = \frac{mv^2}{r} = mr\omega^2.$$

4. Identify the physical agent providing F (tension, friction, normal reaction, gravity, or a component of one of these). The “centripetal force” is not a new force: it is the role played by the resultant of real forces.

WARNING Common traps

Do not add a “centrifugal force” acting on the body in an inertial frame. Do not forget to convert r to metres and ω to rad s^{-1} . The acceleration is not zero even though the speed is constant, because the velocity direction changes.

WORKED EXAMPLE 19 Stone whirled on a string

A stone of mass 0.50 kg is tied to a string of length 1.2 m and whirled in a horizontal circle at constant speed, making 2 revolutions per second. Take $g = 9.81 \text{ m s}^{-2}$.

- Calculate the angular speed and the linear speed of the stone.
- Calculate the centripetal acceleration of the stone.
- Find the tension in the string (assume the string is horizontal).
- The string can withstand a maximum tension of 400 N. Find the greatest number of revolutions per second before it breaks.

SOLUTION

- (a) $f = 2 \text{ Hz}$, so

$$\omega = 2\pi f = 4\pi \approx 12.57 \text{ rad s}^{-1}, \quad v = r\omega = 1.2 \times 4\pi = 4.8\pi \approx 15.1 \text{ m s}^{-1}.$$

- (b) Using $a = r\omega^2$:

$$a = 1.2 \times (4\pi)^2 = 1.2 \times 16\pi^2 = 19.2\pi^2 \approx 189.5 \text{ m s}^{-2}.$$

(That is about 19 times g !)

- (c) The tension provides the centripetal force:

$$T = mr\omega^2 = 0.50 \times 189.5 \approx 94.7 \text{ N}.$$

- (d) At breaking point, $T_{\text{max}} = mr\omega_{\text{max}}^2$, so

$$\omega_{\text{max}} = \sqrt{\frac{T_{\text{max}}}{mr}} = \sqrt{\frac{400}{0.50 \times 1.2}} = \sqrt{666.7} \approx 25.8 \text{ rad s}^{-1}.$$

Hence

$$f_{\max} = \frac{\omega_{\max}}{2\pi} = \frac{25.8}{2\pi} \approx 4.1 \text{ rev s}^{-1}.$$

The string breaks if the stone is whirled faster than about 4.1 revolutions per second.

9.4 Method 4: Circular Motion of Vehicles — Flat and Banked Tracks

A vehicle rounding a bend is in (approximately) uniform circular motion: something must push it towards the centre of the bend. On a flat road that “something” is friction; on a banked track, a component of the normal reaction helps.

METHOD Analysing a vehicle rounding a bend


1. Flat road: the centripetal force is supplied entirely by friction F_f between tyres and road:

$$F_f = \frac{mv^2}{r} \leq \mu mg \implies v_{\max} = \sqrt{\mu gr}.$$

2. Banked track (angle θ , no friction needed): resolve the normal reaction R . Vertically: $R \cos \theta = mg$. Horizontally (towards centre): $R \sin \theta = \frac{mv^2}{r}$. Dividing:

$$\tan \theta = \frac{v^2}{gr} \implies v = \sqrt{gr \tan \theta}.$$

3. Always identify which real force (or component) points towards the centre before writing Newton's second law.
4. Check units and reasonableness: a larger radius or a steeper banking allows a larger speed.



Car on a banked bend (cross-section, centre of the circle to the left). The horizontal component $R \sin \theta$ of the normal reaction provides the centripetal force; the vertical component balances the weight.

WORKED EXAMPLE 20 Car on a bend near Yaoundé

A car of mass 1200 kg rounds a bend of radius 50 m.

- The road is flat and the coefficient of friction between tyres and road is $\mu = 0.8$. Find the maximum safe speed.
- The same bend is now banked at 12° to the horizontal. Find the speed at which the car can take the bend with no tendency to skid (no friction required). Take $g = 9.81 \text{ m s}^{-2}$, $\tan 12^\circ = 0.2126$.

SOLUTION

(a) Flat road. Friction provides the centripetal force, and at the limit $F_f = \mu R = \mu mg$:

$$\frac{mv_{\max}^2}{r} = \mu mg \implies v_{\max} = \sqrt{\mu gr} = \sqrt{0.8 \times 9.81 \times 50} = \sqrt{392.4} \approx 19.8 \text{ m s}^{-1}.$$

That is about 71 km h^{-1} . Note that the mass cancels: the limit is the same for a small car or a loaded lorry.

(b) Banked road. Let R be the normal reaction. Resolving:

$$\text{Vertically: } R \cos \theta = mg,$$

$$\text{Horizontally: } R \sin \theta = \frac{mv^2}{r}.$$

Dividing the second equation by the first:

$$\tan \theta = \frac{v^2}{gr} \implies v = \sqrt{gr \tan \theta} = \sqrt{9.81 \times 50 \times 0.2126} = \sqrt{104.3} \approx 10.2 \text{ m s}^{-1}.$$

At about 10.2 m s^{-1} ($\approx 37 \text{ km h}^{-1}$) the car needs no friction at all; above this speed friction must act down the slope to supplement $R \sin \theta$.

9.5 Method 5: Analysing the Conical Pendulum

METHOD Setting up the conical pendulum equations

A **conical pendulum** is a small bob of mass m on a light inextensible string of length l , moving in a horizontal circle while the string traces a cone of semi-vertical angle θ .

1. Draw the forces: only two — the tension T along the string and the weight mg vertically downwards.
2. Identify the geometry: the radius of the circle is $r = l \sin \theta$; the centre of the circle is vertically below the point of suspension, at depth $h = l \cos \theta$.
3. Resolve the tension into $T \cos \theta$ (vertical) and $T \sin \theta$ (horizontal, towards the centre).
4. Write the two equations:

$$\text{Vertical equilibrium: } T \cos \theta = mg,$$

$$\text{Horizontal (Newton II): } T \sin \theta = mr\omega^2 = \frac{mv^2}{r}.$$


5. Divide to eliminate T :

$$\tan \theta = \frac{r\omega^2}{g} = \frac{v^2}{gr}.$$

6. Deduce the period: substituting $r = l \sin \theta$ gives

$$\omega^2 = \frac{g}{l \cos \theta} = \frac{g}{h}, \quad T_{\text{period}} = 2\pi \sqrt{\frac{l \cos \theta}{g}} = 2\pi \sqrt{\frac{h}{g}}.$$

Key remark: the period depends only on the vertical depth $h = l \cos \theta$ of the bob below the support, not on the mass.



The conical pendulum: the bob moves in a horizontal circle of radius $r = l \sin \theta$ at depth $h = l \cos \theta$ below the support. Only two forces act: tension T and weight mg ; the horizontal component $T \sin \theta$ is the centripetal force.

WORKED EXAMPLE 21 Period of a conical pendulum

A small bob of mass 0.20 kg is attached to a light inextensible string of length 1.5 m fixed at a point O . The bob moves in a horizontal circle with constant angular speed, the string making an angle of 30° with the vertical. Take $g = 9.81 \text{ m s}^{-2}$.

- Find the tension in the string.
- Find the angular speed of the bob.
- Deduce the period of the motion.
- Find the linear speed of the bob.

SOLUTION

(a) Tension. Vertical equilibrium: $T \cos \theta = mg$, so

$$T = \frac{mg}{\cos 30^\circ} = \frac{0.20 \times 9.81}{0.8660} = \frac{1.962}{0.8660} \approx 2.27 \text{ N.}$$

(b) Angular speed. The radius is $r = l \sin \theta = 1.5 \times \sin 30^\circ = 1.5 \times 0.5 = 0.75 \text{ m}$. Horizontal equation: $T \sin \theta = mr\omega^2$, hence

$$\omega^2 = \frac{T \sin \theta}{mr} = \frac{2.27 \times 0.5}{0.20 \times 0.75} = \frac{1.133}{0.15} = 7.556, \quad \omega \approx 2.75 \text{ rad s}^{-1}.$$

Check with the shortcut: $\omega = \sqrt{\frac{g}{l \cos \theta}} = \sqrt{\frac{9.81}{1.5 \times 0.8660}} = \sqrt{7.553} \approx 2.75 \text{ rad s}^{-1}$. ✓

(c) Period.

$$T_{\text{period}} = \frac{2\pi}{\omega} = \frac{2\pi}{2.75} \approx 2.29 \text{ s.}$$

Equivalently, $T_{\text{period}} = 2\pi \sqrt{\frac{l \cos \theta}{g}} = 2\pi \sqrt{\frac{1.299}{9.81}} \approx 2.29 \text{ s}$. ✓

(d) Linear speed.

$$v = r\omega = 0.75 \times 2.75 \approx 2.06 \text{ m s}^{-1}.$$

Check: $\tan \theta = \frac{v^2}{gr}$ gives $v = \sqrt{gr \tan \theta} = \sqrt{9.81 \times 0.75 \times 0.5774} = \sqrt{4.248} \approx 2.06 \text{ m s}^{-1}$. ✓

9.6 Method 6: Comparing and Designing Conical Pendulums

METHOD Using the relationships $\omega^2 = g/h$ and $v = \sqrt{gr \tan \theta}$

For problems comparing or designing conical pendulums:

- Translate the geometry first: $r = l \sin \theta$, $h = l \cos \theta$.

2. Same depth, same period: since $\omega^2 = \frac{g}{h}$, all conical pendulums whose bobs rotate in the same horizontal plane have the same angular speed and period, whatever their lengths or masses.
3. Increasing the speed makes θ increase (since $\cos \theta = \frac{g}{l\omega^2}$): the bob rises, but θ can never reach 90° in practice, because that would require infinite ω .
4. To find one quantity from another, chain the relations:

$$\cos \theta = \frac{g}{l\omega^2}, \quad r = l \sin \theta, \quad v = r\omega, \quad T = \frac{mg}{\cos \theta} = ml\omega^2.$$

5. Check consistency with $\tan \theta = \frac{v^2}{gr}$.

WORKED EXAMPLE 22 Designing a rotating swing ride

At a funfair in Limbe, a “swing carousel” carries children in seats attached by chains of length 4.0 m to a rotating frame. A child with seat has total mass 40 kg. The ride is intended to rotate so that each seat completes one revolution in 5.0 s. Take $g = 9.81 \text{ m s}^{-2}$.

- Calculate the angular speed corresponding to this intended period.
- Show that the angle θ of the chains to the vertical is independent of the mass of the child, and investigate whether the intended period is attainable.
- For an actual period of 3.5 s, find the radius of the circle described by a seat and the linear speed of the seat.
- Calculate the tension in one chain for the 3.5 s period. What happens to θ if the rotation speeds up?

SOLUTION

$$(a) \omega = \frac{2\pi}{T_{\text{period}}} = \frac{2\pi}{5.0} = 1.257 \text{ rad s}^{-1}.$$

(b) For a conical pendulum, $\cos \theta = \frac{g}{l\omega^2}$: the mass does not appear, so θ is the same for a light or a heavy child. Numerically, for the intended period:

$$\cos \theta = \frac{9.81}{4.0 \times (1.257)^2} = \frac{9.81}{4.0 \times 1.579} = \frac{9.81}{6.317} = 1.553.$$

Since $\cos \theta > 1$ is impossible, the intended period is not attainable with 4.0 m chains: the seats would simply hang vertically. The smallest possible period corresponds to $\theta \rightarrow 90^\circ$, i.e. $\omega \rightarrow \sqrt{g/l} = \sqrt{9.81/4.0} = 1.566 \text{ rad s}^{-1}$, giving

$$T_{\text{min}} = \frac{2\pi}{1.566} \approx 4.01 \text{ s}.$$

Any working period must therefore be shorter than about 4.0 s. Take instead a period of 3.5 s: then $\omega = \frac{2\pi}{3.5} = 1.795 \text{ rad s}^{-1}$ and

$$\cos \theta = \frac{9.81}{4.0 \times (1.795)^2} = \frac{9.81}{12.89} = 0.761 \implies \theta \approx 40.4^\circ.$$

(c) With $\theta = 40.4^\circ$:

$$r = l \sin \theta = 4.0 \times \sin 40.4^\circ = 4.0 \times 0.648 = 2.59 \text{ m},$$

$$v = r\omega = 2.59 \times 1.795 \approx 4.65 \text{ m s}^{-1}.$$

(d) Tension:

$$T = \frac{mg}{\cos \theta} = \frac{40 \times 9.81}{0.761} \approx 516 \text{ N}.$$

(Equivalently $T = ml\omega^2 = 40 \times 4.0 \times 3.22 \approx 516 \text{ N}$. ✓) If the ride speeds up, ω^2 increases, so $\cos \theta = \frac{g}{l\omega^2}$ decreases and θ increases: the seats rise higher. The tension $T = ml\omega^2$ also increases, which is why the chains must be strong and regularly inspected.

9.7 Method 7: Synthesis — Multi-Step GCE Problems on Circular Motion

METHOD Strategy for exam questions mixing several notions

1. Read twice and list the data with symbols and SI units; convert rpm, km h^{-1} , cm.
2. Draw a clear diagram: circle, centre, radius, forces. Decide which force(s) point towards the centre.
3. Write the two structural equations (vertical balance; radial Newton's second law) before substituting numbers.
4. Choose the right bridge: $v = r\omega$, $\omega = \frac{2\pi}{T}$, $a = \frac{v^2}{r} = r\omega^2$.
5. Conclude with a sentence answering the question asked, with units and a sensible number of significant figures.

WORKED EXAMPLE 23 GCE-style synthesis: the bucket of water

A bucket of water of total mass 2.0 kg is whirled in a vertical circle of radius 0.90 m at constant angular speed on the end of a rope. Take $g = 9.81 \text{ m s}^{-2}$.

- (a) At the top of the circle, write down the equation of motion of the bucket along the radius.

- (b) Show that the minimum angular speed for the rope to remain taut at the top is $\omega_{\min} = \sqrt{g/r}$, and calculate its value.
- (c) Find the corresponding minimum linear speed and the period of rotation at this limiting speed.
- (d) Explain why the water does not fall out of the bucket at the top when the bucket moves faster than this minimum speed.

SOLUTION

(a) At the top of the circle, the centre is below the bucket, so the centripetal direction is vertically downwards. The forces towards the centre are the weight mg and the tension T of the rope (both point down at the top). Newton's second law along the radius:

$$T + mg = mr\omega^2.$$

(b) The rope remains taut as long as $T \geq 0$. The limiting case is $T = 0$:

$$mg = mr\omega_{\min}^2 \implies \omega_{\min}^2 = \frac{g}{r} \implies \omega_{\min} = \sqrt{\frac{g}{r}}.$$

Numerically:

$$\omega_{\min} = \sqrt{\frac{9.81}{0.90}} = \sqrt{10.9} \approx 3.30 \text{ rad s}^{-1}.$$

(c) Minimum linear speed:

$$v_{\min} = r\omega_{\min} = \sqrt{gr} = \sqrt{9.81 \times 0.90} = \sqrt{8.829} \approx 2.97 \text{ m s}^{-1}.$$

Period at this speed:

$$T_{\text{period}} = \frac{2\pi}{\omega_{\min}} = \frac{2\pi}{3.30} \approx 1.90 \text{ s}.$$

(d) The water and the bucket both need a centripetal force $mr\omega^2$ to follow the circle. When $\omega > \omega_{\min}$, the required centripetal force exceeds the weight alone, so the bottom of the bucket must push on the water (normal reaction) to supply the difference: the water is pressed against the bottom of the bucket instead of falling. At exactly $\omega = \omega_{\min}$, gravity alone provides precisely the required centripetal force and the reaction is zero — the water is in “free fall” along the circle. Below $\omega_{\min}$, gravity provides more than needed, the circular path cannot be maintained, and the water spills. This is the same principle used by pilots looping an aircraft and by the design of roller-coaster loops.

WARNING

Final checklist before submitting your answer

- Angles in radians, ω in rad s^{-1} , distances in metres.

- Centripetal acceleration is $a = \frac{v^2}{r} = r\omega^2$, directed towards the centre — never outwards.
- The centripetal force is the resultant towards the centre; identify the real forces providing it.
- For the conical pendulum: $T \cos \theta = mg$, $T \sin \theta = mr\omega^2$, period = $2\pi\sqrt{\frac{l \cos \theta}{g}}$.
- Give final answers with units and 2–3 significant figures.

10 EXERCISES

10.1 I check my knowledge

EXERCISE 9 Multiple choice: angular quantities

A particle moves with uniform speed on a circle of radius r with angular speed ω . Choose the correct statement and justify briefly:

- (a) The acceleration of the particle is zero because its speed is constant.
- (b) The acceleration is directed along the tangent to the circle.
- (c) The acceleration has magnitude $\omega^2 r$ and is directed towards the centre of the circle.
- (d) The acceleration has magnitude $\frac{v^2}{r}$ and is directed away from the centre.

EXERCISE 10 True or false

State whether each of the following statements is true or false, justifying your answer in one or two sentences.

- 1. In uniform circular motion, the velocity of the particle is constant.
- 2. The centripetal force is an extra force that must be added to the other forces acting on the body.
- 3. If the angular speed of a body moving on a circle is doubled while the radius is unchanged, the centripetal acceleration is multiplied by 4.
- 4. For a conical pendulum, the period depends on the mass of the bob.

EXERCISE 11 Definitions

Define each of the following terms, giving its symbol and SI unit:

- 1. angular speed;
- 2. period of a circular motion;
- 3. centripetal acceleration;
- 4. conical pendulum.

EXERCISE 12 Direct calculations

A grinding wheel in a Douala workshop rotates at 1500 rpm. Calculate:

1. its angular speed in rad s^{-1} ;
2. its period of rotation;
3. the linear speed of a point on the wheel situated 12 cm from the axis.

10.2 I practise**EXERCISE 13** Stone whirled on a table

A stone of mass 0.5 kg is whirled in a horizontal circle of radius 0.8 m on a frictionless table, at a rate of 2 revolutions per second. The stone is attached to the centre by a light inextensible string. Find:

1. the angular speed of the stone;
2. its linear speed;
3. its centripetal acceleration;
4. the tension in the string.

EXERCISE 14 Car rounding a bend

A car of mass 900 kg rounds a flat (unbanked) bend of radius 50 m. The coefficient of friction between the tyres and the road is 0.6. Taking $g = 10 \text{ m s}^{-2}$:

1. identify the force that provides the centripetal force;
2. find the maximum safe speed of the car round the bend;
3. state what happens if the driver exceeds this speed.

EXERCISE 15 Belt-driven pulleys

Two pulleys of radii 10 cm and 25 cm are connected by a belt that does not slip. The smaller pulley rotates at 300 rpm.

1. Explain why the linear speed of the belt is the same at both pulleys.
2. Find the angular speed of the larger pulley in rpm and in rad s^{-1} .

3. Calculate the linear speed of the belt.

EXERCISE 16 Coin on a turntable

A small coin is placed 20 cm from the centre of a horizontal turntable. The coefficient of static friction between the coin and the turntable is 0.5. Taking $g = 10 \text{ m s}^{-2}$, find:

1. the greatest angular speed, in rad s^{-1} , for which the coin does not slip;
2. this angular speed expressed in revolutions per minute.

10.3 I prepare for the GCE

EXERCISE 17 The conical pendulum: structured question

A conical pendulum consists of a bob of mass 0.4 kg attached to a light inextensible string of length 1.2 m. The bob describes a horizontal circle with the string making a constant angle of 37° with the vertical. Take $\sin 37^\circ = 0.6$, $\cos 37^\circ = 0.8$ and $g = 10 \text{ m s}^{-2}$.

1. Draw a clear diagram showing all the forces acting on the bob. (2 marks)
2. By resolving forces vertically, calculate the tension in the string. (3 marks)
3. Write down the equation of motion in the horizontal (radial) direction. (2 marks)
4. Hence calculate the angular speed of the bob. (3 marks)
5. Deduce the linear speed of the bob and the period of the motion. (4 marks)
6. State one assumption made about the string and one about air resistance. (2 marks)

EXERCISE 18 Derivation of the period formula

1. Starting from a diagram of a conical pendulum of string length l , with the bob of mass m describing a horizontal circle while the string makes an angle θ with the vertical, derive from first principles the relation

$$\omega^2 = \frac{g}{l \cos \theta},$$

stating clearly each step and the forces considered.

(6 marks)

2. Deduce that the period of the conical pendulum is

$$T = 2\pi\sqrt{\frac{h}{g}},$$

where h is the vertical distance from the point of suspension to the plane of the circle.
(3 marks)

3. Two conical pendulums of lengths 1.0 m and 1.5 m rotate with the same angular speed. Using the relation of part (a), determine which pendulum makes the larger angle with the vertical, justifying your answer carefully. (4 marks)
4. Show that the linear speed of the bob can be written $v = \sqrt{gl \sin \theta \tan \theta}$, and hence find v when $l = 2.0$ m and $\theta = 30^\circ$, taking $g = 9.81 \text{ m s}^{-2}$. (5 marks)

EXERCISE 19 Circular orbits: extension problem

A satellite of mass m moves with uniform speed v in a circular orbit of radius r about the Earth.

- Write down an expression for the centripetal force acting on the satellite, and explain what physical agent provides this force. (3 marks)
- At the altitude of the orbit, the gravitational force per unit mass is 8.7 N kg^{-1} and $r = 6.9 \times 10^6$ m. Show that the orbital speed is approximately 7.7 km s^{-1} . (4 marks)
- Calculate the period of the orbit, giving your answer in minutes. (4 marks)
- Explain why the satellite can remain in orbit although it is constantly accelerating towards the Earth. (3 marks)
- The satellite is transferred to an orbit of larger radius. Without calculation, state and justify whether its angular speed increases or decreases. (3 marks)

11 SOLUTIONS TO THE EXERCISES

SOLUTION Exercise 1 — Multiple choice: angular quantities

The correct statement is (c).

In uniform circular motion the speed is constant but the velocity is not, because its direction changes continuously. A changing velocity means a non-zero acceleration, so (a) is false. This acceleration is the **centripetal acceleration**: it is directed along the radius towards the centre (not along the tangent, not away from the centre), so (b) and (d) are false. Its magnitude is

$$a = \omega^2 r \quad \left(\text{equivalently } a = \frac{v^2}{r}\right),$$

which is exactly statement (c). Note that $\frac{v^2}{r}$ in (d) has the correct magnitude but the wrong direction, so (d) is rejected.

SOLUTION Exercise 2 — True or false

1. False. The speed is constant, but the velocity vector changes direction at every instant (it is always tangent to the circle). Hence the velocity is not constant — this is precisely why an acceleration exists.
2. False. The centripetal force is not an additional force; it is the resultant of the real forces (tension, friction, weight, reaction...) directed towards the centre. One must never add a “centripetal force” to a force diagram.
3. True. Since $a = \omega^2 r$ with r fixed, a is proportional to ω^2 . Doubling ω multiplies a by $2^2 = 4$.
4. False. For a conical pendulum $T = 2\pi\sqrt{\frac{l\cos\theta}{g}} = 2\pi\sqrt{\frac{h}{g}}$: the mass m cancels when the vertical equilibrium ($T\cos\theta = mg$) is combined with the radial equation. The period depends only on l , θ (or h) and g .

SOLUTION Exercise 3 — Definitions

1. Angular speed ω : the angle swept out per unit time by the radius joining the particle to the centre, $\omega = \frac{\theta}{t}$ (constant for uniform circular motion). SI unit: rad s^{-1} .

2. Period T : the time taken by the particle to complete exactly one full revolution. SI unit: the second (s). It satisfies $\omega = \frac{2\pi}{T}$.
3. Centripetal acceleration $\vec{a}$: the acceleration of a particle in circular motion, directed along the radius towards the centre, of magnitude $a = \frac{v^2}{r} = \omega^2 r$. SI unit: m s^{-2} .
4. Conical pendulum: a system consisting of a small bob of mass m attached to a fixed point by a light inextensible string of length l , the bob describing a horizontal circle with uniform speed so that the string sweeps out the surface of a cone, making a constant angle θ with the vertical.

SOLUTION Exercise 4 — Direct calculations

Given: 1500 rpm, i.e. frequency $f = \frac{1500}{60} = 25 \text{ Hz}$; radius $r = 12 \text{ cm} = 0.12 \text{ m}$.

1. Angular speed:

$$\omega = 2\pi f = 2\pi \times 25 = 50\pi \approx 157.1 \text{ rad s}^{-1}.$$

2. Period:

$$T = \frac{1}{f} = \frac{1}{25} = 0.04 \text{ s}.$$

3. Linear speed of a point at $r = 0.12 \text{ m}$:

$$v = \omega r = 50\pi \times 0.12 = 6\pi \approx 18.8 \text{ m s}^{-1}.$$

SOLUTION Exercise 5 — Stone whirled on a table

Given: $m = 0.5 \text{ kg}$, $r = 0.8 \text{ m}$, $f = 2 \text{ rev s}^{-1}$.

1. Angular speed:

$$\omega = 2\pi f = 2\pi \times 2 = 4\pi \approx 12.6 \text{ rad s}^{-1}.$$

2. Linear speed:

$$v = \omega r = 4\pi \times 0.8 = 3.2\pi \approx 10.1 \text{ m s}^{-1}.$$

3. Centripetal acceleration:

$$a = \omega^2 r = (4\pi)^2 \times 0.8 = 12.8\pi^2 \approx 126.3 \text{ m s}^{-2}.$$

4. On the frictionless table, the weight and the normal reaction cancel vertically; the **tension** alone provides the centripetal force:

$$T = m\omega^2 r = 0.5 \times 12.8\pi^2 = 6.4\pi^2 \approx 63.2 \text{ N}.$$

SOLUTION Exercise 6 — Car rounding a bend

Given: $m = 900 \text{ kg}$, $r = 50 \text{ m}$, $\mu = 0.6$, $g = 10 \text{ m s}^{-2}$.

1. The bend is flat, so the normal reaction is vertical and balances the weight. The only horizontal force available is the **friction** between the tyres and the road: it is friction that provides the centripetal force, directed towards the centre of the bend.
2. Vertically: $R = mg$. The maximum friction is $F_{\max} = \mu R = \mu mg$. At the limiting speed $v_{\max}$:

$$\frac{mv_{\max}^2}{r} = \mu mg \implies v_{\max} = \sqrt{\mu gr} = \sqrt{0.6 \times 10 \times 50} = \sqrt{300} \approx 17.3 \text{ m s}^{-1}.$$

(About 62 km h^{-1} .) Note that the mass cancels: the limiting speed does not depend on m .

3. If the driver exceeds $v_{\max}$, the required centripetal force $\frac{mv^2}{r}$ exceeds the maximum available friction: the tyres lose grip and the car skids outwards, leaving the circular path (it moves off along a curve of larger radius, tangentially outwards).

SOLUTION Exercise 7 — Belt-driven pulleys

Given: $r_1 = 10 \text{ cm} = 0.10 \text{ m}$, $r_2 = 25 \text{ cm} = 0.25 \text{ m}$, small pulley at 300 rpm.

1. The belt does not slip, so every point of the belt has the same linear speed v . At the rim of each pulley, the point of contact must move with the belt (no relative motion), hence the rim speeds of both pulleys equal the belt speed: $v_1 = v_2 = v$.
2. Equality of rim speeds gives $\omega_1 r_1 = \omega_2 r_2$, so

$$\omega_2 = \omega_1 \frac{r_1}{r_2} = 300 \times \frac{10}{25} = 120 \text{ rpm}.$$

$$\text{In rad s}^{-1}: \omega_2 = 120 \times \frac{2\pi}{60} = 4\pi \approx 12.6 \text{ rad s}^{-1}.$$

3. Belt speed (using the small pulley, $\omega_1 = 300 \times \frac{2\pi}{60} = 10\pi \text{ rad s}^{-1}$):

$$v = \omega_1 r_1 = 10\pi \times 0.10 = \pi \approx 3.14 \text{ m s}^{-1}.$$

(Check with the large pulley: $4\pi \times 0.25 = \pi \text{ m s}^{-1}$ — consistent.)

SOLUTION Exercise 8 — Coin on a turntable

Given: $r = 20 \text{ cm} = 0.20 \text{ m}$, $\mu = 0.5$, $g = 10 \text{ m s}^{-2}$.

1. Vertically the coin is in equilibrium: $R = mg$. The centripetal force is supplied by static friction, $F = m\omega^2 r$, and slipping begins when F reaches $\mu R = \mu mg$:

$$m\omega_{\max}^2 r = \mu mg \quad \Rightarrow \quad \omega_{\max} = \sqrt{\frac{\mu g}{r}} = \sqrt{\frac{0.5 \times 10}{0.20}} = \sqrt{25} = 5 \text{ rad s}^{-1}.$$

2. Converting to revolutions per minute:


$$N = \omega_{\max} \times \frac{60}{2\pi} = 5 \times \frac{60}{2\pi} = \frac{150}{\pi} \approx 47.7 \text{ rpm}.$$

SOLUTION Exercise 9 — The conical pendulum: structured question

Given: $m = 0.4 \text{ kg}$, $l = 1.2 \text{ m}$, $\theta = 37^\circ$, $\sin 37^\circ = 0.6$, $\cos 37^\circ = 0.8$, $g = 10 \text{ m s}^{-2}$.

Indicative mark scheme (total 16 marks) is given within each part.

1. Diagram (2 marks). 1 mark for the two forces only: tension T along the string towards the support and weight mg vertically downwards; 1 mark for showing the horizontal circle, the angle θ with the vertical and the centre O of the circle. No “centripetal force” may be drawn as a separate force.



Forces on the bob of a conical pendulum.

2. Vertical resolution (3 marks). The bob has no vertical acceleration, so (M1 for resolving):

$$T \cos \theta = mg \quad \Rightarrow \quad T = \frac{mg}{\cos \theta} = \frac{0.4 \times 10}{0.8} = 5 \text{ N}.$$

(A1 for the equation, A1 for the value.)

3. Radial equation (2 marks). The horizontal component of the tension provides the cen-

tripetal force, with $r = l \sin \theta$:

$$T \sin \theta = m\omega^2 r = m\omega^2 l \sin \theta.$$

(M1 for identifying $T \sin \theta$ as the radial resultant, A1 for $r = l \sin \theta$.)

4. Angular speed (3 marks). Dividing by $m \sin \theta$ (M1):

$$\omega^2 = \frac{T}{ml} = \frac{5}{0.4 \times 1.2} = \frac{5}{0.48} \approx 10.42 \implies \omega \approx 3.23 \text{ rad s}^{-1}.$$

(M1 for substitution, A1 for the value. Equivalently $\omega = \sqrt{g/(l \cos \theta)} = \sqrt{10/0.96}$.)

5. Linear speed and period (4 marks). Radius: $r = l \sin \theta = 1.2 \times 0.6 = 0.72 \text{ m}$ (B1).

$$v = \omega r = 3.23 \times 0.72 \approx 2.32 \text{ m s}^{-1} \quad (\text{A1}); \quad T_{\text{period}} = \frac{2\pi}{\omega} = \frac{2\pi}{3.23} \approx 1.95 \text{ s} \quad (\text{M1 A1}).$$

6. Assumptions (2 marks, 1 each). The string is light (negligible mass) and inextensible (constant length); air resistance is neglected (the motion continues at constant angular speed).

SOLUTION Exercise 10 — Derivation of the period formula

1. Derivation (6 marks). Consider the bob of mass m describing a horizontal circle of radius $r = l \sin \theta$ with uniform angular speed ω . The forces on the bob are only: its weight mg (vertically downwards) and the tension T of the string (along the string towards the point of suspension). (B1: correct force diagram; B1: statement of the two forces.)

Since the bob stays in a horizontal plane, its vertical acceleration is zero. Resolving vertically:

$$T \cos \theta = mg. \quad (\text{M1}) \tag{1}$$

The resultant in the horizontal (radial) direction is the component $T \sin \theta$, directed towards the centre; by Newton's second law with centripetal acceleration $\omega^2 r$:

$$T \sin \theta = m\omega^2 r = m\omega^2 l \sin \theta. \quad (\text{M1 A1}) \tag{2}$$

Dividing (2) by (1):

$$\tan \theta = \frac{\omega^2 l \sin \theta}{g} \implies \frac{\sin \theta}{\cos \theta} = \frac{\omega^2 l \sin \theta}{g},$$

and since $\sin \theta \neq 0$ (the pendulum actually rotates), we cancel $\sin \theta$:

$$\boxed{\omega^2 = \frac{g}{l \cos \theta}} \quad (\text{A1}).$$

2. Period (3 marks). The vertical distance from the suspension point to the plane of the circle is $h = l \cos \theta$ (B1). Hence $\omega^2 = \frac{g}{h}$, and since $\omega = \frac{2\pi}{T}$:

$$\frac{4\pi^2}{T^2} = \frac{g}{h} \implies T = 2\pi\sqrt{\frac{h}{g}} \quad (\text{M1 A1}).$$

The period depends only on the height h , not on m , l or θ separately.

3. Comparison (4 marks). From $\omega^2 = \frac{g}{l \cos \theta}$ with the same ω for both pendulums:

$$l_1 \cos \theta_1 = l_2 \cos \theta_2 = \frac{g}{\omega^2} \implies \cos \theta = \frac{g}{\omega^2 l}. \quad (\text{M1})$$

Thus $\cos \theta$ is a decreasing function of l : the longer pendulum ($l = 1.5$ m) has the smaller $\cos \theta$. Since cosine decreases on $[0, 90^\circ]$, a smaller $\cos \theta$ means a larger angle θ (A1, A1 for the reasoning). Conclusion: the pendulum of length 1.5 m makes the larger angle with the vertical (A1).

4. Linear speed (5 marks). From (2): $m\omega^2 l \sin \theta = T \sin \theta$, and with (1), $T = \frac{mg}{\cos \theta}$, so $\omega^2 = \frac{g}{l \cos \theta}$ (M1). Then

$$v = \omega r = \omega l \sin \theta \implies v^2 = \omega^2 l^2 \sin^2 \theta = \frac{g l^2 \sin^2 \theta}{l \cos \theta} = gl \frac{\sin^2 \theta}{\cos \theta} = gl \sin \theta \tan \theta. \quad (\text{M1 A1})$$

Hence $v = \sqrt{gl \sin \theta \tan \theta}$.

Numerically, with $l = 2.0$ m, $\theta = 30^\circ$, $\sin 30^\circ = 0.5$, $\tan 30^\circ = \frac{1}{\sqrt{3}} \approx 0.5774$, $g = 9.81 \text{ m s}^{-2}$:

$$v = \sqrt{9.81 \times 2.0 \times 0.5 \times 0.5774} = \sqrt{5.664} \approx 2.38 \text{ m s}^{-1}. \quad (\text{M1 A1})$$

SOLUTION Exercise 11 — Circular orbits: extension problem

1. Centripetal force (3 marks). $F = \frac{mv^2}{r}$ (B1), directed towards the centre of the Earth (B1). It is provided entirely by the **gravitational attraction** of the Earth on the satellite (B1) — there is no engine or string.
2. Orbital speed (4 marks). The gravitational force per unit mass is $g' = 8.7 \text{ N kg}^{-1}$, so the gravitational force on the satellite is mg' . Equating this to the centripetal force (M1):

$$mg' = \frac{mv^2}{r} \implies v = \sqrt{g'r} \quad (\text{M1}).$$

$$v = \sqrt{8.7 \times 6.9 \times 10^6} = \sqrt{6.003 \times 10^7} \approx 7.75 \times 10^3 \text{ m s}^{-1} \approx 7.7 \text{ km s}^{-1}. \quad (\text{A1 A1})$$


3. Period (4 marks).

$$T = \frac{2\pi r}{v} \quad (\text{M1}) = \frac{2\pi \times 6.9 \times 10^6}{7.75 \times 10^3} \approx 5.59 \times 10^3 \text{ s} \quad (\text{A1}).$$

Converting: $T \approx \frac{5590}{60} \approx 93 \text{ min}$ (M1 A1) — about one and a half hours, typical of a low Earth orbit.

4. Why it stays in orbit (3 marks). The acceleration is perpendicular to the velocity at every instant, so it changes only the direction of the velocity, not its magnitude (B1). The satellite is in permanent “free fall” towards the Earth, but its large tangential speed means that as it falls, the Earth’s surface curves away beneath it (B1): it continually falls around the Earth, staying at the same radius (B1).
5. Larger orbit (3 marks). From part (b), $v^2 = g'r$ with g' the gravitational field at radius r . More fundamentally, gravity supplies $m\omega^2 r$, and the gravitational force decreases as r increases while the required centripetal force per unit mass $\omega^2 r$ would increase if ω stayed constant (M1). Equating gravitational force to $m\omega^2 r$ shows $\omega^2 = \frac{g'}{r}$ decreases (both because g' decreases and r increases) (M1). Hence the angular speed decreases in a larger orbit (A1) — distant satellites revolve more slowly.

12 SUMMARY SHEET



Mind map of the chapter: uniform circular motion and the conical pendulum.

FICHE BILAN L'essentiel à connaître pour l'examen

1. Key definitions

- **Circular motion**: motion of a particle along a circular path of radius r ; it is uniform when the speed v is constant.
- **Angular displacement** θ : angle swept by the radius, measured in radians ($2\pi \text{ rad} = 360^\circ$).
- **Angular speed** $\omega = \frac{\theta}{t} = \frac{2\pi}{T} = 2\pi f$ (in rad s^{-1}), where T is the **period** and f the **frequency** (in Hz).
- **Linear speed** v : distance travelled per unit time along the arc; $v = \frac{2\pi r}{T}$.
- **Conical pendulum**: a particle attached to a string whose other end is fixed, moving in a horizontal circle so that the string sweeps out a cone of semi-vertical angle α .

2. Laws, formulas and theorems to know

- Arc length: $s = r\theta$ (θ in radians).

- Relationship between linear and angular speed:

$$v = r\omega \quad \text{hence} \quad v = \frac{2\pi r}{T} = 2\pi r f.$$

- Centripetal acceleration** (directed towards the centre):

$$a = \frac{v^2}{r} = r\omega^2 = v\omega = \frac{4\pi^2 r}{T^2}.$$

- Centripetal force** (Newton's second law applied radially):

$$F = ma = \frac{mv^2}{r} = mr\omega^2.$$

It is not a new force: it is the resultant of real forces (tension, friction, weight component, reaction) directed towards the centre.

- Conical pendulum (string of length l , semi-vertical angle α , height of cone $h = l \cos \alpha$):

- Vertical equilibrium: $T \cos \alpha = mg$ (here T = tension).

- Radial equation: $T \sin \alpha = \frac{mv^2}{r} = mr\omega^2$, with $r = l \sin \alpha$.

- Angular speed: $\omega = \sqrt{\frac{g}{h}} = \sqrt{\frac{g}{l \cos \alpha}}$.

- Period: $T = 2\pi \sqrt{\frac{h}{g}} = 2\pi \sqrt{\frac{l \cos \alpha}{g}}$; linear speed: $v = r\omega = \sqrt{gr \tan \alpha}$.

- Banking of a track (no friction): $\tan \alpha = \frac{v^2}{rg}$.

3. Methods

- To solve any circular motion problem: (1) draw the force diagram; (2) resolve vertically (equilibrium if no vertical motion) and horizontally towards the centre (Newton's second law = $mr\omega^2$); (3) eliminate unknowns.
- To convert units: rev/min $\rightarrow$ rad/s: multiply by $\frac{2\pi}{60}$; km/h $\rightarrow$ m/s: divide by 3.6.
- Conical pendulum: identify h (vertical distance from support to the plane of the circle), then apply $\omega = \sqrt{g/h}$.

4. Common mistakes

- Mixing degrees and radians: all formulas ($s = r\theta$, $v = r\omega$) require radians.
- Believing a "centrifugal force" pushes the particle outwards: in an inertial frame only the inward centripetal resultant acts.
- Writing $F = mv^2/r$ as an extra force on the diagram: it is the resultant, never an additional force.

- Confusing T (period, in seconds) with T (tension, in newtons) – use different symbols.
- For the conical pendulum, using l instead of $h = l \cos \alpha$ in $T = 2\pi\sqrt{h/g}$, or l instead of $r = l \sin \alpha$ in $v = r\omega$.
- Forgetting that constant speed does not mean zero acceleration: the velocity changes direction continuously.

5. GCE tips

- Quote $v = r\omega$ and $a = v^2/r$ before substituting; method marks are awarded for correct formulas.
- Show the force diagram clearly: examiners award marks for correct resolution (vertical / radial).
- Keep $g = 9.81 \text{ m s}^{-2}$ (or 9.8 as instructed) and give the final answer to 3 significant figures with units.
- Typical GCE items: car on a banked bend, stone on a string, satellite in circular orbit, conical pendulum period – practise deriving $T = 2\pi\sqrt{l \cos \alpha / g}$ from scratch; the derivation itself is examinable.
- Check coherence: larger r at fixed $\omega \Rightarrow$ larger v and larger a ; larger α in a conical pendulum $\Rightarrow$ shorter period.



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+