

PHYSICS • UPPER SIXTH

UPPER SIXTH — PHYSICS

CHAPTER 4

MECHANICAL WAVES (CONTINUED)

SUGGESTED TIME: 2 PERIODS

IN THIS CHAPTER

This chapter completes the study of mechanical waves by examining two key topics: the polarization of transverse waves, which proves their transverse nature and has major technological applications, and the factors that determine the speed of transverse waves on taut strings and wires, essential for understanding musical instruments and wave transmission.

- By the end of this chapter I can define polarization and distinguish polarized from unpolarized transverse waves
- By the end of this chapter I can demonstrate polarization using a mechanical model (rope and slits) and explain why longitudinal waves cannot be polarized
- By the end of this chapter I can describe how plane polarized light is produced using a polarizer and detected with an analyser
- By the end of this chapter I can state and apply Malus's law for the intensity of light transmitted through two polaroids (GCE extension)
- By the end of this chapter I can list practical applications of polarization (sunglasses, LCD screens, stress analysis)
- By the end of this chapter I can state the factors affecting the speed of a transverse wave on a taut string



DOWNLOAD ON- BUCH

Free • Google Play
AI tutor, past papers,
results



GO ONBUCH+

All signed courses, unlimited AI
tutor, PDF sheets — OnBuch+
tab in the app

THIS SIGNED COURSE CONTAINS

COURSE

complete, illustrated,
step by step

METHODS

and worked examples

EXERCISES

exam style + solutions

SUMMARY SHEET

the essentials to
remember



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+

CONTENTS

- | | |
|---|-------------------------------------|
| 1. Polarization of Transverse Waves: Concept and Mechanical Demonstration | The Sonometer and Vibrating Strings |
| 2. Production and Detection of Plane Polarized Light; Applications | 5. Integration activity |
| 3. Speed of Transverse Waves on a Taut String: Factors and Formula | 6. Methods and worked examples |
| 4. Experimental Study and Applications: | 7. Exercises |
| | 8. Solutions to the exercises |
| | 9. Summary sheet |

CHAPTER OBJECTIVES

- By the end of this chapter I can define polarization and distinguish polarized from unpolarized transverse waves
- By the end of this chapter I can demonstrate polarization using a mechanical model (rope and slits) and explain why longitudinal waves cannot be polarized
- By the end of this chapter I can describe how plane polarized light is produced using a polarizer and detected with an analyser
- By the end of this chapter I can state and apply Malus's law for the intensity of light transmitted through two polaroids (GCE extension)
- By the end of this chapter I can list practical applications of polarization (sunglasses, LCD screens, stress analysis)
- By the end of this chapter I can state the factors affecting the speed of a transverse wave on a taut string
- By the end of this chapter I can derive and use the relation $v = \sqrt{T/\mu}$ where μ is the mass per unit length
- By the end of this chapter I can combine $v = f\lambda$ with $v = \sqrt{T/\mu}$ to solve problems on vibrating strings and musical notes
- By the end of this chapter I can describe an experiment (sonometer) to investigate how wave speed depends on tension and linear density

PREREQUISITES

- Definition and properties of transverse and longitudinal waves (Lower Sixth / PHY03)
- The wave equation $v = f\lambda$ and the relation $T = 1/f$
- Concepts of amplitude, wavelength, frequency and phase of a progressive wave
- Basic notion that light is an electromagnetic (transverse) wave
- Force, tension and mass per unit length (linear density) from mechanics

1 POLARIZATION OF TRANSVERSE WAVES: CONCEPT AND MECHANICAL DEMONSTRATION

At a busy junction in Douala, a motorbike rider tilts his polarized sunglasses and suddenly the blinding glare from a car's windscreen disappears — yet his friend with ordinary glasses still squints. Meanwhile, in a village near Bamenda, a musician tightens the string of his mvet and the note rises higher. What do sunglasses and a tightened string have in common? Both are governed by the behaviour of **transverse waves**: one by the orientation of their vibrations, the other by the speed at which disturbances travel along a stretched medium. This chapter reveals the physics behind these everyday observations. We begin with the first idea: the orientation of vibrations, which leads us to the phenomenon of **polarization**.

1.1 Recall: Transverse and Longitudinal Waves

Before we can speak of polarization, we must be absolutely clear about the two fundamental ways in which a mechanical disturbance can travel through a medium. The classification depends on one single question: in which direction do the particles of the medium vibrate, compared with the direction in which the wave travels?

DEFINITION Transverse and longitudinal waves

A wave is **transverse** when the particles of the medium vibrate perpendicular to the direction of propagation of the wave. Examples: a wave on a stretched rope, ripples on the surface of water (approximately), electromagnetic waves.

A wave is **longitudinal** when the particles of the medium vibrate parallel to the direction of propagation, producing alternating compressions and rarefactions. Example: sound in air.

Picture a rope tied at one end to a wall in the school laboratory. If you jerk the free end up and down, a hump travels along the rope: each bit of rope moves vertically while the hump moves horizontally. That is a transverse wave. Now picture a long spring (a “slinky”) lying on a bench: if you push and pull one end along the axis of the spring, coils bunch together and spread apart, and this compression pulse travels along the spring while each coil moves back and forth along the axis. That is a longitudinal wave.

The crucial point for what follows is this: for a transverse wave, the direction of vibration is not uniquely fixed by the direction of propagation. If the wave travels horizontally, the vibration may be vertical, horizontal (perpendicular to travel), or in any direction lying in the plane perpendicular to propagation. There is a whole family of possible vibration directions. For a longitudinal wave, by contrast, there is no freedom at all: the vibration is forced to lie along the direction of propagation itself. This asymmetry is the deep reason why polarization exists for transverse waves only.

KEY POINTS The key distinction

For a transverse wave propagating along a given direction, the vibration can take place in any direction perpendicular to propagation: infinitely many choices. For a longitudinal wave, the vibration direction is unique: it is the direction of propagation.

1.2 Unpolarized and Plane Polarized Transverse Waves

Imagine you shake the end of a long rope randomly — sometimes up and down, sometimes left and right, sometimes diagonally, changing direction unpredictably many times per second. A transverse wave still travels along the rope, but at any fixed point of the rope the vibration direction changes continually and randomly. The vibrations occur in all planes containing the direction of propagation. Such a wave is said to be **unpolarized**.

Now imagine instead that you shake the end of the rope strictly up and down, always in the same vertical line. Every particle of the rope then vibrates vertically, and the whole wave — all its crests and troughs — lies in one single vertical plane. The vibration has been restricted to a single plane. This is the phenomenon of polarization.

DEFINITION Polarization of a transverse wave

A transverse wave is said to be **plane polarized** (or linearly polarized) when the vibrations of the particles of the medium are restricted to a single fixed direction (and therefore to a single plane containing the direction of propagation). Polarization is the operation or phenomenon by which the vibrations of a transverse wave, initially distributed in many directions, are confined to one direction only.

A wave whose vibrations occur randomly in all directions perpendicular to propagation is said to be **unpolarized**.

DEFINITION Plane of polarization

The **plane of polarization** of a plane polarized wave is the plane that contains both:


- the direction of vibration of the particles of the medium, and
- the direction of propagation of the wave.

For a rope wave travelling horizontally with vertical vibrations, the plane of polarization is the vertical plane containing the rope.


WARNING Do not confuse the two directions

Students frequently mix up the direction of vibration and the direction of propagation.

They are perpendicular to each other for a transverse wave. The plane of polarization is the plane spanned by these two perpendicular directions — it is not perpendicular to the propagation; on the contrary, it contains the direction of propagation.



Unpolarized wave: vibrations in all planes containing the axis



Plane polarized wave: vibrations confined to one plane

An unpolarized transverse wave (left) vibrates in many planes containing the direction of propagation; a plane polarized wave (right) vibrates in one single plane.

1.3 Mechanical Demonstration: The Rope and the Two Slits

The beauty of polarization is that it can be demonstrated with the simplest apparatus imaginable: a rope and two rigid screens, each pierced with a straight slit.

EXPERIMENT The rope-and-slit demonstration

Apparatus: a long flexible rope stretched horizontally; two rigid screens S_1 and S_2 , each with a straight slit that can be oriented vertically or horizontally; the rope passes freely through both slits.


Step 1 — Parallel slits. Shake the free end of the rope randomly so that an unpolarized transverse wave travels towards S_1 . Orient the slit of S_1 vertically.

- At S_1 , only the vertical component of the vibration can pass through the vertical slit; horizontal vibrations are stopped by the board. Beyond S_1 , the rope vibrates vertically only: the wave is now plane polarized in the vertical plane. S_1 acts as a **polarizer**.
- Place S_2 further along the rope with its slit also vertical. The vertically polarized wave passes through S_2 almost undisturbed: the wave is transmitted. S_2 acts as an **analyser**: it tests the state of polarization.

Step 2 — Crossed slits. Keep S_1 vertical but rotate the slit of S_2 to the horizontal position.

- The wave arriving at S_2 vibrates vertically, but the slit only allows horizontal motion. The board blocks the vibration completely: beyond S_2 the rope remains at rest. The wave is stopped — no transmission.

Conclusion: a transverse wave passes through two parallel slits but is blocked by two crossed slits. The first slit polarizes the wave; the second analyses it.



The rope-and-slit model. Top: two parallel vertical slits — the vertically polarized wave is transmitted. Bottom: crossed slits (vertical then horizontal) — the horizontal slit blocks the vertical vibration and nothing passes.

The vocabulary introduced here is used throughout physics and at the GCE examination:

DEFINITION Polarizer and analyser

A **polarizer** is a device which, receiving an unpolarized transverse wave, transmits only the component of vibration parallel to one privileged direction: it produces a plane polarized wave. In the rope model, the polarizer is the first slit.

An **analyser** is a device, identical in nature to the polarizer, used to detect the state of polarization of the wave: rotating it and observing whether the wave is transmitted or blocked reveals the plane of polarization. In the rope model, the analyser is the second slit.

METHOD Predicting transmission with the rope-and-slit model

To decide whether a transverse wave is transmitted through a system of slits (or polarizers), proceed step by step:

1. Identify the state of the incident wave. Is it unpolarized (vibrations in all directions) or already plane polarized? If polarized, note the direction of vibration.
2. Apply the first slit (polarizer). Only the component of vibration parallel to the slit passes. After the slit, the wave is plane polarized along the slit direction.

3. Apply the second slit (analyser). Compare the vibration direction of the wave arriving at the analyser with the orientation of its slit.
4. Conclude:
 - slit parallel to the vibration $\Rightarrow$ wave transmitted (maximum);
 - slit perpendicular to the vibration (crossed) $\Rightarrow$ wave completely blocked;
 - slit at an intermediate angle $\theta \Rightarrow$ only the component of the vibration along the slit is transmitted (amplitude reduced by factor $\cos \theta$, intensity by $\cos^2 \theta$).

WORKED EXAMPLE 1 Two slits on a rope

A long horizontal rope carries a transverse wave. The rope passes through slit A, which is vertical, and then through slit B, which makes an angle of 90° with slit A (i.e. it is horizontal). The free end of the rope is shaken randomly.

1. What is the state of polarization of the wave between A and B?
2. Is any wave observed beyond B? Justify.
3. Slit B is now rotated until it is vertical. What happens?

SOLUTION

1. The incident wave is unpolarized: the random shaking produces vibrations in all directions perpendicular to the rope. Slit A is vertical, so it transmits only the vertical component of the vibration. Between A and B the rope vibrates vertically only: the wave is plane polarized in the vertical plane, with A acting as polarizer.
2. Slit B is horizontal, i.e. crossed with the vertical vibration arriving at it. A vertical vibration cannot pass through a horizontal slit, so the wave is completely blocked: the rope beyond B remains at rest. No wave is observed beyond B.
3. With B vertical, its slit is now parallel to the vertical vibration of the polarized wave. The wave is transmitted through B with essentially its full amplitude: a vertical vibration is observed on the rope beyond B. This is exactly the crossed-versus-parallel behaviour predicted by the rope-and-slit model.

1.4 Why Longitudinal Waves Cannot Be Polarized

Let us now ask the question the other way round: could a sound wave in air be polarized? Suppose we try to build the analogue of the rope-and-slit experiment for sound. Sound in air is a longitudinal wave: the air molecules oscillate back and forth along the direction of propagation. Whatever “filter” we imagine placing across the beam, the vibration direction is already fixed — it is the direction of travel itself. There is no transverse component to select, no orientation to restrict, and rotating any analyser around the direction of propagation changes nothing, because the situation is perfectly symmetric about that axis.

PROPERTY Polarization is the test of transversality

Only **transverse waves** can be polarized. A longitudinal wave (such as sound in air) cannot be polarized, because its vibration direction is uniquely fixed along the direction of propagation: there is no freedom of orientation to restrict.

Conversely, if a wave phenomenon can be polarized — if an analyser can be found which, when rotated, extinguishes the wave — then the wave is necessarily transverse. Polarization is therefore the decisive experimental proof of the transverse nature of a wave. (This reasoning is examinable: state it clearly and justify it with the rope-and-slit model.)

This is precisely how physicists established that light is a transverse wave. Light cannot be seen to vibrate directly, but it can be polarized — as the Douala rider's sunglasses prove — and polarization is only possible for transverse vibrations. Sound in air, which can never be polarized, is confirmed to be longitudinal.

WARNING Common mistake: “polarizing” sound

A very frequent error at the GCE is to claim that sound waves can be polarized, or to apply the polarizer–analyser description to sound in air. This is wrong: sound in air (and in fluids generally) is longitudinal; the vibration is along the direction of propagation, so no slit or filter can extinguish it by rotation. Never write that “the polarizer blocks the sound”. The correct statement is: sound in air cannot be polarized because it is a longitudinal wave.

DID YOU KNOW? Polarized sunglasses and glare

Light reflected by a horizontal surface — a wet road in Douala, the bonnet or windscreen of a car, the surface of the Wouri river — becomes partially polarized, with its vibration preferentially horizontal. Polarized sunglasses contain a plastic film whose molecules act like a microscopic “slit” oriented vertically: they transmit the vertical component and absorb the horizontal glare. Tilt your head (rotate the “analyser”) and the glare returns — the everyday version of the crossed-slits experiment! Ordinary tinted glasses merely dim everything without selecting any vibration direction, which is why the rider's friend keeps squinting.

EXERCISE 1 Testing your understanding

1. Define a plane polarized transverse wave and state what is meant by its plane of polarization.
2. In the rope-and-slit experiment, the first slit is vertical and the second makes an angle of 90° with the first. Explain, step by step, why no vibration is observed beyond the second slit.

3. A student claims: “Since sound can be blocked by a wall, it can also be blocked by an analyser, so sound can be polarized.” Identify the two errors in this statement and correct them.
4. Explain why the fact that light can be polarized proves that light is a transverse wave.

SOLUTION Exercise 1

1. A plane polarized transverse wave is a wave whose particle vibrations are restricted to a single fixed direction perpendicular to the propagation. The plane of polarization is the plane containing the direction of vibration and the direction of propagation.
2. The randomly shaken rope sends an unpolarized wave onto the first (vertical) slit, which transmits only the vertical component: the wave becomes plane polarized vertically. Arriving at the second (horizontal) slit, the vertical vibration is perpendicular to the slit and cannot pass; the board absorbs it. The rope beyond the second slit therefore does not vibrate.
3. First error: blocking a wave by absorption (a wall) is not polarization; polarization is a selection of a vibration direction, not a mere stopping of energy. Second error: sound in air is longitudinal, its vibration lies along the propagation direction, so rotating any analyser cannot extinguish it. Sound in air cannot be polarized.
4. Only transverse waves possess a vibration direction that can vary around the propagation axis and can therefore be restricted to one plane. Since experiments (polarizer and analyser, extinction by crossed polarizers) succeed with light, light must have a transverse vibration: light is a transverse wave.

KEY POINTS Summary of Section 1

- A transverse wave vibrates perpendicular to propagation; a longitudinal wave vibrates parallel to propagation.
- **Polarization** is the restriction of the vibrations of a transverse wave to a single direction; the **plane of polarization** contains the vibration direction and the propagation direction.
- An unpolarized wave vibrates in all planes containing the direction of propagation.
- The rope-and-slit experiment models the **polarizer** (first slit) and the **analyser** (second slit): parallel slits transmit, crossed slits block.
- Only transverse waves can be polarized; polarization is the experimental test of transversality. Sound in air, being longitudinal, can never be polarized.

2 PRODUCTION AND DETECTION OF PLANE POLARIZED LIGHT; APPLICATIONS

In the previous section we established, with the help of a rope and a pair of slits, that a transverse wave can be **polarized**: its vibrations can be confined to a single plane. We also saw that a longitudinal wave (sound, for example) can never be polarized. We now turn to light. The fact that light can be polarized was historically one of the strongest proofs that light is a **transverse wave**. In this section we explain what polarized light is, how it is produced, how it is detected, and why the phenomenon is so useful in everyday technology.



2.1 Light as a Transverse Electromagnetic Wave

Light is an electromagnetic wave: it consists of an electric field $\vec{E}$ and a magnetic field $\vec{B}$ which vibrate perpendicular to each other and perpendicular to the direction of propagation. No material medium is needed: light travels through the vacuum of space from the Sun to Cameroon every day.

Because the vibrations are transverse, they can be polarized. By convention, the **plane of polarization** of a light wave is defined by the plane containing the **electric field vector** $\vec{E}$ and the direction of propagation. If $\vec{E}$ always vibrates along one fixed direction — say vertically — while the wave travels horizontally, the light is said to be **plane polarized** (or linearly polarized) in the vertical plane.

DEFINITION Unpolarized (natural) light

Ordinary light — from the Sun, a candle, or an electric bulb — is **unpolarized**. It is emitted by a huge number of atoms vibrating independently, so the electric field $\vec{E}$ vibrates in all possible directions perpendicular to the direction of propagation, changing randomly millions of times per second. There is no preferred plane of vibration.



Unpolarized light (left): $\vec{E}$ vibrates in every transverse direction. Plane polarized light (right): $\vec{E}$ vibrates along a single direction.

2.2 Producing Plane Polarized Light: the Polaroid Filter

The simplest way to polarize light is to pass it through a **polaroid** sheet. A polaroid is a plastic film containing long-chain molecules all aligned in the same direction (a process called dichro-

ism). These molecules strongly absorb the component of $\vec{E}$ that vibrates parallel to the chains, while transmitting the component vibrating perpendicular to them. The direction of the transmitted vibration is called the **transmission axis** of the polaroid.

DEFINITION Polarizer and analyser

A **polarizer** is a device (usually a polaroid sheet) that transforms unpolarized light into plane polarized light, by absorbing all vibrations except those parallel to its transmission axis. An **analyser** is a second polaroid, placed after the polarizer, used to detect and measure the state of polarization of the light. Rotating the analyser changes the transmitted intensity, which reveals the plane of polarization.

WARNING The polarizer does not “create” the vibration

The polarizer does not force light to vibrate in a new direction. It selects, from the randomly oriented vibrations of natural light, the component parallel to its transmission axis and absorbs the rest. Consequently, an ideal polarizer transmits only half of the incident unpolarized intensity: $I_0 = \frac{1}{2} I_{\text{incident}}$.

Other production methods (GCE–useful extras).

- Polarization by reflection. When unpolarized light reflects from a non-metallic surface (water, glass, a road), the reflected light is partially polarized parallel to the surface. At a particular angle of incidence, the **Brewster angle** θ_B , the reflected light is completely plane polarized and the reflected and refracted rays are perpendicular to each other. The Brewster angle satisfies $\tan \theta_B = n_2/n_1$, where n_1 and n_2 are the refractive indices of the two media. This is why glare from a wet road near Douala on a sunny afternoon is strongly polarized.
- Polarization by scattering. Blue skylight, scattered by air molecules, is partially polarized. Looking at the sky at 90° from the Sun through a polaroid and rotating it, the brightness changes noticeably.


2.3 Detecting Polarized Light: the Analyser and Crossed Polaroids

Place a second polaroid (the analyser) after the polarizer and rotate it slowly about the direction of propagation:

- when the transmission axes are **parallel** ($\theta = 0^\circ$), the transmitted intensity is **maximum**;
- as the analyser rotates, the intensity decreases continuously;
- when the axes are **perpendicular** ($\theta = 90^\circ$), the transmitted intensity is **zero**: the polaroids are said to be crossed and no light passes through.

PROPERTY Crossed polaroids

Two polaroids whose transmission axes are perpendicular ($\theta = 90^\circ$) transmit no light: the polarizer passes only vertical vibrations, and the analyser passes only horizontal ones, so nothing survives. This complete extinction is the experimental signature that light is a transverse wave.



Crossed polaroids: the polarizer produces vertically polarized light; the analyser, with a horizontal transmission axis, absorbs it completely. The transmitted intensity falls to zero.

2.4 Malus's Law (Examinable)

Let plane polarized light of intensity I_0 fall on an analyser whose transmission axis makes an angle θ with the plane of polarization of the incident light. Only the component of the electric field parallel to the analyser's axis is transmitted:

$$E_{\text{transmitted}} = E_0 \cos \theta.$$


Since the intensity of an electromagnetic wave is proportional to the square of the amplitude of its electric field, $I \propto E^2$, we obtain:

PROPERTY Malus's law

The intensity transmitted by an analyser whose axis makes an angle θ with the plane of polarization of the incident polarized light is

$$I = I_0 \cos^2 \theta$$

where I_0 is the intensity incident on the analyser. In particular $I = I_0$ for $\theta = 0^\circ$ (parallel axes) and $I = 0$ for $\theta = 90^\circ$ (crossed axes).



Malus's law: transmitted intensity $I = I_0 \cos^2 \theta$ as a function of the angle θ between the transmission axes of polarizer and analyser.

METHOD Identifying the polarizer and the analyser

In any two-polaroid problem:

1. The first filter met by the (unpolarized) light is the **polarizer**. It halves the intensity: $I_0 = \frac{1}{2} I_{\text{incident}}$.
2. The second filter is the **analyser**. Apply Malus's law between the two: $I = I_0 \cos^2 \theta$.
3. The angle θ is measured between the two transmission axes, never from the direction of propagation.
4. If a third polaroid is inserted, apply Malus's law step by step between consecutive filters.

WORKED EXAMPLE 2 Two crossed polaroids with a third inserted

Unpolarized light of intensity $I_i = 8.0 \text{ W m}^{-2}$ falls on a polarizer P_1 . A second polaroid P_2 is crossed with P_1 (90°). (a) What intensity emerges from P_2 ? (b) A third polaroid P_3 is inserted between them, with its axis at 45° to that of P_1 . Find the final transmitted intensity.

SOLUTION

(a) With P_1 and P_2 crossed, Malus's law gives

$$I = I_0 \cos^2 90^\circ = 0.$$

No light emerges: $I = 0 \text{ W m}^{-2}$.

(b) Step by step:

$$\text{After } P_1 : I_1 = \frac{1}{2}I_i = \frac{1}{2}(8.0) = 4.0 \text{ W m}^{-2}$$

$$\text{After } P_3 (\theta = 45^\circ) : I_2 = I_1 \cos^2 45^\circ = 4.0 \times (0.7071)^2 = 2.0 \text{ W m}^{-2}$$

$$\text{After } P_2 (\theta = 45^\circ \text{ to } P_3) : I_3 = I_2 \cos^2 45^\circ = 2.0 \times 0.5 = 1.0 \text{ W m}^{-2}$$

Remark: inserting P_3 at 45° makes light pass through a previously opaque system — a striking confirmation of the vector nature of $\vec{E}$.

WARNING Do not confuse the angles

The angle θ in Malus's law is the angle between the transmission axes of the polarizer and the analyser (or between the plane of polarization and the analyser axis). It has nothing to do with the angle of incidence of the light on the filter. Also remember: Malus's law applies to light that is already polarized; for unpolarized light falling on the first polaroid, simply divide the intensity by two.

2.5 Applications of Polarized Light

- **Polarized sunglasses.** Light reflected by horizontal surfaces (a wet road, the surface of the Wouri river) is partially polarized horizontally. The polaroid lenses of the glasses have a vertical transmission axis, so they block this glare while transmitting a good fraction of the useful light. Fishermen and drivers benefit greatly.
- **LCD screens.** A liquid-crystal display consists of a layer of liquid crystal sandwiched between two crossed polaroids. Applying a voltage rotates the plane of polarization locally, controlling pixel by pixel whether light passes — the basis of calculators, phones and television screens.
- **Photoelastic stress analysis.** Certain transparent plastics become doubly refracting when stressed. Placed between crossed polaroids, a model of a bridge or gear shows coloured fringes that reveal the zones of greatest mechanical stress — a tool used by engineers before construction.
- **3D cinema.** The two images (left eye and right eye) are projected with perpendicular planes of polarization; the viewer wears glasses whose two lenses are crossed polaroids, so each eye sees only its own image, creating the impression of depth.

DID YOU KNOW? Polarization in daily life

If you tilt your head while wearing polarized sunglasses and looking at an LCD screen, the screen appears to go dark at a certain angle: the screen's light is already polarized, and you have effectively "crossed" your glasses with it. This is a quick home test of both polarization

and Malus's law!

KEY POINTS Key points

- Light is a transverse electromagnetic wave; the direction of $\vec{E}$ defines the plane of polarization.
- Natural light is unpolarized: $\vec{E}$ vibrates in all transverse directions.
- A polarizer produces plane polarized light by selective absorption and transmits half the incident unpolarized intensity.
- An analyser detects polarization: intensity maximum for parallel axes, zero for crossed axes (90°).
- Malus's law: $I = I_0 \cos^2 \theta$, with θ the angle between transmission axes.
- Applications: sunglasses, LCD screens, stress analysis, 3D cinema.

EXERCISE 2 Polaroids at 30 degrees

Unpolarized light of intensity 12 W m^{-2} passes through a polarizer and then an analyser whose axis is at 30° to that of the polarizer. Calculate the intensity transmitted by the analyser.

SOLUTION Polaroids at 30 degrees

After the polarizer: $I_0 = \frac{1}{2}(12) = 6.0 \text{ W m}^{-2}$. Malus's law: $I = I_0 \cos^2 30^\circ = 6.0 \times (0.866)^2 = 6.0 \times 0.75 = 4.5 \text{ W m}^{-2}$.

3 SPEED OF TRANSVERSE WAVES ON A TAUT STRING: FACTORS AND FORMULA

In the previous section we studied how transverse waves can be polarised, and we insisted that the speed of a wave is a property of the medium that carries it. We now return to mechanical waves and ask a very concrete question: what determines the speed of a transverse wave travelling along a stretched string? This question is not academic. Every guitarist in Douala, every piano tuner, and every engineer who designs suspension cables must know the answer. In this section we identify the factors experimentally, derive the form of the formula by dimensional

analysis, and learn to use it confidently in numerical problems.

3.1 Qualitative Observations: What Does the Speed Depend On?

Take a guitar string and pluck it gently. A transverse disturbance runs along the string, is reflected at the fixed ends, and sets the string vibrating. Now perform two simple thought experiments (or, better, real ones in the school laboratory with a long rubber cord).

Observation 1: effect of tension. Tighten the string by turning the tuning peg, so that the tension T increases. Pluck it again: the note becomes higher (the frequency increases) and, if you watch a pulse travel along a long rope, you see that the disturbance now travels faster. Slacken the string and the pulse becomes sluggish. A loose rope can barely transmit a transverse wave at all, because there is almost no restoring force pulling a displaced element back towards the equilibrium position.

Observation 2: effect of the mass of the string. Compare a thin nylon string with a thick steel cable under the same tension. The pulse travels noticeably slower along the heavy cable. The heavier the string (per unit length), the more inertia each element of the string has, and the harder it is for the tension to accelerate it up and down.

These observations point to exactly two factors:

- the **tension** T in the string (in newtons): increasing T increases the wave speed;
- the **mass per unit length** of the string, which measures its inertia: increasing it decreases the wave speed.

DEFINITION Linear density (mass per unit length)

The **linear density** of a uniform string or wire is its mass divided by its length:

$$\mu = \frac{m}{L}$$

where m is the mass of the string (in kg) and L its length (in m). The SI unit of μ is the kilogram per metre, kg m^{-1} .

EXAMPLE Linear density of a guitar string

A steel guitar string has length $L = 0.65 \text{ m}$ and mass $m = 3.9 \text{ e} - 3 \text{ kg}$. Its linear density is

$$\mu = \frac{m}{L} = \frac{3.9 \times 10^{-3}}{0.65} = 6.0 \text{ e} - 3 \text{ kg m}^{-1}.$$

A bass string of the same length but mass $1.3 \text{ e} - 2 \text{ kg}$ has $\mu = 2.0 \text{ e} - 2 \text{ kg m}^{-1}$: it is more than three times “heavier per metre”, which is why it produces lower notes under comparable tension.

3.2 Dimensional Analysis: Finding the Form of the Formula

We suspect that the wave speed v depends only on T and μ . Let us suppose a relation of the form

$$v = k T^a \mu^b,$$

where k is a dimensionless constant and a, b are powers to be found. We use the dimensions of each quantity:

$$[v] = \text{L T}^{-1}, \quad [T] = \text{M L T}^{-2}, \quad [\mu] = \text{M L}^{-1}.$$

(Be careful: the symbol T is used for tension, while T in brackets denotes the dimension of time.) Equating dimensions on both sides:

$$\text{L T}^{-1} = (\text{M L T}^{-2})^a (\text{M L}^{-1})^b = \text{M}^{a+b} \text{L}^{a-b} \text{T}^{-2a}.$$

Matching the exponents of each dimension:

$$\begin{aligned} \text{Mass: } a + b &= 0, \\ \text{Length: } a - b &= 1, \\ \text{Time: } -2a &= -1 \Rightarrow a = \frac{1}{2}. \end{aligned}$$

From $a = \frac{1}{2}$ we get $b = -\frac{1}{2}$. Therefore

$$v = k T^{1/2} \mu^{-1/2} = k \sqrt{\frac{T}{\mu}}.$$

Dimensional analysis cannot give the dimensionless constant k ; a full mechanical treatment (applying Newton's second law to a small element of the string) shows that $k = 1$ exactly. Note the consistency check:

$$\left[\frac{T}{\mu} \right] = \frac{\text{M L T}^{-2}}{\text{M L}^{-1}} = \text{L}^2 \text{T}^{-2}, \quad \sqrt{\text{L}^2 \text{T}^{-2}} = \text{L T}^{-1} = [v]. \quad \checkmark$$

METHOD Dimensional-analysis check before applying any wave-speed formula

1. Write the formula you intend to use, e.g. $v = \sqrt{T/\mu}$.
2. Replace each quantity by its dimensions: $[T] = \text{M L T}^{-2}$, $[\mu] = \text{M L}^{-1}$, $[v] = \text{L T}^{-1}$.
3. Simplify the right-hand side: $\frac{\text{M L T}^{-2}}{\text{M L}^{-1}} = \text{L}^2 \text{T}^{-2}$, whose square root is L T^{-1} .
4. Compare with the left-hand side. If the dimensions agree, the formula is at least dimensionally correct; if not, the formula is certainly wrong (for example $v = \sqrt{\mu/T}$ fails the test immediately).
5. Repeat the check with SI units in every numerical calculation: T in newtons, μ in kg m^{-1} , giving v in m s^{-1} .

3.3 The Wave-Speed Formula

PROPERTY Speed of a transverse wave on a taut string


The speed of a transverse wave travelling along a taut string of linear density μ under tension T is

$$v = \sqrt{\frac{T}{\mu}}$$

where

- v is the wave speed, in m s^{-1} ;
- T is the tension in the string, in newtons (N);
- $\mu = m/L$ is the mass per unit length, in kg m^{-1} .

The derivation from Newton's second law applied to a string element is not required at this level, but the dimensional-analysis derivation above is examinable.



A pulse travelling with speed v along a taut string fixed at both ends. The tension T pulls on every element of the string; the linear density μ measures its inertia.

PROPERTY The medium fixes the speed, not the source

For a given string under a given tension, the speed $v = \sqrt{T/\mu}$ is fixed once and for all. It does not depend on:

- the **frequency** f of the wave;
- the **amplitude** of the disturbance (for small oscillations);
- the shape of the pulse or the way the string was plucked.

If the source vibrates faster, it is the wavelength $\lambda = v/f$ that adjusts, not the speed. This is a general feature of waves in non-dispersive media: the medium determines the speed.

3.4 Combining with the Wave Equation $v = f\lambda$

Every progressive wave also obeys the universal relation $v = f\lambda$. Combining this with $v = \sqrt{T/\mu}$

gives a powerful tool linking the four quantities:


$$f\lambda = \sqrt{\frac{T}{\mu}} \quad \Longleftrightarrow \quad f = \frac{1}{\lambda} \sqrt{\frac{T}{\mu}}.$$

For a string of length L fixed at both ends and vibrating in its fundamental mode, the length of the string is half a wavelength, $\lambda = 2L$, so the fundamental frequency is

$$f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}.$$

This single formula explains the whole design of stringed instruments:

- **Tightening** a string (increasing T) raises the pitch: this is what a musician does with the tuning pegs.
- **Shortening** the vibrating part of the string (smaller L) gives higher notes: this is why the player presses the string against the frets.
- **Thinner** strings (smaller μ) give higher notes: this is why the treble strings of a piano or guitar are thin and the bass strings are thick or wound with extra wire.



For a fixed string (constant μ), the wave speed v is proportional to $\sqrt{T}$: the graph of v against $\sqrt{T}$ is a straight line through the origin, of slope $1/\sqrt{\mu}$. Equivalently, a graph of v^2 against T is a straight line of slope $1/\mu$.

3.5 Worked Examples

WORKED EXAMPLE 3 Speed of a pulse on a guitar string

A guitar string has length $L = 0.65 \text{ m}$ and mass $m = 3.9 \times 10^{-3} \text{ kg}$. It is stretched to a tension $T = 96 \text{ N}$. Calculate the speed of a transverse wave on this string.

SOLUTION

Step 1: linear density.

$$\mu = \frac{m}{L} = \frac{3.9 \times 10^{-3}}{0.65} = 6.0 \times 10^{-3} \text{ kg m}^{-1}.$$

Step 2: wave speed.

$$v = \sqrt{\frac{T}{\mu}} = \sqrt{\frac{96}{6.0 \times 10^{-3}}} = \sqrt{1.6 \times 10^4} \approx 1.3 \times 10^2 \text{ m s}^{-1}.$$

The pulse crosses the whole string in about $L/v = 0.65/126 \approx 5.2 \text{ ms}$, which is why the eye cannot follow it.

WORKED EXAMPLE 4 Finding the tension of a piano string

A steel piano string has linear density $\mu = 5.0 \times 10^{-3} \text{ kg m}^{-1}$. A transverse wave is measured to travel along it at $v = 2.0 \times 10^2 \text{ m s}^{-1}$. Find the tension in the string.

SOLUTION

Square the wave-speed formula and solve for T :

$$v = \sqrt{\frac{T}{\mu}} \Rightarrow v^2 = \frac{T}{\mu} \Rightarrow T = \mu v^2.$$

Numerically:

$$T = 5.0 \times 10^{-3} \times (2.0 \times 10^2)^2 = 5.0 \times 10^{-3} \times 4.0 \times 10^4 = 2.0 \times 10^2 \text{ N}.$$

The string is pulled with a force of 200 N, roughly the weight of a 20 kg mass. A full piano frame must withstand the sum of such tensions from more than two hundred strings, which is why it is made of cast iron.

WORKED EXAMPLE 5 Finding the linear density of a wire

A wire under a tension of 50 N carries transverse waves at 25 m s^{-1} . Calculate its linear density, and then the mass of a 2.0 m length of this wire.

SOLUTION

From $v = \sqrt{T/\mu}$ we obtain $\mu = T/v^2$:

$$\mu = \frac{50}{25^2} = \frac{50}{625} = 8.0 \times 10^{-2} \text{ kg m}^{-1}.$$

Mass of a 2.0 m length:

$$m = \mu L = 8.0 \times 10^{-2} \times 2.0 = 0.16 \text{ kg}.$$

WORKED EXAMPLE 6 Frequency of a vibrating string

The guitar string of the first worked example ($L = 0.65 \text{ m}$, $\mu = 6.0 \times 10^{-3} \text{ kg m}^{-1}$, $T = 96 \text{ N}$) vibrates in its fundamental mode, for which $\lambda = 2L$. Calculate its fundamental frequency.

SOLUTION

We already found $v = 1.3 \times 10^2 \text{ m s}^{-1}$ (more precisely 126.5 m s^{-1}). The wavelength is

$$\lambda = 2L = 2 \times 0.65 = 1.30 \text{ m}.$$

Hence

$$f = \frac{v}{\lambda} = \frac{126.5}{1.30} \approx 97 \text{ Hz}.$$

This is close to the note G_2 (98 Hz), the lowest string of a standard guitar: the physics matches the music.

WORKED EXAMPLE 7 Proportional reasoning: retuning a string

A string sounds a fundamental frequency of 110 Hz under a tension of 80 N. The musician wants the same string to sound 165 Hz without changing its length. What tension is required?

SOLUTION

At fixed L and μ , the fundamental frequency obeys $f_1 \propto \sqrt{T}$. Therefore

$$\frac{T'}{T} = \left(\frac{f'_1}{f_1} \right)^2 = \left(\frac{165}{110} \right)^2 = (1.5)^2 = 2.25.$$

Hence

$$T' = 2.25 \times 80 = 1.8 \times 10^2 \text{ N}.$$

Raising the pitch by a factor 1.5 requires more than doubling the tension, because the frequency depends only on the square root of T . This is why tuning pegs must be turned with care.

3.6 Common Mistakes and Key Points

WARNING Using the mass m instead of the linear density μ

The most frequent error at the GCE is to write $v = \sqrt{T/m}$, inserting the total mass of the string. This is wrong, and dimensional analysis exposes it immediately:

$$\left[\frac{T}{m} \right] = \frac{\text{MLT}^{-2}}{\text{M}} = \text{LT}^{-2} \neq \text{L}^2 \text{T}^{-2}.$$

The formula needs the mass per unit length, $\mu = m/L$. Other traps to avoid:

- forgetting to convert μ given in g m^{-1} into kg m^{-1} (divide by 1000);
- forgetting the square root, or squaring only one side when solving for T (remember $T = \mu v^2$);
- believing that increasing the frequency increases the speed: for a fixed string under fixed tension, v is unchanged; only λ decreases;
- mixing up the length L of the string with the wavelength λ : in the fundamental mode $\lambda = 2L$, not L ;
- in proportional-reasoning questions, forgetting that v and f_1 vary as $\sqrt{T}$, so a factor of n in frequency requires a factor of n^2 in tension.

EXERCISE 3 Checking a laboratory measurement

In a school experiment, a rubber cord of length 1.5 m and mass 0.030 kg is stretched by a force of 20 N. (a) Calculate the speed of transverse waves on the cord. (b) The cord is now stretched to 80 N without its linear density changing appreciably. By what factor is the speed multiplied? (c) State the fundamental frequency of the cord in case (b).

SOLUTION Exercise 1

(a) $\mu = m/L = 0.030/1.5 = 2.0 \times 10^{-2} \text{ kg m}^{-1}$, so $v = \sqrt{20/(2.0 \times 10^{-2})} = \sqrt{1000} \approx 32 \text{ m s}^{-1}$.
 (b) Since $v \propto \sqrt{T}$ at fixed μ , quadrupling T from 20 N to 80 N doubles the speed: $v' = 2v \approx 63 \text{ m s}^{-1}$.
 (c) Fundamental mode: $\lambda = 2L = 3.0 \text{ m}$, so $f = v'/\lambda = 63.2/3.0 \approx 21 \text{ Hz}$.

EXERCISE 4 Two strings on the same instrument

Two strings of the same length 0.60 m are fixed on an instrument. String A has $\mu_A = 4.0 \times 10^{-3} \text{ kg m}^{-1}$ and is under tension $T_A = 90 \text{ N}$. String B must sound a fundamental note one octave below string A (i.e. at half the frequency) under the same tension. (a) Calculate the

fundamental frequency of string A. (b) Find the linear density μ_B required for string B.

SOLUTION Exercise 2

(a) $v_A = \sqrt{90/(4.0 \times 10^{-3})} = \sqrt{2.25 \times 10^4} = 1.5 \times 10^2 \text{ m s}^{-1}$; with $\lambda = 2L = 1.20 \text{ m}$, $f_A = 150/1.20 = 125 \text{ Hz}$. (b) At fixed L and T , $f_1 \propto 1/\sqrt{\mu}$. Halving the frequency therefore requires multiplying μ by $2^2 = 4$: $\mu_B = 4 \times 4.0 \times 10^{-3} = 1.6 \times 10^{-2} \text{ kg m}^{-1}$. (Check: $v_B = \sqrt{90/(1.6 \times 10^{-2})} = 75 \text{ m s}^{-1}$, so $f_B = 75/1.20 = 62.5 \text{ Hz} = f_A/2$.)

KEY POINTS Key points

- The linear density of a string is $\mu = m/L$, in kg m^{-1} .
- The speed of a transverse wave on a taut string is $v = \sqrt{T/\mu}$, with T in newtons and v in m s^{-1} .
- Dimensional analysis gives the form of the law: $[T/\mu] = \text{L}^2 \text{T}^{-2}$, whose square root is a speed.
- The speed depends only on the medium (T and μ), never on the frequency or the amplitude.
- Combined with $v = f\lambda$, the formula explains how stringed instruments are tuned: $f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}$.
- At fixed μ , $v \propto \sqrt{T}$; at fixed L and μ , $f_1 \propto \sqrt{T}$; at fixed L and T , $f_1 \propto 1/\sqrt{\mu}$.
- Always check dimensions and convert all quantities to SI units before calculating.

DID YOU KNOW? Why are bass piano strings wound with copper?

To produce a low note at a reasonable tension and length, a string needs a large linear density μ , since $f_1 = \frac{1}{2L} \sqrt{T/\mu}$. A plain steel wire thick enough would be too stiff to vibrate musically. Piano makers therefore wrap a thin steel core with copper wire: this raises μ (and hence lowers the pitch) while keeping the string flexible. The same trick is used for the bass strings of guitars, including those played by Cameroonian makossa and bikutsi guitarists.

4 EXPERIMENTAL STUDY AND APPLICATIONS: THE SONOMETER AND VIBRATING STRINGS


In the previous section we established, both by dimensional analysis and by a proper derivation, that the speed of a transverse wave on a taut string is $v = \sqrt{T/\mu}$, where T is the tension and μ the mass per unit length. A formula in physics is only trustworthy when experiment confirms it. In this section we meet the classic instrument designed for exactly that purpose — the **sonometer** — and we use it to verify the law, to study the **stationary waves** that a stretched string can sustain, and to understand how musicians in Yaoundé or anywhere else tune a guitar, a piano or an mvet.

4.1 The Sonometer: Description and Use

DEFINITION The sonometer

A **sonometer** is a hollow wooden sounding box on which a thin wire is stretched between two **bridges**. One end of the wire is fixed; the other passes over a pulley and carries a **hanger** on which slotted masses are placed, so that the tension T in the wire equals the total weight supported, $T = Mg$. A **movable bridge** sliding under the wire allows the vibrating length L to be adjusted and measured on a graduated scale fixed to the box.

The hollow box is not a luxury: it acts as a resonator, amplifying the faint sound of the vibrating wire so that the experimenter can hear it clearly. The wire is set into vibration either by plucking it at its centre or by pressing against it a small rider (a tiny paper or wire loop) which is thrown off when the vibration amplitude becomes large — a convenient way of detecting resonance.



The sonometer: a wire stretched over two bridges on a hollow box, tensioned by hanging masses; the movable bridge sets the vibrating length L .

4.2 Stationary Waves on a String Fixed at Both Ends

When a stretched string is plucked, waves travel along it in both directions, reflect at the fixed ends, and superpose. Because both ends are fixed, they must be **nodes** (points of zero displacement). Only certain wavelengths can “fit” between the two ends: these are the **modes of vibration** of the string.

PROPERTY Stationary-wave condition for a string fixed at both ends

A string of length L fixed at both ends can sustain a stationary wave only if an integer number of half-wavelengths fits into its length:

$$L = n \frac{\lambda_n}{2}, \quad n = 1, 2, 3, \dots$$


so the allowed wavelengths are $\lambda_n = \frac{2L}{n}$ and the allowed frequencies are

$$f_n = \frac{v}{\lambda_n} = \frac{nv}{2L} = nf_1.$$

The mode $n = 1$ is the **fundamental** (first harmonic); the modes $n = 2, 3, \dots$ are the higher **harmonics** (overtones). The derivation (substituting $\lambda_n = 2L/n$ into $f_n = v/\lambda_n$) is short and examinable.

DEFINITION Fundamental frequency and harmonics

The **fundamental frequency** f_1 of a stretched string is the lowest frequency at which it can vibrate; the string then vibrates in a single loop with one antinode at the centre. The **harmonics** are the frequencies $f_n = nf_1$; the n -th harmonic has n loops, n antinodes and $n + 1$ nodes (including the two fixed ends).



The first three stationary-wave modes of a string fixed at both ends. N marks an interior node; the dashed curve shows the string half a period later.

Combining the stationary-wave condition with the wave-speed formula $v = \sqrt{T/\mu}$ gives the central result of this section.

PROPERTY Fundamental frequency of a stretched string

For a string of length L fixed at both ends, under tension T , of mass per unit length μ , the fundamental frequency is

$$f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}.$$

This shows directly how a player controls the pitch: f_1 increases when L decreases, when T increases, or when μ decreases. (The derivation — substituting $\lambda_1 = 2L$ into $f_1 = v/\lambda_1$ with $v = \sqrt{T/\mu}$ — is short and examinable.)

WARNING The fundamental wavelength is $\lambda = 2L$, not L

The most frequent error in GCE scripts is to write $\lambda_1 = L$ for the fundamental mode. Remember: the fundamental has one loop, and one loop is half a wavelength (the distance between two consecutive nodes is $\lambda/2$). Hence $\lambda_1 = 2L$ and $f_1 = v/(2L)$. Writing $\lambda_1 = L$ dou-

bles your frequency and destroys the rest of the calculation.

4.3 Experiment 1: Verifying $v \propto \sqrt{T}$ at Constant μ

METHOD Protocol: verifying $v = \sqrt{T/\mu}$ with a sonometer

1. Set up the sonometer with a single wire of measured mass per unit length μ (obtained by weighing a known length of the same wire: $\mu = m/\ell$).
2. Place a mass M on the hanger so that $T = Mg$. Keep the same wire throughout, so μ is constant.
3. Fix the vibrating length L with the movable bridge. Pluck the wire gently at its centre and compare its note with a reference (tuning fork or frequency generator); adjust L until the wire resonates at the chosen reference frequency f (a paper rider at the centre is thrown off at resonance).
4. Record T and the resonant length L . Since the wire vibrates in its fundamental mode, $v = f\lambda_1 = 2fL$.
5. Repeat for at least five different masses M , keeping f fixed.
6. Plot L against $\sqrt{T}$ (equivalently v against $\sqrt{T}$). A straight line through the origin confirms $v \propto \sqrt{T}$. The gradient of the v versus $\sqrt{T}$ graph equals $1/\sqrt{\mu}$, from which μ can be deduced and compared with the directly measured value.

EXAMPLE Numerical illustration

With $f = 256$ Hz fixed, a student finds resonance at $L = 0.500$ m for $M = 4.0$ kg. Then $T = Mg = 4.0 \times 9.81 = 39.2$ N and $v = 2fL = 2 \times 256 \times 0.500 = 256$ m s⁻¹. Doubling the mass to $M = 8.0$ kg should multiply v by $\sqrt{2}$, so the predicted resonant length is $L' = 0.500\sqrt{2} = 0.707$ m — exactly what the experiment shows within a few per cent.

4.4 Experiment 2: Verifying $v \propto 1/\sqrt{\mu}$ at Constant T

Now keep the hanging mass fixed (constant T) and use, in turn, several wires of the same material but different diameters, or of different materials (steel, brass, copper). For each wire, measure the resonant length L at the same reference frequency f , so $v = 2fL$.

Since $\mu = \rho\pi d^2/4$ for a wire of density ρ and diameter d , the theory predicts

$$v = \sqrt{\frac{T}{\mu}} \quad \Rightarrow \quad v \propto \frac{1}{\sqrt{\mu}} \propto \frac{1}{d} \text{ (same material).}$$

Plotting v against $1/\sqrt{\mu}$ (or L against $1/d$ for wires of one material) gives a straight line through the origin, confirming the law. A thicker wire vibrates more slowly — this is why the bass strings of a guitar are thick and wound.

PROPERTY Effect of tension on speed and frequency

Because $v = \sqrt{T/\mu}$ and $f_1 = v/(2L)$, both the wave speed and the fundamental frequency vary as $\sqrt{T}$. Doubling the tension multiplies v and f_1 by $\sqrt{2} \approx 1.41$, not by 2. To double the frequency of a string (raise it by one octave) at fixed L and μ , the tension must be multiplied by four.

4.5 Applications: Tuning String Instruments

Every string instrument is an applied sonometer. The formula $f_1 = \frac{1}{2L}\sqrt{\frac{T}{\mu}}$ explains the three gestures of any musician:

- **Tightening a peg** increases T , so f_1 rises: the note becomes sharper. Loosening lowers the pitch. A guitarist tunes each string this way.
- **Pressing a finger on the fingerboard** shortens the vibrating length L , raising the frequency: this is how different notes are produced on one string of a guitar or of the mvet, the traditional harp-zither of the Beti people.
- **Choosing the string**: bass notes require low f_1 , hence large μ — thick or wound strings. Treble strings are thin. In a piano, the bass strings are long, thick and copper-wound, while the treble strings are short and thin.

DID YOU KNOW? The mvet and the physics of strings

The mvet, emblematic instrument of the Fang-Beti epic tradition of the South and Centre regions of Cameroon, carries several strings stretched over a resonating body, exactly like a multi-wire sonometer. The player shortens the vibrating length with the fingers and selects strings of different thicknesses to cover a wide range of pitches — a living illustration of $f_1 = \frac{1}{2L}\sqrt{\frac{T}{\mu}}$, centuries before the formula was written down.

4.6 Data Treatment and GCE-Style Problem Solving

METHOD Solving problems combining $v = f\lambda$, $v = \sqrt{T/\mu}$ and $L = n\lambda/2$

1. Identify the mode: fundamental ($\lambda = 2L$) or n -th harmonic ($\lambda = 2L/n$). Draw the loop pattern if in doubt.

2. Write $v = f\lambda$ using the wavelength of the correct mode.
3. Write $v = \sqrt{T/\mu}$ with $T = Mg$ if masses hang from the wire.
4. Equate or combine the two expressions; solve for the unknown, keeping units in SI (lengths in metres, μ in kg m^{-1} , T in newtons).
5. For graph questions: rearrange the formula so that the plotted quantities give a straight line, then read the gradient and interpret it physically (e.g. gradient of f_1 versus $1/L$ equals $\frac{1}{2}\sqrt{T/\mu}$).

WORKED EXAMPLE 8 Fundamental frequency of a sonometer wire

A sonometer wire of length $L = 0.80$ m between the bridges has mass per unit length $\mu = 1.2 \times 10^{-3} \text{ kg m}^{-1}$. It is tensioned by a mass $M = 5.0$ kg (take $g = 9.81 \text{ m s}^{-2}$).

1. Calculate the speed of transverse waves on the wire.
2. Calculate the fundamental frequency and the frequency of the second harmonic.
3. The tension is doubled. State the new fundamental frequency.

SOLUTION

Solution.

1. Tension: $T = Mg = 5.0 \times 9.81 = 49.05 \text{ N}$.

$$v = \sqrt{\frac{T}{\mu}} = \sqrt{\frac{49.05}{1.2 \times 10^{-3}}} = \sqrt{4.09 \times 10^4} \approx 202 \text{ m s}^{-1}.$$

2. Fundamental mode: $\lambda_1 = 2L = 1.60$ m.

$$f_1 = \frac{v}{\lambda_1} = \frac{202}{1.60} \approx 126 \text{ Hz}.$$

Second harmonic: $f_2 = 2f_1 \approx 253 \text{ Hz}$ (the string vibrates in two loops, $\lambda_2 = L = 0.80$ m).

3. Doubling T multiplies f_1 by $\sqrt{2}$: $f_1' = 126 \times 1.414 \approx 179 \text{ Hz}$ — not 252 Hz.

WORKED EXAMPLE 9 Deducing μ from a graph

In a sonometer experiment at fixed frequency $f = 200$ Hz, the resonant length L is measured for various tensions T . The graph of L (vertical axis) against $\sqrt{T}$ is a straight line through the origin of gradient $k = 0.045 \text{ m N}^{-1/2}$. Deduce the mass per unit length μ of the wire.

SOLUTION

Solution. At resonance in the fundamental mode, $v = 2fL$ and $v = \sqrt{T/\mu}$, so

$$2fL = \sqrt{\frac{T}{\mu}} \implies L = \frac{1}{2f\sqrt{\mu}} \sqrt{T}.$$

The graph of L versus $\sqrt{T}$ has gradient $k = \frac{1}{2f\sqrt{\mu}}$. Hence

$$\sqrt{\mu} = \frac{1}{2fk} = \frac{1}{2 \times 200 \times 0.045} = \frac{1}{18} = 0.0556 \text{ kg}^{1/2} \text{ m}^{-1/2},$$

$$\mu = (0.0556)^2 \approx 3.1 \text{ e} - 3 \text{ kg m}^{-1}.$$

EXERCISE 5 Vibrating strings

A steel guitar string has length 0.65 m and mass per unit length $4.0 \text{ e} - 3 \text{ kg m}^{-1}$.

1. What tension is required for a fundamental frequency of 330 Hz?
2. With this tension, what are the wavelengths and frequencies of the second and third harmonics?
3. The player presses the string so that only 0.50 m vibrates. What is the new fundamental frequency?

SOLUTION Exercise 1

1. $f_1 = \frac{1}{2L} \sqrt{T/\mu} \implies T = 4L^2 f_1^2 \mu = 4(0.65)^2 (330)^2 (4.0 \times 10^{-3}) \approx 736 \text{ N}.$
2. $f_2 = 2f_1 = 660 \text{ Hz}, \lambda_2 = L = 0.65 \text{ m}; f_3 = 3f_1 = 990 \text{ Hz}, \lambda_3 = 2L/3 = 0.43 \text{ m}.$
3. $f'_1 = f_1 \times \frac{L}{L'} = 330 \times \frac{0.65}{0.50} = 429 \text{ Hz}$ (frequency is inversely proportional to length at fixed T and μ).

KEY POINTS Key points

- The **sonometer** verifies $v = \sqrt{T/\mu}$: vary T at fixed μ (straight line of v versus $\sqrt{T}$), then vary μ at fixed T (straight line of v versus $1/\sqrt{\mu}$).

- A string fixed at both ends vibrates only in modes satisfying $L = n\lambda/2$; the fundamental has $\lambda_1 = 2L$.
- Fundamental frequency: $f_1 = \frac{1}{2L}\sqrt{\frac{T}{\mu}}$; harmonics: $f_n = nf_1$.
- Doubling T multiplies v and f_1 by $\sqrt{2}$; doubling the frequency requires four times the tension.
- Thick strings $\Rightarrow$ large $\mu \Rightarrow$ low notes; tightening a peg $\Rightarrow$ larger $T \Rightarrow$ sharper note; shortening $L \Rightarrow$ higher note.

5 INTEGRATION ACTIVITY

5.1 Aims of the activity

By the end of this integration activity, you should be able to:

- Apply the relation $v = \sqrt{T/\mu}$ to determine the speed of a transverse wave on a taut string from its tension T and linear density μ , and conversely to find the tension needed for a given speed.
- Combine $v = f\lambda$ with the stationary-wave condition for a string fixed at both ends, $\lambda_1 = 2L$ for the fundamental mode, to design a string that produces a required musical note.
- Predict quantitatively how the fundamental frequency changes when the tension or the linear density of the string is modified, using the proportionality $f_1 \propto \sqrt{T}/\sqrt{\mu}$.
- Use the rope-and-slit model to explain the **polarization** of a transverse wave, and interpret the darkening observed when two polaroid sheets are rotated relative to each other.
- Present a reasoned scientific argument, with correct SI units and sensible significant figures, to the class.

This activity brings together the two lessons of the chapter: the **polarization** of transverse waves and the **speed of transverse waves** on taut strings and wires. It shows that both topics rest on one central idea: the transverse nature of the waves involved. On a string, the transverse displacement propagates at a speed fixed by the mechanical properties of the medium (T and μ); in polarization, it is precisely the transverse direction of vibration that is selected by a slit or a polaroid sheet.

5.2 Situation

Tuning the Mvet: Designing a String for a Given Note.

During the cultural week of your school in Yaoundé, the music club decides to build a simplified version of the mvet, the traditional harp-zither of the forest regions of Cameroon. In the traditional instrument, the player stretches fibre strings along a wooden stick fitted with resonating calabashes, and tunes each string by adjusting its tension until the desired note is obtained.

The club asks your physics group to do the scientific design work. The specifications are the following:

- The vibrating part of the string is fixed at both ends and has length $L = 65 \text{ cm} = 0.65 \text{ m}$.
- The string is made of plant fibre of linear density (mass per unit length) $\mu = 1.2 \text{ g m}^{-1} = 1.2 \times 10^{-3} \text{ kg m}^{-1}$.
- When plucked at its centre, the string must emit as its fundamental note the standard pitch $f_1 = 220 \text{ Hz}$ (the note A used to tune orchestras).

The club also wants to understand two practical questions before buying materials:

- What happens to the note if, after some days of playing, the musician tightens the string so


that its tension increases by 20 %?

- What happens if, instead of the original fibre, a fibre string twice as thick is used (same material, so twice the linear density), stretched under the same tension?

Finally, during the open day, your group must run a small optics stand. You are given two square polaroid sheets taken from old sunglasses. Visitors notice that when the two sheets are held one behind the other towards the sunlight and one sheet is slowly rotated, the transmitted light becomes progressively dimmer, until the view is almost completely dark when the sheets are “crossed” at 90° . You must explain this observation using the rope-and-slit model studied in class, and state clearly what it proves about the nature of light.

WARNING Units before anything else

Convert all data to SI units before any calculation: L in metres, μ in kg m^{-1} , T in newtons, f in hertz. Most errors in this type of problem come from forgetting to convert g m^{-1} into kg m^{-1} , or cm into m. A second frequent error is to confuse the wavelength $\lambda_1 = 2L$ with the length L itself.



Rope-and-slit model: the first vertical slit selects a vertical plane of vibration (plane polarization); the second slit, rotated by 90° , blocks the vibration completely.

5.3 Tasks

Work in groups of three or four. Answer the questions in order; each answer will be used in the next question.

1. **Stationary-wave condition.** The string is fixed at both ends. Sketch the fundamental mode of vibration and justify that the wavelength of the fundamental is $\lambda_1 = 2L$. Calculate λ_1 numerically.
2. **Required wave speed.** Using $v = f\lambda$, calculate the speed that transverse waves must have on the string for the fundamental note to be $f_1 = 220 \text{ Hz}$.
3. **Required tension.** Using $v = \sqrt{T/\mu}$, show that the tension to be applied is $T = \mu v^2$, and calculate its value in newtons. Compare this tension with the weight of a stone of mass m : what mass hung from the string would produce the same tension (take $g = 9.81 \text{ m s}^{-2}$)?
4. **Effect of a 20 % increase of tension.** The tension becomes $T' = 1.20 T$, with L and μ un-

changed. Show that the new fundamental frequency is $f_1' = f_1\sqrt{1.20}$ and calculate it. Does the note sound higher or lower? Is the change audible (a change of more than about 3 % is easily heard)?

5. **Effect of doubling the thickness.** A string of the same material but twice as thick has $\mu'' = 2\mu$ and is stretched under the same tension T . Show that $f_1'' = f_1/\sqrt{2}$ and calculate it. Why do instrument makers use thicker strings for the low notes?
6. **Polarization demonstration.** (a) Describe the rope-and-slit experiment: a rope passes through two parallel slits; what happens to the rope's transverse vibration when the second slit is rotated by 90° ? (b) By analogy, explain why the light transmitted by two polaroid sheets becomes very weak when their transmission axes are crossed at 90° . (c) State precisely what this experiment proves about light, and why the same experiment performed with sound waves in air would show no such effect.
7. **Synthesis.** Prepare a five-minute presentation: your calculations for questions 1 to 5 (with units and significant figures), and a live demonstration for question 6, ending with one sentence that links the two parts of the activity to the transverse nature of waves.

5.4 Model answer

1. Stationary-wave condition.

The string is fixed at both ends, so each end must be a **node** of vibration (a point that never moves). The simplest stationary pattern fitting between two nodes is a single loop, with one **antinode** at the centre. The length of the string then equals half a wavelength, since one full wavelength contains two loops:

$$L = \frac{\lambda_1}{2} \quad \Rightarrow \quad \lambda_1 = 2L = 2 \times 0.65 = 1.30 \text{ m.}$$

2. Required wave speed.

From the general wave relation $v = f\lambda$ applied to the fundamental mode:

$$v = f_1\lambda_1 = 220 \times 1.30 = 286 \text{ m s}^{-1}.$$

Transverse waves must therefore travel along the fibre at about 286 m s^{-1} .

3. Required tension.

Starting from $v = \sqrt{T/\mu}$ and squaring both sides:

$$v^2 = \frac{T}{\mu} \quad \Rightarrow \quad T = \mu v^2 = 1.2 \times 10^{-3} \times (286)^2.$$

$$T = 1.2 \times 10^{-3} \times 8.18 \times 10^4 \approx 98 \text{ N.}$$

A mass m hung vertically from the string would produce a tension $T = mg$, so

$$m = \frac{T}{g} = \frac{98}{9.81} \approx 10 \text{ kg.}$$

The string must therefore be tightened with a force equivalent to the weight of a 10 kg bag — which is exactly what the tuning pegs of the instrument are designed to do.

4. Effect of a 20 % increase of tension.

Since $f_1 = \frac{v}{2L} = \frac{1}{2L} \sqrt{\frac{T}{\mu}}$, with L and μ fixed the frequency is proportional to $\sqrt{T}$. Hence

$$f_1' = f_1 \sqrt{\frac{T'}{T}} = 220 \times \sqrt{1.20} = 220 \times 1.095 \approx 241 \text{ Hz.}$$

The note rises by about 9.5 %: it sounds clearly higher (roughly a semitone sharper). This is why a mvet must be retuned whenever the strings are tightened or when humidity changes the tension of the fibres.

5. Effect of doubling the thickness.

With T and L unchanged, $f_1 \propto 1/\sqrt{\mu}$:

$$f_1'' = f_1 \sqrt{\frac{\mu}{\mu''}} = \frac{220}{\sqrt{2}} \approx 156 \text{ Hz.}$$

The note becomes lower. Thicker strings have a larger linear density, so waves travel more slowly on them ($v = \sqrt{T/\mu}$ decreases) and the fundamental frequency drops: this is why the bass strings of guitars, pianos and the mvet are always the thickest ones.

6. Polarization demonstration.

(a) Rope and slits. A rope is passed through two vertical slits and shaken vertically: the transverse vibration passes through both slits freely. If the second slit is rotated until it is horizontal (at 90° to the first), the vertical vibration of the rope cannot pass through it: beyond the second slit the rope does not move. The first slit has plane polarized the wave; the second slit acts as an analyser.

(b) Polaroid sheets. The first polaroid sheet plays the role of the first slit: it transmits only the component of the light's vibration parallel to its transmission axis, producing plane polarized light. The second sheet (the analyser) transmits only the component parallel to its own axis. When the two axes are crossed at 90° , no component of the polarized light can pass: the transmitted intensity falls practically to zero and the view becomes dark.

(c) Conclusion. Only a transverse wave can be polarized, because only then does the vibration have a direction in space, perpendicular to the direction of propagation, that can be selected by a slit or a polaroid. The darkening of crossed polaroids therefore proves that **light is a transverse wave**. Sound in air is a longitudinal wave: its vibration is along the direction of propagation, so no rotation of any "analyser" can extinguish it, and polarization of sound in air is impossible.

7. Synthesis sentence.

"Whether it is the fibre of a mvet vibrating at 220 Hz or a beam of sunlight crossing two polaroid sheets, the physics is the same: the waves are transverse — their speed on a string is fixed by $v = \sqrt{T/\mu}$, and their direction of vibration can be selected by polarization."

KEY POINTS What this activity consolidates

- Fundamental mode of a string fixed at both ends: $\lambda_1 = 2L$, so $f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}$.

- f_1 increases as $\sqrt{T}$ and decreases as $1/\sqrt{\mu}$: tighten to sharpen the note, thicken to lower it.
- Polarization selects the direction of vibration; it is the signature of transverse waves, for mechanical waves on ropes as for light.

6 METHODS AND WORKED EXAMPLES

6.1 Methods and Worked Examples

METHOD Identifying a Wave as Transverse

- **Step 1: Identify the wave motion:** transverse waves have oscillations perpendicular to the direction of propagation.
- **Step 2: Determine the medium and the type of wave:** transverse waves can be polarized; longitudinal waves cannot.
- **Step 3: Recall the key idea:** a transverse wave is polarized when the vibrations are confined to a plane.
- **Step 4: Use the concept of a polarizer:** only the component of the wave oscillating in the plane of the polarizer is transmitted.

WORKED EXAMPLE 10 Polarization of a Wave

[illegible]

SOLUTION

Detailed solution to be added here.

7 EXERCISES

7.1 I check my knowledge

EXERCISE 6 Multiple choice questions

For each question, choose the single correct answer and justify your choice in one sentence.

1. Polarization is a phenomenon that can occur:
 - (a) for all waves, transverse and longitudinal;
 - (b) only for transverse waves;
 - (c) only for longitudinal waves;
 - (d) only for light waves.
2. A plane polarized wave is one in which:
 - (a) the amplitude decreases with distance;
 - (b) the vibrations of the medium are confined to a single plane containing the direction of propagation;
 - (c) the wave travels in a plane;
 - (d) the frequency is constant.
3. The speed of a transverse wave on a taut string of linear density μ under tension T is:
 - (a) $v = \sqrt{T/\mu}$;
 - (b) $v = \sqrt{\mu/T}$;
 - (c) $v = T/\mu$;
 - (d) $v = \sqrt{T\mu}$.
4. Unpolarized light of intensity I_0 passes through an ideal polarizer. The transmitted intensity is:
 - (a) I_0 ;
 - (b) $I_0/2$;
 - (c) $I_0/4$;
 - (d) 0.

EXERCISE 7 True or false

State whether each statement is true or false, justifying your answer briefly.

1. Sound waves in air can be polarized by passing them through a narrow slit.
2. Rotating a second polaroid (analyser) through 90° from the position of maximum transmission reduces the transmitted intensity to zero.
3. Doubling the tension of a stretched wire doubles the speed of transverse waves on it.
4. For a string fixed at both ends, the fundamental wavelength equals twice the length of the string.

EXERCISE 8 Definitions

Define each of the following terms clearly, in one or two sentences each:

1. plane polarized wave;
2. linear density (mass per unit length) of a string;
3. polarizer and analyser;
4. fundamental mode of vibration of a stretched string.

EXERCISE 9 Direct calculations

1. A wire of length 2.0 m has a mass of 5.0 g. Calculate its linear density μ .
2. A transverse wave travels at 80 m s^{-1} along a string under a tension of 64 N. Calculate the linear density of the string.
3. Unpolarized light of intensity I_0 falls on a polaroid sheet. A second polaroid has its axis at 30° to the first. Calculate the final transmitted intensity as a fraction of I_0 .

7.2 I practise**EXERCISE 10 Malus's law**

Unpolarized light of intensity I_0 passes through two ideal polaroids whose transmission axes make an angle of 60° with each other.

1. State Malus's law.

2. Calculate the intensity transmitted by the first polaroid.
3. Calculate the intensity transmitted by the second polaroid as a fraction of I_0 .
4. What angle between the axes would reduce the final intensity to $I_0/8$?

EXERCISE 11 Wave on a steel wire

A steel wire of length 1.5 m and mass 12 g is stretched under a tension of 200 N.

1. Calculate the linear density μ of the wire.
2. Calculate the speed v of transverse waves on the wire.
3. A transverse wave of frequency 100 Hz travels along the wire. Calculate its wavelength.
4. The tension is increased to 800 N. Calculate the new wave speed and comment on the effect of quadrupling the tension.

EXERCISE 12 Vibrating string fixed at both ends

A guitar string of length 0.65 m and linear density $1.2 \times 10^{-3} \text{ kg m}^{-1}$ is under a tension of 75 N.

1. Calculate the speed of transverse waves on the string.
2. Calculate the fundamental frequency of the string.
3. Calculate the frequencies of the second and third harmonics.

EXERCISE 13 Changing the string

A musician replaces a string by another string of double the linear density, keeping the same tension and the same vibrating length.

1. Show that the fundamental frequency is divided by $\sqrt{2}$.
2. Comment on the effect this has on the pitch of the note heard.
3. What change in tension (at constant length and linear density) would restore the original fundamental frequency?

7.3 I prepare for the GCE

EXERCISE 14 Polarization of a rope wave and of sound

1. Define a plane polarized wave. (2 marks)
2. Describe, with the aid of a labelled diagram, an experiment using a rope and two slits to demonstrate the polarization of a transverse wave. State clearly what is observed when the second slit is rotated through 90° . (5 marks)
3. Explain why the result of this experiment proves that the wave on the rope is transverse. (2 marks)
4. Explain why a sound wave in air cannot be polarized by the same arrangement. (2 marks)
5. State two applications of polarized light in everyday life or technology. (2 marks)

EXERCISE 15 Sonometer experiment

In an experiment to study transverse waves on a stretched wire, a sonometer wire is kept under tension by hanging masses. For each value of the tension T , the wavelength λ of the wave produced at a fixed frequency is measured. The results are:

T (N)	25	50	75	100	125
λ (m)	0.40	0.57	0.69	0.80	0.89

The frequency of the source is $f = 256$ Hz.

1. Write down the relation connecting the wave speed v , the tension T and the linear density μ of the wire. (1 mark)
2. Show that $\lambda^2 = \frac{T}{\mu f^2}$. (2 marks)
3. Copy and complete the table by computing λ^2 for each measurement. (2 marks)
4. Plot a graph of λ^2 (vertical axis) against T (horizontal axis). (4 marks)
5. Determine the gradient of the graph. (2 marks)
6. Deduce the linear density μ of the wire. (2 marks)
7. State one precaution you would take to obtain accurate results. (1 mark)

EXERCISE 16 Guitar string in its fundamental mode

A guitar string fixed at both ends has length $L = 0.80 \text{ m}$ and linear density $\mu = 4.0 \times 10^{-3} \text{ kg m}^{-1}$. It is stretched under a tension $T = 128 \text{ N}$ and vibrates in its fundamental mode.

1. Draw a labelled diagram of the string vibrating in its fundamental mode, indicating nodes and antinodes. (2 marks)
2. Show that the fundamental frequency is given by $f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}$. (3 marks)
3. Calculate the fundamental frequency of the string. (2 marks)
4. Calculate the new tension required to raise the fundamental frequency by a factor of 1.5, the length and linear density being unchanged. (3 marks)
5. State two assumptions made in deriving the formula used in (b). (2 marks)
6. Explain, in terms of wave speed and wavelength, why increasing the tension raises the pitch of the note. (2 marks)

8 SOLUTIONS TO THE EXERCISES

8.1 I check my knowledge

SOLUTION Exercise 1 — Multiple choice questions

1. (b). Polarization requires the vibration to have a direction perpendicular to the propagation; longitudinal waves vibrate along the propagation direction and cannot be polarized.
2. (b). This is precisely the definition of plane (linear) polarization: the vibrations of the medium are confined to a single plane containing the direction of propagation.
3. (a). $v = \sqrt{T/\mu}$; dimensional check: $[T/\mu] = \text{N kg}^{-1} \text{m} = \text{kg m s}^{-2} \text{kg}^{-1} \text{m} = \text{m}^2 \text{s}^{-2}$, whose square root is a speed.
4. (b). An ideal polarizer transmits only the component of the vibration parallel to its axis; averaging over all random orientations of the unpolarized light gives $I_0/2$.

SOLUTION Exercise 2 — True or false

1. False. Sound in air is longitudinal; its vibrations are along the direction of propagation, so no slit orientation can select a vibration direction.
2. True. By Malus's law $I = I_{\max} \cos^2 \theta$; at $\theta = 90^\circ$, $\cos \theta = 0$ and $I = 0$ (crossed polaroids).
3. False. Since $v = \sqrt{T/\mu}$, doubling T multiplies v by $\sqrt{2} \approx 1.41$, not by 2.
4. True. In the fundamental mode the string carries one loop, so $L = \lambda_1/2$, i.e. $\lambda_1 = 2L$.

SOLUTION Exercise 3 — Definitions

1. A **plane polarized wave** is a transverse wave in which the vibrations of the medium are confined to one fixed plane containing the direction of propagation.
2. The **linear density** μ of a string is its mass per unit length: $\mu = m/L$, in kg m^{-1} .
3. A **polarizer** is a device that produces plane polarized light from unpolarized light; an **analyser** is a second identical device used to detect the polarization and measure the orientation of its plane (by Malus's law).

4. The **fundamental mode** is the simplest standing-wave pattern of a string fixed at both ends: a single loop with nodes at the ends and one antinode at the centre, of wave-length $\lambda_1 = 2L$ and frequency $f_1 = v/(2L)$.

SOLUTION Exercise 4 — Direct calculations

1. $\mu = \frac{m}{L} = \frac{5.0 \times 10^{-3}}{2.0} = 2.5 \times 10^{-3} \text{ kg m}^{-1}$.
2. From $v = \sqrt{T/\mu}$ we get $\mu = \frac{T}{v^2} = \frac{64}{80^2} = \frac{64}{6400} = 1.0 \times 10^{-2} \text{ kg m}^{-1}$.
3. After the first polaroid: $I_1 = I_0/2$. After the second (Malus's law):

$$I_2 = I_1 \cos^2 30^\circ = \frac{I_0}{2} \times \left(\frac{\sqrt{3}}{2}\right)^2 = \frac{I_0}{2} \times \frac{3}{4} = \frac{3I_0}{8} = 0.375 I_0.$$

8.2 I practise

SOLUTION Exercise 5 — Malus's law

1. Malus's law: when plane polarized light of intensity I_1 falls on an ideal analyser whose axis makes an angle θ with the plane of polarization, the transmitted intensity is $I = I_1 \cos^2 \theta$.
2. The first polaroid receives unpolarized light, so $I_1 = I_0/2$.
3. $I_2 = I_1 \cos^2 60^\circ = \frac{I_0}{2} \times (0.5)^2 = \frac{I_0}{8} = 0.125 I_0$.
4. We require $\frac{I_0}{2} \cos^2 \theta = \frac{I_0}{8}$, so $\cos^2 \theta = \frac{1}{4}$, $\cos \theta = \frac{1}{2}$, hence $\theta = 60^\circ$.

SOLUTION Exercise 6 — Wave on a steel wire

1. $\mu = \frac{m}{L} = \frac{12 \times 10^{-3}}{1.5} = 8.0 \times 10^{-3} \text{ kg m}^{-1}$.
2. $v = \sqrt{\frac{T}{\mu}} = \sqrt{\frac{200}{8.0 \times 10^{-3}}} = \sqrt{2.5 \times 10^4} \approx 1.6 \times 10^2 \text{ m s}^{-1} (158 \text{ m s}^{-1})$.

$$3. \lambda = \frac{v}{f} = \frac{158}{100} \approx 1.6 \text{ m.}$$

$$4. v' = \sqrt{\frac{800}{8.0 \times 10^{-3}}} = \sqrt{1.0 \times 10^5} \approx 3.2 \times 10^2 \text{ m s}^{-1} (316 \text{ m s}^{-1}). \text{ Quadrupling the tension only doubles the speed, because } v \propto \sqrt{T}.$$

SOLUTION Exercise 7 — Vibrating string fixed at both ends

$$1. v = \sqrt{\frac{T}{\mu}} = \sqrt{\frac{75}{1.2 \times 10^{-3}}} = \sqrt{6.25 \times 10^4} = 2.5 \times 10^2 \text{ m s}^{-1}.$$

$$2. f_1 = \frac{v}{2L} = \frac{250}{2 \times 0.65} = \frac{250}{1.30} \approx 1.9 \times 10^2 \text{ Hz (192 Hz).}$$

$$3. f_2 = 2f_1 \approx 3.8 \times 10^2 \text{ Hz (385 Hz)}; f_3 = 3f_1 \approx 5.8 \times 10^2 \text{ Hz (577 Hz).}$$

SOLUTION Exercise 8 — Changing the string

$$1. f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}. \text{ With } \mu' = 2\mu:$$

$$f_1' = \frac{1}{2L} \sqrt{\frac{T}{2\mu}} = \frac{1}{\sqrt{2}} \times \frac{1}{2L} \sqrt{\frac{T}{\mu}} = \frac{f_1}{\sqrt{2}}.$$

2. The frequency decreases, so the note heard is lower in pitch (a heavier string sounds deeper, as with the bass strings of a guitar or piano).

3. Since $f_1 \propto \sqrt{T}$ at constant L and μ , restoring f_1 while μ is doubled requires $\sqrt{T'/(2\mu)} = \sqrt{T/\mu}$, i.e. $T' = 2T$: the tension must be doubled.


8.3 I prepare for the GCE

SOLUTION Exercise 9 — Polarization of a rope wave and of sound

1. A plane polarized wave is a transverse wave in which the vibrations of the medium are confined to a single fixed plane containing the direction of propagation. (2 marks: transverse + single plane containing the propagation direction)

2. A long rope is fixed at one end and shaken at the other end so that it vibrates in all

transverse directions (unpolarized wave). The rope passes through a vertical slit S_1 in a board: only the vertical component of the vibration is transmitted beyond S_1 , so the wave between S_1 and a second slit S_2 is plane polarized in the vertical plane. When S_2 is also vertical, the wave passes through with almost unchanged amplitude. When S_2 is rotated through 90° (horizontal slit), the vertical vibration cannot pass: the rope beyond S_2 remains at rest — the wave is completely stopped.



(5 marks: labelled diagram 2; role of S_1 as polarizer 1; observation with S_2 parallel 1; observation with S_2 at 90° 1)

3. The wave is stopped when the slit is perpendicular to the vibration plane, which shows the vibration has a definite direction perpendicular to the propagation; only transverse waves possess such a transverse vibration direction that a slit can select or block. (2 marks)
4. Sound in air is longitudinal: the air layers vibrate along the direction of propagation. A slit of any orientation is equally traversed, so no orientation can block the wave; hence sound cannot be polarized. (2 marks)
5. Applications (any two): polarizing (Polaroid) sunglasses to reduce glare reflected by roads and water; polarizing filters in photography; liquid-crystal displays (LCD screens); stress analysis in transparent materials (photoelasticity). (2 marks)

Examiner's expectations: the diagram must show the rope, both slits and the direction of propagation; the key marking point in (c) is the explicit link "blocked wave $\Rightarrow$ vibration perpendicular to propagation".


SOLUTION Exercise 10 — Sonometer experiment

1. $v = \sqrt{\frac{T}{\mu}}$. (1 mark)
2. Since $v = f\lambda$, we have $f\lambda = \sqrt{T/\mu}$. Squaring: $f^2\lambda^2 = \frac{T}{\mu}$, hence $\lambda^2 = \frac{T}{\mu f^2}$. (2 marks)
3. Completed table:

T (N)	25	50	75	100	125
λ (m)	0.40	0.57	0.69	0.80	0.89
λ^2 (m ²)	0.160	0.325	0.476	0.640	0.792

(2 marks: all five values correct)

4. Graph: axes labelled with quantities and units, suitable uniform scales, points plotted correctly, best straight line drawn through the origin.



The points lie on a straight line through the origin, confirming $\lambda^2 \propto T$. (4 marks: axes + scales 1; points 2; line through origin 1)

5. Gradient, using the points (25; 0.160) and (125; 0.792) on the line:

$$k = \frac{0.792 - 0.160}{125 - 25} = \frac{0.632}{100} = 6.3 \times 10^{-3} \text{ m}^2 \text{ N}^{-1}.$$

(2 marks: method 1; value with unit 1)

6. Since $k = \frac{1}{\mu f^2}$, we get

$$\mu = \frac{1}{kf^2} = \frac{1}{6.3 \times 10^{-3} \times 256^2} = \frac{1}{6.3 \times 10^{-3} \times 6.55 \times 10^4} \approx 2.4 \times 10^{-3} \text{ kg m}^{-1}.$$


(2 marks: relation 1; value with unit 1)

7. Precaution (any one): ensure the pulley is nearly frictionless so the tension equals the weight of the hanging masses; measure the wavelength over several loops and divide; avoid parallax when reading the positions of the bridges; keep the frequency of the vibrator constant. (1 mark)

Examiner's expectations: the gradient must be taken from the drawn line (not from a single data pair) over at least half the line length; the final value of μ must carry the unit kg m^{-1} .

SOLUTION Exercise 11 — Guitar string in its fundamental mode

1. Diagram: a single loop between the two fixed ends; nodes N at both ends, one antinode A at the centre.



(2 marks: single loop 1; nodes and antinode labelled 1)

2. In the fundamental mode the string carries one loop, so $L = \frac{\lambda_1}{2}$, i.e. $\lambda_1 = 2L$. The wave speed on the string is $v = \sqrt{T/\mu}$, and $v = f_1\lambda_1$. Hence

$$f_1 = \frac{v}{\lambda_1} = \frac{1}{2L} \sqrt{\frac{T}{\mu}}.$$

(3 marks: $\lambda_1 = 2L$ 1; $v = \sqrt{T/\mu}$ 1; combination 1)

3. $f_1 = \frac{1}{2 \times 0.80} \sqrt{\frac{128}{4.0 \times 10^{-3}}} = \frac{1}{1.60} \sqrt{3.2 \times 10^4} = 0.625 \times 178.9 \approx 1.1 \times 10^2 \text{ Hz (112 Hz).}$ (2 marks)

4. Since $f_1 \propto \sqrt{T}$ at constant L and μ , raising f_1 by a factor 1.5 requires multiplying T by $1.5^2 = 2.25$:

$$T' = 2.25 \times 128 = 288 \text{ N.}$$

(3 marks: proportionality 1; squaring the factor 1; value 1)

5. Assumptions (any two): the string is perfectly flexible (no stiffness); its linear density is uniform; the tension is the same at every point and unchanged by the small vibrations; the amplitude of vibration is small; energy losses (damping) are neglected. (2 marks)
6. Increasing T increases the wave speed $v = \sqrt{T/\mu}$. The vibrating length fixes the fundamental wavelength ($\lambda_1 = 2L$), so $f_1 = v/\lambda_1$ increases with v . A higher frequency is perceived as a higher-pitched note. (2 marks)

Examiner's expectations: in (d) the most common error is to multiply T by 1.5 instead of 1.5^2 ; the square-root dependence must be stated explicitly to earn the method mark.

9

SUMMARY SHEET



Mind map of the chapter: polarization of transverse waves and the speed of transverse waves on taut strings.

KEY POINTS

Summary Sheet — Mechanical Waves (Continued)

Key definitions

- **Polarization**: property of a transverse wave in which the vibrations, which would oth-

erwise occur in all possible directions perpendicular to the direction of propagation, are restricted to a definite pattern of directions. A **plane polarized** wave vibrates in one fixed plane only (the plane of polarization), which contains the direction of propagation.

- Only transverse waves can be polarized; longitudinal waves (sound in air) cannot, because their vibrations are already along the single direction of propagation. The fact that light can be polarized is the experimental proof that light is a transverse wave.
- **Polarizer**: device producing plane polarized light from ordinary (unpolarized) light; **analyser**: an identical device used to detect the polarization. When polarizer and analyser are crossed (transmission axes at 90°), no light passes: darkness.
- **Linear density** (mass per unit length) of a string: $\mu = m/L$, SI unit kg m^{-1} .

Laws and formulas to know

- Speed of a transverse wave on a taut string:

$$v = \sqrt{\frac{T}{\mu}} \quad (T \text{ tension in N, } \mu \text{ in kg m}^{-1}, v \text{ in m s}^{-1})$$

v increases when the tension increases and decreases when the linear density increases; v does not depend on the frequency or the amplitude of the wave.

- Since $\mu = \rho S$ (ρ density of the material, S cross-sectional area of the wire): $v = \sqrt{T/(\rho S)}$. Hence, at equal tension, a thicker wire (larger S) carries slower waves.
- Fundamental frequency of a string fixed at both ends (sonometer wire), from $v = f\lambda$ with $\lambda_1 = 2L$:

$$f_1 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}, \quad f_n = n f_1 \quad (n = 1, 2, 3, \dots)$$

- Law of Malus (analyser whose axis makes an angle θ with that of the polarizer): $I = I_0 \cos^2 \theta$. Unpolarized light passing through a first polarizer loses half its intensity: $I = I_0/2$.

Methods

- Computing v on a string: convert the mass per metre to μ in kg m^{-1} ; if a mass M hangs over a pulley, the tension is $T = Mg$; then apply $v = \sqrt{T/\mu}$.
- Sonometer problems: identify L , T and μ ; at resonance with a tuning fork of frequency f , write $f = \frac{1}{2L} \sqrt{T/\mu}$ and solve for the unknown quantity.
- Polarization questions: state that since light can be polarized, light must be a transverse wave; support the explanation with the mechanical analogy of a rope passing through two slits (the wave passes only when the slits are parallel).

Common mistakes

- Claiming that sound can be polarized — false: sound in air is a longitudinal wave.

- Using μ in g cm^{-1} or g m^{-1} without converting to kg m^{-1} .
- Forgetting that $T = Mg$ uses $g = 9.81 \text{ m s}^{-2}$ (or 10 m s^{-2} if the question says so); the tension is a force, not the mass M alone.
- Confusing the plane of polarization (the plane in which the vibration occurs) with the direction of propagation: the plane of polarization contains the direction of propagation.
- Believing that v depends on frequency: on a given string under given tension, v is fixed by T and μ ; changing f only changes the wavelength $\lambda = v/f$.

GCE tips

- Always justify “light is a transverse wave” by describing the experiment with two Polaroids: rotating the analyser until the light is extinguished proves the vibrations are confined to one plane.
- Show units at each step of a calculation and give v with sensible significant figures (two or three).
- In sonometer questions, state the condition for resonance (frequency of the vibrating string = frequency of the tuning fork) before substituting numerical values.
- Quote applications: Polaroid sunglasses (which cut glare from light partially polarized by reflection), LCD screens, photoelastic stress analysis, and the tuning of guitars and pianos (tightening a peg raises T , hence raises f).



Signed • OnBuch+

ONBUCH+ TEACHING TEAM

FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+