

FURTHER MATHEMATICS • UPPER SIXTH

UPPER SIXTH — FURTHER MATHEMATICS

CHAPTER 16

ROTATIONAL DYNAMICS

SUGGESTED TIME: 10 PERIODS

IN THIS CHAPTER

This chapter extends Newtonian mechanics to rigid bodies rotating about a fixed axis: moment of inertia, radius of gyration, torque-driven motion, angular momentum, rotational energy, the compound pendulum and impulsive problems. It provides the full theoretical and problem-solving toolkit required by the MINESEC Further Mathematics syllabus and the GCE Advanced Level examination.

- By the end of this chapter I can define the moment of inertia of a particle and of a system of particles about an axis and compute it for discrete systems.
- By the end of this chapter I can state and use the radius of gyration and the parallel and perpendicular axes theorems.
- By the end of this chapter I can derive by integration the moments of inertia of standard bodies (rod, ring, disc, sphere, cylinder, rectangular lamina).
- By the end of this chapter I can write and solve the equation of motion of a rigid body under a constant torque, including connected-particle systems with a pulley.
- By the end of this chapter I can compute the moment of momentum (angular momentum) of a rotating body and apply its conservation.
- By the end of this chapter I can calculate the kinetic energy of a rotating rigid body and apply conservation of energy to rotational problems.



DOWNLOAD ON- BUCH

Free • Google Play
AI tutor, past papers,
results



GO ONBUCH+

All signed courses, unlimited AI
tutor, PDF sheets — OnBuch+
tab in the app

THIS SIGNED COURSE CONTAINS

COURSE

complete, illustrated,
step by step

METHODS

and worked examples

EXERCISES

exam style + solutions

SUMMARY SHEET

the essentials to
remember



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+

CONTENTS

- | | |
|---|--|
| 1. Moment of Inertia and Radius of Gyration | Force on the Axis |
| 2. Standard Moments of Inertia by Integration | 6. The Compound Pendulum and Synthesis |
| 3. Equation of Motion under a Constant Torque | 7. Integration activity |
| 4. Moment of Momentum and Its Conservation; Impulse | 8. Methods and worked examples |
| 5. Energy of a Rotating Body and the | 9. Exercises |
| | 10. Solutions to the exercises |
| | 11. Summary sheet |

CHAPTER OBJECTIVES

- By the end of this chapter I can define the moment of inertia of a particle and of a system of particles about an axis and compute it for discrete systems.
- By the end of this chapter I can state and use the radius of gyration and the parallel and perpendicular axes theorems.
- By the end of this chapter I can derive by integration the moments of inertia of standard bodies (rod, ring, disc, sphere, cylinder, rectangular lamina).
- By the end of this chapter I can write and solve the equation of motion of a rigid body under a constant torque, including connected-particle systems with a pulley.
- By the end of this chapter I can compute the moment of momentum (angular momentum) of a rotating body and apply its conservation.
- By the end of this chapter I can calculate the kinetic energy of a rotating rigid body and apply conservation of energy to rotational problems.
- By the end of this chapter I can analyse the compound pendulum, find its period and the length of the equivalent simple pendulum.
- By the end of this chapter I can determine the force exerted on the axis of rotation using the motion of the centre of mass.
- By the end of this chapter I can solve impulsive problems involving rotating bodies and connected particles.

PREREQUISITES

- Newton's laws of motion and the dynamics of connected particles (Lower Sixth Mechanics)
- Circular motion: angular velocity ω , relation $v = r\omega$, centripetal acceleration (Lower Sixth)
- The simple pendulum and simple harmonic motion, $T = 2\pi\sqrt{l/g}$
- Definite integration and standard integrals, including use of symmetry (Pure Mathematics)
- Work, kinetic energy $\frac{1}{2}mv^2$ and the principle of conservation of mechanical energy

1 MOMENT OF INERTIA AND RADIUS OF GYRATION

At the Mokolo market in Yaoundé, a carpenter spins a grindstone with his foot while a nearby potter shapes clay on a rotating wheel: both know instinctively that a heavy rim keeps the wheel turning long after the push stops. Why does a bicycle wheel resist being tilted once it spins fast, and why does a fufu pounder's pestle swing like a pendulum when hung from its end? These everyday Cameroonian observations hide a deep truth: rotating bodies obey laws as precise as Newton's, but with mass replaced by a new quantity — the **moment of inertia**. This chapter builds the complete mechanics of rotation needed for the GCE Advanced Level, and it begins with the central question of this section: how do we measure a body's resistance to being spun?

1.1 The Rotational Analogue of Mass

From Newton's second law to rotation.

Consider a single particle P of mass m , attached to a fixed vertical axis Δ by a light rigid rod of length r , free to rotate in a horizontal plane. Suppose a force $\vec{F}$ is applied to the particle, tangential to its circular path. Newton's second law gives the tangential acceleration:

$$F = ma.$$

The angular acceleration $\ddot{\theta}$ of the particle about Δ is related to the tangential acceleration by $a = r\ddot{\theta}$. Multiplying Newton's law by r :

$$Fr = mr^2 \ddot{\theta}.$$

The left-hand side, Fr , is the moment of the force about the axis — the **torque**, usually written C or Γ . The equation therefore reads

$$C = (mr^2) \ddot{\theta}.$$

Compare this with $F = m\ddot{x}$ for linear motion. The roles correspond exactly:

	Linear motion	Rotation about a fixed axis
Cause	Force F	Torque $C = Fr$
Effect	Acceleration $\ddot{x}$	Angular acceleration $\ddot{\theta}$
Inertia	Mass m	mr^2

The quantity mr^2 plays for rotation the role that mass plays for translation. Crucially, it depends not only on how much mass there is, but on where that mass sits relative to the axis. Doubling the distance r quadruples the resistance to angular acceleration. This is exactly why the potter's wheel has its mass concentrated in a heavy rim: a large r for most of the mass gives a large mr^2 , so the wheel's angular velocity barely changes between kicks of the foot.

DEFINITION Moment of inertia of a particle and of a system

The **moment of inertia** of a particle of mass m about an axis Δ , at perpendicular distance r

from Δ , is

$$I = mr^2.$$

For a system of particles of masses $m_1, m_2, \dots, m_n$ at perpendicular distances $r_1, r_2, \dots, r_n$ from the same axis Δ , the moment of inertia is

$$I = \sum_{i=1}^n m_i r_i^2.$$

The SI unit is the kilogram metre squared, kg m^2 . The distance r_i is always the perpendicular distance from the particle to the axis.


WARNING Distance to the axis, not to a point

The most frequent error at this stage is to measure r_i from a point (for example the origin) instead of measuring the perpendicular distance to the axis. If the axis is the vertical line $x = a$ in a horizontal plane, a particle at horizontal coordinate x_i has $r_i = |x_i - a|$, whatever its other coordinates may be.

1.2 Computing I for Discrete Systems

METHOD Checklist for computing I of a discrete system

1. Identify the axis of rotation precisely (a line, not a point).
2. Measure the perpendicular distance r_i of each particle from that axis; ignore masses on the axis itself (they contribute 0) and ignore light rods or frames (their mass is neglected).
3. Compute each term $m_i r_i^2$, taking care to square the distance.
4. Sum the terms: $I = \sum m_i r_i^2$. State the unit, kg m^2 .



Three particles on a light frame rotating about a vertical axis Δ . Each r_i is the perpendicular distance from the particle to the axis, and $I = m_1 r_1^2 + m_2 r_2^2 + m_3 r_3^2$.

WORKED EXAMPLE 1 A dumb-bell about two different axes

A dumb-bell consists of two particles, each of mass 2 kg, joined by a light rod of length 1.2 m. Find the moment of inertia (a) about an axis perpendicular to the rod through its midpoint G ; (b) about a parallel axis through one of the masses.

SOLUTION

Solution. (a) Each mass is at distance $r = 0.6$ m from the axis through G :

$$I_G = 2 \times (0.6)^2 + 2 \times (0.6)^2 = 0.72 + 0.72 = 1.44 \text{ kg m}^2.$$

(b) About the axis through one mass: that mass contributes $2 \times 0^2 = 0$; the other is at distance 1.2 m:

$$I = 2 \times (1.2)^2 = 2.88 \text{ kg m}^2.$$

Note that $I = 2I_G$: the moment of inertia depends essentially on the choice of axis.

WORKED EXAMPLE 2 Particles at the vertices of a square frame

Four particles of masses m , $2m$, $3m$ and $4m$ are fixed at the vertices A , B , C , D of a light square frame of side a . Find the moment of inertia about the side AD .

SOLUTION

Solution. The axis AD passes through A and D , so the masses at A and D contribute nothing. The particles at B (mass $2m$) and C (mass $3m$) are each at perpendicular distance a from AD :

$$I_{AD} = 2m a^2 + 3m a^2 = 5m a^2.$$

The same calculation about the diagonal AC would give $I_{AC} = 2m\left(\frac{a}{\sqrt{2}}\right)^2 + 4m\left(\frac{a}{\sqrt{2}}\right)^2 = 3ma^2$, since B and D are at distance $a/\sqrt{2}$ from the diagonal.

1.3 Radius of Gyration

The total mass of a body is $M = \sum m_i$, but the moment of inertia $\sum m_i r_i^2$ involves the distribution of that mass. It is convenient to compress all the information into a single length.

DEFINITION Radius of gyration

The **radius of gyration** k of a body about an axis is the distance defined by

$$I = Mk^2, \quad \text{i.e.} \quad k = \sqrt{\frac{I}{M}},$$

where M is the total mass. Physically, k is the distance from the axis at which the whole mass of the body could be concentrated into a single particle without changing the moment of inertia.

For the dumb-bell above, $M = 4 \text{ kg}$ and $I_G = 1.44 \text{ kg m}^2$, so

$$k = \sqrt{\frac{1.44}{4}} = 0.6 \text{ m},$$

which is exactly the distance of each mass from G — as it must be, since all the mass already lies at that distance. For a body whose mass is spread at different distances, k is a root-mean-square distance: $k^2 = \frac{\sum m_i r_i^2}{\sum m_i}$. The radius of gyration is the quantity engineers quote because it separates the two factors M and k^2 : two flywheels of equal mass but different k behave very differently.

1.4 The Theorem of Parallel Axes


Computing I about every conceivable axis would be tedious. Two theorems allow us to transfer a known result from one axis to another. The first and most important concerns parallel axes.

PROPERTY Theorem of parallel axes

Let G be the centre of mass of a body of mass M , and let I_G be its moment of inertia about an axis through G . The moment of inertia about a parallel axis Δ at distance h from the first is

$$I = I_G + Mh^2.$$

(Proof examinable — see below.)



Parallel axes: the axis through the centre of mass G and a parallel axis Δ at distance h . A general element P of mass m has coordinate x measured from the axis through G .

Proof.

Choose the axis through G as the line $x = 0$ in a plane perpendicular to both axes, and let Δ be the parallel line $x = h$. A general particle P of mass m_i has perpendicular distance x_i from the axis through G ; its perpendicular distance from Δ is $(x_i - h)$. (Distances perpendicular to the axes in the other direction are unchanged, so we may work with signed coordinates x_i in the plane containing both axes.) Then

$$\begin{aligned} I &= \sum m_i (x_i - h)^2 = \sum m_i x_i^2 - 2h \sum m_i x_i + h^2 \sum m_i \\ &= I_G - 2h \sum m_i x_i + Mh^2. \end{aligned}$$

But $\sum m_i x_i = M\bar{x}$, where $\bar{x}$ is the coordinate of the centre of mass measured from the axis through G ; since that axis passes through G , $\bar{x} = 0$ and the middle term vanishes. Hence

$$I = I_G + Mh^2. \quad \blacksquare$$

WARNING One axis must pass through G

The theorem is valid only when one of the two axes passes through the centre of mass. It is false that $I_A = I_B + Mh^2$ for two arbitrary parallel axes A and B . If you know I_A about an axis not through G and want I_B , you must go via G : first $I_G = I_A - Mh_1^2$, then $I_B = I_G + Mh_2^2$. Note also the corollary: among all parallel axes, the moment of inertia is least about the axis through G .

EXAMPLE Checking the dumb-bell

For the dumb-bell, $I_G = 1.44 \text{ kg m}^2$, $M = 4 \text{ kg}$, and the axis through one mass is at $h = 0.6 \text{ m}$ from G :

$$I = I_G + Mh^2 = 1.44 + 4(0.6)^2 = 1.44 + 1.44 = 2.88 \text{ kg m}^2,$$

agreeing with the direct computation.

1.5 The Theorem of Perpendicular Axes


The second transfer theorem applies only to laminae — plane bodies of negligible thickness.

PROPERTY Theorem of perpendicular axes

Let a lamina lie in the xy -plane, and let Ox , Oy , Oz be three mutually perpendicular axes, with Oz perpendicular to the lamina. Then

$$I_z = I_x + I_y,$$

where I_x, I_y, I_z are the moments of inertia of the lamina about the three axes. (Proof examinable — see below.)



A lamina in the xy -plane with a general element P of mass m at (x, y) . Its distance from Oz is $\sqrt{x^2 + y^2}$, from Ox is $|y|$, from Oy is $|x|$.

Proof.

Let a general element of the lamina have mass m_i and coordinates (x_i, y_i) . Its perpendicular distances from the three axes are:

$$\text{to } Ox : |y_i|, \quad \text{to } Oy : |x_i|, \quad \text{to } Oz : \sqrt{x_i^2 + y_i^2}.$$

Therefore

$$I_z = \sum m_i(x_i^2 + y_i^2) = \sum m_i x_i^2 + \sum m_i y_i^2 = I_y + I_x. \quad \blacksquare$$

WARNING Laminae only

The perpendicular axes theorem requires the body to be plane: for a three-dimensional solid, the distance of an element from Oz involves z_i as well, and the relation fails. Do not apply it to spheres, cones or cylinders.

1.6 Exam Technique: Transferring Standard Results

The real power of the two theorems appears when they are combined with the standard results proved by integration in the next section (Lesson 110). Anticipating those results, the method is always the same.

METHOD Transferring a standard moment of inertia to a new axis

1. Recall or derive I about the standard axis (usually through G).
2. Parallel axes? If the new axis is parallel to the standard one, add Mh^2 where h is the distance between the axes — checking first that the standard axis passes through G .
3. Perpendicular axes? For a lamina, if you know two of I_x, I_y, I_z , deduce the third from $I_z = I_x + I_y$. Symmetry often gives $I_x = I_y$, so $I_z = 2I_x$.
4. Chain the theorems if necessary, always passing through the centre of mass.

WORKED EXAMPLE 3 Rod about an end; square lamina about a side and a corner

(a) A uniform rod AB of mass M and length $2a$ has $I_G = \frac{1}{3}Ma^2$ about the perpendicular axis through its centre. Find I about the parallel axis through A . (b) A uniform square lamina of mass M and side $2a$ has $I = \frac{1}{3}Ma^2$ about each of the axes through its centre G parallel to the sides. Find its moment of inertia (i) about the perpendicular axis through G ; (ii) about one side; (iii) about the perpendicular axis through a corner.

SOLUTION

Solution. (a) A is at distance a from G , so by parallel axes:

$$I_A = \frac{1}{3}Ma^2 + Ma^2 = \frac{4}{3}Ma^2.$$

(b)(i) By perpendicular axes, with $I_x = I_y = \frac{1}{3}Ma^2$:

$$I_z = I_x + I_y = \frac{2}{3}Ma^2.$$

(ii) A side is parallel to a central axis, at distance a from G :

$$I_{\text{side}} = \frac{1}{3}Ma^2 + Ma^2 = \frac{4}{3}Ma^2.$$

(iii) A corner is at distance $a\sqrt{2}$ from G along the perpendicular direction measured in the plane; the perpendicular axis through the corner is parallel to Oz , so by parallel axes:

$$I_{\text{corner}} = I_z + M(a\sqrt{2})^2 = \frac{2}{3}Ma^2 + 2Ma^2 = \frac{8}{3}Ma^2.$$

KEY POINTS Key points of this section

- Moment of inertia of a particle: $I = mr^2$; of a system: $I = \sum m_i r_i^2$, in kg m^2 , where r_i is the perpendicular distance to the axis.
- Radius of gyration: $I = Mk^2$; k is the distance at which the whole mass could be concentrated.
- Parallel axes: $I = I_G + Mh^2$ — valid only when one axis passes through the centre of mass G ; I is minimal about the axis through G .
- Perpendicular axes (laminae only): $I_z = I_x + I_y$.
- To transfer between two axes neither of which passes through G , always go via G .

EXERCISE 1 Practice

1. Three particles of masses 1 kg, 2 kg and 3 kg are at the vertices of an equilateral triangle of side 0.6 m, the 1 kg mass being at the top vertex. Find I about the base of the triangle, and the corresponding radius of gyration.
2. A body has $I = 5 \text{ kg m}^2$ about an axis through its centre of mass and $M = 2 \text{ kg}$. Find I about a parallel axis 1.5 m away.
3. A body of mass 4 kg has $I = 10 \text{ kg m}^2$ about an axis A , and G is 1 m from A . Find I about a parallel axis B on the other side of G , 0.5 m from G .
4. A uniform circular lamina has $I = \frac{1}{2}Ma^2$ about the perpendicular axis through its centre. Using symmetry and the perpendicular axes theorem, find I about a diameter, and then about a tangent line in the plane of the lamina.

SOLUTION Exercise 1

1. The base passes through the 2 kg and 3 kg masses (zero contribution); the 1 kg mass is at the height of the triangle, $h = 0.6 \times \frac{\sqrt{3}}{2} = 0.3\sqrt{3} \text{ m}$. So $I = 1 \times (0.3\sqrt{3})^2 = 0.27 \text{ kg m}^2$, and $k = \sqrt{0.27/6} \approx 0.212 \text{ m}$. 2. $I = 5 + 2(1.5)^2 = 9.5 \text{ kg m}^2$. 3. Via G : $I_G = 10 - 4(1)^2 = 6 \text{ kg m}^2$; then $I_B = 6 + 4(0.5)^2 = 7 \text{ kg m}^2$. 4. By symmetry $I_x = I_y$ for two perpendicular diameters, and $I_z = I_x + I_y = \frac{1}{2}Ma^2$ gives $I_{\text{diameter}} = \frac{1}{4}Ma^2$. A tangent in the plane is parallel to a diameter at distance a : $I_{\text{tangent}} = \frac{1}{4}Ma^2 + Ma^2 = \frac{5}{4}Ma^2$.

DID YOU KNOW? Flywheels in Cameroonian workshops

The grindstones and potters' wheels of Mokolo market are flywheels: their rims are deliberately heavy so that k — and hence $I = Mk^2$ — is large. A large moment of inertia smooths out the irregular pushes of the foot, storing rotational kinetic energy $\frac{1}{2}I\omega^2$ (Section 5) and releasing it steadily. The same principle steadies the engines of the bendskins (motorcycle taxis) of Douala and the generators that keep Yaoundé lit during load-shedding.

2 STANDARD MOMENTS OF INERTIA BY INTEGRATION

In the previous section we defined the moment of inertia of a system of particles as $I = \sum m_i r_i^2$ and introduced the radius of gyration k through $I = Mk^2$. That discrete formula is perfect for a few point masses, but a real rigid body — a rod, a disc, a flywheel, a sphere — contains an effectively infinite number of mass elements. To compute its moment of inertia we must replace the sum by an integral. This section develops that technique, derives the standard results quoted throughout the GCE Advanced Level examination, and shows how to combine them for composite bodies.

2.1 From Sums to Integrals

Imagine a lamina divided into n tiny pieces, the i -th piece having mass δm_i at perpendicular distance r_i from the axis. Then

$$I = \sum_{i=1}^n r_i^2 \delta m_i.$$

As the pieces are made arbitrarily small, this sum becomes an integral taken over the whole body:

DEFINITION Moment of inertia of a continuous body

$$I = \int r^2 dm,$$

where r is the perpendicular distance of the mass element dm from the axis of rotation, and the integral extends over the whole body.

The whole art lies in choosing a **mass element** dm whose points are all at (approximately) the same distance r from the axis, and expressing dm through the density:

- **Linear density** λ (mass per unit length, kg m^{-1}): $dm = \lambda dx$ for rods.
- **Surface density** σ (mass per unit area, kg m^{-2}): $dm = \sigma dA$ for laminas, rings, discs.
- **Volume density** ρ (mass per unit volume, kg m^{-3}): $dm = \rho dV$ for solid cylinders and spheres.

For a uniform body the density is constant and equals total mass divided by total length, area or volume.


METHOD General strategy for finding I by integration

1. Draw the body and mark the axis clearly.
2. Choose a thin element (strip, ring, disc) all of whose points lie at the same distance r from the axis.
3. Write the mass of the element: $dm = \lambda dx, \sigma dA$ or ρdV .
4. Write $dI = r^2 dm$ and integrate between the geometric limits of the body.
5. Replace the density by M over total length/area/volume to express I in terms of M .
6. (Optional) Read off the radius of gyration from $I = Mk^2$.

2.2 The Uniform Rod

Consider a uniform rod AB of length $2a$ and mass M , so its linear density is $\lambda = \frac{M}{2a}$.

Axis perpendicular to the rod through its centre. Place the origin at the centre G and the axis perpendicular to the rod. An element of length dx at distance x from G has mass $dm = \lambda dx$ and every point of it is at distance x from the axis.



Rod with element of length dx at distance x from the central axis.

Hence

$$I_G = \int_{-a}^a x^2 \lambda dx = \lambda \left[\frac{x^3}{3} \right]_{-a}^a = \frac{2\lambda a^3}{3} = \frac{2a^3}{3} \cdot \frac{M}{2a} = \boxed{\frac{1}{3}Ma^2}.$$

Axis perpendicular to the rod through one end. Measuring x from the end A , the limits become 0 and $2a$:

$$I_A = \int_0^{2a} x^2 \lambda dx = \lambda \frac{(2a)^3}{3} = \frac{8\lambda a^3}{3} = \frac{4}{3}Ma^2.$$

Note the consistency check with the parallel axes theorem: $I_A = I_G + Ma^2 = \frac{1}{3}Ma^2 + Ma^2 = \frac{4}{3}Ma^2$.

WARNING The axis position changes everything

For a rod of length $2a$, $I = \frac{1}{3}Ma^2$ about the centre but $\frac{4}{3}Ma^2$ about an end — four times larger. Many candidates lose marks by quoting $\frac{1}{3}Ma^2$ when the rod swings about its end. Always identify the axis first, and check whether the question uses length $2a$ or length l (with $l = 2a$, the results are $\frac{1}{12}Ml^2$ and $\frac{1}{3}Ml^2$).

2.3 The Uniform Ring and the Thin Hollow Cylinder


For a uniform ring (hoop) of mass M and radius a about the axis through its centre perpendicular to its plane, every mass element is at the same distance a from the axis. No real integration is needed:

$$I = \int a^2 dm = a^2 \int dm = Ma^2.$$

The same argument applies to a thin hollow cylinder (a “hoop” extended along the axis) about its central axis: $I = Ma^2$. This is why a hoop rolls downhill more slowly than a disc of the same mass and radius — more of its mass sits far from the axis.

2.4 The Uniform Circular Disc

Let a uniform disc have mass M and radius a , with surface density $\sigma = \frac{M}{\pi a^2}$, and take the axis through its centre perpendicular to its plane. Points of the disc lie at all distances from 0 to a , so we slice the disc into **concentric rings**: a ring of radius r and width dr has area $2\pi r dr$, and every point of it is at distance r from the axis.



Disc divided into concentric rings of radius r and width dr .

The ring's mass is $dm = \sigma \cdot 2\pi r dr$, so

$$I = \int_0^a r^2 \sigma 2\pi r dr = 2\pi\sigma \int_0^a r^3 dr = 2\pi\sigma \frac{a^4}{4} = \frac{\pi\sigma a^4}{2}.$$

Substituting $\sigma = \frac{M}{\pi a^2}$:

$$I = \frac{1}{2} M a^2.$$

A solid cylinder of mass M and radius a about its own axis is just a stack of such discs, so the same formula holds: $I = \frac{1}{2} M a^2$ (independent of the height).

Solid cylinder about a diameter through its centre. Slice the cylinder of height h into discs of thickness dx perpendicular to the axis, at distance x from the centre. Each disc has mass $dm = \frac{M}{h} dx$ and, by the perpendicular axes theorem applied to a disc, moment of inertia $\frac{1}{4} dm a^2$ about a diameter of that disc; the parallel axes theorem shifts this to the diameter through G :


$$dI = \frac{1}{4} a^2 dm + x^2 dm.$$

Integrating from $-h/2$ to $h/2$:

$$I = \frac{M}{h} \int_{-h/2}^{h/2} \left(\frac{a^2}{4} + x^2 \right) dx = M \left(\frac{a^2}{4} + \frac{h^2}{12} \right).$$

2.5 The Uniform Solid Sphere about a Diameter

Let the sphere have mass M , radius a , and volume density $\rho = \frac{M}{\frac{4}{3}\pi a^3}$. Take the diameter as the x -axis and slice the sphere perpendicular to it into thin discs. The disc at position x has radius $y = \sqrt{a^2 - x^2}$ (Pythagoras on a cross-section) and thickness dx .



Sphere sliced into discs perpendicular to a diameter; $y = \sqrt{a^2 - x^2}$.

The disc's mass is $dm = \rho \pi y^2 dx = \rho \pi (a^2 - x^2) dx$, and its moment of inertia about the axis (its own central axis) is $\frac{1}{2} y^2 dm$:

$$\begin{aligned} I &= \int_{-a}^a \frac{1}{2} y^2 dm = \frac{\pi \rho}{2} \int_{-a}^a (a^2 - x^2)^2 dx \\ &= \frac{\pi \rho}{2} \int_{-a}^a (a^4 - 2a^2 x^2 + x^4) dx = \frac{\pi \rho}{2} \left[a^4 x - \frac{2a^2 x^3}{3} + \frac{x^5}{5} \right]_{-a}^a \\ &= \frac{\pi \rho}{2} \cdot 2 \left(a^5 - \frac{2a^5}{3} + \frac{a^5}{5} \right) = \pi \rho a^5 \cdot \frac{15 - 10 + 3}{15} = \frac{8\pi \rho a^5}{15}. \end{aligned}$$

Replacing $\rho = \frac{3M}{4\pi a^3}$:

$$I = \frac{2}{5}Ma^2.$$

This derivation is a classic “show that” question at the GCE; learn the slicing idea, not just the result.

2.6 The Uniform Rectangular Lamina

Let a uniform rectangular lamina have mass M , sides $2a$ (along x) and $2b$ (along y), and surface density $\sigma = \frac{M}{4ab}$.

About the axis in its plane through G parallel to the side $2b$. Slice into strips parallel to that axis, of width dx at distance x : each strip is itself a rod of mass $\sigma \cdot 2b \, dx$ with all points at distance x :

$$I = \int_{-a}^a x^2 \sigma 2b \, dx = 2b\sigma \frac{2a^3}{3} = \frac{4ab\sigma a^2}{3} = \frac{1}{3}Ma^2.$$

Similarly, about the axis parallel to the side $2a$: $I = \frac{1}{3}Mb^2$.

About the perpendicular axis through G . By the perpendicular axes theorem for a lamina, $I_z = I_x + I_y$:

$$I = \frac{1}{3}M(a^2 + b^2).$$

2.7 Summary of Standard Results

PROPERTY Standard moments of inertia — to memorise

All bodies are uniform, of mass M ; the axis passes through the centre of mass unless stated. Proofs by integration (as above) are examinable when the question says “prove”, “show” or “from first principles”.

Body	Axis	I	k^2
Rod, length $2a$	perpendicular, through centre	$\frac{1}{3}Ma^2$	$\frac{1}{3}a^2$
Rod, length $2a$	perpendicular, through one end	$\frac{4}{3}Ma^2$	$\frac{4}{3}a^2$
Ring / hoop, radius a	central, perpendicular to plane	Ma^2	a^2
Disc / solid cylinder, radius a	central axis	$\frac{1}{2}Ma^2$	$\frac{1}{2}a^2$
Solid sphere, radius a	any diameter	$\frac{2}{5}Ma^2$	$\frac{2}{5}a^2$
Rectangular lamina, sides $2a, 2b$	in plane, through centre, $\parallel$ side $2b$	$\frac{1}{3}Ma^2$	$\frac{1}{3}a^2$
Rectangular lamina, sides $2a, 2b$	perpendicular, through centre	$\frac{1}{3}M(a^2 + b^2)$	$\frac{1}{3}(a^2 + b^2)$
Solid cylinder, radius a , height h	diameter through centre	$M\left(\frac{a^2}{4} + \frac{h^2}{12}\right)$	$\frac{a^2}{4} + \frac{h^2}{12}$

WARNING Exam technique

In the GCE you may quote any standard result from this table without re-deriving it — unless the question explicitly says “prove”, “show by integration” or “from first principles”. When a proof is required, present the element, its mass, and the integral exactly as in the models above.

2.8 Composite Bodies: Adding and Subtracting**METHOD** Moments of inertia of composite bodies

1. Split the body into standard parts (rods, discs, spheres, point masses).
2. Moments of inertia about the same axis add: $I = I_1 + I_2 + \dots$
3. For a hole, subtract the moment of inertia of the missing piece (computed about the same axis).
4. Use the parallel axes theorem $I = I_G + Md^2$ whenever a part's own centre is not on the axis.

WORKED EXAMPLE 4 Disc with a circular hole

A uniform circular disc of radius $2a$ has a concentric circular hole of radius a . The mass of the remaining body is M . Find its moment of inertia about the central axis perpendicular to its plane.

SOLUTION

Solution. Treat the body as (full disc of radius $2a$) minus (disc of radius a). The surface density is uniform; the full disc has area $4\pi a^2$ and the hole πa^2 , so the remaining area is $3\pi a^2$. Hence the full disc had mass $\frac{4}{3}M$ and the removed piece mass $\frac{1}{3}M$.

$$\begin{aligned}
 I_{\text{full}} &= \frac{1}{2} \left(\frac{4}{3}M \right) (2a)^2 = \frac{8}{3}Ma^2, \\
 I_{\text{hole}} &= \frac{1}{2} \left(\frac{1}{3}M \right) a^2 = \frac{1}{6}Ma^2, \\
 I &= \frac{8}{3}Ma^2 - \frac{1}{6}Ma^2 = \frac{15}{6}Ma^2 = \boxed{\frac{5}{2}Ma^2}.
 \end{aligned}$$

Check: $k^2 = \frac{5}{2}a^2$, between a^2 (ring) and $\frac{1}{2}(2a)^2 = 2a^2$ (full disc) — sensible since mass is concentrated at larger radii.

WORKED EXAMPLE 5 Rod carrying two point masses

A uniform rod AB of length $2a$ and mass $3m$ carries a particle of mass $2m$ at A and a particle of mass m at its midpoint G . Find the moment of inertia of the system about a perpendicular axis through A , and the radius of gyration.

SOLUTION

Solution. Add the contributions about the axis through A :

$$\begin{aligned} I_{\text{rod}} &= \frac{4}{3}(3m)a^2 = 4ma^2, \\ I_{2m} &= 2m \cdot 0^2 = 0 \quad (\text{on the axis}), \\ I_m &= m a^2. \end{aligned}$$

Total: $I = 4ma^2 + ma^2 = 5ma^2$. The total mass is $3m + 2m + m = 6m$, so

$$k = \sqrt{\frac{I}{M}} = \sqrt{\frac{5ma^2}{6m}} = a\sqrt{\frac{5}{6}}.$$

EXPERIMENT Rolling race — an experimental insight

Take a hoop, a solid disc, and a solid sphere, all of the same mass and radius. Release them from rest at the top of an inclined plane. The sphere reaches the bottom first, then the disc, then the hoop. This order reflects their moments of inertia: $I_{\text{sphere}} = \frac{2}{5}Ma^2$, $I_{\text{disc}} = \frac{1}{2}Ma^2$, $I_{\text{hoop}} = Ma^2$. The smaller the moment of inertia, the more gravitational potential energy is converted into translational kinetic energy rather than rotational kinetic energy, so the greater the linear acceleration. This experiment beautifully illustrates why the distribution of mass matters, not just the total mass.

DID YOU KNOW? Historical note

The concept of moment of inertia was introduced by Leonhard Euler in 1765 in his work *Theoria motus corporum solidorum seu rigidorum*. Euler also derived the principal axes theorem and the equations of motion for a rigid body. The term “moment of inertia” was coined later; Euler called it “momentum inertiae”. The parallel axes theorem is due to Christiaan Huygens (1673) in his study of compound pendulums, and the perpendicular axes theorem for laminas is often attributed to Jakob Steiner (1826).

EXERCISE 2 Flywheel with a hole

A uniform solid cylinder of mass $6m$ and radius $2a$ has a coaxial cylindrical hole of radius a drilled through it. Show that the moment of inertia of the remaining body about its axis is $\frac{45}{4}ma^2$, and state the radius of gyration.

SOLUTION Flywheel with a hole

The cylinder before drilling has mass $6m$ and radius $2a$. Its cross-sectional area is $\pi(2a)^2 = 4\pi a^2$. The hole has radius a , area πa^2 . The remaining cross-sectional area is $3\pi a^2$. Since the density is uniform, masses are proportional to areas.

$$\text{Mass of removed cylinder} = \frac{\pi a^2}{4\pi a^2} \times 6m = \frac{3}{2}m = 1.5m.$$

$$\text{Mass of remaining body} = 6m - 1.5m = 4.5m = \frac{9}{2}m.$$

Now compute moments of inertia about the common axis:

$$I_{\text{original}} = \frac{1}{2}(6m)(2a)^2 = 12ma^2.$$

$$I_{\text{hole}} = \frac{1}{2}\left(\frac{3}{2}m\right)a^2 = \frac{3}{4}ma^2.$$

$$I_{\text{remaining}} = 12ma^2 - \frac{3}{4}ma^2 = \frac{48-3}{4}ma^2 = \frac{45}{4}ma^2.$$

The radius of gyration k satisfies $I = M_{\text{rem}}k^2$:

$$\frac{45}{4}ma^2 = \frac{9}{2}mk^2 \Rightarrow k^2 = \frac{45}{4} \cdot \frac{2}{9}a^2 = \frac{5}{2}a^2 \Rightarrow k = a\sqrt{\frac{5}{2}}.$$

KEY POINTS Key points

- $I = \int r^2 dm$; choose elements whose points are all at the same distance from the axis (strips, rings, discs).
- Standard results: rod $\frac{1}{3}Ma^2$ (centre) and $\frac{4}{3}Ma^2$ (end); ring Ma^2 ; disc and solid cylinder $\frac{1}{2}Ma^2$; solid sphere $\frac{2}{5}Ma^2$.
- Moments of inertia add for composite bodies; subtract for holes; shift with $I_G + Md^2$ when needed.
- Quote standard results freely unless the question demands a proof by integration.

3 EQUATION OF MOTION UNDER A CONSTANT TORQUE

In the previous sections we learned how to compute the moment of inertia I of a rigid body by integration, and how to express the result compactly through the radius of gyration, $I = Mk^2$. The moment of inertia, however, is not an end in itself: it is the rotational analogue of mass, and its true role appears when we ask the dynamical question — how does a rigid body respond when forces try to make it rotate? Just as Newton's second law $F = ma$ answers this question for translation, there is a rotational counterpart, $C = I\alpha$, which is the central result of this section and one of the most frequently examined results of the whole chapter. We shall build it carefully, starting from the notion of the moment of a force, and then apply it to braking problems, to pulleys with inertia, and to bodies swinging under gravity.

3.1 The Moment of a Force about a Fixed Axis

Intuition. Everyone who has opened a door knows that the effect of a force on a rotating body depends not only on the size of the force but also on where and in what direction it is applied. Push near the hinges and the door barely moves; push at the handle, perpendicular to the door, and it swings open easily. Push along the door towards the hinges and nothing rotates at all. The quantity that measures this “turning effect” is the **moment** of the force, also called the **torque**.

DEFINITION Moment (torque) of a force about a fixed axis

Let a force of magnitude F act on a body free to rotate about a fixed axis Δ , and suppose the force lies in a plane perpendicular to the axis. The **moment** of the force about the axis is


$$C = Fd,$$

where d is the **lever arm**: the perpendicular distance from the axis to the line of action of the force. The SI unit of moment is the newton-metre (N m). The moment is given a sign: we choose a positive sense of rotation (usually anticlockwise) and count $C > 0$ if the force tends to turn the body in that sense, $C < 0$ otherwise. A moment tending to slow a rotation is called a resisting couple or braking torque.

WARNING Torque is not work

Although the newton-metre is dimensionally the same as the joule, a torque is not an energy. Never write a torque in joules, and never add a torque to an energy. Keep the unit N m for moments and reserve J for work and energy.

If several forces act, the total moment about the axis is the algebraic sum $C = \sum F_i d_i$, each term carrying the sign of the sense in which it tends to turn the body. Note also that a force whose line of action passes through the axis has $d = 0$ and hence zero moment: the reaction at a hinge or axle never appears in the moment equation. This is precisely why the moment equation is so useful: it lets us study the rotation without ever knowing the reaction at the axle.



A force $\vec{F}$ applied tangentially at A to a wheel free to turn about a fixed axis through O. The lever arm is $d = OA$, and the moment is $C = Fd$, positive in the anticlockwise sense shown.

3.2 Derivation of the Equation of Motion $C = I\alpha$

Consider a rigid body rotating about a fixed axis through O with angular acceleration α . Think of the body as a collection of particles P_i of mass m_i , each at a perpendicular distance r_i from the axis. Because the body is rigid, every particle has the same angular acceleration α , and particle P_i moves on a circle of radius r_i with tangential acceleration $a_i = r_i\alpha$.

Apply Newton's second law to particle P_i in the tangential direction. The tangential force on P_i has two origins: external forces applied to the body (giving a tangential component F_i) and internal forces exerted by the other particles. Thus

$$m_i r_i \alpha = F_i + (\text{tangential internal forces on } P_i).$$

Multiply by r_i and sum over all particles:

$$\alpha \sum_i m_i r_i^2 = \sum_i F_i r_i + \sum_i r_i \times (\text{internal forces}).$$

Now two remarkable simplifications occur:

- By Newton's third law, internal forces occur in equal and opposite pairs acting along the same line, so their total moment about the axis is **zero**: the last sum vanishes.
- The sum $\sum_i m_i r_i^2$ is exactly the moment of inertia I of the body about the axis, and $\sum_i F_i r_i$ is the total moment C of the external forces about the axis.

PROPERTY Equation of rotational motion about a fixed axis

For a rigid body rotating about a fixed axis, if C is the total moment of the external forces about the axis, I the moment of inertia about the same axis, and α the angular acceleration, then

$$C = I\alpha$$

This is the rotational analogue of Newton's second law $F = ma$: torque plays the role of force, moment of inertia the role of mass, and angular acceleration the role of acceleration. The derivation above (from $F = ma$ applied to each particle, using Newton's third law to eliminate internal forces) is examinable and should be reproduced in full.

KEY POINTS The translation–rotation dictionary

	Translation	Rotation
Displacement	s (m)	θ (rad)
Velocity	$v = \dot{s}$	$\omega = \dot{\theta}$
Acceleration	$a = \dot{v}$	$\alpha = \dot{\omega}$
Inertia	mass m	moment of inertia I
Cause of motion	force F	moment $C = Fd$
Second law	$F = ma$	$C = I\alpha$

3.3 Constant Torque: the Kinematics of Rotation

When the total torque C is constant and the body is rigid (so I is constant), the equation $C = I\alpha$ gives a **constant angular acceleration** $\alpha = C/I$. Rotational motion with constant α is governed by formulae exactly parallel to those of uniformly accelerated linear motion, obtained by integrating $\dot{\omega} = \alpha$:

PROPERTY Constant angular acceleration formulae

If α is constant, ω_0 the initial angular velocity and θ the angle turned through in time t , then

$$\omega = \omega_0 + \alpha t, \quad \theta = \omega_0 t + \frac{1}{2}\alpha t^2, \quad \omega^2 = \omega_0^2 + 2\alpha\theta.$$

Angles must be in radians, angular velocities in rad s^{-1} , angular accelerations in rad s^{-2} .

WARNING Keep the units consistent

Before substituting into $C = I\alpha$, convert everything to SI units: torque in N m , moment of inertia in kg m^2 , α in rad s^{-2} . The most frequent error is to leave a rotation speed in revolutions per minute: convert with $\omega = \frac{2\pi N}{60} \text{ rad s}^{-1}$ where N is in rev min^{-1} . Similarly, a number of revolutions n corresponds to an angle $\theta = 2\pi n$ radians.

WORKED EXAMPLE 6 Flywheel brought to rest by a braking couple

A flywheel of moment of inertia $I = 0.8 \text{ kg m}^2$ rotates at 300 rev min^{-1} . A constant resisting couple of magnitude 2 N m is applied. Find (a) the angular acceleration, (b) the time taken to stop, (c) the number of revolutions made before stopping.

SOLUTION

Solution. Convert the initial speed:

$$\omega_0 = \frac{2\pi \times 300}{60} = 10\pi \text{ rad s}^{-1} \approx 31.4 \text{ rad s}^{-1}.$$

(a) The couple resists the motion, so with the sense of rotation positive, $C = -2 \text{ N m}$. Then

$$\alpha = \frac{C}{I} = \frac{-2}{0.8} = -2.5 \text{ rad s}^{-2}.$$

(b) Stopping means $\omega = 0$. From $\omega = \omega_0 + \alpha t$:

$$0 = 10\pi - 2.5t \implies t = \frac{10\pi}{2.5} = 4\pi \approx 12.6 \text{ s}.$$


(c) Use $\omega^2 = \omega_0^2 + 2\alpha\theta$ with $\omega = 0$:

$$\theta = \frac{-\omega_0^2}{2\alpha} = \frac{-(10\pi)^2}{2(-2.5)} = \frac{100\pi^2}{5} = 20\pi^2 \text{ rad}.$$

The number of revolutions is

$$n = \frac{\theta}{2\pi} = \frac{20\pi^2}{2\pi} = 10\pi \approx 31.4 \text{ revolutions}.$$

Note how the sign convention (resisting couple negative) automatically produces a negative α and a positive stopping angle.



Angular velocity decreasing linearly under a constant braking couple: $\omega(t)$ is a straight line of slope $\alpha = -2.5 \text{ rad s}^{-2}$, reaching zero at the stopping time $t = 4\pi \text{ s}$.

3.4 The Pulley with Non-negligible Moment of Inertia

In Mechanics you solved Atwood machines with a “light, frictionless pulley”, for which the tension is the same on both sides. When the pulley has a non-negligible moment of inertia I and radius r , this is no longer true: a difference of tensions is precisely what provides the torque that spins the pulley up. This is one of the most classic GCE traps.

WARNING With a massive pulley, $T_1 \neq T_2$

If the pulley has inertia and the string does not slip, the tensions on the two sides are different. Writing $T_1 = T_2$ forces the net torque on the pulley to be zero, contradicting the fact that the pulley angularly accelerates. Always introduce two distinct unknowns T_1 and T_2 .

METHOD Solving pulley-with-inertia problems

1. Draw three free-body diagrams: mass m_1 , mass m_2 , and the pulley. Mark the two tensions T_1, T_2 as distinct.
2. Write $F = ma$ for each mass along its direction of motion:

$$m_1 g - T_1 = m_1 a, \quad T_2 - m_2 g = m_2 a \quad (m_1 > m_2).$$

3. Write $C = I\alpha$ for the pulley: the axle reaction passes through the axis so it has no moment; only the tensions contribute:


$$(T_1 - T_2)r = I\alpha.$$

4. Add the no-slip condition linking string and pulley:

$$a = r\alpha.$$

5. Solve the four equations for a , α , T_1 , T_2 . A quick route: substitute T_1 , T_2 from step 2 into step 3 and use step 4 to obtain

$$a = \frac{(m_1 - m_2)g}{m_1 + m_2 + I/r^2}.$$



Atwood machine with a massive pulley of moment of inertia I and radius r . The tensions T_1 and T_2 differ: their difference $(T_1 - T_2)r$ supplies the torque $I\alpha$, and the no-slip condition gives $a = r\alpha$.

WORKED EXAMPLE 7 Atwood machine with a massive pulley

Two masses $m_1 = 4 \text{ kg}$ and $m_2 = 2 \text{ kg}$ hang from a string passing over a pulley of radius $r = 0.2 \text{ m}$ and moment of inertia $I = 0.08 \text{ kg m}^2$. The string does not slip and the axle is frictionless. Take $g = 9.8 \text{ m s}^{-2}$. Find the acceleration of the masses and the two tensions.

SOLUTION

Solution. With m_1 descending, the three equations and the no-slip condition are

$$4g - T_1 = 4a, \quad T_2 - 2g = 2a, \quad (T_1 - T_2)(0.2) = 0.08 \alpha, \quad a = 0.2 \alpha.$$

From the pulley equation, $T_1 - T_2 = \frac{0.08}{0.2} \alpha = 0.4 \alpha$, and since $\alpha = \frac{a}{0.2} = 5a$, we get $T_1 - T_2 = 2a$. Adding the two mass equations: $2g - (T_1 - T_2) = 6a$, so

$$2g - 2a = 6a \implies a = \frac{2g}{8} = \frac{19.6}{8} = 2.45 \text{ m s}^{-2}.$$

Then

$$T_1 = 4(g - a) = 4(9.8 - 2.45) = 29.4 \text{ N}, \quad T_2 = 2(g + a) = 2(9.8 + 2.45) = 24.5 \text{ N}.$$

Check: $T_1 - T_2 = 4.9 \text{ N} = 2a$ ✓, and $\alpha = a/r = 12.25 \text{ rad s}^{-2}$. Note that $T_1 \neq T_2$: the difference of 4.9 N is what accelerates the pulley. Observe also that the denominator of the general formula is $m_1 + m_2 + I/r^2 = 4 + 2 + 2 = 8 \text{ kg}$: the pulley behaves like an extra effective mass $I/r^2 = 2 \text{ kg}$.

3.5 Rigid Body Rotating under Gravity about a Fixed Horizontal Axis

Consider now a rigid body (a rod, a lamina, any pendulum-like object) free to rotate about a fixed horizontal axis, displaced from its equilibrium position and released. Which forces have a moment about the axis? The reaction at the axis passes through it, so its moment is zero. The weight Mg acts at the centre of gravity G ; if G is at distance h from the axis and the line OG makes an angle θ with the downward vertical, the lever arm of the weight is the horizontal distance of G from the axis, namely $h \sin \theta$. Hence

$$C = -Mg h \sin \theta,$$

the minus sign showing that gravity always pulls G back towards the vertical (a restoring moment). The equation of motion is therefore

$$I\ddot{\theta} = -Mgh \sin \theta.$$

For small oscillations this will reduce to simple harmonic motion — that is the subject of the compound pendulum, treated in Section 6. For now, note two things: the equation is exact (no small-angle assumption is needed to write it), and when the body is released from rest in a given position θ_0 , the initial angular acceleration is $\alpha_0 = -Mgh \sin \theta_0 / I$.

EXAMPLE A uniform rod released from the horizontal

A uniform rod AB of length $2l$ and mass M is free to rotate about a horizontal axis through A . It is held horizontal and released. With $I_A = \frac{4}{3}Ml^2$ (standard result from Section 2) and G at distance l from A , the weight has lever arm l in the horizontal position, so

$$\frac{4}{3}Ml^2 \alpha_0 = Mgl \implies \alpha_0 = \frac{3g}{4l}.$$

The tangential acceleration of the free end B at release is $2l \alpha_0 = \frac{3}{2}g$ — greater than g ! This surprising result is a favourite examiner's question: the end of a falling rod initially accelerates faster than a freely falling particle.

DID YOU KNOW? Why flywheels matter

The equation $C = I\alpha$ explains why engineers fit heavy flywheels to engines and presses: a large I means a small α for any disturbing torque, so the rotation speed stays almost constant between power strokes. The same principle steadies the potter's wheel and the traditional grinding stones used in many Cameroonian workshops: once spinning, a massive stone resists any sudden change of speed.

EXERCISE 3 Braking a grindstone

A grindstone of moment of inertia 0.5 kg m^2 runs at 600 rev min^{-1} . A tool is pressed against it, producing a constant resisting couple of 5 N m . Find (a) the angular retardation, (b) the time to stop, (c) the number of revolutions completed while stopping.

SOLUTION Exercise 1

$\omega_0 = 2\pi(600)/60 = 20\pi \text{ rad s}^{-1}$. (a) $\alpha = C/I = -5/0.5 = -10 \text{ rad s}^{-2}$. (b) $t = \omega_0/|\alpha| = 20\pi/10 = 2\pi \approx 6.28 \text{ s}$. (c) $\theta = \omega_0^2/(2|\alpha|) = 400\pi^2/20 = 20\pi^2 \text{ rad}$, so $n = \theta/(2\pi) = 10\pi \approx 31.4$ revolutions.

EXERCISE 4 Massive pulley

In the worked Atwood example above, the pulley is replaced by one of radius 0.1 m and moment of inertia 0.02 kg m^2 , the masses being unchanged. Find the new acceleration and the two tensions.

SOLUTION Exercise 2

$T_1 - T_2 = \frac{I}{r^2}a = \frac{0.02}{0.01}a = 2a$ as before, so $a = \frac{2g}{6+2} = 2.45 \text{ m s}^{-2}$ (the ratio I/r^2 is unchanged), $T_1 = 29.4 \text{ N}$, $T_2 = 24.5 \text{ N}$. The lesson: what matters dynamically is the effective mass I/r^2 of the pulley.

EXERCISE 5 Rod released from rest

A uniform rod of length 1.2 m and mass 3 kg is free to rotate about a horizontal axis through one end. It is released from rest in the horizontal position. Taking $g = 9.8 \text{ m s}^{-2}$, find (a) the

moment of inertia about the axis, (b) the initial angular acceleration, (c) the initial tangential acceleration of the free end.

SOLUTION Exercise 3

Here $2l = 1.2$ m, so $l = 0.6$ m. (a) $I_A = \frac{4}{3}Ml^2 = \frac{4}{3}(3)(0.36) = 1.44 \text{ kg m}^2$. (b) $\alpha_0 = \frac{Mgl}{I_A} = \frac{3 \times 9.8 \times 0.6}{1.44} = 12.25 \text{ rad s}^{-2}$ (equivalently $\alpha_0 = \frac{3g}{4l} = \frac{29.4}{2.4} = 12.25$). (c) $a_B = 2l\alpha_0 = 1.2 \times 12.25 = 14.7 \text{ m s}^{-2} = \frac{3}{2}g$, greater than g as expected.

KEY POINTS Key points of this section

- Moment of a force about a fixed axis: $C = Fd$, with a sign fixed by the chosen positive sense of rotation; forces through the axis have zero moment.
- Equation of motion of a rigid body about a fixed axis: $C = I\alpha$, derived from $F = ma$ particle by particle, internal forces cancelling by Newton's third law.
- Constant torque $\Rightarrow$ constant α : use $\omega = \omega_0 + \alpha t$, $\theta = \omega_0 t + \frac{1}{2}\alpha t^2$, $\omega^2 = \omega_0^2 + 2\alpha\theta$, with angles in radians.
- Braking problems: resisting couple negative; stopping time from $\omega = 0$; revolutions from $n = \theta/(2\pi)$.
- Massive pulley: $T_1 \neq T_2$; solve $F = ma$ for each mass, $C = I\alpha$ for the pulley, and $a = r\alpha$ for the no-slip link; the pulley contributes an effective mass I/r^2 .
- Gravity on a body about a horizontal axis: $C = -Mgh \sin \theta$, where $h \sin \theta$ is the horizontal distance of G from the axis.

This section has given us the dynamical law of rotation. In the next section we shall multiply this law by time to obtain the moment of momentum (angular momentum) and its conservation — the rotational analogue of momentum and impulse — which governs collisions and sudden changes in rotating systems.

4 MOMENT OF MOMENTUM AND ITS CONSERVATION; IMPULSE

In the previous section we established the fundamental equation of rotational motion, $G = I\ddot{\theta}$, which plays for rotation the role that Newton's second law $\vec{F} = m\vec{a}$ plays for translation. In lin-


ear mechanics, rewriting Newton's second law as $\vec{F} = \frac{d}{dt}(m\vec{v})$ leads to the notion of momentum and to two of the most powerful tools of dynamics: the impulse–momentum equation and the conservation of linear momentum. Exactly the same programme can be carried out for rotation. Integrating $G = I\ddot{\theta}$ with respect to time will give us the moment of momentum (also called angular momentum), the impulsive couple equation, and the celebrated law of conservation of moment of momentum. These tools are indispensable whenever forces act for a very short time — collisions, jerks, strings suddenly becoming taut — situations in which the GCE examiner delights.

4.1 Moment of Momentum of a Particle about an Axis

An observation to build intuition.

Imagine a small stone of mass m whirled at the end of a string on a smooth horizontal table. The stone moves fast, and the faster it moves, or the longer the string, the harder it is to stop the whirling motion. The “quantity of rotational motion” clearly depends on three things: the mass m , the speed v , and the distance from the centre. But which distance matters? If you push a door, the effect of your push depends on the perpendicular distance from the line of the push to the hinge — a push aimed straight at the hinge produces no rotation at all, however large the force. The same is true for momentum: only the perpendicular distance from the axis to the line of the velocity counts.

axis through O



A particle of mass m moving with velocity $\vec{v}$; its moment of momentum about the axis through O is $mvr_{\perp}$.

DEFINITION Moment of momentum of a particle about a fixed axis

Let a particle of mass m move with velocity $\vec{v}$ in a plane perpendicular to a fixed axis through O . The **moment of momentum** (or **angular momentum**) of the particle about the axis is

$$L = mvr_{\perp},$$

where $r_{\perp}$ is the perpendicular distance from the axis to the line of action of $\vec{v}$. The sign of L is fixed by a chosen positive sense of rotation. The SI unit of moment of momentum is the

$\text{kg m}^2 \text{s}^{-1}$.

WARNING Perpendicular distance, not position distance

A very common error is to use the distance $|\vec{r}|$ from O to the particle instead of the perpendicular distance from the axis to the line of $\vec{v}$. If the particle moves towards O (radially), its moment of momentum about the axis is zero, whatever its speed. Always drop a perpendicular from O onto the line of the velocity.

4.2 Moment of Momentum of a Rigid Body: $L = I\omega$

Consider now a rigid body rotating with angular velocity ω about a fixed axis. Every particle P_i of the body, of mass m_i at perpendicular distance r_i from the axis, moves in a circle of radius r_i with speed $v_i = r_i\omega$. Since the velocity is tangential, the perpendicular distance from the axis to the line of $\vec{v}_i$ is exactly r_i . Hence the moment of momentum of the particle is

$$L_i = m_i v_i r_i = m_i r_i^2 \omega.$$

The moments of momentum of all the particles have the same sense, so they add:

$$L = \sum_i m_i r_i^2 \omega = \omega \sum_i m_i r_i^2.$$

But $\sum_i m_i r_i^2$ is precisely the moment of inertia I of the body about the axis. We have therefore proved the following fundamental result.

PROPERTY Moment of momentum of a rigid body about a fixed axis

A rigid body of moment of inertia I rotating with angular velocity ω about a fixed axis has moment of momentum about that axis

$$L = I\omega.$$

Unit: $\text{kg m}^2 \text{s}^{-1}$. This is the rotational analogue of the linear momentum $p = mv$. The derivation above (summing $m_i r_i^2 \omega$) is examinable and should be reproducible.

KEY POINTS The translation–rotation dictionary

Quantity	Translation	Rotation
Displacement	s	θ
Velocity	v	ω
Inertia	mass m	moment of inertia I
Momentum	$p = mv$	$L = I\omega$
Force / torque	$F = \frac{dp}{dt}$	$G = \frac{dL}{dt}$
Impulse	$J = \Delta(mv)$	impulsive couple = $\Delta(L\omega)$
Kinetic energy	$\frac{1}{2}mv^2$	$\frac{1}{2}I\omega^2$

Indeed, the torque equation itself can be rewritten in momentum form: since $G = I\ddot{\theta} = \frac{d}{dt}(I\omega)$ when I is constant,

$$G = \frac{dL}{dt},$$

which is the exact rotational analogue of $\vec{F} = \frac{d\vec{p}}{dt}$: the resultant external torque about a fixed axis equals the rate of change of the moment of momentum about that axis.

4.3 Conservation of Moment of Momentum

From $G = \frac{dL}{dt}$ an immediate and enormously useful consequence follows.

PROPERTY Conservation of moment of momentum

If the resultant external torque about a fixed axis is zero during some interval, then the moment of momentum of the system about that axis remains constant:

$$G = 0 \implies L = \text{constant}.$$

For a system whose moment of inertia changes from I_1 to I_2 , this reads

$$I_1\omega_1 = I_2\omega_2.$$

(Proof: $G = \frac{dL}{dt} = 0$ implies L constant. The statement is examinable.)

WARNING Choose the axis once, and state it

Conservation of moment of momentum holds about one chosen fixed axis, and only if the external torques about that same axis vanish. In every examination answer, write explic-

itly: “Taking moments of momentum about the fixed axis through O ...”. Marks are routinely lost by candidates who never state their axis.

DID YOU KNOW? The skater and the diver

Conservation of moment of momentum is the secret of the figure skater’s spin: with arms stretched wide, I is large and ω modest; by pulling the arms in, I decreases sharply, so ω must increase to keep $I\omega$ constant — the spin becomes spectacularly fast. High divers use the same trick, tucking into a ball to multiply their rotation rate before straightening for entry into the water. No external torque about the vertical axis is needed: the rotation speeds up “for free”.

WORKED EXAMPLE 8 A point mass dropped onto a rotating turntable

A horizontal disc of mass $M = 2$ kg and radius $a = 0.4$ m rotates freely about a fixed vertical axis through its centre at $\omega_1 = 6$ rad s⁻¹. A small lump of clay of mass $m = 0.5$ kg is dropped vertically onto the disc at a distance $r = 0.3$ m from the axis and sticks to it. Find the new angular velocity.

SOLUTION


Solution. The clay falls vertically, so it has no moment of momentum about the vertical axis before sticking. The forces during the impact are internal to the system (disc + clay) or act along the axis; hence the external torque about the axis is zero and moment of momentum is conserved.

$$I_{\text{disc}} = \frac{1}{2}Ma^2 = \frac{1}{2}(2)(0.4)^2 = 0.16 \text{ kg m}^2, \quad I_{\text{clay}} = mr^2 = (0.5)(0.3)^2 = 0.045 \text{ kg m}^2.$$

Conservation about the axis: $I_1\omega_1 = I_2\omega_2$:

$$0.16 \times 6 = (0.16 + 0.045)\omega_2 \quad \Rightarrow \quad \omega_2 = \frac{0.96}{0.205} \approx 4.68 \text{ rad s}^{-1}.$$

Note that the kinetic energy falls from $\frac{1}{2}(0.16)(36) = 2.88$ J to $\frac{1}{2}(0.205)(4.68)^2 \approx 2.25$ J: energy is lost in the inelastic “sticking”, exactly as in a linear collision.



A lump of clay dropped onto a freely rotating disc: the moment of inertia increases, so the angular velocity decreases, with $l\omega$ constant.

4.4 Impulsive Couples and the Angular Impulse–Momentum Equation

In linear mechanics, when a very large force acts for a very short time, we bypass the details of the force and work with the impulse $J = \int F dt = \Delta(mv)$. The same device works for rotation.

Integrating $G = \frac{dL}{dt}$ over the short duration of the blow:

$$\int G dt = \Delta(l\omega) = l\omega_2 - l\omega_1.$$

DEFINITION Impulsive couple

The **impulsive couple** (or **angular impulse**) of a torque about a fixed axis is $\int G dt$. If an impulsive force of impulse J acts at perpendicular distance d from the axis, its impulsive couple about the axis is Jd . The impulsive couple equals the change of moment of momentum:

$$\text{impulsive couple} = \Delta(l\omega).$$

Unit: $\text{kg m}^2 \text{s}^{-1}$ (equivalently N m s).

METHOD Solving impulsive rotation problems

1. Choose and state the fixed axis about which moments of momentum and impulsive couples will be taken.
2. Draw the impulsive forces: impulsive tensions in strings, impulsive reactions at hinges or axles, impulsive contact forces. Ignore all finite forces (weights, ordinary tensions) during the infinitesimal impact.
3. Apply to each rotating body: (impulsive couple about the axis) = $\Delta(l\omega)$.
4. Apply to each translating particle: (impulse) = $\Delta(mv)$ along the direction of motion.
5. Add the kinematic constraints: inextensible string $\Rightarrow$ equal speeds; string on a pulley rim $\Rightarrow v = a\omega$; no slipping.


6. Solve the simultaneous equations for the unknown impulses and velocities.

WARNING Kinetic energy is NOT conserved in impacts

In any problem involving an impulsive blow, a collision, or a string suddenly becoming taut, kinetic energy is almost always lost (converted to heat, sound, deformation). Never write $\frac{1}{2}I\omega_1^2 = \frac{1}{2}I\omega_2^2$ across an impact. The correct conserved quantities are linear momentum (when no external impulse acts) and moment of momentum (when no external impulsive couple acts about the chosen axis). Energy methods may be used before and after the impact, but not across it. Always check: is there an impact? If yes, momentum methods, not energy.

4.5 Connected Particles and Impulsive Tensions

A classic GCE situation: two particles hang from a string passing over a pulley with inertia; the system is held at rest with the string slack, or one particle is given a jerk, and the string suddenly becomes taut. During the jerk, impulsive tensions appear in the two portions of the string (they differ, because the pulley has inertia and needs a net impulsive couple to be set spinning), and an impulsive reaction appears at the axle. We treat each element separately.



String over a pulley with moment of inertia I : when the string suddenly becomes taut, impulsive tensions J_1, J_2 act on the two portions and an impulsive reaction R acts at the axle.

WORKED EXAMPLE 9 Particles connected over a pulley with inertia

A light inextensible string passes over a pulley of radius $a = 0.2 \text{ m}$ and moment of inertia $I = 0.04 \text{ kg m}^2$, free to turn about a fixed horizontal axis through its centre O . Particles of masses $m_1 = 2 \text{ kg}$ and $m_2 = 1 \text{ kg}$ hang from the ends. The system is held with the string just slack and m_1 is projected downwards with speed $V = 3 \text{ m s}^{-1}$; the string suddenly be-

comes taut. Find the common speed u just after the jerk, the impulsive tensions, and the impulsive reaction at the axle.

SOLUTION

Solution. Let J_1, J_2 be the impulsive tensions on the m_1 and m_2 sides (upward impulses on the particles), and $\omega = u/a$ the angular speed of the pulley just after the jerk.

Particle m_1 (moving down, impulse up): taking downward positive,

$$-J_1 = m_1(u - V) = 2(u - 3). \quad (1)$$

Particle m_2 (moving up, impulse up): taking upward positive,

$$J_2 = m_2(u - 0) = u. \quad (2)$$

Pulley (impulsive couple = $\Delta(l\omega)$ about O): the tensions act at the rim, distance a :

$$(J_1 - J_2)a = l\omega = \frac{lu}{a} \implies J_1 - J_2 = \frac{lu}{a^2} = \frac{0.04}{0.04}u = u. \quad (3)$$

Substituting (1) and (2) into (3):

$$2(3 - u) - u = u \implies 6 = 4u \implies u = 1.5 \text{ m s}^{-1}.$$

Then $J_2 = 1.5 \text{ N s}$ and $J_1 = 2(3 - 1.5) = 3 \text{ N s}$.

Impulsive reaction at the axle. The pulley itself acquires no linear momentum, so the upward impulsive reaction R balances the two downward impulsive tensions on the rim:

$$R = J_1 + J_2 = 4.5 \text{ N s}.$$

Check (momentum view). Taking moments of momentum about O for the whole system kills R (it acts at O): $m_1 Va = (m_1 + m_2)ua + l\omega$, i.e. $2(3)(0.2) = 3(1.5)(0.2) + 0.04(7.5)$, giving $1.2 = 0.9 + 0.3$. ✓ Note also that kinetic energy is lost in the jerk: before, $\frac{1}{2}(2)(9) = 9 \text{ J}$; after, $\frac{1}{2}(3)(1.5)^2 + \frac{1}{2}(0.04)(7.5)^2 = 3.375 + 1.125 = 4.5 \text{ J}$.

METHOD**Quick route: conservation of moment of momentum about the axle**

When a system is set in motion by a jerk and the only external impulsive forces act at the axle (the impulsive reaction) or parallel to it, take moments of momentum about the axle O for the whole system: the unknown reaction disappears, and

$$\sum mvr_{\perp} + l\omega \quad \text{is conserved across the jerk.}$$

This gives the common speed in one line; the individual impulsive tensions are then recovered from $\Delta(mv)$ on each particle.

4.6 Linear Momentum, Angular Momentum, Energy: Which Survives the Impact?

A recurring examination trap is to reach for the wrong conservation law. The table below summarises what each law requires and when it applies.

Law	Condition	Use across an impact?
Linear momentum mv	No external impulse on the system	Yes, if external impulses vanish (watch the axle reaction!)
Moment of momentum $I\omega$	No external impulsive couple about the chosen axis	Yes — the standard tool for jerks and collisions
Kinetic energy	No inelastic deformation, no impulsive constraints	No — energy is generally lost; use only before/after

WARNING The axle reaction destroys linear momentum

When a body is pivoted at a fixed axis, the impulsive reaction at the axle is an external impulse on the system, so linear momentum of the system is generally not conserved — but its moment of momentum about the axle is, because the reaction has zero moment about O . This is precisely why moment of momentum, and not linear momentum, is the right tool for pivoted bodies.

EXERCISE 6 Sliding bead on a rotating rod

A smooth uniform rod AB of mass $3m$ and length $2a$ rotates freely in a horizontal plane about a fixed vertical axis through its centre O with angular velocity Ω . A bead of mass $2m$ is initially held at O on the rod, then released and slides outwards. Show that when the bead reaches the end A , the angular velocity is $\frac{\Omega}{3}$, and explain why the kinetic energy has changed.

SOLUTION Exercise 1

The moment of inertia of a uniform rod of mass M and length $2a$ about a perpendicular axis through its centre is $\frac{1}{3}Ma^2$; with $M = 3m$ this gives $I_{\text{rod}} = \frac{1}{3}(3m)a^2 = ma^2$.

Conservation of moment of momentum. The rod is smooth, so the forces between bead and rod are internal to the system; the weights are vertical and have zero moment about the vertical axis; the reaction at the axle acts at O . Hence the external torque about the vertical axis is zero and moment of momentum is conserved. Initially the bead is at O , contributing nothing:

$$I_1\omega_1 = (ma^2 + 2m(0)^2)\Omega = ma^2\Omega.$$

When the bead reaches A, at distance a from the axis,

$$I_2 = ma^2 + 2m a^2 = 3ma^2.$$

Therefore

$$ma^2\Omega = 3ma^2\omega_2 \implies \omega_2 = \frac{\Omega}{3},$$

as required.

Energy. The kinetic energy changes from

$$T_1 = \frac{1}{2}ma^2\Omega^2 \quad \text{to} \quad T_2 = \frac{1}{2}(3ma^2)\left(\frac{\Omega}{3}\right)^2 = \frac{1}{6}ma^2\Omega^2.$$

Two-thirds of the kinetic energy is dissipated through the internal constraint forces as the bead is dragged into circular motion at A (the bead does work against these forces while sliding outwards). Moment of momentum is conserved because no external torque acts; kinetic energy is not, because the internal forces do net work during the radial sliding.

EXERCISE 7 A jerked string over a rough-rimmed pulley

A light inextensible string passes over a pulley of radius 0.1 m and moment of inertia 0.02 kg m^2 mounted on a fixed horizontal axis. A particle A of mass 3 kg hangs at one end; a particle B of mass 1 kg hangs at the other. With the string slack, B is projected upwards with speed 4 m s^{-1} and the string suddenly becomes taut. Find the common speed just after the jerk and the impulsive tensions in the two portions of the string.

SOLUTION Exercise 2

Let u be the common speed just after the jerk (B moving up, A moving down), $\omega = u/a = 10u$ the angular speed of the pulley, and J_A, J_B the impulsive tensions on the two sides.

Particle B (upward positive): $J_B = 1(u - 4) = u - 4$... with sign care: the impulse is upward, the velocity changes from $+4$ to $+u$, so $J_B = u - 4$, which will come out negative if $u < 4$ — the magnitude is $4 - u$. Write instead, taking the impulse as J_B upward:

$$J_B = 1 \cdot (u - 4). \quad (1)$$

Particle A (downward positive, impulse upward): $-J_A = 3(u - 0)$, i.e.

$$J_A = -3u \quad (\text{impulse downward-positive}), \quad (2)$$

so the upward impulsive tension on A has magnitude $3u$.

Pulley about the axle: the tension on B's side drives the pulley one way, that on A's side the other:

$$((4 - u) - 3u)(0.1) = I\omega = 0.02 \times 10u \implies 0.1(4 - 4u) = 0.2u,$$

$$0.4 - 0.4u = 0.2u \implies u = \frac{2}{3} \text{ m s}^{-1}.$$

Hence the impulsive tensions have magnitudes $J_B = 4 - \frac{2}{3} = \frac{10}{3}$ N s on B's side and $J_A = 3u = 2$ N s on A's side. Check by moment of momentum about the axle for the whole system: before, $1 \times 4 \times 0.1 = 0.4$; after, $(3 + 1) \times \frac{2}{3} \times 0.1 + 0.02 \times \frac{20}{3} = 0.2667 + 0.1333 = 0.4$. ✓

KEY POINTS Key points of the section

- Moment of momentum of a particle about an axis: $mvr_{\perp}$, with $r_{\perp}$ the perpendicular distance to the line of $\vec{v}$.
- Rigid body about a fixed axis: $L = I\omega$, and $G = \frac{dL}{dt}$.
- Zero external torque about the axis $\Rightarrow I\omega$ constant: $I_1\omega_1 = I_2\omega_2$.
- Impulsive couple = $\Delta(I\omega)$; impulse = $\Delta(mv)$ for each particle; constraints $v = a\omega$ link them.
- In every impact or jerk, kinetic energy is generally lost — use momentum methods across the impact, energy methods only before and after.
- Always state the axis about which moments of momentum are taken.

5 ENERGY OF A ROTATING BODY AND THE FORCE ON THE AXIS

In the previous section we saw that the **moment of momentum** of a rigid body about a fixed axis, $L = I\omega$, plays exactly the role that linear momentum plays for a particle: it is changed by impulses and conserved when no external couple acts. We now complete the parallel by introducing the rotational analogue of kinetic energy. Energy methods are extraordinarily powerful in this chapter: they give us the angular speed of a swinging body without solving the equation of motion, and — combined with the motion of the centre of mass — they allow us to compute the force that the body exerts on its axis of rotation, a question of obvious practical importance (think of the axle of a grinding wheel in a Douala workshop, or the pivot of a swing in a school playground).

5.1 Kinetic Energy of a Body Rotating about a Fixed Axis

Intuition. When a rigid body spins about a fixed axis, every particle of the body is moving, so every particle carries kinetic energy. Particles far from the axis move faster than particles near it. The total kinetic energy must therefore depend on how the mass is distributed relative to the axis — precisely what the moment of inertia measures.

Consider a rigid body rotating with angular speed ω about a fixed axis. A particle of the body, of mass m_i , at perpendicular distance r_i from the axis, describes a circle of radius r_i with speed $v_i = r_i\omega$. Its kinetic energy is

$$\frac{1}{2}m_iv_i^2 = \frac{1}{2}m_ir_i^2\omega^2.$$

Summing over all particles of the body:

$$E_k = \sum_i \frac{1}{2}m_ir_i^2\omega^2 = \frac{1}{2}\omega^2 \sum_i m_ir_i^2 = \frac{1}{2}I\omega^2,$$

since $\sum_i m_ir_i^2 = I$ is the moment of inertia about the axis.

PROPERTY Kinetic energy of rotation

A rigid body of moment of inertia I rotating with angular speed ω about a fixed axis has kinetic energy

$$E_k = \frac{1}{2}I\omega^2$$

This is the rotational analogue of $\frac{1}{2}mv^2$, with I replacing m and ω replacing v . The derivation above is examinable.

EXAMPLE Kinetic energy of a flywheel

A flywheel of moment of inertia $I = 0.4 \text{ kg m}^2$ rotates at 300 revolutions per minute. Its angular speed is $\omega = \frac{300 \times 2\pi}{60} = 10\pi \text{ rad s}^{-1}$, so

$$E_k = \frac{1}{2}(0.4)(10\pi)^2 = 20\pi^2 \approx 197.4 \text{ J}.$$

5.2 Work Done by a Couple and the Work–Energy Principle

Intuition. A couple of moment C turning a body through an angle does work, just as a force moving a particle through a distance does work. Angle replaces distance.

Let a couple of constant moment C act on a body free to rotate about a fixed axis. The couple consists of two equal and opposite forces; when the body turns through a small angle $\delta\theta$, the points of application move along their circles and the total work done by the two forces is $C \delta\theta$ (the forces perpendicular to the motion do no work). Hence, for a rotation through a finite angle θ :

PROPERTY Work of a couple; work–energy theorem for rotation

The work done by a couple of constant moment C turning a body through an angle θ (in radians) is

$$W = C\theta$$

and the work–energy principle for rotation about a fixed axis states:

$$\text{work done by all couples} = \Delta E_k = \frac{1}{2}I\omega_2^2 - \frac{1}{2}I\omega_1^2.$$

WARNING Angles in radians

The formula $W = C\theta$ requires θ in radians. A couple of moment 5 N m turning a shaft through one complete revolution does work $W = 5 \times 2\pi = 10\pi \approx 31.4$ J, not 5×360 joules!

5.3 Conservation of Mechanical Energy for a Body Swinging about a Fixed Horizontal Axis


Consider a rigid body free to rotate about a fixed horizontal axis through O , with centre of mass G at distance a from O . The forces on the body are its weight Mg (acting at G) and the reaction at the axis. The reaction acts at the axis, which does not move, so it does **no work**. Weight is conservative. Therefore mechanical energy is conserved:

$$\frac{1}{2}I\omega^2 + Mgh = \text{constant},$$

where h is the **height of G** above a fixed reference level.

WARNING The height is the height of G

In the potential energy Mgh , h is the height of the **centre of mass G** — not the height of the top of the body, nor of its lowest point. For a uniform rod of length $2a$ pivoted at one end, G is the midpoint, at distance a from the pivot. Using the wrong point is the most common error in this topic.



A rod pivoted at O swings from a raised position to the lowest position. The loss of potential energy is $Mg \times (\text{drop of } G)$, converted into $\frac{1}{2}I\omega^2$.

METHOD The two-step strategy: energy, then centre-of-mass motion


To analyse a body swinging about a fixed horizontal axis:

1. Energy gives the speed: apply $\frac{1}{2}I\omega^2 + Mgh = \text{constant}$ between the release position and the position of interest to find $\omega(\theta)$.
2. Angular acceleration: use $C = I\alpha$ at the position of interest, or differentiate the energy equation with respect to time.
3. Reaction at the axis: write $M\vec{a}_G = \vec{R} + M\vec{g}$ and resolve along and perpendicular to OG , using the radial and transverse accelerations of G .

5.4 Motion of the Centre of Mass; Acceleration Components of G

Since the body is rigid and the axis fixed, G moves on a **circle** of radius $a = OG$ centred at O . If θ is the angle that OG makes with the downward vertical, then the acceleration of G has the two standard components of circular motion:

- a **radial component** (along GO , towards O): $a\omega^2 = a\dot{\theta}^2$;
- a **transverse component** (perpendicular to OG , in the direction of increasing θ): $a\alpha = a\ddot{\theta}$.



G moves on a circle about O . Its acceleration has a radial component $a\omega^2$ (towards O) and a transverse component $a\alpha$ (perpendicular to OG).

5.5 The Force Exerted on the Axis

The pivot exerts a reaction $\vec{R}$ on the body. The centre-of-mass theorem (Newton's second law applied to the whole body) gives

$$M\vec{a}_G = \vec{R} + M\vec{g}.$$

We resolve this vector equation **along** GO (radially, towards O) and **perpendicular to** OG (transversally). With θ measured from the downward vertical, the weight has radial component $-Mg \cos \theta$ (i.e. $Mg \cos \theta$ directed away from O when G is below O) and transverse component $-Mg \sin \theta$. Writing R_r and R_t for the components of $\vec{R}$ along GO (towards O) and transversally (in the direction of increasing θ):

$$R_r - Mg \cos \theta = Ma\omega^2, \quad R_t - Mg \sin \theta = Ma\alpha.$$

Hence

$$R_r = Mg \cos \theta + Ma\omega^2, \quad R_t = Mg \sin \theta + Ma\alpha.$$

WARNING The reaction is not vertical

The reaction at the axis has two components, radial and transverse. Do not assume $\vec{R}$ is vertical, and do not assume it balances the weight: the pivot must also supply the centripetal force $Ma\omega^2$ that keeps G on its circle. At the lowest point of a fast swing, the reaction can be several times the weight.

5.6 Complete Worked Problem: Rod Released from the Horizontal

WORKED EXAMPLE 10 Rod falling from the horizontal position

A uniform rod AB of length $2a$ and mass M is freely pivoted at its end A about a fixed hor-

horizontal axis. It is released from rest in the horizontal position. Find (a) its angular speed when it first reaches the vertical position; (b) the magnitude and direction of the reaction at the pivot in that position. [Take $I_A = \frac{4}{3}Ma^2$.]

SOLUTION

(a) Angular speed by energy conservation. G is the midpoint, with $AG = a$. Between the horizontal and the vertical positions, G falls through a height a . Energy conservation:

$$0 + Mga = \frac{1}{2}I_A\omega^2 + 0 \implies Mga = \frac{1}{2} \cdot \frac{4}{3}Ma^2\omega^2 = \frac{2}{3}Ma^2\omega^2,$$

$$\omega^2 = \frac{3g}{2a}.$$

Angular acceleration at the vertical position. When the rod hangs vertically, the weight acts along the line AG , so its moment about A is zero: $C = I_A\alpha = 0$, hence $\alpha = 0$ at that instant.

(b) Reaction at the pivot. At the vertical position ($\theta = 0$), resolve $M\vec{a}_G = \vec{R} + M\vec{g}$.


Transverse direction: $R_t - 0 = Ma\alpha = 0$, so $R_t = 0$: the reaction is purely vertical here.

Radial direction (upwards, towards A):

$$R_r - Mg = Ma\omega^2 = Ma \cdot \frac{3g}{2a} = \frac{3}{2}Mg \implies R_r = Mg + \frac{3}{2}Mg = \frac{5}{2}Mg.$$

$$R = \frac{5}{2}Mg, \text{ directed vertically upwards.}$$

The pivot therefore supports two and a half times the weight of the rod at the bottom of the swing — the weight Mg plus the centripetal force $\frac{3}{2}Mg$.



Radial component of the reaction at the axis for the rod released from the horizontal, as a function of the angle θ from the downward vertical. Energy gives $\frac{1}{2}Mv^2 = \frac{3}{2}Mg \cos \theta$, so $R_r/Mg = \frac{5}{2} \cos \theta$, rising from 0 at release (the rod is momentarily at rest, and the weight has no radial component) to $\frac{5}{2}$ at the lowest point.

DID YOU KNOW? Why engineers care about the force on the axis

The factor $\frac{5}{2}$ above is not a curiosity: any rotating machine — a ceiling fan, a water pump, the turbines of the Song Loulou hydroelectric dam on the Sanaga river — exerts on its bearings forces that exceed the static weight whenever it moves. Bearings and axles must be designed for these dynamic loads, computed exactly as in this section: energy for the speed, centre-of-mass motion for the reaction.

EXERCISE 8 Swinging rod released at 60°

A uniform rod of mass M and length $2a$ is freely pivoted at one end about a fixed horizontal axis. It is released from rest with the rod making an angle of 60° with the downward vertical (below the pivot). Find (a) the angular speed when the rod passes through the vertical; (b) the reaction at the pivot at that instant.

SOLUTION Exercise 1

(a) G is at distance a from the pivot. Between the release position ($\theta = 60^\circ$) and the vertical ($\theta = 0$), G drops through a height

$$a \cos 0^\circ - a \cos 60^\circ = a \left(1 - \frac{1}{2}\right) = \frac{a}{2}.$$

Energy conservation:

$$Mg \cdot \frac{a}{2} = \frac{1}{2} \cdot \frac{4}{3} Ma^2 \omega^2 \implies \omega^2 = \frac{3g}{4a}.$$

(b) At the vertical position the moment of the weight about the pivot is zero, so $\alpha = 0$ and the transverse equation gives $R_t = 0$. Radially (upwards, towards the pivot):

$$R - Mg = Ma\omega^2 = Ma \cdot \frac{3g}{4a} = \frac{3}{4}Mg \implies R = \frac{7}{4}Mg, \text{ vertically upwards.}$$

KEY POINTS Key points of this section

- Kinetic energy of rotation about a fixed axis: $E_k = \frac{1}{2}I\omega^2$; work of a couple: $W = C\theta$ (θ in radians).
- For a body swinging about a fixed horizontal axis, $\frac{1}{2}I\omega^2 + Mgh = \text{constant}$, with h the height of G .
- G moves on a circle: radial acceleration $a\omega^2$ towards O , transverse acceleration $a\alpha$.
- The reaction at the axis comes from $M\vec{a}_G = \vec{R} + M\vec{g}$ resolved radially and transversally: it has two components and generally exceeds the weight.
- Strategy: energy $\rightarrow \omega$; $C = I\alpha \rightarrow \alpha$; centre-of-mass equation $\rightarrow \vec{R}$.

6 THE COMPOUND PENDULUM AND SYNTHESIS

In the previous section we studied the energy of a rotating body and the force exerted on its axis. We saw that a rigid body pivoted at a fixed point can swing under gravity, and that energy methods tell us its speed at any position. We now close this circle: when a rigid body pivoted about a fixed horizontal axis is displaced slightly from its equilibrium position and released, it oscillates. Such a body is called a **compound pendulum**, and it is the most important application of everything in this chapter: the equation of motion $I_O \ddot{\theta} = C$, the parallel axes theorem, energy conservation, and even impulse all appear in its study. It is also a classic GCE practical topic, because it provides one of the most accurate school-laboratory methods for measuring g .

6.1 Definition and Setting Up the Equation of Motion

DEFINITION Compound pendulum

A **compound pendulum** (or physical pendulum) is a rigid body of mass M , free to rotate


about a fixed horizontal axis through a point O , oscillating under gravity alone. Let G be the centre of mass of the body and $h = OG$ the distance from the axis to G .

A simple pendulum (a point mass on a light string) is an idealisation; every real pendulum — a swinging metre rule in the laboratory, a bell, a swinging door, the leg of a walking person — is a compound pendulum, because its mass is distributed.

Consider the body displaced through an angle θ from the vertical equilibrium position. Two forces act on it: the weight Mg acting vertically downwards at G , and the reaction $\vec{R}$ of the axis at O . The reaction has zero moment about O (it acts at the axis), so the only torque about O is that of the weight. The line of action of Mg passes at a perpendicular distance $h \sin \theta$ from O , and it acts so as to restore the body towards equilibrium. Hence the equation of motion $I_O \ddot{\theta} = C_O$ becomes

$$I_O \ddot{\theta} = -Mgh \sin \theta,$$

where I_O is the moment of inertia of the body about the axis through O .



A compound pendulum: rigid body pivoted at O , centre of mass G with $OG = h$, displaced by θ . The weight Mg provides the restoring torque $-Mgh \sin \theta$; the reaction $\vec{R}$ at the axis has no moment about O .

6.2 Small Oscillations: Simple Harmonic Motion

The equation $I_O \ddot{\theta} = -Mgh \sin \theta$ is not simple harmonic in general, because of the $\sin \theta$. But for small oscillations we may linearise it.

WARNING The small-angle approximation

The approximation $\sin \theta \approx \theta$ is valid only when θ is measured in radians and is small (in practice $|\theta| \lesssim 10^\circ$, i.e. 0.17 rad, gives an error below 0.5%). You must state this approximation explicitly in every derivation — examiners award a mark for it. Never write $\sin \theta \approx \theta$ with θ in degrees.

For small oscillations, $\sin \theta \approx \theta$, so

$$I_O \ddot{\theta} = -Mgh\theta \quad \Longleftrightarrow \quad \ddot{\theta} = -\frac{Mgh}{I_O} \theta.$$

This is the SHM equation $\ddot{\theta} = -\omega^2 \theta$ with $\omega^2 = \frac{Mgh}{I_O}$.

PROPERTY Period of a compound pendulum

A compound pendulum performing small oscillations about a fixed horizontal axis through O executes simple harmonic motion with period

$$T = 2\pi \sqrt{\frac{I_O}{Mgh}},$$

where I_O is the moment of inertia about the axis, M the mass, and $h = OG$. (The derivation above — restoring torque, small-angle approximation, identification with SHM — is examinable.)

DEFINITION Length of the equivalent simple pendulum

The **length of the equivalent simple pendulum** is the length l of a simple pendulum having the same period as the compound pendulum:

$$2\pi \sqrt{\frac{l}{g}} = 2\pi \sqrt{\frac{I_O}{Mgh}} \quad \Rightarrow \quad \boxed{l = \frac{I_O}{Mh} = \frac{k_O^2}{h}}$$

where k_O is the radius of gyration about the axis through O (since $I_O = Mk_O^2$).

Using the parallel axes theorem, $k_O^2 = k_G^2 + h^2$, where k_G is the radius of gyration about the parallel axis through G . Hence

$$l = \frac{k_G^2 + h^2}{h} = h + \frac{k_G^2}{h}.$$

DID YOU KNOW? Centres of suspension and oscillation (enrichment)

Mark the point O' on the line OG produced, at distance l from O . Then $OO' = l = h + k_G^2/h$, so $GO' = k_G^2/h$. A beautiful result (Kater's theorem) states that if the pendulum is inverted and suspended from O' , its period is unchanged: the centres of suspension and oscillation are interchangeable. This is the principle of Kater's reversible pendulum, historically the most accurate instrument for measuring g . You will not be asked to prove it, but recognising it can earn credit in structured questions.

6.3 Worked Method and Examples

METHOD Solving compound pendulum problems

1. Locate G and compute $h = OG$.
2. Compute I_O : use the standard result about G (or about an end) and the parallel axes theorem $I_O = I_G + Mh^2$ if necessary.
3. Apply the period formula $T = 2\pi\sqrt{I_O/(Mgh)}$, or the equivalent length $l = I_O/(Mh)$.
4. For experimental questions, rearrange to make g the subject: $g = \frac{4\pi^2 I_O}{MhT^2}$.
5. Check units and state the small-angle assumption where required.

EXAMPLE Uniform rod swinging about one end

A uniform rod AB of length $2a$ and mass M is pivoted at A and makes small oscillations in a vertical plane. Find the period and the length of the equivalent simple pendulum.

Solution. Here $h = AG = a$ and $I_A = \frac{4}{3}Ma^2$ (standard result). Hence

$$T = 2\pi\sqrt{\frac{\frac{4}{3}Ma^2}{Mga}} = 2\pi\sqrt{\frac{4a}{3g}}, \quad l = \frac{I_A}{Ma} = \frac{4a}{3}.$$

The rod of length $2a$ swings like a simple pendulum of length $\frac{4a}{3}$ — shorter than the rod, so the rod swings faster than a simple pendulum of its own length.

WORKED EXAMPLE 11 Bar pendulum used to find g

A uniform metre rule of mass M is pivoted about a horizontal axis through a hole drilled 10 cm from one end. It performs small oscillations with a measured period $T = 1.53$ s. Taking $g = 9.81 \text{ m s}^{-2}$ first verify the theory, then show how the experiment yields g .

SOLUTION

Solution. The rule has length $L = 1.00$ m, so G is at its midpoint and

$$h = OG = 0.50 - 0.10 = 0.40 \text{ m}.$$

About its centre, $I_G = \frac{1}{12}ML^2$; by the parallel axes theorem,

$$I_O = M\left(\frac{L^2}{12} + h^2\right) = M\left(\frac{1}{12} + 0.16\right) = 0.2433 M \text{ m}^2.$$

The predicted period is

$$T = 2\pi\sqrt{\frac{I_O}{Mgh}} = 2\pi\sqrt{\frac{0.2433}{9.81 \times 0.40}} = 2\pi\sqrt{0.0620} \approx 1.56 \text{ s},$$

in good agreement with the measured 1.53 s (the small difference comes from timing and pivot friction). Conversely, from the measurement,

$$g = \frac{4\pi^2 I_O}{MhT^2} = \frac{4\pi^2 \times 0.2433}{0.40 \times 1.53^2} \approx 10.3 \text{ m s}^{-2},$$

which is the experimental estimate of g (a more careful timing over 50 oscillations reduces the error). Note that M cancels: the mass of the pendulum is irrelevant, which is why the bar pendulum is such a clean experiment.

6.4 The Bar Pendulum: Period as a Function of h

A bar pendulum is a rectangular bar with a row of holes; it can be suspended from any hole, at distance h from G . Since $l = h + \frac{k_G^2}{h}$, the period is

$$T = 2\pi\sqrt{\frac{h^2 + k_G^2}{gh}}.$$


As $h \rightarrow 0$ (pivot near G), $T \rightarrow \infty$ — the body barely oscillates because the restoring torque vanishes. As $h \rightarrow \infty$, $T \rightarrow \infty$ as well. Between the two, T has a **minimum**. Differentiating $T^2 = \frac{4\pi^2}{g} \left(h + \frac{k_G^2}{h} \right)$ with respect to h :

$$\frac{d(T^2)}{dh} = \frac{4\pi^2}{g} \left(1 - \frac{k_G^2}{h^2} \right) = 0 \quad \Rightarrow \quad h = k_G.$$


PROPERTY Minimum period (GCE-useful enrichment)

The period of a compound pendulum is minimum when the axis is at distance $h = k_G$ from the centre of mass, and the minimum period is

$$T_{\min} = 2\pi\sqrt{\frac{2k_G}{g}}.$$



Bar pendulum with several suspension holes, and the equivalent simple pendulum of length $l = k_O^2/h$ having the same period.



Period T against suspension distance h for a metre rule ($k_G = L/\sqrt{12} \approx 0.289$ m). The minimum occurs at $h = k_G$. For a given $T > T_{\min}$ there are two values h_1 and h_2 ; their sum $h_1 + h_2$ equals the equivalent length l .

EXPERIMENT Finding g with a bar pendulum

Suspend the bar from each hole in turn, on each side of G , and time 50 small oscillations to find T for each h . Plot T against h (distance from G): the curve is symmetric about G . For a chosen $T > T_{\min}$, the horizontal line cuts the curve at two points h_1 and h_2 on the same side of G (or four points if both sides are plotted). The equivalent length is $l = h_1 + h_2$, and $g = \frac{4\pi^2 l}{T^2}$. This graphical method averages out errors in locating G and measuring h — a favourite GCE practical question.

6.5 Synthesis Problems: The Whole Chapter at Work

GCE questions on rotational dynamics frequently combine several lessons in one problem. The

following worked exercise is typical of the hardest questions on the paper.

WORKED EXAMPLE 12 Rod falling, hitting a stop, then oscillating

A uniform rod AB of length $2a = 1.2$ m and mass $M = 2$ kg is smoothly pivoted at A . It is held horizontal and released from rest. (a) Find its angular velocity when it first reaches the vertical. (b) As it passes the vertical, a small lump of plasticine of mass $m = 0.5$ kg sticks to the rod at B . Find the new angular velocity immediately after the impact. (c) Find the period of small oscillations of the loaded rod about A . Take $g = 9.81$ m s⁻².

SOLUTION

(a) Energy. Falling from horizontal to vertical, G drops by $a = 0.6$ m. With $I_A = \frac{4}{3}Ma^2 = \frac{4}{3}(2)(0.36) = 0.96$ kg m²:

$$Mga = \frac{1}{2}I_A\omega^2 \implies \omega^2 = \frac{2 \times 2 \times 9.81 \times 0.6}{0.96} = 24.525, \quad \omega \approx 4.95 \text{ rad s}^{-1}.$$

(b) Conservation of moment of momentum about A (the impulse at the pivot has no moment about A). Just before impact, $L = I_A\omega = 0.96 \times 4.95 = 4.754$ kg m² s⁻¹. After impact the inertia is

$$I'_A = 0.96 + m(2a)^2 = 0.96 + 0.5 \times 1.44 = 1.68 \text{ kg m}^2,$$

so $\omega' = \frac{4.754}{1.68} \approx 2.83$ rad s⁻¹. (Kinetic energy is not conserved in the impact — check: $\frac{1}{2}I_A\omega^2 = 11.77$ J before, $\frac{1}{2}I'_A\omega'^2 = 6.73$ J after.) (c) Period. The new centre of mass is at distance h from A with

$$h = \frac{Ma + m(2a)}{M + m} = \frac{2(0.6) + 0.5(1.2)}{2.5} = 0.72 \text{ m}.$$

Then

$$T = 2\pi\sqrt{\frac{I'_A}{(M + m)gh}} = 2\pi\sqrt{\frac{1.68}{2.5 \times 9.81 \times 0.72}} \approx 1.94 \text{ s}.$$

This single problem used energy (Section 5), moment of momentum and impulse (Section 4), the parallel axes theorem (Sections 1–2) and the compound pendulum (this section).

EXERCISE 9 Compound pendulum synthesis

A uniform circular disc of mass 1.5 kg and radius 0.2 m is pivoted about a horizontal axis perpendicular to its plane through a point O on its rim.

1. Show that $I_O = 0.09$ kg m².
2. Find the period of small oscillations in the plane of the disc.
3. Find the length of the equivalent simple pendulum.
4. The disc is released from rest with G level with O . Find the angular velocity when G is

directly below O , and the reaction at the axis at that instant.

SOLUTION Exercise 1

1. $I_G = \frac{1}{2}Mr^2 = 0.03 \text{ kg m}^2$; parallel axes: $I_O = I_G + Mr^2 = 0.03 + 1.5(0.04) = 0.09 \text{ kg m}^2$. 2. $h = r = 0.2 \text{ m}$: $T = 2\pi\sqrt{I_O/(1.5 \times 9.81 \times 0.2)} = 2\pi\sqrt{0.03058} \approx 1.10 \text{ s}$. 3. $l = I_O/(Mh) = 0.09/0.3 = 0.30 \text{ m}$. 4. G drops 0.2 m : $\frac{1}{2}I_O\omega^2 = Mgh \Rightarrow \omega^2 = 2(1.5)(9.81)(0.2)/0.09 = 65.4$, $\omega \approx 8.09 \text{ rad s}^{-1}$. At the lowest point the reaction R is vertical; the centre of mass moves in a circle of radius h , so $R - Mg = Mh\omega^2$, giving $R = 1.5(9.81) + 1.5(0.2)(65.4) = 14.7 + 19.6 = 34.3 \text{ N}$ upwards.

6.6 Revision Map: The Translation–Rotation Analogy

Nearly every formula of this chapter is the rotational twin of a translational formula you already know. Learning the dictionary below is the fastest way to revise the whole chapter.

KEY POINTS Translation–rotation analogy table

Quantity / law	Translation	Rotation
Displacement	x	θ
Velocity	$v = \dot{x}$	$\omega = \dot{\theta}$
Acceleration	$a = \dot{v}$	$\ddot{\theta}$
Inertia	mass m	moment of inertia $I = \sum mr^2$
Force / torque	F	$C = Fr$
Equation of motion	$F = ma$	$C = I\ddot{\theta}$
Momentum	$p = mv$	$L = I\omega$
Impulse	$J = \Delta p$	$Jr = \Delta L$
Kinetic energy	$\frac{1}{2}mv^2$	$\frac{1}{2}I\omega^2$
Work / power	Fx, Fv	$C\theta, C\omega$
SHM period	$2\pi\sqrt{m/k}$	$2\pi\sqrt{I_O/(Mgh)}$

Key chapter results: $I_O = I_G + Mh^2$; $k_O^2 = k_G^2 + h^2$; $L = I\omega$ conserved when no external torque; energy $\frac{1}{2}I\omega^2 + Mgy_G$ conserved for smooth pivots; compound pendulum $T = 2\pi\sqrt{I_O/(Mgh)}$, equivalent length $l = k_O^2/h$, minimum period at $h = k_G$.

WARNING Final checklist of classic errors

- Forgetting the parallel axes theorem: $I_O \neq I_G$ unless the pivot is at G .
- Mixing h (pivot to G) with the full length of the body.
- Using $\sin \theta \approx \theta$ without stating it, or with θ in degrees.
- Conserving kinetic energy through an inelastic impact — only moment of momentum about the pivot is conserved there.
- In $T = 2\pi\sqrt{I_O/(Mgh)}$, using I_G instead of I_O — the single most common error in this topic.

You have now completed the chapter on rotational dynamics: from the definition of moment of inertia, through the equation of motion under a constant torque, moment of momentum, energy, and finally the compound pendulum. Master the analogy table, rehearse the derivations flagged as examinable, and practise synthesis problems like the ones above — that is exactly the profile of the GCE Advanced Level questions on this chapter.

7 INTEGRATION ACTIVITY

7.1 Aims of the activity

This closing activity brings together all the ideas of the chapter in one authentic engineering study. By the end of it, you should be able to:

- select and use the standard **moment of inertia** of a uniform disc, $I = \frac{1}{2}MR^2$, and of a hoop, $I = MR^2$;
- apply the **work–energy principle** for rotation, $W_C = \Delta E_k$, with $E_k = \frac{1}{2}I\omega^2$ and the work of a constant couple $W = C\theta$;
- use the equation of motion of a rigid body under a constant torque, $C = I\alpha$, together with the constant-acceleration kinematic relations $\omega^2 = \omega_0^2 + 2\alpha\theta$ and $\omega = \omega_0 + \alpha t$;
- apply **conservation of moment of momentum** (angular momentum) when a mass is suddenly added to a rotating body, and compute the associated **energy loss**;
- compare two designs (disc versus rim-loaded wheel) and justify an engineering choice with numbers.

KEY POINTS Formulae you will need

Uniform disc about its central axis: $I = \frac{1}{2}MR^2$; hoop (mass at the rim): $I = MR^2$. Rotational kinetic energy: $E_k = \frac{1}{2}I\omega^2$. Work of a constant couple: $W = C\theta$. Equation of motion: $C = I\alpha$. Angular momentum about a fixed axis: $L = I\omega$, conserved when the external torque about the axis is zero.

7.2 Situation


EXPERIMENT The potter's wheel of Bamessing

In the village of Bamessing (Ndop, North-West Region), pottery is a centuries-old craft. A craftsman, Pa Nformi, uses a traditional kick-wheel: a heavy horizontal wheel mounted on a vertical axle in smooth bearings. The potter gives the wheel one strong kick, then shapes the clay while the wheel spins freely. If the wheel slows down too quickly, the pot becomes lopsided, so the wheel must keep spinning long enough after a single kick. Pa Nformi asks your Further Mathematics class to design the wheel. He gives you the following specifications and measurements:

- The wheel is modelled as a uniform disc of radius $R = 0.30$ m and negligible thickness, rotating about a fixed vertical axis through its centre.

- One strong kick supplies the wheel with a kinetic energy of exactly $E_0 = 120 \text{ J}$.
- Friction in the bearings and air resistance are modelled by a constant resisting couple $C_r = 0.5 \text{ N m}$.
- Requirement: after the kick, the wheel must complete at least $N = 40$ revolutions before coming to rest.
- Later, while the wheel spins freely, a lump of clay of mass $m = 2 \text{ kg}$ is dropped vertically onto the wheel at the rim and sticks there.

Take $g = 9.81 \text{ m s}^{-2}$ where needed. The axle is frictionless apart from the resisting couple already given, and its own moment of inertia is neglected.



Top view (left) and side view (right) of the potter's wheel. The clay lump is dropped onto the rim.

7.3 Tasks

Work in groups of three or four. Present every numerical answer with its unit and a short sentence of interpretation.

1. **Minimum moment of inertia.** Using the work–energy principle between the instant just after the kick and the instant the wheel stops, show that the wheel needs a minimum moment of inertia $I_{\min}$ and compute its value. (Hint: the resisting couple does work $-C_r\theta$ over the total angle $\theta = 2\pi N$.)
2. **Mass of the disc.** Deduce the mass M of a uniform disc of radius 0.30 m having this moment of inertia. Comment on whether such a wheel could reasonably be made of stone or of hardwood.
3. **Initial angular velocity.** Compute the angular velocity ω_0 just after the kick, in rad s^{-1} and in revolutions per minute (rev/min).

4. **Deceleration and stopping time.** Using $C = I\alpha$, find the angular deceleration α . Check, with the kinematic relation $\omega^2 = \omega_0^2 + 2\alpha\theta$, that the wheel indeed stops after exactly 40 revolutions, and find the time taken to stop.
5. **Consistency check.** Recover the same stopping angle by a purely energetic argument and confirm that the two methods agree. Why must they agree?
6. **The lump of clay.** The wheel is spinning at ω_0 when the 2 kg lump of clay is dropped vertically onto the rim and sticks. Explain why the moment of momentum about the axle is conserved during the drop, even though the resisting couple acts. Compute the new angular speed ω_1 and the kinetic energy lost in the process. Where does this energy go?
7. **Design discussion: disc or ring?** Suppose instead that the same mass M is concentrated at the rim (a heavy ring with light spokes). Compute the new moment of inertia, the new number of revolutions after the same 120 J kick, and the new initial angular speed. Which design is better for Pa Nformi, and what practical disadvantages might the ring design have?
8. **Final report.** Write a short justified recommendation to Pa Nformi: shape, mass, radius, expected performance.

7.4 Model answer

1. Minimum moment of inertia.

The wheel starts with kinetic energy $E_0 = 120$ J and stops after turning through an angle θ . The only work done is that of the resisting couple: $W = -C_r\theta$. The work–energy principle gives

$$0 - E_0 = -C_r\theta \quad \Rightarrow \quad \theta = \frac{E_0}{C_r}.$$

With $C_r = 0.5$ N m, $\theta = 120/0.5 = 240$ rad, which corresponds to

$$N = \frac{\theta}{2\pi} = \frac{240}{2\pi} = \frac{120}{\pi} \approx 38.2 \text{ revolutions.}$$

This is less than the required 40 revolutions. Crucially, θ (and hence N) does not depend on the moment of inertia I at all. Therefore **no choice of I can make the wheel reach 40 revolutions** with the given E_0 and C_r . The specification is infeasible as written.

To meet the requirement we must either increase the kick energy or reduce the resisting couple. The maximum allowable resisting couple for 40 revolutions is

$$C_{r,\max} = \frac{E_0}{2\pi N} = \frac{120}{80\pi} = \frac{1.5}{\pi} \approx 0.477 \text{ N m.}$$

We assume the bearings are improved so that $C'_r = 0.45$ N m $< C_{r,\max}$. Then the wheel will stop after

$$\theta = \frac{120}{0.45} = 266.\bar{6} \text{ rad} \approx 42.4 \text{ revolutions,}$$

satisfying the requirement with a margin. We continue the design with $C'_r = 0.45$ N m.

WARNING A lesson in modelling

Always check that a specification is feasible before computing detailed parameters. Here the work–energy test immediately shows the original brief is impossible: no moment of inertia, however large, can make 120 J do more than 120 J of work. A larger I makes the wheel spin slower but for the same total angle.

2. Mass of the disc.

The moment of inertia does not affect the number of revolutions, but Pa Nformi also wants a wheel that spins slowly enough to work on comfortably. We impose a maximum initial angular speed of $150 \text{ rev/min} = 5\pi \text{ rad s}^{-1}$. From $E_0 = \frac{1}{2}I\omega_0^2$,

$$I = \frac{2E_0}{\omega_0^2} = \frac{240}{(5\pi)^2} = \frac{240}{25\pi^2} = \frac{9.6}{\pi^2} \approx 0.972 \text{ kg m}^2.$$

For a uniform disc, $I = \frac{1}{2}MR^2$, so

$$M = \frac{2I}{R^2} = \frac{2 \times 0.972}{0.09} \approx 21.6 \text{ kg}.$$

A stone disc of radius 0.30 m and mass about 22 kg is entirely realistic for a traditional kick-wheel (density of stone $\approx 2500 \text{ kg m}^{-3}$ gives a thickness of $\approx 3 \text{ cm}$).

3. Initial angular velocity.

With $I = 0.972 \text{ kg m}^2$ and $E_0 = 120 \text{ J}$:

$$\omega_0 = \sqrt{\frac{2E_0}{I}} = \sqrt{\frac{240}{0.972}} \approx 15.7 \text{ rad s}^{-1} = 150 \text{ rev/min},$$

consistent with our design choice.

4. Deceleration and stopping time.

The equation of motion $C = I\alpha$ with $C = -C_r = -0.45 \text{ N m}$ gives

$$\alpha = \frac{-0.45}{0.972} \approx -0.463 \text{ rad s}^{-2}.$$

Kinematic check using $\omega^2 = \omega_0^2 + 2\alpha\theta$ with $\omega = 0$:

$$\theta = \frac{\omega_0^2}{2|\alpha|} = \frac{(15.7)^2}{2 \times 0.463} \approx 266 \text{ rad} \approx 42.4 \text{ revolutions} \geq 40. \quad \checkmark$$

Stopping time:

$$t = \frac{\omega_0}{|\alpha|} = \frac{15.7}{0.463} \approx 33.9 \text{ s}.$$

5. Consistency check.

Energetically, $\theta = \frac{E_0}{C'_r} = \frac{120}{0.45} \approx 266.7 \text{ rad}$ — identical to the kinematic result. The two methods must agree because the kinematic relation $\omega^2 = \omega_0^2 + 2\alpha\theta$, multiplied by $\frac{1}{2}I$, is the work–energy theorem:

$$\frac{1}{2}I\omega^2 - \frac{1}{2}I\omega_0^2 = I\alpha\theta = C\theta.$$

6. The lump of clay.

During the very short time Δt in which the clay is dropped and sticks, the impulse of the resisting couple $C'_r \Delta t$ is negligible. The forces between clay and wheel are internal to the system (wheel + clay), so the moment of momentum about the axle is conserved:

$$I\omega_0 = (I + mR^2)\omega_1.$$

Here $mR^2 = 2 \times 0.09 = 0.18 \text{ kg m}^2$, so $I_{\text{total}} = 0.972 + 0.18 = 1.152 \text{ kg m}^2$.

$$\omega_1 = \frac{I}{I + mR^2} \omega_0 = \frac{0.972}{1.152} \times 15.7 = \frac{27}{32} \times 5\pi = \frac{135\pi}{32} \approx 13.25 \text{ rad s}^{-1} \approx 126.5 \text{ rev/min}.$$

Energy before: $E_0 = 120 \text{ J}$. Energy after:

$$E_1 = \frac{1}{2}(I + mR^2)\omega_1^2 = \frac{1}{2} \times 1.152 \times (13.25)^2 \approx 101.25 \text{ J}.$$

Energy lost: $\Delta E = 120 - 101.25 = 18.75 \text{ J}$. This energy is dissipated as heat and sound during the inelastic “collision” while the clay slips on the wheel before sticking. Note that angular momentum is conserved but kinetic energy is not.

7. Disc or ring?

With the same mass $M = 21.6 \text{ kg}$ concentrated at the rim (a heavy ring with light spokes), the moment of inertia is

$$I_{\text{ring}} = MR^2 = 21.6 \times 0.09 = 1.944 \text{ kg m}^2,$$

exactly double the disc value. For the same 120 J kick:

$$\omega'_0 = \sqrt{\frac{2E_0}{I_{\text{ring}}}} = \sqrt{\frac{240}{1.944}} \approx 11.11 \text{ rad s}^{-1} \approx 106 \text{ rev/min},$$

a gentler working speed. The number of revolutions is unchanged ($\approx 42.4 \text{ rev}$), since it depends only on E_0 and C'_r ; but the stopping time increases by a factor $\sqrt{2}$ to

$$t' = \frac{\omega'_0}{|\alpha'|} = \frac{\omega'_0}{C'_r/I_{\text{ring}}} = \frac{I_{\text{ring}}\omega'_0}{C'_r} = \sqrt{2} \frac{I_{\text{disc}}\omega_0}{C'_r} \approx 1.414 \times 33.9 \approx 48.0 \text{ s},$$

giving over a minute of useful spinning. The lower speed is more comfortable for shaping clay. Disadvantages: a rim-loaded wheel is harder to build and balance, the spokes must be strong enough to transmit the torque, and the rim is more exposed to knocks.

8. Final recommendation.

Improve the bearings to bring the resisting couple down to about 0.45 N m; build a rim-loaded wheel (hoop) of mass $\approx 22 \text{ kg}$ and radius 0.30 m. One 120 J kick then gives $\approx 106 \text{ rev/min}$ initially, more than 40 revolutions, and about 48 seconds of working time — with the bonus that dropping a 2 kg lump of clay on the rim slows the wheel by only about 16% (from 106 to $\approx 89 \text{ rev/min}$).

DID YOU KNOW? Flywheels everywhere

Pa Nformi's wheel is a **flywheel**: a store of rotational kinetic energy. The same physics governs the flywheels that smooth the motion of engines, the massive stone wheels of grinding mills, and modern flywheel energy-storage systems used to stabilise electrical grids — including experimental installations paired with solar mini-grids in rural areas. The trade-off you discovered — for a fixed energy, more inertia means lower speed but longer running time — is exactly the trade-off engineers face when sizing any flywheel.

8 METHODS AND WORKED EXAMPLES


9 MOMENT OF INERTIA AND RADIUS OF GYRATION

9.1 Definition and Computation by Integration

METHOD Moment of inertia by summation or integration

1. Write the definition $I = \sum m_i r_i^2$ for discrete masses, or $I = \int r^2 dm$ for a continuous body, where r is the perpendicular distance from the axis.
2. For a continuous body, choose a thin element (strip, ring, shell) whose every point is at the same distance r from the axis; express its mass dm using the density (linear λ , surface σ , or volume ρ).
3. Express dm in terms of a single variable and integrate between the correct limits.
4. Check the dimensions (kg m^2) and, where possible, compare with a standard result.

Reflexes: for a thin rod of length $2a$ about its centre use strips; for a disc use concentric rings; for a sphere use slices. Always state the axis clearly.



Element of a uniform rod for moment of inertia calculation.

WORKED EXAMPLE 13 Moment of inertia of a uniform rod about its centre

A uniform thin rod AB has mass M and length $2a$. By integration, find its moment of inertia about an axis through its centre, perpendicular to its length.

SOLUTION

Let the axis pass through the centre O of the rod, perpendicular to AB . The linear density is

$$\lambda = \frac{M}{2a}.$$

Take a small element of length dx at distance x from O . Its mass is

$$dm = \lambda dx = \frac{M}{2a} dx,$$

and every point of this element is at distance x from the axis, so its contribution is $dI = x^2 dm$.

Integrating over the whole rod, from $x = -a$ to $x = a$:

$$\begin{aligned} I &= \int_{-a}^a x^2 \frac{M}{2a} dx = \frac{M}{2a} \left[\frac{x^3}{3} \right]_{-a}^a \\ &= \frac{M}{2a} \cdot \frac{2a^3}{3} = \frac{1}{3} Ma^2. \end{aligned}$$

Hence $I = \frac{1}{3} Ma^2$ about a perpendicular axis through the centre.

Check: by the parallel axis theorem, about an end the moment of inertia is $I = \frac{1}{3} Ma^2 + Ma^2 = \frac{4}{3} Ma^2$, the standard result.

9.2 Radius of Gyration and the Two Axis Theorems

METHOD Radius of gyration, parallel and perpendicular axes

1. Write $I = Mk^2$: the radius of gyration k concentrates all the mass at distance k from the axis.
2. Parallel axis theorem: $I = I_G + Mh^2$, where I_G is about the parallel axis through the centre of mass G and h is the distance between the axes.
3. Perpendicular axis theorem (lamina only, axis Oz perpendicular to the lamina): $I_z = I_x + I_y$.
4. Combine: to move between two axes neither through G , go via G : $I_2 = I_1 - Mh_1^2 + Mh_2^2$.

Reflex: I_G is always the smallest moment of inertia among parallel axes.

WORKED EXAMPLE 14 Radius of gyration of a rectangular lamina

A uniform rectangular lamina has sides $2a$ and $2b$ and mass M . Find (a) its radius of gyration about the axis through its centre perpendicular to its plane; (b) its moment of inertia about a parallel axis through a corner.

SOLUTION

For the lamina in the xy -plane with centre at the origin, the standard results about axes through G in the plane are

$$I_x = \frac{1}{3}Mb^2, \quad I_y = \frac{1}{3}Ma^2.$$

(a) By the perpendicular axis theorem,

$$I_z = I_x + I_y = \frac{1}{3}M(a^2 + b^2).$$

Since $I_z = Mk^2$,


$$k = \sqrt{\frac{a^2 + b^2}{3}}.$$

(b) The corner is at distance $h = \sqrt{a^2 + b^2}$ from G . By the parallel axis theorem,

$$\begin{aligned} I_{\text{corner}} &= I_z + Mh^2 = \frac{1}{3}M(a^2 + b^2) + M(a^2 + b^2) \\ &= \frac{4}{3}M(a^2 + b^2). \end{aligned}$$

10 STANDARD MOMENTS OF INERTIA BY INTEGRATION

10.1 Uniform Disc about its Symmetry Axis



Concentric ring element for a uniform disc.

WORKED EXAMPLE 15 Moment of inertia of a uniform disc

A uniform disc of mass M and radius R rotates about an axis through its centre perpendic-

ular to its plane. Derive $I = \frac{1}{2}MR^2$ by integration.

SOLUTION

Surface density $\sigma = \frac{M}{\pi R^2}$. Consider a concentric ring of radius r and width dr . Its area is $2\pi r dr$, so its mass is

$$dm = \sigma \cdot 2\pi r dr = \frac{2M}{R^2} r dr.$$

Every point of the ring is at distance r from the axis, hence

$$dI = r^2 dm = \frac{2M}{R^2} r^3 dr.$$

Integrate from $r = 0$ to $r = R$:

$$I = \frac{2M}{R^2} \int_0^R r^3 dr = \frac{2M}{R^2} \cdot \frac{R^4}{4} = \frac{1}{2}MR^2.$$

Thus $I = \frac{1}{2}MR^2$.

10.2 Uniform Rectangular Lamina about Perpendicular Axis through Centre

WORKED EXAMPLE 16 Moment of inertia of a rectangular lamina by integration

A uniform rectangular lamina of mass M has sides $2a$ and $2b$. Derive the moments of inertia about axes through its centre parallel to the sides, and hence the moment of inertia about the perpendicular axis through the centre.

SOLUTION

Place the lamina in the xy -plane with centre at the origin, sides parallel to the axes. Surface density $\sigma = \frac{M}{4ab}$.

About Ox (parallel to side $2a$): Take a strip parallel to Ox at distance y , width dy , length $2a$. Its mass $dm = \sigma \cdot 2a dy$. Every point is at distance $|y|$ from Ox , so

$$I_x = \int_{-b}^b y^2 dm = 2a\sigma \int_{-b}^b y^2 dy = 2a\sigma \cdot \frac{2b^3}{3} = \frac{4a\sigma b^3}{3}.$$

Substitute $\sigma = M/(4ab)$:

$$I_x = \frac{4a}{3} \cdot \frac{M}{4ab} \cdot b^3 = \frac{1}{3}Mb^2.$$

About Oy : By symmetry, $I_y = \frac{1}{3}Ma^2$.

About Oz (perpendicular through centre): By the perpendicular axis theorem,

$$I_z = I_x + I_y = \frac{1}{3}M(a^2 + b^2).$$

These are the standard results used in the previous section.

10.3 Uniform Solid Sphere about a Diameter

WORKED EXAMPLE 17 Moment of inertia of a uniform solid sphere

A uniform solid sphere of mass M and radius R . Derive $I = \frac{2}{5}MR^2$ about a diameter.

SOLUTION

Volume density $\rho = \frac{M}{\frac{4}{3}\pi R^3} = \frac{3M}{4\pi R^3}$. Slice the sphere into discs perpendicular to the chosen diameter (the x -axis). A disc at distance x from the centre has radius $y = \sqrt{R^2 - x^2}$ and thickness dx . Its volume is $\pi y^2 dx$, mass

$$dm = \rho \pi (R^2 - x^2) dx.$$

The moment of inertia of this disc about its own axis (the x -axis) is $\frac{1}{2}dm y^2$. Hence

$$dI = \frac{1}{2}\rho \pi (R^2 - x^2)^2 dx.$$

Integrate from $x = -R$ to $x = R$:

$$\begin{aligned} I &= \frac{1}{2}\rho \pi \int_{-R}^R (R^2 - x^2)^2 dx = \rho \pi \int_0^R (R^4 - 2R^2x^2 + x^4) dx \\ &= \rho \pi \left[R^4x - \frac{2}{3}R^2x^3 + \frac{1}{5}x^5 \right]_0^R = \rho \pi R^5 \left(1 - \frac{2}{3} + \frac{1}{5} \right) \\ &= \rho \pi R^5 \cdot \frac{8}{15}. \end{aligned}$$

Substitute $\rho = \frac{3M}{4\pi R^3}$:

$$I = \frac{3M}{4\pi R^3} \cdot \pi R^5 \cdot \frac{8}{15} = \frac{24}{60}MR^2 = \frac{2}{5}MR^2.$$

Thus $I = \frac{2}{5}MR^2$.

10.4 Uniform Spherical Shell about a Diameter

WORKED EXAMPLE 18 Moment of inertia of a uniform spherical shell

A uniform thin spherical shell of mass M and radius R . Derive $I = \frac{2}{3}MR^2$ about a diameter.

SOLUTION

Surface density $\sigma = \frac{M}{4\pi R^2}$. Use spherical coordinates: a ring at polar angle θ has radius $R \sin \theta$, width $R d\theta$. Its area is $2\pi R \sin \theta \cdot R d\theta = 2\pi R^2 \sin \theta d\theta$, mass

$$dm = \sigma \cdot 2\pi R^2 \sin \theta d\theta = \frac{M}{2} \sin \theta d\theta.$$

Distance from the axis (diameter) is $R \sin \theta$, so

$$dI = (R \sin \theta)^2 dm = \frac{M}{2} R^2 \sin^3 \theta d\theta.$$

Integrate θ from 0 to π :

$$I = \frac{M}{2} R^2 \int_0^\pi \sin^3 \theta d\theta = \frac{M}{2} R^2 \int_0^\pi \sin \theta (1 - \cos^2 \theta) d\theta.$$

Let $u = \cos \theta$, $du = -\sin \theta d\theta$:

$$\int_0^\pi \sin^3 \theta d\theta = \int_1^{-1} -(1 - u^2) du = \int_{-1}^1 (1 - u^2) du = \left[u - \frac{u^3}{3} \right]_{-1}^1 = \frac{4}{3}.$$

Hence

$$I = \frac{M}{2} R^2 \cdot \frac{4}{3} = \frac{2}{3} MR^2.$$

Thus $I = \frac{2}{3} MR^2$.

KEY POINTS

Summary of standard moments of inertia

Body	Axis	Moment of Inertia
Uniform thin rod, mass M , length $2a$	Through centre, $\perp$ to rod	$\frac{1}{3}Ma^2$
Uniform thin rod, mass M , length $2a$	Through one end, $\perp$ to rod	$\frac{4}{3}Ma^2$
Uniform disc, mass M , radius R	Through centre, $\perp$ to plane	$\frac{1}{2}MR^2$
Uniform disc, mass M , radius R	Diameter (in plane)	$\frac{1}{4}MR^2$
Uniform rectangular lamina, mass M , sides $2a, 2b$	Through centre, $\perp$ to plane	$\frac{1}{3}M(a^2 + b^2)$
Uniform solid sphere, mass M , radius R	Diameter	$\frac{2}{5}MR^2$
Uniform spherical shell, mass M , radius R	Diameter	$\frac{2}{3}MR^2$
Uniform solid cylinder, mass M , radius R	Axis of symmetry	$\frac{1}{2}MR^2$

11 EQUATION OF MOTION UNDER A CONSTANT TORQUE

11.1 Newton's Second Law for Rotation

METHOD Rigid body rotating about a fixed axis under constant torque

1. Compute the total moment of inertia I about the fixed axis (sum contributions of all parts).
2. Compute the resultant torque Γ about the axis (watch the signs: choose a positive sense of rotation).
3. Apply the equation of motion $\Gamma = I\ddot{\theta}$, i.e. $\ddot{\theta} = \Gamma/I$ (constant angular acceleration).
4. Use the constant-angular-acceleration formulae, analogues of the linear ones:

$$\omega = \omega_0 + \alpha t, \quad \theta = \omega_0 t + \frac{1}{2}\alpha t^2, \quad \omega^2 = \omega_0^2 + 2\alpha\theta.$$

Reflex: a torque from a tangential force F at distance r is $\Gamma = Fr$; a couple of forces F separated by d gives $\Gamma = Fd$.

WORKED EXAMPLE 19 Flywheel accelerated by a constant torque

A flywheel of moment of inertia $I = 0.8 \text{ kg m}^2$ is mounted on a fixed horizontal axle. A constant torque of 6 N m is applied while a frictional couple of 1 N m opposes the motion. Starting from rest, find (a) the angular acceleration; (b) the angular velocity after 10 s ; (c) the number of revolutions made in that time.

SOLUTION

(a) Resultant torque: $\Gamma = 6 - 1 = 5 \text{ N m}$. Then

$$\alpha = \ddot{\theta} = \frac{\Gamma}{I} = \frac{5}{0.8} = 6.25 \text{ rad s}^{-2}.$$

(b) With $\omega_0 = 0$:

$$\omega = \alpha t = 6.25 \times 10 = \boxed{62.5 \text{ rad s}^{-1}}.$$

(c) Angle turned through:

$$\theta = \frac{1}{2} \alpha t^2 = \frac{1}{2} (6.25)(100) = 312.5 \text{ rad}.$$

Number of revolutions:

$$N = \frac{\theta}{2\pi} = \frac{312.5}{2\pi} \approx \boxed{49.7 \text{ revolutions}}.$$

12 MOMENT OF MOMENTUM AND ITS CONSERVATION; IMPULSE

12.1 Angular Momentum and Angular Impulse

METHOD Angular impulse and moment of momentum

1. Moment of momentum (angular momentum) about a fixed axis: $L = I\omega$.
2. Angular impulse of a torque: $\int \Gamma dt = \Delta L = I\omega_2 - I\omega_1$.
3. For a particle of mass m moving with speed v at perpendicular distance r from the axis, $L = mvr$.
4. For connected systems (string over a pulley with inertia), write separate equations: $ma = mg - T$ type for each particle, and $(T_1 - T_2)r = I\alpha$ for the pulley, with $a = r\alpha$ (no slipping).

Reflex: when the pulley has inertia, the tensions on the two sides are different.

WORKED EXAMPLE 20 Masses hanging over a massive pulley

A light inextensible string passes over a pulley of mass 2 kg and radius 0.1 m, modelled as a uniform disc ($I = \frac{1}{2}Mr^2$). Masses of 3 kg and 1 kg hang from the ends. The string does not slip on the pulley. Taking $g = 9.8 \text{ m s}^{-2}$, find the acceleration of the masses and the two tensions.

SOLUTION

Moment of inertia of the pulley:

$$I = \frac{1}{2}(2)(0.1)^2 = 0.01 \text{ kg m}^2.$$

Let T_1 act on the 3 kg side, T_2 on the 1 kg side, and let a be the acceleration of the 3 kg mass downwards.

Particle equations (Newton's second law):

$$\begin{aligned} 3g - T_1 &= 3a, \\ T_2 - g &= a. \end{aligned}$$

Pulley equation (torque = $I\alpha$, with $\alpha = a/r$):

$$(T_1 - T_2)r = I\frac{a}{r} \implies T_1 - T_2 = \frac{Ia}{r^2} = \frac{0.01}{0.01}a = a.$$

Adding the three equations eliminates T_1, T_2 :

$$3g - g = 3a + a + a = 5a \implies a = \frac{2g}{5} = \frac{19.6}{5} = 3.92 \text{ m s}^{-2}.$$

Then

$$T_1 = 3(g - a) = 3(5.88) = 17.64 \text{ N}, \quad T_2 = g + a = 13.72 \text{ N}.$$

Check: $T_1 - T_2 = 3.92 = a$ as required. Note $T_1 \neq T_2$ because the pulley has inertia.

12.2 Conservation of Angular Momentum

METHOD Conservation of angular momentum

1. Check that the external torque about the axis is zero (internal forces, however large, do not change L).

2. Write $I_1\omega_1 = I_2\omega_2$ where I may change (masses moving in/out, body changing shape).
3. For a point mass m added to or removed from a rotating system, adjust I accordingly:

$$I_{\text{new}} = I_{\text{old}} + mr^2.$$
4. Kinetic energy is not conserved in such processes (internal forces do work): expect KE to change.

WORKED EXAMPLE 21 Mass dropped onto a rotating turntable

A horizontal turntable of moment of inertia 0.5 kg m^2 rotates freely at 4 rad s^{-1} about a vertical axis. A small bag of sand of mass 2 kg is dropped vertically onto it and sticks at a distance 0.3 m from the axis. Find the new angular velocity and the loss of kinetic energy.

SOLUTION

No external torque acts about the vertical axis, so moment of momentum is conserved.
 New moment of inertia:

$$I_2 = 0.5 + mr^2 = 0.5 + 2(0.3)^2 = 0.5 + 0.18 = 0.68 \text{ kg m}^2.$$

Conservation of L :

$$I_1\omega_1 = I_2\omega_2 \quad \Rightarrow \quad \omega_2 = \frac{0.5 \times 4}{0.68} = \frac{2}{0.68} \approx 2.94 \text{ rad s}^{-1}.$$

Kinetic energies:

$$KE_1 = \frac{1}{2}I_1\omega_1^2 = \frac{1}{2}(0.5)(16) = 4 \text{ J},$$

$$KE_2 = \frac{1}{2}(0.68)(2.94)^2 \approx 2.94 \text{ J}.$$

Loss of kinetic energy: $4 - 2.94 \approx 1.06 \text{ J}$, dissipated as heat and sound when the bag grips the turntable (an inelastic process).

13 ENERGY OF A ROTATING BODY AND THE FORCE ON THE AXIS

13.1 Rotational Kinetic Energy and Conservation of Energy

13.2 Force Exerted on the Axis of Rotation

METHOD Conservation of energy for a rotating rigid body

1. Write the kinetic energy as $KE = \frac{1}{2}I\omega^2$ (rotation about a fixed axis); add $\frac{1}{2}Mv_G^2$ if the body also translates.
2. Write the change in gravitational potential energy from the vertical displacement of the centre of mass: $\Delta PE = Mg \Delta h_G$.
3. If only gravity does work, $KE + PE = \text{constant}$; use this to find ω in any position.
4. To find the force on the axis: use the motion of the centre of mass,

$$\vec{F}_{\text{axis}} + M\vec{g} = M\vec{a}_G,$$

with a_G having radial component $h\omega^2$ (towards the axis) and tangential component $h\alpha$, where $h = OG$.

WORKED EXAMPLE 22 Rod falling from the vertical; force on the hinge

A uniform rod of mass M and length $2a$ is freely hinged at one end O and released from rest in the vertical (unstable) position. Find (a) its angular velocity when it has turned through an angle θ ; (b) the horizontal and vertical components of the reaction at the hinge when $\theta = 90^\circ$.

SOLUTION

Moment of inertia about O : $I_O = \frac{4}{3}Ma^2$; the centre of mass G is at distance a from O .

(a) When the rod makes angle θ with the upward vertical, G has fallen a distance $a(1 - \cos \theta)$.

Energy conservation:

$$\frac{1}{2}I_O\omega^2 = Mga(1 - \cos \theta) \implies \omega^2 = \frac{3g}{2a}(1 - \cos \theta).$$

(b) At $\theta = 90^\circ$: $\omega^2 = \frac{3g}{2a}$.

Angular acceleration from $\Gamma = I\alpha$ at $\theta = 90^\circ$ (weight has moment Mga about O):

$$Mga = \frac{4}{3}Ma^2\alpha \implies \alpha = \frac{3g}{4a}.$$

Acceleration of G (at $\theta = 90^\circ$, G moves horizontally; radial direction is horizontal, tangential is vertical):

$$a_{\text{rad}} = a\omega^2 = \frac{3g}{2} \text{ (horizontal, towards } O), \quad a_{\text{tan}} = a\alpha = \frac{3g}{4} \text{ (vertically downwards).}$$

Newton's second law for G , with hinge reaction (X, Y) :

$$X = Ma_{\text{rad}} = \frac{3}{2}Mg, \quad Mg - Y = Ma_{\text{tan}} = \frac{3}{4}Mg \implies Y = \frac{1}{4}Mg.$$

Hence the hinge exerts $X = \frac{3}{2}Mg$ horizontally and $Y = \frac{1}{4}Mg$ vertically upwards; magnitude $R = \frac{Mg}{4}\sqrt{37}$.

14 THE COMPOUND PENDULUM AND SYNTHESIS

14.1 Period of a Compound Pendulum

METHOD Period of a compound pendulum

1. Identify the pivot O ; compute I_O about the pivot (often via the parallel axis theorem: $I_O = I_G + Mh^2 = M(k_G^2 + h^2)$, with $h = OG$).
2. Write the restoring torque for angular displacement θ : $\Gamma = -Mgh \sin \theta$.
3. For small oscillations, $\sin \theta \approx \theta$, giving $\ddot{\theta} = -\frac{Mgh}{I_O}\theta$: SHM with

$$T = 2\pi\sqrt{\frac{I_O}{Mgh}} = 2\pi\sqrt{\frac{k_G^2 + h^2}{gh}}.$$

4. The equivalent simple pendulum has length $\ell = \frac{k_G^2 + h^2}{h}$; the centre of oscillation O' lies at distance ℓ from O , and O and O' are interchangeable (Kater's idea).

Reflex: always check that the small-angle approximation is stated; the formula is only valid for small oscillations.

WORKED EXAMPLE 23 Compound pendulum: uniform rod swinging about one end

A uniform rod of length 1.2 m swings as a compound pendulum about a horizontal axis through one end. Taking $g = 9.8 \text{ m s}^{-2}$, find (a) the period of small oscillations; (b) the length of the equivalent simple pendulum; (c) the distance from the pivot of the centre of oscillation.

SOLUTION

Let $2a = 1.2 \text{ m}$, so $a = 0.6 \text{ m}$ and $h = OG = a = 0.6 \text{ m}$.
About the centre: $I_G = \frac{1}{3}Ma^2$, so $k_G^2 = \frac{1}{3}a^2 = 0.12 \text{ m}^2$.

(a) Period:

$$T = 2\pi\sqrt{\frac{k_G^2 + h^2}{gh}} = 2\pi\sqrt{\frac{0.12 + 0.36}{9.8 \times 0.6}} = 2\pi\sqrt{\frac{0.48}{5.88}}.$$

$$\frac{0.48}{5.88} = 0.08163 \text{ s}^2, \quad T = 2\pi(0.2857) \approx \boxed{1.79 \text{ s}}.$$

(b) Equivalent simple pendulum length:

$$\ell = \frac{k_G^2 + h^2}{h} = \frac{0.48}{0.6} = \boxed{0.8 \text{ m}}.$$

(c) The centre of oscillation is at distance $\ell = 0.8 \text{ m}$ below the pivot, i.e. 0.2 m below G . Check (Kater's property): if the rod were swung about an axis through this point O' , with $h' = 0.2 \text{ m}$, then

$$\frac{k_G^2 + h'^2}{h'} = \frac{0.12 + 0.04}{0.2} = 0.8 \text{ m} = \ell,$$

giving the same period, as expected: pivot and centre of oscillation are interchangeable.

14.2 Combined Rotation and Translation: Rolling Motion

METHOD Rigid body rolling or rotating with connected motion

1. Draw a clear diagram; mark all forces and the axis/ instantaneous constraints.
2. Choose your tool: energy conservation (cleanest when only gravity does work and no slipping dissipates energy) or equations of motion ($F = Ma_G$ and $\Gamma_G = I_G \alpha$).
3. For rolling without slipping, impose the constraint $v_G = r\omega$, $a_G = r\alpha$.
4. Total kinetic energy: $KE = \frac{1}{2}Mv_G^2 + \frac{1}{2}I_G\omega^2$.

WORKED EXAMPLE 24 Cylinder rolling down an inclined plane

A solid cylinder of mass M and radius r rolls without slipping down a plane inclined at 30° to the horizontal, starting from rest. Find (a) its acceleration; (b) its speed after travelling 2 m down the slope ($g = 9.8 \text{ m s}^{-2}$); (c) the minimum coefficient of friction for rolling to be maintained.

SOLUTION

For a solid cylinder, $I_G = \frac{1}{2}Mr^2$. Rolling constraint: $a = r\alpha$.

(a) Equations of motion along the plane and about G:

$$Mg \sin 30^\circ - F = Ma, \quad Fr = I_G \alpha = \frac{1}{2}Mr^2 \cdot \frac{a}{r} = \frac{1}{2}Mra.$$

From the second equation $F = \frac{1}{2}Ma$. Substituting:

$$Mg \sin 30^\circ = Ma + \frac{1}{2}Ma = \frac{3}{2}Ma \implies a = \frac{2g \sin 30^\circ}{3} = \frac{g}{3} = \boxed{3.27 \text{ m s}^{-2}}.$$

(b) With $u = 0$, $s = 2 \text{ m}$: $v^2 = 2as = 2 \times 3.27 \times 2 = 13.07$, so

$$v \approx \boxed{3.62 \text{ m s}^{-1}}.$$

(Energy check: $Mgh = \frac{1}{2}Mv^2 + \frac{1}{2}I_G\omega^2 = \frac{3}{4}Mv^2$ with $h = 2 \sin 30^\circ = 1 \text{ m}$ gives $v^2 = \frac{4}{3}g = 13.07$.)

(c) Friction needed: $F = \frac{1}{2}Ma = \frac{1}{6}Mg$. Normal reaction: $N = Mg \cos 30^\circ$. Rolling requires $F \leq \mu N$:

$$\mu \geq \frac{F}{N} = \frac{Mg/6}{Mg \cos 30^\circ} = \frac{1}{6 \times 0.866} \approx \boxed{0.19}.$$

WARNING Examiner's warnings

- Never confuse I_G with I_O : apply the parallel axis theorem carefully before writing $\Gamma = I\ddot{\theta}$ about a pivot.
- In pulley problems with a massive pulley, the two tensions are different; writing $T_1 = T_2$ is the most common error.
- Conservation of moment of momentum does not imply conservation of kinetic energy when bodies stick or I changes.
- For the compound pendulum, the formula $T = 2\pi\sqrt{I_O/(Mgh)}$ requires small oscillations; state this assumption.
- Keep all angles in radians when using $\omega^2 = \omega_0^2 + 2\alpha\theta$ and torque equations.

15 EXERCISES

15.1 I check my knowledge

EXERCISE 10 Moment of inertia of point masses

Three particles of masses 1 kg, 2 kg and 3 kg are fixed at the vertices of a light equilateral triangular frame of side 0.6 m. Find the moment of inertia and the radius of gyration about an axis through the 1 kg mass perpendicular to the plane of the triangle.

EXERCISE 11 Radius of gyration of a uniform rod

A uniform rod of mass 4 kg and length 2 m rotates about an axis through one end perpendicular to the rod. State the moment of inertia and calculate the radius of gyration about this axis.

EXERCISE 12 Standard moment of inertia by integration

Prove by integration that the moment of inertia of a uniform disc of mass M and radius a about a diameter is $\frac{1}{4}Ma^2$. You may quote the moment of inertia of a disc about its central axis perpendicular to its plane.

EXERCISE 13 Constant torque and angular motion

A flywheel of moment of inertia 0.8 kg m^2 rotates at 300 rev/min. It is brought to rest in 15 s by a constant braking couple. Find the magnitude of the couple and the number of revolutions made while stopping.

15.2 I practise

EXERCISE 14 Masses on a pulley with moment of inertia

Two masses of 3 kg and 5 kg hang from a light inextensible string passing over a pulley of mass 4 kg and radius 0.2 m modelled as a uniform disc. The system is released from rest. Find the acceleration of the masses and the tension in each part of the string.

EXERCISE 15 Rod released from horizontal

A uniform rod AB of length 1.2 m and mass 2 kg is free to rotate in a vertical plane about a smooth horizontal axis through A. The rod is released from rest when horizontal. Find its angular speed when vertical and the magnitude of the reaction at A at that instant.

EXERCISE 16 Disc with added mass on rim

A uniform disc of mass 2 kg and radius 0.5 m rotates freely at 4 rad/s about its fixed vertical axis. A particle of mass 0.5 kg is gently placed on the rim and adheres to it. Find the new angular speed and the loss of kinetic energy.

EXERCISE 17 Compound pendulum: rod and disc

A compound pendulum consists of a uniform rod AB of mass M and length $2a$, with a uniform disc of mass M and radius a fixed to the rod at B, the plane of the disc being perpendicular to the rod. The pendulum oscillates in a vertical plane about a horizontal axis through A. Find the moment of inertia about A, the period of small oscillations, and the reaction on the axis when the pendulum passes through its lowest position with angular speed ω .

15.3 I prepare for the GCE**EXERCISE 18** Small oscillations of a rod

A uniform rod of mass M and length $2a$ makes small oscillations in a vertical plane about one end. Show that the period is $2\pi\sqrt{\frac{4a}{3g}}$ and state the length of the equivalent simple pendulum. [7 marks]

EXERCISE 19 Impulsive tension and energy

A light string is wrapped round a pulley of moment of inertia I and radius r . A mass m is attached to the free end of the string. The mass is released from rest and falls a distance h before the string suddenly becomes taut. Using energy and impulsive tension, find the angular speed of the pulley just after the jerk. [8 marks]

EXERCISE 20 GCE structured question: compound pendulum

A compound pendulum is made by rigidly attaching a uniform disc of mass $2m$ and radius a to the end B of a uniform rod AB of mass m and length $2a$. The disc lies in the same plane as the rod and its centre is at B. The pendulum is free to rotate in a vertical plane about a smooth horizontal axis through A.

1. Find the moment of inertia of the pendulum about the axis through A. [4 marks]
2. The pendulum is released from rest with AB horizontal. Find the angular speed when AB is vertical. [5 marks]
3. Find the magnitude and direction of the reaction at the axis A when the pendulum passes through the vertical position. [6 marks]
4. Determine the period of small oscillations about the equilibrium position. [5 marks]

16 SOLUTIONS TO THE EXERCISES

SOLUTION Exercise 1 — Moment of inertia of point masses

The moment of inertia of a system of point masses about an axis is $I = \sum m_i r_i^2$, where r_i is the perpendicular distance from the axis.

The axis passes through the 1 kg mass and is perpendicular to the plane of the triangle. Hence the 1 kg mass lies on the axis ($r = 0$). The other two masses are at the other vertices of the equilateral triangle of side 0.6 m; each is at distance 0.6 m from the axis.

$$I = (2 \text{ kg})(0.6 \text{ m})^2 + (3 \text{ kg})(0.6 \text{ m})^2 = (2 + 3) \times 0.36 = 1.8 \text{ kg m}^2.$$

Total mass $M = 1 + 2 + 3 = 6 \text{ kg}$. The radius of gyration k is defined by $I = Mk^2$:

$$k = \sqrt{\frac{I}{M}} = \sqrt{\frac{1.8}{6}} = \sqrt{0.3} \approx 0.548 \text{ m}.$$

Answer: $I = 1.8 \text{ kg m}^2$, $k = \sqrt{0.3} \text{ m} \approx 0.548 \text{ m}$.

SOLUTION Exercise 2 — Radius of gyration of a uniform rod

For a uniform rod of mass M and length L about an axis through one end perpendicular to the rod, the standard moment of inertia is

$$I = \frac{1}{3}ML^2.$$

Here $M = 4 \text{ kg}$, $L = 2 \text{ m}$:

$$I = \frac{1}{3} \times 4 \times (2)^2 = \frac{16}{3} \text{ kg m}^2.$$

The radius of gyration k satisfies $I = Mk^2$:

$$k = \sqrt{\frac{I}{M}} = \sqrt{\frac{16/3}{4}} = \sqrt{\frac{4}{3}} = \frac{2}{\sqrt{3}} = \frac{2\sqrt{3}}{3} \text{ m} \approx 1.155 \text{ m}.$$

Answer: $I = \frac{16}{3} \text{ kg m}^2$, $k = \frac{2\sqrt{3}}{3} \text{ m}$.

SOLUTION Exercise 3 — Standard moment of inertia by integration

We prove that the moment of inertia of a uniform disc of mass M and radius a about a diameter is $\frac{1}{4}Ma^2$.

Method 1 (Perpendicular axis theorem): The moment of inertia of the disc about its central axis perpendicular to its plane is $I_z = \frac{1}{2}Ma^2$. Let I_x and I_y be the moments of inertia about two perpendicular diameters in the plane of the disc. By symmetry $I_x = I_y$. The perpendicular axis theorem states $I_z = I_x + I_y = 2I_x$. Hence

$$I_x = \frac{1}{2}I_z = \frac{1}{2} \times \frac{1}{2}Ma^2 = \frac{1}{4}Ma^2.$$

Method 2 (Direct integration): Place the disc in the xy -plane with centre at the origin. The diameter is the x -axis. Consider a thin strip parallel to the x -axis at distance y from it, of width dy . The strip has length $2\sqrt{a^2 - y^2}$. Its area is $dA = 2\sqrt{a^2 - y^2} dy$. Mass per unit area $\sigma = M/(\pi a^2)$. The moment of inertia of the strip about the x -axis is $dI = y^2 dm = y^2 \sigma dA$. Integrating from $y = -a$ to $y = a$:

$$I = \sigma \int_{-a}^a 2y^2 \sqrt{a^2 - y^2} dy.$$

Using the substitution $y = a \sin \theta$, $dy = a \cos \theta d\theta$, $\sqrt{a^2 - y^2} = a \cos \theta$, the integral becomes

$$I = \sigma \int_{-\pi/2}^{\pi/2} 2a^2 \sin^2 \theta \cdot a \cos \theta \cdot a \cos \theta d\theta = 2\sigma a^4 \int_{-\pi/2}^{\pi/2} \sin^2 \theta \cos^2 \theta d\theta.$$

Since $\sin^2 \theta \cos^2 \theta = \frac{1}{4} \sin^2 2\theta = \frac{1}{8}(1 - \cos 4\theta)$, the integral evaluates to $\frac{\pi}{8}$. Thus

$$I = 2\sigma a^4 \cdot \frac{\pi}{8} = \frac{\pi}{4} \sigma a^4 = \frac{\pi}{4} \cdot \frac{M}{\pi a^2} \cdot a^4 = \frac{1}{4}Ma^2.$$

Answer: $I = \frac{1}{4}Ma^2$ (proved).

SOLUTION Exercise 4 — Constant torque and angular motion

Initial angular speed: $\omega_0 = 300 \text{ rev/min} = 300 \times \frac{2\pi}{60} = 10\pi \text{ rad/s}$. Final angular speed $\omega = 0$ after time $t = 15 \text{ s}$. Constant angular acceleration α :

$$\omega = \omega_0 + \alpha t \Rightarrow 0 = 10\pi + 15\alpha \Rightarrow \alpha = -\frac{2\pi}{3} \text{ rad/s}^2.$$

Magnitude of braking couple (torque): $\tau = I|\alpha| = 0.8 \times \frac{2\pi}{3} = \frac{1.6\pi}{3} \approx 1.676 \text{ N m}$.

Angular displacement during stopping:

$$\theta = \omega_0 t + \frac{1}{2}\alpha t^2 = 10\pi \times 15 + \frac{1}{2}\left(-\frac{2\pi}{3}\right) \times 225 = 150\pi - 75\pi = 75\pi \text{ rad}.$$

Number of revolutions: $N = \frac{\theta}{2\pi} = \frac{75\pi}{2\pi} = 37.5$.

Answer: Couple = $\frac{1.6\pi}{3} \text{ N m} \approx 1.68 \text{ N m}$; revolutions = 37.5.

SOLUTION Exercise 5 — Masses on a pulley with moment of inertia

Let T_1 be the tension on the 3 kg side, T_2 on the 5 kg side. The pulley is a uniform disc: $I = \frac{1}{2}MR^2 = \frac{1}{2} \times 4 \times (0.2)^2 = 0.08 \text{ kg m}^2$. Let a be the downward acceleration of the 5 kg mass (and upward acceleration of the 3 kg mass). The angular acceleration of the pulley is $\alpha = a/R$.

Equations of motion:

$$5g - T_2 = 5a \quad (1)$$

$$T_1 - 3g = 3a \quad (2)$$

$$(T_2 - T_1)R = I\alpha = I\frac{a}{R} \Rightarrow T_2 - T_1 = \frac{I}{R^2}a = \frac{0.08}{0.04}a = 2a \quad (3)$$

Add (1) and (2): $5g - T_2 + T_1 - 3g = 8a \Rightarrow 2g - (T_2 - T_1) = 8a$. Substitute (3): $2g - 2a = 8a \Rightarrow 2g = 10a \Rightarrow a = \frac{g}{5} = 1.96 \text{ m/s}^2$ (using $g = 9.8 \text{ m/s}^2$).

Then

$$T_2 = 5g - 5a = 5 \times 9.8 - 5 \times 1.96 = 49 - 9.8 = 39.2 \text{ N},$$

$$T_1 = 3g + 3a = 3 \times 9.8 + 3 \times 1.96 = 29.4 + 5.88 = 35.28 \text{ N}.$$

Answer: $a = 1.96 \text{ m/s}^2$, $T_1 = 35.28 \text{ N}$, $T_2 = 39.2 \text{ N}$.

SOLUTION Exercise 6 — Rod released from horizontal

Rod: mass $M = 2 \text{ kg}$, length $L = 1.2 \text{ m}$. Moment of inertia about end A:

$$I = \frac{1}{3}ML^2 = \frac{1}{3} \times 2 \times (1.2)^2 = 0.96 \text{ kg m}^2.$$

Loss of gravitational potential energy when the rod falls from horizontal to vertical: the centre of mass drops by $L/2 = 0.6 \text{ m}$.

$$\Delta U = Mg\frac{L}{2} = 2 \times 9.8 \times 0.6 = 11.76 \text{ J}.$$

This equals the gain in rotational kinetic energy:

$$\frac{1}{2}I\omega^2 = 11.76 \Rightarrow \omega^2 = \frac{2 \times 11.76}{0.96} = 24.5 \Rightarrow \omega = \sqrt{24.5} \approx 4.95 \text{ rad/s}.$$

Reaction at A when vertical: At the lowest point, the centre of mass moves in a circle of radius $L/2$. The centripetal force required is

$$F_c = M\frac{v_{\text{cm}}^2}{L/2} = M\frac{(\omega L/2)^2}{L/2} = M\omega^2\frac{L}{2}.$$

Forces on the rod: weight Mg downwards, reaction R upwards. Net upward force provides centripetal acceleration:

$$R - Mg = M\omega^2\frac{L}{2}.$$

Using $\omega^2 = 3g/L$ (from energy: $\frac{1}{2} \cdot \frac{1}{3}ML^2\omega^2 = Mg\frac{L}{2} \Rightarrow \omega^2 = 3g/L$):

$$M\omega^2\frac{L}{2} = M \cdot \frac{3g}{L} \cdot \frac{L}{2} = \frac{3}{2}Mg.$$

Hence

$$R = Mg + \frac{3}{2}Mg = \frac{5}{2}Mg = 2.5 \times 2 \times 9.8 = 49 \text{ N}.$$

Direction: vertically upward.

Answer: $\omega \approx 4.95 \text{ rad/s}$, $R = 49 \text{ N}$ upward.

SOLUTION Exercise 7 — Disc with added mass on rim

Disc: $M = 2 \text{ kg}$, $R = 0.5 \text{ m}$. Initial moment of inertia:

$$I_{\text{disc}} = \frac{1}{2}MR^2 = \frac{1}{2} \times 2 \times (0.5)^2 = 0.25 \text{ kg m}^2.$$

Initial angular speed $\omega_0 = 4 \text{ rad/s}$. Initial angular momentum:

$$L = I_{\text{disc}}\omega_0 = 0.25 \times 4 = 1 \text{ kg m}^2/\text{s}.$$

Particle of mass $m = 0.5 \text{ kg}$ placed on the rim. Its moment of inertia about the axis: $mR^2 = 0.5 \times 0.25 = 0.125 \text{ kg m}^2$. Total moment of inertia after adhesion:


$$I_{\text{total}} = 0.25 + 0.125 = 0.375 \text{ kg m}^2.$$

Angular momentum is conserved (no external torque about the axis):

$$\omega_{\text{new}} = \frac{L}{I_{\text{total}}} = \frac{1}{0.375} = \frac{8}{3} \approx 2.667 \text{ rad/s}.$$

Answer: New angular speed $\omega = \frac{8}{3} \text{ rad/s} \approx 2.67 \text{ rad/s}$.

17 SUMMARY SHEET



Mind map of the chapter Rotational Dynamics.

FICHE BILAN L'essentiel à connaître pour l'examen

Key definitions

- **Moment of inertia** of a particle: $I = mr^2$ (r = perpendicular distance from the axis). For a system or rigid body: $I = \sum m_i r_i^2 = \int r^2 dm$. Unit: kg m^2 .
- **Radius of gyration** k : $I = Mk^2$, i.e. $k = \sqrt{I/M}$ — the distance at which the whole mass could be concentrated to give the same I .
- **Torque** (moment of a force) about an axis: $G = Fd$ where d is the perpendicular distance from the axis to the line of action.
- **Moment of momentum** (angular momentum) about a fixed axis: $L = I\omega$.
- **Compound pendulum**: a rigid body swinging freely about a fixed horizontal axis.

Standard moments of inertia (proved by integration)

- Uniform rod, mass M , length $2a$, about centre: $I = \frac{1}{3}Ma^2$; about one end: $I = \frac{4}{3}Ma^2$.
- Uniform hoop (ring) radius a about central axis: $I = Ma^2$.
- Uniform disc radius a about central axis: $I = \frac{1}{2}Ma^2$.

- Uniform sphere radius a about a diameter: $I = \frac{2}{5}Ma^2$.
- **Parallel axes theorem:** $I = I_G + Mh^2$ (I_G about the parallel axis through the centre of mass, h = distance between axes).
- **Perpendicular axes theorem** (lamina): $I_z = I_x + I_y$.

Laws and formulas to know

- Equation of rotational motion about a fixed axis: $G = I\ddot{\theta}$ (rotational analogue of $F = ma$).
- Constant torque G : constant angular acceleration; the constant-acceleration formulas apply with $s \rightarrow \theta$, $u \rightarrow \omega_0$, $v \rightarrow \omega$, $a \rightarrow \ddot{\theta}$:

$$\omega = \omega_0 + \ddot{\theta}t, \quad \theta = \omega_0 t + \frac{1}{2}\ddot{\theta}t^2, \quad \omega^2 = \omega_0^2 + 2\ddot{\theta}\theta.$$

- Angular impulse: change of moment of momentum, $J = I\omega_2 - I\omega_1$.
- **Conservation of moment of momentum:** if the total external moment about the axis is zero, $I_1\omega_1 = I_2\omega_2$ (e.g. two bodies engaging on the same axis).
- Kinetic energy of rotation: $E_k = \frac{1}{2}I\omega^2$; work done by a constant torque: $W = G\theta$; power: $P = G\omega$.
- Work-energy principle: $G\theta = \frac{1}{2}I\omega^2 - \frac{1}{2}I\omega_0^2$; conservation of energy: $\frac{1}{2}I\omega^2 + Mgh = \text{constant}$.
- Compound pendulum: period of small oscillations

$$T = 2\pi\sqrt{\frac{I}{Mgh}} = 2\pi\sqrt{\frac{k^2 + h^2}{gh}},$$

where h = distance from axis to centre of mass; equivalent simple pendulum length $\ell = \frac{k^2 + h^2}{h}$. Minimum period when $h = k$.

- Force on the axis: resolve along and perpendicular to GO using $\Sigma F = M\ddot{x}$, $M\ddot{y}$ with $\ddot{x} = -h\omega^2$, $\ddot{y} = h\ddot{\theta}$ (components of acceleration of G), together with $G = I_O\ddot{\theta}$.

Methods

1. Finding I by integration: choose a strip/element of mass $dm = \rho dV$ at distance r from the axis; write $I = \int r^2 dm$; express everything in one variable; integrate between correct limits.
2. Constant torque problems: compute I (use parallel axes if needed), then $\ddot{\theta} = G/I$, then use the angular kinematics formulas.
3. Connected particles: write $F = ma$ for each translating particle and $G = I\ddot{\theta}$ for the rotating body; link with $a = r\ddot{\theta}$; solve simultaneously.

4. Impulse problems: apply angular impulse = change of $I\omega$ to each body; use conservation of moment of momentum at engagement.

5. Compound pendulum: find I about the pivot (parallel axes), then $T = 2\pi\sqrt{I/(Mgh)}$.

Common mistakes

- Confusing I about the centre with I about an end — always check the axis and use parallel axes correctly ($I = I_G + Mh^2$, never $I_G - Mh^2$).
- Mixing units: angles must be in radians in all formulas.
- Using $G = I\ddot{\theta}$ with I about the wrong axis (the axis must be the fixed axis of rotation).
- Forgetting that energy is not conserved in inelastic engagements (impulse problems), even though moment of momentum is.
- Taking moments of forces that pass through the axis (their moment is zero).
- Sign errors in the force on the axis: draw a clear diagram and fix positive directions first.

GCE tips

- Learn the four standard results and be ready to prove any of them by integration — this is a frequent examinable proof.
- Show the equation $G = I\ddot{\theta}$ explicitly before substituting numbers; method marks are awarded for it.
- In compound pendulum questions, quote $T = 2\pi\sqrt{I/(Mgh)}$ and define h clearly on a diagram.
- Keep answers in exact form (surds, π) unless a decimal is requested; give units (kg m^2 , rad s^{-1} , N m).
- Check dimensional consistency: $I\omega^2$ has units of energy — a quick way to validate a result.



Signed • OnBuch+

ONBUCH+ TEACHING TEAM
FOLLOWS THE OFFICIAL MINESEC SYLLABUS

OnBuch+