Distributed Systems Group (PDS)
Department Software Technology
Faculty EEMCS
DELFT UNIVERSITY OF TECHNOLOGY

LAB EXERCISES DISTRIBUTED ALGORITHMS (IN4150)

Exercise 3a

Implementation of Randomized Byzantine Agreement

D.H.J. Epema

April 11, 2016

1 Goal

Consensus and fault tolerance are core topics in distributed systems, and algorithms for reaching consensus are fundamental to the field of distributed computing. In this exercise a randomized solution for consensus has to be implemented that works in both synchronous and asynchronous systems.

2 Assignment

Implement the randomized algorithm for Byzantine Agreement in synchronous and asynchronous systems with a completely connected network (Algorithm 5.8 of the lecture notes). The implementation can be done in Java/RMI or Python. In designing, implementing, and testing your algorithm, take into account the following issues:

- 1. Your program should be truly distributed in that processes in the distributed algorithm run on multiple machines (so don't use a single JVM on a single machine that simulates all processes; it is of course allowed to have a single JVM in one machine simulate multiple processes).
- 2. Build into your program artificial random delays before processes perform their actions.
- 3. First test the correctness of your program for small numbers of processors.
- 4. Include different failure patterns for the faulty processes, e.g., by having them never send any message at all, or by having them flip a coin for every potential message whether to actually send it or not, and if so, for the contents of the message.

- 5. Also run your program with a number of faulty processes that is at least equal to one-fifth of the total number of processes, and check that then your program does not (always) give correct results.
- 6. Try to drive the execution of your program to a number of processes that is as large as possible.

3 Report

Write a short (5-7 page) report in which you list for each test case that you run:

- the initial values of the correct processes
- the number of rounds used for reaching consensus
- the random values used by the correct processes in every round in which they cannot reach a decision

Also report what happens when running your program with a number of faulty processes that is too high. Don't include the algorithm itself or its explanation in the report.