

TCR

git diff solution (Jens Heuseveldt, Ludo Pulles, Pim Spelier)

CONTENTS

- 0.1. De winnende aanpak
- 0.2. Wrong Answer
- 0.3. Detecting overflow
- 0.4. Covering problems
- 0.5. Game theory
 - 1. Mathematics
 - 2. Datastructures
 - 2.2. Binary Indexed Tree $\mathcal{O}(\log n)$
 - 3. Graph Algorithms
 - 3.1. Maximum matching $\mathcal{O}(nm)$
 - 3.4. Shortest path
 - 3.5. Max-flow min-cut
 - 3.6. Min-cost max-flow
 - 3.7. Minimal Spanning Tree
 - 4. String algorithms
 - 4.3. Suffix array $\mathcal{O}(n \log^2 n)$
 - 4.4. Longest Common Subsequence $\mathcal{O}(n^2)$
 - 4.5. Levenshtein Distance $\mathcal{O}(n^2)$
 - 4.7. Aho-Corasick Algorithm $\mathcal{O}(N + \sum_{i=1}^m |S_i|)$
 - 5. Geometry
 - 5.2. Rotating Calipers $\mathcal{O}(n)$
 - 6. Miscellaneous
 - 6.2. Fast Fourier Transform $\mathcal{O}(n \log n)$

At the start of a contest, type this in a terminal:

```
1|printf "set nu sw=4 ts=4 sts=4 noet ai hls shellcmdflag=-ic\
|   nsy on | colo slate" > .vimrc
2|printf "\nalias gsubmit='g++ -Wall -Wshadow -std=c++11'" >> .
|   bashrc
3|printf "\nalias gll='gsubmit -DLOCAL -g'" >> .bashrc
4| . .bashrc
5|mkdir contest; cd contest
```

template.cpp

```
1|#include<bits/stdc++.h>
2|using namespace std;
3|
4|// Order statistics tree (if supported by judge!):
5|#include <ext/pb_ds/assoc_container.hpp>
6|#include <ext/pb_ds/tree_policy.hpp>
7|using namespace __gnu_pbds;
8|
9|template<class TK, class TM>
10|using order_tree = tree<TK, TM, less<TK>, rb_tree_tag,
|   tree_order_statistics_node_update>;
```

```
11|// iterator find_by_order(int r) (zero based)
12|// int order_of_key(TK v)
13|template<class TV> using order_set = order_tree<TV, null_type
|   >;
14|
15|#define x first
16|#define y second
17|#define pb push_back
18|#define eb emplace_back
19|#define rep(i,a,b) for(auto i=(a);i!=(b); ++i)
20|#define all(v) (v).begin(), (v).end()
21|#define rs resize
22|
23|typedef long long ll;
24|typedef pair<int, int> pii;
25|typedef vector<int> vi;
26|typedef vector<vi> vvi;
27|template<class T> using min_queue = priority_queue<T, vector<
|   T>, greater<T>>;
28|
29|const int INF = 2147483647; // (1 << 30) - 1 + (1 << 30)
30|const ll LLINF = (1LL << 62) - 1 + (1LL << 62); // =
|   9.223.372.036.854.775.807
31|const double PI = acos(-1.0);
32|
33|#ifdef LOCAL
34|#define DBG(x) cerr << __LINE__ << ": " << #x << " = " << (x)
|   << endl
35|#else
36|#define DBG(x)
37|const bool LOCAL = false;
38|#endif
39|
40|void Log() { if(LOCAL) cerr << "\n\n"; }
41|template<class T, class... S>
42|void Log(T t, S... s) { if(LOCAL) cerr << t << "\t", Log(s
|   ...); }
43|
44|// lambda-expression: [] (args) -> retType { body }
45|int main() {
46|    ios_base::sync_with_stdio(false); // fast IO
47|    cin.tie(NULL); // fast IO
48|    cerr << boolalpha; // print true/false
49|    (cout << fixed).precision(10); // adjust precision
50|
51|    return 0;
52|}
```

Prime numbers: 982451653 , 81253449 , $10^3 + \{-9, -3, 9, 13\}$, $10^6 + \{-17, 3, 33\}$, $10^9 + \{7, 9, 21, 33, 87\}$

0.1. De winnende aanpak.

- Goed slapen & een vroeg ritme hebben
- Genoeg drinken & eten voor en tijdens de wedstrijd
- Een lijst van alle problemen met info waar het over gaat, en wie het goed kan oplossen
- Ludo moet **ALLE** opgaves goed lezen
- Test de kleine voorbeeldgevallen
- Houd na 2 uur een pauze en overleg waar iedereen mee bezig is
- Maak zelf wat test-cases
- Typ de dingen uit de TCR, die je zeker nodig hebt, alvast in
- Als iemand niks te doen heeft, kan hij nodige dingen uit de TCR typen.

- We moeten ook een voorbeeld test-case voor TCR algoritmes hebben om te testen of het goed overgetypt is
- Bij geometrie moeten we om kunnen gaan met meerdere input manieren (voor bv. lijnen)
- Gebruik veel long long's

0.2. Wrong Answer.

- (1) Print de oplossing om te debuggen! Kijk ook naar andere (mogelijk makkelijkere) problemen.
- (2) Bedenk zelf test-cases met **randgevallen!**
- (3) Controleer op **overflow** (gebruik **OVERAL** long long, long double).
- (4) *Kijk naar overflows in tussenantwoorden bij modulo.* Controleer de **precisie**.
- (5) Controleer op **typo's**.
- (6) Loop de voorbeeldinput accuraat langs.
- (7) Controller op off-by-one-errors (in indices of lus-grenzen)?

0.3. **Detecting overflow.** These are GNU builtins, detect both overflow and underflow. Returns a boolean upon failure, otherwise the result is present in ref. Follow the template:

```
1|bool isOverflown = __builtin_[add|mul|sub]_overflow(a, b, &
|   res);
```

0.4. Covering problems.

Minimum edge cover \iff Maximum independent set

Matching: A set of edges without common vertices (*Maximum is the largest such set, maximal is a set which you cannot add more edges to without breaking the property*).

Minimum Vertex Cover: A set vertices (cover) such that each edge in the graph is incident to at least one vertex of the set.

Minimum Edge Cover: A set of edges (cover) such that every vertex is incident to at least one edge of the set.

Maximum Independent Set: A set of vertices in a graph such that no two of them are adjacent.

König's theorem: In any bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover

0.5. **Game theory.** A game can be reduced to Nim if it is a finite impartial game. Nim and its variants include:

Nim: Let $X = \bigoplus_{i=1}^n x_i$, then $(x_i)_{i=1}^n$ is a winning position iff $X \neq 0$. Find a move by picking k such that $x_k > x_k \oplus X$.

Misère Nim: Regular Nim, except that the last player to move *loses*. Play regular Nim until there is only one pile of size larger than 1, reduce it to 0 or 1 such that there is an odd number of piles.

Staricase Nim: Stones are moved down a staircase and only removed from the last pile. $(x_i)_{i=1}^n$ is an L -position if $(x_{2i-1})_{i=1}^{n/2}$ is (i.e. only look at odd-numbered piles).

Moore's Nim_k: The player may remove from at most k piles (Nim = Nim₁). Expand the piles in base 2, do a carry-less addition in base $k + 1$ (i.e. the number of ones in each column should be divisible by $k + 1$).

Dim⁺: The number of removed stones must be a divisor of the pile size. The Sprague-Grundy function is $k + 1$ where 2^k is the largest power of 2 dividing the pile size.

Aliquot game: Same as above, except the divisor should be proper (hence 1 is also a terminal state, but watch out for size 0 piles). Now the Sprague-Grundy function is just k .

Nim (at most half): Write $n + 1 = 2^m y$ with m maximal, then the Sprague-Grundy function of n is $(y - 1)/2$.

Lasker's Nim: Players may alternatively split a pile into two new non-empty piles. $g(4k + 1) = 4k + 1$, $g(4k + 2) = 4k + 2$, $g(4k + 3) = 4k + 4$, $g(4k + 4) = 4k + 3$ ($k \geq 0$).

Hackenbush on trees: A tree with stalks $(x_i)_{i=1}^n$ may be replaced with a single stalk with length $\bigoplus_{i=1}^n x_i$.

A useful identity: $\bigoplus_{x=0}^{a-1} x = \{0, a - 1, 1, a\}[a \bmod 4]$.

1. MATHEMATICS

```
1 int abs(int x) { return x > 0 ? x : -x; }
2 int sign(int x) { return (x > 0) - (x < 0); }
3
4 // greatest common divisor
5 ll gcd(ll a, ll b) { while (b) a %= b, swap(a, b); return a; }
6
7 // least common multiple
7 ll lcm(ll a, ll b) { return a / gcd(a, b) * b; }
8
8 ll mod(ll a, ll b) { return (a %= b) < 0 ? a + b : a; }
9
10 // safe multiplication (ab % m) for m <= 4e18 in O(log b)
11 ll mulmod(ll a, ll b, ll m) {
12     ll r = 0;
13     while (b) {
14         if (b & 1) r = (r + a) % m;
15         a = (a + a) % m;
16         b >>= 1;
17     }
18     return r;
19 }
20
21 // safe exponentation (a^b % m) for m <= 2e9 in O(log b)
22 ll powmod(ll a, ll b, ll m) {
23     ll r = 1;
24     while (b) {
25         if (b & 1) r = (r * a) % m; // r = mulmod(r, a, m);
26         a = (a * a) % m; // a = mulmod(a, a, m);
27         b >>= 1;
28     }
29     return r;
30 }
31
32 // returns x, y such that ax + by = gcd(a, b)
33 ll egcd(ll a, ll b, ll &x, ll &y) {
34     ll xx = y = 0, yy = x = 1;
35     while (b) {
36         x -= a / b * xx; swap(x, xx);
37         y -= a / b * yy; swap(y, yy);
38         a %= b; swap(a, b);
39     }
40     return a;
41 }
42
43 // Chinese remainder theorem
44 const pll NO_SOLUTION(0, -1);
45 // Returns (u, v) such that x = u % v <=> x = a % n and x = b % m
46 pll crt(ll a, ll n, ll b, ll m) {
47     ll s, t, d = egcd(n, m, s, t), nm = n * m;
48     if (mod(a - b, d)) return NO_SOLUTION;
```

```
49     return pll(mod(s * b * n + t * a * m, nm) / d, nm / d);
50     /* when n, m > 10^6, avoid overflow:
51     return pll(mod(mulmod(mulmod(s, b, nm), n, nm)
52         + mulmod(mulmod(t, a, nm), m, nm), nm) / d,
53         nm / d); */
54 }
55 // phi[i] = #{ 0 < j <= i | gcd(i, j) = 1 }
56 vi totient(int N) {
57     vi phi(N);
58     for (int i = 0; i < N; i++) phi[i] = i;
59     for (int i = 2; i < N; i++)
60         if (phi[i] == i)
61             for (int j = i; j < N; j += i) phi[j] -= phi[j] / i;
62     return phi;
63 }
64
65 // calculate nCk % p (p prime!)
66 ll lucas(ll n, ll k, ll p) {
67     ll ans = 1;
68     while (n) {
69         ll np = n % p, kp = k % p;
70         if (np < kp) return 0;
71         ans = mod(ans * binom(np, kp), p); // (np C kp)
72         n /= p; k /= p;
73     }
74     return ans;
75 }
76
77 // returns if n is prime for n < 3e24 ( > 2^64)
78 bool millerRabin(ll n)
79 {
80     if (n < 2 || n % 2 == 0) return n == 2;
81     ll d = n - 1, ad, s = 0, r;
82     for (; d % 2 == 0; d /= 2) s++;
83     for (int a : { 2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41 }) {
84         if (n == a) return true;
85         if ((ad = powmod(a, d, n)) == 1) continue;
86         for (r = 0; r < s && ad + 1 != n; r++)
87             ad = mulmod(ad, ad, n);
88         if (r == s) return false;
89     }
90     return true;
91 }
```

2. DATASTRUCTURES

```
1 typedef /* Tree element */ S;
2 const int n = 1 << 20;
3 S t[2 * n];
4
5 // required axiom: associativity
6 S combine(S l, S r) { return l + r; } // sum segment tree
7 S combine(S l, S r) { return max(l, r); } // max segment tree
8
9 void build() {
10     for (int i = n; --i; ) t[i] = combine(t[2 * i], t[2 * i + 1]);
11 }
12
13 // set value v on position i
```

```
14 void update(int i, S v) {
15     for (t[i += n] = v; i /= 2; ) t[i] = combine(t[2 * i], t[2 * i + 1]);
16 }
17
18 // sum on interval [l, r)
19 S query(int l, int r) {
20     S resL, resR;
21     for (l += n, r += n; l < r; l /= 2, r /= 2) {
22         if (l & 1) resL = combine(resL, t[l++]);
23         if (r & 1) resR = combine(t[--r], resR);
24     }
25     return combine(resL, resR);
26 }
```

2.2. Binary Indexed Tree $\mathcal{O}(\log n)$. Use one-based indices ($i > 0$)!

```
1 int bit[MAXN + 1];
2
3 // arr[i] += v
4 void update(int i, int v) {
5     while (i <= MAXN) bit[i] += v, i += i & -i;
6 }
7
8 // returns sum of arr[i], where i: [1, i]
9 int query(int i) {
10     int v = 0; while (i) v += bit[i], i -= i & -i; return v;
11 }
12
13 int par[MAXN], rnk[MAXN];
14
15 void uf_init(int n) {
16     fill_n(par, n, -1);
17     fill_n(rnk, n, 0);
18 }
19
20 int uf_find(int v) {
21     return par[v] < 0 ? v : par[v] = uf_find(par[v]);
22 }
23
24 void uf_union(int a, int b) {
25     if ((a = uf_find(a)) == (b = uf_find(b))) return;
26     if (rnk[a] < rnk[b]) swap(a, b);
27     if (rnk[a] == rnk[b]) rnk[a]++;
28     par[b] = a;
29 }
```

3. GRAPH ALGORITHMS

3.1. Maximum matching $\mathcal{O}(nm)$. This problem could be solved with a flow algorithm like Dinic's algorithm which runs in $\mathcal{O}(\sqrt{VE})$, too.

```
1 const int sizeL = 1e4, sizeR = 1e4;
2
3 bool vis[sizeR];
4 int par[sizeR]; // par : R -> L
5 vi adj[sizeL]; // adj : L -> (N -> R)
6
7 bool match(int u) {
```

```

8   for (int v : adj[u]) {
9       if (vis[v]) continue;
10      vis[v] = true;
11      if (par[v] == -1 || match(par[v])) {
12          par[v] = u;
13          return true;
14      }
15  }
16  return false;
17 }

19 // perfect matching iff ret == sizeL == sizeR
20 int maxmatch() {
21     fill_n(par, sizeR, -1);
22     int ret = 0;
23     for (int i = 0; i < sizeL; i++) {
24         fill_n(vis, sizeR, false);
25         ret += match(i);
26     }
27     return ret;
28 }

```

```

1 vvi adj, comps;
2 vi tidx, lnk, cnr, st;
3 vector<bool> vis;
4 int age, ncomps;

6 void tarjan(int v) {
7     tidx[v] = lnk[v] = ++age;
8     vis[v] = true;
9     st.pb(v);

11    for (int w : adj[v]) {
12        if (!tidx[w]) tarjan(w), lnk[v] = min(lnk[v], lnk[w]);
13    }

15    if (lnk[v] != tidx[v]) return;

17    comps.pb(vi());
18    int w;
19    do {
20        vis[w = st.back()] = false;
21        cnr[w] = ncomps;
22        comps.back().pb(w);
23        st.pop_back();
24    } while (w != v);
25    ncomps++;
26 }

28 void findSCC(int n) {
29     age = ncomps = 0;
30     vis.assign(n, false);
31     tidx.assign(n, 0);
32     lnk.resize(n);
33     cnr.resize(n);
34     comps.clear();

36     for (int i = 0; i < n; i++)
37         if (tidx[i] == 0) tarjan(i);
38 }
39 }

```

3.2.1. 2-SAT $\mathcal{O}(V + E)$. Include findSCC.

```

1 void init2sat(int n) { adj.assign(2 * n, vi()); }
2
3 // vl, vr = true -> variable l, variable r should be negated.
4 void imply(int xl, bool vl, int xr, bool vr) {
5     adj[2 * xl + vl].pb(2 * xr + vr);
6     adj[2 * xr + !vr].pb(2 * xl + !vl);
7 }
8
9 void satOr(int xl, bool vl, int xr, bool vr) { imply(xl, !vl,
10             xr, vr); }
11 void satConst(int x, bool v) { imply(x, !v, x, v); }
12 void satIff(int xl, bool vl, int xr, bool vr) {
13     imply(xl, vl, xr, vr);
14     imply(xr, vr, xl, vl);
15 }
16 bool solve2sat(int n, vector<bool> &sol) {
17     findSCC(2 * n);
18     for (int i = 0; i < n; i++)
19         if (cnr[2 * i] == cnr[2 * i + 1]) return false;
20     vector<bool> seen(n, false);
21     sol.assign(n, false);
22     for (vi &comp : comps) {
23         for (int v : comp) {
24             if (seen[v / 2]) continue;
25             seen[v / 2] = true;
26             sol[v / 2] = v & 1;
27         }
28     }
29     return true;
30 }

```

```

1 vvi adj; // assumes bidirected graph, adjust accordingly
2
3 bool cycle_detection() {
4     stack<int> s;
5     vector<bool> vis(MAXN, false);
6     vi par(MAXN, -1);
7     s.push(0);
8     vis[0] = true;
9     while(!s.empty()) {
10        int cur = s.top();
11        s.pop();
12        for(int i : adj[cur]) {
13            if(vis[i] && par[cur] != i) return true;
14            s.push(i);
15            par[i] = cur;
16            vis[i] = true;
17        }
18    }
19    return false;
20 }

```

3.4. Shortest path.

3.4.1. Dijkstra $\mathcal{O}(E + V \log V)$.

```

1 int n = 100;
2 ll d[MAXN][MAXN];
3 for (int i = 0; i < n; i++) fill_n(d[i], n, 1e18);
4 // set direct distances from i to j in d[i][j] (and d[j][i])
5 for (int i = 0; i < n; i++)
6     for (int j = 0; j < n; j++)
7         for (int k = 0; k < n; k++)
8             d[j][k] = min(d[j][k], d[j][i] + d[i][k]);

```

3.4.3. Bellman Ford $\mathcal{O}(VE)$. This is only useful if there are edges with weight $w_{ij} < 0$ in the graph.

```

1 vector<pair<pii, ll>> edges; // ((from, to), weight)
2 vector<ll> dist;
3
4 // when undirected, add back edges
5 bool bellman_ford(int V, int source) {
6     dist.assign(V, 1e18);
7     dist[source] = 0;
8
9     bool updated = true;
10    int loops = 0;
11    while (updated && loops < n) {
12        updated = false;
13        for (auto e : edges) {
14            int alt = dist[e.x.x] + e.y;
15            if (alt < dist[e.x.y]) {
16                dist[e.x.y] = alt;
17                updated = true;
18            }
19        }
20    }
21    return loops < n; // loops >= n: negative cycles
22 }

```

3.5. Max-flow min-cut.

```

1 struct edge {
2     int to, rev;
3     ll cap, flow;
4     edge(int t, int r, ll c) : to(t), rev(r), cap(c), flow(0) {}
5 };
6
7 int s, t, level[MAXN]; // s = source, t = sink
8 vector<edge> g[MAXN];
9
10 void add_edge(int fr, int to, ll cap) {
11     g[fr].pb(edge(to, g[to].size(), cap));
12     g[to].pb(edge(fr, g[fr].size() - 1, 0));
13 }
14
15 bool dinic_bfs() {
16     fill_n(level, MAXN, 0);
17     level[s] = 1;
18
19     queue<int> q;
20     q.push(s);
21     while (!q.empty()) {
22         int cur = q.front();
23         q.pop();
24         for (edge e : g[cur]) {

```

```

25         if (level[e.to] == 0 && e.flow < e.cap) {
26             level[e.to] = level[cur] + 1;
27             q.push(e.to);
28         }
29     }
30 }
31 return level[t] != 0;
32 }
33
34 ll dinic_dfs(int cur, ll maxf) {
35     if (cur == t) return maxf;
36
37     ll f = 0;
38     bool isSat = true;
39     for (edge &e : g[cur]) {
40         if (level[e.to] != level[cur] + 1 || e.flow >= e.cap)
41             continue;
42         ll df = dinic_dfs(e.to, min(maxf - f, e.cap - e.flow));
43         f += df;
44         e.flow -= df;
45         g[e.to][e.rev].flow += df;
46         isSat &= e.flow == e.cap;
47         if (maxf == f) break;
48     }
49     if (isSat) level[cur] = 0;
50     return f;
51 }
52
53 ll dinic_maxflow() {
54     ll f = 0;
55     while (dinic_bfs()) f += dinic_dfs(s, LLINF);
56     return f;
57 }

```

3.6. Min-cost max-flow. Find the cheapest possible way of sending a certain amount of flow through a flow network.

```

1 struct edge {
2     // to, rev, flow, capacity, weight
3     int t, r;
4     ll f, c, w;
5     edge(int _t, int _r, ll _c, ll _w) : t(_t), r(_r), f(0),
6         c(_c), w(_w) {}
7 };
8
9 int n, par[MAXN];
10 vector<edge> adj[MAXN];
11 ll dist[MAXN];
12
13 bool findPath(int s, int t) {
14     fill_n(dist, n, LLINF);
15     fill_n(par, n, -1);
16
17     priority_queue< pii, vector<pii>, greater<pii> > q;
18     q.push(pii(dist[s] = 0, s));
19
20     while (!q.empty()) {
21         int d = q.top().x, v = q.top().y;
22         q.pop();
23         if (d > dist[v]) continue;

```

```

24         for (edge e : adj[v]) {
25             if (e.f < e.c && d + e.w < dist[e.t]) {
26                 q.push(pii(dist[e.t] = d + e.w, e.t));
27                 par[e.t] = e.r;
28             }
29         }
30     }
31     return dist[t] < INF;
32 }
33
34 pair<ll, ll> minCostMaxFlow(int s, int t) {
35     ll cost = 0, flow = 0;
36     while (findPath(s, t)) {
37         ll f = INF, c = 0;
38         int cur = t;
39         while (cur != s) {
40             const edge &rev = adj[cur][par[cur]], &e = adj[
41                 rev.t][rev.r];
42             f = min(f, e.c - e.f);
43             cur = rev.t;
44         }
45         cur = t;
46         while (cur != s) {
47             edge &rev = adj[cur][par[cur]], &e = adj[rev.t][
48                 rev.r];
49             c += e.w;
50             e.f += f;
51             rev.f -= f;
52             cur = rev.t;
53         }
54         cost += f * c;
55         flow += f;
56     }
57     return pair<ll, ll>(cost, flow);
58 }
59
60 inline void addEdge(int from, int to, ll cap, ll weight) {
61     adj[from].pb(edge(to, adj[to].size(), cap, weight));
62     adj[to].pb(edge(from, adj[from].size() - 1, 0, -weight));
63 }

```

3.7. Minimal Spanning Tree.

3.7.1. Kruskal $\mathcal{O}(E \log V)$.

4. STRING ALGORITHMS

```

1 const int SIGMA = 26;
2
3 struct trie {
4     bool word;
5     trie **adj;
6
7     trie() : word(false), adj(new trie*[SIGMA]) {
8         for (int i = 0; i < SIGMA; i++) adj[i] = NULL;
9     }
10
11     void addWord(const string &str) {
12         trie *cur = this;
13         for (char ch : str) {
14             int i = ch - 'a';
15             if (!cur->adj[i]) cur->adj[i] = new trie();
16             cur = cur->adj[i];

```

```

17     }
18     cur->word = true;
19 }
20
21 bool isWord(const string &str) {
22     trie *cur = this;
23     for (char ch : str) {
24         int i = ch - 'a';
25         if (!cur->adj[i]) return false;
26         cur = cur->adj[i];
27     }
28     return cur->word;
29 }
30 };

```

```

1 // z[i] = length of longest substring starting from s[i]
2 // which is also a prefix of s.
3 vi z_function(const string &s) {
4     int n = (int) s.length();
5     vi z(n);
6     for (int i = 1, l = 0, r = 0; i < n; ++i) {
7         if (i <= r) z[i] = min(r - i + 1, z[i - l]);
8         while (i + z[i] < n && s[z[i]] == s[i + z[i]]) ++z[i];
9         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
10    }
11    return z;

```

4.3. Suffix array $\mathcal{O}(n \log^2 n)$. This creates an array $P[0], P[1], \dots, P[n-1]$ such that the suffix $S[i \dots n]$ is the $P[i]^{th}$ suffix of S when lexicographically sorted.

```

1 typedef pair<pii, int> tii;
2
3 const int maxlogn = 17, int maxn = 1 << maxlogn;
4
5 tii make_triple(int a, int b, int c) { return tii(pii(a, b),
6     c); }
7
8 int p[maxlogn + 1][maxn];
9 tii L[maxn];
10
11 int suffixArray(string S) {
12     int N = S.size(), stp = 1, cnt = 1;
13     for (int i = 0; i < N; i++) p[0][i] = S[i];
14     for (; cnt < N; stp++, cnt <= 1) {
15         for (int i = 0; i < N; i++) {
16             L[i] = tii(pii(p[stp-1][i], i + cnt < N ? p[stp-1][i + cnt] : -1), i);
17         }
18         sort(L, L + N);
19         for (int i = 0; i < N; i++) {
20             p[stp][L[i].y] = i > 0 && L[i].x == L[i-1].x ? p[
21                 stp][L[i-1].y] : i;
22         }
23     }
24     return stp - 1; // result is in p[stp - 1][0 .. (N - 1)]

```

4.4. Longest Common Subsequence $\mathcal{O}(n^2)$. SUBSTRING: consecutive characters !!!

```
1 int dp[STR_SIZE][STR_SIZE]; // DP problem
2
3 int lcs(const string &w1, const string &w2) {
4     int n1 = w1.size(), n2 = w2.size();
5     for (int i = 0; i < n1; i++) {
6         for (int j = 0; j < n2; j++) {
7             if (i == 0 || j == 0) dp[i][j] = 0;
8             else if (w1[i - 1] == w2[j - 1]) dp[i][j] = dp[i
9                 - 1][j - 1] + 1;
10            else dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
11        }
12    }
13    return dp[n1][n2];
14}
15
16 // backtrace
17 string getLCS(const string &w1, const string &w2) {
18     int i = w1.size(), j = w2.size();
19     string ret = "";
20     while (i > 0 && j > 0) {
21         if (w1[i - 1] == w2[j - 1]) ret += w1[--i], j--;
22         else if (dp[i][j - 1] > dp[i - 1][j]) j--;
23         else i--;
24     }
25     reverse(ret.begin(), ret.end());
26     return ret;
27 }
```

4.5. Levenshtein Distance $\mathcal{O}(n^2)$. Also known as the ‘Edit distance’.

```
1 int dp[MAX_SIZE][MAX_SIZE]; // DP problem
2
3 int levDist(const string &w1, const string &w2) {
4     int n1 = w1.size(), n2 = w2.size();
5     for (int i = 0; i <= n1; i++) dp[i][0] = i; // removal
6     for (int j = 0; j <= n2; j++) dp[0][j] = j; // insertion
7     for (int i = 1; i <= n1; i++)
8         for (int j = 1; j <= n2; j++)
9             dp[i][j] = min(
10                 1 + min(dp[i - 1][j], dp[i][j - 1]),
11                 dp[i - 1][j - 1] + (w1[i - 1] != w2[j - 1])
12             );
13     return dp[n1][n2];
14}
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
```

```
16 }
17 } else if (j > 0) j = T[j];
18 else i++;
19 }
20 return matches;
21 }
```

4.7. Aho-Corasick Algorithm $\mathcal{O}(N + \sum_{i=1}^m |S_i|)$. All given P must be unique!

```
1 const int MAXP = 100, MAXLEN = 200, SIGMA = 26, MAXTRIE =
2     MAXP * MAXLEN;
3 int nP;
4 string P[MAXP], S;
5
6 int pnr[MAXTRIE], to[MAXTRIE][SIGMA], sLink[MAXTRIE], dLink[
7     MAXTRIE], nnodes;
8 void ahoCorasick() {
9     fill_n(pnr, MAXTRIE, -1);
10    for (int i = 0; i < MAXTRIE; i++) fill_n(to[i], SIGMA, 0)
11        ;
12    fill_n(sLink, MAXTRIE, 0);
13    fill_n(dLink, MAXTRIE, 0);
14    nnodes = 1;
15    // STEP 1: MAKE A TREE
16    for (int i = 0; i < nP; i++) {
17        int cur = 0;
18        for (char c : P[i]) {
19            int i = c - 'a';
20            if (to[cur][i] == 0) to[cur][i] = nnodes++;
21            cur = to[cur][i];
22        }
23        pnr[cur] = i;
24    }
25    // STEP 2: CREATE SUFFIX_LINKS AND DICT_LINKS
26    queue<int> q;
27    q.push(0);
28    while (!q.empty()) {
29        int cur = q.front();
30        q.pop();
31        for (int c = 0; c < SIGMA; c++) {
32            if (to[cur][c]) {
33                int sl = sLink[to[cur][c]] = cur == 0 ? 0 :
34                    to[sLink[cur]][c];
35                // if all strings have equal length, remove
36                this:
37                dLink[to[cur][c]] = pnr[sl] >= 0 ? sl : dLink
38                    [sl];
39                q.push(to[cur][c]);
40            } else to[cur][c] = to[sLink[cur]][c];
41        }
42    }
43    // STEP 3: TRAVERSE S
44    for (int cur = 0, i = 0, n = S.size(); i < n; i++) {
45        cur = to[cur][S[i] - 'a'];
46        for (int hit = pnr[cur] >= 0 ? cur : dLink[cur]; hit;
47            hit = dLink[hit]) {
48            cerr << P[pnr[hit]] << " found at [" << (i + 1 -
49                P[pnr[hit]].size()) << ", " << i << "]" << endl;
50        }
51    }
52 }
```

5. GEOMETRY

```
1 const double EPS = 1e-7, PI = acos(-1.0);
2
3 typedef long long NUM; // EITHER double OR long long
4 typedef pair<NUM, NUM> pt;
5 #define x first
6 #define y second
7
8 pt operator+(pt p, pt q) { return pt(p.x + q.x, p.y + q.y); }
9 pt operator-(pt p, pt q) { return pt(p.x - q.x, p.y - q.y); }
10
11 pt& operator+=(pt &p, pt q) { return p = p + q; }
12 pt& operator-=(pt &p, pt q) { return p = p - q; }
13
14 pt operator*(pt p, NUM l) { return pt(p.x * l, p.y * l); }
15 pt operator/(pt p, NUM l) { return pt(p.x / l, p.y / l); }
16
17 NUM operator*(pt p, pt q) { return p.x * q.x + p.y * q.y; }
18 NUM operator^(pt p, pt q) { return p.x * q.y - p.y * q.x; }
19
20 istream& operator>>(istream &in, pt &p) { return in >> p.x >>
21     p.y; }
22 ostream& operator<<(ostream &out, pt p) { return out << '('
23     << p.x << ", " << p.y << ')'; }
24
25 NUM lenSq(pt p) { return p * p; }
26 NUM lenSq(pt p, pt q) { return lenSq(p - q); }
27 double len(pt p) { return hypot(p.x, p.y); } // more overflow
28 safe
29 double len(pt p, pt q) { return len(p - q); }
30
31 typedef pt frac;
32 typedef pair<double, double> vec;
33 vec getvec(pt p, pt dp, frac t) { return vec(p.x + 1. * dp.x
34     * t.x / t.y, p.y + 1. * dp.y * t.x / t.y); }
35
36 // square distance from pt a to line bc
37 frac distPtLineSq(pt a, pt b, pt c) {
38     a -= b, c -= b;
39     return frac((a ^ c) * (a ^ c), c * c);
40 }
41
42 // square distance from pt a to line segment bc
43 frac distPtSegmentSq(pt a, pt b, pt c) {
44     a -= b, c -= b;
45     NUM dot = a * c, len = c * c;
46     if (dot <= 0) return frac(a * a, 1);
47     if (dot >= len) return frac((a - c) * (a - c), 1);
48     return frac(a * a * len - dot * dot, len);
49 }
50
51 // projects pt a onto line segment bc
52 frac proj(pt a, pt b, pt c) { return frac((a - b) * (c - b),
53     (c - b) * (c - b)); }
54 vec projv(pt a, pt b, pt c) { return getvec(b, c - b, proj(a,
55     b, c)); }
56 }
```

```

51 | bool collinear(pt a, pt b, pt c) { return ((a - b) ^ (a - c))
    | == 0; }
52 |
53 | bool pointOnSegment(pt a, pt b, pt c) {
54 |     NUM dot = (a - b) * (c - b), len = (c - b) * (c - b);
55 |     return collinear(a, b, c) && 0 <= dot && dot <= len;
56 | }
57 |
58 | // true => 1 intersection, false => parallel, so 0 or \infy
    | solutions
59 | bool linesIntersect(pt a, pt b, pt c, pt d) { return ((a - b)
    | ^ (c - d)) != 0; }
60 | vec lineLineIntersection(pt a, pt b, pt c, pt d) {
61 |     double det = (a - b) ^ (c - d);
62 |     pt ret = (c - d) * (a ^ b) - (a - b) * (c ^ d);
63 |     return vec(ret.x / det, ret.y / det);
64 | }
65 |
66 | // dp, dq are directions from p, q
67 | // intersection at p + t_i dp, for 0 <= i < return value
68 | int segmentIntersection(pt p, pt dp, pt q, pt dq, frac &t0,
    | frac &t1)
69 | {
70 |     if (dp * dp == 0) swap(p, q), swap(dp, dq); // dq = 0
71 |     if (dp * dp == 0) { t0 = t1 = frac(0, 1); return p == q;
    | } // dp = dq = 0
72 |
73 |     pt dpq = (q - p);
74 |     NUM c = dp ^ dq, c0 = dpq ^ dp, c1 = dpq ^ dq;
75 |     if (c == 0) { // parallel, dp > 0, dq >= 0
76 |         if (c0 != 0) return 0; // not collinear
77 |         NUM v0 = dpq * dp, v1 = v0 + dq * dp, dp2 = dp * dp;
78 |         if (v1 < v0) swap(v0, v1);
79 |         t0 = frac(v0 = max(v0, (NUM) 0), dp2);
80 |         t1 = frac(v1 = min(v1, dp2), dp2);
81 |         return (v0 <= v1) + (v0 < v1);
82 |     } else if (c < 0) c = -c, c0 = -c0, c1 = -c1;
83 |     t0 = t1 = frac(c1, c);
84 |     return 0 <= min(c0, c1) && max(c0, c1) <= c;
85 | }
86 |
87 | // Returns TWICE the area of a polygon to keep it an integer
88 | NUM polygonTwiceArea(const vector<pt> &pts) {
89 |     NUM area = 0;
90 |     for (int N = pts.size(), i = 0, j = N - 1; i < N; j = i
    | ++))
91 |         area += pts[i] ^ pts[j];
92 |     return abs(area); // area < 0 <=> pts ccw
93 | }
94 |
95 | bool pointInPolygon(pt p, const vector<pt> &pts) {
96 |     double sum = 0;
97 |     for (int N = pts.size(), i = 0, j = N - 1; i < N; j = i
    | ++)) {
98 |         if (pointOnSegment(p, pts[i], pts[j])) return true;
99 |         // boundary
100 |         double angle = acos((pts[i] - p) * (pts[j] - p) / len
    | (pts[i], p) / len(pts[j], p));
101 |         sum += ((pts[i] - p) ^ (pts[j] - p)) < 0 ? angle : -
    | angle;
102 |     }
    | return abs(abs(sum) - 2 * PI) < EPS;

```

```

1 | // points are given by: pts[ret[0]], pts[ret[1]], ... pts[ret
    | [ret.size()-1]]
2 | vi convexHull(const vector<pt> &pts) {
3 |     if (pts.empty()) return vi();
4 |     vi ret;
5 |     // find one outer point:
6 |     int fsti = 0, n = pts.size();
7 |     pt fstpt = pts[0];
8 |     for(int i = n; i--;) {
9 |         if (pts[i] < fstpt) fstpt = pts[fsti = i];
10 |     }
11 |     ret.pb(fsti);
12 |     pt refr = pts[fsti];
13 |
14 |     vi ord; // index into pts
15 |     for (int i = n; i--;) {
16 |         if (pts[i] != refr) ord.pb(i);
17 |     }
18 |     sort(ord.begin(), ord.end(), [&pts, &refr] (int a, int b)
    | -> bool {
19 |         NUM cross = (pts[a] - refr) ^ (pts[b] - refr);
20 |         return cross != 0 ? cross > 0 : lenSq(refr, pts[a]) <
    | lenSq(refr, pts[b]);
21 | });
22 |     for (int i : ord) {
23 |         // NOTE: > INCLUDES points on the hull-line, >=
    | EXCLUDES
24 |         while (ret.size() > 1 &&
    | ((pts[ret[ret.size()-2]]-pts[ret.back()]) ^ (
    | pts[i]-pts[ret.back()])) >= 0)
25 |             ret.pop_back();
26 |         ret.pb(i);
27 |     }
28 |     return ret;
29 | }
30 | }

```

5.2. Rotating Calipers $\mathcal{O}(n)$. Finds the longest distance between two points in a convex hull.

```

1 | NUM rotatingCalipers(vector<pt> &hull) {
2 |     int n = hull.size(), a = 0, b = 1;
3 |     if (n <= 1) return 0.0;
4 |     while (((hull[1] - hull[0]) ^ (hull[(b + 1) % n] - hull[b
    | ])) > 0) b++;
5 |     NUM ret = 0.0;
6 |     while (a < n) {
7 |         ret = max(ret, lenSq(hull[a], hull[b]));
8 |         if (((hull[(a + 1) % n] - hull[a % n]) ^ (hull[(b +
    | 1) % n] - hull[b])) <= 0) a++;
9 |         else if (++b == n) b = 0;
10 |     }
11 |     return ret;
12 | }

```

```

1 | int n;
2 | pt pts[maxn];
3 |
4 | struct byY {
5 |     bool operator()(int a, int b) const { return pts[a].y <
    | pts[b].y; }

```

```

6 | };
7 |
8 | inline NUM dist(pii p) {
9 |     return hypot(pts[p.x].x - pts[p.y].x, pts[p.x].y - pts[p.
    | y].y);
10 | }
11 |
12 | pii minpt(pii p1, pii p2) {
13 |     return (dist(p1) < dist(p2)) ? p1 : p2;
14 | }
15 |
16 | // closest pts (by index) inside pts[l ... r], with sorted y
    | values in ys
17 | pii closest(int l, int r, vi &ys) {
18 |     if (r - l == 2) { // don't assume 1 here.
19 |         ys = { l, l + 1 };
20 |         return pii(l, l + 1);
21 |     } else if (r - l == 3) { // brute-force
22 |         ys = { l, l + 1, l + 2 };
23 |         sort(ys.begin(), ys.end(), byY());
24 |         return minpt(pii(l, l + 1), minpt(pii(l, l + 2), pii(
    | l + 1, l + 2)));
25 |     }
26 |     int m = (l + r) / 2;
27 |     vi yl, yr;
28 |     pii delta = minpt(closest(l, m, yl), closest(m, r, yr));
29 |     NUM ddelta = dist(delta), xm = .5 * (pts[m-1].x + pts[m].
    | x);
30 |     merge(yl.begin(), yl.end(), yr.begin(), yr.end(),
    | back_inserter(ys), byY());
31 |     deque<int> q;
32 |     for (int i : ys) {
33 |         if (abs(pts[i].x - xm) <= ddelta) {
34 |             for (int j : q) delta = minpt(delta, pii(i, j));
35 |             q.pb(i);
36 |             if (q.size() > 8) q.pop_front(); // magic from
    | Introduction to Algorithms.
37 |         }
38 |     }
39 |     return delta;
40 | }

```

6. MISCELLANEOUS

```

1 | bool test(int n);
2 |
3 | int search(int lo, int hi) {
4 |     // assert(test(lo) && !test(hi));
5 |     while (hi - lo > 1) {
6 |         int m = (lo + hi) / 2;
7 |         (test(m) ? lo : hi) = m;
8 |     }
9 |     // assert(test(lo) && !test(hi));
10 |     return lo;
11 | }

```


6.2. **Fast Fourier Transform** $\mathcal{O}(n \log n)$. Given two polynomials $A(x) = a_0 + a_1x + \dots + a_{n/2}x^{n/2}$ and $B(x) = b_0 + b_1x + \dots + b_{n/2}x^{n/2}$, FFT calculates all coefficients of $C(x) = A(x) \cdot B(x) = c_0 + c_1x + \dots + c_nx^n$, with $c_i = \sum_{j=0}^i a_j b_{i-j}$.

```
1 typedef complex<double> cpx;
2 const int logmaxn = 20, maxn = 1 << logmaxn;
3
4 cpx a[maxn] = {}, b[maxn] = {}, c[maxn];
5
6 void fft(cpx *src, cpx *dest) {
7     for (int i = 0, rep = 0; i < maxn; i++, rep = 0) {
8         for (int j = i, k = logmaxn; k-- >= 1; rep = (rep
9             << 1) | (j & 1);
10             dest[rep] = src[i];
11     }
12     for (int s = 1, m = 1; m <= maxn; s++, m *= 2) {
13         cpx r = exp(cpx(0, 2.0 * PI / m));
14         for (int k = 0; k < maxn; k += m) {
15             cpx cr(1.0, 0.0);
16             for (int j = 0; j < m / 2; j++) {
17                 cpx t = cr * dest[k + j + m / 2];
18                 dest[k + j + m / 2] = dest[k + j] - t;
19                 dest[k + j] += t;
20                 cr *= r;
21             }
22         }
23     }
24 }
25 void multiply() {
26     fft(a, c);
27     fft(b, a);
28     for (int i = 0; i < maxn; i++) b[i] = conj(a[i] * c[i]);
29     fft(b, c);
30     for (int i = 0; i < maxn; i++) c[i] = conj(c[i]) / (1.0 *
31         maxn);
32 }
```

```
1 int a[MAXN + 1][MAXM + 1]; // matrix, 1-based
2
3 int minimum_assignment(int n, int m) { // n rows, m columns
4     vi u(n + 1), v(m + 1), p(m + 1), way(m + 1);
5
6     for (int i = 1; i <= n; i++) {
7         p[0] = i;
8         int j0 = 0;
9         vi minv(m + 1, INF);
10        vector<char> used(m + 1, false);
11        do {
12            used[j0] = true;
13            int i0 = p[j0], delta = INF, j1;
14            for (int j = 1; j <= m; j++)
15                if (!used[j]) {
16                    int cur = a[i0][j] - u[i0] - v[j];
17                    if (cur < minv[j]) minv[j] = cur, way[j]
18                        = j0;
19                    if (minv[j] < delta) delta = minv[j], j1
20                        = j;
21                }
22            for (int j = 0; j <= m; j++) {
23                if (used[j]) u[p[j]] += delta, v[j] -= delta;
```

```
22         else minv[j] -= delta;
23     }
24     j0 = j1;
25     while (p[j0] != 0);
26     do {
27         int j1 = way[j0];
28         p[j0] = p[j1];
29         j0 = j1;
30     } while (j0);
31 }
32
33 // column j is assigned to row p[j]
34 // for (int j = 1; j <= m; ++ j) ans[p[j]] = j;
35 return -v[0];
36 }
```

```
1 typedef double NUM;
2
3 #define MAXN 110
4 #define EPS 1e-5
5
6 NUM mat[MAXN][MAXN + 1], vals[MAXN];
7 bool hasval[MAXN];
8
9 bool is_zero(NUM a) { return -EPS < a && a < EPS; }
10 bool eq(NUM a, NUM b) { return is_zero(a - b); }
11
12 int solvemmat(int n)
13 {
14     for (int i = 0; i < n; i++)
15         for (int j = 0; j < n; j++) cin >> mat[i][j];
16     for (int i = 0; i < n; i++) cin >> mat[i][n];
17
18     int pivrow = 0, pivcol = 0;
19     while (pivcol < n) {
20         int r = pivrow, c;
21         while (r < n && is_zero(mat[r][pivcol])) r++;
22         if (r == n) { pivcol++; continue; }
23
24         for (c = 0; c <= n; c++) swap(mat[pivrow][c], mat[r][
25             c]);
26
27         r = pivrow++; c = pivcol++;
28         NUM div = mat[r][c];
29         for (int col = c; col <= n; col++) mat[r][col] /= div
30             ;
31         for (int row = 0; row < n; row++) {
32             if (row == r) continue;
33             NUM times = -mat[row][c];
34             for (int col = c; col <= n; col++) mat[row][col]
35                 += times * mat[r][col];
36         }
37         // now mat is in RREF
38         for (int r = pivrow; r < n; r++)
39             if (!is_zero(mat[r][n])) return 0;
40
41         fill_n(hasval, n, false);
42         for (int col = 0, row; col < n; col++) {
43             hasval[col] = !is_zero(mat[row][col]);
44             if (!hasval[col]) continue;
```

```
43         for (int c = col + 1; c < n; c++) {
44             if (!is_zero(mat[row][c])) hasval[col] = false;
45         }
46         if (hasval[col]) vals[col] = mat[row][n];
47         row++;
48     }
49
50     for (int i = 0; i < n; i++)
51         if (!hasval[i]) return 2;
52     return 1;
53 }
```

