

TCR

TCR

CONTENTS

- 0.1. De winnende aanpak
- 0.2. Wrong Answer
- 0.3. Detecting overflow
- 0.4. Covering problems
- 0.5. Game theory
1. Mathematics
2. Datastructures
- 2.1. Standard segment tree $\mathcal{O}(\log n)$
- 2.2. Binary Indexed Tree $\mathcal{O}(\log n)$
- 2.3. Disjoint-Set / Union-Find $\mathcal{O}(\alpha(n))$
3. Graph Algorithms
- 3.1. Maximum matching $\mathcal{O}(nm)$
- 3.2. Strongly Connected Components $\mathcal{O}(V + E)$
- 3.3. Cycle Detection $\mathcal{O}(V + E)$
- 3.4. Shortest path
- 3.5. Max-flow min-cut
- 3.6. Min-cost max-flow
- 3.7. Minimal Spanning Tree
4. String algorithms
- 4.1. Trie
- 4.2. Z-algorithm $\mathcal{O}(n)$
- 4.3. Suffix array $\mathcal{O}(n \log^2 n)$
- 4.4. Longest Common Subsequence $\mathcal{O}(n^2)$
- 4.5. Levenshtein Distance $\mathcal{O}(n^2)$
- 4.6. Knuth-Morris-Pratt algorithm $\mathcal{O}(N + M)$
- 4.7. Aho-Corasick Algorithm $\mathcal{O}(N + \sum_{i=1}^m |S_i|)$
5. Geometry
- 5.1. Convex Hull $\mathcal{O}(n \log n)$
- 5.2. Rotating Calipers $\mathcal{O}(n)$
- 5.3. Closest points $\mathcal{O}(n \log n)$
6. Miscellaneous
- 6.1. Binary search $\mathcal{O}(\log(hi - lo))$
- 6.2. Fast Fourier Transform $\mathcal{O}(n \log n)$
- 6.3. Minimum Assignment (Hungarian Algorithm) $\mathcal{O}(n^3)$
- 6.4. Partial linear equation solver $\mathcal{O}(N^3)$

At the start of a contest, type this in a terminal:

```
1 printf "set nu sw=4 ts=4 sts=4 noet ai hls shellcmdflag=-ic\nsy on |
   colo slate" > .vimrc
2 printf "\nalias gsubmit='g++ -Wall -Wshadow -std=c++11'" >> .bashrc
3 printf "\nalias gll='gsubmit -DLOCAL -g'" >> .bashrc
4 . .bashrc
5 mkdir contest; cd contest
```

template.cpp

```
1 #include<bits/stdc++.h>
2 using namespace std;
3
4 // Order statistics tree (if supported by judge!):
5 #include <ext/pb_ds/assoc_container.hpp>
6 #include <ext/pb_ds/tree_policy.hpp>
7 using namespace __gnu_pbds;
8
9 template<class TK, class TM>
10 using order_tree = tree<TK, TM, less<TK>, rb_tree_tag,
   tree_order_statistics_node_update>;
11 // iterator find_by_order(int r) (zero based)
12 // int order_of_key(TK v)
13 template<class TV> using order_set = order_tree<TV, null_type>;
14
15 #define x first
16 #define y second
17 #define pb push_back
18 #define eb emplace_back
19 #define rep(i,a,b) for(auto i=(a);i!=(b); ++i)
20 #define all(v) (v).begin(), (v).end()
21 #define rs resize
22
23 typedef long long ll;
24 typedef pair<int, int> pii;
25 typedef vector<int> vi;
26 typedef vector<vi> vvi;
27 template<class T> using min_queue = priority_queue<T, vector<T>,
   greater<T>>;
28
29 const int INF = 2147483647; // (1 << 30) - 1 + (1 << 30)
30 const ll LLINF = (1LL << 62) - 1 + (1LL << 62); // =
   9.223.372.036.854.775.807
31 const double PI = acos(-1.0);
32
33 #ifdef LOCAL
34 #define DBG(x) cerr << __LINE__ << ": " << #x << " = " << (x) << endl
35 #else
36 #define DBG(x)
37 const bool LOCAL = false;
38 #endif
39
40 void Log() { if(LOCAL) cerr << "\n\n"; }
41 template<class T, class... S>
42 void Log(T t, S... s) { if(LOCAL) cerr << t << "\t", Log(s...); }
43
44 // lambda-expression: [] (args) -> retType { body }
45 int main() {
46     ios_base::sync_with_stdio(false); // fast IO
47     cin.tie(NULL); // fast IO
48     cerr << boolalpha; // print true/false
49     (cout << fixed).precision(10); // adjust precision
50
51     return 0;
52 }
```

Prime numbers: 982451653 , 81253449 , $10^3 + \{-9, -3, 9, 13\}$, $10^6 + \{-17, 3, 33\}$, $10^9 + \{7, 9, 21, 33, 87\}$

0.1. De winnende aanpak.

- Goed slapen & een vroeg ritme hebben
- Genoeg drinken & eten voor en tijdens de wedstrijd
- Een lijst van alle problemen met info waar het over gaat, en wie het goed kan oplossen
- Ludo moet **ALLE** opgaves goed lezen
- Test de kleine voorbeeldgevallen
- Houd na 2 uur een pauze en overleg waar iedereen mee bezig is
- Maak zelf wat test-cases
- Typ de dingen uit de TCR, die je zeker nodig hebt, alvast in
- Als iemand niks te doen heeft, kan hij nodige dingen uit de TCR typen.
- We moeten ook een voorbeeld test-case voor TCR algoritmes hebben om te testen of het goed overgetypt is
- Bij geometrie moeten we om kunnen gaan met meerdere input manieren (voor bv. lijnen)

- Gebruik veel long long's

0.2. Wrong Answer.

- (1) Print de oplossing om te debuggen! Kijk ook naar andere (mogelijk makkelijkere) problemen.
- (2) Bedenk zelf test-cases met **randgevallen!**
- (3) Controleer op **overflow** (gebruik **OVERAL** long long, long double).
- (4) *Kijk naar overflows in tussenantwoorden bij modulo.* Controleer de **precisie**.
- (5) Controleer op **typo's**.
- (6) Loop de voorbeeldinput accuraat langs.
- (7) Controller op off-by-one-errors (in indices of lus-grenzen)?

0.3. Detecting overflow. These are GNU builtins, detect both overflow and underflow. Returns a boolean upon failure, otherwise the result is present in ref. Follow the template:

```
1 bool isOverflowed = __builtin_[add|mul|sub]_overflow(a, b, \&res);
```

0.4. Covering problems.

Minimum edge cover \iff Maximum independent set

Matching: A set of edges without common vertices (*Maximum is the largest such set, maximal is a set which you cannot add more edges to without breaking the property*).

Minimum Vertex Cover: A set vertices (cover) such that each edge in the graph is incident to at least one vertex of the set.

Minimum Edge Cover: A set of edges (cover) such that every vertex is incident to at least one edge of the set.

Maximum Independent Set: A set of vertices in a graph such that no two of them are adjacent.

König's theorem: In any bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover

0.5. Game theory. A game can be reduced to Nim if it is a finite impartial game. Nim and its variants include:

Nim: Let $X = \bigoplus_{i=1}^n x_i$, then $(x_i)_{i=1}^n$ is a winning position iff $X \neq 0$. Find a move by picking k such that $x_k > x_k \oplus X$.

Misère Nim: Regular Nim, except that the last player to move *loses*. Play regular Nim until there is only one pile of size larger than 1, reduce it to 0 or 1 such that there is an odd number of piles.

Staricase Nim: Stones are moved down a staircase and only removed from the last pile. $(x_i)_{i=1}^n$ is an L -position if $(x_{2i-1})_{i=1}^{n/2}$ is (i.e. only look at odd-numbered piles).

Moore's Nim_k: The player may remove from at most k piles (Nim = Nim₁). Expand the piles in base 2, do a carry-less addition in base $k + 1$ (i.e. the number of ones in each column should be divisible by $k + 1$).

Dim⁺: The number of removed stones must be a divisor of the pile size. The Sprague-Grundy function is $k + 1$ where 2^k is the largest power of 2 dividing the pile size.

Aliquot game: Same as above, except the divisor should be proper (hence 1 is also a terminal state, but watch out for size 0 piles). Now the Sprague-Grundy function is just k .

Nim (at most half): Write $n + 1 = 2^m y$ with m maximal, then the Sprague-Grundy function of n is $(y - 1)/2$.

Lasker's Nim: Players may alternatively split a pile into two new non-empty piles. $g(4k + 1) = 4k + 1$, $g(4k + 2) = 4k + 2$, $g(4k + 3) = 4k + 4$, $g(4k + 4) = 4k + 3$ ($k \geq 0$).

Hackenbush on trees: A tree with stalks $(x_i)_{i=1}^n$ may be replaced with a single stalk with length $\bigoplus_{i=1}^n x_i$.

A useful identity: $\bigoplus_{x=0}^{a-1} x = \{0, a-1, 1, a\}[a \bmod 4]$.

1. MATHEMATICS

```
1 int abs(int x) { return x > 0 ? x : -x; }
2 int sign(int x) { return (x > 0) - (x < 0); }
3
4 // greatest common divisor
5 ll gcd(ll a, ll b) { while (b) a %= b, swap(a, b); return a; }
6 // least common multiple
7 ll lcm(ll a, ll b) { return a / gcd(a, b) * b; }
8 ll mod(ll a, ll b) { return (a %= b) < 0 ? a + b : a; }
9
10 // safe multiplication (ab % m) for m <= 4e18 in O(log b)
11 ll mulmod(ll a, ll b, ll m) {
12     ll r = 0;
13     while (b) {
14         if (b & 1) r = (r + a) % m;
15         a = (a + a) % m;
16         b >>= 1;
17     }
18     return r;
19 }
20
21 // safe exponentation (a^b % m) for m <= 2e9 in O(log b)
22 ll powmod(ll a, ll b, ll m) {
23     ll r = 1;
24     while (b) {
25         if (b & 1) r = (r * a) % m; // r = mulmod(r, a, m);
26         a = (a * a) % m; // a = mulmod(a, a, m);
27         b >>= 1;
28     }
29     return r;
30 }
31
32 // returns x, y such that ax + by = gcd(a, b)
33 ll egcd(ll a, ll b, ll &x, ll &y) {
34     ll xx = y = 0, yy = x = 1;
35     while (b) {
36         x -= a / b * xx; swap(x, xx);
37         y -= a / b * yy; swap(y, yy);
38         a %= b; swap(a, b);
39     }
40     return a;
41 }
42
43 // Chinese remainder theorem
44 const pll NO_SOLUTION(0, -1);
45 // Returns (u, v) such that x = u % v <=> x = a % n and x = b % m
46 pll crt(ll a, ll n, ll b, ll m) {
47     ll s, t, d = egcd(n, m, s, t), nm = n * m;
48     if (mod(a - b, d)) return NO_SOLUTION;
49     return pll(mod(s * b * n + t * a * m, nm) / d, nm / d);
50     /* when n, m > 10^6, avoid overflow:
51     return pll(mod(mulmod(mulmod(s, b, nm), n, nm)
52         + mulmod(mulmod(t, a, nm), m, nm), nm) / d, nm / d);
53     */
54 }
55 // phi[i] = #{ 0 < j <= i | gcd(i, j) = 1 }
56 vi totient(int N) {
57     vi phi(N);
58     for (int i = 0; i < N; i++) phi[i] = i;
59     for (int i = 2; i < N; i++)
60         if (phi[i] == i)
61             for (int j = i; j < N; j += i) phi[j] -= phi[j] / i;
62     return phi;
63 }
64
65 // calculate nCk % p (p prime!)
66 ll lucas(ll n, ll k, ll p) {
67     ll ans = 1;
68     while (n) {
69         ll np = n % p, kp = k % p;
70         if (np < kp) return 0;
71         ans = mod(ans * binom(np, kp), p); // (np C kp)
```

```
72         n /= p; k /= p;
73     }
74     return ans;
75 }
76
77 // returns if n is prime for n < 3e24 ( > 2^64)
78 bool millerRabin(ll n)
79 {
80     if (n < 2 || n % 2 == 0) return n == 2;
81     ll d = n - 1, ad, s = 0, r;
82     for (; d % 2 == 0; d /= 2) s++;
83     for (int a : { 2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41 }) {
84         if (n == a) return true;
85         if ((ad = powmod(a, d, n)) == 1) continue;
86         for (r = 0; r < s && ad + 1 != n; r++)
87             ad = mulmod(ad, ad, n);
88         if (r == s) return false;
89     }
90     return true;
91 }
```

2. DATASTRUCTURES

```
2.1. Standard segment tree O(log n).
1 typedef /* Tree element */ S;
2 const int n = 1 << 20;
3 S t[2 * n];
4
5 // required axiom: associativity
6 S combine(S l, S r) { return l + r; } // sum segment tree
7 S combine(S l, S r) { return max(l, r); } // max segment tree
8
9 void build() {
10     for (int i = n; --i; ) t[i] = combine(t[2 * i], t[2 * i + 1]);
11 }
12
13 // set value v on position i
14 void update(int i, S v) {
15     for (t[i += n] = v; i /= 2; ) t[i] = combine(t[2 * i], t[2 * i + 1]);
16 }
17
18 // sum on interval [l, r)
19 S query(int l, int r) {
20     S resL, resR;
21     for (l += n, r += n; l < r; l /= 2, r /= 2) {
22         if (l & 1) resL = combine(resL, t[l++]);
23         if (r & 1) resR = combine(t[--r], resR);
24     }
25     return combine(resL, resR);
26 }
```

2.2. Binary Indexed Tree O(log n). Use one-based indices (i > 0)!

```
1 int bit[MAXN + 1];
2
3 // arr[i] += v
4 void update(int i, int v) {
5     while (i <= MAXN) bit[i] += v, i += i & -i;
6 }
7
8 // returns sum of arr[i], where i: [1, i]
9 int query(int i) {
10     int v = 0; while (i) v += bit[i], i -= i & -i; return v;
11 }
```

2.3. Disjoint-Set / Union-Find O(α(n)).

```
1 int par[MAXN], rnk[MAXN];
2
3 void uf_init(int n) {
4     fill_n(par, n, -1);
5     fill_n(rnk, n, 0);
6 }
7
8 int uf_find(int v) {
9     return par[v] < 0 ? v : par[v] = uf_find(par[v]);
10 }
11
```

```
12 void uf_union(int a, int b) {
13     if ((a = uf_find(a)) == (b = uf_find(b))) return;
14     if (rnk[a] < rnk[b]) swap(a, b);
15     if (rnk[a] == rnk[b]) rnk[a]++;
16     par[b] = a;
17 }
```

3. GRAPH ALGORITHMS

3.1. Maximum matching $\mathcal{O}(nm)$. This problem could be solved with a flow algorithm like Dinic's algorithm which runs in $\mathcal{O}(\sqrt{VE})$, too.

```
1 const int sizeL = 1e4, sizeR = 1e4;
2
3 bool vis[sizeR];
4 int par[sizeR]; // par : R -> L
5 vi adj[sizeL]; // adj : L -> (N -> R)
6
7 bool match(int u) {
8     for (int v : adj[u]) {
9         if (vis[v]) continue;
10        vis[v] = true;
11        if (par[v] == -1 || match(par[v])) {
12            par[v] = u;
13            return true;
14        }
15    }
16    return false;
17 }
18
19 // perfect matching iff ret == sizeL == sizeR
20 int maxmatch() {
21     fill_n(par, sizeR, -1);
22     int ret = 0;
23     for (int i = 0; i < sizeL; i++) {
24         fill_n(vis, sizeR, false);
25         ret += match(i);
26     }
27     return ret;
28 }
```

3.2. Strongly Connected Components $\mathcal{O}(V + E)$.

```
1 vvi adj, comps;
2 vi tidx, lnk, cnr, st;
3 vector<bool> vis;
4 int age, ncomps;
5
6 void tarjan(int v) {
7     tidx[v] = lnk[v] = ++age;
8     vis[v] = true;
9     st.pb(v);
10
11     for (int w : adj[v]) {
12         if (!tidx[w]) tarjan(w), lnk[v] = min(lnk[v], lnk[w]);
13         else if (vis[w]) lnk[v] = min(lnk[v], tidx[w]);
14     }
15
16     if (lnk[v] != tidx[v]) return;
17
18     comps.pb(vi());
19     int w;
20     do {
21         vis[w = st.back()] = false;
22         cnr[w] = ncomps;
23         comps.back().pb(w);
24         st.pop_back();
25     } while (w != v);
26     ncomps++;
27 }
28
29 void findSCC(int n) {
30     age = ncomps = 0;
31     vis.assign(n, false);
32     tidx.assign(n, 0);
33     lnk.resize(n);
34     cnr.resize(n);
35     comps.clear();
36 }
```

```
37     for (int i = 0; i < n; i++)
38         if (tidx[i] == 0) tarjan(i);
39 }
```

3.2.1. 2-SAT $\mathcal{O}(V + E)$. Include findSCC.

```
1 void init2sat(int n) { adj.assign(2 * n, vi()); }
2
3 // vl, vr = true -> variable l, variable r should be negated.
4 void imply(int xl, bool vl, int xr, bool vr) {
5     adj[2 * xl + vl].pb(2 * xr + vr);
6     adj[2 * xr + !vr].pb(2 * xl + !vl);
7 }
8
9 void satOr(int xl, bool vl, int xr, bool vr) { imply(xl, !vl, xr, vr);
10 }
11 void satConst(int x, bool v) { imply(x, !v, x, v); }
12 void satIff(int xl, bool vl, int xr, bool vr) {
13     imply(xl, vl, xr, vr);
14     imply(xr, vr, xl, vl);
15 }
16 bool solve2sat(int n, vector<bool> &sol) {
17     findSCC(2 * n);
18     for (int i = 0; i < n; i++)
19         if (cnr[2 * i] == cnr[2 * i + 1]) return false;
20     vector<bool> seen(n, false);
21     sol.assign(n, false);
22     for (vi &comp : comps) {
23         for (int v : comp) {
24             if (seen[v / 2]) continue;
25             seen[v / 2] = true;
26             sol[v / 2] = v & 1;
27         }
28     }
29     return true;
30 }
```

3.3. Cycle Detection $\mathcal{O}(V + E)$.

```
1 vvi adj; // assumes bidirected graph, adjust accordingly
2
3 bool cycle_detection() {
4     stack<int> s;
5     vector<bool> vis(MAXN, false);
6     vi par(MAXN, -1);
7     s.push(0);
8     vis[0] = true;
9     while (!s.empty()) {
10         int cur = s.top();
11         s.pop();
12         for (int i : adj[cur]) {
13             if (vis[i] && par[cur] != i) return true;
14             s.push(i);
15             par[i] = cur;
16             vis[i] = true;
17         }
18     }
19     return false;
20 }
```

3.4. Shortest path.

3.4.1. Dijkstra $\mathcal{O}(E + V \log V)$.

```
3.4.2. Floyd-Warshall  $\mathcal{O}(V^3)$ .
1 int n = 100;
2 ll d[MAXN][MAXN];
3 for (int i = 0; i < n; i++) fill_n(d[i], n, 1e18);
4 // set direct distances from i to j in d[i][j] (and d[j][i])
5 for (int i = 0; i < n; i++)
6     for (int j = 0; j < n; j++)
7         for (int k = 0; k < n; k++)
8             d[j][k] = min(d[j][k], d[j][i] + d[i][k]);
```

3.4.3. Bellman Ford $\mathcal{O}(VE)$. This is only useful if there are edges with weight $w_{ij} < 0$ in the graph.

```
1 vector<pair<pii, ll>> edges; // ((from, to), weight)
2 vector<ll> dist;
3
4 // when undirected, add back edges
5 bool bellman_ford(int V, int source) {
6     dist.assign(V, 1e18);
7     dist[source] = 0;
8
9     bool updated = true;
10    int loops = 0;
11    while (updated && loops < n) {
12        updated = false;
13        for (auto e : edges) {
14            int alt = dist[e.x.x] + e.y;
15            if (alt < dist[e.x.y]) {
16                dist[e.x.y] = alt;
17                updated = true;
18            }
19        }
20    }
21    return loops < n; // loops >= n: negative cycles
22 }
```

3.5. Max-flow min-cut.

3.5.1. Dinic's Algorithm $\mathcal{O}(V^2E)$.

```
1 struct edge {
2     int to, rev;
3     ll cap, flow;
4     edge(int t, int r, ll c) : to(t), rev(r), cap(c), flow(0) {}
5 };
6
7 int s, t, level[MAXN]; // s = source, t = sink
8 vector<edge> g[MAXN];
9
10 void add_edge(int fr, int to, ll cap) {
11     g[fr].pb(edge(to, g[to].size(), cap));
12     g[to].pb(edge(fr, g[fr].size() - 1, 0));
13 }
14
15 bool dinic_bfs() {
16     fill_n(level, MAXN, 0);
17     level[s] = 1;
18
19     queue<int> q;
20     q.push(s);
21     while (!q.empty()) {
22         int cur = q.front();
23         q.pop();
24         for (edge e : g[cur]) {
25             if (level[e.to] == 0 && e.flow < e.cap) {
26                 level[e.to] = level[cur] + 1;
27                 q.push(e.to);
28             }
29         }
30     }
31     return level[t] != 0;
32 }
33
34 ll dinic_dfs(int cur, ll maxf) {
35     if (cur == t) return maxf;
36
37     ll f = 0;
38     bool isSat = true;
39     for (edge &e : g[cur]) {
40         if (level[e.to] != level[cur] + 1 || e.flow == e.cap)
41             continue;
42         ll df = dinic_dfs(e.to, min(maxf - f, e.cap - e.flow));
43         f += df;
44         e.flow += df;
45         g[e.to][e.rev].flow -= df;
46         isSat &= e.flow == e.cap;
47         if (maxf == f) break;
48     }
49     if (isSat) level[cur] = 0;
50     return f;
51 }
```

```
51 }
52
53 ll dinic_maxflow() {
54     ll f = 0;
55     while (dinic_bfs()) f += dinic_dfs(s, LLINF);
56     return f;
57 }
```

3.6. Min-cost max-flow. Find the cheapest possible way of sending a certain amount of flow through a flow network.

```
1 struct edge {
2     // to, rev, flow, capacity, weight
3     int t, r;
4     ll f, c, w;
5     edge(int _t, int _r, ll _c, ll _w) : t(_t), r(_r), f(0), c(_c), w(
6         _w) {}
7
8     int n, par[MAXN];
9     vector<edge> adj[MAXN];
10    ll dist[MAXN];
11
12    bool findPath(int s, int t) {
13        fill_n(dist, n, LLINF);
14        fill_n(par, n, -1);
15
16        priority_queue<pii, vector<pii>, greater<pii>> q;
17        q.push(pii(dist[s] = 0, s));
18
19        while (!q.empty()) {
20            int d = q.top().x, v = q.top().y;
21            q.pop();
22            if (d > dist[v]) continue;
23
24            for (edge e : adj[v]) {
25                if (e.f < e.c && d + e.w < dist[e.t]) {
26                    q.push(pii(dist[e.t] = d + e.w, e.t));
27                    par[e.t] = e.r;
28                }
29            }
30        }
31        return dist[t] < INF;
32    }
33
34    pair<ll, ll> minCostMaxFlow(int s, int t) {
35        ll cost = 0, flow = 0;
36        while (findPath(s, t)) {
37            ll f = INF, c = 0;
38            int cur = t;
39            while (cur != s) {
40                const edge &rev = adj[cur][par[cur]], &e = adj[rev.t][rev.r];
41                f = min(f, e.c - e.f);
42                cur = rev.t;
43            }
44            cur = t;
45            while (cur != s) {
46                edge &rev = adj[cur][par[cur]], &e = adj[rev.t][rev.r];
47                c += e.w;
48                e.f += f;
49                rev.f -= f;
50                cur = rev.t;
51            }
52            cost += f * c;
53            flow += f;
54        }
55        return pair<ll, ll>(cost, flow);
56    }
57
58    inline void addEdge(int from, int to, ll cap, ll weight) {
59        adj[from].pb(edge(to, adj[to].size(), cap, weight));
60        adj[to].pb(edge(from, adj[from].size() - 1, 0, -weight));
61    }
```

3.7. Minimal Spanning Tree.

3.7.1. Kruskal $\mathcal{O}(E \log V)$.

4. STRING ALGORITHMS

```
4.1. Trie.
1 const int SIGMA = 26;
2
3 struct trie {
4     bool word;
5     trie **adj;
6
7     trie() : word(false), adj(new trie*[SIGMA]) {
8         for (int i = 0; i < SIGMA; i++) adj[i] = NULL;
9     }
10
11     void addWord(const string &str) {
12         trie *cur = this;
13         for (char ch : str) {
14             int i = ch - 'a';
15             if (!cur->adj[i]) cur->adj[i] = new trie();
16             cur = cur->adj[i];
17         }
18         cur->word = true;
19     }
20
21     bool isWord(const string &str) {
22         trie *cur = this;
23         for (char ch : str) {
24             int i = ch - 'a';
25             if (!cur->adj[i]) return false;
26             cur = cur->adj[i];
27         }
28         return cur->word;
29     }
30 };
```

```
4.2. Z-algorithm  $\mathcal{O}(n)$ .
1 // z[i] = length of longest substring starting from s[i] which is also
   a prefix of s.
2 vi z_function(const string &s) {
3     int n = (int) s.length();
4     vi z(n);
5     for (int i = 1, l = 0, r = 0; i < n; ++i) {
6         if (i <= r) z[i] = min (r - i + 1, z[i - l]);
7         while (i + z[i] < n && s[z[i]] == s[i + z[i]]) ++z[i];
8         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
9     }
10    return z;
11 }
```

4.3. Suffix array $\mathcal{O}(n \log^2 n)$. This creates an array $P[0], P[1], \dots, P[n - 1]$ such that the suffix $S[i \dots n]$ is the $P[i]^{th}$ suffix of S when lexicographically sorted.

```
1 typedef pair<pii, int> tii;
2
3 const int maxlogn = 17, int maxn = 1 << maxlogn;
4
5 tii make_triple(int a, int b, int c) { return tii(pii(a, b), c); }
6
7 int p[maxlogn + 1][maxn];
8 tii L[maxn];
9
10 int suffixArray(string S) {
11     int N = S.size(), stp = 1, cnt = 1;
12     for (int i = 0; i < N; i++) p[0][i] = S[i];
13     for (; cnt < N; stp++, cnt <= 1) {
14         for (int i = 0; i < N; i++) {
15             L[i] = tii(pii(p[stp-1][i], i + cnt < N ? p[stp-1][i + cnt]
16                           : -1), i);
17         }
18         sort(L, L + N);
19         for (int i = 0; i < N; i++) {
20             p[stp][L[i].y] = i > 0 && L[i].x == L[i-1].x ? p[stp][L[i-1].y] : i;
21         }
22         return stp - 1; // result is in p[stp - 1][0 .. (N - 1)]
23     }
```

4.4. Longest Common Subsequence $\mathcal{O}(n^2)$. SUBSTRING: *consecutive characters* !!!

```
1 int dp[STR_SIZE][STR_SIZE]; // DP problem
2
3 int lcs(const string &w1, const string &w2) {
4     int n1 = w1.size(), n2 = w2.size();
5     for (int i = 0; i < n1; i++) {
6         for (int j = 0; j < n2; j++) {
7             if (i == 0 || j == 0) dp[i][j] = 0;
8             else if (w1[i - 1] == w2[j - 1]) dp[i][j] = dp[i - 1][j - 1] + 1;
9             else dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
10        }
11    }
12    return dp[n1][n2];
13 }
14
15 // backtrace
16 string getLCS(const string &w1, const string &w2) {
17     int i = w1.size(), j = w2.size();
18     string ret = "";
19     while (i > 0 && j > 0) {
20         if (w1[i - 1] == w2[j - 1]) ret += w1[--i], j--;
21         else if (dp[i][j - 1] > dp[i - 1][j]) j--;
22         else i--;
23     }
24     reverse(ret.begin(), ret.end());
25     return ret;
26 }
```

4.5. Levenshtein Distance $\mathcal{O}(n^2)$. Also known as the ‘Edit distance’.

```
1 int dp[MAX_SIZE][MAX_SIZE]; // DP problem
2
3 int levDist(const string &w1, const string &w2) {
4     int n1 = w1.size(), n2 = w2.size();
5     for (int i = 0; i <= n1; i++) dp[i][0] = i; // removal
6     for (int j = 0; j <= n2; j++) dp[0][j] = j; // insertion
7     for (int i = 1; i <= n1; i++)
8         for (int j = 1; j <= n2; j++)
9             dp[i][j] = min(
10                 1 + min(dp[i - 1][j], dp[i][j - 1]),
11                 dp[i - 1][j - 1] + (w1[i - 1] != w2[j - 1])
12             );
13     return dp[n1][n2];
14 }
```

```
4.6. Knuth-Morris-Pratt algorithm  $\mathcal{O}(N + M)$ .
1 int kmp_search(const string &word, const string &text) {
2     int n = word.size();
3     vi T(n + 1, 0);
4     for (int i = 1, j = 0; i < n; ) {
5         if (word[i] == word[j]) T[++i] = ++j; // match
6         else if (j > 0) j = T[j]; // fallback
7         else i++; // no match, keep zero
8     }
9     int matches = 0;
10    for (int i = 0, j = 0; i < text.size(); ) {
11        if (text[i] == word[j]) {
12            i++;
13            if (++j == n) { // match at interval [i - n, i)
14                matches++;
15                j = T[j];
16            }
17            } else if (j > 0) j = T[j];
18            else i++;
19        }
20        return matches;
21    }
```

4.7. Aho-Corasick Algorithm $\mathcal{O}(N + \sum_{i=1}^m |S_i|)$. All given P must be unique!

```
1 const int MAXP = 100, MAXLEN = 200, SIGMA = 26, MAXTRIE = MAXP * MAXLEN
   ;
2
```

```
3 int nP;
4 string P[MAXP], S;
5
6 int pnr[MAXTRIE], to[MAXTRIE][SIGMA], sLink[MAXTRIE], dLink[MAXTRIE],
   nnodes;
7
8 void ahoCorasick() {
9     fill_n(pnr, MAXTRIE, -1);
10    for (int i = 0; i < MAXTRIE; i++) fill_n(to[i], SIGMA, 0);
11    fill_n(sLink, MAXTRIE, 0);
12    fill_n(dLink, MAXTRIE, 0);
13    nnodes = 1;
14    // STEP 1: MAKE A TREE
15    for (int i = 0; i < nP; i++) {
16        int cur = 0;
17        for (char c : P[i]) {
18            int i = c - 'a';
19            if (to[cur][i] == 0) to[cur][i] = nnodes++;
20            cur = to[cur][i];
21        }
22        pnr[cur] = i;
23    }
24    // STEP 2: CREATE SUFFIX_LINKS AND DICT_LINKS
25    queue<int> q;
26    q.push(0);
27    while (!q.empty()) {
28        int cur = q.front();
29        q.pop();
30        for (int c = 0; c < SIGMA; c++) {
31            if (to[cur][c]) {
32                int sl = sLink[to[cur][c]] = cur == 0 ? 0 : to[sLink[
33                    cur]][c];
34                // if all strings have equal length, remove this:
35                dLink[to[cur][c]] = pnr[sl] >= 0 ? sl : dLink[sl];
36                q.push(to[cur][c]);
37            } else to[cur][c] = to[sLink[cur]][c];
38        }
39        // STEP 3: TRAVERSE S
40        for (int cur = 0, i = 0, n = S.size(); i < n; i++) {
41            cur = to[cur][S[i] - 'a'];
42            for (int hit = pnr[cur] >= 0 ? cur : dLink[cur]; hit; hit =
43                dLink[hit]) {
44                cerr << P[pnr[hit]] << " found at [" << (i + 1 - P[pnr[hit]
45                    ].size()) << ", " << i << "]" << endl;
46            }
47        }
```

5. GEOMETRY

```
1 const double EPS = 1e-7, PI = acos(-1.0);
2
3 typedef long long NUM; // EITHER double OR long long
4 typedef pair<NUM, NUM> pt;
5 #define x first
6 #define y second
7
8 pt operator+(pt p, pt q) { return pt(p.x + q.x, p.y + q.y); }
9 pt operator-(pt p, pt q) { return pt(p.x - q.x, p.y - q.y); }
10
11 pt& operator+=(pt &p, pt q) { return p = p + q; }
12 pt& operator-=(pt &p, pt q) { return p = p - q; }
13
14 pt operator*(pt p, NUM l) { return pt(p.x * l, p.y * l); }
15 pt operator/(pt p, NUM l) { return pt(p.x / l, p.y / l); }
16
17 NUM operator*(pt p, pt q) { return p.x * q.x + p.y * q.y; }
18 NUM operator^(pt p, pt q) { return p.x * q.y - p.y * q.x; }
19
20 istream& operator>>(istream &in, pt &p) { return in >> p.x >> p.y; }
21 ostream& operator<<(ostream &out, pt p) { return out << '(' << p.x << "
   , " << p.y << ')'; }
22
23 NUM lenSq(pt p) { return p * p; }
24 NUM lenSq(pt p, pt q) { return lenSq(p - q); }
25 double len(pt p) { return hypot(p.x, p.y); } // more overflow safe
26 double len(pt p, pt q) { return len(p - q); }
```

```
27
28 typedef pt frac;
29 typedef pair<double, double> vec;
30 vec getvec(pt p, pt dp, frac t) { return vec(p.x + 1. * dp.x * t.x / t.
    y, p.y + 1. * dp.y * t.x / t.y); }
31
32 // square distance from pt a to line bc
33 frac distPtLineSq(pt a, pt b, pt c) {
34     a -= b, c -= b;
35     return frac((a ^ c) * (a ^ c), c * c);
36 }
37
38 // square distance from pt a to linesegment bc
39 frac distPtSegmentSq(pt a, pt b, pt c) {
40     a -= b; c -= b;
41     NUM dot = a * c, len = c * c;
42     if (dot <= 0) return frac(a * a, 1);
43     if (dot >= len) return frac((a - c) * (a - c), 1);
44     return frac(a * a * len - dot * dot, len);
45 }
46
47 // projects pt a onto linesegment bc
48 frac projPt(a, pt b, pt c) { return frac((a - b) * (c - b), (c - b) *
    (c - b)); }
49 vec projv(pt a, pt b, pt c) { return getvec(b, c - b, proj(a, b, c)); }
50
51 bool collinear(pt a, pt b, pt c) { return ((a - b) ^ (a - c)) == 0; }
52
53 bool pointOnSegment(pt a, pt b, pt c) {
54     NUM dot = (a - b) * (c - b), len = (c - b) * (c - b);
55     return collinear(a, b, c) && 0 <= dot && dot <= len;
56 }
57
58 // true => 1 intersection, false => parallel, so 0 or \infy solutions
59 bool linesIntersect(pt a, pt b, pt c, pt d) { return ((a - b) ^ (c - d)
    ) != 0; }
60 vec lineLineIntersection(pt a, pt b, pt c, pt d) {
61     double det = (a - b) ^ (c - d);
62     pt ret = (c - d) * (a ^ b) - (a - b) * (c ^ d);
63     return vec(ret.x / det, ret.y / det);
64 }
65
66 // dp, dq are directions from p, q
67 // intersection at p + t_i dp, for 0 <= i < return value
68 int segmentIntersection(pt p, pt dp, pt q, pt dq, frac &t0, frac &t1)
69 {
70     if (dp * dp == 0) swap(p, q), swap(dp, dq); // dq = 0
71     if (dp * dp == 0) { t0 = t1 = frac(0, 1); return p == q; } // dp =
        dq = 0
72
73     pt dpq = (q - p);
74     NUM c = dp ^ dq, c0 = dpq ^ dp, c1 = dpq ^ dq;
75     if (c == 0) { // parallel, dp > 0, dq >= 0
76         if (c0 != 0) return 0; // not collinear
77         NUM v0 = dpq * dp, v1 = v0 + dq * dp, dp2 = dp * dp;
78         if (v1 < v0) swap(v0, v1);
79         t0 = frac(v0 = max(v0, (NUM) 0), dp2);
80         t1 = frac(v1 = min(v1, dp2), dp2);
81         return (v0 <= v1) & (v0 < v1);
82     } else if (c < 0) c = -c, c0 = -c0, c1 = -c1;
83     t0 = t1 = frac(c1, c);
84     return 0 <= min(c0, c1) && max(c0, c1) <= c;
85 }
86
87 // Returns TWICE the area of a polygon to keep it an integer
88 NUM polygonTwiceArea(const vector<pt> &pts) {
89     NUM area = 0;
90     for (int N = pts.size(), i = 0, j = N - 1; i < N; j = i++)
91         area += pts[i] ^ pts[j];
92     return abs(area); // area < 0 <=> pts ccw
93 }
94
95 bool pointInPolygon(pt p, const vector<pt> &pts) {
96     double sum = 0;
97     for (int N = pts.size(), i = 0, j = N - 1; i < N; j = i++) {
98         if (pointOnSegment(p, pts[i], pts[j])) return true; // boundary
99         double angle = acos((pts[i] - p) * (pts[j] - p) / len(pts[i], p)
            ) / len(pts[j], p));
100         sum += ((pts[i] - p) ^ (pts[j] - p)) < 0 ? angle : -angle;
101     }
```

```
102     return abs(abs(sum) - 2 * PI) < EPS;
103 }
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```

```
20     return pii(1, 1 + 1);
21 } else if (r - 1 == 3) { // brute-force
22     ys = { 1, 1 + 1, 1 + 2 };
23     sort(ys.begin(), ys.end(), byY());
24     return minpt(pii(1, 1 + 1), minpt(pii(1, 1 + 2), pii(1 + 1, 1 +
        2)));
25 }
26 int m = (l + r) / 2;
27 vi yl, yr;
28 pii delta = minpt(closest(l, m, yl), closest(m, r, yr));
29 NUM ddelta = dist(delta), xm = .5 * (pts[m-1].x + pts[m].x);
30 merge(yl.begin(), yl.end(), yr.begin(), yr.end(), back_inserter(ys),
    byY());
31 deque<int> q;
32 for (int i : ys) {
33     if (abs(pts[i].x - xm) <= ddelta) {
34         for (int j : q) delta = minpt(delta, pii(i, j));
35         q.pb(i);
36         if (q.size() > 8) q.pop_front(); // magic from Introduction
            to Algorithms.
37     }
38 }
39 return delta;
40 }
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```

6. MISCELLANEOUS

```
6.1. Binary search  $\mathcal{O}(\log(hi - lo))$ .
1 bool test(int n);
2
3 int search(int lo, int hi) {
4     // assert(test(lo) && !test(hi));
5     while (hi - lo > 1) {
6         int m = (lo + hi) / 2;
7         (test(m) ? lo : hi) = m;
8     }
9     // assert(test(lo) && !test(hi));
10    return lo;
11 }
```

6.2. Fast Fourier Transform $\mathcal{O}(n \log n)$. Given two polynomials $A(x) = a_0 + a_1x + \dots + a_{n/2}x^{n/2}$ and $B(x) = b_0 + b_1x + \dots + b_{n/2}x^{n/2}$, FFT calculates all coefficients of $C(x) = A(x) \cdot B(x) = c_0 + c_1x + \dots c_nx^n$, with $c_i = \sum_{j=0}^i a_j b_{i-j}$.

```
1 typedef complex<double> cpx;
2 const int logmaxn = 20, maxn = 1 << logmaxn;
3
4 cpx a[maxn] = {}, b[maxn] = {}, c[maxn];
5
6 void fft(cpx *src, cpx *dest) {
7     for (int i = 0, rep = 0; i < maxn; i++, rep = 0) {
8         for (int j = i, k = logmaxn; k--> j >= 1) rep = (rep << 1) | (
            j & 1);
9         dest[rep] = src[i];
10    }
11    for (int s = 1, m = 1; m <= maxn; s++, m *= 2) {
12        cpx r = exp(cpx(0, 2.0 * PI / m));
13        for (int k = 0; k < maxn; k += m) {
14            cpx cr(1.0, 0.0);
15            for (int j = 0; j < m / 2; j++) {
16                cpx t = cr * dest[k + j + m / 2];
17                dest[k + j + m / 2] = dest[k + j] - t;
18                dest[k + j] += t;
19                cr *= r;
20            }
21        }
22    }
23 }
24
25 void multiply() {
26     fft(a, c);
27     fft(b, a);
28     for (int i = 0; i < maxn; i++) b[i] = conj(a[i] * c[i]);
29     fft(b, c);
30     for (int i = 0; i < maxn; i++) c[i] = conj(c[i]) / (1.0 * maxn);
31 }
```

```
6.3. Minimum Assignment (Hungarian Algorithm)  $\mathcal{O}(n^3)$ .
1 int a[MAXN + 1][MAXM + 1]; // matrix, 1-based
2
3 int minimum_assignment(int n, int m) { // n rows, m columns
4     vi u(n + 1), v(m + 1), p(m + 1), way(m + 1);
5
6     for (int i = 1; i <= n; i++) {
7         p[0] = i;
8         int j0 = 0;
9         vi minv(m + 1, INF);
10        vector<char> used(m + 1, false);
11        do {
12            used[j0] = true;
13            int i0 = p[j0], delta = INF, j1;
14            for (int j = 1; j <= m; j++)
15                if (!used[j]) {
16                    int cur = a[i0][j] - u[i0] - v[j];
17                    if (cur < minv[j]) minv[j] = cur, way[j] = j0;
18                    if (minv[j] < delta) delta = minv[j], j1 = j;
19                }
20            for (int j = 0; j <= m; j++) {
21                if (used[j]) u[p[j]] += delta, v[j] -= delta;
22                else minv[j] -= delta;
23            }
24            j0 = j1;
25        } while (p[j0] != 0);
26        do {
27            int j1 = way[j0];
28            p[j0] = p[j1];
29            j0 = j1;
30        } while (j0);
31    }
32
33    // column j is assigned to row p[j]
34    // for (int j = 1; j <= m; ++ j) ans[p[j]] = j;
35    return -v[0];
36 }
```

```
39 fill_n(hasval, n, false);
40 for (int col = 0, row; col < n; col++) {
41     hasval[col] = !is_zero(mat[row][col]);
42     if (!hasval[col]) continue;
43     for (int c = col + 1; c < n; c++) {
44         if (!is_zero(mat[row][c])) hasval[col] = false;
45     }
46     if (hasval[col]) vals[col] = mat[row][n];
47     row++;
48 }
49
50 for (int i = 0; i < n; i++)
51     if (!hasval[i]) return 2;
52 return 1;
53 }
```

6.4. Partial linear equation solver $\mathcal{O}(N^3)$. «««< HEAD

```
1 typedef double NUM;
2
3 #define MAXN 110
4 #define EPS 1e-5
5
6 NUM mat[MAXN][MAXN + 1], vals[MAXN];
7 bool hasval[MAXN];
8
9 bool is_zero(NUM a) { return -EPS < a && a < EPS; }
10 bool eq(NUM a, NUM b) { return is_zero(a - b); }
11
12 int solvemmat(int n)
13 {
14     for(int i = 0; i < n; i++)
15         for (int j = 0; j < n; j++) cin >> mat[i][j];
16     for (int i = 0; i < n; i++) cin >> mat[i][n];
17
18     int pivrow = 0, pivcol = 0;
19     while (pivcol < n) {
20         int r = pivrow, c;
21         while (r < n && is_zero(mat[r][pivcol])) r++;
22         if (r == n) { pivcol++; continue; }
23
24         for (c = 0; c <= n; c++) swap(mat[pivrow][c], mat[r][c]);
25
26         r = pivrow++; c = pivcol++;
27         NUM div = mat[r][c];
28         for (int col = c; col <= n; col++) mat[r][col] /= div;
29         for (int row = 0; row < n; row++) {
30             if (row == r) continue;
31             NUM times = -mat[row][c];
32             for (int col = c; col <= n; col++) mat[row][col] += times *
                 mat[r][col];
33         }
34     }
35     // now mat is in RREF
36     for (int r = pivrow; r < n; r++)
37         if (!is_zero(mat[r][n])) return 0;
38 }
```

```
=====

1  typedef double NUM;
2
3  #define MAXN 110
4  #define EPS 1e-5
5
6  NUM mat[MAXN][MAXN + 1], vals[MAXN];
7  bool hasval[MAXN];
8
9  bool is_zero(NUM a) { return -EPS < a && a < EPS; }
10 bool eq(NUM a, NUM b) { return is_zero(a - b); }
11
12 int solvemmat(int n)
13 {
14     for(int i = 0; i < n; i++)
15         for (int j = 0; j < n; j++) cin >> mat[i][j];
16     for (int i = 0; i < n; i++) cin >> mat[i][n];
17
18     int pivrow = 0, pivcol = 0;
19     while (pivcol < n) {
20         int r = pivrow, c;
21         while (r < n && is_zero(mat[r][pivcol])) r++;
22         if (r == n) { pivcol++; continue; }
23
24         for (c = 0; c <= n; c++) swap(mat[pivrow][c], mat[r][c]);
25
26         r = pivrow++; c = pivcol++;
27         NUM div = mat[r][c];
28         for (int col = c; col <= n; col++) mat[r][col] /= div;
29         for (int row = 0; row < n; row++) {
30             if (row == r) continue;
31             NUM times = -mat[row][c];
32             for (int col = c; col <= n; col++) mat[row][col] += times * mat[r][col];
33         }
34     }
35     // now mat is in RREF
36     for (int r = pivrow; r < n; r++)
37         if (!is_zero(mat[r][n])) return 0;
38
39     fill_n(hasval, n, false);
40     for (int col = 0, row; col < n; col++) {
41         hasval[col] = !is_zero(mat[row][col]);
42         if (!hasval[col]) continue;
43         for (int c = col + 1; c < n; c++) {
44             if (!is_zero(mat[row][c])) hasval[col] = false;
45         }
46         if (hasval[col]) vals[col] = mat[row][n];
47         row++;
48     }
49
50     for (int i = 0; i < n; i++)
51         if (!hasval[i]) return 2;
52     return 1;
53 }
```

»»»> 6f9e7f0f4b6e0690dfea4b352511edebd24ac35b