

ARCH LINUX "FROM SCRATCH" + GNOME + INTEL CHIPSET + UEFI + SECURE BOOT

1. UEFI & KEYBOARD & LOCALE

IMPORTANT: ENABLE SECURE BOOT WITH NO KEYS ENROLLED

```
ls /sys/firmware/efi/efivars ... if there's an error ... it's not UEFI
```

```
efibootmgr ... should list "Linux Boot Manager"
```

```
loadkeys br-abnt2
```

```
nano /etc/locale.gen ... unmark LANG=pt_BR.UTF-8
```

```
locale-gen
```

```
nano /etc/locale.conf ... set LANG=pt_BR.UTF-8
```

2. NETWORK & CONNECTIVITY BY WI-FI

```
ip link
```

```
iwctl
```

```
device list
```

```
station wlan0 scan
```

```
station wlan0 get-networks
```

```
station wlan0 connect
```

```
exit
```

```
ping 1.1.1.3
```

```
timedatectl
```

```
ls /usr/share/kbd/consolefonts/ | grep ter-122b
```

```
if yes: setfont ter-122b
```

```
if not: pacman -Sy terminus-font
```

```
then : setfont ter-122b
```

3. PARTITIONING & FORMATTING NVME

```
parted /dev/nvme0n1 mklabel gpt
```

```
parted /dev/nvme0n1 mkpart ESP fat32 1MiB 1025MiB
```

```
parted /dev/nvme0n1 set 1 esp on
```

```
parted /dev/nvme0n1 mkpart primary ext4 1025MiB 4097MiB
```

```
parted /dev/nvme0n1 mkpart primary btrfs 4097MiB 100%
```

```
mkfs.fat -F32 /dev/nvme0n1p1
```

```
mkfs.ext4 -L BOOT /dev/nvme0n1p2
```

```
mkfs.btrfs -L ROOT /dev/nvme0n1p3
```

4. MOUNTING BTRFS SUBVOLUMES

```
mount /dev/nvme0n1p3 /mnt
```

```
btrfs subvolume create /mnt/@
```

```
btrfs subvolume create /mnt/@home
```

```
btrfs subvolume create /mnt/@log
```

```
btrfs subvolume create /mnt/@pkg
```

```
btrfs subvolume create /mnt/@snapshots
```

```
umount /mnt
```

```
mount -o subvol=@ /dev/nvme0n1p3 /mnt
```

```
mkdir -p /mnt/{home,var/log,var/cache/pacman/pkg,var/snapshots}
```

```
mount -o subvol=@home /dev/nvme0n1p3 /mnt/home  
mount -o subvol=@log /dev/nvme0n1p3 /mnt/var/log  
mount -o subvol=@pkg /dev/nvme0n1p3 /mnt/var/cache/pacman/pkg  
mount -o subvol=@snapshots /dev/nvme0n1p3 /mnt/var/snapshots
```

```
mkdir -p /mnt/boot
```

```
mount /dev/nvme0n1p2 /mnt/boot
```

```
mkdir -p /mnt/boot/efi
```

```
mount /dev/nvme0n1p1 /mnt/boot/efi
```

5. BASE SYSTEM INSTALLATION FOR INTEL CHIPSET

```
reflector --latest 20 --sort rate --save /etc/pacman.d/mirrorlist
```

```
pacstrap -K /mnt base linux-firmware linux-zen linux-zen-headers dkms dracut  
intel-ucode vulkan-intel vulkan-mesa-device-select vulkan-tools apparmor  
btrfs-progs efibootmgr iwd nano networkmanager sbctl sudo
```

```
genfstab -U /mnt > /mnt/etc/fstab
```

6. CHROOT CONFIGURATION

```
arch-chroot /mnt
```

```
ln -sf /usr/share/zoneinfo/America/Araguaina /etc/localtime  
hwclock --systohc  
nano /etc/locale.gen ... check if LANG=pt_BR.UTF-8 is enabled  
locale-gen  
nano /etc/locale.conf ... set LANG=pt_BR.UTF-8  
nano /etc/vconsole.conf ... set KEYMAP=br-abnt2  
nano /etc/hostname ... set book (choose a personal name)
```

```
passwd ... setting "root" admin password
```

```
useradd -m -g users -G wheel -s /bin/bash arch (choose a personal name)  
passwd arch ... setting arch sudo password  
EDITOR=nano visudo  
%wheel ALL=(ALL:ALL) ALL ... uncomment for enabling sudo for arch user
```

7. BOOTLOADER (SYSTEMD-BOOT)

```
bootctl install
```

```
blkid /dev/nvme0n1p3 ... catch the UUID in PARTUUID field
```

```
nano /boot/loader/entries/arch-zen.conf
```

```
title Arch Linux Zen  
linux /vmlinuz-linux-zen  
initrd /intel-ucode.img  
initrd /initramfs-linux-zen.img  
options root=PARTUUID=<UUID caught> zswap.enabled=0 rootfstype=btrfs  
rootflags=subvol=@ rw apparmor=1 security=apparmor loglevel=3
```

IMPORTANT: Dracut does not create or manage initramfs fallback

```
nano /boot/loader/loader.conf
```

```
timeout 3
console-mode max
editor no

sbctl verify
sbctl create-keys
sbctl verify
sbctl sign -s ... (sign each entrie listed above)
sbctl enroll-keys
sbctl list-enrolled-keys
sbctl status
```

```
nano /etc/sysctl.d/99-sysctl.conf
```

```
kernel.kptr_restrict = 2
kernel.dmesg_restrict = 1
kernel.randomize_va_space = 2
fs.protected_hardlinks = 1
fs.protected_symlinks = 1
```

```
sysctl --system
```

```
mkdir -p /etc/pacman.d/hooks (necessary)
```

```
nano /etc/pacman.d/hooks/99-secureboot.hook
```

```
[Trigger]
```

```
Operation = Upgrade
```

```
Type = Package
```

```
Target = linux-zen
```

```
Target = systemd
```

```
[Action]
```

```
Description = Signing linux-zen kernel & initramfs & systemd-boot with sbctl
```

```
When = PostTransaction
```

```
Exec = /bin/sh -c 'sbctl sign -s /boot/vmlinuz-linux-zen 2>/dev/null || true
&& sbctl sign -s /boot/initramfs-*.img 2>/dev/null || true && sbctl sign
-s /boot/EFI/B00T/B00TX64.EFI 2>/dev/null || true && sbctl sign -s
/boot/EFI/systemd/systemd-bootx64.efi 2>/dev/null || true'
```

```
ls /sys/firmware/efi/efivars ... check if UEFI remain active
```

```
efibootmgr ... should list "Linux Boot Manager"
```

```
systemctl enable NetworkManager.service ... enable network connection
```

```
dracut --force --verbose
```

```
exit ... exiting from chroot environment
```

```
umount -R /mnt
```

```
swapoff -a
```

reboot + F2 + Secure Boot + Custom Mode + Import Keys [only if you did not has used sbctl enroll-keys]

8. POST-INSTALLATION NETWORK CONFIGURATION

Login: root

```
systemctl start NetworkManager.service
```

```
nmcli general status
nmcli device status
nmcli device wifi list
nmcli device wifi connect "SSID" --ask (or -a)
```

```
pacman -Sy terminus-font
setfont ter-122b
```

9. INSTALLING GNOME AND ESSENTIAL PACKAGES

```
[ Gnome Desktop - 36 ] pacman -S gdm adwaita-icon-theme gnome gnome-
backgrounds gnome-bluetooth gnome-boxes gnome-browser-connector gnome-
calculator gnome-calendar gnome-characters gnome-clocks gnome-color-manager
gnome-control-center gnome-disk-utility gnome-firmware gnome-info-collect
gnome-keyring gnome-logs gnome-menus gnome-music gnome-online-accounts gnome-
power-manager gnome-session gnome-settings-daemon gnome-shell-extensions
gnome-terminal gnome-text-editor gnome-themes-extra gnome-tweaks gnome-usage
gnome-user-docs gnome-weather xdg-desktop-portal-gnome xdg-user-dirs-gtk
xkeyboard-config mutter
```

```
[ Applications - 41 ] pacman -S collision decibels eog extension-manager
eyedropper file-roller firefox firefox-18n-pt-br firewallld foliate font-
manager fragments gedit gparted gthumb gvfs gvfs-afc gvfs-dnssd gvfs-goa
gvfs-gphoto2 gvfs-mtp gvfs-nfs gvfs-smb gvfs-wsdd libreoffice-still
libreoffice-still-pt-br loupe mission-center mpv nautilus network-manager-
applet papers pavucontrol qalculate-gtk seahorse shotwell showtime simple-
scan snapshot system-config-printer timeshift
```

```
[ CLI-I - 52 ] pacman -S alsa-utils aspell aspell-en aspell-pt at-spi2-core
avahi bashtop bat bind-tools bluez bluez-utils colord cronie cups cups-
browsed cups-filters cups-pdf curl ethtool fail2ban fastfetch fd ffmpeg
foomatic-db foomatic-db-engine foomatic-db-ppds fwupd fzf gedit-plugins git
glances grc grilo-plugins gst-plugins-base gst-plugins-base-libs gutenprint
hspell htop hunspell hwinfo imagemagick inxi iproute2 less libssh libssh2
libvncserver libvoikko libwireplumber localsearch lsd lsof
```

```
[ CLI-II - 51 ] pacman -S man-db man-pages mesa-utils meson ninja nmap nss-
mdns ntfs-3g nuspell p7zip pacman-contrib parted pipewire pipewire-pulse
powertop ptyxis pwgen qt5-wayland qt6-wayland reflector ripgrep rpcbind rygel
smartmontools speech-dispatcher speedtest-cli tecla tinysparql tlp tree unzip
upower v4l-utils v4l2loopback-utils wget wireless_tools wireplumber yt-dlp
zip zram-generator zsh zsh-autocomplete zsh-autosuggestions zsh-completions
zsh-history-substring-search zsh-lovers zsh-syntax-highlighting yelp yelp-
tools yelp-xsl zed
```

```
systemctl enable gdm.service
```

```
systemctl status gdm.service
```

```
systemctl enable apparmor.service
systemctl enable avahi-daemon.service
systemctl enable bluetooth.service
systemctl enable crone.service
systemctl enable cups.service
systemctl enable cups-browsed.service
systemctl enable firewalld.service
systemctl enable tlp.service
```

reboot

Login: "user" & "password" ... if fail --> make login by CLI

CLI command: sudo systemctl start gdm.service

sbctl status

```
Secure Boot: enabled
Setup Mode: disabled
Vendor keys: disabled
User keys: enrolled
```

bootctl status

```
Secure Boot: enabled (user keys)
```

10. CONFIGURATIONS AND OPTIMIZATIONS

1. setup gnome-control-center
2. setup gnome-tweaker
3. setup extension-manager
4. setup fstab: sudo nano /etc/fstab
5. setup timeshift
6. setup zram-generator
7. setup zsh: chsh -s /bin/zsh \$USER ... then logout / login
8. install fonts :

```
sudo pacman -S gnu-free-fonts ttf-anonymous-pro ttf-atkinson-hyperlegible
ttf-bitstream-vera ttf-caladea ttf-carlito ttf-cascadia-code ttf-crimson-pro
ttf-crimson-pro-variable ttf-croscore ttf-dejavu ttf-doulos-sil ttf-droid
ttf-eurof ttf-fantasque-sans-mono ttf-fira-code ttf-fira-mono ttf-fira-sans
ttf-hack ttf-ibm-plex ttf-inconsolata ttf-input ttf-jetbrains-mono ttf-
junicode ttf-junicode-variable ttf-khmer ttf-lato ttf-liberation ttf-
libertinus ttf-linux-libertine ttf-linux-libertine-g ttf-material-icons ttf-
material-symbols-variable ttf-meslo-nerd ttf-mona-sans ttf-monospace-frozen
ttf-monospace-variable ttf-monofur ttf-monoid ttf-montserrat ttf-nunito ttf-
opensans ttf-overpass ttf-roboto ttf-roboto-mono
```

* * *