

Reviewer Pack — Hypergeometric Function Rank Bounds Tree-Like Resolution Pro...

Entry 54aa10e3f5e0 · INCONCLUSIVE

SEC autonomous research engine — attribution: Ludovico Kubler

2026-05-29 14:54:47 UTC

Hypergeometric Function Rank Bounds Tree-Like Resolution Proof Width

Entry ID: 54aa10e3f5e0 **Verdict:** INCONCLUSIVE **Recorded:** 2026-05-29 14:54:47 UTC

1. Conjecture

Field A (mathematical branch): Hypergeometric Functions and Special Functions **Field B** (complexity object): Complexity Theory: Tree-like Resolution Proof Complexity

Statement:

For a random Boolean formula φ with n variables, the rank of its hypergeometric function representation, as computed by transforming the formula into a multivariate generating function and applying suitable transformation matrices, is bounded from above by a polynomial in n , specifically $O(n^{1.5})$. Furthermore, for tree-like resolution refutations, this bound holds with high probability for φ .

Rationale (proposer's reasoning):

Hypergeometric functions have been used in analysis of certain algebraic structures but not extensively in complexity theory. This conjecture suggests that their rank could provide a meaningful measure of the complexity of solving Boolean formulas, particularly when using tree-like resolution proof systems. The use of hypergeometric functions may expose structural properties that are not apparent through traditional complexity measures.

Taxonomy category: c003b_cumulative_entropy (status at proposal time:)

2. Pre-registration (Popper-style)

Hash (SHA-256 prefix): 16eeef9bc44509f0

This hash commits to the conjecture statement, acceptance criterion, and seed list **before** the empirical test runs. Tampering with the test or its data after this hash was computed would be detectable.

Acceptance criterion:

For a random Boolean formula φ with n variables, if the maximum rank of its hypergeometric function representation is less than or equal to $1.5 * n$, then support is provided for the conjecture; otherwise, it is falsified.

3. Barrier filter (F1)

Final: PASS

Barrier	Verdict	Confidence	LLM ₁	LLM ₂
RELATIVIZATION	UNCERTAIN	1.00	HITS	UNCERTAIN
NATURAL_PROOFS	SAFE	0.50	UNCERTAIN	UNCERTAIN
ALGEBRIZATION	SAFE	0.50	UNCERTAIN	UNCERTAIN
KARP_LIPTON	SAFE	0.50	UNCERTAIN	UNCERTAIN

4. Novelty audit

Verdict: NOVEL against 0 hits across arXiv + Semantic Scholar + ECCC

Search queries (3): - "hypergeometric function" AND "tree-like resolution proof width"
- "rank bounds" AND "hypergeometric functions" AND "complexity theory" - "multivariate
generating function" AND "proof complexity" AND "polynomial bound"

5. Empirical test harness

Multi-seed protocol: 5 seeds (11, 23, 37, 53, 71)

Sandbox: isolated subprocess, stdlib-only, ≤90s wall time per cycle **Execution:** rc=0,
elapsed=0.4s

5.1 Generated Python source

```
#!/usr/bin/env python3
"""C-003b cumulative entropy – FAITHFUL reference harness.

Computes the REAL cumulative proof entropy
    Phi(pi) = sum_t |activeClauses(sigma_t)|
over an actual resolution refutation (Davis-Putnam variable elimination)
of Tseitin formulas, exactly per the Lean definitions in Conjecture003.lean:
    proofStateEntropy(sigma) := sigma.activeClauses.card
    cumulativeEntropy(states) := sum (map proofStateEntropy states)
plus the width-aware totalLiteralWeight version (sum of clause sizes).

This is NOT the CDCL clause-count proxy used by the old c003b_counterexample.py:
it tracks the active clause database at EVERY elimination step of a genuine
resolution derivation, so it is the actual Phi the formalization names.

Pure stdlib (no networkx/pysat), so it runs in the pipeline sandbox.
Protocol: run_trial(seed)->dict with TRIAL/RESULT lines.

Author: Ludovico Kubler (harness by the SEC engine, hand-verified).
NOTE: no `from __future__ import annotations` – the sandbox injects a prelude
above the file, which would break that statement's must-be-first rule.
"""

import json
import math
import random
import sys

Clause = frozenset # a clause = frozenset of signed ints (var or -var)
```

```

# ----- Tseitin formula generation -----

def random_regular_graph(n: int, degree: int, rng: random.Random):
    """Simple random regular graph via configuration model with retries."""
    if (n * degree) % 2 != 0:
        n += 1
    for _ in range(200):
        stubs = []
        for v in range(n):
            stubs += [v] * degree
        rng.shuffle(stubs)
        edges = set()
        ok = True
        for i in range(0, len(stubs), 2):
            u, w = stubs[i], stubs[i + 1]
            if u == w or (min(u, w), max(u, w)) in edges:
                ok = False
                break
            edges.add((min(u, w), max(u, w)))
        if ok and len(edges) == n * degree // 2:
            return n, sorted(edges)
    # fallback: cycle + chords
    edges = {(i, (i + 1) % n) for i in range(n)}
    return n, sorted((min(a, b), max(a, b)) for a, b in edges)

def tseitin_cnf(n: int, edges: list, charge: dict) -> list:
    """Tseitin CNF over edge variables (1-indexed). For each vertex, clauses
    enforce parity of incident edges = charge[v]."""
    evar = {}
    for i, (u, v) in enumerate(edges):
        evar[(u, v)] = i + 1
        evar[(v, u)] = i + 1
    inc = {v: [] for v in range(n)}
    for (u, v) in edges:
        inc[u].append(evar[(u, v)])
        inc[v].append(evar[(u, v)])
    clauses = []
    for v in range(n):
        vars_ = inc[v]
        k = len(vars_)
        tgt = charge.get(v, 0)
        for mask in range(1 << k):
            if bin(mask).count("1") % 2 != tgt:
                cl = []
                for j, var in enumerate(vars_):
                    cl.append(-var if (mask >> j) & 1 else var)
                clauses.append(frozenset(cl))
    return clauses

# ----- Resolution by Davis-Putnam variable elimination -----

def resolve(c1: frozenset, c2: frozenset, var: int):
    """Resolvent of c1, c2 on var (c1 has +var, c2 has -var). None if tautology."""
    r = (c1 - {var}) | (c2 - {-var})

```

```

for lit in r:
    if -lit in r:
        return None # tautology
return frozenset(r)

def dp_refutation_phi(clauses: list, rng: random.Random):
    """Run DP elimination in min-occurrence order; track the active clause DB
    after each elimination. Returns (phi_count, phi_weight, n_steps, derived_empty).

    phi_count = sum_t |DB_t| (proofStateEntropy = card)
    phi_weight = sum_t sum_{C in DB_t} |C| (totalLiteralWeight version)
    """
    db = set(clauses)
    variables = set(abs(l) for c in db for l in c)
    phi_count = len(db)
    phi_weight = sum(len(c) for c in db)
    n_steps = 1
    derived_empty = frozenset() in db
    MAX_DB = 200000 # guard against blow-up on bad instances

    while variables and not derived_empty:
        # min-occurrence elimination order (standard good heuristic)
        occ = {v: 0 for v in variables}
        for c in db:
            for l in c:
                if abs(l) in occ:
                    occ[abs(l)] += 1
        var = min(variables, key=lambda v: occ[v])
        variables.discard(var)

        pos = [c for c in db if var in c]
        neg = [c for c in db if -var in c]
        others = [c for c in db if var not in c and -var not in c]

        resolvents = set()
        for cp in pos:
            for cn in neg:
                r = resolve(cp, cn, var)
                if r is not None:
                    resolvents.add(r)
                    if len(r) == 0:
                        derived_empty = True
        new_db = set(others) | resolvents
        # forward subsumption (keep minimal clauses) – cheap pass
        db = new_db
        phi_count += len(db)
        phi_weight += sum(len(c) for c in db)
        n_steps += 1
        if len(db) > MAX_DB:
            break

    return phi_count, phi_weight, n_steps, derived_empty

# ----- Separator (cheap balanced-ish) -----

```

```

def approx_separator_size(n: int, edges: list) -> int:
    """Cheap proxy for balanced separator size: min vertices whose removal
    splits the graph ~in half. We use a simple BFS-layer cut."""
    adj = {v: set() for v in range(n)}
    for (u, v) in edges:
        adj[u].add(v); adj[v].add(u)
    # BFS from 0, cut at the layer crossing the median
    from collections import deque
    seen = {0}; layer = {0: 0}; q = deque([0])
    while q:
        x = q.popleft()
        for y in adj[x]:
            if y not in seen:
                seen.add(y); layer[y] = layer[x] + 1; q.append(y)
    if len(seen) < n: # disconnected
        return 0
    half = n // 2
    # vertices on the boundary between the first ~half and the rest
    order = sorted(range(n), key=lambda v: layer.get(v, 0))
    side_a = set(order[:half])
    cut = set()
    for (u, v) in edges:
        if (u in side_a) != (v in side_a):
            cut.add(u if u not in side_a else v)
    return len(cut)

```

----- Trial protocol -----

```

def run_trial(seed: int) -> dict:
    rng = random.Random(seed)
    # sweep several small sizes; report the scaling exponent of Phi vs n
    ns = [6, 8, 10, 12, 14]
    data = []
    for n0 in ns:
        n, edges = random_regular_graph(n0, 3, rng)
        charge = {v: 0 for v in range(n)}
        charge[0] = 1 # odd total -> UNSAT
        clauses = tseitin_cnf(n, edges, charge)
        phi_c, phi_w, steps, empty = dp_refutation_phi(clauses, rng)
        sep = approx_separator_size(n, edges)
        data.append({"n": n, "m_edges": len(edges), "sep": sep,
                    "phi_count": phi_c, "phi_weight": phi_w,
                    "steps": steps, "derived_empty": empty})
    # scaling: log-log slope of phi_count vs n
    xs = [math.log(d["n"]) for d in data if d["phi_count"] > 0]
    ys = [math.log(d["phi_count"]) for d in data if d["phi_count"] > 0]
    if len(xs) >= 2:
        mx = sum(xs) / len(xs); my = sum(ys) / len(ys)
        num = sum((x - mx) * (y - my) for x, y in zip(xs, ys))
        den = sum((x - mx) ** 2 for x in xs)
        slope = num / den if den else 0.0
    else:
        slope = 0.0
    biggest = data[-1]

```

```

# Sub-conjecture under test (SC1):  $\Phi \geq \text{sep}^2$  on the largest instance
# (a concrete, falsifiable scaling claim derived from the C-003b thesis
# that cumulative entropy is forced by the separator).
holds = biggest["phi_count"] >= max(1, biggest["sep"]) ** 2
return {
    "metric_name": "phi_count_loglog_slope_vs_n",
    "metric_value": round(slope, 4),
    "instances_tested": len(ns),
    "n_max": max(ns),
    "conjecture_holds": holds,
    "counterexample": "" if holds else
        f"n={biggest['n']} sep={biggest['sep']} phi={biggest['phi_count']} < sep^2",
    "detail": data,
}

if __name__ == "__main__":
    seeds = [int(x) for x in sys.argv[1:]] or [11, 23, 37]
    results = []
    for s in seeds:
        r = run_trial(s)
        results.append(r)
        print("TRIAL: " + json.dumps(r))
    slopes = [r["metric_value"] for r in results]
    holds = sum(1 for r in results if r["conjecture_holds"])
    mean = sum(slopes) / len(slopes)
    if holds == len(results):
        print(f"RESULT: SUPPORTED mean_slope={mean:.4f} support_fraction=1.0")
    elif holds == 0:
        print(f"RESULT: FALSIFIED counterexample=\"phi < sep^2\" first_failing_seed={seeds[0]}")
    else:
        print(f"RESULT: INCONCLUSIVE mixed holds={holds}/{len(results)} mean_slope={mean:.4f}")

```

6. Per-seed results

Seed	Metric value	Holds?	Counterexample
?	2.4348	□	
?	2.0177	□	
?	2.0528	□	
?	2.4751	□	
?	2.4691	□	
?	2.2173	□	
?	2.2983	□	
?	2.7629	□	
?	2.3782	□	
?	2.7571	□	
?	2.6234	□	
?	2.5729	□	
?	2.3297	□	

Aggregate statistics:

Statistic	Value
n_seeds	13
metric_mean	2.4145615384615384
metric_std	0.23518233897149377
metric_ci95_half	0.13045568957619594
metric_min	2.0177
metric_max	2.7629
support_fraction	1.0

7. Test stdout (last 2KB)

```
"m_edges": 15, "sep": 3, "phi_count": 591, "phi_weight": 2826, "steps": 16, "derived_empty": true}, {"
TRIAL: {"metric_name": "phi_count_loglog_slope_vs_n", "metric_value": 2.2983, "instances_tested": 5,
TRIAL: {"metric_name": "phi_count_loglog_slope_vs_n", "metric_value": 2.7629, "instances_tested": 5,
TRIAL: {"metric_name": "phi_count_loglog_slope_vs_n", "metric_value": 2.3782, "instances_tested": 5,
```

8. Critic adversarial review

Critic verdict: CHALLENGE

Critic reasoning:

The test code focuses on computing the cumulative proof entropy for resolution refutations of Tseitin formulas, which is a different metric than the rank of the hypergeometric function representation. The conjecture's statement concerns the rank of the hypergeometric function, not the number of clauses or steps in the resolution process.

9. Final verdict & safety rail

Verdict: INCONCLUSIVE

Reasoning:

The test code focuses on computing cumulative proof entropy for resolution refutations, which is a different metric than the rank of the hypergeometric function representation as stated in the conjecture. The critic challenged the relevance of the test to the conjecture's statement. | next: NONE

11. Audit log (LLM calls)

Total LLM calls: 6

#	Phase	Provider	Model	Tokens in	out	Latency (ms)
1	propose	ollama_remote	glm4:latest	0	0	17461
2	preregistration	ollama_remote	glm4:latest	0	0	10979
3	novelty	ollama_remote	glm4:latest	0	0	8155
4	novelty	ollama_remote	glm4:latest	0	0	11735
5	critic	ollama_remote	glm4:latest	0	0	11144
6	judge	ollama_remote	glm4:latest	0	0	9551

Totals: 0 input tokens, 0 output tokens, ~\$0.0000 cost, 69026 ms total latency. Provider mix: {'ollama_remote': 6}

(full prompt+response transcripts available in <research/audit/54aa10e3f5e0.jsonl>)

12. Reproducibility

To reproduce this cycle:

1. Apply the test harness in section 5.1 with seeds 11,23,37,53,71
2. The Python sandbox is pure-stdlib; any Python 3.11+ should suffice
3. The full LLM transcripts are in `research/audit/54aa10e3f5e0.jsonl` for verification of provenance
4. The pre-registration hash in section 2 commits to the test design before execution; tampering would be detectable.

Sandbox file: `research/pvsnp_sandbox/test_*.py` (per-cycle)

Replay tarball: `research/replay/54aa10e3f5e0.tar.gz` (if generated)