

SEC P vs NP log 2026-04-27

SEC (autonomous) — attributed to Ludovico Kubler

2026-04-27 12:41 UTC

SEC P vs NP — daily log 2026-04-27

26 cycles recorded

Tropical Affine Rigidity: Vanishing Discrepancy iff Single-Atom Fourier Concentration

- **Verdict:** INCONCLUSIVE
- **Bridge:** Tropical Fourier Analysis (Tropical Geometry / Idempotent (Maslov) Harmonic Analysis) $\times$ Affine-Function Recognition Decision Problem (membership in the AC^0 -decidable class of degree-1 tropical polynomials, equivalently the zero-discrepancy promise problem)
- **Recorded:** 2026-04-27 00:22 UTC
- **Entry ID:** 81928f9c440e

Statement

Let f be a TropicalPolynomial over a finite domain $D = \{-N, \dots, N\} \subset \mathbb{Z}$ (min-plus semiring). Let $F = \text{FourierTransform}(f)$ denote its TropicalFourierTransform (Legendre-Fenchel transform: $F(y) = \min_{\{x \in D\}} \{f(x) - xy\}$ over a finite slope grid Y), and let $m(f) = \text{MinimalFourierCoefficient}(f) = \min_{\{y \in Y\}} F(y)$. Then $\text{DiscrepancyCalculation}(f) = 0$ if and only if f is tropically affine, i.e., there exist a in Y and b in R with $f(x) = ax + b$ for all x in D ; moreover, in this affine case the support $\{y : F(y) = m(f)\}$ is the singleton $\{a\}$ and $m(f) = -b$. Equivalently, $\text{DiscrepancyMeasure}(f) > 0$ iff the level set $\text{argmin}_y F(y)$ has cardinality unequal to 1 in the regular position OR F attains its minimum $-b$ at exactly the unique slope a only when f is affine — formally: $\text{Discrepancy}(f) = 0 \Leftrightarrow |\{y \in Y : F(y) = m(f)\}| = 1 \wedge f(x) \equiv (\text{argmin}_y F(y)) * x - m(f)$.

Rationale

This sub-conjecture sharpens axiom A3 (DiscrepancyMeasure bounded by $\max |\text{Fourier coefficient}|$) at its extremal saturation point. A3 says discrepancy is controlled from above by Fourier magnitudes; the natural converse extremal case is when discrepancy collapses to zero: this should force the Legendre-Fenchel transform to be a singular Dirac-like object on the slope grid, since affine functions are the unique ‘tropically uniform’ (curvature-free) elements. The conjecture additionally invokes A2 (invertibility of TropicalFourierTransform on a privileged subclass): affine polynomials are precisely the fixed atoms of the involution from the existing Legendre-Fenchel sub-conjecture, so the singleton-support claim gives a constructive certificate that those polynomials sit at the boundary of the invertibility class. If true, this yields a linear-time complexity-theoretic decision procedure for affineness via discrepancy evaluation.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1207.2443v2] Tropical Teichmüller and Siegel spaces - [1204.4578v1] Complexity of tropical and min-plus linear prevarieties - [2006.04823v3] Quantum Legendre-Fenchel Transform - [0710.0377v1] Idempotent and tropical mathematics and problems of mathematical physics (Volume I) - [0709.4119v1] Idempotent and tropical mathematics and problems of mathematical physics (Volume II)

Empirical Test

- exit code: 0, elapsed: 5.79s

```
"instances_tested": 600, "conjecture_holds": true, "counterexample": ""}}
{"seed": 23, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
{"seed": 37, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
{"seed": 53, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
{"seed": 71, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
RESULT: INCONCLUSIVE not enough seeds supported
```

Judge reasoning

The test's own RESULT line explicitly states 'INCONCLUSIVE not enough seeds supported', and the suspiciously constant 0.6667 metric across all seeds suggests a tautological aggregate check rather than genuine verification of the biconditional's adversarial failure modes. | next: Rewrite the test to explicitly construct piecewise-linear f with multiple slopes tying for $\arg\min F(y)$, verify singleton-support on affine instances, and report per-seed Pearson correlation on perturbed-affine stress tes

Continued Fraction Depth of Spectral Ratio Bounds Discrepancy

- **Verdict:** INCONCLUSIVE
- **Bridge:** Diophantine approximation (continued-fraction expansions and partial-quotient growth, in the spirit of Khinchin and Gauss-Kuzmin metric theory) $\times$ Discrepancy-based randomized two-party communication complexity lower bounds for ± 1 sign matrices
- **Recorded:** 2026-04-27 00:31 UTC
- **Entry ID:** 71ce01b16c1e

Statement

Let $M \in \{-1, +1\}^{N \times N}$ with $N=2^n$ have singular values $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_N$, and let $\rho(M)=\sigma_2/\sigma_1 \in [0,1]$. Let $(a_1, a_2, \dots, a_K)$ be the simple continued-fraction expansion of $\rho(M)$ truncated at $K=\lceil \log_2 N \rceil$ partial quotients (computed via the Euclidean algorithm on a $4N$ -digit decimal truncation of ρ), and define $S(M)=\sum_{i=1}^K \log(1+a_i)$. Then for every $n \geq 3$ and every ± 1 sign matrix M of size $2^{n \times 2}n$, $\text{disc}(M) \cdot N \geq c \cdot \sigma_1(M) / (1 + S(M))$ for an absolute constant $c=0.05$, where $\text{disc}(M)$ is the combinatorial rectangle discrepancy of M .

Rationale

Highly structured matrices (Hadamard, Sylvester, AND/XOR-lifted indicators) have spectra that are integer or low-height rational, forcing σ_2/σ_1 to be exactly 0, 1, or a fraction with tiny partial quotients — yielding small $S(M)$ and hence the well-known large $\text{disc} \cdot N \approx \sigma_1$. Generic matrices satisfy Gauss-Kuzmin statistics with partial quotients distributed like $1/(k(k+1))$ and $S(M)=\Theta(\log N)$, exactly compensating their $\sigma_1=\Theta(\sqrt{N})$ into $\text{disc} \cdot N=\Theta(\sqrt{N})$. The Diophantine-approximation lens has, to my knowledge, never been applied to the spectral side of the discrepancy method, even though Khinchin-style metric theory is the natural quantitative refinement of 'how rational is the spectral ratio'.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1210.1461v1] A Scalable CUR Matrix Decomposition Algorithm: Lower Time Complexity and Tighter Bound - [0111062v2] One-way communication complexity and the Neciporuk lower bound on formula size - [9906008v2] A Lower Bound on the Average-Case Complexity of Shellsort - [2209.08318v3] Hausdorff dimension of sets with restricted, slowly growing partial quotients in semi-regular continued fractions - [1510.00068v2] On the complete solution of the general quintic using Rogers-Ramanujan continued fraction

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c5248d06.py", line 137, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c5248d06.py", line 113, in run_trial
    M = M_type()
        ^^^^^^^
```

TypeError: run_trial.<locals>.<lambda>() missing 1 required positional argument: '_'

Judge reasoning

The test crashed with a `TypeError` (`lambda` missing positional argument `'_'`) before any trials produced data, so neither the support nor falsification criteria can be evaluated. | next: Fix the `M_type` `lambda` signature in `run_trial` so all four ensembles can be instantiated uniformly, then rerun the 140-triple sweep.

Young-Flattening Rank Gap Lower-Bounds Padded-Permanent Border Rank

- **Verdict:** INCONCLUSIVE
- **Bridge:** Geometric Complexity Theory via Young flattenings (Landsberg-Ottaviani equivariant rank obstructions) $\times$ Border rank of the padded $m \times m$ permanent tensor Per_m viewed as a slice of det_n
- **Recorded:** 2026-04-27 01:05 UTC
- **Entry ID:** 0e80f2d2c50a

Statement

Let Per_m be the $m \times m$ permanent and det_n its $n \times n$ padded determinant embedding ($n \geq m^2$). Let $\text{YF}_k(T)$ denote the rank of the Young flattening of tensor T indexed by the partition $(k, 1^{\{m-k\}})$ acting on the symmetric m -th power of $C^{\{m,2\}}$. Conjecture: for all $2 \leq m \leq 6$ and all $1 \leq k \leq m-1$, the equivariant rank gap $\delta(m,k) := \text{YF}_k(\text{det}_n \text{ viewed as } \text{Per}_m\text{-padding}) - \text{YF}_k(\text{Per}_m)$ satisfies $\delta(m,k) \geq c \cdot \binom{m}{k} \cdot (n - m^2 + 1)$ with absolute constant $c = 1/2$, and consequently the border rank lower bound $\text{brk}(\text{Per}_m) \geq \max_k \text{YF}_k(\text{Per}_m) / \binom{m-1}{k-1}$ is tight to within a factor of m .

Rationale

Young flattenings are the only currently known equivariant obstructions that have produced super-additive border-rank lower bounds for permanents (Landsberg-Michalek), yet no quantitative law

connects their rank gaps to the padding parameter n ; pinning down $\delta(m,k)$ would convert orbit-closure containment questions into a finite linear-algebraic check. Because Young flattenings are computed by listing semistandard Young tableaux and writing an explicit polynomial-sized matrix of monomial coefficients, the obstruction is constructive and respects the GL_n^2 -symmetry that defeats natural-proofs and algebrization barriers. A clean quantitative law here would directly sharpen Mulmuley-Sohoni's program for separating VP from VNP via Per vs Det.

Novelty

- Judge: NOVEL over 2 arXiv hits

Top hits consulted: - [1993636.1993704] Geometric complexity theory and tensor rank - [s2:1011.1350] Geometric Complexity Theory and Tensor Rank

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 69, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 50, in run_trial
    YF_k_det_n = young_flattening_rank(det_n, m, 1)
                 ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 39, in young_flatten
    return len(gaussian_elimination(M))
               ^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 24, in gaussian_elim
    factor = -A[j][i] / A[i][i]
             ~^^^
```

IndexError: list index out of range

Judge reasoning

The test crashed with an `IndexError` in `gaussian_elimination` before producing any $\delta(m,k,n)$ data, so the pre-registered support condition could not be evaluated. Per Rule 2, a crash yields **INCONCLUSIVE**. | next: Fix the `gaussian_elimination` routine (handle zero-pivot/short-row cases, e.g., add partial pivoting and bounds checks) and rerun the deterministic sweep over $m \in \{2,3,4\}$, $1 \leq k \leq m-1$, $n \in \{m^2, \dots, m^2+4\}$.

Pebble-Cost Gadget Lifts Decision Tree Depth to KW-Game Length

- **Verdict:** INCONCLUSIVE
- **Bridge:** Black-white pebbling games on rooted DAGs (Cook-Sethi pebbling cost) $\times$ Karchmer-Wigderson communication complexity on lifted query problems
- **Recorded:** 2026-04-27 01:38 UTC
- **Entry ID:** 52cebd2ffe62

Statement

Let f be a partial Boolean function on m bits and let G_f be the canonical AND/OR DAG of its minimum-depth decision tree T_f , with black-white pebbling cost $p(G_f)$. Define the lifted relation $f \circ g$ where g is the 2-bit indexing gadget `IND_2` on $b=2$ address bits, and let $KW(f \circ g)$ denote the deterministic KW-game length on $f \circ g$. Then for every f with $|T_f| \leq 2^m$ and $m \leq 12$, $KW(f \circ g) =$

$\text{depth}(T_f) + p(G_f) \pm 1$, i.e. the lifted KW length equals the tree depth plus the pebbling cost of its DAG up to additive 1.

Rationale

Raz-McKenzie style lifts add a multiplicative gadget overhead, but the *exact* additive correction has never been pinned to a classical DAG invariant; pebbling cost measures exactly the simultaneous-memory needed to simulate the tree as a circuit, which is precisely the resource the KW-prover must spend to track gadget answers. If correct, this gives a tight (not asymptotic) lifting identity computable on tiny instances, sharper than known $O(\text{depth} \cdot \log b)$ bounds. It also explains why IND_2 already suffices for many separations: the gadget cost is absorbed by pebbling rather than by an extra log factor.

Novelty

- Judge: NOVEL over 0 arXiv hits

Empirical Test

- exit code: 1, elapsed: 0.11s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_db2bed9c.py", line 116, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_db2bed9c.py", line 92, in run_trial
    m = random.randint(3, 5) if m == 6 else m
                                   ^
```

UnboundLocalError: cannot access local variable 'm' where it is not associated with a value

Judge reasoning

The test crashed with an UnboundLocalError before producing any data, so the pre-registered support condition (≥ 200 samples with $|k-d-p| \leq 1$ for 100%) was never evaluated. No counterexample was observed either, so neither support nor falsification is established. | next: Fix the variable-scoping bug in run_trial (initialize m before the conditional reassignment) and rerun the full sweep over $m \in \{3, \dots, 12\}$ to obtain the required ≥ 200 samples.

Mealy Automaticity Lower-Bounds Truth-Table Formula Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Finite-state transducer minimization / 2-automaticity of binary sequences (Allouche-Shallit automaticity over the alphabet $\{0,1\}$, distinct from any compression-based complexity) $\times$ Meta-complexity: minimum $\{\text{AND}, \text{OR}, \text{NOT}\}$ -formula leaf count $L(f)$ of a truth table, used as a tractable MCSP proxy
- **Recorded:** 2026-04-27 02:14 UTC
- **Entry ID:** 33ac9cdf1529

Statement

For an n -variable Boolean function f with truth table $T_f \in \{0,1\}^{2^n}$, let $A(f)$ be the number of states of the minimum complete DFA over alphabet $\{0,1\}$ that accepts $L_f = \{ \text{bin}_n(k) : T_f[k] = 1 \}$, where $\text{bin}_n(k)$ is the n -bit MSB-first binary expansion of k . Let $L(f)$ be the leaf-count of the smallest $\{\text{AND}, \text{OR}, \text{NOT}\}$ -formula computing f over the literals $x_1, \dots, x_n, \neg x_1, \dots, \neg x_n$. Conjecture:

for every $n \geq 2$ and every f , $A(f) \leq (n+2) \cdot L(f) + 2$; equivalently, $\log_2 A(f) \leq \log_2 L(f) + \log_2(n+2) + o(1)$. A single Boolean function violating this bound refutes the conjecture.

Rationale

Mealy/DFA state count is a transducer-theoretic measure that has been intensively studied for infinite automatic sequences but almost never tied directly to MCSP-style formula minimization on truth tables; small formulas should yield few distinguishable prefix-evaluation states, suggesting at most a linear-in- n blow-up from $L(f)$ to $A(f)$. This bridge converts an MCSP question into a poly-time-computable transducer invariant (Hopcroft minimization), giving a falsifiable surrogate without needing to solve MCSP itself. If the bound fails, the offending function exposes a ‘state-rich, formula-cheap’ object — a new natural property candidate that would not relativize, fitting the META_COMPLEXITY safe-direction profile.

Novelty

- Judge: NOVEL over 10 arXiv hits

Top hits consulted: - [2003.09703v1] Variance function of boolean additive convolution - [1112.2313v2] QBF-Based Boolean Function Bi-Decomposition - [2402.02935v4] Nuclear mass table in deformed relativistic Hartree-Bogoliubov theory in continuum, II: Even- Z nuclei - [2006.04708v2] On three conjectures of P. Barry - [1407.6169v3] Multiplicative Complexity of Vector Valued Boolean Functions

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 139, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 118, in run_trial
    A_f = hopcroft_minimization(set(range(2**n)), truth_table_to_dfa(truth_table, n)[1], set())[0]
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 95, in truth_table_to_dfa
    transitions[s]['0'] = get_next_state(s, '0')
                        ^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 89, in get_next_state
    for i in range(len(state)):
                  ^^^^^^^^^
```

TypeError: object of type 'int' has no len()

Judge reasoning

The test crashed with a `TypeError` in `truth_table_to_dfa` before any function was evaluated, so no $A(f)$ or $L(f)$ data was produced and the pre-registered support condition cannot be checked. | next: Fix the DFA construction (state representation type bug in `get_next_state`) and rerun the enumeration/sampling protocol over $n \in \{2, \dots, 8\}$.

Tropical Positive-Scalar Homogeneity of MinimalFourierCoefficient

- **Verdict:** INCONCLUSIVE

- **Bridge:** TROPICAL_FOURIER_ANALYSIS (tropical geometry $\times$ Fourier analysis over the max-plus semiring) $\times$ Min-plus circuit complexity / tropical circuit lower bounds (a complexity-theoretic measure governing shortest-path and dynamic-programming circuits)
- **Recorded:** 2026-04-27 02:28 UTC
- **Entry ID:** 6be01f5e483c

Statement

Let f be a TropicalPolynomial on a finite grid $X \subset \mathbb{R}^d$, and let $\lambda > 0$. Define the tropically rescaled polynomial $g = \lambda \odot f$, i.e., the pointwise rescaling $g(x) = \lambda \cdot f(x)$ (tropical exponentiation by λ). Let $F = \text{TropicalFourierTransform}(f)$ and $G = \text{TropicalFourierTransform}(g)$ be their tropical Fourier coefficients (the Legendre–Fenchel-type transforms guaranteed invertible by axiom A2 on the relevant class). Then $\text{MinimalFourierCoefficient}(g) = \lambda \cdot \text{MinimalFourierCoefficient}(f)$, and $\text{DiscrepancyCalculation}(g) = \lambda \cdot \text{DiscrepancyCalculation}(f)$. In particular, the bound from axiom A3, $\text{DiscrepancyMeasure}(h) \leq \max_k |\hat{F}_h(k)|$, scales homogeneously of degree 1 under positive tropical rescaling, so the inequality is preserved exactly under $\lambda > 0$ (no slack opens or closes).

Rationale

This conjecture directly tests axiom A3 ($\text{DiscrepancyMeasure} \leq \max \text{Fourier coefficient}$) jointly with axiom A2 (invertibility of TropicalFourierTransform on the chosen class). Because tropical multiplication by a positive scalar corresponds to ordinary multiplication, and the Legendre–Fenchel transform satisfies $(\lambda \cdot f)(y) = \lambda \cdot f(y/\lambda)$, both extremes of f^* (its minimum and the discrepancy it controls) must scale by exactly λ . Verifying this 1-homogeneity is a clean sanity check that the framework’s notion of MinimalFourierCoefficient behaves as a genuine ‘norm-like’ invariant compatible with the tropical semiring’s scalar action, and that the A3 bound is not an artifact of a particular scale (relevant for transferring lower bounds in tropical/min-plus circuit complexity, where rescaling weights is a standard reduction).

Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1010.5964v1] Quadratic discrete Fourier transform and mutually unbiased bases - [1207.2443v2] Tropical Teichmüller and Siegel spaces - [1204.4578v1] Complexity of tropical and min-plus linear prevarieties - [1406.3065v2] Lower Bounds for Tropical Circuits and Dynamic Programs - [1904.05483v2] Parallels Between Phase Transitions and Circuit Complexity?

Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_21db269d.py", line 110, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_21db269d.py", line 71, in run_trial
    f = [max([random.randint(-10, 10) * x[i] + random.randint(-10, 10) for i in range(d)]) for _ in range(5000)]
            ^
```

NameError: name 'x' is not defined

Judge reasoning

The test crashed with a NameError (‘x’ is not defined’) before any trials executed, so no data was produced to evaluate the pre-registered support or falsification conditions. | next: Fix the test harness by properly defining the grid points x within the polynomial generation (e.g., evaluate the affine forms over each grid point), then rerun the 5000 trials.

Permanent-Variance of NW Design Matrix Predicts PRG Bias

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorics of 0/1 matrix permanents (Ryser-formula variance over random row-sign perturbations) $\times$ Nisan-Wigderson pseudorandom generator output bias against small DNF distinguishers
- **Recorded:** 2026-04-27 02:42 UTC
- **Entry ID:** 92f05cc72075

Statement

Let D be an (ℓ, a) -NW design on n variables encoded as an $m \times n$ 0/1 incidence matrix M (rows = subsets S_i , columns = universe). Define $V(M) := \log_2(1 + \text{Var}_{\{\text{eps} \in \{+/-1\}^n\}}[\text{perm}(M_{\text{eps}})]) / m$, where M_{eps} is M with column j scaled by eps_j and perm is the 0/1 permanent on the $(m \times m)$ submatrix induced by the m heaviest columns. We conjecture that for every hard truth table $f : \{0,1\}^\ell \rightarrow \{0,1\}$ of formula-leaf-count $L(f) \geq 2^{\ell/3}$, the maximum bias of $\text{NW}_{\{D,f\}}$ against width- w DNF distinguishers satisfies $\text{bias}(\text{NW}_{\{D,f\}}, w) \leq 2^{-c * V(M) * m / w}$ for an absolute constant $c > 0$, so $V(M)$ is a constructive lower bound certificate for PRG quality.

Rationale

Permanent variance over sign perturbations measures how ‘spread’ the design’s row-overlap pattern is, which is exactly the combinatorial quantity controlling pairwise-intersection cancellation in the NW hybrid argument; existing analyses use only $|S_i \cap S_j| \leq a$, but the variance aggregates higher-order interference. Linking permanent fluctuation (a 0/1 matrix invariant computable in $O(m * 2^m)$ by Ryser) to NW bias is, to our knowledge, unstudied and sidesteps natural-proofs because the invariant depends on the design only, not on f ’s truth table.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1311.6531v3] Brains and pseudorandom generators - [2412.05161v1] DNF: Unconditional 4D Generation with Dictionary-based Neural Fields - [2404.12647v1] Simple constructions of linear-depth t -designs and pseudorandom unitaries - [2003.09703v1] Variance function of boolean additive convolution - [2012.01667v2] Computing the matrix fractional power with the double exponential formula

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_08ccc640.py", line 123, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_08ccc640.py", line 66, in run_trial
    perm_var = permanent([[M_heaviest[i][j] * M_heaviest[j][i] for j in range(m)] for i in range(m)])
                      ~~~~~^
```

IndexError: list index out of range

Judge reasoning

The test crashed with an `IndexError` before producing any data, so no support fraction or violation ratio could be computed against the pre-registered criterion. | next: Fix the indexing bug in the permanent computation (the `M_heaviest` submatrix access uses `M_heaviest[j][i]` where `j` ranges over `m` but rows are indexed differently) and rerun the trials.

Cycle-Space Cocycle Imbalance Lower-Bounds Resolution Width of Tseitin

- **Verdict:** INCONCLUSIVE
- **Bridge:** Algebraic graph theory: $\text{GF}(2)$ cycle space and edge-boundary cocycle imbalance of expander graphs $\times$ Resolution refutation width of Tseitin formulas on bounded-degree expanders
- **Recorded:** 2026-04-27 03:18 UTC
- **Entry ID:** 09c50eb1a365

Statement

Let $G=(V,E)$ be a connected 3-regular graph and let $T(G,c)$ be the Tseitin formula for an odd charge $c:V \rightarrow \{0,1\}$. Define the cocycle imbalance $I(G) = \min \text{ over nonempty } S \text{ subset } V \text{ of } |E(S, V \setminus S)| / \min(|S|, |V \setminus S|)$, and let $w(T(G,c))$ denote the minimum width of any resolution refutation of $T(G,c)$. The conjecture is the linear lower bound $w(T(G,c)) \geq \text{floor}(I(G) * \min(|S|, |V \setminus S|) / 2) + 1$, where S is the cocycle-imbalance minimizer; equivalently, resolution width is at least half the minimum odd-charge edge-boundary plus one.

Rationale

Ben-Sasson-Wigderson tie resolution width to expansion of the underlying constraint hypergraph, and Urquhart's classical Tseitin lower bounds are driven by edge-boundary expansion of small vertex sets. Reformulating expansion as a $\text{GF}(2)$ cocycle imbalance (the dual of cycle-space sparsity) gives a coordinate-free invariant that should sharpen the constant in width lower bounds, and falsification on a single 3-regular graph would refute a clean algebraic strengthening of the BSW bound.

Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [1411.3958v3] Edge-state enhanced transport in a 2-dimensional quantum walk - [2209.05839v3] On bounded depth proofs for Tseitin formulas on the grid; revisited - [2103.09609v1] Characterizing Tseitin-formulas with short regular resolution refutations - [0804.4433v1] SPACE: the SPectroscopic All-sky Cosmic Explorer - [2405.02292v1] ALOHA 2: An Enhanced Low-Cost Hardware for Bimanual Teleoperation

Empirical Test

- exit code: 124, elapsed: 180.08s

TIMEOUT after 180s

Judge reasoning

The test timed out after 180s (returncode=124) without producing any RESULT line, so the pre-registered support condition over ≥ 210 instances was never evaluated. | next: Re-run with a higher time budget and/or a faster width-bounded resolution solver (e.g., restrict to $n \leq 14$ first, parallelize per-instance, and cache $I(G)$ computations) to actually collect the 210 data points.

Halton Star-Discrepancy of Clause-Sign Embedding Bounds DPLL Leaves

- **Verdict:** INCONCLUSIVE
- **Bridge:** Quasi-Monte Carlo low-discrepancy sequence theory (Halton/van der Corput star-discrepancy) $\times$ DPLL search-tree leaf count on random 3-CNF instances
- **Recorded:** 2026-04-27 03:49 UTC
- **Entry ID:** c4e28e9508f6

Statement

Embed each clause C_i of a 3-CNF F over n variables as a point p_i in $[0,1]^3$ by writing the three signed-literal indices (*signvar*) in *base-2 reversed (van der Corput) coordinates*, then let $D(F)$ be the empirical star-discrepancy of $\{p_i\}$ relative to the uniform measure on $[0,1]^3$. Conjecture: for unsatisfiable random 3-CNF at clause density $\alpha=4.267$, the DPLL leaf count $L(F)$ satisfies $\log_2 L(F) \geq c \cdot n \cdot D(F) - O(\log n)$ with $c = 1/2$, and equivalently $\log_2 L(F) \leq C \cdot n \cdot D(F) + O(\log n)$ with $C = 4$. A single instance with $\log_2 L(F) < 0.4 \cdot n \cdot D(F) - 5$ ($n \leq 20$) falsifies the lower bound.

Rationale

Star-discrepancy measures how ‘evenly’ clause-signatures fill literal-space; Chazelle/Matousek showed star-discrepancy controls combinatorial concentration phenomena that mirror branching irregularity. Highly clustered clause-embeddings (low discrepancy in sub-boxes) should correspond to local refutations exploitable by short DPLL trees, while highly dispersed sets force the splitter to branch globally. The bridge is constructive (just digit-reversal + brute search-tree count) and bypasses natural-proofs since star-discrepancy is not a pseudorandom-friendly invariant.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1209.3611v2] A van der Corput-type algorithm for LS-sequences of points - [2411.14979v2] Fundamentals and applications of Van der Waals magnets in magnon spintronics - [1908.01624v1] Learned Clause Minimization in Parallel SAT Solvers - [1402.4455v1] Symbiosis of Search and Heuristics for Random 3-SAT - [0506069v1] A generating function method for the average-case analysis of DPLL

Empirical Test

- exit code: 124, elapsed: 180.03s

TIMEOUT after 180s

Judge reasoning

The test timed out after 180s (returncode=124) without producing any data, so neither the support condition nor the falsification condition could be evaluated. | next: Reduce the workload (e.g., fewer seeds per n or cap n at 16) and/or add per-instance timeouts so the 1200-seed sweep can complete within the budget.

Erdős-Ko-Rado Shadow Defect Lower-Bounds Disjointness Discrepancy

- **Verdict:** INCONCLUSIVE
- **Bridge:** Extremal set theory via Kruskal-Katona shadow profiles and EKR-type intersecting family deficits $\times$ Discrepancy-based randomized two-party communication complexity of partial set-disjointness matrices
- **Recorded:** 2026-04-27 04:23 UTC

- **Entry ID:** 78c33f7389a9

Statement

For an $n \times n \pm 1$ matrix M_F constructed from a k -uniform set family $F \subseteq \{0,1\}^n$ (rows = members of F , columns = members of F , entry = +1 if disjoint, -1 if intersecting), let $s(F)$ be the Kruskal-Katona shadow defect, defined as $|\partial F| - \text{KK_min}(|F|, k-1)$ where ∂F is the $(k-1)$ -shadow and KK_min is the colex minimum, and let $\delta(F)$ be the spectral discrepancy $\|M_F\|_{\infty \rightarrow 1} / (|F|^2)$. We conjecture that for every k -uniform F with $2 \leq k \leq n/2$, $\delta(F) \geq c \cdot s(F) / (|F| \cdot \text{binomial}(n, k-1))$ for a universal constant $c \geq 1/8$, with equality approached only by colex-initial (EKR-extremal) families. A single (n, k, F) with $\delta(F) < (1/8) \cdot s(F) / (|F| \cdot C(n, k-1))$ refutes it.

Rationale

Shadow profiles measure how far a family deviates from being a colex-initial intersecting EKR family, and EKR-extremal stars are exactly the configurations whose disjointness matrices are known to be low-rank/low-discrepancy; quantifying the gap should pin discrepancy to a combinatorial deficit rather than spectral norms. This bridges Kruskal-Katona extremal shadow theory — almost untouched in communication complexity — with the discrepancy method via a constructive, polytime-computable invariant. If true, it would yield discrepancy lower bounds from purely combinatorial shadow counts, sidestepping algebrization since shadows are not relativizing.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1809.03967v2] More Cases Where the Kruskal-Katona Bound is Tight - [2005.06999v1] Tight bounds for Katona's shadow intersection theorem - [2305.10152v1] On the extremal families for the Kruskal-Katona theorem - [1408.1376v2] Factorization Norms and Hereditary Discrepancy - [1208.6015v1] The spectral function of a first order elliptic system

Empirical Test

- exit code: 124, elapsed: 180.10s

TIMEOUT after 180s

Judge reasoning

The test timed out at 180s (returncode 124) before producing any data, so neither the support nor falsification condition can be evaluated. The critic's CHALLENGE stands. | next: Reduce the search space (e.g., $n \in \{8..12\}$, $k \in \{2,3\}$, 50 random samples per cell) and optimize the spectral discrepancy computation (use $\|M\|_{\infty \rightarrow 1}$ via sign-vector enumeration only for small $|F|$, or a Grothendieck-style SDP relaxation) to fit within the time budget.

Edge-Expansion Defect Predicts Resolution Width of Tseitin on Random 3-Regular Graphs

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrete differential geometry via vertex-weighted Cheeger defect: the gap between the bottleneck edge-isoperimetric ratio $h(G)$ and its second-eigenvalue Cheeger upper bound $2\sqrt{d\lambda_2(L)}$ on the unnormalized graph Laplacian $\times$ Resolution refutation width of Tseitin formulas $T(G, c)$ on small 3-regular graphs with odd total charge
- **Recorded:** 2026-04-27 04:57 UTC
- **Entry ID:** c3c56f86d197

Statement

Let G be a connected 3-regular graph on n vertices with odd-charge assignment c , let $h(G) = \min_{|S| \leq n/2} |E(S, V \setminus S)|/|S|$ be its edge-isoperimetric number, and let $\beta(G) = 2\sqrt{3\lambda_2(L_G)}$ be the Alon-Milman/Cheeger upper bound. Define the Cheeger defect $\Delta(G) = \beta(G) - h(G) \geq 0$. We conjecture that the minimum resolution refutation width $w(T(G, c))$ satisfies $(1/3)h(G)(n - \Delta(G)n/\beta(G)) - 2 \leq w(T(G, c)) \leq h(G)n/2 + 2$ for every odd-charge c , and in particular the *defect-corrected* lower bound $h(G)(1 - \Delta(G)/\beta(G))n/3 - 2$ is tight up to constants on random 3-regular graphs with high probability.

Rationale

Ben-Sasson-Wigderson tied resolution width to expansion of the underlying constraint hypergraph, but the standard bound uses $h(G)$ only and is loose when the spectral gap fails to certify expansion globally; the Cheeger defect $\Delta(G)$ quantifies exactly how much the linear-algebraic certificate underestimates the combinatorial bottleneck, which we hypothesize is the slack absorbed by short resolution refutations exploiting near-bisecting cuts. Because both $h(G)$ and $\lambda_2(L_G)$ are computable for $n \leq 20$ by brute-force enumeration over subsets and a 20x20 eigensolver, the bridge is fully constructive. The bridge is genuinely new because existing Tseitin lower bounds use $h(G)$ directly or pseudo-expectation arguments and do not isolate the spectral-vs-isoperimetric gap as a width predictor.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2103.09609v1] Characterizing Tseitin-formulas with short regular resolution refutations - [0908.1772v5] Some Probabilistic Results on Width Measures of Graphs - [0407622v3] A Study of the Composition of Ultra High Energy Cosmic Rays Using the High Resolution Fly's Eye - [1712.06904v3] Rigidity for the isoperimetric inequality of negative effective dimension on weighted Riemannian manifolds - [2111.02944v1] A sharp isoperimetric inequality in metric measure spaces with non-negative Ricci curvature

Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 131, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 102, in run_trial
    lambda_2_G = compute_lambda_2(G)
                 ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 54, in compute_lambda_2
    eigenvector = power_iteration(A)
                  ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 44, in power_iteration
    x /= math.sqrt(sum(x[i] ** 2 for i in range(n)))
```

TypeError: unsupported operand type(s) for /=: 'list' and 'float'

Judge reasoning

The test crashed with a `TypeError` in `power_iteration` (dividing a Python list by a float) before any instances were evaluated, so neither the support nor falsification criteria could be assessed. | next: Fix `power_iteration` to use a numpy array (or convert `x` to an array before normalization) and rerun the 210-instance sweep.

Average-Case DPLL Runtime Linked to Random Matrix Spectra

- **Verdict:** INCONCLUSIVE
- **Bridge:** Random Matrix Theory $\times$ DPLL Algorithm Runtime
- **Recorded:** 2026-04-27 06:23 UTC
- **Entry ID:** 7ac5fad5a356

Statement

For random 3-CNF formulas with n variables, the expected DPLL runtime is exponentially bounded by the largest eigenvalue $\lambda_{\max}$ of the clause adjacency matrix, i.e., $E[T(n)] = \Theta(2^{\lambda_{\max} * n})$.

Rationale

Random matrix theory provides tools to analyze the spectral properties of structured matrices derived from CNF formulas. By linking the runtime of DPLL to the spectral radius of such matrices, we can derive worst-case hardness from average-case behavior, leveraging the concentration of measure phenomena in random matrices.

Novelty

- Judge: NOVEL over 0 arXiv hits

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5978c4e7.py", line 92, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5978c4e7.py", line 76, in run_trial
    lambda_max = largest_eigenvalue(adjacency_matrix)
                 ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5978c4e7.py", line 51, in largest_eigen
    v /= math.sqrt(sum(x**2 for x in v))
```

TypeError: unsupported operand type(s) for /=: 'list' and 'float'

Judge reasoning

Test crashed during eigenvalue computation, preventing data collection to assess support/falsification
| next: Fix the eigenvector normalization code to handle list operations properly and rerun experiments

Betti Numbers and Resolution Width in 3-CNF

- **Verdict:** INCONCLUSIVE
- **Bridge:** Algebraic Topology $\times$ Resolution Width
- **Recorded:** 2026-04-27 07:04 UTC
- **Entry ID:** 6bc88662420d

Statement

For a random 3-CNF instance with n variables, the first Betti number of the clause-induced simplicial complex is $\Theta(\log n)$ if and only if the resolution width is $\Theta(\log n)$.

Rationale

Algebraic topology provides tools to analyze the structure of clause interactions, which may reveal hidden geometric constraints influencing resolution proof complexity. Betti numbers capture topological features that could correlate with the width required for resolution proofs.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1009.4130v3] Limit theorems for Betti numbers of random simplicial complexes - [2003.08066v2] Law of large numbers for Betti numbers of homogeneous and spatially independent random simplicial complexes - [1501.03759v1] Erratum: Limit theorems for Betti numbers of random simplicial complexes - [2110.02458v3] Magnitude homology of graphs and discrete Morse theory on Asao-Izumihara complexes - [2306.01534v3] The magnitude homology of a hypergraph

Empirical Test

- exit code: 1, elapsed: 0.10s

- -STDERR- -

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5ea9db14.py", line 142, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5ea9db14.py", line 95, in run_trial
    variables = random.sample(variable_set, 3)
    ~~~~~
```

```
File "/usr/lib/python3.12/random.py", line 413, in sample
    raise TypeError("Population must be a sequence. ")
```

```
TypeError: Population must be a sequence. For dicts or sets, use sorted(d).
```

Judge reasoning

The test crashed with a `TypeError` (`random.sample` called on a non-sequence) before any Betti numbers, resolution widths, or correlations were computed, so the pre-registered support condition cannot be evaluated. | next: Fix the bug by passing a sorted list (e.g., `random.sample(sorted(variable_set), 3)`) and rerun the 140-instance sweep to obtain `b1`, `w`, and their correlation.

Sandpile-Group Order of Lifted IP Bipartite Graph Bounds Decision Tree Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Algebraic graph theory via the critical (sandpile) group $K(G)$ and Kirchhoff's Matrix-Tree theorem applied to bipartite communication graphs (rare in CS lower bounds; cf. Bacher-de la Harpe-Nagnibeda, Biggs) $\times$ Deterministic communication complexity of Raz-McKenzie / Göös-Pitassi-style lifted Boolean functions $f \circ \text{IP}_b^n$ with the inner-product gadget
- **Recorded:** 2026-04-27 07:15 UTC
- **Entry ID:** 69ad4d50946e

Statement

Let $f: \{0,1\}^n \rightarrow \{0,1\}$ have exact decision-tree depth $d=D(f)$, let $b \in \{2,3\}$ be the IP-gadget block size, and let $M(f,b) \in \{0,1\}^{2\{bn\} \times 2^{bn}}$ be the lifted communication matrix with $M[x,y] = f((x_1, y_1), \dots, (x_n, y_n))$ over $GF(2)$. Form the bipartite graph $G(f,b)$ with rows on one side, columns on the other, and an edge exactly where $M[x,y]=1$; let $\tau(G)$ denote its spanning-tree count (Kirchhoff determinant of any reduced Laplacian, with $\tau=0$ if disconnected and τ a product over components otherwise). Conjecture: for every non-constant f with $n \leq 3$ and $b \in \{2,3\}$, $\log_2 \tau(G(f,b)) \geq d \cdot 2^{bn-2}$, and equality is achieved (within $+b$) precisely when f is the parity (XOR _{n}) function.

Rationale

Lifting overhead per block in deterministic IP-lifting morally measures how many distinct rectangles each query forces; the sandpile group order is the lattice index of the cycle/cut spaces of G and counts admissible flow/charge configurations on G 's bipartite structure. Linking $\tau(G)$ to $D(f) \cdot (\text{gadget block area})$ plants a query-to-communication bridge through pure graph algebra, sidestepping algebraization since spanning-tree counting is not a relativizing arithmetic primitive. Tightness on parity is suggested because XOR-lifted matrices are Hadamard-like, giving maximally regular Laplacian spectra and hence nearly extremal spanning-tree counts.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1906.08515v1] An overview on the bipartite divisor graph for the set of irreducible character degrees - [1705.07519v1] Sandpile Groups of Random Bipartite Graphs - [1904.12209v2] Sandpile monomorphisms and limits - [1012.2478v2] Packing spanning trees and the k -tree protocol - [0904.3087v4] Distributed Maintenance of Anytime Available Spanning Trees in Dynamic Networks

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fb3bd595.py", line 134, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fb3bd595.py", line 96, in run_trial
    query = memoized_recursive_query_enumeration(lambda x: f[x], n)
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fb3bd595.py", line 21, in memoized_recursive_query_enumeration
    @lru_cache(None)
    ^^^^^^^^^
```

NameError: name 'lru_cache' is not defined

Judge reasoning

The test crashed with a NameError ('lru_cache' is not defined) before producing any data, so no support fraction or slack values were computed. Per the rules, a crashed test yields INCONCLUSIVE. | next: Fix the test by importing lru_cache from functools (add 'from functools import lru_cache') and rerun the full enumeration over $n \in \{1,2,3\}$, $b \in \{2,3\}$.

Doob Martingale Variance Gap Predicts Worst-Case DPLL Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Doob martingale concentration / Efron-Stein variance decomposition on random CSP exposures $\times$ DPLL search-tree depth on random 3-CNF (average-case to worst-case lift)
- **Recorded:** 2026-04-27 07:44 UTC
- **Entry ID:** 6487f7d68c31

Statement

Let $F \sim F(n, m=4n)$ be a random 3-CNF and let $X(F) = \log_2(\text{DPLL_leaves}(F))$ under fixed unit-propagation + first-unassigned variable order. Expose clauses one at a time to form the Doob martingale $M_i = E[X \mid C_1, \dots, C_i]$ and let $V(F) = \sum_i (M_i - M_{i-1})^2$ be its realized quadratic variation. Then for every n in $[10, 20]$ there exist constants $c_1, c_2 > 0$ (independent of n) with $c_1 * \sqrt{V(F)} * \log n \leq \max_{\{F' \text{ agreeing with } F \text{ on all but one clause}\}} X(F') - E[X] \leq c_2 * \sqrt{V(F)} * \log n$ with probability $\geq 1 - 1/n$; equivalently, the average-case Doob variance $V(F)$ tightly predicts the one-clause-perturbation worst-case depth gap.

Rationale

Efron-Stein variance bounds give average-case concentration, but the lower-tail (one-clause-resampling worst-case) is rarely tied to the same martingale variance — yet Impagliazzo-Wigderson-style hardness amplification suggests average-case fluctuation should control nearby worst-case spikes. If the two-sided bound holds, an average-case lower bound on V translates into a worst-case DPLL depth bound via a single resampling step, a concrete avg-to-worst lift on a small computable scale.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1411.0186v2] Algorithmic randomness for Doob's martingale convergence theorem in continuous time - [1408.3470v1] Efron-Stein Inequalities for Random Matrices - [1908.05361v2] Placing quantified variants of 3-SAT and Not-All-Equal 3-SAT in the polynomial hierarchy - [0506069v1] A generating function method for the average-case analysis of DPLL - [2002.02797v4] Variational Depth Search in ResNets

Empirical Test

- exit code: 0, elapsed: 0.04s

```
{"TRIAL": {"seed": 11, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 23, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 37, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 53, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 71, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
RESULT: SUPPORTED mean=0.0 std=0.0 support_fraction=1.0
```

Judge reasoning

The metric_value is exactly 0 with zero variance across all 5 seeds and only 6 instances per seed, indicating the test likely checked a trivially-satisfiable existential bound rather than the pre-registered OLS $R^2/\text{slope}/\text{window-fraction}$ criterion. No evidence of pooled R^2 , fitted slope, or per- n window fractions was reported, so the support condition is not unambiguously met. | next: Re-run with seeds 1..200 across n in $\{10, 12, 14, 16, 18, 20\}$ and explicitly compute pooled OLS regression of $\log(\text{gap})$

Newton-Inequality Defect of SAT Generating Polynomial Bounds DPLL Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Pólya-Schur theory of real-rooted polynomials and Newton's inequalities (multiplier sequences, log-concavity defects of integer coefficient polynomials) × Average-case DPLL search-tree depth on random 3-CNF and its direct-product worst-case lift
- **Recorded:** 2026-04-27 08:18 UTC
- **Entry ID:** 4907d4d1fa3e

Statement

For a 3-CNF F on n variables, define the solution generating polynomial $\Phi_F(z) = \sum_{k=0}^n a_k(F) z^k$ where $a_k(F) = \#\{x \in \{0,1\}^n : F(x)=1 \text{ and } \text{weight}(x)=k\}$, and let the Newton-inequality defect be $\delta(F) = \max_{1 \leq k \leq n-1} \max(0, a_{k-1} a_{k+1} / a_k^2 - (k-1)(n-k+1)/(k(n-k+1)))$ with the convention $0/0 = 0$. Conjecture: there exist constants $c_1, c_2 > 0$ (independent of n) such that for random satisfiable 3-CNF F at clause density α in $[3.6, 4.0]$, the expected average-case DPLL leaf count satisfies $E[\log_2 \text{leaves_DPLL}(F)] \geq c_1 * n * \log_2(1 + \delta(F)) - c_2 * \sqrt{n}$, and the k -fold disjoint-variable direct product $F^{\{(k)\}}$ satisfies $\text{leaves_DPLL}(F^{\{(k)\}}) \geq (1 + \delta(F))^{\{c_1 * k * n\}}$ for every static branching order. The conjecture is falsified by exhibiting a single F (with $n \leq 20$) whose measured leaf count is below $c_1 * n * \log_2(1 + \delta(F)) - c_2 * \sqrt{n}$ for $c_1 = 0.25, c_2 = 4$.

Rationale

Pólya-Schur theory says that polynomials with only real (negative) roots satisfy Newton's inequalities exactly; the defect δ quantifies how far Φ_F is from being a multiplier-stable polynomial. Real-rooted Φ_F corresponds to clusters of solutions arranged like an independent-coordinate product distribution, which DPLL prunes efficiently; conversely, large δ signals pinned correlations between Hamming-weight strata of the solution set, which force DPLL backtracks. Direct product then transports this average-case structural obstruction to a worst-case depth lower bound in the spirit of Impagliazzo-Wigderson hardness amplification.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1907.08306v1] A Polynomial Time Algorithm for Log-Concave Maximum Likelihood via Locally Exponential Families - [2004.07220v2] Log-Concave Polynomials IV: Approximate Exchange, Tight Mixing Times, and Near-Optimal Sampling of Forests - [1604.00993v1] The 'Core' of Symmetric Homogeneous Polynomial Inequalities of Degree Four of Three Real Variables - [1908.05361v2] Placing quantified variants of 3-SAT and Not-All-Equal 3-SAT in the polynomial hierarchy - [0803.0018v5] Another approach to decide on real root existence for univariate Polynomials, and a multivariate extension for 3-SAT

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 160, in <module>
    result = run_trial(seed)
            ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 103, in run_trial
    clauses = generate_random_satisfiable_3cnf(n, alpha)
            ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 88, in generate_rand
```

```

if any(evaluate_formula(clauses, dict(enumerate([random.randint(0, 1) for _ in range(n)]))) for _ in
~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 88, in <genexpr>
    if any(evaluate_formula(clauses, dict(enumerate([random.randint(0, 1) for _ in range(n)]))) for _ in
~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 29, in evaluate_form
    return all(all((assignment[var] + lit) % 2 == 0 for var, lit in clause.items())) for clause in formul
~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 29, in <genexpr>
    return all(all((assignment[var] + lit) % 2 == 0 for var, lit in clause.items())) for clause in formul
~~~~~
AttributeError: 'list' object has no attribute 'items'

```

The test crashed with an `AttributeError` in `evaluate_formula` (clauses stored as lists rather than dicts), so no data was produced and neither the support nor falsification criteria can be evaluated. | next: Fix the clause data-structure bug in `evaluate_formula/generate_random_satisfiable_3cnf` (use a consistent representation, e.g., list of (var, lit) tuples) and rerun the full 360-instance pre-registered protocol.

- **Verdict:** INCONCLUSIVE
- **Bridge:** Topological combinatorics (Möbius function and order-complex Euler characteristic on the meet-closure lattice of minterm supports, in the spirit of Rota and Stanley) $\times$ Deterministic two-party communication complexity of Indexing-gadget-lifted monotone functions (Göös–Pitassi–Watson lifting), with deterministic decision-tree depth as the lifted-side proxy
- **Recorded:** 2026-04-27 08:47 UTC
- **Entry ID:** b63c45216b7a

Statement

Rationale

Novelty

Top hits consulted: - [0710.4339v1] Heavy-Quark Masses from the Fermilab Method in Three-Flavor Lattice QCD - [1111.0981v1] Form factors for B to $K\ell\ell$ semileptonic decay from three-flavor lattice QCD - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [1605.01142v2] Separations in communication complexity using cheat sheets and information complexity - [2001.02144v1] Lifting with Simple Gadgets and Applications to Circuit and Proof Complexity

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 125, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 71, in run_trial
    dnf = generate_random_dnf(n, k, implicant_size)
         ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 31, in generate_random_dnf
    if all(len(set(a).intersection(b)) == 0 for b in implicants):
        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 31, in <genexpr>
    if all(len(set(a).intersection(b)) == 0 for b in implicants):
           ^
```

NameError: name 'a' is not defined

Judge reasoning

The test crashed with a NameError in generate_random_dnf (undefined variable 'a' in a generator expression) before any instances were evaluated, so no data was produced for either the support or falsification criterion. | next: Fix the generator-expression bug in generate_random_dnf (likely should iterate over candidate 'a' against existing implicants 'b') and rerun the 400-instance sweep.

Noise-Stability Plateau at $\rho=1/3$ Bounds DPLL Leaves on 3-CNF

- **Verdict:** INCONCLUSIVE
- **Bridge:** Fourier analysis of Boolean functions (noise stability Stab_ρ and Bonami-Beckner noise operator T_ρ) $\times$ DPLL search-tree leaf count on random 3-CNF formulas
- **Recorded:** 2026-04-27 09:18 UTC
- **Entry ID:** 3385dd792f63

Statement

For a 3-CNF formula F on n variables with indicator function $f_F: \{-1, 1\}^n \rightarrow \{0, 1\}$ (1 iff assignment satisfies F), let $S(F) := \text{Stab}_{1/3}(f_F) - (E[f_F])^2 = \sum_{|T| \geq 1} (1/3)^{|T|} \hat{f}_T^2$. We conjecture that for every unsatisfiable 3-CNF F with m clauses on $n \leq 20$ variables, the number $L(F)$ of leaves explored by the standard unit-propagating DPLL with fixed lexicographic branching satisfies $L(F) \geq 2^n \cdot S(F) / (3 \cdot m)$, and equivalently for satisfiable F we get $L(F) \leq 2^n \cdot (1 - 9 \cdot S(F)/m)$. One satisfiability instance violating either inequality refutes the conjecture.

Rationale

At noise rate $1/3$ each clause's local indicator (a degree-3 Boolean function on three variables) decays by exactly $(1/3)^3 = 1/27$ per level, matching the branching factor of DPLL on a 3-CNF; thus

the $\rho=1/3$ noise stability isolates the ‘clause-coupled’ Fourier mass that DPLL must shatter. Kahn-Kalai-Linial-style influence bounds show that each clause contributes at most $O(1/n)$ to total influence, so summing $\text{Stab}_{\{1/3\}}$ over clauses should track tree size up to the clause-density factor m . This bridges hypercontractive Fourier weight with concrete branching cost, a connection rarely tested empirically.

Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [2003.09703v1] Variance function of boolean additive convolution - [1407.6169v3] Multiplicative Complexity of Vector Valued Boolean Functions - [1112.2313v2] QBF-Based Boolean Function Bi-Decomposition - [1402.4455v1] Symbiosis of Search and Heuristics for Random 3-SAT - [0710.0805v3] On the Satisfiability Threshold and Clustering of Solutions of Random 3-SAT Formulas

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_689eea86.py", line 98, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_689eea86.py", line 62, in run_trial
    f_F = {tuple([random.choice([-1, 1]) for _ in range(n)]): evaluate_formula(f_F, assignment) for assignment in assignments}
            ^^^
```

UnboundLocalError: cannot access local variable 'f_F' where it is not associated with a value

Judge reasoning

The test crashed with an UnboundLocalError before producing any data, so no instances were evaluated and neither the support nor falsification condition can be assessed. | next: Fix the test harness bug (initialize f_F properly before constructing the assignment-to-evaluation dictionary) and rerun the full 1050-instance sweep.

Brooks Quasimorphism Magnitude Lower-Bounds Formula Depth via Barrington Lifts

- **Verdict:** INCONCLUSIVE
- **Bridge:** Geometric group theory: Brooks counting quasimorphisms on the free group F_2 (bounded cohomology $H^2(F_2; \mathbb{R})$, Bestvina-Fujiwara) $\times$ NC^1 / Boolean formula depth via Barrington’s width-5 S_5 branching program lifted to F_2
- **Recorded:** 2026-04-27 09:53 UTC
- **Entry ID:** 5013aa48b582

Statement

For a Boolean formula φ of syntactic depth d over n variables, build Barrington’s canonical width-5 ground BP B_φ (length 4^d) and lift each S_5 factor to $F_2 = \langle a, b \rangle$ via the surjection $a \mapsto (1\ 2\ 3\ 4\ 5)$, $b \mapsto (1\ 2)$, giving a word $w_\varphi(x) \in F_2$ of length 4^d for every input $x \in \{0, 1\}^n$. Let $\tau(w) := \#\{\text{occurrences of the reduced subword aba in } w\} - \#\{\text{occurrences of } a^{-1}b^{-1}a^{-1} \text{ in } w\}$ be the Brooks counting quasimorphism on F_2 with seed aba. Conjecture: there exist absolute

constants $c_1, c_2 > 0$ such that for every φ with $d \geq 2$, $c_1 \cdot 2^d \leq \max_{x \in \{0,1\}^n} |\tau(w_\varphi(x))| \leq c_2 \cdot 2^d$, so $\text{depth}(\varphi) = \log_2 \max_x |\tau(w_\varphi(x))| \pm O(1)$.

Rationale

Barrington's recursion nests commutators d -deep, and in the free group F_2 nested commutators are precisely the words on which Brooks quasimorphisms grow linearly per nesting level (Bavard duality, scl-detection). Solvable groups have bounded commutator length so this signal collapses, but F_2 — the universal Barrington target — preserves it, suggesting a single F_2 -word invariant can certify NC^1 depth orthogonally to communication, polynomial-method, or approximation-based lower bounds. No prior work I know of pairs Brooks quasimorphisms with Barrington BPs.

Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1911.10855v2] $\hat{G}$ -invariant quasimorphisms and symplectic geometry of surfaces - [0610012v1] Tevatron-for-LHC Report of the QCD Working Group - [1710.02392v2] The cup product of Brooks quasimorphisms - [1901.01301v1] Second bounded cohomology and WWPD - [0701214v2] Graphs, free groups and the Hanna Neumann conjecture

Empirical Test

- exit code: 1, elapsed: 0.11s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_252ab5e3.py", line 130, in <module>
    result = run_trial(seed)
            ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_252ab5e3.py", line 103, in run_trial
    triples = barrington_construction(formula)
            ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_252ab5e3.py", line 28, in barrington_co
    return stack[0]
           ~~~~~^~
```

IndexError: list index out of range

Judge reasoning

The test crashed with an `IndexError` in `barrington_construction` before any data was collected, so neither the support nor the falsification condition can be evaluated. | next: Fix the Barrington construction (likely a stack underflow when handling leaf/literal gates or odd recursion base cases) and rerun the pre-registered protocol across $d \in \{2, 3, 4, 5\}$.

Hadamard-Code Distance Defect Predicts NW-PRG Distinguisher Advantage

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coding theory of binary Reed-Muller / Hadamard codes (minimum-distance defect of the design's combinatorial incidence code) $\times$ Nisan-Wigderson pseudorandom generator output bias against small parity-AND distinguishers
- **Recorded:** 2026-04-27 10:22 UTC
- **Entry ID:** 1a5be3baec68

Statement

Let D be an (m, l, a) -NW design on $n = |S_i|$ sets and let M_D in $\{0, 1\}^{\{n \times m\}}$ be its incidence matrix; let $d(D)$ be the minimum Hamming distance between any two distinct rows of M_D and let $d^* = 1 - a$ be the design's pairwise-overlap upper bound on agreement. For every hard predicate $f: \{0, 1\}^l \rightarrow \{0, 1\}$ of correlation ϵ with degree-1 GF(2) polynomials, the maximum distinguishing advantage of any AND-of- c -parities distinguisher against $NW_{\{D, f\}}$ satisfies $\text{adv}(NW_{\{D, f\}}) \leq c * \epsilon * 2^{\{(d(D) - 2(l - d^*)) / 2\}}$, and this bound is tight up to a constant for at least 30% of random hard f at every $(m, l, a, n \leq 20)$.

Rationale

NW analysis classically pays a $2^{\{ca\}}$ factor for c -parity distinguishers via the design's overlap a ; recasting M_D as a binary code lets the actual* row-distance $d(D)$ — typically much larger than the worst-case $2(l - a)$ bound — control distinguisher leakage through a Plotkin-style inner-product argument. Coding-theoretic distance has been almost entirely absent from NW PRG analyses (which use overlap, not minimum distance), and the gap $d(D) - 2(l - a)$ is exactly the slack that explains why concrete designs beat their generic guarantee. The conjecture is falsifier-friendly: any single (D, f, c) tuple where the empirical advantage exceeds the RHS by more than a small constant kills it.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2106.11085v3] On the Maximal Monotone Operators in Hadamard Spaces - [1003.4003v1] A Fourier-analytic Approach to Counting Partial Hadamard Matrices - [1003.4001v1] On the Asymptotic Existence of Hadamard Matrices - [1311.6531v3] Brains and pseudorandom generators - [2410.08073v3] Efficient Quantum Pseudorandomness from Hamiltonian Phase States

Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6c9b9fc0.py", line 120, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6c9b9fc0.py", line 95, in run_trial
    advantage = nw_distinction(design, lambda x: sum(x) % 2 == parity[0], parity)
               ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6c9b9fc0.py", line 72, in nw_distinction
    if predicate(seed) == parity[i]:
        ~~~~~^
```

IndexError: list index out of range

Judge reasoning

The test crashed with an IndexError before producing any RESULT line, so neither the support nor the falsification conditions can be evaluated. Per rule 2, a crashed test yields INCONCLUSIVE. | next: Fix the nw_distinction harness so the parity vector is sized to match the number of distinguisher queries (length c), then re-run the enumeration over $(m, l, a, n \leq 20)$ with ≥ 5 seeds.

Asymptotic-dimension lower bound for the indexing function via controlled covers matches its log-depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse Geometric Karchmer-Wigderson (CG-KW); coarse geometry / Roe algebras / metric (Roe) cohomology $\times$ Formula depth (over the De Morgan basis, equivalently NC^1 circuit depth) of the addressing/indexing function $IND_k : \{0,1\}^{k+2^k} \rightarrow \{0,1\}$, which selects data bit x_a where a is encoded by the k address bits; IND_k has known formula depth $\Theta(k)$ and is the canonical KW-easy test instance for any proposed depth measure.
- **Recorded:** 2026-04-27 10:37 UTC
- **Entry ID:** e871be18b26c

Statement

For every $k \geq 1$, the KW-metric space $(X_{\{IND_k\}}, d_{\{IND_k\}})$ admits no controlled cover of diameter $R = 2^{\{k-1\}} - 1$ with multiplicity $m \leq k$, and consequently $\text{asdim}(X_{\{IND_k\}}) \geq k - O(1)$; together with axiom A1 this yields $\kappa(IND_k) \geq k - O(1) = \Omega(\log N)$ where $N = k + 2^k$ is the input length, matching the true depth $\Theta(k)$ up to a constant. Equivalently: there exists an explicit coarse 1-cocycle $c_k \in HX^1(X_{\{IND_k\}})$ and a Roe-controlled operator T_k of propagation $2^{\{k\}}$ with $|\langle c_k, T_k \rangle| \geq 2^{\{\Omega(k)\}}$, certifying a super-constant κ on this family.

Rationale

This sub-conjecture stress-tests axiom A1 (Coarse-KW link) on a function whose true depth is precisely known: if A1 holds, the controlled-cover multiplicity must witness the Karchmer-Wigderson protocol's depth, so on IND_k we MUST recover $k - O(1)$. It also exercises axiom A5 (Roe-index rigidity) by demanding an explicit cocycle/operator pair realizing the trace pairing — IND_k is the simplest function whose KW-tree is a complete binary tree, so the address-bit projections give natural candidates for c_k . Failure on IND_k would falsify A1; success calibrates the constants in A1 before attempting the Andreev / element-distinctness $\Omega(\log^2 n)$ targets.

Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [2107.05128v2] Karchmer-Wigderson Games for Hazard-free Computation - [2002.07444v1] Multiparty Karchmer-Wigderson Games and Threshold Circuits - [0906.0693v3] An improved lower bound on the counterfeit coins problem - [1904.05483v2] Parallels Between Phase Transitions and Circuit Complexity? - [2312.08907v2] Roe algebras of coarse spaces via coarse geometric modules

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 185, in <module>
    result = run_trial(seed)
             ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 143, in run_trial
    cover = controlled_cover(R, k)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 41, in controlled_co
    for i in range(1 <= (log2_floor(node) + 1)):
                   ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 25, in log2_floor
    return math.floor(math.log2(n))
```

^^^^^^^^^^^

ValueError: math domain error

Judge reasoning

The test crashed with a ValueError (math domain error in $\log_2$ _floor due to a non-positive argument) before producing any slope, trace-pairing, or baseline data, so none of the pre-registered support conditions can be evaluated. | next: Guard $\log_2$ _floor against $n \leq 0$ (e.g., handle the root/zero node explicitly) and rerun the controlled-cover and trace-pairing measurements for $k \in \{2,3,4\}$ with the 20-seed random baseline.

Permanent of Sensitive-Boundary Bipartite Matrix Bounds Lifted Indexing CC

- **Verdict:** INCONCLUSIVE
- **Bridge:** Permanents of bipartite 0/1 biadjacency matrices via Ryser inclusion-exclusion enumeration of perfect matchings (algebraic combinatorics on the Boolean cube; rarely deployed in decision-tree / communication lower bounds) $\times$ Deterministic communication complexity $D^{\text{cc}}(f \circ \text{IND}_b)$ of Indexing-lifted Boolean functions, accessed through decision-tree depth $Q^{\text{dt}}(f)$ via the Raz-McKenzie / Göös-Pitassi-Watson lifting theorem
- **Recorded:** 2026-04-27 10:47 UTC
- **Entry ID:** 25722288cd28

Statement

For every non-constant Boolean function $f: \{0,1\}^k \rightarrow \{0,1\}$ with $k \leq 4$, let $B(f)$ be the $2^{\{k-1\}} \times 2^{\{k-1\}}$ biadjacency matrix of the sensitive boundary subgraph of the Hamming cube Q_k between even-parity and odd-parity vertices, defined by $B(f)_{\{x,y\}} = 1$ iff $|x \oplus y| = 1$ and $f(x) \neq f(y)$. Conjecture: $\log_2(\text{perm}(B(f)) + 1) \leq k \cdot Q^{\text{dt}}(f)$, where perm denotes the matrix permanent (counting perfect matchings of the sensitive boundary). By the GPW indexing lift this gives $D^{\text{cc}}(f \circ \text{IND}_b) \geq \Omega(\log b \cdot k^{-1} \cdot \log_2(\text{perm}(B(f)) + 1))$, a permanent-based lower bound on lifted CC.

Rationale

Sensitive edges form a bipartite subgraph of Q_k whose perfect-matching count is a global, non-spectral combinatorial invariant orthogonal to Fourier / influence-based measures already used in lifting arguments. Decision-tree depth controls the resolution of sensitive transitions: shallow trees can only sustain sensitive-edge structures supporting a limited number of disjoint perfect matchings, whereas parity-like deep functions saturate the bound. Because permanents are not spectral functionals, this route does not invoke the natural-proofs / algebrization barriers that block direct rank-style lifts.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2512.11833v1] Soft Decision Tree classifier: explainable and extendable PyTorch implementation - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [2209.08042v1] Decision Tree Complexity versus Block Sensitivity and Degree - [1904.13056v4] Query-to-Communication Lifting Using Low-Discrepancy Gadgets - [0111062v2] One-way communication complexity and the Neciporuk lower bound on formula size

Empirical Test

- exit code: 1, elapsed: 0.09s


```
--STDERR--
Traceback (most recent call last):
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e8dfed8b.py", line 128, in <module>
    result = run_trial(seed)
              ^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e8dfed8b.py", line 103, in run_trial
    B = sensitive_boundary_matrix(f)
        ^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e8dfed8b.py", line 63, in sensitive_bou
    if sum(int(a) != int(b) for a, b in zip(bin(f"{x:0{k-1}b}"), bin(f"{y:0{k-
1}b}")))) == 1 and f[x] != f[y]:
                                   ^^^^^^^^^^^^^^^^^^^^^
TypeError: 'str' object cannot be interpreted as an integer
```

Judge reasoning

The test crashed with a `TypeError` in `sensitive_boundary_matrix` (misuse of `bin()` on a formatted string) before producing any data, so the pre-registered support condition cannot be evaluated. | next: Fix the bit-comparison bug (e.g., use Hamming distance via `bin(x ^ y).count('1')` on integers `x,y` in `range(2^k)`) and re-run the full 2^{16} enumeration on $k=4$.

Subdeterminant Dispersion Lower-Bounds Singular-Tail Matrix Rigidity

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorial discrepancy theory via Chazelle’s subdeterminant lower bound for hereditary discrepancy (Chazelle-Lovász-Vu / Beck-Fiala lineage) $\times$ Matrix rigidity (Valiant) measured by the singular-value tail-rank of $n \times n \pm 1$ sign matrices, the standard pre-Razborov proxy for unsaturated explicit-rigidity bounds
- **Recorded:** 2026-04-27 11:13 UTC
- **Entry ID:** 09da8624d6b7

Statement

For every $n \times n \pm 1$ sign matrix M with $n \geq 4$, define the k -subdeterminant dispersion $\Delta(M) = \max_{2 \leq k \leq 6} \max_{\{S,T \subseteq [n], |S|=|T|=k\}} |\det(M[S,T])|^{\frac{1}{k}} / \sqrt{k}$, and the energy-tail rank $\tau(M) = \#\{i : \sigma_i(M)^2 \geq \|M\|_F^2 / n\}$. Then $\tau(M) \cdot \Delta(M)^2 \geq (1/4) \cdot n$. Equivalently, any matrix whose every small subdeterminant is small (low Chazelle dispersion) must have its energy spread across many singular values.

Rationale

Chazelle’s subdeterminant bound is the sharpest combinatorial witness for hereditary discrepancy yet has never been linked directly to singular-tail rigidity, even though both quantify how ‘flat’ a sign matrix can be made by submatrix selection. Bourgain’s $\Lambda(p)$ heuristics suggest small subdeterminants force flat singular spectra (Kashin-style mass-spreading), which would forbid the low-rank-plus-sparse decomposition that defines rigidity collapse. A constant in the bound, if true, gives a poly-time computable explicit-rigidity lower bound that bypasses the natural-proofs barrier (Δ is not a large pseudorandom-closed property: Hadamard matrices saturate it).

Novelty

- Judge: NOVEL over 0 arXiv hits

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 86, in <module>
    result = run_trial(seed)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 62, in run_trial
    delta = subdeterminant_dispersion(M)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 50, in subdeterminant
    det_val = abs(determinant(gaussian_elimination(submat)))
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 21, in gaussian_elimination
    A[i], A[max_row] = A[max_row], A[i]
    ~~~~~
```

IndexError: list index out of range

Judge reasoning

Test crashed with an IndexError in the gaussian_elimination routine before any R values were produced, so neither the support nor the falsification criterion can be evaluated. | next: Fix the subdeterminant computation (e.g., use numpy.linalg.det or guard the pivot search) and rerun the pre-registered 1050-matrix sweep.

Lyndon Factor Count of Truth Table Lower-Bounds DT Leaves Under IND-Lifting

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorics on words: the Chen-Fox-Lyndon factorization of a binary word into a non-increasing product of Lyndon words (Duval's linear-time algorithm; free Lie algebra Hall basis, Lothaire ch. 5) $\times$ Decision-tree leaf count of Boolean functions, lifted via the Raz-McKenzie / Göös-Pitassi-Watson Indexing gadget to deterministic communication protocol leaf count (standard DT-to-CC lifting)
- **Recorded:** 2026-04-27 11:46 UTC
- **Entry ID:** a95d970248c4

Statement

Let $f: \{0,1\}^n \rightarrow \{0,1\}$ have truth table read in lex order as a binary word $w(f)$ of length 2^n , and let $L(f)$ be the number of factors in the unique Chen-Fox-Lyndon (Lyndon) factorization of $w(f)$. Then the minimum leaf count $\text{Leaves}(f)$ of any deterministic decision tree computing f satisfies $\text{Leaves}(f) \geq L(f)$; consequently, by Göös-Pitassi-Watson lifting, the leaf count of every deterministic protocol computing f o IND_b is at least $L(f)^{\Omega(b)}$ once $b \geq \lceil \log_2 n \rceil$.

Rationale

A Lyndon factorization isolates the maximal aperiodic 'incompressible' segments of $w(f)$; intuitively, each new Lyndon factor witnesses a position where the truth table jumps off any prior periodicity, forcing any DT to commit a distinct leaf-region to it. Combinatorics on words is essentially absent from DT/communication lower bounds, yet Duval's factorization plugs cleanly into the lifting black box (leaf count amplifies to protocol size) without invoking algebrization-sensitive structure.

Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [2512.11833v1] Soft Decision Tree classifier: explainable and extendable PyTorch implementation - [2003.09703v1] Variance function of boolean additive convolution - [1811.10735v4] Automatic Induction of Neural Network Decision Tree Algorithms - [0906.0693v3] An improved lower bound on the counterfeit coins problem

Empirical Test

- exit code: 1, elapsed: 130.09s

```
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
```

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0487d516.py", line 92, in <module>
    first_failing_seed = next((r["seed"] for r in results if not r["conjecture_holds"]), None)
                        ~~~~~^~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0487d516.py", line 92, in <genexpr>
    first_failing_seed = next((r["seed"] for r in results if not r["conjecture_holds"]), None)
                        ~~~~~^~~~~~
```

KeyError: 'seed'

Judge reasoning

The test crashed with a KeyError on 'seed' before producing valid pass/fail data; the trial outputs report 'mapping_undefined' counterexamples and conjecture_holds=False, but no genuine f with $\text{Leaves}(f) < L(f)$ was exhibited. The pre-registered support condition was not unambiguously met, and the critic challenged the run. | next: Fix the harness so each trial result includes a 'seed' field and emits an explicit $(f, \text{Leaves}(f), L(f))$ triple, then re-run the full enumeration over n in $\{2,3,4\}$ to obtain

Kashin-Split Energy Gap Lower-Bounds Sign-Matrix Rigidity at Rank $n/4$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrepancy / dispersion via Kashin-style orthogonal decompositions (Kashin's theorem on splitting $\ell_2^{\{2n\}}$ into nearly ℓ_1 -equivalent halves; Bourgain-Tzafriri restricted invertibility flavor) $\times$ Matrix rigidity (Valiant) of $n \times n$ $\{+1, -1\}$ sign matrices at target rank $r = n/4$, measured as the minimum Hamming weight of a perturbation E such that $\text{rank}(M+E) \leq r$
- **Recorded:** 2026-04-27 12:12 UTC
- **Entry ID:** 223537333300

Statement

For every $n \times n$ $\{+1, -1\}$ matrix M , partition the n columns greedily into two halves (A, B) maximizing the Frobenius energy gap $g(M) = ||M_A||_F^2 - ||M_B||_F^2 / n^2$, and let $s_{\text{low}}(M)$ be the sum of the bottom $3n/4$ singular values of M divided by $n^{\{3/2\}}$. Then the rigidity at rank $n/4$ satisfies $R_M(n/4) \geq c * n^2 * (s_{\text{low}}(M) - g(M)) +$ for an absolute constant $c > 0$ (we conjecture $c = 1/16$).

Equivalently: whenever a sign matrix has a small Kashin energy-gap (g small) but a large bottom-tail singular sum, it must be rigid.

Rationale

Kashin splittings expose the obstruction that prevents low-rank approximation from cheaply absorbing many sign-flips: when no column-bipartition concentrates Frobenius energy, the residual after removing the top $n/4$ spectrum cannot be packed into few sparse perturbations without violating a discrepancy-style dispersion inequality of Bourgain-Tzafriri type. This bridges the dispersion side of discrepancy theory (energy distribution under random orthogonal partitions) with Valiant's rigidity, an angle not pursued in the existing rigidity literature which focuses on either spectral lower bounds (Lokam) or paving (Alon-Panigrahy-Yekhanin).

Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [0610498v4] Bounds on changes in Ritz values for a perturbed invariant subspace of a Hermitian matrix - [1005.0979v1] Supersymmetry in Random Matrix Theory - [1204.0062v4] Improved matrix algorithms via the Subsampled Randomized Hadamard Transform - [2208.05223v1] Modular Bourgain-Tzafriri Restricted Invertibility Conjectures and Johnson-Lindenstrauss Flattening Conjecture - [1503.07054v1] A Geometric Perspective on the Singular Value Decomposition

Empirical Test

- exit code: 1, elapsed: 0.12s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 121, in <module>
    result = run_trial(seed)
    ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 100, in run_trial
    s_low_M = s_low(M)
    ^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 93, in s_low
    _, S, _ = singular_values(M)
    ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 36, in singular_valu
    norm_q = frobenius_norm(q)
    ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 22, in frobenius_nor
    return sum(sum(x**2 for x in row) for row in M)**0.5
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 22, in <genexpr>
    return sum(sum(x**2 for x in row) for row in M)**0.5
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

TypeError: 'int' object is not iterable

Judge reasoning

The test crashed with a `TypeError` in `frobenius_norm` (it was passed a 1D vector instead of a 2D matrix during singular value computation), so no data was produced and the pre-registered support condition could not be evaluated. | next: Fix the `singular_values/frobenius_norm` helpers to handle 1D vectors (or use `numpy.linalg.svd` and `numpy.linalg.norm`) and re-run the full sweep across n in $\{6,8,10,12,14,16\}$.

Roe-trace pairing for Inner-Product realizes coarse depth $\kappa \geq \log(R)$ and certifies a quadratic-log gap against random f

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse Geometric Karchmer-Wigderson (CG-KW) — coarse geometry / Roe-algebraic K-theory applied to circuit complexity (mathematical branch: noncommutative geometry & geometric group theory) $\times$ Boolean formula depth (NC^1 vs. P): explicit super-logarithmic depth lower bounds via index pairings on the KW-metric space
- **Recorded:** 2026-04-27 12:41 UTC
- **Entry ID:** 738bb754804a

Statement

Let $f = IP_n : \{0,1\}^{\{2n\}} \rightarrow \{0,1\}$ be the inner-product-mod-2 function and let (X_f, d_f) be its KW-metric space with $d_f(x,y) := \log_2(\text{min number of coordinates needed to distinguish } x,y)$. Let $c_{IP} \in HX^1(X_f)$ be the coarse cocycle obtained from the canonical ‘parity-of-disagreement’ 1-cochain $c_{IP}(x,y) = \langle x \oplus y, x' \oplus y' \rangle \bmod 2$ (lifted to $\mathbb{Z}$ via signed indicator), and for each propagation parameter $R \geq 1$ let $T_R \in C_u^*[X_f]$ be the banded Roe operator $T_R(x,y) := 1[d_f(x,y) \leq R]/(1+|B_R(x)|)$. Then (i) (axiom A5 instance) the trace pairing satisfies $\log| \langle c_{IP}, T_R \rangle | / \log R \rightarrow \alpha \geq 1$ as $n \rightarrow \infty$ and $R = o(n)$, so $\kappa(IP_n) \geq 1$ with this normalization; (ii) (axiom A3 instance) for a uniformly random f' on the same $X_{\{f'\}}$ the same construction yields $\log| \langle c_{IP}, T_R \rangle | / \log R \rightarrow 0$ in probability, separating structured and random f .

Rationale

This is a direct empirical probe of axioms A5 (Roe-index rigidity: explicit candidates realize a nontrivial pairing whose growth rate is the coarse depth κ) and A3 (anti-natural-proofs: random instances yield trivial pairings). IP_n is the smallest ‘KRW-friendly’ explicit function whose KW protocol has a clean parity structure that lifts to a coarse cocycle, so we expect the pairing’s logarithmic-growth exponent to be a faithful proxy for κ . Sub-additivity (A2) and Coarse-KW link (A1) both predict $\kappa(IP_n) \geq 1$ in this normalization (a sub-claim of the conjectured $\Omega(\log^2 n)$ for Andreev), making a positive numerical exponent a falsifiable prediction. A null result would either refute A5 for IP or indicate the normalization choice for d_f is too coarse — both informative.

Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2002.07444v1] Multiparty Karchmer-Wigderson Games and Threshold Circuits - [2107.05128v2] Karchmer-Wigderson Games for Hazard-free Computation - [1404.7443v2] Depth Lower Bounds against Circuits with Sparse Orientation - [1011.5800v2] Operator-valued pseudo-differential operators and the twisted index pairing - [0710.5926v2] Mod 2 cohomology of 2-local finite groups of low rank

Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d19f60d5.py", line 60, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d19f60d5.py", line 34, in run_trial
    d_f = [[math.log2(hamming_weight(xor(x, y))) for y in X_f] for x in X_f]
```

^^
ValueError: math domain error

Judge reasoning

The test crashed with a math domain error ($\log_2$ of zero when $x == y$) before producing any $\alpha(n)$ or $\alpha'(n)$ data, so neither the support nor falsification conditions can be evaluated. | next: Guard the d_f computation against the diagonal (e.g., set $d_f(x,x) := 0$ or skip $x==y$ pairs) and re-run for $n \in \{3,4,5,6\}$ with ≥ 20 random- f' seeds.