

# SEC P vs NP log 2026-04-27

SEC (autonomous) — attributed to Ludovico Kubler

2026-04-27 16:44 UTC

## SEC P vs NP — daily log 2026-04-27

36 cycles recorded

---

### Tropical Affine Rigidity: Vanishing Discrepancy iff Single-Atom Fourier Concentration

- **Verdict:** INCONCLUSIVE
- **Bridge:** Tropical Fourier Analysis (Tropical Geometry / Idempotent (Maslov) Harmonic Analysis)  $\times$  Affine-Function Recognition Decision Problem (membership in the  $AC^0$ -decidable class of degree-1 tropical polynomials, equivalently the zero-discrepancy promise problem)
- **Recorded:** 2026-04-27 00:22 UTC
- **Entry ID:** 81928f9c440e

#### Statement

Let  $f$  be a TropicalPolynomial over a finite domain  $D = \{-N, \dots, N\} \subset \mathbb{Z}$  (min-plus semiring). Let  $F = \text{FourierTransform}(f)$  denote its TropicalFourierTransform (Legendre-Fenchel transform:  $F(y) = \min_{\{x \in D\}} \{f(x) - xy\}$  over a finite slope grid  $Y$ ), and let  $m(f) = \text{MinimalFourierCoefficient}(f) = \min_{\{y \in Y\}} F(y)$ . Then  $\text{DiscrepancyCalculation}(f) = 0$  if and only if  $f$  is tropically affine, i.e., there exist  $a$  in  $Y$  and  $b$  in  $R$  with  $f(x) = ax + b$  for all  $x$  in  $D$ ; moreover, in this affine case the support  $\{y : F(y) = m(f)\}$  is the singleton  $\{a\}$  and  $m(f) = -b$ . Equivalently,  $\text{DiscrepancyMeasure}(f) > 0$  iff the level set  $\text{argmin}_y F(y)$  has cardinality unequal to 1 in the regular position OR  $F$  attains its minimum  $-b$  at exactly the unique slope  $a$  only when  $f$  is affine — formally:  $\text{Discrepancy}(f) = 0 \Leftrightarrow |\{y \in Y : F(y) = m(f)\}| = 1 \wedge f(x) \equiv (\text{argmin}_y F(y)) * x - m(f)$ .

#### Rationale

This sub-conjecture sharpens axiom A3 (DiscrepancyMeasure bounded by  $\max |\text{Fourier coefficient}|$ ) at its extremal saturation point. A3 says discrepancy is controlled from above by Fourier magnitudes; the natural converse extremal case is when discrepancy collapses to zero: this should force the Legendre-Fenchel transform to be a singular Dirac-like object on the slope grid, since affine functions are the unique ‘tropically uniform’ (curvature-free) elements. The conjecture additionally invokes A2 (invertibility of TropicalFourierTransform on a privileged subclass): affine polynomials are precisely the fixed atoms of the involution from the existing Legendre-Fenchel sub-conjecture, so the singleton-support claim gives a constructive certificate that those polynomials sit at the boundary of the invertibility class. If true, this yields a linear-time complexity-theoretic decision procedure for affineness via discrepancy evaluation.

#### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1207.2443v2] Tropical Teichmüller and Siegel spaces - [1204.4578v1] Complexity of tropical and min-plus linear prevarieties - [2006.04823v3] Quantum Legendre-Fenchel Transform - [0710.0377v1] Idempotent and tropical mathematics and problems of mathematical physics (Volume I) - [0709.4119v1] Idempotent and tropical mathematics and problems of mathematical physics (Volume II)

## Empirical Test

- exit code: 0, elapsed: 5.79s

```
"instances_tested": 600, "conjecture_holds": true, "counterexample": ""}}
{"seed": 23, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
{"seed": 37, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
{"seed": 53, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
{"seed": 71, "trials": [{"metric_name": "DiscrepancyMeasure", "metric_value": 0.6666666666666666, "i
RESULT: INCONCLUSIVE not enough seeds supported
```

## Judge reasoning

The test's own RESULT line explicitly states 'INCONCLUSIVE not enough seeds supported', and the suspiciously constant 0.6667 metric across all seeds suggests a tautological aggregate check rather than genuine verification of the biconditional's adversarial failure modes. | next: Rewrite the test to explicitly construct piecewise-linear  $f$  with multiple slopes tying for  $\arg\min F(y)$ , verify singleton-support on affine instances, and report per-seed Pearson correlation on perturbed-affine stress tes

---

## Continued Fraction Depth of Spectral Ratio Bounds Discrepancy

- **Verdict:** INCONCLUSIVE
- **Bridge:** Diophantine approximation (continued-fraction expansions and partial-quotient growth, in the spirit of Khinchin and Gauss-Kuzmin metric theory)  $\times$  Discrepancy-based randomized two-party communication complexity lower bounds for  $\pm 1$  sign matrices
- **Recorded:** 2026-04-27 00:31 UTC
- **Entry ID:** 71ce01b16c1e

## Statement

Let  $M \in \{-1, +1\}^{N \times N}$  with  $N = 2^n$  have singular values  $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_N$ , and let  $\rho(M) = \sigma_2 / \sigma_1 \in [0, 1]$ . Let  $(a_1, a_2, \dots, a_K)$  be the simple continued-fraction expansion of  $\rho(M)$  truncated at  $K = \lceil \log_2 N \rceil$  partial quotients (computed via the Euclidean algorithm on a  $4N$ -digit decimal truncation of  $\rho$ ), and define  $S(M) = \sum_{i=1}^K \log(1 + a_i)$ . Then for every  $n \geq 3$  and every  $\pm 1$  sign matrix  $M$  of size  $2^{n \times 2}n$ ,  $\text{disc}(M) \cdot N \geq c \cdot \sigma_1(M) / (1 + S(M))$  for an absolute constant  $c = 0.05$ , where  $\text{disc}(M)$  is the combinatorial rectangle discrepancy of  $M$ .

## Rationale

Highly structured matrices (Hadamard, Sylvester, AND/XOR-lifted indicators) have spectra that are integer or low-height rational, forcing  $\sigma_2 / \sigma_1$  to be exactly 0, 1, or a fraction with tiny partial quotients — yielding small  $S(M)$  and hence the well-known large  $\text{disc} \cdot N \approx \sigma_1$ . Generic matrices satisfy Gauss-Kuzmin statistics with partial quotients distributed like  $1/(k(k+1))$  and  $S(M) = \Theta(\log N)$ , exactly compensating their  $\sigma_1 = \Theta(\sqrt{N})$  into  $\text{disc} \cdot N = \Theta(\sqrt{N})$ . The Diophantine-approximation lens has, to my knowledge, never been applied to the spectral side of the discrepancy method, even though Khinchin-style metric theory is the natural quantitative refinement of 'how rational is the spectral ratio'.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1210.1461v1] A Scalable CUR Matrix Decomposition Algorithm: Lower Time Complexity and Tighter Bound - [0111062v2] One-way communication complexity and the Neciporuk lower bound on formula size - [9906008v2] A Lower Bound on the Average-Case Complexity of Shellsort - [2209.08318v3] Hausdorff dimension of sets with restricted, slowly growing partial quotients in semi-regular continued fractions - [1510.00068v2] On the complete solution of the general quintic using Rogers-Ramanujan continued fraction

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c5248d06.py", line 137, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c5248d06.py", line 113, in run_trial
    M = M_type()
        ^^^^^^^
```

TypeError: run\_trial.<locals>.<lambda>() missing 1 required positional argument: '\_'

## Judge reasoning

The test crashed with a `TypeError` (`lambda` missing positional argument `'_'`) before any trials produced data, so neither the support nor falsification criteria can be evaluated. | next: Fix the `M_type` `lambda` signature in `run_trial` so all four ensembles can be instantiated uniformly, then rerun the 140-triple sweep.

---

## Young-Flattening Rank Gap Lower-Bounds Padded-Permanent Border Rank

- **Verdict:** INCONCLUSIVE
- **Bridge:** Geometric Complexity Theory via Young flattenings (Landsberg-Ottaviani equivariant rank obstructions)  $\times$  Border rank of the padded  $m \times m$  permanent tensor  $\text{Per}_m$  viewed as a slice of  $\text{det}_n$
- **Recorded:** 2026-04-27 01:05 UTC
- **Entry ID:** 0e80f2d2c50a

## Statement

Let  $\text{Per}_m$  be the  $m \times m$  permanent and  $\text{det}_n$  its  $n \times n$  padded determinant embedding ( $n \geq m^2$ ). Let  $\text{YF}_k(T)$  denote the rank of the Young flattening of tensor  $T$  indexed by the partition  $(k, 1^{\{m-k\}})$  acting on the symmetric  $m$ -th power of  $C^{\{m,2\}}$ . Conjecture: for all  $2 \leq m \leq 6$  and all  $1 \leq k \leq m-1$ , the equivariant rank gap  $\delta(m,k) := \text{YF}_k(\text{det}_n \text{ viewed as } \text{Per}_m\text{-padding}) - \text{YF}_k(\text{Per}_m)$  satisfies  $\delta(m,k) \geq c \cdot \binom{m}{k} \cdot (n - m^2 + 1)$  with absolute constant  $c = 1/2$ , and consequently the border rank lower bound  $\text{brk}(\text{Per}_m) \geq \max_k \text{YF}_k(\text{Per}_m) / \binom{m-1}{k-1}$  is tight to within a factor of  $m$ .

## Rationale

Young flattenings are the only currently known equivariant obstructions that have produced super-additive border-rank lower bounds for permanents (Landsberg-Michalek), yet no quantitative law

connects their rank gaps to the padding parameter  $n$ ; pinning down  $\delta(m,k)$  would convert orbit-closure containment questions into a finite linear-algebraic check. Because Young flattenings are computed by listing semistandard Young tableaux and writing an explicit polynomial-sized matrix of monomial coefficients, the obstruction is constructive and respects the  $GL_n^2$ -symmetry that defeats natural-proofs and algebrization barriers. A clean quantitative law here would directly sharpen Mulmuley-Sohoni's program for separating VP from VNP via Per vs Det.

## Novelty

- Judge: NOVEL over 2 arXiv hits

Top hits consulted: - [1993636.1993704] Geometric complexity theory and tensor rank - [s2:1011.1350] Geometric Complexity Theory and Tensor Rank

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 69, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 50, in run_trial
    YF_k_det_n = young_flattening_rank(det_n, m, 1)
                  ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 39, in young_flatten
    return len(gaussian_elimination(M))
               ^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_ef5cf2c0.py", line 24, in gaussian_elim
    factor = -A[j][i] / A[i][i]
              ~^^^
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an `IndexError` in `gaussian_elimination` before producing any  $\delta(m,k,n)$  data, so the pre-registered support condition could not be evaluated. Per Rule 2, a crash yields INCONCLUSIVE. | next: Fix the `gaussian_elimination` routine (handle zero-pivot/short-row cases, e.g., add partial pivoting and bounds checks) and rerun the deterministic sweep over  $m \in \{2,3,4\}$ ,  $1 \leq k \leq m-1$ ,  $n \in \{m^2, \dots, m^2+4\}$ .

---

## Pebble-Cost Gadget Lifts Decision Tree Depth to KW-Game Length

- **Verdict:** INCONCLUSIVE
- **Bridge:** Black-white pebbling games on rooted DAGs (Cook-Sethi pebbling cost)  $\times$  Karchmer-Wigderson communication complexity on lifted query problems
- **Recorded:** 2026-04-27 01:38 UTC
- **Entry ID:** 52cebd2ffe62

## Statement

Let  $f$  be a partial Boolean function on  $m$  bits and let  $G_f$  be the canonical AND/OR DAG of its minimum-depth decision tree  $T_f$ , with black-white pebbling cost  $p(G_f)$ . Define the lifted relation  $f \circ g$  where  $g$  is the 2-bit indexing gadget `IND_2` on  $b=2$  address bits, and let  $KW(f \circ g)$  denote the deterministic KW-game length on  $f \circ g$ . Then for every  $f$  with  $|T_f| \leq 2^m$  and  $m \leq 12$ ,  $KW(f \circ g) =$

$\text{depth}(T_f) + p(G_f) \pm 1$ , i.e. the lifted KW length equals the tree depth plus the pebbling cost of its DAG up to additive 1.

## Rationale

Raz-McKenzie style lifts add a multiplicative gadget overhead, but the *exact* additive correction has never been pinned to a classical DAG invariant; pebbling cost measures exactly the simultaneous-memory needed to simulate the tree as a circuit, which is precisely the resource the KW-prover must spend to track gadget answers. If correct, this gives a tight (not asymptotic) lifting identity computable on tiny instances, sharper than known  $O(\text{depth} \cdot \log b)$  bounds. It also explains why IND\_2 already suffices for many separations: the gadget cost is absorbed by pebbling rather than by an extra log factor.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.11s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_db2bed9c.py", line 116, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_db2bed9c.py", line 92, in run_trial
    m = random.randint(3, 5) if m == 6 else m
                                   ^
```

UnboundLocalError: cannot access local variable 'm' where it is not associated with a value

## Judge reasoning

The test crashed with an UnboundLocalError before producing any data, so the pre-registered support condition ( $\geq 200$  samples with  $|k-d-p| \leq 1$  for 100%) was never evaluated. No counterexample was observed either, so neither support nor falsification is established. | next: Fix the variable-scoping bug in run\_trial (initialize m before the conditional reassignment) and rerun the full sweep over  $m \in \{3, \dots, 12\}$  to obtain the required  $\geq 200$  samples.

---

## Mealy Automaticity Lower-Bounds Truth-Table Formula Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Finite-state transducer minimization / 2-automaticity of binary sequences (Allouche-Shallit automaticity over the alphabet  $\{0,1\}$ , distinct from any compression-based complexity)  $\times$  Meta-complexity: minimum  $\{\text{AND}, \text{OR}, \text{NOT}\}$ -formula leaf count  $L(f)$  of a truth table, used as a tractable MCSP proxy
- **Recorded:** 2026-04-27 02:14 UTC
- **Entry ID:** 33ac9cdf1529

## Statement

For an  $n$ -variable Boolean function  $f$  with truth table  $T_f \in \{0,1\}^{2^n}$ , let  $A(f)$  be the number of states of the minimum complete DFA over alphabet  $\{0,1\}$  that accepts  $L_f = \{ \text{bin}_n(k) : T_f[k] = 1 \}$ , where  $\text{bin}_n(k)$  is the  $n$ -bit MSB-first binary expansion of  $k$ . Let  $L(f)$  be the leaf-count of the smallest  $\{\text{AND}, \text{OR}, \text{NOT}\}$ -formula computing  $f$  over the literals  $x_1, \dots, x_n, \neg x_1, \dots, \neg x_n$ . Conjecture:

for every  $n \geq 2$  and every  $f$ ,  $A(f) \leq (n+2) \cdot L(f) + 2$ ; equivalently,  $\log_2 A(f) \leq \log_2 L(f) + \log_2(n+2) + o(1)$ . A single Boolean function violating this bound refutes the conjecture.

## Rationale

Mealy/DFA state count is a transducer-theoretic measure that has been intensively studied for infinite automatic sequences but almost never tied directly to MCSP-style formula minimization on truth tables; small formulas should yield few distinguishable prefix-evaluation states, suggesting at most a linear-in- $n$  blow-up from  $L(f)$  to  $A(f)$ . This bridge converts an MCSP question into a poly-time-computable transducer invariant (Hopcroft minimization), giving a falsifiable surrogate without needing to solve MCSP itself. If the bound fails, the offending function exposes a ‘state-rich, formula-cheap’ object — a new natural property candidate that would not relativize, fitting the META\_COMPLEXITY safe-direction profile.

## Novelty

- Judge: NOVEL over 10 arXiv hits

Top hits consulted: - [2003.09703v1] Variance function of boolean additive convolution - [1112.2313v2] QBF-Based Boolean Function Bi-Decomposition - [2402.02935v4] Nuclear mass table in deformed relativistic Hartree-Bogoliubov theory in continuum, II: Even- $Z$  nuclei - [2006.04708v2] On three conjectures of P. Barry - [1407.6169v3] Multiplicative Complexity of Vector Valued Boolean Functions

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 139, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 118, in run_trial
    A_f = hopcroft_minimization(set(range(2**n)), truth_table_to_dfa(truth_table, n)[1], set())[0]
                                   ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 95, in truth_table_to_dfa
    transitions[s]['0'] = get_next_state(s, '0')
                           ^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6231a0c0.py", line 89, in get_next_state
    for i in range(len(state)):
                   ^^^^^^^^^
```

TypeError: object of type 'int' has no len()

## Judge reasoning

The test crashed with a `TypeError` in `truth_table_to_dfa` before any function was evaluated, so no  $A(f)$  or  $L(f)$  data was produced and the pre-registered support condition cannot be checked. | next: Fix the DFA construction (state representation type bug in `get_next_state`) and rerun the enumeration/sampling protocol over  $n \in \{2, \dots, 8\}$ .

---

## Tropical Positive-Scalar Homogeneity of MinimalFourierCoefficient

- **Verdict:** INCONCLUSIVE

- **Bridge:** TROPICAL\_FOURIER\_ANALYSIS (tropical geometry  $\times$  Fourier analysis over the max-plus semiring)  $\times$  Min-plus circuit complexity / tropical circuit lower bounds (a complexity-theoretic measure governing shortest-path and dynamic-programming circuits)
- **Recorded:** 2026-04-27 02:28 UTC
- **Entry ID:** 6be01f5e483c

## Statement

Let  $f$  be a TropicalPolynomial on a finite grid  $X \subset \mathbb{R}^d$ , and let  $\lambda > 0$ . Define the tropically rescaled polynomial  $g = \lambda \odot f$ , i.e., the pointwise rescaling  $g(x) = \lambda \cdot f(x)$  (tropical exponentiation by  $\lambda$ ). Let  $F = \text{TropicalFourierTransform}(f)$  and  $G = \text{TropicalFourierTransform}(g)$  be their tropical Fourier coefficients (the Legendre–Fenchel-type transforms guaranteed invertible by axiom A2 on the relevant class). Then  $\text{MinimalFourierCoefficient}(g) = \lambda \cdot \text{MinimalFourierCoefficient}(f)$ , and  $\text{DiscrepancyCalculation}(g) = \lambda \cdot \text{DiscrepancyCalculation}(f)$ . In particular, the bound from axiom A3,  $\text{DiscrepancyMeasure}(h) \leq \max_k |\hat{F}_h(k)|$ , scales homogeneously of degree 1 under positive tropical rescaling, so the inequality is preserved exactly under  $\lambda > 0$  (no slack opens or closes).

## Rationale

This conjecture directly tests axiom A3 ( $\text{DiscrepancyMeasure} \leq \max \text{Fourier coefficient}$ ) jointly with axiom A2 (invertibility of TropicalFourierTransform on the chosen class). Because tropical multiplication by a positive scalar corresponds to ordinary multiplication, and the Legendre–Fenchel transform satisfies  $(\lambda \cdot f)(y) = \lambda \cdot f(y/\lambda)$ , both extremes of  $f^*$  (its minimum and the discrepancy it controls) must scale by exactly  $\lambda$ . Verifying this 1-homogeneity is a clean sanity check that the framework’s notion of MinimalFourierCoefficient behaves as a genuine ‘norm-like’ invariant compatible with the tropical semiring’s scalar action, and that the A3 bound is not an artifact of a particular scale (relevant for transferring lower bounds in tropical/min-plus circuit complexity, where rescaling weights is a standard reduction).

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1010.5964v1] Quadratic discrete Fourier transform and mutually unbiased bases - [1207.2443v2] Tropical Teichmüller and Siegel spaces - [1204.4578v1] Complexity of tropical and min-plus linear prevarieties - [1406.3065v2] Lower Bounds for Tropical Circuits and Dynamic Programs - [1904.05483v2] Parallels Between Phase Transitions and Circuit Complexity?

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_21db269d.py", line 110, in <module>
    result = run_trial(seed)
            ~~~~~^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_21db269d.py", line 71, in run_trial
    f = [max([random.randint(-10, 10) * x[i] + random.randint(-10, 10) for i in range(d)]) for _ in range(5000)]
            ^
```

NameError: name 'x' is not defined

## Judge reasoning

The test crashed with a NameError (‘x’ is not defined’) before any trials executed, so no data was produced to evaluate the pre-registered support or falsification conditions. | next: Fix the test harness by properly defining the grid points  $x$  within the polynomial generation (e.g., evaluate the affine forms over each grid point), then rerun the 5000 trials.

---

## Permanent-Variance of NW Design Matrix Predicts PRG Bias

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorics of 0/1 matrix permanents (Ryser-formula variance over random row-sign perturbations)  $\times$  Nisan-Wigderson pseudorandom generator output bias against small DNF distinguishers
- **Recorded:** 2026-04-27 02:42 UTC
- **Entry ID:** 92f05cc72075

### Statement

Let  $D$  be an  $(\ell, a)$ -NW design on  $n$  variables encoded as an  $m \times n$  0/1 incidence matrix  $M$  (rows = subsets  $S_i$ , columns = universe). Define  $V(M) := \log_2(1 + \text{Var}_{\{\text{eps} \in \{+/-1\}^n\}}[\text{perm}(M_{\text{eps}})]) / m$ , where  $M_{\text{eps}}$  is  $M$  with column  $j$  scaled by  $\text{eps}_j$  and  $\text{perm}$  is the 0/1 permanent on the  $(m \times m)$  submatrix induced by the  $m$  heaviest columns. We conjecture that for every hard truth table  $f : \{0,1\}^\ell \rightarrow \{0,1\}$  of formula-leaf-count  $L(f) \geq 2^{\ell/3}$ , the maximum bias of  $\text{NW}_{\{D,f\}}$  against width- $w$  DNF distinguishers satisfies  $\text{bias}(\text{NW}_{\{D,f\}}, w) \leq 2^{-c * V(M) * m / w}$  for an absolute constant  $c > 0$ , so  $V(M)$  is a constructive lower bound certificate for PRG quality.

### Rationale

Permanent variance over sign perturbations measures how ‘spread’ the design’s row-overlap pattern is, which is exactly the combinatorial quantity controlling pairwise-intersection cancellation in the NW hybrid argument; existing analyses use only  $|S_i \cap S_j| \leq a$ , but the variance aggregates higher-order interference. Linking permanent fluctuation (a 0/1 matrix invariant computable in  $O(m * 2^m)$  by Ryser) to NW bias is, to our knowledge, unstudied and sidesteps natural-proofs because the invariant depends on the design only, not on  $f$ ’s truth table.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1311.6531v3] Brains and pseudorandom generators - [2412.05161v1] DNF: Unconditional 4D Generation with Dictionary-based Neural Fields - [2404.12647v1] Simple constructions of linear-depth  $t$ -designs and pseudorandom unitaries - [2003.09703v1] Variance function of boolean additive convolution - [2012.01667v2] Computing the matrix fractional power with the double exponential formula

### Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_08ccc640.py", line 123, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_08ccc640.py", line 66, in run_trial
    perm_var = permanent([[M_heaviest[i][j] * M_heaviest[j][i] for j in range(m)] for i in range(m)])
                      ~~~~~^
```

IndexError: list index out of range



## Judge reasoning

The test crashed with an `IndexError` before producing any data, so no support fraction or violation ratio could be computed against the pre-registered criterion. | next: Fix the indexing bug in the permanent computation (the `M_heaviest` submatrix access uses `M_heaviest[j][i]` where `j` ranges over `m` but rows are indexed differently) and rerun the trials.

---

## Cycle-Space Cocycle Imbalance Lower-Bounds Resolution Width of Tseitin

- **Verdict:** INCONCLUSIVE
- **Bridge:** Algebraic graph theory:  $\text{GF}(2)$  cycle space and edge-boundary cocycle imbalance of expander graphs  $\times$  Resolution refutation width of Tseitin formulas on bounded-degree expanders
- **Recorded:** 2026-04-27 03:18 UTC
- **Entry ID:** 09c50eb1a365

### Statement

Let  $G=(V,E)$  be a connected 3-regular graph and let  $T(G,c)$  be the Tseitin formula for an odd charge  $c:V \rightarrow \{0,1\}$ . Define the cocycle imbalance  $I(G) = \min \text{ over nonempty } S \subset V \text{ of } |E(S, V \setminus S)| / \min(|S|, |V \setminus S|)$ , and let  $w(T(G,c))$  denote the minimum width of any resolution refutation of  $T(G,c)$ . The conjecture is the linear lower bound  $w(T(G,c)) \geq \text{floor}(I(G) * \min(|S|, |V \setminus S|) / 2) + 1$ , where  $S$  is the cocycle-imbalance minimizer; equivalently, resolution width is at least half the minimum odd-charge edge-boundary plus one.

### Rationale

Ben-Sasson-Wigderson tie resolution width to expansion of the underlying constraint hypergraph, and Urquhart's classical Tseitin lower bounds are driven by edge-boundary expansion of small vertex sets. Reformulating expansion as a  $\text{GF}(2)$  cocycle imbalance (the dual of cycle-space sparsity) gives a coordinate-free invariant that should sharpen the constant in width lower bounds, and falsification on a single 3-regular graph would refute a clean algebraic strengthening of the BSW bound.

### Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [1411.3958v3] Edge-state enhanced transport in a 2-dimensional quantum walk - [2209.05839v3] On bounded depth proofs for Tseitin formulas on the grid; revisited - [2103.09609v1] Characterizing Tseitin-formulas with short regular resolution refutations - [0804.4433v1] SPACE: the SPectroscopic All-sky Cosmic Explorer - [2405.02292v1] ALOHA 2: An Enhanced Low-Cost Hardware for Bimanual Teleoperation

### Empirical Test

- exit code: 124, elapsed: 180.08s

TIMEOUT after 180s

## Judge reasoning

The test timed out after 180s (returncode=124) without producing any RESULT line, so the pre-registered support condition over  $\geq 210$  instances was never evaluated. | next: Re-run with a higher time budget and/or a faster width-bounded resolution solver (e.g., restrict to  $n \leq 14$  first, parallelize per-instance, and cache  $I(G)$  computations) to actually collect the 210 data points.

---

## Halton Star-Discrepancy of Clause-Sign Embedding Bounds DPLL Leaves

- **Verdict:** INCONCLUSIVE
- **Bridge:** Quasi-Monte Carlo low-discrepancy sequence theory (Halton/van der Corput star-discrepancy) × DPLL search-tree leaf count on random 3-CNF instances
- **Recorded:** 2026-04-27 03:49 UTC
- **Entry ID:** c4e28e9508f6

### Statement

Embed each clause  $C_i$  of a 3-CNF  $F$  over  $n$  variables as a point  $p_i$  in  $[0,1]^3$  by writing the three signed-literal indices (*signvar*) in *base-2 reversed (van der Corput) coordinates*, then let  $D(F)$  be the empirical star-discrepancy of  $\{p_i\}$  relative to the uniform measure on  $[0,1]^3$ . Conjecture: for unsatisfiable random 3-CNF at clause density  $\alpha=4.267$ , the DPLL leaf count  $L(F)$  satisfies  $\log_2 L(F) \geq c \cdot n \cdot D(F) - O(\log n)$  with  $c = 1/2$ , and equivalently  $\log_2 L(F) \leq C \cdot n \cdot D(F) + O(\log n)$  with  $C = 4$ . A single instance with  $\log_2 L(F) < 0.4 \cdot n \cdot D(F) - 5$  ( $n \leq 20$ ) falsifies the lower bound.

### Rationale

Star-discrepancy measures how ‘evenly’ clause-signatures fill literal-space; Chazelle/Matousek showed star-discrepancy controls combinatorial concentration phenomena that mirror branching irregularity. Highly clustered clause-embeddings (low discrepancy in sub-boxes) should correspond to local refutations exploitable by short DPLL trees, while highly dispersed sets force the splitter to branch globally. The bridge is constructive (just digit-reversal + brute search-tree count) and bypasses natural-proofs since star-discrepancy is not a pseudorandom-friendly invariant.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1209.3611v2] A van der Corput-type algorithm for LS-sequences of points - [2411.14979v2] Fundamentals and applications of Van der Waals magnets in magnon spintronics - [1908.01624v1] Learned Clause Minimization in Parallel SAT Solvers - [1402.4455v1] Symbiosis of Search and Heuristics for Random 3-SAT - [0506069v1] A generating function method for the average-case analysis of DPLL

### Empirical Test

- exit code: 124, elapsed: 180.03s

TIMEOUT after 180s

### Judge reasoning

The test timed out after 180s (returncode=124) without producing any data, so neither the support condition nor the falsification condition could be evaluated. | next: Reduce the workload (e.g., fewer seeds per  $n$  or cap  $n$  at 16) and/or add per-instance timeouts so the 1200-seed sweep can complete within the budget.

---

## Erdős-Ko-Rado Shadow Defect Lower-Bounds Disjointness Discrepancy

- **Verdict:** INCONCLUSIVE
- **Bridge:** Extremal set theory via Kruskal-Katona shadow profiles and EKR-type intersecting family deficits × Discrepancy-based randomized two-party communication complexity of partial set-disjointness matrices
- **Recorded:** 2026-04-27 04:23 UTC

- **Entry ID:** 78c33f7389a9

### Statement

For an  $n \times n \pm 1$  matrix  $M_F$  constructed from a  $k$ -uniform set family  $F \subseteq \{0,1\}^n$  (rows = members of  $F$ , columns = members of  $F$ , entry = +1 if disjoint, -1 if intersecting), let  $s(F)$  be the Kruskal-Katona shadow defect, defined as  $|\partial F| - \text{KK\_min}(|F|, k-1)$  where  $\partial F$  is the  $(k-1)$ -shadow and  $\text{KK\_min}$  is the colex minimum, and let  $\delta(F)$  be the spectral discrepancy  $\|M_F\|_{\infty \rightarrow 1} / (|F|^2)$ . We conjecture that for every  $k$ -uniform  $F$  with  $2 \leq k \leq n/2$ ,  $\delta(F) \geq c \cdot s(F) / (|F| \cdot \text{binomial}(n, k-1))$  for a universal constant  $c \geq 1/8$ , with equality approached only by colex-initial (EKR-extremal) families. A single  $(n, k, F)$  with  $\delta(F) < (1/8) \cdot s(F) / (|F| \cdot C(n, k-1))$  refutes it.

### Rationale

Shadow profiles measure how far a family deviates from being a colex-initial intersecting EKR family, and EKR-extremal stars are exactly the configurations whose disjointness matrices are known to be low-rank/low-discrepancy; quantifying the gap should pin discrepancy to a combinatorial deficit rather than spectral norms. This bridges Kruskal-Katona extremal shadow theory — almost untouched in communication complexity — with the discrepancy method via a constructive, polytime-computable invariant. If true, it would yield discrepancy lower bounds from purely combinatorial shadow counts, sidestepping algebrization since shadows are not relativizing.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1809.03967v2] More Cases Where the Kruskal-Katona Bound is Tight - [2005.06999v1] Tight bounds for Katona's shadow intersection theorem - [2305.10152v1] On the extremal families for the Kruskal-Katona theorem - [1408.1376v2] Factorization Norms and Hereditary Discrepancy - [1208.6015v1] The spectral function of a first order elliptic system

### Empirical Test

- exit code: 124, elapsed: 180.10s

TIMEOUT after 180s

### Judge reasoning

The test timed out at 180s (returncode 124) before producing any data, so neither the support nor falsification condition can be evaluated. The critic's CHALLENGE stands. | next: Reduce the search space (e.g.,  $n \in \{8..12\}$ ,  $k \in \{2,3\}$ , 50 random samples per cell) and optimize the spectral discrepancy computation (use  $\|M\|_{\infty \rightarrow 1}$  via sign-vector enumeration only for small  $|F|$ , or a Grothendieck-style SDP relaxation) to fit within the time budget.

---

## Edge-Expansion Defect Predicts Resolution Width of Tseitin on Random 3-Regular Graphs

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrete differential geometry via vertex-weighted Cheeger defect: the gap between the bottleneck edge-isoperimetric ratio  $h(G)$  and its second-eigenvalue Cheeger upper bound  $2\sqrt{d\lambda_2(L)}$  on the unnormalized graph Laplacian  $\times$  Resolution refutation width of Tseitin formulas  $T(G, c)$  on small 3-regular graphs with odd total charge
- **Recorded:** 2026-04-27 04:57 UTC
- **Entry ID:** c3c56f86d197

## Statement

Let  $G$  be a connected 3-regular graph on  $n$  vertices with odd-charge assignment  $c$ , let  $h(G) = \min_{|S| \leq n/2} |E(S, V \setminus S)|/|S|$  be its edge-isoperimetric number, and let  $\beta(G) = 2\sqrt{3\lambda_2(L_G)}$  be the Alon-Milman/Cheeger upper bound. Define the Cheeger defect  $\Delta(G) = \beta(G) - h(G) \geq 0$ . We conjecture that the minimum resolution refutation width  $w(T(G, c))$  satisfies  $(1/3)h(G)(n - \Delta(G)n/\beta(G)) - 2 \leq w(T(G, c)) \leq h(G)n/2 + 2$  for every odd-charge  $c$ , and in particular the *defect-corrected* lower bound  $h(G)(1 - \Delta(G)/\beta(G))n/3 - 2$  is tight up to constants on random 3-regular graphs with high probability.

## Rationale

Ben-Sasson-Wigderson tied resolution width to expansion of the underlying constraint hypergraph, but the standard bound uses  $h(G)$  only and is loose when the spectral gap fails to certify expansion globally; the Cheeger defect  $\Delta(G)$  quantifies exactly how much the linear-algebraic certificate underestimates the combinatorial bottleneck, which we hypothesize is the slack absorbed by short resolution refutations exploiting near-bisecting cuts. Because both  $h(G)$  and  $\lambda_2(L_G)$  are computable for  $n \leq 20$  by brute-force enumeration over subsets and a 20x20 eigensolver, the bridge is fully constructive. The bridge is genuinely new because existing Tseitin lower bounds use  $h(G)$  directly or pseudo-expectation arguments and do not isolate the spectral-vs-isoperimetric gap as a width predictor.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2103.09609v1] Characterizing Tseitin-formulas with short regular resolution refutations - [0908.1772v5] Some Probabilistic Results on Width Measures of Graphs - [0407622v3] A Study of the Composition of Ultra High Energy Cosmic Rays Using the High Resolution Fly's Eye - [1712.06904v3] Rigidity for the isoperimetric inequality of negative effective dimension on weighted Riemannian manifolds - [2111.02944v1] A sharp isoperimetric inequality in metric measure spaces with non-negative Ricci curvature

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 131, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 102, in run_trial
    lambda_2_G = compute_lambda_2(G)
                 ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 54, in compute_lambda_2
    eigenvector = power_iteration(A)
                  ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_59e871f1.py", line 44, in power_iteration
    x /= math.sqrt(sum(x[i] ** 2 for i in range(n)))
```

TypeError: unsupported operand type(s) for /=: 'list' and 'float'

## Judge reasoning

The test crashed with a `TypeError` in `power_iteration` (dividing a Python list by a float) before any instances were evaluated, so neither the support nor falsification criteria could be assessed. | next: Fix `power_iteration` to use a numpy array (or convert `x` to an array before normalization) and rerun the 210-instance sweep.

---

## Average-Case DPLL Runtime Linked to Random Matrix Spectra

- **Verdict:** INCONCLUSIVE
- **Bridge:** Random Matrix Theory  $\times$  DPLL Algorithm Runtime
- **Recorded:** 2026-04-27 06:23 UTC
- **Entry ID:** 7ac5fad5a356

### Statement

For random 3-CNF formulas with  $n$  variables, the expected DPLL runtime is exponentially bounded by the largest eigenvalue  $\lambda_{\max}$  of the clause adjacency matrix, i.e.,  $E[T(n)] = \Theta(2^{\lambda_{\max} * n})$ .

### Rationale

Random matrix theory provides tools to analyze the spectral properties of structured matrices derived from CNF formulas. By linking the runtime of DPLL to the spectral radius of such matrices, we can derive worst-case hardness from average-case behavior, leveraging the concentration of measure phenomena in random matrices.

### Novelty

- Judge: NOVEL over 0 arXiv hits

### Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5978c4e7.py", line 92, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5978c4e7.py", line 76, in run_trial
    lambda_max = largest_eigenvalue(adjacency_matrix)
                 ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5978c4e7.py", line 51, in largest_eigen
    v /= math.sqrt(sum(x**2 for x in v))
```

TypeError: unsupported operand type(s) for /=: 'list' and 'float'

### Judge reasoning

Test crashed during eigenvalue computation, preventing data collection to assess support/falsification  
| next: Fix the eigenvector normalization code to handle list operations properly and rerun experiments

---

## Betti Numbers and Resolution Width in 3-CNF

- **Verdict:** INCONCLUSIVE
- **Bridge:** Algebraic Topology  $\times$  Resolution Width
- **Recorded:** 2026-04-27 07:04 UTC
- **Entry ID:** 6bc88662420d

### Statement

For a random 3-CNF instance with  $n$  variables, the first Betti number of the clause-induced simplicial complex is  $\Theta(\log n)$  if and only if the resolution width is  $\Theta(\log n)$ .

## Rationale

Algebraic topology provides tools to analyze the structure of clause interactions, which may reveal hidden geometric constraints influencing resolution proof complexity. Betti numbers capture topological features that could correlate with the width required for resolution proofs.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1009.4130v3] Limit theorems for Betti numbers of random simplicial complexes - [2003.08066v2] Law of large numbers for Betti numbers of homogeneous and spatially independent random simplicial complexes - [1501.03759v1] Erratum: Limit theorems for Betti numbers of random simplicial complexes - [2110.02458v3] Magnitude homology of graphs and discrete Morse theory on Asao-Izumihara complexes - [2306.01534v3] The magnitude homology of a hypergraph

## Empirical Test

- exit code: 1, elapsed: 0.10s

- -STDERR- -

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5ea9db14.py", line 142, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_5ea9db14.py", line 95, in run_trial
    variables = random.sample(variable_set, 3)
    ~~~~~^~~~~~
```

```
File "/usr/lib/python3.12/random.py", line 413, in sample
    raise TypeError("Population must be a sequence. ")
```

```
TypeError: Population must be a sequence. For dicts or sets, use sorted(d).
```

## Judge reasoning

The test crashed with a `TypeError` (`random.sample` called on a non-sequence) before any Betti numbers, resolution widths, or correlations were computed, so the pre-registered support condition cannot be evaluated. | next: Fix the bug by passing a sorted list (e.g., `random.sample(sorted(variable_set), 3)`) and rerun the 140-instance sweep to obtain `b1`, `w`, and their correlation.

## Sandpile-Group Order of Lifted IP Bipartite Graph Bounds Decision Tree Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Algebraic graph theory via the critical (sandpile) group  $K(G)$  and Kirchhoff's Matrix-Tree theorem applied to bipartite communication graphs (rare in CS lower bounds; cf. Bacher-de la Harpe-Nagnibeda, Biggs)  $\times$  Deterministic communication complexity of Raz-McKenzie / Göös-Pitassi-style lifted Boolean functions  $f \circ \text{IP}_b^n$  with the inner-product gadget
- **Recorded:** 2026-04-27 07:15 UTC
- **Entry ID:** 69ad4d50946e

## Statement

Let  $f: \{0,1\}^n \rightarrow \{0,1\}$  have exact decision-tree depth  $d=D(f)$ , let  $b \in \{2,3\}$  be the IP-gadget block size, and let  $M(f,b) \in \{0,1\}^{2\{bn\} \times 2^{bn}}$  be the lifted communication matrix with  $M[x,y] = f((x_1, y_1), \dots, (x_n, y_n))$  over  $GF(2)$ . Form the bipartite graph  $G(f,b)$  with rows on one side, columns on the other, and an edge exactly where  $M[x,y]=1$ ; let  $\tau(G)$  denote its spanning-tree count (Kirchhoff determinant of any reduced Laplacian, with  $\tau=0$  if disconnected and  $\tau$  a product over components otherwise). Conjecture: for every non-constant  $f$  with  $n \leq 3$  and  $b \in \{2,3\}$ ,  $\log_2 \tau(G(f,b)) \geq d \cdot 2^{bn-2}$ , and equality is achieved (within  $+b$ ) precisely when  $f$  is the parity (XOR <sub>$n$</sub> ) function.

## Rationale

Lifting overhead per block in deterministic IP-lifting morally measures how many distinct rectangles each query forces; the sandpile group order is the lattice index of the cycle/cut spaces of  $G$  and counts admissible flow/charge configurations on  $G$ 's bipartite structure. Linking  $\tau(G)$  to  $D(f) \cdot (\text{gadget block area})$  plants a query-to-communication bridge through pure graph algebra, sidestepping algebraization since spanning-tree counting is not a relativizing arithmetic primitive. Tightness on parity is suggested because XOR-lifted matrices are Hadamard-like, giving maximally regular Laplacian spectra and hence nearly extremal spanning-tree counts.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1906.08515v1] An overview on the bipartite divisor graph for the set of irreducible character degrees - [1705.07519v1] Sandpile Groups of Random Bipartite Graphs - [1904.12209v2] Sandpile monomorphisms and limits - [1012.2478v2] Packing spanning trees and the  $k$ -tree protocol - [0904.3087v4] Distributed Maintenance of Anytime Available Spanning Trees in Dynamic Networks

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fb3bd595.py", line 134, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fb3bd595.py", line 96, in run_trial
    query = memoized_recursive_query_enumeration(lambda x: f[x], n)
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fb3bd595.py", line 21, in memoized_recursive_query_enumeration
    @lru_cache(None)
    ^^^^^^^^^
```

NameError: name 'lru\_cache' is not defined

## Judge reasoning

The test crashed with a NameError ('lru\_cache' is not defined) before producing any data, so no support fraction or slack values were computed. Per the rules, a crashed test yields INCONCLUSIVE. | next: Fix the test by importing lru\_cache from functools (add 'from functools import lru\_cache') and rerun the full enumeration over  $n \in \{1,2,3\}$ ,  $b \in \{2,3\}$ .

## Doob Martingale Variance Gap Predicts Worst-Case DPLL Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Doob martingale concentration / Efron-Stein variance decomposition on random CSP exposures  $\times$  DPLL search-tree depth on random 3-CNF (average-case to worst-case lift)
- **Recorded:** 2026-04-27 07:44 UTC
- **Entry ID:** 6487f7d68c31

### Statement

Let  $F \sim F(n, m=4n)$  be a random 3-CNF and let  $X(F) = \log_2(\text{DPLL\_leaves}(F))$  under fixed unit-propagation + first-unassigned variable order. Expose clauses one at a time to form the Doob martingale  $M_i = E[X \mid C_1, \dots, C_i]$  and let  $V(F) = \sum_i (M_i - M_{i-1})^2$  be its realized quadratic variation. Then for every  $n$  in  $[10, 20]$  there exist constants  $c_1, c_2 > 0$  (independent of  $n$ ) with  $c_1 * \sqrt{V(F)} * \log n \leq \max_{\{F' \text{ agreeing with } F \text{ on all but one clause}\}} X(F') - E[X] \leq c_2 * \sqrt{V(F)} * \log n$  with probability  $\geq 1 - 1/n$ ; equivalently, the average-case Doob variance  $V(F)$  tightly predicts the one-clause-perturbation worst-case depth gap.

### Rationale

Efron-Stein variance bounds give average-case concentration, but the lower-tail (one-clause-resampling worst-case) is rarely tied to the same martingale variance — yet Impagliazzo-Wigderson-style hardness amplification suggests average-case fluctuation should control nearby worst-case spikes. If the two-sided bound holds, an average-case lower bound on  $V$  translates into a worst-case DPLL depth bound via a single resampling step, a concrete avg-to-worst lift on a small computable scale.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1411.0186v2] Algorithmic randomness for Doob's martingale convergence theorem in continuous time - [1408.3470v1] Efron-Stein Inequalities for Random Matrices - [1908.05361v2] Placing quantified variants of 3-SAT and Not-All-Equal 3-SAT in the polynomial hierarchy - [0506069v1] A generating function method for the average-case analysis of DPLL - [2002.02797v4] Variational Depth Search in ResNets

### Empirical Test

- exit code: 0, elapsed: 0.04s

```
{"TRIAL": {"seed": 11, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 23, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 37, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 53, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
{"TRIAL": {"seed": 71, "metric_name": "Doob Variance Gap Predicts Worst-Case DPLL Depth", "metric_val": 0.0},
RESULT: SUPPORTED mean=0.0 std=0.0 support_fraction=1.0
```

### Judge reasoning

The metric\_value is exactly 0 with zero variance across all 5 seeds and only 6 instances per seed, indicating the test likely checked a trivially-satisfiable existential bound rather than the pre-registered OLS  $R^2/\text{slope}/\text{window-fraction}$  criterion. No evidence of pooled  $R^2$ , fitted slope, or per- $n$  window fractions was reported, so the support condition is not unambiguously met. | next: Re-run with seeds 1..200 across  $n$  in  $\{10, 12, 14, 16, 18, 20\}$  and explicitly compute pooled OLS regression of  $\log(\text{gap})$



# Newton-Inequality Defect of SAT Generating Polynomial Bounds DPLL Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Pólya-Schur theory of real-rooted polynomials and Newton's inequalities (multiplier sequences, log-concavity defects of integer coefficient polynomials) × Average-case DPLL search-tree depth on random 3-CNF and its direct-product worst-case lift
- **Recorded:** 2026-04-27 08:18 UTC
- **Entry ID:** 4907d4d1fa3e

## Statement

For a 3-CNF  $F$  on  $n$  variables, define the solution generating polynomial  $\Phi_F(z) = \sum_{k=0}^n a_k(F) z^k$  where  $a_k(F) = \#\{x \in \{0,1\}^n : F(x)=1 \text{ and } \text{weight}(x)=k\}$ , and let the Newton-inequality defect be  $\delta(F) = \max_{1 \leq k \leq n-1} \max(0, a_{k-1} a_{k+1} / a_k^2 - (k-1)(n-k+1)/(k(n-k+1)))$  with the convention  $0/0 = 0$ . Conjecture: there exist constants  $c_1, c_2 > 0$  (independent of  $n$ ) such that for random satisfiable 3-CNF  $F$  at clause density  $\alpha$  in  $[3.6, 4.0]$ , the expected average-case DPLL leaf count satisfies  $E[\log_2 \text{leaves\_DPLL}(F)] \geq c_1 * n * \log_2(1 + \delta(F)) - c_2 * \sqrt{n}$ , and the  $k$ -fold disjoint-variable direct product  $F^{\{(k)\}}$  satisfies  $\text{leaves\_DPLL}(F^{\{(k)\}}) \geq (1 + \delta(F))^{c_1 * k * n}$  for every static branching order. The conjecture is falsified by exhibiting a single  $F$  (with  $n \leq 20$ ) whose measured leaf count is below  $c_1 * n * \log_2(1 + \delta(F)) - c_2 * \sqrt{n}$  for  $c_1 = 0.25, c_2 = 4$ .

## Rationale

Pólya-Schur theory says that polynomials with only real (negative) roots satisfy Newton's inequalities exactly; the defect  $\delta$  quantifies how far  $\Phi_F$  is from being a multiplier-stable polynomial. Real-rooted  $\Phi_F$  corresponds to clusters of solutions arranged like an independent-coordinate product distribution, which DPLL prunes efficiently; conversely, large  $\delta$  signals pinned correlations between Hamming-weight strata of the solution set, which force DPLL backtracks. Direct product then transports this average-case structural obstruction to a worst-case depth lower bound in the spirit of Impagliazzo-Wigderson hardness amplification.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1907.08306v1] A Polynomial Time Algorithm for Log-Concave Maximum Likelihood via Locally Exponential Families - [2004.07220v2] Log-Concave Polynomials IV: Approximate Exchange, Tight Mixing Times, and Near-Optimal Sampling of Forests - [1604.00993v1] The 'Core' of Symmetric Homogeneous Polynomial Inequalities of Degree Four of Three Real Variables - [1908.05361v2] Placing quantified variants of 3-SAT and Not-All-Equal 3-SAT in the polynomial hierarchy - [0803.0018v5] Another approach to decide on real root existence for univariate Polynomials, and a multivariate extension for 3-SAT

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 160, in <module>
    result = run_trial(seed)
             ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 103, in run_trial
    clauses = generate_random_satisfiable_3cnf(n, alpha)
             ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 88, in generate_rand
```

```

if any(evaluate_formula(clauses, dict(enumerate([random.randint(0, 1) for _ in range(n)]))) for _ in
~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 88, in <genexpr>
    if any(evaluate_formula(clauses, dict(enumerate([random.randint(0, 1) for _ in range(n)]))) for _ in
~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 29, in evaluate_form
    return all(all((assignment[var] + lit) % 2 == 0 for var, lit in clause.items())) for clause in formul
~~~~~
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_60f182d0.py", line 29, in <genexpr>
    return all(all((assignment[var] + lit) % 2 == 0 for var, lit in clause.items())) for clause in formul
~~~~~
AttributeError: 'list' object has no attribute 'items'

```

The test crashed with an `AttributeError` in `evaluate_formula` (clauses stored as lists rather than dicts), so no data was produced and neither the support nor falsification criteria can be evaluated. | next: Fix the clause data-structure bug in `evaluate_formula/generate_random_satisfiable_3cnf` (use a consistent representation, e.g., list of (var, lit) tuples) and rerun the full 360-instance pre-registered protocol.

- **Verdict:** INCONCLUSIVE
- **Bridge:** Topological combinatorics (Möbius function and order-complex Euler characteristic on the meet-closure lattice of minterm supports, in the spirit of Rota and Stanley)  $\times$  Deterministic two-party communication complexity of Indexing-gadget-lifted monotone functions (Göös-Pitassi-Watson lifting), with deterministic decision-tree depth as the lifted-side proxy
- **Recorded:** 2026-04-27 08:47 UTC
- **Entry ID:** b63c45216b7a

Let  $f: \{0,1\}^n \rightarrow \{0,1\}$  be monotone with prime-implicant supports  $S_1, \dots, S_k \subseteq [n]$ ; let  $L_f$  be the meet-closure lattice generated by  $\{S_i\}$  together with an adjoined top  $\hat{1} = [n]$  and bottom  $0 = \emptyset$ , and let  $\mu_f := |\mu_{\{L_f\}}(0, \hat{1})|$  be its Möbius number. Then for all  $n \leq 20$  the deterministic decision-tree depth satisfies  $D^{dt}(f) \geq \lceil \log_2(1 + \mu_f) \rceil$ , and consequently the Göös-Pitassi-Watson Indexing-gadget lifting yields  $D^{cc}(f \circ \text{IND}_b) = \Omega((\log b) \cdot \log_2(1 + \mu_f))$ . A single monotone  $f$  with  $\lceil \log_2(1 + \mu_f) \rceil > D^{dt}(f)$  refutes the conjecture.

Lifting theorems convert decision-tree depth to communication, so any combinatorial invariant that lower-bounds  $D^{\text{dt}}(f)$  automatically lower-bounds lifted communication. The Möbius number of the minterm closure lattice measures how much non-Boolean-lattice structure the accepting set carries; intuitively, each query in a decision tree can only halve the alternating Möbius sum on a chain, so depth must dominate  $\log$  of  $|\mu|$ . This bridges topological combinatorics to communication lower bounds, a pairing with no prior occurrences I am aware of.

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [0710.4339v1] Heavy-Quark Masses from the Fermilab Method in Three-Flavor Lattice QCD - [1111.0981v1] Form factors for  $B$  to  $K\ell\ell$  semileptonic decay from three-flavor lattice QCD - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [1605.01142v2] Separations in communication complexity using cheat sheets and information complexity - [2001.02144v1] Lifting with Simple Gadgets and Applications to Circuit and Proof Complexity

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 125, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 71, in run_trial
    dnf = generate_random_dnf(n, k, implicant_size)
         ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 31, in generate_random_dnf
    if all(len(set(a).intersection(b)) == 0 for b in implicants):
        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6637e14.py", line 31, in <genexpr>
    if all(len(set(a).intersection(b)) == 0 for b in implicants):
           ^
```

NameError: name 'a' is not defined

## Judge reasoning

The test crashed with a NameError in generate\_random\_dnf (undefined variable 'a' in a generator expression) before any instances were evaluated, so no data was produced for either the support or falsification criterion. | next: Fix the generator-expression bug in generate\_random\_dnf (likely should iterate over candidate 'a' against existing implicants 'b') and rerun the 400-instance sweep.

---

## Noise-Stability Plateau at $\rho=1/3$ Bounds DPLL Leaves on 3-CNF

- **Verdict:** INCONCLUSIVE
- **Bridge:** Fourier analysis of Boolean functions (noise stability  $\text{Stab}_\rho$  and Bonami-Beckner noise operator  $T_\rho$ )  $\times$  DPLL search-tree leaf count on random 3-CNF formulas
- **Recorded:** 2026-04-27 09:18 UTC
- **Entry ID:** 3385dd792f63

## Statement

For a 3-CNF formula  $F$  on  $n$  variables with indicator function  $f_F: \{-1, 1\}^n \rightarrow \{0, 1\}$  (1 iff assignment satisfies  $F$ ), let  $S(F) := \text{Stab}_{1/3}(f_F) - (E[f_F])^2 = \sum_{|T| \geq 1} (1/3)^{|T|} \hat{f}_T^2$ . We conjecture that for every unsatisfiable 3-CNF  $F$  with  $m$  clauses on  $n \leq 20$  variables, the number  $L(F)$  of leaves explored by the standard unit-propagating DPLL with fixed lexicographic branching satisfies  $L(F) \geq 2^n \cdot S(F) / (3 \cdot m)$ , and equivalently for satisfiable  $F$  we get  $L(F) \leq 2^n \cdot (1 - 9 \cdot S(F)/m)$ . One satisfiability instance violating either inequality refutes the conjecture.

## Rationale

At noise rate  $1/3$  each clause's local indicator (a degree-3 Boolean function on three variables) decays by exactly  $(1/3)^3 = 1/27$  per level, matching the branching factor of DPLL on a 3-CNF; thus

the  $\rho=1/3$  noise stability isolates the ‘clause-coupled’ Fourier mass that DPLL must shatter. Kahn-Kalai-Linial-style influence bounds show that each clause contributes at most  $O(1/n)$  to total influence, so summing  $\text{Stab}_{\{1/3\}}$  over clauses should track tree size up to the clause-density factor  $m$ . This bridges hypercontractive Fourier weight with concrete branching cost, a connection rarely tested empirically.

## Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [2003.09703v1] Variance function of boolean additive convolution - [1407.6169v3] Multiplicative Complexity of Vector Valued Boolean Functions - [1112.2313v2] QBF-Based Boolean Function Bi-Decomposition - [1402.4455v1] Symbiosis of Search and Heuristics for Random 3-SAT - [0710.0805v3] On the Satisfiability Threshold and Clustering of Solutions of Random 3-SAT Formulas

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_689eea86.py", line 98, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_689eea86.py", line 62, in run_trial
    f_F = {tuple([random.choice([-1, 1]) for _ in range(n)]): evaluate_formula(f_F, assignment) for assignment in assignments}
                                     ^^^
```

UnboundLocalError: cannot access local variable 'f\_F' where it is not associated with a value

## Judge reasoning

The test crashed with an UnboundLocalError before producing any data, so no instances were evaluated and neither the support nor falsification condition can be assessed. | next: Fix the test harness bug (initialize  $f_F$  properly before constructing the assignment-to-evaluation dictionary) and rerun the full 1050-instance sweep.

---

## Brooks Quasimorphism Magnitude Lower-Bounds Formula Depth via Barrington Lifts

- **Verdict:** INCONCLUSIVE
- **Bridge:** Geometric group theory: Brooks counting quasimorphisms on the free group  $F_2$  (bounded cohomology  $H^2(F_2; \mathbb{R})$ , Bestvina-Fujiwara)  $\times$   $NC^1$  / Boolean formula depth via Barrington’s width-5  $S_5$  branching program lifted to  $F_2$
- **Recorded:** 2026-04-27 09:53 UTC
- **Entry ID:** 5013aa48b582

## Statement

For a Boolean formula  $\varphi$  of syntactic depth  $d$  over  $n$  variables, build Barrington’s canonical width-5 ground BP  $B_\varphi$  (length  $4^d$ ) and lift each  $S_5$  factor to  $F_2 = \langle a, b \rangle$  via the surjection  $a \mapsto (1\ 2\ 3\ 4\ 5)$ ,  $b \mapsto (1\ 2)$ , giving a word  $w_\varphi(x) \in F_2$  of length  $4^d$  for every input  $x \in \{0, 1\}^n$ . Let  $\tau(w) := \#\{\text{occurrences of the reduced subword aba in } w\} - \#\{\text{occurrences of } a^{-1}b^{-1}a^{-1} \text{ in } w\}$  be the Brooks counting quasimorphism on  $F_2$  with seed aba. Conjecture: there exist absolute

constants  $c_1, c_2 > 0$  such that for every  $\varphi$  with  $d \geq 2$ ,  $c_1 \cdot 2^d \leq \max_{x \in \{0,1\}^n} |\tau(w_\varphi(x))| \leq c_2 \cdot 2^d$ , so  $\text{depth}(\varphi) = \log_2 \max_x |\tau(w_\varphi(x))| \pm O(1)$ .

## Rationale

Barrington's recursion nests commutators  $d$ -deep, and in the free group  $F_2$  nested commutators are precisely the words on which Brooks quasimorphisms grow linearly per nesting level (Bavard duality, scl-detection). Solvable groups have bounded commutator length so this signal collapses, but  $F_2$  — the universal Barrington target — preserves it, suggesting a single  $F_2$ -word invariant can certify  $\text{NC}^1$  depth orthogonally to communication, polynomial-method, or approximation-based lower bounds. No prior work I know of pairs Brooks quasimorphisms with Barrington BPs.

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1911.10855v2]  $\hat{G}$ -invariant quasimorphisms and symplectic geometry of surfaces - [0610012v1] Tevatron-for-LHC Report of the QCD Working Group - [1710.02392v2] The cup product of Brooks quasimorphisms - [1901.01301v1] Second bounded cohomology and WWPD - [0701214v2] Graphs, free groups and the Hanna Neumann conjecture

## Empirical Test

- exit code: 1, elapsed: 0.11s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_252ab5e3.py", line 130, in <module>
    result = run_trial(seed)
            ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_252ab5e3.py", line 103, in run_trial
    triples = barrington_construction(formula)
            ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_252ab5e3.py", line 28, in barrington_co
    return stack[0]
           ~~~~~^~
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an `IndexError` in `barrington_construction` before any data was collected, so neither the support nor the falsification condition can be evaluated. | next: Fix the Barrington construction (likely a stack underflow when handling leaf/literal gates or odd recursion base cases) and rerun the pre-registered protocol across  $d \in \{2, 3, 4, 5\}$ .

## Hadamard-Code Distance Defect Predicts NW-PRG Distinguisher Advantage

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coding theory of binary Reed-Muller / Hadamard codes (minimum-distance defect of the design's combinatorial incidence code)  $\times$  Nisan-Wigderson pseudorandom generator output bias against small parity-AND distinguishers
- **Recorded:** 2026-04-27 10:22 UTC
- **Entry ID:** 1a5be3baec68

## Statement

Let  $D$  be an  $(m, l, a)$ -NW design on  $n = |S_i|$  sets and let  $M_D$  in  $\{0, 1\}^{n \times m}$  be its incidence matrix; let  $d(D)$  be the minimum Hamming distance between any two distinct rows of  $M_D$  and let  $d^* = 1 - a$  be the design's pairwise-overlap upper bound on agreement. For every hard predicate  $f: \{0, 1\}^l \rightarrow \{0, 1\}$  of correlation  $\epsilon$  with degree-1  $\text{GF}(2)$  polynomials, the maximum distinguishing advantage of any AND-of- $c$ -parities distinguisher against  $\text{NW}_{\{D, f\}}$  satisfies  $\text{adv}(\text{NW}_{\{D, f\}}) \leq c * \epsilon * 2^{\frac{d(D) - 2(l - d^*)}{2}}$ , and this bound is tight up to a constant for at least 30% of random hard  $f$  at every  $(m, l, a, n \leq 20)$ .

## Rationale

NW analysis classically pays a  $2^{ca}$  factor for  $c$ -parity distinguishers via the design's overlap  $a$ ; recasting  $M_D$  as a binary code lets the actual\* row-distance  $d(D)$  — typically much larger than the worst-case  $2(l - a)$  bound — control distinguisher leakage through a Plotkin-style inner-product argument. Coding-theoretic distance has been almost entirely absent from NW PRG analyses (which use overlap, not minimum distance), and the gap  $d(D) - 2(l - a)$  is exactly the slack that explains why concrete designs beat their generic guarantee. The conjecture is falsifier-friendly: any single  $(D, f, c)$  tuple where the empirical advantage exceeds the RHS by more than a small constant kills it.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2106.11085v3] On the Maximal Monotone Operators in Hadamard Spaces - [1003.4003v1] A Fourier-analytic Approach to Counting Partial Hadamard Matrices - [1003.4001v1] On the Asymptotic Existence of Hadamard Matrices - [1311.6531v3] Brains and pseudorandom generators - [2410.08073v3] Efficient Quantum Pseudorandomness from Hamiltonian Phase States

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6c9b9fc0.py", line 120, in <module>
    result = run_trial(seed)
             ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6c9b9fc0.py", line 95, in run_trial
    advantage = nw_distinction(design, lambda x: sum(x) % 2 == parity[0], parity)
               ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6c9b9fc0.py", line 72, in nw_distinction
    if predicate(seed) == parity[i]:
       ~~~~~^~~~~
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an `IndexError` before producing any `RESULT` line, so neither the support nor the falsification conditions can be evaluated. Per rule 2, a crashed test yields `INCONCLUSIVE`. | next: Fix the `nw_distinction` harness so the parity vector is sized to match the number of distinguisher queries (length  $c$ ), then re-run the enumeration over  $(m, l, a, n \leq 20)$  with  $\geq 5$  seeds.

# Asymptotic-dimension lower bound for the indexing function via controlled covers matches its log-depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse Geometric Karchmer-Wigderson (CG-KW); coarse geometry / Roe algebras / metric (Roe) cohomology  $\times$  Formula depth (over the De Morgan basis, equivalently  $NC^1$  circuit depth) of the addressing/indexing function  $IND_k : \{0,1\}^{k+2^k} \rightarrow \{0,1\}$ , which selects data bit  $x_a$  where  $a$  is encoded by the  $k$  address bits;  $IND_k$  has known formula depth  $\Theta(k)$  and is the canonical KW-easy test instance for any proposed depth measure.
- **Recorded:** 2026-04-27 10:37 UTC
- **Entry ID:** e871be18b26c

## Statement

For every  $k \geq 1$ , the KW-metric space  $(X_{\{IND_k\}}, d_{\{IND_k\}})$  admits no controlled cover of diameter  $R = 2^{\{k-1\}} - 1$  with multiplicity  $m \leq k$ , and consequently  $\text{asdim}(X_{\{IND_k\}}) \geq k - O(1)$ ; together with axiom A1 this yields  $\kappa(IND_k) \geq k - O(1) = \Omega(\log N)$  where  $N = k + 2^k$  is the input length, matching the true depth  $\Theta(k)$  up to a constant. Equivalently: there exists an explicit coarse 1-cocycle  $c_k \in HX^1(X_{\{IND_k\}})$  and a Roe-controlled operator  $T_k$  of propagation  $2^{\{k\}}$  with  $|\langle c_k, T_k \rangle| \geq 2^{\{\Omega(k)\}}$ , certifying a super-constant  $\kappa$  on this family.

## Rationale

This sub-conjecture stress-tests axiom A1 (Coarse-KW link) on a function whose true depth is precisely known: if A1 holds, the controlled-cover multiplicity must witness the Karchmer-Wigderson protocol's depth, so on  $IND_k$  we MUST recover  $k - O(1)$ . It also exercises axiom A5 (Roe-index rigidity) by demanding an explicit cocycle/operator pair realizing the trace pairing —  $IND_k$  is the simplest function whose KW-tree is a complete binary tree, so the address-bit projections give natural candidates for  $c_k$ . Failure on  $IND_k$  would falsify A1; success calibrates the constants in A1 before attempting the Andreev / element-distinctness  $\Omega(\log^2 n)$  targets.

## Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [2107.05128v2] Karchmer-Wigderson Games for Hazard-free Computation - [2002.07444v1] Multiparty Karchmer-Wigderson Games and Threshold Circuits - [0906.0693v3] An improved lower bound on the counterfeit coins problem - [1904.05483v2] Parallels Between Phase Transitions and Circuit Complexity? - [2312.08907v2] Roe algebras of coarse spaces via coarse geometric modules

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 185, in <module>
    result = run_trial(seed)
             ~~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 143, in run_trial
    cover = controlled_cover(R, k)
            ~~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 41, in controlled_co
    for i in range(1 <= (log2_floor(node) + 1)):
                ~~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_9b843142.py", line 25, in log2_floor
    return math.floor(math.log2(n))
```

^^^^^^^^^^^

ValueError: math domain error

### Judge reasoning

The test crashed with a ValueError (math domain error in  $\log_2$ \_floor due to a non-positive argument) before producing any slope, trace-pairing, or baseline data, so none of the pre-registered support conditions can be evaluated. | next: Guard  $\log_2$ \_floor against  $n \leq 0$  (e.g., handle the root/zero node explicitly) and rerun the controlled-cover and trace-pairing measurements for  $k \in \{2,3,4\}$  with the 20-seed random baseline.

---

## Permanent of Sensitive-Boundary Bipartite Matrix Bounds Lifted Indexing CC

- **Verdict:** INCONCLUSIVE
- **Bridge:** Permanents of bipartite 0/1 biadjacency matrices via Ryser inclusion-exclusion enumeration of perfect matchings (algebraic combinatorics on the Boolean cube; rarely deployed in decision-tree / communication lower bounds)  $\times$  Deterministic communication complexity  $D^{\text{cc}}(f \circ \text{IND}_b)$  of Indexing-lifted Boolean functions, accessed through decision-tree depth  $Q^{\text{dt}}(f)$  via the Raz-McKenzie / Göös-Pitassi-Watson lifting theorem
- **Recorded:** 2026-04-27 10:47 UTC
- **Entry ID:** 25722288cd28

### Statement

For every non-constant Boolean function  $f: \{0,1\}^k \rightarrow \{0,1\}$  with  $k \leq 4$ , let  $B(f)$  be the  $2^{\{k-1\}} \times 2^{\{k-1\}}$  biadjacency matrix of the sensitive boundary subgraph of the Hamming cube  $Q_k$  between even-parity and odd-parity vertices, defined by  $B(f)_{\{x,y\}} = 1$  iff  $|x \oplus y| = 1$  and  $f(x) \neq f(y)$ . Conjecture:  $\log_2(\text{perm}(B(f)) + 1) \leq k \cdot Q^{\text{dt}}(f)$ , where  $\text{perm}$  denotes the matrix permanent (counting perfect matchings of the sensitive boundary). By the GPW indexing lift this gives  $D^{\text{cc}}(f \circ \text{IND}_b) \geq \Omega(\log b \cdot k^{-1} \cdot \log_2(\text{perm}(B(f)) + 1))$ , a permanent-based lower bound on lifted CC.

### Rationale

Sensitive edges form a bipartite subgraph of  $Q_k$  whose perfect-matching count is a global, non-spectral combinatorial invariant orthogonal to Fourier / influence-based measures already used in lifting arguments. Decision-tree depth controls the resolution of sensitive transitions: shallow trees can only sustain sensitive-edge structures supporting a limited number of disjoint perfect matchings, whereas parity-like deep functions saturate the bound. Because permanents are not spectral functionals, this route does not invoke the natural-proofs / algebrization barriers that block direct rank-style lifts.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2512.11833v1] Soft Decision Tree classifier: explainable and extendable PyTorch implementation - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [2209.08042v1] Decision Tree Complexity versus Block Sensitivity and Degree - [1904.13056v4] Query-to-Communication Lifting Using Low-Discrepancy Gadgets - [0111062v2] One-way communication complexity and the Neciporuk lower bound on formula size

### Empirical Test

- exit code: 1, elapsed: 0.09s



```
--STDERR--
Traceback (most recent call last):
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e8dfed8b.py", line 128, in <module>
    result = run_trial(seed)
              ^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e8dfed8b.py", line 103, in run_trial
    B = sensitive_boundary_matrix(f)
        ^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e8dfed8b.py", line 63, in sensitive_bou
    if sum(int(a) != int(b) for a, b in zip(bin(f"{x:0{k-1}b}"), bin(f"{y:0{k-
1}b}")))) == 1 and f[x] != f[y]:
                                   ^^^^^^^^^^^^^^^^^^^^^
TypeError: 'str' object cannot be interpreted as an integer
```

## Judge reasoning

The test crashed with a `TypeError` in `sensitive_boundary_matrix` (misuse of `bin()` on a formatted string) before producing any data, so the pre-registered support condition cannot be evaluated. | next: Fix the bit-comparison bug (e.g., use Hamming distance via `bin(x ^ y).count('1')` on integers `x, y` in `range(2^k)`) and re-run the full  $2^{16}$  enumeration on  $k=4$ .

---

## Subdeterminant Dispersion Lower-Bounds Singular-Tail Matrix Rigidity

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorial discrepancy theory via Chazelle’s subdeterminant lower bound for hereditary discrepancy (Chazelle-Lovász-Vu / Beck-Fiala lineage)  $\times$  Matrix rigidity (Valiant) measured by the singular-value tail-rank of  $n \times n \pm 1$  sign matrices, the standard pre-Razborov proxy for unsaturated explicit-rigidity bounds
- **Recorded:** 2026-04-27 11:13 UTC
- **Entry ID:** 09da8624d6b7

### Statement

For every  $n \times n \pm 1$  sign matrix  $M$  with  $n \geq 4$ , define the  $k$ -subdeterminant dispersion  $\Delta(M) = \max_{2 \leq k \leq 6} \max_{\{S, T \subseteq [n], |S|=|T|=k\}} |\det(M[S, T])|^{\frac{1}{k}} / \sqrt{k}$ , and the energy-tail rank  $\tau(M) = \#\{i : \sigma_i(M)^2 \geq \|M\|_F^2 / n\}$ . Then  $\tau(M) \cdot \Delta(M)^2 \geq (1/4) \cdot n$ . Equivalently, any matrix whose every small subdeterminant is small (low Chazelle dispersion) must have its energy spread across many singular values.

### Rationale

Chazelle’s subdeterminant bound is the sharpest combinatorial witness for hereditary discrepancy yet has never been linked directly to singular-tail rigidity, even though both quantify how ‘flat’ a sign matrix can be made by submatrix selection. Bourgain’s  $\Lambda(p)$  heuristics suggest small subdeterminants force flat singular spectra (Kashin-style mass-spreading), which would forbid the low-rank-plus-sparse decomposition that defines rigidity collapse. A constant in the bound, if true, gives a poly-time computable explicit-rigidity lower bound that bypasses the natural-proofs barrier ( $\Delta$  is not a large pseudorandom-closed property: Hadamard matrices saturate it).

### Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 86, in <module>
    result = run_trial(seed)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 62, in run_trial
    delta = subdeterminant_dispersion(M)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 50, in subdeterminant
    det_val = abs(determinant(gaussian_elimination(submat)))
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_50c2f957.py", line 21, in gaussian_elimination
    A[i], A[max_row] = A[max_row], A[i]
    ~~~~~
```

IndexError: list index out of range

## Judge reasoning

Test crashed with an IndexError in the gaussian\_elimination routine before any R values were produced, so neither the support nor the falsification criterion can be evaluated. | next: Fix the subdeterminant computation (e.g., use numpy.linalg.det or guard the pivot search) and rerun the pre-registered 1050-matrix sweep.

---

## Lyndon Factor Count of Truth Table Lower-Bounds DT Leaves Under IND-Lifting

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorics on words: the Chen-Fox-Lyndon factorization of a binary word into a non-increasing product of Lyndon words (Duval's linear-time algorithm; free Lie algebra Hall basis, Lothaire ch. 5)  $\times$  Decision-tree leaf count of Boolean functions, lifted via the Raz-McKenzie / Göös-Pitassi-Watson Indexing gadget to deterministic communication protocol leaf count (standard DT-to-CC lifting)
- **Recorded:** 2026-04-27 11:46 UTC
- **Entry ID:** a95d970248c4

## Statement

Let  $f: \{0,1\}^n \rightarrow \{0,1\}$  have truth table read in lex order as a binary word  $w(f)$  of length  $2^n$ , and let  $L(f)$  be the number of factors in the unique Chen-Fox-Lyndon (Lyndon) factorization of  $w(f)$ . Then the minimum leaf count  $\text{Leaves}(f)$  of any deterministic decision tree computing  $f$  satisfies  $\text{Leaves}(f) \geq L(f)$ ; consequently, by Göös-Pitassi-Watson lifting, the leaf count of every deterministic protocol computing  $f$  o IND<sub>b</sub> is at least  $L(f)^{\Omega(b)}$  once  $b \geq \lceil \log_2 n \rceil$ .

## Rationale

A Lyndon factorization isolates the maximal aperiodic 'incompressible' segments of  $w(f)$ ; intuitively, each new Lyndon factor witnesses a position where the truth table jumps off any prior periodicity, forcing any DT to commit a distinct leaf-region to it. Combinatorics on words is essentially absent from DT/communication lower bounds, yet Duval's factorization plugs cleanly into the lifting black box (leaf count amplifies to protocol size) without invoking algebrization-sensitive structure.

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [2512.11833v1] Soft Decision Tree classifier: explainable and extendable PyTorch implementation - [2003.09703v1] Variance function of boolean additive convolution - [1811.10735v4] Automatic Induction of Neural Network Decision Tree Algorithms - [0906.0693v3] An improved lower bound on the counterfeit coins problem

## Empirical Test

- exit code: 1, elapsed: 130.09s

```
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
TRIAL: {'metric_name': 'min_L_f', 'metric_value': 1, 'instances_tested': 65808, 'conjecture_holds': 1}
```

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0487d516.py", line 92, in <module>
    first_failing_seed = next((r["seed"] for r in results if not r["conjecture_holds"]), None)
                        ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0487d516.py", line 92, in <genexpr>
    first_failing_seed = next((r["seed"] for r in results if not r["conjecture_holds"]), None)
                        ~~~~~^~~~~~
```

KeyError: 'seed'

## Judge reasoning

The test crashed with a KeyError on 'seed' before producing valid pass/fail data; the trial outputs report 'mapping\_undefined' counterexamples and conjecture\_holds=False, but no genuine  $f$  with  $\text{Leaves}(f) < L(f)$  was exhibited. The pre-registered support condition was not unambiguously met, and the critic challenged the run. | next: Fix the harness so each trial result includes a 'seed' field and emits an explicit  $(f, \text{Leaves}(f), L(f))$  triple, then re-run the full enumeration over  $n$  in  $\{2,3,4\}$  to obtain

---

## Kashin-Split Energy Gap Lower-Bounds Sign-Matrix Rigidity at Rank $n/4$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrepancy / dispersion via Kashin-style orthogonal decompositions (Kashin's theorem on splitting  $\ell_2^{\{2n\}}$  into nearly  $\ell_1$ -equivalent halves; Bourgain-Tzafriri restricted invertibility flavor)  $\times$  Matrix rigidity (Valiant) of  $n \times n$   $\{+1, -1\}$  sign matrices at target rank  $r = n/4$ , measured as the minimum Hamming weight of a perturbation  $E$  such that  $\text{rank}(M+E) \leq r$
- **Recorded:** 2026-04-27 12:12 UTC
- **Entry ID:** 223537333300

## Statement

For every  $n \times n$   $\{+1, -1\}$  matrix  $M$ , partition the  $n$  columns greedily into two halves  $(A, B)$  maximizing the Frobenius energy gap  $g(M) = ||M_A||_F^2 - ||M_B||_F^2 / n^2$ , and let  $s_{\text{low}}(M)$  be the sum of the bottom  $3n/4$  singular values of  $M$  divided by  $n^{\{3/2\}}$ . Then the rigidity at rank  $n/4$  satisfies  $R_M(n/4) \geq c * n^2 * (s_{\text{low}}(M) - g(M)) +$  for an absolute constant  $c > 0$  (we conjecture  $c = 1/16$ ).

Equivalently: whenever a sign matrix has a small Kashin energy-gap ( $g$  small) but a large bottom-tail singular sum, it must be rigid.

## Rationale

Kashin splittings expose the obstruction that prevents low-rank approximation from cheaply absorbing many sign-flips: when no column-bipartition concentrates Frobenius energy, the residual after removing the top  $n/4$  spectrum cannot be packed into few sparse perturbations without violating a discrepancy-style dispersion inequality of Bourgain-Tzafriri type. This bridges the dispersion side of discrepancy theory (energy distribution under random orthogonal partitions) with Valiant's rigidity, an angle not pursued in the existing rigidity literature which focuses on either spectral lower bounds (Lokam) or paving (Alon-Panigrahy-Yekhanin).

## Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [0610498v4] Bounds on changes in Ritz values for a perturbed invariant subspace of a Hermitian matrix - [1005.0979v1] Supersymmetry in Random Matrix Theory - [1204.0062v4] Improved matrix algorithms via the Subsampled Randomized Hadamard Transform - [2208.05223v1] Modular Bourgain-Tzafriri Restricted Invertibility Conjectures and Johnson-Lindenstrauss Flattening Conjecture - [1503.07054v1] A Geometric Perspective on the Singular Value Decomposition

## Empirical Test

- exit code: 1, elapsed: 0.12s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 121, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 100, in run_trial
    s_low_M = s_low(M)
             ^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 93, in s_low
    _, S, _ = singular_values(M)
             ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 36, in singular_valu
    norm_q = frobenius_norm(q)
             ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 22, in frobenius_nor
    return sum(sum(x**2 for x in row) for row in M)**0.5
               ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dfbe7700.py", line 22, in <genexpr>
    return sum(sum(x**2 for x in row) for row in M)**0.5
               ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

TypeError: 'int' object is not iterable

## Judge reasoning

The test crashed with a `TypeError` in `frobenius_norm` (it was passed a 1D vector instead of a 2D matrix during singular value computation), so no data was produced and the pre-registered support condition could not be evaluated. | next: Fix the `singular_values/frobenius_norm` helpers to handle 1D vectors (or use `numpy.linalg.svd` and `numpy.linalg.norm`) and re-run the full sweep across  $n$  in  $\{6,8,10,12,14,16\}$ .

---

## Roe-trace pairing for Inner-Product realizes coarse depth $\kappa \geq \log(R)$ and certifies a quadratic-log gap against random $f$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse Geometric Karchmer-Wigderson (CG-KW) — coarse geometry / Roe-algebraic K-theory applied to circuit complexity (mathematical branch: noncommutative geometry & geometric group theory)  $\times$  Boolean formula depth ( $NC^1$  vs.  $P$ ): explicit super-logarithmic depth lower bounds via index pairings on the KW-metric space
- **Recorded:** 2026-04-27 12:41 UTC
- **Entry ID:** 738bb754804a

### Statement

Let  $f = IP_n : \{0,1\}^{\{2n\}} \rightarrow \{0,1\}$  be the inner-product-mod-2 function and let  $(X_f, d_f)$  be its KW-metric space with  $d_f(x,y) := \log_2(\text{min number of coordinates needed to distinguish } x,y)$ . Let  $c_{IP} \in HX^1(X_f)$  be the coarse cocycle obtained from the canonical ‘parity-of-disagreement’ 1-cochain  $c_{IP}(x,y) = \langle x \oplus y, x' \oplus y' \rangle \bmod 2$  (lifted to  $\mathbb{Z}$  via signed indicator), and for each propagation parameter  $R \geq 1$  let  $T_R \in C_u^*[X_f]$  be the banded Roe operator  $T_R(x,y) := 1[d_f(x,y) \leq R]/(1+|B_R(x)|)$ . Then (i) (axiom A5 instance) the trace pairing satisfies  $\log| \langle c_{IP}, T_R \rangle | / \log R \rightarrow \alpha \geq 1$  as  $n \rightarrow \infty$  and  $R = o(n)$ , so  $\kappa(IP_n) \geq 1$  with this normalization; (ii) (axiom A3 instance) for a uniformly random  $f'$  on the same  $X_{\{f'\}}$  the same construction yields  $\log| \langle c_{IP}, T_R \rangle | / \log R \rightarrow 0$  in probability, separating structured and random  $f$ .

### Rationale

This is a direct empirical probe of axioms A5 (Roe-index rigidity: explicit candidates realize a nontrivial pairing whose growth rate is the coarse depth  $\kappa$ ) and A3 (anti-natural-proofs: random instances yield trivial pairings).  $IP_n$  is the smallest ‘KRW-friendly’ explicit function whose KW protocol has a clean parity structure that lifts to a coarse cocycle, so we expect the pairing’s logarithmic-growth exponent to be a faithful proxy for  $\kappa$ . Sub-additivity (A2) and Coarse-KW link (A1) both predict  $\kappa(IP_n) \geq 1$  in this normalization (a sub-claim of the conjectured  $\Omega(\log^2 n)$  for Andreev), making a positive numerical exponent a falsifiable prediction. A null result would either refute A5 for IP or indicate the normalization choice for  $d_f$  is too coarse — both informative.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2002.07444v1] Multiparty Karchmer-Wigderson Games and Threshold Circuits - [2107.05128v2] Karchmer-Wigderson Games for Hazard-free Computation - [1404.7443v2] Depth Lower Bounds against Circuits with Sparse Orientation - [1011.5800v2] Operator-valued pseudo-differential operators and the twisted index pairing - [0710.5926v2] Mod 2 cohomology of 2-local finite groups of low rank

### Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d19f60d5.py", line 60, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d19f60d5.py", line 34, in run_trial
    d_f = [[math.log2(hamming_weight(xor(x, y))) for y in X_f] for x in X_f]
```



```

TRIAL: {'metric_name': 'Betti Sum - DNF Min', 'metric_value': 0, 'instances_tested': 0, 'conjecture_h
TRIAL: {'metric_name': 'Betti Sum - DNF Min', 'metric_value': 0, 'instances_tested': 0, 'conjecture_h
TRIAL: {'metric_name': 'Betti Sum - DNF Min', 'metric_value': 0, 'instances_tested': 0, 'conjecture_h
TRIAL: {'metric_name': 'Betti Sum - DNF Min', 'metric_value': 0, 'instances_tested': 0, 'conjecture_h
TRIAL: {'metric_name': 'Betti Sum - DNF Min', 'metric_value': 0, 'instances_tested': 0, 'conjecture_h
RESULT: FALSIFIED counterexample="singular_matrix" first_failing_seed=11

```

### Judge reasoning

The test reported FALSIFIED with counterexample='singular\_matrix' but instances\_tested=0 across all trials, indicating a Betti-computation implementation failure (singular GF(2) matrix) rather than a genuine functional counterexample. No actual  $f$  was evaluated, so neither support nor falsification of the conjecture is demonstrated. | next: Fix the GF(2) boundary-rank computation (e.g., use a robust Smith normal form or sparse rank routine) so  $B(f)$  can be evaluated on real instances, then re-run

---

## Zeckendorf Length of NW Design Rows Bounds PRG Parity Bias

- **Verdict:** INCONCLUSIVE
- **Bridge:** Zeckendorf / Ostrowski numeration: representation of integers as sums of non-consecutive Fibonacci numbers and the resulting digit-length statistic  $z(N)$  (Lekkerkerker-Carlitz metric theory of Fibonacci expansions, rarely deployed outside number theory)  $\times$  Output bias of the Nisan-Wigderson pseudorandom generator  $NW_D^f$  against parity (linear  $\chi_T$ ) distinguishers, where  $D$  is a combinatorial  $(d,m,k,t)$ -design and  $f$  is a Boolean hard function
- **Recorded:** 2026-04-27 13:16 UTC
- **Entry ID:** b133863cfef2

### Statement

Let  $D = \{S_1, \dots, S_m\}$  be any  $(d,m,k,t)$ -NW design on  $[d]$ , and let  $z_i$  be the number of Fibonacci summands in the Zeckendorf representation of  $N_i = \sum_{j \in S_i} 2^{j-1}$ ; set  $Z(D) = (1/m) \sum_i z_i$ . Then for every Boolean  $f: \{0,1\}^k \rightarrow \{0,1\}$  whose largest non-empty Fourier coefficient  $\max_{\emptyset \neq U \subseteq [k]} |\hat{f}(U)|$  equals  $\eta$ , the NW-PRG output bias against any non-empty parity test obeys  $|\text{bias}_T(D,f)| := |2^{-d} \sum_{s \in \{0,1\}^d} \{\oplus_{i \in T} f(s|_{S_i})\}| \leq \eta^{|T|} \cdot 2^{\{t \cdot (|T| \text{ choose } 2)\}} \cdot (1 + Z(D)/k)^{|T|-1}$ . A single  $(D,f,T)$  with  $k \leq 5$ ,  $m \leq 8$ ,  $d \leq 10$  violating this inequality refutes the conjecture.

### Rationale

NW analyses bound bias by  $\eta^{|T|} \cdot 2^{\{t \cdot C(|T|,2)\}}$  (the standard Nisan-Wigderson lemma); the new factor  $(1 + Z(D)/k)^{|T|-1}$  predicts that designs whose row-indicators are arithmetically 'simple' in the Fibonacci base (low Zeckendorf length, i.e., concentrated bit patterns) leak more correlation through  $f$ , while rows with maximally spread Zeckendorf decompositions act more like Beatty-equidistributed indices and force tighter cancellation. This bridges Zeckendorf metric theory with NW pseudorandomness — a pairing with effectively no prior literature — and offers a falsifier-friendly tightening of the classical bound that is meaningful only when  $Z(D)$  is non-trivially correlated with the design's discrepancy.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1311.6531v3] Brains and pseudorandom generators - [2404.12647v1] Simple constructions of linear-depth  $t$ -designs and pseudorandom unitaries - [2601.03730v1] Perception-Aware Bias Detection for Query Suggestions - [1906.10962v3] The Fibonacci Sequence

and Schreier-Zeckendorf Sets - [1302.6583v1] A note on closed-form representation of Fibonacci numbers using Fibonacci trees

## Empirical Test

- exit code: 1, elapsed: 0.30s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6b011f3.py", line 110, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_d6b011f3.py", line 95, in run_trial
    support_fraction = sum(1 for result in results if result["conjecture_holds"]) / len(results)
                        ~~~~~^~~~~~
```

ZeroDivisionError: division by zero

## Judge reasoning

The test crashed with a ZeroDivisionError before any trial data was collected, so neither the support nor falsification criterion was evaluated. | next: Fix the trial generation so designs are actually produced (ensure results list is non-empty), then rerun the pre-registered sweep over  $k \in \{3, 4, 5\}$ ,  $m \in \{4..8\}$ ,  $t \in \{1, 2\}$ .

---

## Sturmian Factor-Complexity Lower-Bounds DNF-MCSP Term Count

- **Verdict:** INCONCLUSIVE
- **Bridge:** Symbolic dynamics on the Boolean hypercube: subword/factor complexity  $p_w(k)$  of the Gray-code linearization of a truth table, in the Morse-Hedlund / Sturmian tradition (rarely deployed in meta-complexity)  $\times$  DNF-MCSP: minimum number of product terms  $\text{DNF\_min}(f)$  needed to represent a Boolean function  $f: \{0, 1\}^n \rightarrow \{0, 1\}$  given its  $2^n$ -bit truth table (Hirahara-Oliveira-Santhanam restricted-MCSP variant)
- **Recorded:** 2026-04-27 13:49 UTC
- **Entry ID:** 848aa89a6626

## Statement

Let  $w(f)$  be the binary word of length  $2^n$  obtained by listing  $f$ 's truth table in standard reflected Gray-code order, and let  $P(f) = \max_{1 \leq k \leq n} p_w(f)(k)/k$  where  $p_w(k)$  is the number of distinct length- $k$  factors of  $w$ . Then  $\text{DNF\_min}(f) \geq \lceil P(f)/2 \rceil$  for every non-constant  $f$  on  $n \leq 6$  variables, with equality achieved by every parity function  $\chi_S$  restricted to its essential variables. Equivalently: any  $f$  whose Gray-code word realizes factor-complexity ratio  $P(f) > 2T$  cannot be expressed as a DNF with  $\leq T$  terms.

## Rationale

Gray-code traversal makes adjacent truth-table positions differ in exactly one input bit, so a single AND-term contributes a contiguous arithmetic-progression-like block to  $w(f)$ ; bounding the number of distinct factors therefore bounds the combinatorial diversity of term-boundaries, which in turn bounds  $\text{DNF\_min}$ . Symbolic dynamics has been heavily used in automata theory and formal languages but, to our knowledge, never linked to MCSP-style term-minimization; Sturmian/Morse-Hedlund growth gives a clean, computable scalar invariant. Because the bound is a simple counting inequality on a  $2^n$ -bit word it sidesteps relativization (the mapping is purely syntactic on the truth table).



## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1303.5057v1] GRay: a Massively Parallel GPU-Based Code for Ray Tracing in Relativistic Spacetimes - [1203.2323v2] The greedy flip tree of a subword complex - [2412.05161v1] DNF: Unconditional 4D Generation with Dictionary-based Neural Fields - [1501.01331v1] DNF complexity of complete boolean functions - [2511.07739v3] A Lower Bound for the Fourier Entropy of Boolean Functions on the Biased Hypercube

## Empirical Test

- exit code: 124, elapsed: 180.08s

TIMEOUT after 180s

## Judge reasoning

The test timed out after 180s without producing any RESULT line, so the pre-registered support condition cannot be evaluated and the critic's challenge stands. | next: Optimize the DNF\_min computation (e.g., use Quine-McCluskey with caching or an ILP solver) and reduce sample sizes or parallelize so the test completes within the timeout.

---

## Haar-Wavelet Star-Discrepancy of Sign Matrix Lower-Bounds Rigidity at Rank $n/2$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Combinatorial discrepancy via 2D Haar-wavelet star-discrepancy of  $\pm 1$  sign matrices (Roth-Schmidt / Matousek  $L^2$  anchored-box discrepancy on the dyadic grid; rarely deployed against rigidity)  $\times$  Matrix rigidity (Valiant) at target rank  $r = n/2$ : minimum Hamming weight  $R(M, n/2)$  of a perturbation  $E$  with  $\text{rank}(M+E) \leq n/2$  over the rationals, the standard pre-Razborov rigidity proxy
- **Recorded:** 2026-04-27 14:18 UTC
- **Entry ID:** bb503edce1c2

## Statement

For every  $n \times n$  sign matrix  $M$  with  $n$  a power of 2, let  $D(M) = \max$  over dyadic anchored boxes  $B \subseteq [n] \times [n]$  of  $|\sum_{(i,j) \in B} M_{ij}| / \sqrt{|B|}$ , the normalized Haar star-discrepancy. We conjecture  $R(M, n/2) \geq c \cdot D(M)^2 / \log n$  for some absolute  $c > 0$ , and in particular for the Hadamard sign matrix  $H_n$  we conjecture  $D(H_n) = \Theta(\sqrt{n})$  so that  $R(H_n, n/2) = \Omega(n / \log n)$ . One  $n \leq 16$  sign matrix  $M$  with  $\text{rank}(M+E) \leq n/2$  achievable at Hamming weight  $< c \cdot D(M)^2 / \log n$  falsifies it.

## Rationale

Star-discrepancy on the dyadic anchored-box system measures how badly a sign pattern aligns with low-rank Haar tensor projectors, and any low-rank perturbation can only destroy  $O(\text{rank} \cdot \log n)$  Haar coefficients; thus a large worst-anchored-box imbalance should force many sign flips to reach rank  $n/2$ . This bridges Roth-Schmidt  $L^2$  discrepancy machinery — never directly fed into Valiant rigidity — to the explicit-Hadamard frontier where existing rank-trick bounds saturate at  $\Omega(n^{2/r} \cdot \log(n/r))$ . The constructive mapping (enumerate dyadic boxes, sum entries, normalize) is computable in  $O(n^2 \log^2 n)$  and gives a falsifier-friendly quantitative invariant.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [0702067v1] The Haar Wavelet Transform of a Dendrogram: Additional Notes - [1005.0979v1] Supersymmetry in Random Matrix Theory - [1112.1588v2] Evaluating Matrix Functions by Resummations on Graphs: the Method of Path-Sums - [0909.2030v2] Size Bounds for Conjunctive Queries with General Functional Dependencies - [1308.3946v1] Optimal Algorithms for Testing Closeness of Discrete Distributions

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_63ec3b34.py", line 108, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_63ec3b34.py", line 86, in run_trial
    H_n = hadamard_matrix(n)
          ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_63ec3b34.py", line 35, in hadamard_matrix
    H = hadamard_matrix(n // 2)
        ^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_63ec3b34.py", line 39, in hadamard_matrix
    bottom_right = [-x for x in H]
                   ^^
```

TypeError: bad operand type for unary -: 'list'

## Judge reasoning

The test crashed with a `TypeError` in `hadamard_matrix` (negating a list of lists instead of elements), so no instances were evaluated and neither the support nor falsification condition can be assessed. | next: Fix `hadamard_matrix` to recurse on numpy arrays (or negate element-wise) and rerun the full 5-seed  $\times \geq 200$ -instance protocol for  $n \in \{4, 8, 16\}$ .

---

## Roe-cohomological concentration: $HX^1(X_f)$ vanishes for random $f$ , separating natural-proof properties from $\kappa$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse Geometric Karchmer-Wigderson (CG-KW); coarse geometry / Roe algebras over finite KW-metric spaces  $\times$  Boolean formula-depth lower bounds ( $NC^1$  vs.  $P$ ) — a complexity-theoretic invariant on the family of  $n$ -variate boolean functions
- **Recorded:** 2026-04-27 14:43 UTC
- **Entry ID:** 7c5ad65991c5

## Statement

Let  $f: \{0,1\}^n \rightarrow \{0,1\}$  be drawn uniformly at random and let  $(X_f, d_f)$  be the KW-metric space with  $d_f$  instantiated as Hamming distance on  $X_f = f^{-1}(0) \sqcup f^{-1}(1)$ . For the controlled radius  $R = 1$  and the discrete coarse coboundary operator  $\delta$  on the Roe-style cochain complex  $C^*_{\text{coarse}}(X_f)$ , define  $h^1(f) := \dim_R HX^1(X_f) = \dim \ker(\delta^1) - \dim \text{im}(\delta^0)$ . The sub-conjecture (instance of axiom A3, anti-natural-proofs) asserts: (i) for  $n \in \{3, 4, 5, 6\}$  the empirical mean of  $h^1(f)$  over uniform  $f$  tends to 0 as  $n$  grows, with  $\Pr[h^1(f) > 0] \leq \exp(-\Omega(n))$ ; (ii) for the explicit family  $f_n = \text{PARITY}_n$ ,  $h^1(f_n) \geq n - 1$ , so the trace pairing  $(c, T)$  realizes  $\kappa(\text{PARITY}_n)$

$\geq \log(R) \cdot (n-1)/n$  with  $R = 2$ ; (iii) consequently  $\kappa$  is not a ‘large’ property in the Razborov–Rudich sense, since it fails the largeness criterion on the uniform ensemble while remaining nonzero on explicit functions, blocking the natural-proofs obstruction to A1.

## Rationale

This directly tests axiom A3 (Roe-algebraic concentration of measure). A3 predicts that  $\kappa$ -based proofs evade Razborov–Rudich because random  $f$  have trivial coarse cohomology — the  $d_f$ -metric of a generic  $f$  is too ‘uniformly mixed’ to support a nontrivial Roe-controlled cocycle, while structured  $f$  (PARITY, AND-OR towers) inherit nontrivial  $HX^1$  from their algebraic stratification of  $\{0,1\}^n$ . If concentration fails (random  $f$  routinely have  $h^1 > 0$ ), then A3 is wrong and the framework collides with the natural-proofs barrier; if it holds,  $\kappa$  is a ‘small’ invariant that still distinguishes explicit functions, which is exactly the regime needed for A1 to give a lawful  $P \notin NC^1$  attack.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2107.05128v2] Karchmer-Wigderson Games for Hazard-free Computation - [2002.07444v1] Multiparty Karchmer-Wigderson Games and Threshold Circuits - [2109.13292v1] The Hochschild Cohomology of Uniform Roe Algebras - [0805.1385v3] Almost-natural proofs - [2003.09703v1] Variance function of boolean additive convolution

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cb2e6197.py", line 78, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cb2e6197.py", line 40, in run_trial
    G = {i: [j for j in range(len(X)) if hamming_distance(i, j) <= 1] for i in range(len(X))}
             ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cb2e6197.py", line 18, in hamming_distance
    return sum(xi != yi for xi, yi in zip(x, y))
             ^^^^^^^^^
```

TypeError: 'int' object is not iterable

## Judge reasoning

The test crashed with a TypeError (‘int’ object is not iterable) inside hamming\_distance before producing any data, so no empirical results were collected for either the random ensemble or PARITY\_n. | next: Fix the bug by representing X elements as bit-vectors (e.g., tuples or binary strings) rather than ints, or convert i,j to their binary representations inside hamming\_distance, then rerun the trials.

---

## Antichain-Width of Query Certificate Poset Bounds Lifted IND CC

- **Verdict:** INCONCLUSIVE
- **Bridge:** Order theory / Dilworth’s theorem on the poset of minimal 0/1-certificates of a Boolean function ordered by sub-assignment, with antichain-width  $w(f)$  computed via Koenig-style maximum matching on the certificate bipartite graph (rarely deployed in lifting-theorem lower

bounds; distinct from rank/Mobius approaches)  $\times$  Deterministic two-party communication complexity  $D^{\text{cc}}(f \circ \text{IND}_b)$  of Indexing-gadget-lifted Boolean functions, accessed through deterministic decision-tree depth  $Q^{\text{dt}}(f)$  via the Raz-McKenzie / Goos-Pitassi-Watson lifting theorem

- **Recorded:** 2026-04-27 14:50 UTC
- **Entry ID:** 52be4733a1c4

## Statement

For every Boolean function  $f: \{0,1\}^n \rightarrow \{0,1\}$  with  $n \leq 12$ , let  $w(f)$  be the Dilworth antichain-width of the poset  $P(f)$  whose elements are the minimal 0-certificates and minimal 1-certificates of  $f$ , ordered by sub-assignment refinement ( $a \leq b$  iff  $\text{dom}(a) \subseteq \text{dom}(b)$  and  $a$  agrees with  $b$  on  $\text{dom}(a)$ ). Then  $Q^{\text{dt}}(f) \geq \lceil \log_2(w(f) + 1) \rceil$ , and consequently the  $\text{IND}_b$ -lifted deterministic communication complexity satisfies  $D^{\text{cc}}(f \circ \text{IND}_b) \geq \lceil \log_2(w(f)+1) \rceil \cdot \log_2(b) - O(\log n)$ . Falsifier: a single  $f$  with  $w(f) \geq 2^{(Q^{\text{dt}}(f)+1)}$ .

## Rationale

Lifting theorems convert decision-tree depth to communication depth, but the depth side is usually bounded via adversary or rank arguments; Dilworth width on the certificate poset captures a combinatorial ‘spread’ of incompatible partial proofs that any decision tree must distinguish, giving a poset-theoretic depth bound that should compose cleanly under IND-lifting. Because antichains of minimal certificates are pairwise incompatible, every deterministic tree must reach distinct leaves on each, forcing  $\log_2(w)$  depth without invoking algebrization-sensitive algebra. If true, the bound provides a purely order-theoretic certificate that survives the gadget product, opening a non-rank route to monotone-style depth separations.

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [2512.11833v1] Soft Decision Tree classifier: explainable and extendable PyTorch implementation - [2211.17214v1] Lifting to Parity Decision Trees Via Stifling - [1302.4207v1] A composition theorem for decision tree complexity - [1306.1593v2] The root posets and their rich antichains - [2511.07739v3] A Lower Bound for the Fourier Entropy of Boolean Functions on the Biased Hypercube

## Empirical Test

- exit code: 1, elapsed: 0.39s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2595fd2f.py", line 137, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2595fd2f.py", line 118, in run_trial
    w_f = maximum_bipartite_matching(poset)
          ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2595fd2f.py", line 69, in maximum_bipartite_matching
    dfs(u)
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2595fd2f.py", line 59, in dfs
    for v in graph[u]:
             ^^^^^
```

KeyError: 0

## Judge reasoning

The test crashed with a `KeyError` in the bipartite matching routine before producing any data, so neither the support nor falsification conditions can be evaluated. | next: Fix the `maximum_bipartite_matching` function to initialize `graph[u]` as an empty adjacency list (e.g., via `defaultdict(list)`) and rerun the pre-registered protocol.

---

## Apolar Span of Clause-Product Polynomial Bounds DPLL Leaves

- **Verdict:** INCONCLUSIVE
- **Bridge:** Apolarity / partial-derivative-span (Macaulay inverse system, catalecticant rank) — the Iarrobino–Kanev / Landsberg–Ottaviani lineage that underlies GCT border-rank obstructions for permanent vs. determinant. × Lexicographic DPLL search-tree leaf count on small unsatisfiable 3-CNF formulas.
- **Recorded:** 2026-04-27 15:25 UTC
- **Entry ID:** fe0af6ae6d43

### Statement

For an unsatisfiable 3-CNF  $F$  on  $n \leq 10$  variables with  $m$  clauses, attach to each clause  $C$  the affine linear form  $L_C := \text{off}(C) + \sum \{\text{positive } x_i \in C\} x_i - \sum \{\text{negative } \neg x_i \in C\} x_i$ , where  $\text{off}(C) = (\#\text{negative literals in } C)$ ; thus  $L_C(x)$  equals the number of true literals of  $C$  at  $x \in \{0,1\}^n$ . Let  $f_F := \prod \{C \in F\} L_C \in Q[x_1, \dots, x_n]$ , let  $\pi : Q[x] \rightarrow Q[x]/(x_i^2 - x_i) \cong Q^{t^2 n}$  be the squarefree-reduction map, and define  $\mu(F) := \dim_Q \text{span}\{\pi(\partial\{x_i\} f_F) : i=1, \dots, n\} \subseteq Q^{t^2 n}$ , computed via the identity  $\pi(\partial\{x_i\} f_F) = \sum \{C\} s(C,i) \cdot \pi(\prod \{C' \neq C\} L_{C'})$  where  $s(C,i) \in \{-1, 0, +1\}$  is the sign of variable  $x_i$  in clause  $C$ . Conjecture: for every unsatisfiable  $F$  in this regime,  $\mu(F) \geq \lceil \log_2 D_F \rceil$ , where  $D_F$  is the leaf count of depth-first DPLL with unit propagation that always branches on the lowest-indexed unassigned variable (positive branch first); a single unsatisfiable  $F$  with  $\mu(F) < \lceil \log_2 D_F \rceil$  refutes it.

### Rationale

Apolarity converts lower bounds on partial-derivative-span dimension into border-rank obstructions, the engine of Landsberg–Ottaviani’s permanent lower bounds inside GCT. Each clause is genuinely a linear form, so  $f_F$  is exactly the kind of degree- $m$  product whose derivative-span GCT analyzes for orbit-closure obstructions; the squarefree projection  $\pi$  is the natural finite Macaulay quotient. Linking  $\mu(F)$  to DPLL leaves tests whether the algebraic rigidity that obstructs orbit-closure containment is the same rigidity that obstructs DPLL collapse — a candidate computational shadow of GCT obstructions.

### Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [0906.0693v3] An improved lower bound on the counterfeit coins problem - [1007.1875v2] Lower Bounds for Quantum Oblivious Transfer - [1801.08709v2] Adaptive Lower Bound for Testing Monotonicity on the Line - [2405.16149v3] Small unsatisfiable  $k$ -CNFs with bounded literal occurrence - [1203.3706v2] On the Complexity of Computing Minimal Unsatisfiable LTL formulas

### Empirical Test

- exit code: 1, elapsed: 0.10s

```
ome/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 159, in <module>
    result = run_trial(seed)
```

```

^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 115, in run_trial
    if is_unsat(F, n):
        ^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 107, in is_unsat
    return not dpll(F, assignment, n)
        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 85, in dpll
    if dpll(F - {tuple(sorted([var + 1 if sign > 0 else -(var + 1) for sign, var in clause])) for clause i
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 85, in dpll
    if dpll(F - {tuple(sorted([var + 1 if sign > 0 else -(var + 1) for sign, var in clause])) for clause i
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 85, in dpll
    if dpll(F - {tuple(sorted([var + 1 if sign > 0 else -(var + 1) for sign, var in clause])) for clause i
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
[Previous line repeated 993 more times]
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_38d58c5e.py", line 80, in dpll
    if all(lit in assignment and assignment[lit] == sign for lit, sign in clause):
        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
RecursionError: maximum recursion depth exceeded

```

## Judge reasoning

The test crashed with a RecursionError in the DPLL implementation before producing any data, so no instances were evaluated against the pre-registered criterion. | next: Fix the DPLL routine (iterative implementation or raise recursion limit, and correct the buggy clause-filtering expression) and rerun the 30-instance protocol.

---

## Cheeger Constant of Quotient Multigraph Bounds Tseitin Resolution Width

- **Verdict:** INCONCLUSIVE
- **Bridge:** Spectral graph theory via Cheeger constants of edge-contraction quotient multigraphs ( $h(G/S)$  over induced vertex partitions  $S$ , rarely applied to proof complexity)  $\times$  Resolution refutation width  $w(T(G,c) \vdash \perp)$  of Tseitin formulas on small 3-regular graphs with odd total charge
- **Recorded:** 2026-04-27 15:55 UTC
- **Entry ID:** d25429e913d1

### Statement

For every 3-regular graph  $G$  on  $n \leq 20$  vertices with odd-total charge  $c$ , let  $h(G) = \min$  over balanced bipartitions  $S$  of  $|E(S, V \setminus S)| / \min(|S|, |V \setminus S|)$ , and let  $h_q(G) = \min$  over partitions  $P$  of  $V$  into  $k \geq 2$  nonempty blocks of  $(\text{cut-edges of } P) / (k-1)$ . We conjecture  $w(T(G,c) \vdash \perp) \geq \lceil h_q(G) \rceil$  and moreover  $w(T(G,c) \vdash \perp) \leq 3 \cdot h_q(G) + 2$  across all such  $(G,c)$ . Equivalently, the resolution width of Tseitin equals the quotient-Cheeger constant up to a constant factor of 3, sharper than the standard expansion bound which uses only  $h(G)$ .

### Rationale

Classical Ben-Sasson-Wigderson and Urquhart bounds use vertex-expansion of subsets of size  $n/3..2n/3$  to prove  $\Omega(h^*)$  width lower bounds, but they discard cut information from finer partitions. The quotient-multigraph Cheeger constant  $h_q$  aggregates parity obstructions across all coarsenings of  $G$ , exactly matching the inductive contraction structure used in resolution derivations of



parity-like functions. By GPW lifting with indexing gadget  $\text{IND}_b$ , this entails  $D^{\text{cc}}(f \cdot \text{IND}_b) \geq \lceil \log_2(\lambda_2(f)+1) \rceil \cdot \log_2 b - O(\log k)$ .

## Rationale

Schensted's theorem makes  $\lambda_2(\pi_f)$  the length of the longest weakly-decreasing subsequence of  $\pi_f$ , a global obstruction distinct from antichain width, matroid rank, or Möbius invariants — it captures how thoroughly the value-class boundary scrambles the lex order. Each decision-tree query can split the truth table into two halves but cannot shorten a long alternating descent chain by more than a factor of 2, suggesting  $Q^{\text{dt}}$  must grow logarithmically with  $\lambda_2$ . The construction is a simple permutation statistic, side-steps the natural-proofs barrier ( $\lambda_2$  is not a pseudorandom property — random  $f$  has  $\lambda_2 \approx c \cdot 2^{\{k/2\}}$ ), is unaffected by algebrization (no oracle-relativizing structure), and RSK has never been deployed inside the GPW lifting framework.

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1808.06095v5] Skew RSK and the switching on ballot tableau pairs - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [2512.11833v1] Soft Decision Tree classifier: explainable and extendable PyTorch implementation - [0109079v2]  $\text{GL}(n, q)$  and Increasing Subsequences in Nonuniform Random Permutations - [2309.01208v1] Streaming and Query Once Space Complexity of Longest Increasing Subsequence

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_4eae8e14.py", line 89, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_4eae8e14.py", line 63, in run_trial
    pi_f = sorted(range(n), key=lambda x: (f(x, j) for j in range(k)))
             ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

TypeError: '<' not supported between instances of 'generator' and 'generator'

## Judge reasoning

The test crashed with a `TypeError` before producing any data — the sort key was incorrectly written as a generator expression rather than a tuple, so no functions were evaluated and no `RESULT` line was produced. | next: Fix the key in the sort to `key=lambda x: (f(x), x)` (using the precomputed truth table  $f[x]$ ) and rerun the full enumeration over all 65536 functions on  $k=4$ .

## Coarse-dimensional KRW direct sum: asdim is sub-additive under block composition

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse Geometric Karchmer-Wigderson (CG-KW) framework; coarse geometry / asymptotic-dimension theory (Gromov, Bell-Dranishnikov)  $\times$  Boolean formula-depth complexity; the Karchmer-Raz-Wigderson (KRW) direct-sum conjecture for  $\text{NC}^1$  lower bounds
- **Recorded:** 2026-04-27 16:44 UTC
- **Entry ID:** f685d342f4c0



## Statement

For all Boolean functions  $f: \{0,1\}^n \rightarrow \{0,1\}$  and  $g: \{0,1\}^m \rightarrow \{0,1\}$ , let  $(X_f, d_f)$  and  $(X_g, d_g)$  denote their KW-metric spaces and let  $(X_{f \circ g}, d_{f \circ g})$  be the coarse\_product encoding the block composition  $f \circ g$ . Then there exists a universal constant  $C \leq 2$  such that  $\text{asdim}(X_{f \circ g}) \geq \text{asdim}(X_f) + \text{asdim}(X_g) - C$ . Equivalently, certified by the asymptotic-dimension-witness primitive: if  $\chi_f, \chi_g$  are optimal  $(k_f, R_f)$ - and  $(k_g, R_g)$ -witnesses for  $X_f, X_g$  respectively, then no  $(k_f + k_g - C - 1, R)$ -witness exists for  $X_{f \circ g}$  for any finite  $R$ . Combined with axiom A1, this yields the KRW-style implication  $d(f \circ g) \geq \Omega(d(f)) + \Omega(d(g)) - O(1)$ .

## Rationale

This sub-conjecture tests axiom A2 (Composition sub-additivity) directly using the framework's coarse\_product primitive. It mirrors the classical Bell-Dranshnikov inequality  $\text{asdim}(X \times Y) \leq \text{asdim}(X) + \text{asdim}(Y)$  for metric products, asserting that the matching lower bound also holds for the depth-adjusted KW-product metric  $d_{f \circ g}$ . The mechanism is structural: a controlled cover of  $X_{f \circ g}$  of multiplicity  $m$  must, when restricted to fibers, refine into controlled covers of  $X_f$  and  $X_g$ , so the multiplicity exponents add. Verifying A2 on small instances closes the gap between  $\kappa$ -additivity and KRW, since Andreev-style amplification then bootstraps  $\kappa$ -bounds through composition (Axiom A5).

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [2107.05128v2] Karchmer-Wigderson Games for Hazard-free Computation - [2002.07444v1] Multiparty Karchmer-Wigderson Games and Threshold Circuits - [0711.0446v1] Asymptotic Properties of Hilbert Geometry - [2306.00615v5] Toward Better Depth Lower Bounds: A KRW-like theorem for Strong Composition - [2307.07605v1] First-order Methods for Affinely Constrained Composite Non-convex Non-smooth Problems: Lower Complexity Bound and Near-o

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2678b93a.py", line 158, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2678b93a.py", line 110, in run_trial
    d_f_val = max(d_f(f, x, y) for x, y in itertools.combinations(X_f, 2))
               ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2678b93a.py", line 110, in <genexpr>
    d_f_val = max(d_f(f, x, y) for x, y in itertools.combinations(X_f, 2))
                   ^
```

NameError: name 'f' is not defined

## Judge reasoning

The test crashed with a NameError ('f' is not defined') before producing any data, so the pre-registered support condition could not be evaluated. Per Rule 2, a crash yields INCONCLUSIVE. | next: Fix the bug in run\_trial (line 110) by passing f as an argument to d\_f within the generator expression, then re-run the deterministic enumeration over all 36 (f,g) pairs.