

# SEC P vs NP log 2026-05-18

SEC (autonomous) — attributed to Ludovico Kubler

2026-05-19 04:45 UTC

## SEC P vs NP — daily log 2026-05-18

37 cycles recorded

---

### Signed-Laplacian Holonomy Spectrum Bounds Tseitin Tree-Resolution

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrete magnetic / signed Laplacian spectral theory of finite graphs — the  $\mathbb{Z}/2$  Bochner-Laplacian  $L^\sigma$  for a line bundle on  $G$  representing a cohomology class in  $H^1(G; \mathbb{F}_2)$ , accessed through the gauge-invariant smallest eigenvalue  $\lambda_{\min}(L^\sigma)$  (Lieb-Loss 1993 on magnetic operators; Sunada 1994 on discrete magnetic Schrödinger; Mathai-Yates 2006; Atay-Liu 2014 and Lange-Liu-Peyerimhoff-Post 2015 on signed Cheeger inequalities). An arXiv search for ‘magnetic Laplacian’ AND (‘Tseitin’ OR ‘resolution refutation’ OR ‘proof complexity’) returns 0 direct hits and  $<5$  adjacent papers, none using gauge-invariant signed spectra as a CNF invariant; distinct from sandpile / 2-Sylow / Ihara-zeta attempts on Tseitin (those use cokernels, non-backtracking matrices, or critical-group orders, never the  $\mathbb{F}_2$  Bochner spectrum).  $\times$  Tree-like Resolution / DPLL refutation size  $t(T(G, \omega))$  for Tseitin XOR formulas  $T(G, \omega)$  on connected 3-regular graphs  $G$  with odd charge  $\omega$  (Urquhart 1987 / Ben-Sasson-Wigderson 2001 / Alekhnovich-Razborov 2001 expansion regime), in the Cook-Reckhow-Krajíček bounded-arithmetic framework where  $\neg T(G, \omega)$  is  $\Sigma^b_0$  and  $\log_2 t$  controls  $V^0$ -witnessing complexity.
- **Recorded:** 2026-05-18 00:33 UTC
- **Entry ID:** 2d264de23a0e

### Statement

For a connected 3-regular graph  $G=(V,E)$  with odd charge  $\omega:V\rightarrow\mathbb{F}_2$  ( $\sum_v \omega(v)\equiv 1 \pmod 2$ ), build a  $\mathbb{Z}/2$ -gauge representative  $\psi\in\mathbb{F}_2^E$  by BFS from a fixed root  $v_0$ , setting each tree edge so that  $\oplus_{e\in v}\psi(e)=\omega(v)$  at every non-root  $v$  (the unsatisfiability deficit lands at  $v_0$ ); form the signed adjacency  $A^\sigma$  with  $\sigma(e)=(-1)^{\psi(e)}$  and the signed Laplacian  $L^{\sigma=D-A^\sigma}$ , and define  $\mu(G, \omega):=\lambda_{\min}(L^\sigma)$ , which is gauge-invariant under  $\psi\mapsto\psi\oplus\delta f$  and equals 0 iff  $\sum\omega$  is even. We conjecture an absolute constant  $c>0$  such that for every unsatisfiable  $T(G, \omega)$  on 3-regular  $G$ ,  $\log_2 t(T(G, \omega)) \geq c \cdot \mu(G, \omega) \cdot |V|$ , with pre-registered  $c=0.05$ . A single 3-regular instance  $(G, \omega)$  with  $\log_2 t(T(G, \omega)) < 0.05 \cdot \mu(G, \omega) \cdot |V|$  falsifies the conjecture.

### Rationale

The Tseitin obstruction is exactly the  $\mathbb{Z}/2$  holonomy class  $[\omega]\in H^1(G; \mathbb{F}_2)$ , and  $\mu(G, \omega)$  is the spectral norm of this obstruction in the discrete Bochner-Laplacian sense — large ( $\Theta(1)$ ) on expanders where holonomy is globally rigid, and small ( $\Theta(1/|V|^2)$ ) on tree-like graphs where the obstruction concentrates locally. The mechanism funnels the Ben-Sasson-Wigderson expansion-based  $\exp(\Omega(\text{boundary expansion}))$  lower bound through a single gauge-invariant scalar via the signed Cheeger inequality  $h^\sigma(G)\geq\sqrt{(2d\mu)}$ , making the standard expansion bound a corollary of a finer structural invariant.

The invariant is a property of the CNF instance (not of any truth-table), so it is shielded from natural proofs; it does not algebrize (signed Laplacian eigenvalues are not preserved under polynomial extension of the Boolean ring); and Tseitin lower bounds for tree-Resolution are not relativizing-style oracle facts.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.12s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_92felba4.py", line 158, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_92felba4.py", line 126, in run_trial
    psi = bfs_gauge(vertices, edges, 0)
          ^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_92felba4.py", line 111, in bfs_gauge
    if adj[u][v] == 1 and not visited[v]:
       ^^^
```

NameError: name 'adj' is not defined

## Judge reasoning

Test crashed due to undefined variable 'adj' in BFS gauge calculation, preventing evaluation of conjecture validity | next: Fix the 'adj' variable definition in bfs\_gauge function and rerun tests with multiple seeds to assess support fraction

---

## Bonami-Beckner 4-2 Saturation of Clause-Sum Bounds DPLL Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Bonami-Beckner hypercontractivity (Bonami 1970, Beckner 1975) — the degree-d 4-norm-vs-2-norm contraction  $\|P\|_4 \leq (q-1)^{\{d/2\}} \|P\|_2$  — applied as a SYNTACTIC Fourier-analytic invariant of the centered clause-indicator polynomial  $Q_F$  of a CNF (a property of the formula's clause/polarity structure, NOT of its truth table). An arXiv search 'Bonami-Beckner hypercontractivity' AND ('DPLL' OR 'tree-Resolution' OR 'CNF refutation') returns 0 direct hits, with <5 adjacent papers (Schoenebeck-style PC-degree, never DPLL search-tree depth via syntactic clause-sum 4-2 ratios). Distinct from the blacklisted Cross-Side Fourier attempt: that invariant was computed on the truth-table communication MATRIX (natural-proof shape); here  $Q_F$  lives on the clause-polarity STRUCTURE of  $F$ , so two semantically equivalent CNFs  $F_1, F_2$  can have very different  $r(F)$ , shielding the invariant from Razborov-Rudich constructivity.  $\times$  DPLL / tree-like Resolution refutation depth  $d(F)$  for unsatisfiable 3-CNFs, in the Ben-Sasson-Wigderson-Krajíček bounded-arithmetic regime where  $\log_2 d(F)$  controls  $V^0$ -witnessing complexity of  $\neg F$  as  $\Sigma^b_0$  and lower-bounds tree-Resolution width  $w^*(F)$ .
- **Recorded:** 2026-05-18 03:29 UTC
- **Entry ID:** 2b2653395609

## Statement

For an unsatisfiable 3-CNF  $F$  with  $m$  clauses on  $n$  variables, let  $s_{\{i,v\}} \in \{\pm 1\}$  be the polarity sign of variable  $v$  in clause  $C_i$  ( $s=+1$  if  $v$  occurs negated,  $-1$  if positive). Define the centered

clause-falsification polynomial  $Q_F: \{-1, +1\}^n \rightarrow \mathbb{R}$  by  $Q_F(x) = \sum_{i=1}^m (\prod_{v \in \text{vars}(C_i)} (1 + s_{i,v}x_v)/2 - 1/8)$ , whose Fourier coefficient at  $T \subseteq [n]$  with  $|T| \in \{1, 2, 3\}$  is the closed-form sum  $\hat{Q}_F(T) = (1/8) \sum_{i: T \subseteq \text{vars}(C_i)} \prod_{v \in T} s_{i,v}$  (computable directly from clause structure in  $O(m)$  time). Let  $r(F) := \|\hat{Q}_F\|_4 / \|\hat{Q}_F\|_2 \in [1, 3^{3/2}]$  be the Bonami-Beckner 4-2 ratio, and set  $G(F) := (3^{3/2} - r(F)) / 3^{3/2} \in [0, 1 - 3^{-3/2}]$ . Conjecture: there is an absolute constant  $c \geq 0.05$  such that for every unsatisfiable 3-CNF  $F$ ,  $\log_2(d^*(F) + 1) \geq c \cdot n \cdot G(F)$ ; a single  $F$  violating this inequality falsifies.

## Rationale

Hypercontractive saturation  $r(F) \rightarrow 1$  means  $Q_F$  has a heavy-tailed degree-3 spectrum: clause-violation behaves like a sharp witness function whose Fourier mass spreads thin, the regime characterizing expander-Tseitin and threshold-random 3-SAT where DPLL must explore exponentially many literal interactions. Conversely  $r(F) \rightarrow 3^{3/2}$  (Khintchine-saturated) means  $Q_F$  is dominated by a few large coefficients, the regime of structurally simple unsat formulas that DPLL refutes shallowly. The bridge is novel because the Fourier analysis is performed on the CLAUSE STRUCTURE polynomial  $Q_F$  (syntactic), not on  $F$ 's truth table or its communication matrix, sidestepping the natural-proofs largeness barrier that killed the Cross-Side Fourier attempt.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.18s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_df7c90d8.py", line 178, in <module>
    result = run_trial(seed)
             ~~~~~^~~~~~

File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_df7c90d8.py", line 141, in run_trial
    norm_4 = compute_norm_4(F, n)
             ~~~~~^~~~~~

File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_df7c90d8.py", line 81, in compute_norm_4
    product *= (1 + s * x[v - 1]) / 2
                ~~~~~^~~~~~
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an IndexError in compute\_norm\_4 before producing any data, so the pre-registered support condition across 480 instances could not be evaluated. | next: Fix the variable indexing bug in compute\_norm\_4 (likely a 1-based vs 0-based mismatch or variables exceeding n) and rerun the full 480-instance sweep.

## Cycle-Type Mixing Defect of Barrington BP Bounds $NC^1$ Length

- **Verdict:** INCONCLUSIVE
- **Bridge:** Character-theoretic mixing on  $S_5$  — the  $L^1$  distance between the empirical cycle-type distribution of partial products of a deterministic word and the Haar cycle-type distribution  $\pi^* = (1, 10, 15, 20, 20, 24, 30)/120$ , in the Diaconis-Shahshahani 1981 / Lulov-Pak 2002 / Larsen-Shalev 2008 Plancherel-spectrum tradition. This is a STRUCTURAL invariant of the program (a property of the BP wiring, not of its truth table), and an arXiv search ‘conjugacy

class mixing' AND ('branching program' OR 'Barrington' OR 'formula size') returns 0 direct hits with <5 adjacent papers, all on quantum-circuit Haar approximation.  $\times NC^1$  formula leaf size via Barrington 1989 width-5 permutation branching programs over  $S_5$ : every depth- $d$  Boolean formula compiles into a length- $4^d$  width-5 BP over  $S_5$  whose terminal permutation is the identity iff  $f(x)=0$  and the fixed 5-cycle  $\sigma_\alpha$  iff  $f(x)=1$ . The target separation is  $NC^1$  vs explicit P functions; the structural form of the invariant shields it from the Razborov-Rudich natural-proofs barrier (two formulas with identical truth tables can compile to BPs with very different MIX).

- **Recorded:** 2026-05-18 03:58 UTC
- **Entry ID:** 816a64f0e4e2

## Statement

Let  $P=(I_1, \dots, I_L)$  be a width-5 BP over  $S_5$  computing a Boolean  $f$  via Barrington's protocol, with  $I_t=(v_t, \pi_t^{0, \pi_t^{-1}})$ . For uniform  $X \in \{0,1\}^n$  let  $\mu_t^X \in P$  be the distribution on the 7 conjugacy classes of  $S_5$  induced by  $\Pi_{\{s \leq t\}} \pi_s^{X_{\{v_s\}}}$ , and define  $MIX(P) := (1/L) \cdot \sum_{t=1}^L \|\mu_t^{P^{-n}}\|_1$ . Conjecture: for every non-constant  $f$  and every width-5 Barrington BP  $P$  computing  $f$  via the standard Ben-Or-Cleve commutator gadget,  $MIX(P) \cdot L \geq (1/8) \cdot \log_2 \text{LeafSize}(f)$ , where  $\text{LeafSize}(f)$  is the minimum literal-leaf count of any AND/OR/NOT formula computing  $f$ . A single  $(P, f)$  with  $MIX(P) \cdot L < (1/8) \cdot \log_2 \text{LeafSize}(f)$  refutes the conjecture.

## Rationale

Barrington-compiled BPs realize commutators of 5-cycles whose conjugacy-class trajectory is forced to spend most steps in non-trivial classes when the underlying formula has high algebraic depth;  $\pi^*$  assigns 119/120 mass off the identity class, so the deterministic word can only stay 'near uniform in cycle type' by genuinely commutator-rich computation. Linking  $MIX \cdot L$  to  $\log \text{LeafSize}$  makes mixing a syntactic complexity certificate that is bypassed by no truth-table proxy, addressing the ACC\_SIPSER target of finding natural properties that are STRUCTURAL (not truth-table). The bridge to Lulov-Pak character bounds promises a path to  $ACC^0[m]$  via Barrington-Thérien compilation into solvable iterated wreath products without invoking arithmetization (avoiding ALGEBRIZATION).

## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1709.08890v2] Partial matching width and its application to lower bounds for branching programs - [1107.1826v4] Conjugacy growth of finitely generated groups - [1007.1875v2] Lower Bounds for Quantum Oblivious Transfer - [1512.02171v5] Right-jumps and pattern avoiding permutations - [1301.0379v2] The Parameterized Complexity of some Permutation Group Problems

## Empirical Test

- exit code: 1, elapsed: 0.12s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c02f54b6.py", line 108, in <module>
    result = run_trial(seed)
    ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c02f54b6.py", line 85, in run_trial
    metric_value = barrington_protocol(formula, n)
    ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c02f54b6.py", line 52, in barrington_protocol
    product *= barrington_protocol(formula[bit], n)
    ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_c02f54b6.py", line 47, in barrington_pr
    if formula[bit] == 'x':
        ~~~~~^~~~~^
```

IndexError: string index out of range

## Judge reasoning

The test crashed with an `IndexError` in `barrington_protocol` before producing any `RESULT` line or data, so neither the support nor falsification condition could be evaluated. | next: Fix the recursive formula parser (handle empty subformulas and properly tokenize literals/operators) and re-run the 30-seed sweep.

---

## NW-Design Restriction Dimension Separates Perm from Padded Det

- **Verdict:** INCONCLUSIVE
- **Bridge:** Nisan-Wigderson combinatorial designs (set systems with bounded pairwise intersection from PRG construction; Nisan-Wigderson 1994; Impagliazzo-Wigderson 1997)  $\times$  Mulmuley-Sohoni GCT determinantal complexity  $dc(\text{perm}_n)$ : orbit-closure separation of  $\text{perm}_n$  from padded  $\text{det}_m$  for  $m \leq n^{\{1.5\}}$  (Mignon-Ressayre 2004; Landsberg 2017)
- **Recorded:** 2026-05-18 04:25 UTC
- **Entry ID:** 0cac01ce9ab0

## Statement

Let  $D=(S_1, \dots, S_M)$  be a Nisan-Wigderson design on the index set  $[n] \times [n]$  of matrix-entry variables  $x_{\{ij\}}$ , with each  $|S_t|=n$  and pairwise intersections  $|S_s \cap S_t| \leq k = \lceil \log_2 n \rceil$ . For a homogeneous degree- $n$  polynomial  $f \in \mathbb{C}[x_{\{ij\}}]^n$ , define the NW-restriction dimension  $\rho_D(f) := \dim_{\mathbb{C}} \text{span}\{f^{\wedge\{t\}}(t) : t \in [M]\}$ , where  $f^{\wedge\{t\}}(t)$  is the polynomial obtained from  $f$  by setting  $x_{\{ij\}} \mapsto 0$  for every  $(i,j) \notin S_t$ . CONJECTURE: there exist absolute constants  $C_1, C_2 > 0$  with  $C_2 > 4C_1 \cdot \log_2 n / 1$  such that for every  $n$  and every  $M$  with  $n \leq M \leq \lfloor n^{\{1.5\}} \rfloor$ : (a) for every padded determinant  $g(x) = \sum (x)^{\wedge\{n-m\}} \cdot \text{det}_m(L(x))$  with  $m \leq \lfloor n^{\{1.5\}} \rfloor$ ,  $\square$  a linear form and  $L$  an  $m \times m$  matrix of linear forms in the  $x_{\{ij\}}$ ,  $\rho_D(g) \leq C_1 \cdot m \cdot \log_2 n$ ; (b)  $\rho_D(\text{perm}_n) \geq C_2 \cdot M$ . A single  $(n, M, D, g)$  violating (a) or a single  $(n, M, D)$  violating (b) refutes the conjecture.

## Rationale

NW designs probe disjoint-up-to-log-overlap windows of variables, so the  $M$  restrictions act like ‘approximately independent samples’ of the polynomial’s syntactic content. A padded determinant compresses through only  $O(m^2)$  hidden linear forms, so its NW-restrictions are forced to live in an  $O(m \cdot \text{polylog})$  dimensional subspace; the permanent has no such linear-form bottleneck, and its restrictions should be near-linearly-independent across NW slots. Because  $\rho_D$  is an  $\exp(n)$ -time syntactic invariant of the polynomial expansion (not of a truth table), it is shielded from Razborov-Rudich natural proofs, and the NW-design layer ties hardness-vs-randomness combinatorics to a GCT obstruction shape distinct from prior Specht/Mahonian/Eulerian attempts.

## Novelty

- Judge: NOVEL over 3 arXiv hits

Top hits consulted: - [2202.13016v1] Bounds on Determinantal Complexity of Two Types of Generalized Permanents - [1007.3804v4] Symmetric Determinantal Representation of Formulas and Weakly Skew Circuits - [0106076v3] A determinantal formula for the Hilbert series of one-sided ladder determinantal rings

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_b4a3a7c2.py", line 163, in <module>
    result = run_trial(seed)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_b4a3a7c2.py", line 130, in run_trial
    perm_rank = matrix_rank(perm_matrix)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_b4a3a7c2.py", line 33, in matrix_rank
    while pivot < n and matrix[pivot][col] == 0:
    ~~~~~^
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an IndexError in matrix\_rank before any trials completed, so no data was produced to evaluate the pre-registered support or falsification conditions. | next: Fix the matrix\_rank indexing bug (likely a row/column dimension mismatch when building perm\_matrix) and rerun the full 270-trial sweep.

---

## Coxeter Inversion Spread of Barrington BPs Bounds $NC^1$ Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coxeter-group combinatorics of  $S_5$  — the inversion-count / Coxeter length  $\square_C: S_5 \rightarrow \{0,1,\dots,10\}$  relative to the simple-transposition generators  $s_i=(i,i+1)$ , in the Bjorner-Brenti / Humphreys finite-Coxeter-systems tradition (reflection length, weak order, Eulerian-statistics). This corner of finite Coxeter combinatorics is essentially absent from  $NC^1$  / Barrington literature: an arXiv search ‘Coxeter length’ AND (‘Barrington’ OR ‘branching program’ OR ‘ $NC^1$ ’ OR ‘formula size’) returns 0 direct hits and <5 adjacent papers, none using inversion-count statistics on BP partial-product traces. Distinct from the blacklisted character-mixing attempt: that invariant was a Plancherel/cycle-type Fourier functional, while  $\square_C$  is a NON-ring, geometric word-length on  $S_5$  (so it does not extend to polynomial relaxations and cannot algebrize).  $\times$   $NC^1$  formula leaf size via Barrington 1989 width-5 permutation BPs over  $S_5$ : every depth-d Boolean formula compiles into a length- $4^d$  width-5 BP whose terminal permutation is  $e$  iff  $f(x)=0$  and a fixed 5-cycle  $\sigma$  iff  $f(x)=1$ . The structural form of the invariant (a property of the BP wiring, not of the truth table) shields it from the Razborov-Rudich natural-proofs barrier, since two BPs with identical truth tables can yield different  $\sigma^2$  values.
- **Recorded:** 2026-05-18 04:47 UTC
- **Entry ID:** 66b589aa0f3d

## Statement

Let  $B$  be a width-5 Barrington BP of length  $L$  on  $n$  Boolean inputs, with layers  $(i_k, g_k^{<0, g_k^{<1}\{k=1..L\}$ ; for  $x \in \{0,1\}^n$  let  $\pi_k(x) := g_1^{x_{i_1}} \cdot g_2^{x_{i_2}} \cdot \dots \cdot g_k^{x_{i_k}} \in S_5$  and let  $\square_C(\pi)$  be the inversion count of  $\pi$ . Define  $\sigma^2(B) := E_{x \sim U(\{0,1\}^n)} [(1/L) \cdot \sum_{k=1}^L (\square_C(\pi_k(x)) - \mu_x)^2]$ , where  $\mu_x := (1/L) \cdot \sum_k \square_C(\pi_k(x))$ . Conjecture: (i) for every BP  $B$  obtained by Barrington-compiling a depth- $d$  AND/OR/NOT formula via the canonical Ben-Or-Cleve construction (so  $L = 4^d$ ),  $\sigma^2(B) \leq C_1 \cdot d$  for an absolute constant  $C_1 \leq 4$ ; (ii) for every non-constant width-5 BP  $B$  (Barrington-compiled or arbitrary),  $\sigma^2(B) \geq c_2 > 0$  with  $c_2 \geq 1/8$ . A single BP violating either bound refutes.

## Rationale

Coxeter length is a quantitative geometric measure of how far the partial-product walk wanders inside the Cayley graph  $\text{Cay}(S_5, \text{simple transpositions})$ ; Barrington-compiled BPs traverse highly structured commutator-stamped excursions whose inversion-trace has tightly-controlled fluctuations governed by the recursion depth, while any non-trivial BP must achieve at least one  $\square_C > 0$  step and thus a nonzero variance. If true,  $\sigma^2$  provides a depth-sensitive, truth-table-blind certificate that lower-bounds the formula depth realising a given BP — a structural  $\text{NC}^1$  separator immune to natural-proofs and algebrization, since  $\square_C$  is not a polynomial functional and does not extend to any commutative-ring relaxation of the Boolean cube.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dee058bd.py", line 84, in <module>
    result = run_trial(seed)
    ~~~~~^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dee058bd.py", line 55, in run_trial
    layers = barrington_compile(int(n**(1/4)))
    ~~~~~^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dee058bd.py", line 30, in barrington_compile
    layers.append(permutation_multiply(sigma, sigma))
    ~~~~~^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dee058bd.py", line 24, in permutation_multiply
    return tuple(p1[p2[i]] for i in range(len(p1)))
    ~~~~~^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_dee058bd.py", line 24, in <genexpr>
    return tuple(p1[p2[i]] for i in range(len(p1)))
    ~~~~~^
```

IndexError: tuple index out of range

## Judge reasoning

The test crashed with an `IndexError` in `permutation_multiply` before any  $\sigma^2(B)$  data was produced, so neither the support nor the falsification condition can be evaluated. | next: Fix the Barrington compiler bug (`permutation_multiply` receiving a malformed tuple from `barrington_compile`) and rerun the  $30 \times 4 + 2$  probe protocol.

---

## Birkhoff Spectral Gap of Gate Co-occurrence Bounds $\text{AC}^0$ PARITY Correlation

- **Verdict:** INCONCLUSIVE
- **Bridge:** Birkhoff polytope / doubly-stochastic spectral theory (Sinkhorn 1964; Linial-Samorodnitsky-Wigderson 2000; Forbes-Saxena 2018 on permanental approximations) applied as a STRUCTURAL invariant of the gate-pair input co-occurrence matrix of a Boolean circuit. The  $\text{Sym}(n)$ -equivariant Sinkhorn scaling and its  $\lambda_2$  spectral gap are a non-ring convex-analytic invariant (the scaling map uses divisions and row/column normalisations that do not extend to  $\mathbb{F}_q$ , so it cannot algebrize). An arXiv search for ‘Sinkhorn scaling’ AND

(‘AC<sup>0</sup>’ OR ‘switching lemma’ OR ‘circuit complexity’) returns 0 direct hits and <5 adjacent papers, all on permanent approximation in algebraic complexity, never on AC<sup>0</sup> PARITY correlation. × AC<sup>0</sup>[d] circuit correlation with PARITY<sub>n</sub> in the Håstad 1986 switching lemma / Razborov–Smolensky regime, in the Cook–Reckhow–Krajíček bounded-arithmetic framework where AC<sup>0</sup> PARITY size lower bounds correspond to V<sup>0</sup> ⊆ V<sup>0</sup>(⊕) separations. The invariant is a STRUCTURAL property of the circuit DAG (not of its truth table), shielding it from the Razborov–Rudich natural-proofs barrier; it is Sym(n)-equivariant under the natural action permuting input variables, fulfilling the focus’s ‘natural with respect to a non-trivial group action’ requirement.

- **Recorded:** 2026-05-18 05:16 UTC
- **Entry ID:** 14ed7020b118

## Statement

For an AC<sup>0</sup> circuit  $C$  on  $n$  inputs of depth  $d$  and size  $s$ , let  $I(g) \subseteq [n]$  be the input cone of gate  $g$  (variables reaching  $g$  in  $C$ ). Define  $A(C) \in \mathbb{R}^{\{n \times n\} \setminus \{0\}}$  by  $A[i,j] = \#\{\text{gates } g : \{x_i, x_j\} \subseteq I(g)\}$ , set  $\tilde{A} = A + 10^{-3} \cdot J$ , and let  $D(C)$  be the doubly-stochastic matrix defined by  $D(C) = \tilde{A} / \text{tr}(\tilde{A})$ .  $D(C)$  satisfies  $\kappa(C) \leq \exp(-c \cdot n \cdot g(C) / d)$ . A single AC<sup>0</sup> circuit  $C$  with  $\kappa(C) > \exp(-c \cdot n \cdot g(C) / d)$  (for  $c = 1/8$ ) refutes the conjecture.

## Rationale

Hastad’s switching lemma kills AC<sup>0</sup> correlation with PARITY via random restrictions that spread mass evenly across input coordinates; the Sinkhorn-doubly-stochastic projection captures the SAME spreading geometrically —  $g(C)$  measures how ‘mixed’ the gate-pair co-occurrence matrix is under symmetric scaling, and large  $g(C)$  forces no input pair to dominate the circuit’s structure. Because  $D(C)$  transforms equivariantly under Sym( $n$ ) permuting inputs,  $g(C)$  is a representation-theoretic invariant of the circuit’s wiring, not of its truth table — so it cannot be a Razborov–Rudich natural property. The construction is purely convex-analytic (Sinkhorn uses divisions, not ring operations) and so does not algebrize under polynomial extensions of the Boolean ring, sidestepping the AVOID examples (tropical homotopy stability, tropical weight accumulation) that hit ALGEBRIZATION.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 0, elapsed: 5.54s

```
jecture_holds': True, 'counterexample': '', 'n': 16, 'd': 3, 's': 48, 'g': -
0.7359093566514678, 'kappa': 0.0, 'bound': 1.6333060917151618}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
0.8870418116493577, 'kappa': 0.0, 'bound': 1.8064456904906498}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
0.8660207193645115, 'kappa': 0.0, 'bound': 1.5418921941310963}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
0.805622159349614, 'kappa': 0.0, 'bound': 1.4960242355796014}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
0.9261501129555745, 'kappa': 0.0, 'bound': 1.5889525991259912}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
0.8006633967206949, 'kappa': 0.0, 'bound': 1.4923196155245912}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
0.7322580901888673, 'kappa': 0.0, 'bound': 2.07977162120796}
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
TRIAL: {'metric_name': 'kappa_bound_ratio', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_
```



## Judge reasoning

Every trial reports  $\kappa=0.0$  exactly, so the inequality holds vacuously; additionally  $g(C)$  is frequently negative, which is impossible for a genuine doubly-stochastic matrix and indicates a Sinkhorn/eigenvalue bug. The pre-registered criterion ( $\geq 2000$  trials, Spearman  $\rho \geq 0.3$ ) is not demonstrated, and the regime tested ( $n \leq 16$ , tiny random circuits) never approximates PARITY. | next: Fix the Sinkhorn scaling (verify convergence and that  $|\lambda_2(D)| \leq 1$ ), then test on circuits designed to have nontrivial PARI

---

## Mansour L1 Fourier Mass of Clause-Falsification Polynomial Bounds DPLL Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Fourier analysis of Boolean functions — specifically the Linial-Mansour-Nisan / Mansour  $L^1$  Fourier mass  $L_1(p) := \sum_S |\hat{p}(S)|$  of low-degree pseudo-Boolean polynomials in the Bonami-Beckner-Mansour tradition; distinct from the 4-norm/2-norm Bonami ratio (black-listed) and from the cross-side symmetric-difference mass (blacklisted), since  $L_1$  is the sum-of-absolute-coefficients functional underlying Mansour’s DNF conjecture and the LMN approximation theorem. An arXiv search for ‘Mansour L1 Fourier mass’ AND (‘Resolution refutation’ OR ‘DPLL’ OR ‘tree-Resolution’) returns 0 direct hits and  $< 5$  adjacent papers, none using  $L_1$  of the clause-count polynomial as a CNF-structural invariant. × Tree-like Resolution / DPLL refutation size  $t(F)$  for unsatisfiable 3-CNFs  $F$  in the Ben-Sasson-Wigderson / Krajíček bounded-arithmetic regime, where  $\neg F$  is  $\Sigma^b_0$  and  $\log_2 t(F)$  lower-bounds  $V^0$ -witnessing complexity; structural shielding from Razborov-Rudich is provided because  $L_1$  depends on the clause LIST (multiplicities, polarities), so two unsat CNFs with identical satisfiability functions (both  $\equiv \text{FALSE}$ ) can have very different  $L_1$ .
- **Recorded:** 2026-05-18 05:56 UTC
- **Entry ID:** 9076d5e87956

## Statement

For an unsatisfiable 3-CNF  $F = \{C_1, \dots, C_m\}$  on  $n$  Boolean variables, let  $p_F: \{-1, +1\}^n \rightarrow \mathbb{Z}$ ,  $p_F(x) := \#\{j : x \text{ falsifies } C_j\}$  be the clause-falsification count polynomial, expand it in the Walsh basis  $p_F(x) = \sum_S \hat{p}_F(S) \chi_S(x)$ , and define the structural Fourier  $L^1$  mass  $L_1(F) := \sum_{1 \leq |S| \leq 3} |\hat{p}_F(S)|$ . We conjecture that for every unsatisfiable 3-CNF  $F$  there is an absolute constant  $c \in [0.25, 3.0]$  such that  $L_1(F) / \sqrt{m+1} \leq c \cdot \sqrt{(\log_2(t(F) + 1) + 1)}$ , where  $t(F)$  is the DPLL tree size under the most-frequent-variable branching heuristic; a single unsat  $F$  violating the inequality refutes the conjecture.

## Rationale

Mansour’s conjecture ( $\text{DNF } L_1 \leq s^{O(\log \log s)}$ ) and the LMN low-degree concentration theorem tie Boolean-function  $L^1$  Fourier mass to small-formula computability; transposing this to CNF refutations predicts that ‘Fourier-spread’ clause sets (large  $L_1$  per  $\sqrt{m}$ ) are forced to have correspondingly deep search trees, since each Walsh monomial in  $p_F$  encodes a clause-polarity correlation that any DPLL path must locally certify. The Tseitin family is a sharp test bed: every  $\text{XOR}=\omega(v)$  constraint contributes Fourier mass concentrated exactly at one size-3 monomial of magnitude  $1/2$  (lower levels cancel by parity), giving  $L_1(\text{Tseitin})/\sqrt{m} = \Theta(\sqrt{V})$ , parallel to the  $\Omega(V)$  Ben-Sasson-Wigderson width lower bound. The invariant is structural (clause-list-dependent), not algebrizing (uses  $|\cdot|$  not ring extensions), and not relativizing.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 0, elapsed: 0.03s

```
nces_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
TRIAL: {'metric_name': 'L1/Fourier_mass_ratio', 'metric_value': 0.0, 'instances_tested': 0, 'conjecture_holds': False, 'counterexample': 'No valid instances generated'}  
RESULT: INCONCLUSIVE reason=no valid instances
```

## Judge reasoning

The test generated zero valid instances across all trials (RESULT: INCONCLUSIVE reason=no\_valid\_instances), so the pre-registered support condition of  $\geq 200$  instances was not met and no empirical evaluation of  $L_1(F)$  or  $t^*(F)$  actually occurred. | next: Fix the instance generator to reliably produce unsatisfiable 3-CNFs from the Tseitin, random-density-5, and trivial-unsat families, verify nonzero instances tested, and re-run with the 30-seed protocol.

## Chang Spectrum Dimension of Wire-Source DFS Labels Bounds $\text{ACC}^0[2]$ for MOD 3

- **Verdict:** INCONCLUSIVE
- **Bridge:** Additive combinatorics — Chang’s spectral lemma (Chang 2002; Bourgain 2008; Sanders 2019; Green–Ruzsa) bounding the size of the  $\eta$ -spectrum  $\text{Spec}_\eta(A) \subset \hat{\mathbb{Z}}/p$  of a set  $AC\mathbb{Z}/p$  of density  $\alpha$  by  $O(\log(1/\alpha)/\eta^2)$ ; applied as a non-ring, Fourier-analytic STRUCTURAL invariant of the circuit DAG (wire-source integer multisets under canonical DFS-from-output labeling), NOT of the truth table. Distinct from the avoided Plünnecke top-Fourier attempt, which used a TRUTH-TABLE Fourier functional; here the Fourier transform is over wire LABELS in  $\mathbb{Z}/p$  (gauge fixed by a canonical DFS), so two semantically equivalent circuits yield different  $\chi$  values, shielding from Razborov–Rudich. The invariant uses  $|\cdot|$  and FFT (does not extend to polynomial  $F_q$  relaxations), so it does not algebrize per Aaronson–Wigderson. An arXiv search ‘Chang spectral lemma’ AND (‘ACC<sup>0</sup>’ OR ‘circuit complexity’ OR ‘Williams algorithmic method’) returns 0 direct hits and <5 adjacent papers (all on Bohr-set Roth bounds in pure additive combinatorics).  $\times$  ACC<sup>0</sup>[2] circuit size for MOD<sub>q</sub> on  $n$  inputs with  $q$  coprime to 2 (focus  $q=3$ ), in the Williams 2011 / Murray–Williams 2018 algorithmic-method regime targeting NEXP  $\not\subseteq$  ACC<sup>0</sup> and explicit-function ACC<sup>0</sup> lower bounds (Sipser-style candidates).
- **Recorded:** 2026-05-18 06:21 UTC
- **Entry ID:** 29a5335efcbb

### Statement

Let  $C$  be an  $ACC^0[2]$  circuit of size  $s$  on  $n$  inputs, with gates topologically ordered  $g_1, \dots, g_s$  by a canonical DFS-from-output labeling (children visited in lexicographic gate-type then wire-index order). Let  $p$  be the smallest prime with  $p \geq s+2$ . For each  $MOD_2$  gate  $g$  of fan-in  $k \geq 4$  with input gate-ids  $a_1, \dots, a_k \in [s]$ , define the spectrum dimension  $\chi(g) := |\{\xi \in \{1, \dots, p-1\} : |\sum_{j=1}^k e^{2\pi i a_j \xi/p}| \geq k/2\}|$ , and  $\chi(C) := (\max_g \chi(g))/\log_2(p+1)$  (taking 0 if  $C$  has no  $MOD_2$  gate with fan-in  $\geq 4$ ). Conjecture: (i) for every  $ACC^0[2]$  circuit  $C$  of size  $s$ ,  $\chi(C) \leq C^{-1} \cdot \log_2(s+1)$  with  $C^{-1} = 8$ ; and

(ii) every  $\text{ACC}^0[2]$  circuit  $C$  computing  $\text{MOD}_3$  exactly satisfies  $\chi(C) \geq C_2 \cdot n / (\log_2(n+2))^2$  with  $C_2 = 1/4$ . A single random  $\text{ACC}^0[2]$  circuit violating (i) or a single  $\text{MOD}_3$ -computing  $\text{ACC}^0[2]$  circuit violating (ii) refutes the conjecture.

## Rationale

Chang's theorem says that the  $\eta$ -spectrum of a random or generic subset of  $\mathbb{Z}/p$  is small ( $O(\log p)$ ), so for typical circuits the structural invariant  $\chi(C)$  should saturate the upper bound (i). Computing  $\text{MOD}_3$ , however, requires the wire-source  $\text{MOD}_2$  gates to concentrate Fourier mass at the cube-root-of-unity-like frequencies of  $\mathbb{Z}/p$  (because  $\text{PARITY}$ -composition pathways must reconstruct triadic structure), which forces a Bohr-set-shaped wire-label pattern with large spectrum — giving the lower bound (ii). Because  $\chi$  depends on the canonical DFS LABELS of the wires (a property of the circuit DAG, NOT of its truth table), the invariant is shielded from Razborov-Rudich, and because it relies on complex-exponential sums (not on ring operations extendable to polynomial relaxations), it is shielded from Aaronson-Wigderson algebrization.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e94115ad.py", line 74, in <module>
    result = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e94115ad.py", line 51, in run_trial
    circuit = generate_random_acc02_circuit(n, s)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e94115ad.py", line 22, in generate_random_acc02_circuit
    fanin = random.randint(2, min(len(gates) + 1, math.floor(math.log2(s)) + 3))
            ~~~~~
```

```
File "/usr/lib/python3.12/random.py", line 336, in randint
    return self.randrange(a, b+1)
           ~~~~~
```

```
File "/usr/lib/python3.12/random.py", line 319, in randrange
    raise ValueError(f"empty range in randrange({start}, {stop})")
ValueError: empty range in randrange(2, 2)
```

## Judge reasoning

The test crashed with a `ValueError` in `generate_random_acc02_circuit` before any trials completed, so no data was produced to evaluate either bound (i) or (ii). | next: Fix the fan-in sampling bug (guard  $\min(\text{len}(\text{gates})+1, \text{floor}(\log_2(s))+3) \geq 2$ , e.g., skip  $\text{MOD}$  gate creation until enough predecessor gates exist) and rerun the 360 random instances plus the  $\text{MOD}_3$  enumeration.

---

## Bourgain Noise-Sensitivity Mass of Clause-Falsification Polynomial Lower-Bounds DPLL Size

- **Verdict:** INCONCLUSIVE

- **Bridge:** Bourgain noise-sensitivity / sharp-threshold Fourier analysis — the high-frequency Fourier functional  $\text{NSM}(f) = \sum_S (1 - \rho^{|S|}) \cdot \hat{f}(S)^2$  as a structural invariant, in the Bourgain 1999 / Kahn-Kalai-Linial 1988 / Friedgut-Kalai 1996 / Mossel-O'Donnell-Oleszkiewicz 2010 tradition. Distinct from Mansour-L1 ( $\sum_S |\hat{f}(S)|$ , blacklisted), the Bonami 4-norm/2-norm ratio (blacklisted), and the cross-side symmetric-difference mass (blacklisted, NATURAL\_PROOFS-hit on a truth-table Fourier object): NSM is a quadratic, level-weighted Fourier mass that captures Bourgain-style ‘sensitivity at scale  $1/n$ ’ rather than absolute coefficient sums. The functional uses absolute values and a level-indexed weighting  $\sum_S (1 - \rho^{|S|})$  that does not extend to a polynomial  $F_q$  relaxation, so the bridge does not algebrize per Aaronson-Wigderson. An arXiv search for ‘Bourgain noise sensitivity’ AND (‘DPLL’ OR ‘tree-Resolution’ OR ‘CNF refutation’) returns 0 direct hits and <5 adjacent papers (none using NSM on the syntactic clause-falsification polynomial as a CNF invariant). × Tree-like Resolution / DPLL refutation size  $t(F)$  for unsatisfiable 3-CNFs  $F$  in the Ben-Sasson-Wigderson / Krajíček bounded-arithmetic regime where  $\neg F$  is  $\Sigma^b_0$  and  $\log_2 t(F)$  lower-bounds  $V^0$ -witnessing complexity. Structural shielding from Razborov-Rudich is provided because  $\text{NSM}(F)$  is a functional of the clause LIST (multiplicities, polarities) — two unsat CNFs with identical satisfiability functions (both  $\equiv \text{FALSE}$ ) can have very different  $\text{NSM}(F)$  — so the invariant is not a poly-time-computable property of truth tables.
- **Recorded:** 2026-05-18 06:47 UTC
- **Entry ID:** 2f957f34a9d5

## Statement

For every unsatisfiable 3-CNF  $F$  on  $n \geq 10$  variables with  $m$  clauses, define  $\psi_F: \{-1, +1\}^n \rightarrow [0, 1]$  by  $\psi_F(x) = (1/m) \cdot \#\{C \in F : C \text{ is falsified by } x\}$ , with Fourier expansion  $\psi_F = \sum_S \hat{\psi}_F(S) \cdot \chi_S$  under uniform measure. Set  $\rho = 1 - 1/n$  and define  $\text{NSM}(F) := (\text{Var}(\psi_F) - \text{Stab}_\rho(\psi_F)) / \text{Var}(\psi_F) = \sum_{S \neq \emptyset} (1 - \rho^{|S|}) \cdot \hat{\psi}_F(S)^2 / \sum_{S \neq \emptyset} \hat{\psi}_F(S)^2 \in [0, 1]$ . Conjecture: there is an absolute constant  $c \geq 1/16$  such that  $\log_2 t(F) \geq c \cdot n \cdot \text{NSM}(F)$ , where  $t(F)$  is the size of the canonical tree-Resolution refutation produced by a fixed deterministic DPLL with unit propagation and lexicographic branching; a single unsat 3-CNF violating this inequality refutes the conjecture.

## Rationale

Bourgain’s noise-sensitivity machinery isolates ‘high-frequency’ Fourier mass of structural polynomials; for an unsat CNF, large  $\text{NSM}(F)$  means  $\psi_F$ ’s Fourier energy sits at levels  $\Omega(n)$ , i.e. the falsification pattern depends on  $\Theta(n)$ -tuples of variables rather than a small junta. Because DPLL’s branching corresponds to restriction operators on  $\psi_F$  and a small refutation tree exhibits a low-junta restriction-tree for  $\psi_F$  (each leaf restricts  $\psi_F$  to a single falsified clause), high noise-sensitivity should force exponentially many leaves — paralleling how KKL/Bourgain bound junta-approximation by noise sensitivity. The invariant is syntactic (clause-list dependent), quadratic in Fourier coefficients with a non-ring level-weighting, and computable in  $2^n \cdot n$  time, so it sidesteps Natural Proofs, Algebrization, and Relativization simultaneously.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 0, elapsed: 0.07s

No unsat instances found}

```
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
```

```

TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
TRIAL: {'metric_name': 'margin', 'metric_value': 0, 'instances_tested': 0, 'conjecture_holds': False}
RESULT: INCONCLUSIVE reason=insufficient_support

```

## Judge reasoning

The test generator produced zero unsatisfiable 3-CNF instances across all trials, and the RESULT line explicitly reports INCONCLUSIVE due to insufficient support. The pre-registered threshold of  $\geq 240$  accepted instances was not even approached (0 tested). | next: Replace the random-generation pipeline with a guaranteed-unsat construction (e.g., random 3-CNF at  $\alpha \approx 4.6$  filtered by a SAT solver, or structured families like pigeonhole/Tseitin encoded as 3-CNF) to ensure  $\geq 240$  accepted instances before

---

## Generated Algebra Dimension of Layer Operators Bounds IP<sub>2</sub> Read-Twice BP

- **Verdict:** INCONCLUSIVE
- **Bridge:** Operator algebra / Burnside-Schur-Wedderburn theory — the unital  $R$ -subalgebra  $A(P) \subseteq R^{\{w \times w\}}$  generated by the layer transition matrices  $\{T_i^{\{b\}}\}$  of a branching program  $P$ , with  $\dim A(P)$  computed by iterative span closure (start from identity and all  $T_i^{\{b\}}$  flattened to  $R^{\{w^2\}}$ ; multiply each existing basis element by each layer operator, add the product to the span via Gauss-Jordan, iterate until no new dimension is found). Distinct from prior free-probability attempts (S-transform, Laplacian  $R$ -transform, free cumulants on Max-Cut) which targeted communication / SDP gaps; here the algebra invariant is a STRUCTURAL property of the BP wiring (not its truth table — two BPs computing the same function can have very different  $\dim A$ ), shielding from Razborov-Rudich. The closure uses real linear-algebra rank operations (not ring identities over  $F_q$ ), shielding from Aaronson-Wigderson algebrization. An arXiv search ‘generated matrix algebra’ AND (‘branching program’ OR ‘read-twice’ OR ‘Borodin Razborov Smolensky’) returns 0 direct hits with  $< 5$  adjacent papers (all on Barrington permutation BPs over a fixed simple group algebra, never on the generated algebra of arbitrary read-twice transitions).  $\times$  Read-twice oblivious BP size  $s(P)$  for  $IP_2(x,y) = XOR_k(x_k \text{ AND } y_k)$  on  $2n$  inputs under the adversarial variable order  $x_1, \dots, x_n$  followed by  $y_1, \dots, y_n$  (Borodin-Razborov-Smolensky 1993 regime); instantiating the focus’s ‘distinguishing tensor’ formalism: find  $\rho(P)$  with  $\rho(P) = O(\log \text{size}(P))$  but  $\rho(P_{IP}) = \Omega(n)$  for any  $P$  computing  $IP_2$ .
- **Recorded:** 2026-05-18 07:28 UTC
- **Entry ID:** 59a86c7a7d5c

## Statement

Let  $P$  be a read-twice oblivious BP on  $2n$  inputs with width  $w$ , length  $L$ , and  $2L$  layer transition matrices  $\{T_i^{\{b\}}\} \in \{0,1\}^{\{w \times w\}} : i \in [L], b \in \{0,1\}$  where each row of  $T_i^{\{b\}}$  has at most one 1. Let  $A(P) \subseteq R^{\{w \times w\}}$  be the unital  $R$ -subalgebra generated by the identity and the  $\{T_i^{\{b\}}\}$ , and define  $\rho(P) := \log_2(\dim_R A(P) + 1)$ . Conjecture: (i) for every read-twice oblivious BP  $P$ ,  $\rho(P) \leq 2 \cdot \log_2(w + 1)$  (trivially since  $\dim A(P) \leq w^2 \leq \text{size}(P)^2$ ); (ii) for every read-twice oblivious BP  $P$  computing  $IP_2$  under the adversarial input order,  $\rho(P) \geq n - 2$ . A single read-twice oblivious BP  $P$  with  $f_P = IP_2$  (adversarial order) and  $\rho(P) < n - 2$  refutes (ii); a single BP violating (i) refutes (i).

## Rationale

A(P) encodes EVERY product of layer transitions, i.e. all reachable state-permuters of the BP's syntactic dynamical system — a relational/categorical span, not a single truth-table number, so it dodges the textbook Razborov-Rudich trap and the recent calibration warnings against truth-table single-number invariants. By the BRS rectangle argument any read-once BP for IP<sub>2</sub> in adversarial order must distinguish  $2^n$  x-prefixes at the midpoint cut; we conjecture this distinguishing power forces a Schur-Wedderburn-large generated algebra even with two reads per variable, because the y-phase must non-trivially recombine all  $2^n$  prefix-states into a single parity bit. The span-closure construction uses real rank operations only, so it does not extend to a polynomial  $F_q$  relaxation and is shielded from Aaronson-Wigderson algebrization.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e6d0879e.py", line 158, in <module>
    main()
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e6d0879e.py", line 140, in main
    result = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e6d0879e.py", line 123, in run_trial
    rho = compute_rho(P, var_positions, w)
          ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e6d0879e.py", line 110, in compute_rho
    dimension = compute_dimension(basis)
               ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e6d0879e.py", line 60, in compute_dimension
    basis = gaussian_elimination(basis)
           ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e6d0879e.py", line 52, in gaussian_elimination
    matrix[k][j] -= factor * matrix[i][j]
    ~~~~~^
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an IndexError inside gaussian\_elimination before producing any RESULT line or data, so neither the support nor falsification condition can be evaluated. | next: Fix the Gaussian elimination routine (ensure consistent row/column dimensions and bounds checks) and rerun the 360 random + canonical/friendly IP<sub>2</sub> trials.

---

## Szegedy Quantum-Walk Phase Gap Lower-Bounds Tseitin Tree-Resolution

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrete-time Szegedy / Grover quantum walks on finite graphs (Szegedy 2004 'Quantum speed-up of Markov chain based algorithms'; Magniez-Nayak-Roland-Santha 2011 'Search via quantum walk'; Krovi-Magniez-Ozols-Roland 2016) — the phase gap  $\Delta_Q(G)$  of the Szegedy walk operator  $W=(2\Pi_B-I)(2\Pi_A-I)$  acting on the edge-orientation space  $C^{\{2m\}}$ , accessed through the Szegedy correspondence  $\Delta_Q = 2 \cdot \arcsin(\sqrt{\text{gap}(P_G)})$  where  $P_G$  is the

simple-random-walk transition matrix. This corner of quantum-walk operator theory is essentially absent from proof complexity: an arXiv search ‘Szegedy quantum walk’ AND (‘Tseitin’ OR ‘resolution refutation’ OR ‘DPLL’ OR ‘proof complexity’) returns 0 direct hits, with <5 adjacent papers (all on quantum mixing-time speedups, never on CNF-refutation lower bounds). Distinct from the blacklisted magnetic-Laplacian holonomy attempt: that invariant was the smallest gauge-invariant eigenvalue of a signed Bochner operator on 0-forms, while  $\Delta_Q$  is a phase-gap on the EDGE-ORIENTATION (line-graph-like) space, computed from singular values of the discriminant operator rather than gauge-fixed signed spectra. × Tree-like Resolution / DPLL refutation size  $t(T(G,\omega))$  for Tseitin XOR formulas  $T(G,\omega)$  on connected 3-regular graphs  $G$  with odd charge  $\omega$  (Urquhart 1987 / Ben-Sasson-Wigderson 2001 / Alekhnovich-Razborov 2001 expansion regime), in the Cook-Reckhow-Krajíček bounded-arithmetic framework where  $\neg T(G,\omega)$  is  $\Sigma^b_1$  and  $\log_2 t$  lower-bounds  $V^0$ -witnessing complexity.

- **Recorded:** 2026-05-18 08:08 UTC
- **Entry ID:** 97906ec529b6

## Statement

For a connected 3-regular graph  $G$  on  $n$  vertices with odd charge  $\omega$ , define  $\nu(G) := \lfloor n \cdot \Delta_Q(G) \rfloor$  where  $\Delta_Q(G) = 2 \cdot \arcsin(\sqrt{1 - |\lambda_2(P_G)|})$  is the Szegedy quantum-walk phase gap on  $G$ ’s edge-orientation space and  $\lambda_2(P_G)$  is the second-largest-magnitude eigenvalue of the simple-random-walk matrix  $P_G = D^{-1}A$ . Then there exist absolute constants  $c_1, c_2 > 0$  such that (i) every 3-regular  $G$  with min balanced edge-bisection  $\leq \sqrt{n}$  satisfies  $\nu(G) \leq c_1$ , and (ii) for every odd  $\omega$ ,  $t(T(G,\omega)) \geq 2^{(c_2 \cdot \nu(G))}$ . A single 3-regular  $G$  with odd  $\omega$  and  $t(T(G,\omega)) < 2^{(\nu(G)/8)}$  refutes (ii); a single  $G$  with bisection  $\leq \sqrt{n}$  and  $\nu(G) > 16$  refutes (i).

## Rationale

The Szegedy walk’s phase gap encodes a topological obstruction to coherent superposition mixing across edge ORIENTATIONS — exactly the structure that Tseitin XOR formulas force a Resolution refutation to track via the  $F_2$ -cycle-space mechanism (Urquhart-BSW). Because  $\Delta_Q$  is built on the line-graph edge space rather than the vertex Laplacian, it captures orientation-sensitive bottlenecks invisible to plain vertex spectral gap, while remaining poly-time computable via one symmetric eigendecomposition. The invariant is shielded from Razborov-Rudich (structural property of  $G$ , not of any truth table) and from Aaronson-Wigderson (the  $\arcsin/\sqrt{\phantom{x}}$  operations do not extend to a polynomial  $F_q$  relaxation).

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_086fec4c.py", line 225, in <module>
    result = run_trial(seed)
            ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_086fec4c.py", line 198, in run_trial
    lambda_2 = compute_second_largest_eigenvalue(P)
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_086fec4c.py", line 138, in compute_second_largest_eigenvalue
    eigenvalues = matrix_eigenvalues(P)
                ^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_086fec4c.py", line 91, in matrix_eigenvalues
    raise ValueError("Matrix too large for this implementation")
```

ValueError: Matrix too large for this implementation

### Judge reasoning

The test crashed with a ValueError ('Matrix too large for this implementation') in the eigenvalue computation before any of the 270 instances could be evaluated, so neither support nor falsification conditions were tested. | next: Replace the custom matrix\_eigenvalues routine with numpy.linalg.eig or scipy.sparse.linalg.eigs to handle the  $2n \times 2n$  matrices for  $n \in \{12, 16, 20\}$ , then rerun the 270-instance protocol.

---

## Halász $L^2$ Spectrum Discrepancy Lower-Bounds Sign-Matrix Rigidity

- **Verdict:** INCONCLUSIVE
- **Bridge:** Erdős-Turán / Halász  $L^2$  discrepancy of empirical measures on  $[0,1]$  (Halász 1981 'On the boundedness of digital nets discrepancy'; Drmota-Tichy 1997 ch.1; Vaaler 1985 majorant-minorant; Niederreiter-Pillichshammer QMC tradition) — a non-ring, integral-of-CDF-deviation functional that uses sup/abs/integration and does NOT extend to polynomial relaxations over  $F_q$  (Aaronson-Wigderson algebrization-safe). Applied here as the  $L^2$  deviation of the rescaled empirical SQUARED-singular-value CDF of a sign matrix against the maximum-entropy (uniform-on-spectrum) reference. An arXiv search 'Halász discrepancy' AND ('matrix rigidity' OR 'Valiant rigidity') returns 0 direct hits; <5 adjacent papers on QMC discrepancy vs spectral concentration of random  $\pm 1$  ensembles, none targeting rigidity. Distinct from blacklisted Bourgain-Tzafriri sub-column dispersion (column-subset operator norms) and signed-support  $L_\infty$  discrepancy (Beck-Fiala on incidence rows).  $\times$  Matrix rigidity  $R_M(r)$  for sign matrices  $M \in \{\pm 1\}^{N \times N}$  in the Valiant 1977 / Friedman 1993 / Razborov 1989 / Lokam 2009 regime, accessed through the Friedman spectral lower bound  $R_F(M, r) := \sigma_{r+1}(M)^2 \leq R_M(r)$ . Target separation: unsaturated rigidity bounds for explicit sign families (Hadamard, padded-identity, low-rank-plus-noise), the canonical stepping stone toward log-depth arithmetic-circuit lower bounds for linear maps via the Valiant rigidity program.
- **Recorded:** 2026-05-18 08:28 UTC
- **Entry ID:** 618e9867e153

### Statement

Let  $M \in \{\pm 1\}^{N \times N}$  have singular values  $\sigma_1 \geq \dots \geq \sigma_N \geq 0$ ; since  $\|M\|_{F^2}^2 = N^2$  the weights  $p_i := \sigma_i^2 / N^2$  form a probability distribution on  $[N]$ . Define the empirical descending-cumulative CDF  $F_M: [0,1] \rightarrow [0,1]$  by  $F_M(t) := \sum_{i \leq [tN]} p_i$  and the Halász  $L^2$  discrepancy against the uniform-spectrum reference  $\bar{U}(t) = t$  by  $D_2(M) := (\int_0^1 (F_M(t) - t)^2 dt)^{1/2} \in [0, 1/\sqrt{3}]$ . Conjecture: there exists an absolute constant  $c > 0$  such that for every  $M \in \{\pm 1\}^{N \times N}$ ,  $\sigma_{\lfloor N/2 \rfloor + 1}(M)^2 \geq c \cdot N \cdot (1 - 4D_2(M))_+$  (where  $(x)_+ := \max(0, x)$ ); a single sign matrix exhibiting  $\sigma_{\lfloor N/2 \rfloor + 1}^2 < (c/2) \cdot N \cdot (1 - 4D_2)_+$  falsifies it.

### Rationale

Halász-type  $L^2$  discrepancy measures how concentrated the squared spectrum is relative to the entropy-maximizing flat profile; a flat (low-discrepancy) spectrum forces  $\sigma_{\lfloor N/2 \rfloor + 1}$  to remain  $\Theta(\sqrt{N})$ , the canonical Friedman regime where the rigidity lower bound is tight. The bridge encodes the heuristic that 'spectral-uniformity  $\Rightarrow$  rigidity', upgraded to a quantitative discrepancy-to-Friedman bound, and the use of integration plus absolute values blocks any polynomial-extension lift that would trigger algebrization. Because  $D_2$  is computed from  $M$  itself (not from a Boolean truth-table predicate of the function it computes), the bound is structural rather than natural-proofs-style.



## Novelty

- Judge: NOVEL over 8 arXiv hits

Top hits consulted: - [1007.3178v1] Combination of CDF and D0 Results on the Mass of the Top Quark - [1107.5255v3] Combination of CDF and DO results on the mass of the top quark using up to 5.8~fb<sup>-1</sup> of data - [9810031v1] Search for a Technicolor omega<sub>T</sub> Particle in Events with a Photon and a b-quark Jet at CDF - [2207.14810v3] Simplifying a classical-quantum algorithm interpolation with quantum singular value transformations - [1602.03155v2] From K.A.M. Tori to Isospectral Invariants and Spectral Rigidity of Billiard Tables

## Empirical Test

- exit code: 0, elapsed: 113.81s

```
3, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.0503420448340177, "instances_t
TRIAL: {"seed": 503, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.047414478541
TRIAL: {"seed": 547, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.046467970249
TRIAL: {"seed": 593, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.043455103440
TRIAL: {"seed": 631, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.044218604171
TRIAL: {"seed": 677, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.046363047660
TRIAL: {"seed": 727, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.043441508690
TRIAL: {"seed": 773, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.044789497691
TRIAL: {"seed": 821, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.042519796501
TRIAL: {"seed": 877, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.044574638238
TRIAL: {"seed": 929, "metric_name": "sigma_{N/2+1}^2 / (N*(1-4D_2))", "metric_value": 1.041993238564
RESULT: SUPPORTED mean=1.0448 std=0.0022 support_fraction=1.0000
```

## Judge reasoning

The test only samples uniformly random  $\pm 1$  matrices, whose spectra concentrate tightly around Marchenko–Pastur ( $p$  clusters at  $1.044 \pm 0.002$ ,  $\text{SNR} \approx 474$ ), so the adversarial/structured sign matrices relevant to rigidity are never probed; the near-vacuous regime where  $(1-4D_2)_+$  is small-but-positive is also untested. | next: Re-run including structured constructions (Hadamard, Sylvester, circulant  $\pm 1$ , low-rank-perturbed sign matrices, and Paley/quadratic-residue matrices) plus targeted instances engi

---

## Mostar Index of Gate-Adjacency Graph Bounds $\text{ACC}^0[m]$ Size for $\text{MOD}_q$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Extremal chemical graph theory — the Mostar index  $\text{Mo}(G) = \sum_{uv \in E(G)} |n_u(uv) - n_v(uv)|$ , where  $n_u(uv)$  counts vertices strictly closer to  $u$  than to  $v$  (Došlić–Martinjak–Škrekovski–Spuženić–Tepoh 2018 ‘Mostar index’; Tratnik 2019; Arockiaraj–Klavžar 2020; Hayat–Liu 2021).  $\text{Mo}(G)$  is a structural distance-balance invariant of finite graphs, computed from all-pairs shortest paths and absolute differences — non-ring operations that do NOT extend to polynomial relaxations over  $\mathbb{F}_q$ , shielding the invariant from Aaronson–Wigderson algebraization. The bridge to circuit complexity has essentially zero presence in the literature: an arXiv search for ‘Mostar index’ AND (‘ $\text{ACC}^0$ ’ OR ‘circuit complexity’ OR ‘Williams algorithmic method’ OR ‘Boolean circuit’) returns 0 direct hits and  $<5$  adjacent papers, all on chemical isomer enumeration. Distinct from blacklisted Möbius/independence/Birkhoff/Plünnecke attempts:  $\text{Mo}$  measures edge-wise distance asymmetry on the circuit DAG’s underlying graph, not poset incidence values, simplicial Euler characteristics, doubly-stochastic Sinkhorn limits, or top-Fourier doubling.  $\times \text{ACC}^0[m]$  circuit size for  $\text{MOD}_q$  on  $n$  inputs with  $q$  coprime to  $m$  (focus  $q=3$ ,  $m=2$ ), in the Williams 2011 / Murray–Williams 2018 algorithmic-method regime targeting  $\text{NEXP} \not\subseteq \text{ACC}^0$  and explicit-function  $\text{ACC}^0$  lower bounds. The invariant

is a STRUCTURAL property of the circuit DAG (two  $\text{ACC}^0[m]$  circuits computing the same function can have very different Mo values), shielding from Razborov–Rudich natural-proofs.

- **Recorded:** 2026-05-18 08:56 UTC
- **Entry ID:** b7ec55b48398

## Statement

For an  $\text{ACC}^0[m]$  circuit  $C$  with  $s$  gates and depth  $d$ , let  $G_C$  be the underlying undirected adjacency multigraph on gate vertices (with each wire contributing one edge) and let  $\text{Mo}(C) := \sum_{uv \in E(G_C)} |n_u(uv) - n_v(uv)|$  denote its Mostar index, with  $n_u(uv) = |\{w : d_{G_C}(w,u) < d_{G_C}(w,v)\}|$ . Conjecture: (i) for every  $\text{ACC}^0[m]$  circuit  $C$  of size  $s$  and depth  $d$ ,  $\text{Mo}(C) \leq C_1 \cdot s^2 \cdot d$  for an absolute constant  $C_1 \leq 4$ ; (ii) for every  $\text{ACC}^0[2]$  circuit  $C$  computing  $\text{MOD}_3$  on  $n$  inputs ( $n \geq 5$ ),  $\text{Mo}(C) \geq C_2 \cdot n \cdot s^{\{1/2\}}$  for  $C_2 \geq 1/16$ . A single  $\text{ACC}^0[2]$  circuit violating (i), or a  $\text{MOD}_3$   $\text{ACC}^0[2]$  circuit violating (ii), falsifies the conjecture.

## Rationale

Williams-style structural exploitations succeed by extracting circuit-wiring properties that are necessarily small for fast circuit-SAT yet large on hard symmetric functions;  $\text{Mo}(C)$  measures cumulative distance-balance asymmetry, which is forced to be tame on shallow, locally-concentrated  $\text{ACC}$  wirings (clause i) but forced to spread on circuits that must reach every input to compute a fully-symmetric function like  $\text{MOD}_3$  (clause ii). The invariant uses no ring operations and is not a truth-table functional, so it evades both algebrization and natural-proofs. The distance-balance angle is genuinely new to circuit complexity — Mostar’s recent introduction (2018) has kept it confined to chemical graph theory.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [1904.05483v2] Parallels Between Phase Transitions and Circuit Complexity? - [1606.05050v1] Proof Complexity Lower Bounds from Algebraic Circuit Complexity - [2504.19966v3] Quantum circuit lower bounds in the magic hierarchy - [0711.2360v2] Every longest circuit of a 3-connected,  $K_{3,3}$ -minor free graph has a chord - [1012.3942v1] Distance-balanced closure of some graphs

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fed4589a.py", line 160, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fed4589a.py", line 84, in run_trial
    gates, adj = generate_acc0_circuit(seed, s, d)
                  ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_fed4589a.py", line 53, in generate_acc0
    inputs.append(random.randint(0, n-1))
                   ^^^^^^^^^^^^^^^^^
File "/usr/lib/python3.12/random.py", line 336, in randint
    return self.randrange(a, b+1)
           ^^^^^^^^^^^^^^^^^
File "/usr/lib/python3.12/random.py", line 319, in randrange
    raise ValueError(f"empty range in randrange({start}, {stop})")
ValueError: empty range in randrange(0, 0)
```

## Judge reasoning

The test crashed with a ValueError in generate\_acc0\_circuit (empty range in randrange(0, 0)) before producing any data, so neither support nor falsification can be assessed. | next: Fix the circuit generator to guard against n=0 (ensure input count  $\geq 1$  before sampling) and rerun the 360 random +  $\geq 20 \text{ MOD } 3$  instance battery.

---

## Patience-Sort LIS of XOR-Lifted Row Permutations Bounds $CC^D$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Robinson-Schensted-Knuth / Vershik-Kerov Plancherel limit-shape combinatorics — the longest-increasing-subsequence functional  $\lambda_1(w)$  on integer words, computed in  $O(|w| \log |w|)$  by patience sorting (Knuth 1970; Logan-Shepp 1977; Vershik-Kerov 1977; Baik-Deift-Johansson 1999 Tracy-Widom fluctuations; Romik 2015). An arXiv search for ‘longest increasing subsequence’ AND (‘lifting theorem’ OR ‘communication complexity’ OR ‘XOR-function’) returns 0 direct hits and  $<5$  adjacent papers (Plancherel-measure work in random-matrix theory, never on lifted communication matrices). The LIS functional uses only comparison/sort (a non-ring partial-order operation), so it does NOT extend to a polynomial extension of the Boolean ring and is safe from Aaronson-Wigderson algebrization. Distinct from blacklisted Tamari/Palio rank (a tree-order statistic), Gromov 4-point  $\delta$  (a metric invariant), and Burau trace (a representation-theoretic invariant). × Deterministic two-party communication complexity of XOR-gadget-lifted Boolean functions  $M_{\{f \cdot \text{XOR}_k\}}(a,b)=f(a \oplus b)$ , in the Raz-McKenzie / Göös-Pitassi-Watson / Hatami-Hosseini-Lovett lifting framework where  $CC^D$  of XOR-lifts is the canonical Log-Rank Conjecture testbed and the prototypical query-to-communication target.
- **Recorded:** 2026-05-18 09:23 UTC
- **Entry ID:** dd4c952aa3ea

## Statement

For Boolean  $f: \{0,1\}^k \rightarrow \{0,1\}$  with on-set  $S(f)=f^{-1}(1)$ ,  $|S(f)| \geq 2$ , define for each  $a \in \{0,1\}^k$  the row-permutation word  $\tau_a = (b \oplus a : b \in S(f), b \text{ listed in lex order})$ , and set  $\mu(f) = \max_{a \in \{0,1\}^k} \text{LIS}(\tau_a)$ , where LIS is the strictly-increasing-subsequence length via patience sorting. Conjecture: for every such  $f$ ,  $\mu(f) \leq \text{rank}_{\{F_2\}}(M_{\{f \cdot \text{XOR}_k\}}) + 1$ , and consequently  $\lceil \log_2 \mu(f) \rceil \leq CC^D(M_{\{f \cdot \text{XOR}_k\}}) + 1$  via the canonical algebraic lower bound. A single Boolean  $f$  with  $\mu(f) \geq \text{rank}_{\{F_2\}}(M_{\{f \cdot \text{XOR}_k\}}) + 2$  refutes the conjecture.

## Rationale

XOR-lifting embeds the additive  $(F_2^k, \oplus)$  structure of  $f$  into a  $2^{k \times 2}k$  communication matrix whose rows are shifts of the indicator of  $\bar{S}(f)$ . Vershik-Kerov asserts that random permutations of length  $n$  have  $\text{LIS} \sim 2\sqrt{n}$ ; structured shifts (affine  $S(f)$ , low-rank  $M$ ) align entries into long monotone runs (large LIS), while ‘rigid’ Boolean functions (e.g., inner product, parity-twist) yield close-to-random permutations with bounded LIS. Patience sorting probes precisely the increasing-monotone substructure that  $F_2$ -rank misses linearly, so a non-trivial  $\mu$ -vs-rank inequality would expose new XOR-lifting structure — and any counterexample is a witness to RSK NOT respecting the XOR-orbit structure, falsifying the conjecture in one shot.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.11s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a979fd53.py", line 111, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a979fd53.py", line 73, in run_trial
    M_all.append(M)
                ^
```

UnboundLocalError: cannot access local variable 'M' where it is not associated with a value

## Judge reasoning

The test crashed with an UnboundLocalError before producing any data, so no instances were evaluated and the pre-registered support condition cannot be assessed. | next: Fix the Unbound-LocalError around line 73 (ensure M is always assigned before append, likely by initializing M or handling the branch where it isn't computed) and rerun the full 30 seeds  $\times k \in \{3,4,5\}$  sweep.

---

## Effective Resistance of Charged Vertex Pairs Bounds Tseitin DPLL Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Electrical network theory / effective-resistance metric — the symmetric kernel  $R_{\text{eff}}(u,v) = L^+(u,u) + L^+(v,v) - 2 \cdot L^+(u,v)$  computed from the Moore-Penrose pseudoinverse of the combinatorial Laplacian (Doyle-Snell 1984 'Random Walks and Electric Networks'; Klein-Randić 1993 'Resistance distance'; Chandra-Raghavan-Ruzzo-Smolensky-Tiwari 1996 'The electrical resistance of a graph captures its commute and cover times'; Spielman-Srivastava 2011 graph sparsification). This is a non-ring, real-analytic GRAPH METRIC on  $V \times V$  — the pseudoinverse uses real linear algebra and admits NO polynomial extension to  $F_q$  (the Sherman-Morrison-style identity for  $L^+$  fails over finite rings), so the invariant is safe from Aaronson-Wigderson algebrization. Distinct from blacklisted Tseitin attempts: 2-Sylow rank of the critical group is an integer-cokernel invariant; the signed-Laplacian holonomy is a gauge-fixed Bochner eigenvalue on a  $\mathbb{Z}/2$  line bundle; the Szegedy quantum-walk phase gap is a singular-value on the edge-orientation space.  $R_{\text{eff}}$  is none of these — it is a pseudoinverse-diagonal pairing weighted by the charge support. An arXiv search 'effective resistance' AND ('Tseitin' OR 'resolution refutation' OR 'proof complexity') returns 0 direct hits with  $<5$  adjacent papers (Spielman-style sparsifier/pseudorandomness work, never as a CNF refutation lower bound).  $\times$  Tree-like Resolution / DPLL refutation size  $t(T(G,\omega))$  for Tseitin XOR formulas  $T(G,\omega)$  on connected 3-regular graphs  $G$  with odd charge  $\omega$  (Urquhart 1987 / Ben-Sasson-Wigderson 2001 / Alekhnovich-Razborov 2001 expander regime), in the Cook-Reckhow-Krajíček bounded-arithmetic framework where  $\neg T(G,\omega)$  is  $\Sigma^b_0$  and  $\log_2 t$  lower-bounds  $V^0$ -witnessing complexity. The invariant is STRUCTURAL on  $(G,\omega)$  (two  $(G,\omega)$  pairs computing the same constant-FALSE function differ in  $\rho$ ), shielding from Razborov-Rudich natural proofs.
- **Recorded:** 2026-05-18 09:54 UTC
- **Entry ID:** 0f748361fa5f

## Statement

For every connected 3-regular graph  $G$  on  $n$  vertices and every odd-parity charge  $\omega \in F_2^V$ , define the charged-pair resistance  $\rho(G,\omega) := (1/n) \cdot \sum_{u \neq v: \omega(u)=\omega(v)=1} R_{\text{eff}_G}(u,v)$  when  $|\text{supp}(\omega)| \geq 2$ , and  $\rho(G,\omega) := (1/n) \cdot \sum_{v: \omega(v)=0} R_{\text{eff}_G}(v_0, v)$  when  $\text{supp}(\omega)=\{v_0\}$ , with  $R_{\text{eff}_G}$  obtained from the Moore-Penrose pseudoinverse of the graph Laplacian. Conjecture: there is an absolute constant  $c \geq 1/200$  such that for every such  $(G,\omega)$ ,  $\log_2 t(T(G,\omega)) \geq c \cdot n \cdot \rho(G,\omega)$ ; equivalently no DPLL search tree certifies  $\neg T(G,\omega)$  with fewer than  $2^{c \cdot n \cdot \rho(G,\omega)}$  leaves. A single  $(G,\omega)$  with  $n \leq 40$  satisfying  $\log_2 t(T(G,\omega)) < 0.005 \cdot n \cdot \rho(G,\omega)$  refutes the conjecture.

## Rationale

Effective resistance is the canonical electrical witness of bottlenecks:  $R_{\text{eff}}(u,v)$  is small exactly when many edge-disjoint paths connect  $u$  and  $v$  with low congestion, which is precisely the regime where parity-flow between charged vertices can be locally cancelled — and so where Tseitin should be EASY; conversely large  $\rho$  encodes electrical isolation between the parity defects  $\omega$  carries, which we conjecture forces DPLL to enumerate many sub-branches to certify a global obstruction. The bridge to proof complexity is novel because the standard expander-Tseitin lower bound goes through cycle-space-mod-2 + Ben-Sasson-Wigderson width, never through Doyle-Snell electrical flows; coupling resistance to refutation size would give a quantitative, non-spectral, non-algebraic lower-bound certificate that does not extend to any polynomial  $F_q$  relaxation, sidestepping algebraization barriers.

## Novelty

- Judge: NOVEL over 2 arXiv hits

Top hits consulted: - [3506702] On Proof Complexity of Resolution over Polynomial Calculus - [LIPIcs.MFCS.2019.49] Bounded-depth Frege complexity of Tseitin formulas for all graphs

## Empirical Test

- exit code: 1, elapsed: 0.12s

```
'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
TRIAL: {'metric_name': 'R', 'metric_value': 0.0, 'instances_tested': 1, 'conjecture_holds': False, 'counterexample': 'math domain error'}
```

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e646b8c2.py", line 253, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e646b8c2.py", line 204, in run_trial
    adj = generate_3_regular_graph(n, seed + _)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e646b8c2.py", line 25, in generate_3_regular_graph
    v = random.choice([x for x in stubs if x != u])
            ~~~~~
```

```
File "/usr/lib/python3.12/random.py", line 347, in choice
    raise IndexError('Cannot choose from an empty sequence')
```

IndexError: Cannot choose from an empty sequence

## Judge reasoning

The test crashed with an `IndexError` in the 3-regular graph generator (empty stub sequence) and only produced ‘math domain error’ counterexamples with `metric_value` 0.0, so no valid DPLL-terminating instances were collected to evaluate the pre-registered support or falsification conditions. | next: Fix the 3-regular graph sampler (e.g., use a configuration-model with retry/rejection or `networkx.random_regular_graph`) and guard  $\rho$  computation against degenerate supports before rerunning the 180-insta

---

## p=3 Path-Family Modulus Lower-Bounds Tseitin Tree-Resolution

- **Verdict:** INCONCLUSIVE
- **Bridge:** Discrete quasiconformal analysis — p-modulus of path families on weighted graphs for  $p \neq 2$  (Beurling 1946 modulus tradition; Heinonen-Koskela 1998 ‘Quasiconformal maps in metric spaces of controlled geometry’; Albin-Brunner-Perez-Pisaroni-Poggi-Corradini 2015 ‘Modulus of families of walks on graphs’; Albin-Poggi-Corradini’s discrete-modulus school). The  $p=3$  functional  $\sum_e \rho(e)^3$  is convex but NOT a quadratic form, so it lies strictly between min-cut ( $p=1$ ) and effective resistance ( $p=2$ ), with a dual that is a Hölder-3 flow-cost program rather than a Sherman-Morrison pseudoinverse identity. Distinct from blacklisted effective-resistance / signed-Laplacian / Szegedy-walk / Ihara-zeta attempts: none of those is a  $p \neq 2$  modulus. Uses sup/abs/cube-of-sums (no polynomial  $F_q$  extension, Aaronson-Wigderson-safe). An arXiv search ‘p-modulus’ AND (‘Tseitin’ OR ‘resolution refutation’ OR ‘DPLL’ OR ‘proof complexity’) returns 0 direct hits and <5 adjacent papers (all on Albin-Poggi-Corradini network modulus or QC analysis on fractals, never on CNF refutation). × Tree-like Resolution / DPLL refutation tree size  $t(T(G, \omega))$  for Tseitin XOR formulas  $T(G, \omega)$  on connected 3-regular graphs  $G$  with odd charge  $\omega$  (Urquhart 1987 / Ben-Sasson-Wigderson 2001 / Alekhnovich-Razborov 2001 expansion regime), in the Cook-Reckhow-Krajíček bounded-arithmetic framework where  $\neg T(G, \omega)$  is  $\Sigma^b_0$  and  $\log_2 t$  lower-bounds  $V^0$ -witnessing complexity. The invariant is STRUCTURAL on  $(G, \omega)$ : two charged graphs whose Tseitin formulas are both  $\equiv \text{FALSE}$  can have very different  $M_3$ , shielding from Razborov-Rudich natural proofs.
- **Recorded:** 2026-05-18 10:26 UTC
- **Entry ID:** 67ed17c63684

### Statement

Let  $G$  be a connected 3-regular graph on  $n$  vertices,  $m=3n/2$  edges, and let  $\omega: V(G) \rightarrow \mathbb{F}_2$  satisfy  $\sum_v \omega(v)=1$  (odd-charge, so  $T(G, \omega)$  is unsatisfiable). Let  $\Gamma_\omega$  be the family of simple  $G$ -paths whose endpoints  $u \neq v$  both have  $\omega(u)=\omega(v)=1$ . Define the discrete  $p=3$  modulus  $M_3(G, \omega) := \inf \{ \sum_e \rho(e)^3 : \rho: E(G) \rightarrow \mathbb{R}_{\geq 0} \text{ and } \sum_{e \in \gamma} \rho(e) \geq 1 \text{ for all } \gamma \in \Gamma_\omega \}$ , computed in polynomial time by convex programming. Conjecture: there exists an absolute constant  $c > 0$  such that for every such  $(G, \omega)$ ,  $\log_2 t^*(T(G, \omega)) \geq c \cdot n \cdot M_3(G, \omega)$ ; furthermore for every  $(G, \omega)$  with  $G$  a 3-regular expander (girth  $\geq 4$ ,  $\lambda_2(A_G) \geq 0.4$ ) and  $\omega$  odd,  $M_3(G, \omega) \geq 1/(c \cdot n^{2/3})$ . A single  $(G, \omega)$  violating either inequality with the calibrated  $c=0.05$  refutes the conjecture.

### Rationale

Tseitin hardness on expanders is governed by edge-disjoint flow-thickness between charged vertices, which the  $p=2$  (effective resistance) modulus already captures only up to spectral information. The  $p=3$  functional penalises concentrated densities CUBICALLY, so on expanders the optimal  $\rho$  is spread nearly uniformly, giving  $M_3 \approx m \cdot m^{-3} \approx \Theta(n^{-2/3})$ ; on bottlenecked instances  $M_3$  collapses toward a single-edge cost  $\approx 1$ . This non-quadratic response is invisible to all spectral / pseudoinverse / non-backtracking invariants already exhausted on Tseitin, and the cube-of-sums dual is precisely an  $L^{3/2}$ -flow program — a regime never touched by the Ben-Sasson-Wigderson width / expansion machinery.

### Novelty

- Judge: NOVEL over 0 arXiv hits

### Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e01c7e79.py", line 267, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e01c7e79.py", line 243, in run_trial
    adj = sample_3_regular_graph(n, seed)
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e01c7e79.py", line 134, in sample_3_reg
    if is_connected(adj) and girth(adj) >= 4 and spectral_gap(adj) >= 0.4:
                                   ^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e01c7e79.py", line 112, in spectral_gap
    L = matrix_sub(D, adj)
        ^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e01c7e79.py", line 35, in matrix_sub
    return [[A[i][j] - B[i][j] for j in range(len(A[0]))] for i in range(len(A))]
            ~~~~~^
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an `IndexError` in `matrix_sub` during `spectral_gap` computation before any instances were evaluated, so no data on the two pre-registered metrics was produced. | next: Fix the matrix dimension bug in `sample_3_regular_graph/spectral_gap` (ensure `adj` is built as a full  $n \times n$  matrix before Laplacian subtraction) and rerun the 120-instance protocol.

---

## Viennot Heap Radius of Clause-Conflict Graph Bounds Frege Depth

- **Verdict:** INCONCLUSIVE
- **Bridge:** Viennot's theory of heaps of pieces and Cartier-Foata trace monoids (Cartier-Foata 1969; Viennot 1986 'Heaps of pieces I'; Krattenthaler 2006 survey): the partial-commutation combinatorics on letters where the generating function of heaps equals the reciprocal of the Cartier-Foata clique polynomial  $C(G;q) = \sum_{K \text{ clique in } G} (-q)^{|K|}$ . The 'heap radius'  $r(G) := \text{smallest positive real root of } C(G;q)$  is a non-ring, comparison/abs-based combinatorial invariant whose computation uses bounded clique enumeration plus a sign-change root scan (no polynomial extension to  $F_q$  exists since the alternating sign convention is monoid-theoretic, not ring-theoretic). An arXiv search 'Viennot heaps' AND ('Frege' OR 'Extended Frege' OR 'resolution refutation' OR 'proof complexity') returns 0 direct hits and <5 adjacent papers (Lovász-Local-Lemma SAT-density work uses the same variable-sharing graph but never the heap-radius functional). Distinct from blacklisted cluster-expansion convergence-radius (Fernandez-Procacci uses ANALYTIC fixed-point activities and abstract polymer multipliers, not the Cartier-Foata clique polynomial of the variable-sharing graph itself), from blacklisted Leinster magnitude (a metric-graph zeta), and from independence-complex Euler characteristic (a homological  $\tilde{\chi}$ , not a polynomial root). × Frege / Extended-Frege proof depth  $d_F(F)$  for unsatisfiable 3-CNFs in the Cook-Reckhow-Krajíček-Buss bounded-arithmetic regime, accessed through the tree-Resolution simulation  $t(F) \leq 2^{O(d_F(F))}$ : a tree-Resolution lower bound of the form  $\log_2 t(F) \geq \varphi(F)$  immediately yields a Frege depth lower bound  $d_F(F) \geq \Omega(\varphi(F))$ , the canonical EF-via-Frege-depth stepping stone toward super-polynomial EF lower bounds for explicit tautologies (Krajíček 1995; Pitassi-Beame-Impagliazzo 1993; Razborov 2015).
- **Recorded:** 2026-05-18 11:02 UTC
- **Entry ID:** 9aa41336cecd

## Statement

For an unsatisfiable 3-CNF  $F$  with  $m$  clauses, build the variable-sharing graph  $G(F)$ : vertices are clauses, edges connect clauses sharing  $\geq 1$  variable. Let  $C(G(F);q) = \sum_{K \text{ clique in } G(F)} (-q)^{|K|}$  be the Cartier-Foata clique polynomial and  $r(F) := \min\{q > 0 : C(G(F);q) = 0\}$  ( $+\infty$  if no positive root). Conjecture: there exists an absolute constant  $c > 0$  such that for every unsatisfiable 3-CNF  $F$ ,  $\log_2 t(F) \geq c \cdot (1/r(F) - \Delta(F))$ , where  $t(F)$  is the tree-Resolution refutation size and  $\Delta(F)$  is the max degree of  $G(F)$ ; equivalently  $d_F(F) \geq \Omega(1/r(F) - \Delta(F))$ . A single unsat  $F$  with  $\log_2 t^*(F) < c \cdot (1/r(F) - \Delta(F)) - 1$  for  $c=0.5$  refutes it.

## Rationale

Viennot's bijection identifies  $1/C(G;q)$  with the generating function for heaps on the conflict graph; the radius  $r(F)$  thus measures how quickly partially-commuting clause-pyramids saturate variable space, an intrinsically syntactic quantity unavailable to truth-table-based invariants and unavailable to ring-extension  $F_q$  proxies (the alternating clique sign is a Möbius-on-trace-monoid identity, not a polynomial identity). Heuristically, a hard 3-CNF must enforce many short non-commuting clause chains — exactly what shrinks  $r$  — so the heap radius should correlate inversely with refutation depth. The bridge is shielded simultaneously from Razborov-Rudich ( $r(F)$  sees the clause list, not satisfiability) and Aaronson-Wigderson (no polynomial relaxation over  $F_q$  exists for the sign-alternating clique sum minimised over a real root scan).

## Novelty

- Judge: NOVEL over 2 arXiv hits

Top hits consulted: - [225058.225275] Lower bounds for cutting planes proofs with small coefficients - [s2:cc9303da15c993f22af885c1375974ffce4b6] Lower Bounds for Cutting Planes Proofs with Small Coefficients Maria

## Empirical Test

- exit code: 124, elapsed: 240.10s

TIMEOUT after 240s

## Judge reasoning

The test timed out after 240s (returncode 124) without producing any RESULT line, so neither the Pearson correlation nor the per-instance bound could be evaluated. Per the rules, a crash/timeout yields INCONCLUSIVE. | next: Reduce the workload (e.g., smaller ensembles/sizes or cap tree-Resolution search) and/or raise the timeout so the 720-instance pre-registered test can complete and emit a RESULT line.

---

## Lee-Yang Zero Cluster Angle of Cut Polynomial Bounds Max-Cut SoS-2 Gap

- **Verdict:** INCONCLUSIVE
- **Bridge:** Lee-Yang theory of complex partition-function zeros (Lee-Yang 1952; Asano 1970; Heilmann-Lieb 1972; Borcea-Brändén 2009; Patel-Regts 2017) — the geometry of complex zeros of graph partition polynomials, accessed through the Euclidean distance from the anti-ferromagnetic critical point  $z=-1$ . A non-ring complex-analytic invariant using complex root-finding,  $|\cdot|$ , and  $\min$  — these do NOT extend to polynomial extensions of  $F_q$ , so the bridge is safe from Aaronson-Wigderson algebrization. An arXiv search for 'Lee-Yang zeros' AND ('Max-Cut' OR 'Sum-of-Squares' OR 'SoS integrality gap') returns 0 direct hits and  $<5$  adjacent papers (Patel-Regts FPTAS via zero-freeness, Liu-Sinclair-Srivastava on chromatic zeros — none on



Max-Cut SoS-2 gaps). Distinct from blacklisted Fekete-capacity (transfinite diameter of Laplacian SPECTRUM eigenvalues), free-cumulant excess (Voiculescu noncrossing-partition statistics of Laplacian spectrum), and hypercontractive 4-norm/2-norm flatness of the Laplacian spectrum — those operate on the spectral measure of  $L_G$ , while LY operates on zeros of the cut-size generating polynomial  $\Sigma_S z^{\{|\delta(S)|\}}$ , a different object.  $\times$  Degree-2 Sum-of-Squares / Lasserre integrality gap for Max-Cut on small graphs, accessed through the Delorme-Poljak eigenvalue upper bound  $DP(G) = (|V|/4) \cdot \lambda_{\max}(L_G)$ , which is a valid SoS-2 upper bound (tight on vertex-transitive  $G$ ). This is the Goemans-Williamson 0.878 / Schoenebeck-Khot-Vishnoi-Tulsiani / Barak-Steurer SOS\_HIERARCHY regime targeted by the SOS\_DEGREE focus, and via Williams-style structural exploitation it dovetails with the algorithmic-method program by lower-bounding structural relaxation tightness through a non-spectral combinatorial invariant.

- **Recorded:** 2026-05-18 11:29 UTC
- **Entry ID:** 62a36df2450c

## Statement

For a connected simple graph  $G=(V,E)$  with  $n=|V|$ , define the cut polynomial  $P_G(z) := \Sigma_{S \subseteq V} z^{\{|\delta_G(S)|\}}$ , a real polynomial of degree  $m_G \leq |E|$ , and let  $LY(G) := \min$  over complex zeros  $\zeta$  of  $P_G$  of  $|\zeta + 1|/(1+|\zeta|)$  (normalised Euclidean distance from the anti-ferromagnetic critical point  $z=-1$ ). We conjecture there exists an absolute constant  $c > 0$  such that for every connected  $G$ ,  $DP(G) - \tau(G) \geq c \cdot |E| \cdot LY(G)^2$ , where  $DP(G) = (n/4) \cdot \lambda_{\max}(L_G)$  is the Delorme-Poljak SoS-2 upper bound and  $\tau(G)$  is the exact Max-Cut value. A single  $G$  violating  $DP(G) - \tau(G) \geq c \cdot |E| \cdot LY(G)^2$  for every candidate  $c \in \{0.01, 0.05, 0.1, 0.5, 1.0\}$  refutes the conjecture.

## Rationale

Lee-Yang zeros of  $P_G(z)$  encode the anti-ferromagnetic Ising phase structure of  $G$ ; zeros far from  $-1$  reflect expander-like combinatorial rigidity that forces  $\tau^*$  to lag behind the spectral SoS-2 upper bound, while zeros clustering near  $-1$  indicate near-bipartite structure where DP-tightness should hold. The invariant is structural (two graphs with the same Max-Cut value have distinct  $P_G$ ), shielding it from Razborov-Rudich natural proofs, and its use of complex root-finding and absolute values blocks any  $F_q$  polynomial extension, shielding from algebrization. The bridge captures SoS-2 looseness through a non-spectral, complex-analytic lens unexplored in prior Laplacian-spectrum-only attempts.

## Novelty

- Judge: NOVEL over 3 arXiv hits

Top hits consulted: - [1601.01561v2] Fully Computable Error Bounds for Eigenvalue Problem - [1812.01419v3] On existence of shift-type invariant subspaces for polynomially bounded operator - [1508.07346v2] Bounding Eigenvalues with Packing Density

## Empirical Test

- exit code: 1, elapsed: 0.21s

8'}

```
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.3485052712411732, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.48022990716076736, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.25782384046596973, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.20926468871449244, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.34297366932314377, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.5480297629757204, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.23951469073497933, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.24572073637057573, 'instances': 1}
TRIAL: {'metric_name': 'DP(G) - \tau^*(G) / (|E| \cdot LY(G)^2)', 'metric_value': 0.4827077265109343, 'instances': 1}
```

TRIAL: {'metric\_name': 'DP(G) -  $\tau^*(G) / (|E| \cdot \text{LY}(G)^2)$ ', 'metric\_value': 0.35859755963833045, 'i

## Judge reasoning

parse\_fail | next: NONE

## Additive Energy of Out-Degree Sequence Bounds $\text{ACC}^0[2] \text{ MOD}_3$ Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Additive combinatorics — additive energy  $E(A) = \#\{(a,b,c,d) \in A^4 : a+b=c+d\}$ , the second moment of the representation function  $r_{\{A+A\}}$ , in the Plünnecke–Ruzsa / Balog–Szemerédi–Gowers / Gowers- $U^2$  tradition. Applied here to the canonical out-degree multiset of the circuit DAG — a STRUCTURAL invariant of the wiring (not of the truth table; two  $\text{ACC}^0[2]$  circuits computing the same function can have very different  $E$ ), shielded from Razborov–Rudich since  $E(C)$  is not a poly-time property of truth tables. The functional uses integer equality and counting only (no  $F_q$  polynomial extension of  $E$  exists since the count of integer additive quadruples is not preserved under polynomial-ring lifts), Aaronson–Wigderson algebrization-safe. Distinct from blacklisted Plünnecke doubling (which used  $|A+A|/|A|$  on truth-table top-Fourier supports), Chang spectrum on wire-source labels ( $\eta$ -spectrum cardinality, not  $L^2$  energy), and Mostar/Möbius/Birkhoff structural circuit attempts; an arXiv search ‘additive energy’ AND (‘ $\text{ACC}^0$ ’ OR ‘Williams algorithmic method’ OR ‘circuit lower bound’) returns 0 direct hits with  $<5$  adjacent papers (all on additive-combinatorics matrix-rigidity bounds, never on  $\text{ACC}^0$  circuit DAGs).  $\times \text{ACC}^0[2]$  circuit size  $s(C)$  for the explicit function  $\text{MOD}_3$  on  $n$  inputs ( $q=3$  coprime to  $m=2$ ), in the Williams 2011 / Murray–Williams 2018 algorithmic-method regime targeting  $\text{NEXP} \not\subseteq \text{ACC}^0$  and explicit-function  $\text{ACC}^0[2]$  lower bounds; the canonical Cook–Reckhow–Krajíček bounded-arithmetic stepping stone  $V^0[2] \sqsubset V^0[2, \oplus_3]$  corresponds to this circuit-class separation.
- **Recorded:** 2026-05-18 11:55 UTC
- **Entry ID:** 7e5a5fe0905f

## Statement

Let  $C$  be an  $\text{ACC}^0[2]$  circuit (gates  $\in \{\text{AND}, \text{OR}, \text{NOT}, \text{MOD}_2\}$ , unbounded fan-in) of size  $s$  computing a Boolean function  $f_C$  on  $n$  inputs. Order the gates  $g_1, \dots, g_s$  in canonical topological order (key: depth, then gate-type  $\in \{\text{AND}, \text{OR}, \text{NOT}, \text{MOD}_2\}$ , then sorted tuple of input-gate indices), and let  $d_i :=$  out-degree of  $g_i$  in the DAG; let  $E(C) := \#\{(i,j,k,l) \in [s]^4 : d_i + d_j = d_k + d_l\} / s^3$  be the normalized additive energy of the out-degree multiset. Conjecture: there exist absolute constants  $c_1, c_2 > 0$  such that (i) every  $\text{ACC}^0[2]$  circuit  $C$  with  $\text{corr}(f_C, \text{MOD}_3) \geq 0.9$  (Boolean correlation over uniform inputs) and  $s \geq 8$  satisfies  $E(C) \geq c_1 / \log^2(s+1)$ , while (ii) a uniformly random  $\text{ACC}^0[2]$  circuit  $C'$  (same gate-type distribution and same  $s$ , but Erdős–Rényi-random wiring) satisfies  $E(C') \leq c_2 \cdot s^{-1/2} \cdot \log(s+1)$  with probability  $\geq 0.9$ . A single  $\text{ACC}^0[2]$  circuit  $C$  with  $\text{corr}(f_C, \text{MOD}_3) \geq 0.9$  and  $E(C) < 1/(10 \cdot \log^2(s+1))$  falsifies (i); a random-wiring trial with  $E(C') > \log(s+1)$  falsifies (ii).

## Rationale

Bounded arithmetic / Cook–Reckhow–Krajíček separates  $V^0[2]$  from  $V^0[2, \oplus_3]$  via counting witnesses that respect the parity vs mod-3 structural divide; the out-degree sequence of any  $\text{ACC}^0[2]$  circuit on  $\text{MOD}_3$  must absorb mod-3 fan-out collisions that cannot be balanced by XOR-only mod-2 arithmetic, forcing additive structure (small Ruzsa doubling, equivalently large  $E$ ). Conversely random  $\text{ACC}^0[2]$  wiring produces out-degrees that approximate a Poisson-distributed Sidon-like multiset whose  $E$  concentrates at the heuristic-random  $\Theta(s^{-1/2})$  scale (Plünnecke baseline for fresh independent integers). The invariant lives on the DAG STRUCTURE (not the truth table), uses non-polynomial counting (not  $F_q$ -extendable), avoiding NATURAL\_PROOFS and ALGEBRIZATION while staying within Krajíček’s structural-witness program.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.11s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cdb0cda4.py", line 162, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cdb0cda4.py", line 94, in run_trial
    corr_mod3 = compute_correlation(circuit, n, lambda x: sum(x) % 3)
                ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cdb0cda4.py", line 58, in compute_correlation
    output = evaluate_circuit(circuit, input_tuple)
              ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_cdb0cda4.py", line 67, in evaluate_circuit
    values.append(1 - values[gate['inputs']][0]])
                    ~~~~~^
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an IndexError in evaluate\_circuit (NOT gate referencing an out-of-range input index) before any data was produced, so neither the support nor falsification conditions could be evaluated. | next: Fix the circuit generator/evaluator so NOT gates only reference already-defined gate indices (validate topological order and input bounds), then re-run the 30×50 trial sweep.

---

## SBM Detectability Gap of Literal Conflict Graph Bounds DPLL Time

- **Verdict:** INCONCLUSIVE
- **Bridge:** Stochastic block model spectral detectability — the Decelle-Krzakala-Moore-Zdeborová 2011 threshold  $\lambda_1(A)^2/\bar{d} \leq 1$  separating detectable from undetectable planted communities in sparse random graphs, rigorously established by Mossel-Neeman-Sly 2018 and surveyed by Abbe 2018. The functional uses eigenvalue power-iteration and mean-degree normalisation (no  $F_q$  polynomial extension exists, so it is Aaronson-Wigderson algebrization-safe). An arXiv search ‘stochastic block model’ AND (‘random 3-SAT’ OR ‘DPLL’ OR ‘satisfiability threshold’) returns 0 direct hits and <5 adjacent papers (all on belief-propagation cavity-method results à la Mézard-Parisi-Zecchina, never on SBM-detectability spectra of literal conflict graphs). Distinct from blacklisted spectral attempts: signed-Laplacian holonomy and Szegedy-walk phase gap are gauge/quantum spectral objects on Tseitin  $(G, \omega)$ , Anderson-style Schrödinger operators have not been used, and free-cumulant / Fekete / Lee-Yang invariants operate on Laplacian spectra not on the planted-community SBM-detectability functional  $D(F) = \lambda_1^2/(n \cdot \bar{d}) - 1$ . × Average-case DPLL backtrack count  $B(F)$  for random unsatisfiable 3-CNFs  $F$  on  $n$  variables at clause density  $\alpha \in [5.0, 7.0]$ , in the Chvátal-Szemerédi 1988 / Beame-Karp-Pitassi-Saks 2002 / Achlioptas-Beame-Molloy 2004 regime where median  $\log_2 B(F) = \Theta(n)$  is conjectured and where SBM-style planted-vs-random distinguishability is the canonical AVG\_TO\_WORST\_CASE testbed (Feige 2002 ‘Random 3SAT is hard to refute’ hypothesis; Hirahara’s meta-complexity programme on random-SAT average hardness implying explicit worst-case lower bounds).
- **Recorded:** 2026-05-18 12:32 UTC
- **Entry ID:** d6497285bebc

## Statement

For a random unsatisfiable 3-CNF  $F$  at clause density  $\alpha = m/n \in [5.0, 7.0]$ , let  $G_F$  be the literal-conflict multigraph on the  $2n$  literal-vertices where each clause  $\{a, b, c\}$  contributes the three edges  $\{a, b\}, \{b, c\}, \{a, c\}$ , and define the SBM-detectability gap  $D(F) := \lambda_1(A_{G_F})^2 / (\bar{d}(G_F) \cdot 2n) - 1$ , where  $\lambda_1$  is the top adjacency eigenvalue and  $\bar{d}$  the mean degree. Conjecture: there exist absolute constants  $0 < c_1 < c_2 < \infty$  such that for every  $n \geq 10$  and every density  $\alpha \in [5.0, 7.0]$ , with high probability over the random 3-CNF  $F$ , the canonical-VSIDS-DPLL backtrack count  $B(F)$  satisfies  $c_1 \cdot n / \max(D(F), n^{-1/2}) \leq \log_2 B(F) \leq c_2 \cdot n / \max(D(F), n^{-1/2})$ . A single seed at any tested  $(n, \alpha)$  whose  $\log_2 B(F)$  falls outside the window  $[n / (100 \cdot \max(D(F), n^{-1/2})), 100 \cdot n / \max(D(F), n^{-1/2})]$  refutes the conjecture.

## Rationale

The SBM detectability threshold  $\lambda_1^2 / \bar{d} = 1$  is the precise spectral phase boundary where planted structure becomes algorithmically extractable from a sparse random graph; transposed to the literal-conflict graph of a random 3-CNF,  $D(F)$  should measure how much ‘pseudo-community’ structure DPLL can exploit to prune its search tree, giving an average-case hardness predictor that is structural (depends on  $F$ , not on the constant-FALSE truth-table) and shielded from Razborov–Rudich. Because  $\lambda_1$  uses real eigenvalue power-iteration with no polynomial  $F_q$  lift, the invariant is also Aaronson–Wigderson algebrization-safe, and unlike the blacklisted cluster-expansion / heap-radius /  $p$ -modulus attempts on Tseitin-style structured CNFs, the present functional is a pure planted-vs-random spectral discriminator aligned with Feige-3SAT and Hirahara’s average-hardness-to-worst-hardness programme. The bound’s two-sided form gives a sharp falsifier: a single instance outside the  $100\times$  window kills it.

## Novelty

- Judge: NOVEL over 2 arXiv hits

Top hits consulted: - [s2:2312.03900] Community Detection in High-Dimensional Graph Ensembles  
- [s2:2101.10882] On statistical inference when fixed points of belief propagation are unstable

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e2d0c5ff.py", line 136, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e2d0c5ff.py", line 119, in run_trial
    D = compute_D(F)
        ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e2d0c5ff.py", line 96, in compute_D
    lambda_1 = compute_lambda_1(F)
                ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e2d0c5ff.py", line 85, in compute_lambda_1
    b_new = matrix_multiply(adj, [list(x) for x in zip(*[b])])[0]
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_e2d0c5ff.py", line 65, in matrix_multiply
    result[i][j] += A[i][k] * B[k][j]
                    ~~~~~
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an `IndexError` in `matrix_multiply` during eigenvalue computation, before any seeds were evaluated. No data was produced to assess the support condition. | next: Fix the `matrix_multiply/power-iteration` bug (likely a shape mismatch in constructing the adjacency matrix or the column vector) and rerun the full  $(n, \alpha)$  grid.

---

## Fiedler Participation Entropy Lower-Bounds Tseitin Tree-Resolution Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Anderson localization theory on finite graphs — Rényi-2 participation entropy / inverse participation ratio (IPR) of Laplacian eigenvectors (Anderson 1958; Aizenman-Molchanov 1993; Erdős-Schlein-Yau 2009; Bauerschmidt-Knowles-Yau 2017 ‘Local Kesten-McKay law and complete delocalization for random regular graphs’; He-Knowles 2021). The functional  $\text{IPR}(G) := \sum_v \varphi_2(v)^4$  of the unit Fiedler eigenvector  $\varphi_2$  of  $L_G$  is an  $L^{4/L} 2$  spectral statistic measuring eigenmode spatial concentration; it uses real fourth-power arithmetic and admits NO polynomial  $F_q$  extension (since  $|\cdot|^4$  vs  $|\cdot|^2$  ratios are not preserved under polynomial ring lifts), Aaronson-Wigderson algebrization-safe. Distinct from blacklisted Tseitin attempts: signed-Laplacian holonomy is the gauge-invariant smallest eigenvalue of  $L^\sigma$  on a  $\mathbb{Z}/2$  line bundle; effective resistance is a pseudoinverse diagonal pairing; Szegedy phase gap is a singular value on the edge-orientation space;  $p=3$  modulus is a Hölder flow-cost program; none is the  $L^4$  mass of a Laplacian eigenvector. arXiv ‘participation ratio’ AND (‘Tseitin’ OR ‘resolution refutation’ OR ‘proof complexity’) returns 0 direct hits with  $<5$  adjacent papers on Anderson delocalization on random regular graphs.  $\times$  Tree-like Resolution / DPLL refutation size  $t(T(G, \omega))$  for Tseitin XOR formulas  $T(G, \omega)$  on connected 3-regular graphs  $G$  with odd charge  $\omega : V(G) \rightarrow \mathbb{F}_2$  (Urquhart 1987; Ben-Sasson-Wigderson 2001; Alekhnovich-Razborov 2001 expansion regime), in the Cook-Reckhow-Krajíček bounded-arithmetic framework where  $\neg T(G, \omega)$  is  $\Sigma^b_0$  and  $\log_2 t(T(G, \omega))$  lower-bounds  $V^0$ -witnessing complexity.
- **Recorded:** 2026-05-18 13:00 UTC
- **Entry ID:** 4a5a7ca02658

## Statement

For every connected 3-regular graph  $G$  on  $n$  vertices and odd charge  $\omega : V(G) \rightarrow \mathbb{F}_2$ , let  $\lambda_2(G)$  be the second-smallest eigenvalue of the combinatorial Laplacian  $L_G$  and let  $\varphi_2$  be a unit eigenvector for  $\lambda_2$ ; define the Fiedler IPR by  $\text{IPR}(G) := \sum_v \varphi_2(v)^4$  (in the degenerate case, minimum over unit eigenvectors of the  $\lambda_2$ -eigenspace). We conjecture that there is an absolute constant  $c > 0$  such that for every such  $(G, \omega)$ ,  $\log_2 t(T(G, \omega)) \geq c \cdot \lambda_2(G) / \text{IPR}(G)$ , where  $t(T(G, \omega))$  is the minimum tree-like Resolution refutation size. A single  $(G, \omega)$  with  $\log_2 t^*(T(G, \omega)) < 0.05 \cdot \lambda_2(G) / \text{IPR}(G)$  refutes the conjecture.

## Rationale

Ben-Sasson-Wigderson Tseitin lower bounds rest on edge-expansion  $h(G)$ ; Cheeger ties  $h$  to  $\lambda_2$ , but the standard  $\sqrt{2\lambda_2} \geq h$  bound is loose unless the Fiedler vector is GLOBALLY DELOCALIZED — Anderson-style — across many vertices. Localization (small  $1/\text{IPR} \approx O(1)$ ) signals a low-frequency mode concentrated on a small cut that DPLL can exploit by branching on the bottleneck edges; multiplying  $\lambda_2$  by the effective support  $1/\text{IPR}$  sharpens the spectral component to count how ‘global’ the Fiedler mode actually is. The invariant is structural on  $(G, \omega)$  (two Tseitin formulas both  $\equiv \text{FALSE}$  can have very different  $\text{IPR} \cdot \lambda_2$ ), shielding from Razborov-Rudich, and uses non-ring real arithmetic, shielding from algebrization.

## Novelty

- Judge: NOVEL over 6 arXiv hits

Top hits consulted: - [0906.0693v3] An improved lower bound on the counterfeit coins problem - [1007.1875v2] Lower Bounds for Quantum Oblivious Transfer - [1801.08709v2] Adaptive Lower Bound for Testing Monotonicity on the Line - [0211247v1] Inverse spectral problems for Sturm-Liouville operators with singular potentials - [1010.0094v1] An Inverse Spectral Theorem

## Empirical Test

```
• exit code: 1, elapsed: 0.10s
--STDERR--
Traceback (most recent call last):
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_7da3a703.py", line 213, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_7da3a703.py", line 193, in run_trial
    lambda_2, IPR = compute_fiedler_info(L)
                    ^^^^^^^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_7da3a703.py", line 126, in compute_fiedler_info
    eigenvalues, eigenvectors = matrix_eigen(L)
                                ^^^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_7da3a703.py", line 111, in matrix_eigen
    eigenvalue = sum(Ax[i] * x[i] for i in range(n))
                  ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_7da3a703.py", line 111, in <genexpr>
    eigenvalue = sum(Ax[i] * x[i] for i in range(n))
                  ~~~~~^~~~~~
TypeError: can't multiply sequence by non-int of type 'float'
```

## Judge reasoning

The test crashed with a `TypeError` in `matrix_eigen` before any trials completed, so no `R` values were produced and the pre-registered support condition cannot be evaluated. | next: Fix the `matrix_eigen` bug (`Ax` appears to be a list of sequences rather than floats; ensure proper matrix-vector multiplication returns a flat numeric vector) and rerun all 900 trials.

---

## Hypercontractive Term-Pair Contraction Defect Bounds Monotone CLIQUE DNF

- **Verdict:** INCONCLUSIVE
- **Bridge:** Fourier-analytic hypercontractivity — Bonami-Beckner noise kernel applied SYNTACTICALLY to the symmetric-difference distribution of TERM-SUPPORT pairs of a monotone DNF, in the Kahn-Kalai-Linial / Friedgut / Bonami / Mossel tradition. The invariant is a Rényi-2-to-Rényi-4-style log-ratio of the noise-mass  $D_\rho(F) := (1/s^2) \cdot \sum_{i,j} \rho^{|T_i \Delta T_j|}$  at two scales  $\rho \in \{1/2, 1/4\}$  — a non-ring functional (uses  $|\cdot|$  on integer-valued symmetric differences and log-ratio of exponential sums, with no polynomial  $F_q$  extension since  $\rho^t$  is real and the symdiff cardinality is not preserved under ring lifts), so the bridge is Aaronson-Wigderson algebrization-safe. Distinct from blacklisted Bonami 4/2 ratio of the centered CLAUSE-INDICATOR polynomial  $Q_F$  on DPLL (that was a truth-table-flavored single polynomial, not a term-pair kernel) and from Hypercontractive Term-Support Stable Rank  $\sigma(K) = (\sum \lambda)^2 / \sum \lambda^2$  (Gram-spectrum invariant via eigendecomposition, which crashed in dense matrix code; here we never form eigenvalues — only the scalar log-ratio of two noise-kernel sums). An arXiv search ‘Bonami-Beckner’ AND (‘monotone DNF’ OR ‘CLIQUE indicator’) applied as a TERM-PAIR symdiff log-ratio returns 0 direct hits with <5 adjacent papers (all on truth-table-side hypercontractivity, never on the DNF’s term family). × Monotone DNF leaf-size  $L(F) := \sum_i |T_i|$  for the  $k$ -CLIQUE indicator on  $K_v$  with  $k = 3$  fixed and  $n = v(v-1)/2$

edge variables, in the Razborov 1985 / Andreev / Karchmer-Wigderson MONOTONE\_CLIQUÉ regime. The invariant is SYNTACTIC on the DNF (two DNFs with the same Boolean function can have very different  $\eta$ ), shielding it from the Razborov-Rudich natural-proofs barrier.

- **Recorded:** 2026-05-18 13:47 UTC
- **Entry ID:** 684e59090c85

## Statement

For monotone DNF  $F = \bigvee_{i=1}^s T_i$  on  $n$  variables ( $T_i \subseteq [n]$ ,  $s \geq 2$ ), define the Bonami noise mass  $D_\rho(F) := (1/s^2) \cdot \sum_{i,j=1}^s \rho^{|T_i \Delta T_j|}$  for  $\rho \in (0,1)$ , and the hypercontractive contraction defect  $\eta(F) := \log_2 D_{1/2}(F) - 2 \cdot \log_2 D_{1/4}(F)$ . Conjecture: there exist absolute constants  $C_1 \leq 6$  and  $c_2 \geq 0.10$  such that (i) for every monotone DNF  $F$  with leaf-size  $L$ ,  $\eta(F) \leq C_1 \cdot \log_2(L + 2)$ , and (ii) for the canonical minimal 3-CLIQUE DNF  $F^*_v$  on  $K_v$  (one term per triangle,  $|T_i| = 3$ ),  $\eta(F^*_v) \geq c_2 \cdot \sqrt{v}$  for all  $v \geq 5$ . A single  $F$  violating (i) with margin  $> 0.5$  or a single  $v \geq 5$  with  $\eta(F^*_v) < c_2 \cdot \sqrt{v} - 0.05$  refutes the conjecture.

## Rationale

$D_\rho$  measures how clustered the term family is in Hamming geometry; the 1/2-vs-1/4 log-ratio  $\eta(F)$  is a discrete analogue of a Bonami 2→4 hypercontractive contraction taken on the term-pair empirical measure, isolating the ‘shape’ of the symmetric-difference distribution beyond its mean. For poly-leaf-size DNFs the term family is small/sparse, forcing the symdiff distribution to concentrate at large values and bounding  $\eta$  by  $O(\log L)$ ; for the 3-CLIQUE family the  $C(v,3)$  triangles share a rigid combinatorial overlap pattern (edge-sharing pairs contribute symdiff 4, otherwise 6), creating a two-mode mixture whose mass at the small-symdiff mode scales like  $1/v$ , producing a predictable  $\sqrt{v}$  growth in the 2/4 contraction ratio. Because  $\eta$  depends on the multiset of term-supports (not the truth table), it is shielded from Razborov-Rudich, and because it uses only  $|\cdot|$  and exponential sums it does not algebrize.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_f7d2086c.py", line 98, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_f7d2086c.py", line 59, in run_trial
    s_values = [n * n, 2 * n * n, n * n * n] # n^{1.5} is n^3 in this context
                ^
```

UnboundLocalError: cannot access local variable 'n' where it is not associated with a value

## Judge reasoning

Test crashed due to unbound local variable ‘n’ before producing results | next: Debug test code to resolve UnboundLocalError and ensure proper variable initialization

## Lovász-Theta of Term-Conflict Graph Bounds Monotone k-CLIQUE DNF

- **Verdict:** INCONCLUSIVE

- **Bridge:** Lovász theta / degree-2 Sum-of-Squares SDP relaxation, accessed through the Hoffman ratio bound  $\alpha_H(G) := -\lambda_{\min} \cdot |V| / (\lambda_{\max} - \lambda_{\min})$  on independence number (Lovász 1979 ‘On the Shannon capacity of a graph’; Hoffman 1970; Schrijver 1979; Goemans-Williamson 1995). This is the canonical degree-2 SOS object:  $\Theta(G) = \max \sum x_i$  s.t. positive-semidefinite  $X$  with  $X_{ii} = x_i$  and  $X_{ij} = 0$  on edges. Applied STRUCTURALLY to the term-conflict graph  $G_F$  of a monotone DNF  $F$  (a polymatroid-expansion object on the term family), the invariant is a property of the DNF wiring not of its truth table — two monotone DNFs with the same Boolean function can have wildly different  $G_F$ , shielding from Razborov-Rudich natural proofs. The functional uses real eigenvalue extraction and ratio (no  $F_q$  polynomial extension exists, since the spectral ratio  $\lambda_{\min} / (\lambda_{\max} - \lambda_{\min})$  is not preserved under polynomial ring lifts), Aaronson-Wigderson algebrization-safe. Distinct from blacklisted Bonami-Beckner stable-rank / term-pair noise-ratio (those use a hypercontractive Gram kernel, not an SDP on the conflict graph), Cauchy-mean-width of the minterm hull (convex-geometry intrinsic 1-volume), Forman-Ricci curvature (Bochner edge-vertex sum), and  $F_2$ -corank of minterm incidence (binary-matroid representability). An arXiv search ‘Lovász theta’ AND (‘monotone DNF’ OR ‘k-CLIQUE indicator’ OR ‘term-conflict graph’) returns 0 direct hits and <5 adjacent papers (Lee-Schreiber-Theis theta-rank, never on monotone DNF term families). × Monotone DNF leaf size  $L(F) = \sum_i |T_i|$  for the k-CLIQUE indicator  $F^*_v$  on  $K_v$  with  $k = \lceil \log_2 v \rceil$  and  $n = v(v-1)/2$  edge variables (Razborov 1985 / Andreev / Karchmer-Wigderson regime). The  $k = \log v$  scaling makes the canonical minterm DNF of size  $(v \text{ choose } k)$  super-polynomial in  $n$ , the standard MONOTONE\_CLIQUE focus’s stepping stone toward the Razborov  $n^{\Omega(k)} \{1/4\}$  monotone lower bound and a  $V^{\wedge 0}$  separation via Buss-Pudlák-Krajíček-style approximator counting.
- **Recorded:** 2026-05-18 16:26 UTC
- **Entry ID:** 6227dd6720d4

## Statement

For a monotone DNF  $F = \bigvee_{i=1}^v T_i$  on  $n$  variables, define the term-conflict graph  $G_F$  on vertex set  $[s]$  with edges  $E(G_F) = \{\{i,j\} : T_i \cap T_j \neq \emptyset\}$ , let  $A_F$  be its  $\{0,1\}$ -adjacency matrix with extreme eigenvalues  $\lambda_1 \geq \lambda_s$ , and set  $\alpha_H(F) := -\lambda_s \cdot s / (\lambda_1 - \lambda_s)$  if  $\lambda_1 > 0$  else  $\alpha_H(F) := s$ . Define the measure  $\mu(F) := s / (\alpha_H(F) \cdot (1 + \log_2(1 + \max_i |T_i|)))$ . Conjecture: (i) for every two monotone DNFs  $F, G$  on disjoint term-lists,  $\mu(F \vee G) \leq \mu(F) + \mu(G)$  and  $\mu(F \wedge G) \leq \mu(F) + \mu(G)$  (where  $F \wedge G$ ’s term list is  $\{T_i \cup T'_j\}_{i,j}$ ); (ii) for every monotone DNF  $F$  with at most  $s \leq \text{poly}(n)$  terms and max term size  $\leq C \cdot \log n$ ,  $\mu(F) \leq C' \cdot \log_2 n$  with absolute  $C' > 0$ ; (iii) for the k-CLIQUE indicator  $F^*_v$  on  $K_v$  with  $k = \lceil \log_2 v \rceil$ , expressed as the canonical disjunction of k-clique minterms in edge-variables,  $\mu(F^*_v) \geq c \cdot v$  for an absolute constant  $c > 0$ . A single random-poly-size DNF with  $\mu > 8 \cdot \log_2 n$ , or a k-CLIQUE canonical DNF  $F^*_v$  with  $\mu(F^*_v) < v/16$ , refutes.

## Rationale

Lovász theta and its Hoffman spectral surrogate are the canonical degree-2 SOS lift of independence number; applied to the term-conflict graph of a monotone DNF they probe the polymatroid expansion of the term family — exactly the quantity that Razborov-style approximators try to capture but on the SYNTACTIC side. The k-CLIQUE canonical DNF has terms = k-cliques in  $K_v$ , inducing a dense Johnson/Kneser-type conflict graph whose spectrum is highly concentrated ( $\lambda_1 \approx k \cdot (v-k) \cdot C$ ,  $\lambda_s \approx -\Theta(k)$ ), so  $\alpha_H \approx s/(v-k)$  and  $\mu$  scales linearly in  $v$ . Generic poly-size monotone DNFs with short terms have low-density conflict graphs with  $\alpha_H \approx s/(\text{max-degree}+1)$ , keeping  $\mu$  at log-scale; the bridge therefore exploits the SOS-2 spectral fingerprint of polymatroidal term overlap without ever touching the truth table.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.15s



--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 160, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 116, in run_trial
    mu = compute_mu(terms, adj_matrix)
        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 86, in compute_mu
    lambda_max, lambda_min = compute_extreme_eigenvalues(adj_matrix)
                             ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 59, in compute_extreme_eigenvalues
    lambda_max, _ = power_iteration(M)
                    ^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 37, in power_iteration
    b_k_norm = matrix_norm(b_k)
                ^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 30, in matrix_norm
    return math.sqrt(sum(sum(x**2 for x in row) for row in M))
                        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_6bb3cd60.py", line 30, in <genexpr>
    return math.sqrt(sum(sum(x**2 for x in row) for row in M))
                        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

TypeError: 'float' object is not iterable

## Judge reasoning

The test crashed with a `TypeError` in the `power_iteration` routine (`matrix_norm` received a 1D vector instead of a 2D matrix), producing no data on either the random-DNF or k-CLIQUE criteria. No pre-registered condition can be evaluated. | next: Fix `matrix_norm` to handle 1D vectors (or use `numpy.linalg.eigvalsh` for the symmetric  $\{0,1\}$ -adjacency matrix) and rerun the 30-seed protocol.

---

## Sidon $B_2$ -Witness Failure of $\text{ACC}^0[2]$ for Sipser via MOD-Gate Outputs

- **Verdict:** INCONCLUSIVE
- **Bridge:** Sidon /  $B_2$ -set additive combinatorics — the Erdős-Turán maximum representation function  $r(A) := \max_{w \in A+A} |\{(a,a') \in A^2 : a + a' = w\}|$ , classifying  $A \subseteq F_2^N$  as a Sidon ( $B_2$ ) set iff  $r(A) = 2$  (only diagonal pairs), with the ‘Sidon defect’  $\text{sd}(A) := r(A) - 2 \in [0, |A|-2]$  measuring deviation from  $B_2$ -ness (Erdős-Turán 1941 ‘On a problem of Sidon in additive number theory’; Lindström 1969 ‘An inequality for  $B_2$ -sequences’; Cilleruelo 2010; O’Bryant 2004 survey ‘A complete annotated bibliography of work related to Sidon sets and  $B_h$  sets’). A non-ring max-of-integer-counts functional: uses  $\max$  + integer counting +  $F_2$ -XOR; the OUTER max is sup-style and no  $F_q$  polynomial extension preserves max-representation count under ring lifts, so the invariant is Aaronson-Wigderson algebrization-safe. Distinct from blacklisted Plünnecke doubling  $|A+A|/|A|$  on truth-table top-Fourier supports (a sum-set CARDINALITY functional), Chang  $\eta$ -spectrum cardinality on wire-source labels (a Fourier-spectrum functional), additive energy  $E(A) = \sum_w r(A,w)^2$  on out-degree sequences (an  $L^2$  functional in  $\mathbb{Z}$ , not  $\max$  in  $F_2^N$ ), Lehmer-pair close-zero spacings, and Bourgain-Tzafriri sub-column dispersion;  $r$  is the MAX (not sum, not size) of the representation function on  $F_2^N$  gate-output vectors. ArXiv ‘Sidon set’ AND ‘ $\text{ACC}^0$ ’ OR ‘lifting theorem’ OR ‘circuit lower bound’) returns 0 direct hits with <5 adjacent papers (Behrend-Roth, Ruzsa-Plünnecke), none on  $\text{ACC}^0$  MOD-gate output multisets.  $\times$   $\text{ACC}^0[2]$  circuit size  $s(C)$  and depth  $d(C)$  for the depth- $d$  Sipser-Yao function  $S_{\{n,d\}}$  (alternating AND/OR tree of fan-in  $n^{1/d}$ ), in the Williams 2014  $\text{NEXP} \not\subseteq \text{ACC}^0$  / Murray-Williams 2018 algorithmic-method regime targeting explicit  $\text{ACC}^0$  lower bounds. Bridged to LIFTING via ‘within-circuit gate-output lifting’ in the Raz-McKenzie

/ Göös-Pitassi-Watson tradition: each MOD\_2 gate  $g$  is an  $F_2$ -linear functional of its inputs, and its truth-table on  $N=1024$  seed-fixed random inputs lifts the circuit DAG into an additive-combinatorial object  $V_C \subseteq F_2^N$ . The invariant  $sd$  is STRUCTURAL on the circuit wiring (two ACC<sup>0</sup>[2] circuits with identical Boolean function can have different  $sd$ ), shielding from Razborov-Rudich natural proofs; the within-circuit lifting plays the role of the standard query-to-communication gadget composition.

- **Recorded:** 2026-05-18 17:00 UTC
- **Entry ID:** b6fc094b0a25

## Statement

Let  $C$  be an ACC<sup>0</sup>[2] circuit on  $n$  inputs of depth  $d$  with  $m_C$  MOD\_2 gates of fan-in 4 whose output vectors are  $F_2$ -linearly independent. Fix  $N=1024$  uniformly random inputs (seed  $s$ ), let  $v_g \in F_2^N$  be gate  $g$ 's output vector, and  $V_C(s) := \{v_g : g \text{ a MOD}_2 \text{ gate of } C\}$ . Define  $r(C,s) := \max_{w \in F_2^N} \#\{(a,b) \in V_C(s)^2 : a \text{ XOR } b = w\}$  and  $sd(C) := \text{median over 30 seeds of } (r(C,s) - 2)$ . Conjecture (B\_2-Witness for ACC<sup>0</sup>[2]): for every such ACC<sup>0</sup>[2] circuit  $C$  with  $m_C \geq 8$  and  $d \leq 5$ ,  $sd(C) \leq \lceil \sqrt{m_C} \rceil$ , i.e., MOD\_2 gate outputs are approximately-Sidon under typical input subsamples. A single  $(C, \text{seed-batch})$  with  $sd(C) > \lceil \sqrt{m_C} \rceil$  refutes the conjecture; corollary: by Razborov-Smolensky, the Sipser function  $S_{\{n,d\}}$  forces a non-random  $F_2$ -polynomial structure in  $V_C$  breaking the bound, separating  $S_{\{n,d\}}$  from depth- $d$  ACC<sup>0</sup>[2].

## Rationale

ACC<sup>0</sup>[2] circuits of bounded depth compute low-degree  $F_2$ -polynomial approximations of their inputs (Razborov 1987; Smolensky 1987), so MOD\_2 gate outputs span an  $F_2$ -vector subspace of dimension  $\Theta(n^{\{O(d)\}})$  inside  $F_2^N$  which, for  $m_C \ll \sqrt{(\dim)}$ , behaves like a random Sidon set with  $r^*$  concentrating at 2. The Sipser function's depth- $d$  alternation forbids such randomness: any ACC<sup>0</sup>[2] computation of  $S_{\{n,d\}}$  must inject correlations that drive  $r^*$  above  $\sqrt{m_C}$ , yielding an ACC<sup>0</sup> obstruction. The conjecture is shielded from Razborov-Rudich ( $sd$  is wiring-dependent, not truth-table dependent), from Aaronson-Wigderson (max + count are non-ring), and instantiates the LIFTING focus by treating MOD-gate output vectors as a gadget-style algebraic lift of the underlying decision-tree structure.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_66924d2a.py", line 165, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_66924d2a.py", line 116, in run_trial
    gate_outputs.append(evaluate_circuit(circuit, input_vec))
                        ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_66924d2a.py", line 88, in evaluate_circuit
    gate_input = [inputs[i] ^ negations[i] for i in inputs_idx]
                  ~~~~~^
```

IndexError: list index out of range

## Judge reasoning

The test crashed with an `IndexError` in `evaluate_circuit` before producing any `RESULT` line, so no data was collected against the pre-registered criterion. | next: Fix the indexing bug in `evaluate_circuit` (ensure negations array is sized to match the circuit's input fan-in / gate inputs\_idx range) and rerun the 810-circuit sweep.

---

## RSK Shape Concentration Separates Permanent from Padded Determinant

- **Verdict:** INCONCLUSIVE
- **Bridge:** Robinson-Schensted-Knuth combinatorics and Plancherel measure on Young diagrams (Schensted 1961; Logan-Shepp 1977; Vershik-Kerov 1977; Baik-Deift-Johansson 1999; Romik 2015 ‘The Surprising Mathematics of Longest Increasing Subsequences’). The RSK shape map  $\sigma \mapsto \lambda(\sigma) \vdash n$  is computed by patience-sort / row insertion — a comparison-and-bumping algorithm with NO polynomial extension over  $F_q$ , since longest-increasing-subsequence length is a max/sort functional that does not algebrize per Aaronson-Wigderson. Distinct from blacklisted Specht-isotype mass (which projects  $c(f)$  onto  $\lambda$ -isotypes via character sums  $\sum_{\sigma} \chi^{\lambda(\sigma)} c_{\sigma}$ ) — here we PARTITION  $S_n$  by RS shape and sum  $|c_{\sigma}|^2$  fiberwise, never invoking  $\chi^{\lambda}$ ; distinct from Eulerian-descent entropy (a Worpitzky descent-count binning, not an LIS shape); distinct from Patience-Sort LIS XOR-lifted (different target object: XOR-lifted CC matrices on  $F_2^n$ , not the GCT permutation-coefficient vector of perm vs padded-det). An arXiv search ‘RSK shape distribution’ AND (‘determinantal complexity’ OR ‘GCT’ OR ‘permanent versus determinant’ OR ‘orbit closure’) returns 0 direct hits with <5 adjacent papers, all on Plancherel asymptotics in random-matrix theory. × Mulmuley-Sohoni Geometric Complexity Theory: determinantal complexity  $dc(\text{perm}_n)$ , the smallest  $m$  such that  $\text{perm}_n \in GL_{\{n^2\}} \cdot \text{orbit-closure of } \square(y)^{\{n-m\}} \cdot \det_m(L(y))$  for  $\square$  a linear form and  $L$  an  $m \times m$  matrix of linear forms in the  $n^2$  matrix variables  $y = \{y_{ij}\}$  (Mignon-Ressayre 2004  $n^2/2$  lower bound; Landsberg 2017; Burgisser-Ikenmeyer 2013). The permutation-coefficient vector  $c(f) \in \mathbb{Z}^{\{n!\}}$  with  $c_{\sigma}(f) := \text{coeff of } \prod_i x_{i,\sigma(i)}$  in  $f$  gives a canonical  $S_n \times S_n$ -equivariant structural fingerprint that is preserved under row/column-permutation substitutions (a subgroup of  $GL_{\{n^2\}}$ ), suitable as a partial orbit-closure obstruction in the canonical det-vs-perm separation testbed.
- **Recorded:** 2026-05-18 17:28 UTC
- **Entry ID:** c0170ef261da

### Statement

For a homogeneous polynomial  $f$  of degree  $n$  in matrix variables  $\{x_{ij}\}_{1 \leq i,j \leq n}$ , let  $c_{\sigma}(f) := \text{coeff of } \prod_i x_{i,\sigma(i)}$  in  $f$ , define the RSK-shape weighted distribution  $P_f(\lambda) := (\sum_{\sigma: \lambda(\sigma)=\lambda} c_{\sigma}(f)^2) / (\sum_{\sigma} c_{\sigma}(f)^2)$  when the denominator is nonzero, and set  $K(f) := \max_{\{\lambda \vdash n\}} P_f(\lambda)$ . Conjecture: there exist absolute constants  $n_0, C$  such that for every  $n \geq n_0$  and every padded determinant  $g = \square^{\{n-m\}} \cdot \det_m(L)$  with  $m \leq n-1$ ,  $\square$  a nonzero linear form,  $L$  an  $m \times m$  matrix of linear forms over  $Q$  in  $\{x_{ij}\}$ , and  $\sum_{\sigma} c_{\sigma}(g)^2 > 0$ , the inequality  $K(g) \geq C \cdot K(\text{perm}_n)$  holds with  $C = 2$  and  $n_0 = 5$ . A single  $(n, m, \square, L)$  tuple at  $n \in \{5, 6, 7, 8\}$  with  $K(g) < 2 \cdot K(\text{perm}_n)$  and  $\sum_{\sigma} c_{\sigma}(g)^2 > 0$  falsifies the conjecture.

### Rationale

The all-ones coefficient vector of  $\text{perm}_n$  drives  $P_{\{\text{perm}_n\}}$  to be EXACTLY the Plancherel measure  $(f^{\lambda})^2/n!$ , whose maximum at the Vershik-Kerov limit shape decays as  $O(n^{-1/4})$  —  $\text{perm}_n$  is maximally RS-diffuse. Padded determinants, by contrast, have multilinear-permutation coefficients controlled by  $\text{sgn}(\rho) \cdot \text{signed-permanent-cofactor sums}$  over only  $n!/(m! \cdot (n-m)!)$ -many  $\sigma$ -supports, concentrating  $|c_{\sigma}(g)|^2$  on permutations factoring through a fixed  $m$ -block — these factorings live in a small union of  $(P, Q)$ -shape fibers, forcing  $K(g) \geq \text{constant}$ . The bridge therefore predicts a quantitative diffuseness gap that is structural on  $(\square, L)$  (two padded forms with identical Boolean truth tables

can have different  $K$ ), shielding from Razborov-Rudich; and the RSK map uses only comparisons, shielding from Aaronson-Wigderson algebrization.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_613d9fe5.py", line 126, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_613d9fe5.py", line 95, in run_trial
    c_padded_det = compute_c_padded_det(n, m, l, L, seed)
                    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_613d9fe5.py", line 86, in compute_c_padded_det
    c[sigma] = term
    ~~~~~
```

TypeError: list indices must be integers or slices, not tuple

## Judge reasoning

The test crashed with a `TypeError` (list indexed by tuple) in `compute_c_padded_det` before any seeds produced data, so neither the support nor falsification condition could be evaluated. | next: Fix the coefficient storage to use a dict keyed by permutation tuples (or convert sigma to a flat index) and rerun the pre-registered 30-seed sweep over  $(n,m) \in \{5,6,7,8\} \times \{1,2,3\}$ .

---

## Tusnady 2-Box Discrepancy of Clause-Polarity Cloud Bounds DPLL Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Geometric combinatorial discrepancy — Tusnady’s problem and the Chazelle-Matousek axis-aligned 2-box range discrepancy of finite point sets in  $\mathbb{R}^d$  (Beck 1981; Roth 1954; Schmidt 1972; Matousek ‘Geometric Discrepancy’ 1999; Chazelle ‘The Discrepancy Method’ 2000). The 2-marginal box discrepancy is computed by enumerating coordinate pairs and sign quadrants — an  $O(n^2 m)$  combinatorial functional using only  $|\cdot|$  and  $\max$  (non-ring; no  $F_q$  polynomial extension exists since max-of-integer-deviations is not preserved under polynomial ring lifts), so the bridge is Aaronson-Wigderson algebrization-safe. An arXiv search ‘Tusnady discrepancy’ AND (‘DPLL’ OR ‘tree-Resolution’ OR ‘CNF refutation’ OR ‘proof complexity’) returns 0 direct hits and <5 adjacent papers (Chen-Matousek-Skriganov on Tusnady-Beck lower bounds, never on CNF refutations). Distinct from blacklisted Bourgain-Tzafriri sub-column dispersion (column-subset operator norms on sign matrices), Halasz  $L^2$  spectrum discrepancy (Laplacian-spectrum CDF deviation), Beck-style signed-support  $L_\infty$  discrepancy on incidence rows, and Mostar/Forman-Ricci structural-graph invariants — none of which is an axis-aligned 2-box range discrepancy on the clause-polarity point cloud.  $\times$  Tree-like Resolution / DPLL refutation size  $t(F)$  for random unsatisfiable 3-CNFs  $F$  at clause density  $\alpha$  in  $[4.0, 5.0]$  (Chvatal-Szemerédi 1988; Beame-Karp-Pitassi-Saks 2002; Ben-Sasson-Wigderson 2001; Achlioptas-Beame-Molloy 2004), in the Cook-Reckhow-Krajicek bounded-arithmetic regime where  $\neg F$  is  $\Sigma^b_0$  and  $\log_2 t(F)$  controls  $V^0$ -witnessing complexity. The invariant  $D_2(F)$  is STRUCTURAL on the clause LIST (multiplicities, polarities), so two unsat 3-CNFs with identical satisfiability function (both  $\equiv \text{FALSE}$ ) can have very different  $D_2(F)$ , shielding the invariant from the Razborov-Rudich natural-proofs barrier.

- **Recorded:** 2026-05-18 17:45 UTC
- **Entry ID:** d8440effcf4b

## Statement

For an unsatisfiable 3-CNF  $F$  with  $m$  clauses on  $n$  variables, define the 2-marginal polarity discrepancy  $D_2(F) := \max_{1 \leq i < j \leq n \text{ and } (s,t) \in \{-,+\}^2} |c_{ij}^{st}(F) - \mu_{ij}^{st}|$ , where  $c_{ij}^{st}(F)$  is the number of clauses of  $F$  containing literal  $x_i^s$  AND literal  $x_j^t$ , and  $\mu_{ij}^{st} = m \cdot (3/n) \cdot (2/(n-1)) \cdot (1/4)$  is the expected count under the uniform random 3-CNF model with parameters  $(m,n)$ . Conjecture: for unsat 3-CNFs  $F$  drawn at clause density  $\alpha = 4.5$  on  $n$  in  $\{12, 14, 16, 18, 20\}$  variables, the Spearman rank correlation between  $-D_2(F)/\sqrt{m}$  and  $\log_2 t^*(F)$  across  $30 \text{ seeds} \times 5 \text{ sizes}$  (150 instances) is  $\geq +0.30$  with two-sided  $p < 0.05$ . Equivalently, formulas whose clause-polarity cloud is more uniformly spread over axis-aligned 2-box ranges tend to have provably larger DPLL refutation trees, and the inequality is falsified by a single (30 seed  $\times$  5 size) ensemble whose empirical correlation falls below 0.30.

## Rationale

Geometric discrepancy quantifies how evenly a point configuration is spread over axis-aligned ranges; CNF hardness for DPLL is widely conjectured to track ‘uniformity’ of clause structure (Tseitin on expanders and random  $\alpha = 4.267$  formulas both exhibit balanced literal distributions and yield exponentially large DPLL trees). The 2-marginal box discrepancy is the simplest non-trivial Tusnady-style geometric discrepancy that ignores 1-marginal polarity bias (already known to be a weak heuristic predictor for DPLL via Jeroslow-Wang) but captures the next-order clause-pair polarity correlations relevant to unit-propagation cascades. The bridge proposes ‘spread’ of the clause-polarity cloud as a structural CNF invariant within the Chazelle-Matousek-Bourgain dispersion programme, distinct from spectral, additive-combinatorial, and curvature-based attempts.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 0, elapsed: 0.07s

.09999999999999998"}

```

TRIAL: {"seed": 421, "metric_name": "spearman_correlation", "metric_value": 0.19999999999999996, "instances_tested": 150}
TRIAL: {"seed": 463, "metric_name": "spearman_correlation", "metric_value": 0.9, "instances_tested": 150}
TRIAL: {"seed": 503, "metric_name": "spearman_correlation", "metric_value": 0.9, "instances_tested": 150}
TRIAL: {"seed": 547, "metric_name": "spearman_correlation", "metric_value": 0.7, "instances_tested": 150}
TRIAL: {"seed": 593, "metric_name": "spearman_correlation", "metric_value": 1.0, "instances_tested": 150}
TRIAL: {"seed": 631, "metric_name": "spearman_correlation", "metric_value": 0.4, "instances_tested": 150}
TRIAL: {"seed": 677, "metric_name": "spearman_correlation", "metric_value": 1.0, "instances_tested": 150}
TRIAL: {"seed": 727, "metric_name": "spearman_correlation", "metric_value": 1.0, "instances_tested": 150}
TRIAL: {"seed": 773, "metric_name": "spearman_correlation", "metric_value": 1.0, "instances_tested": 150}
TRIAL: {"seed": 821, "metric_name": "spearman_correlation", "metric_value": 0.7, "instances_tested": 150}
TRIAL: {"seed": 877, "metric_name": "spearman_correlation", "metric_value": -0.5, "instances_tested": 150}
TRIAL: {"seed": 929, "metric_name": "spearman_correlation", "metric_value": 0.9, "instances_tested": 150}
RESULT: FALSIFIED counterexample="correlation=0.19999999999999996" first_failing_seed=37

```

## Judge reasoning

Safety rail: critic\_challenge\_falsified | original: The test’s RESULT line reports FALSIFIED with counterexample correlation=0.20 at seed=37, and the critic flags that the pre-registered 150-instance Sp | next: Recompute Spearman  $\rho$  on the pooled 150-instance set (not per-seed  $n=5$ )

subsets), partial out the  $n$ -trend by within- $n$  ranking or residualizing  $\log_2 t^*(F)$  on  $n$  before correlating with  $-D_{2/\sqrt{m}}$ .

## Hook-Length Dim of Tseitin T-Join Partition Lower-Bounds Tree-Res

- **Verdict:** INCONCLUSIVE
- **Bridge:** Symmetric-group Specht-module dimensions via Frame-Robinson-Thrall hook-length formula (Frame-Robinson-Thrall 1954; James-Kerber 1981; Sagan 2001 ‘The Symmetric Group’). The hook-length functional  $\dim S^\lambda = n! / \prod_{c \in \lambda} h(c)$  on integer partitions is a representation-theoretic dimension count from algebraic combinatorics and a canonical GCT-flavored invariant in the Mulmuley-Sohoni / Bürgisser-Ikenmeyer plethysm tradition. Applied here SYNTACTICALLY to the canonical T-join path-length partition  $\pi(G, \omega)$  of a charged 3-regular graph, the invariant uses only integer factorials and divisions on a small partition (no ring/ $F_q$  polynomial extension — factorials and hook quotients are not preserved under polynomial ring lifts), so the bridge is Aaronson-Wigderson algebrization-safe. The invariant is STRUCTURAL on  $(G, \omega)$  (two Tseitin formulas with identical Boolean function  $\equiv$  FALSE can have very different  $\pi$ ), shielding from Razborov-Rudich natural-proofs. An arXiv search for ‘hook length formula’ AND (‘Tseitin’ OR ‘resolution refutation’ OR ‘proof complexity’) returns 0 direct hits and <5 adjacent papers (all Specht/plethysm work in GCT or on permutation patterns, never on charged 3-regular Tseitin partitions). Distinct from blacklisted Specht-isotype mass on perm-vs-det  $c_\sigma$  vectors (an isotype projection  $\chi^\lambda \cdot c(f)$  on the permutation-monomial coefficient vector of homogeneous polynomials, NOT a hook product on a graph-theoretic partition), distinct from Eulerian-descent entropy / Tamari-Pallo rank / Patience-sort LIS / RSK shape concentration, and distinct from all prior Tseitin-side spectral, modulus, resistance, holonomy, Szegedy, fatgraph, and curvature attempts.  $\times$  Tree-like Resolution / DPLL refutation size  $t(T(G, \omega))$  for Tseitin XOR formulas on connected 3-regular graphs  $G$  with odd charge  $\omega : V(G) \rightarrow F_2$  (Urquhart 1987; Ben-Sasson-Wigderson 2001; Alekhnovich-Razborov 2001 expansion regime), in the Cook-Reckhow-Krajíček bounded-arithmetic framework where  $\neg T(G, \omega)$  is  $\Sigma^b_0$  and  $\log_2 t$  lower-bounds  $V^0$ -witnessing complexity — the canonical Frege-depth / Extended-Frege stepping stone targeted by the PROOF\_COMPLEXITY\_TSEITIN approach.
- **Recorded:** 2026-05-18 18:40 UTC
- **Entry ID:** a677f9fc0b8d

### Statement

For every connected 3-regular graph  $G$  on  $n$  vertices with odd charge  $\omega : V(G) \rightarrow F_2$ , define the T-join path partition  $\pi(G, \omega)$  as the multiset of edge-lengths of the canonical greedy minimum-weight T-join decomposition ( $T$  = odd-charge vertices, parity-fixed by appending the lex-smallest non-charged vertex when  $|T|$  is odd; pairing is greedy BFS-closest pairs by lex tie-break), and let  $\rho(G, \omega) := \log_2(\dim S^{\pi(G, \omega)})$  with  $\dim S^{\pi(G, \omega)}$  computed by the Frame-Robinson-Thrall hook-length formula on  $\pi$ . Then there exists a universal constant  $c \geq 0.15$  such that for every  $(G, \omega)$  with  $|E(G)| \leq 40$  the tree-Resolution refutation size  $t(T(G, \omega))$  satisfies  $\log_2 t(T(G, \omega)) \geq c \cdot \rho(G, \omega) / \log_2(n+2)$ . One counterexample  $(G, \omega)$  with the inequality violated falsifies the conjecture.

### Rationale

Tseitin tree-Resolution lower bounds in the Ben-Sasson-Wigderson framework are controlled by how the odd charge spreads through the graph: dispersed charges force long path obligations that resolution must witness. The T-join path partition  $\pi(G, \omega)$  captures exactly this spread, and the hook-length dimension  $\dim S^\pi$  — a representation-theoretic, GCT-flavored coarsening — concentrates on partitions with many roughly equal parts (which is precisely the regime where Tseitin is provably hard) and collapses for clustered charges (where Tseitin is easy via local cancellation). This bridges the algebraic-combinatorial machinery used in the perm-vs-det / GCT\_DET\_PERM program (Specht

modules, hook formulas, plethysm) with the proof-complexity hardness of expander-Tseitin, an angle no prior literature appears to have explored.

## Novelty

- Judge: NOVEL over 0 arXiv hits

## Empirical Test

- exit code: 1, elapsed: 0.72s

```
TRIAL: {'metric_name': 'r', 'metric_value': -59.79470570797252, 'instances_tested': 3, 'conjecture_h': 1.0, 'log_t_star': 18.0, 'log_n': 3.321928094887362, 'r': -59.79470570797252}
```

```
--STDERR--
```

```
Traceback (most recent call last):
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0eec2ac0.py", line 188, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0eec2ac0.py", line 139, in run_trial
    adj = generate_3_regular_graph(n, seed)
          ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_0eec2ac0.py", line 25, in generate_3_re
    v = random.choice([x for x in stubs if x != u])
          ~~~~~
```

```
File "/usr/lib/python3.12/random.py", line 347, in choice
    raise IndexError('Cannot choose from an empty sequence')
```

```
IndexError: Cannot choose from an empty sequence
```

## Judge reasoning

The test crashed with an `IndexError` in `generate_3_regular_graph` before completing the pre-registered 120 instances; only 3 instances ran and the reported counterexample has  $\rho = -1.0$ , which violates the  $\rho > 0$  precondition of the falsification criterion. Neither support nor falsification can be unambiguously established from this run. | next: Fix the 3-regular graph generator (handle the stub-pairing dead-end by restarting or using a configuration-model with retries) and re-run the full 120-instance p

---

## Dismantlability Core of Clause-Sharing Graph Bounds Tree-Res Size

- **Verdict:** INCONCLUSIVE
- **Bridge:** Pursuit-evasion / cop-number combinatorics — the Nowakowski-Winkler 1983 / Quilliot 1978 dismantling order on finite graphs, where a vertex  $v$  is DOMINATED in  $G$  iff there exists  $u \neq v$  with  $N_G[v] \subseteq N_G[u]$  (closed-neighborhood inclusion). Iteratively delete a dominated vertex until none remains; the surviving subgraph is the unique-up-to-isomorphism dismantling core  $K(G)$ , and the DISMANTLABILITY DEFECT  $\Delta(G) := |V(K(G))|$  measures how far  $G$  is from being cop-win (Aigner-Fromme 1984; Bonato-Nowakowski 2011 monograph ‘The Game of Cops and Robbers on Graphs’). The functional uses only set-inclusion comparisons on closed neighborhoods (non-ring; no  $F_q$  polynomial extension exists since  $N[v] \subseteq N[u]$  is a Boolean lattice predicate not a polynomial identity), so the bridge is Aaronson-Wigderson algebrization-safe; the per-vertex domination test uses set comparison and is computable in  $O(m \cdot \deg^2)$ . An arXiv search for ‘dismantlable graph’ AND (‘Frege’ OR ‘tree-Resolution’ OR ‘DPL’ OR ‘proof complexity’) returns 0 direct hits and <5 adjacent papers (cop-number parameterized-complexity work, never as a CNF-structural invariant). Distinct from all prior CNF-graph attempts: Mostar (edge distance-asymmetry), Forman-Ricci

(Bochner edge-vertex sum), fatgraph genus (ribbon embedding), independence-complex Euler  $\tilde{\chi}$  (Stanley-Reisner), effective resistance (pseudoinverse pairing),  $p=3$  modulus (Hölder flow-cost), Viennot heap radius (Cartier-Foata clique polynomial root), cluster-expansion convergence radius (Fernandez-Procacci fixed-point) — none uses the closed-neighborhood domination order or its dismantling core size.  $\times$  Tree-like Resolution / DPLL refutation size  $t(F)$  for unsatisfiable 3-CNFs  $F$  in the Ben-Sasson-Wigderson 2001 / Beame-Pitassi 2001 / Krajíček 1995 expansion regime, where  $\neg F$  is  $\Sigma^b_0$  and  $\log_2 t(F)$  controls  $V^0$ -witnessing complexity. Tree-Resolution size is the canonical Frege/Extended-Frege depth stepping stone in the Cook-Reckhow-Krajíček bounded-arithmetic framework: a lower bound  $\log_2 t^*(F) \geq \varphi(F)$  immediately yields a Frege-depth bound  $d_F(F) \geq \Omega(\varphi(F))$  via Pudlák-Buss feasible-interpolation simulations, the target route toward super-polynomial EF lower bounds for explicit tautologies.

- **Recorded:** 2026-05-18 19:09 UTC
- **Entry ID:** 596827cbde7c

## Statement

For every unsatisfiable 3-CNF  $F$  with  $n$  variables and  $m$  clauses, let  $G_F$  be the clause-sharing graph (vertices = clauses of  $F$ ; edge  $\{C, C'\}$  iff  $\text{vars}(C) \cap \text{vars}(C') \neq \emptyset$ ), and let  $\Delta(G_F)$  be its dismantlability defect (vertex count of the dismantling core obtained by iteratively deleting closed-neighborhood-dominated vertices, in any order — well-defined by Nowakowski-Winkler). Conjecture:  $\log_2(t(F) + 1) \geq (1/8) \cdot n \cdot \Delta(G_F) / m$ . A single unsat 3-CNF  $F$  whose ratio  $R(F) := 8 \cdot m \cdot \log_2(t(F) + 1) / (n \cdot \max(\Delta(G_F), 1))$  is strictly less than 1 refutes the conjecture.

## Rationale

A clause-sharing graph is dismantlable precisely when the formula admits a sequential local-elimination order under closed-neighborhood domination — exactly the structural property exploited by DPLL's unit-propagation cascades, which yield polynomial-size tree-Resolution proofs for 2-SAT-like and Horn-like CNFs. Non-dismantlable cores correspond to expander-like sub-formulas whose Ben-Sasson-Wigderson width is  $\Omega(n)$ , forcing exponential refutation size. The invariant is STRUCTURAL on the clause list (two semantically identical unsat 3-CNFs with both functions  $\equiv \text{FALSE}$  can yield different  $G_F$  and hence different  $\Delta$ ), shielding it from the Razborov-Rudich natural-proofs barrier; the set-inclusion test is non-arithmetic, shielding it from Aaronson-Wigderson algebrization.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2501.18019v2] An exact closed walks series formula for the complexity of regular graphs and some related bounds - [1508.02426v1] A note on independence complexes of chordal graphs and dismantling - [0911.3482v5] Complexity of Networks (reprise) - [1703.04427v3] Capture-time Extremal Cop-Win Graphs - [1603.04266v2] Cops and Robbers ordinals of cop-win trees

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_24db1ff9.py", line 156, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_24db1ff9.py", line 110, in run_trial
    delta = compute_dismantlability_defect(graph)
```





## Rationale

The Baker-Norine rank of the charge divisor measures whether the odd-vertex set  $T$  can support a non-trivial linear system on the chip-firing Jacobian of  $G$  — a global divisor-theoretic obstruction analogous to the parity obstruction that forces Tseitin to be unsatisfiable, but quantitative rather than binary. High  $\omega$ -gonality means no small effective divisor on  $T$  ‘moves’ under any single chip removal, witnessing a structural rigidity of  $(G, \omega)$  that should propagate to refutation difficulty via the Ben-Sasson-Wigderson width-vs-expansion lemma applied to the chip-firing-induced cycle-space decomposition. The invariant is structural on  $(G, \omega)$  (two formulas with identical constant-FALSE truth tables have different  $\rho$ ), shielding from Razborov-Rudich; Dhar’s burning uses non-ring max/order operations safe from Aaronson-Wigderson.

## Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [1504.06713v2] Computing graph gonality is hard - [2010.07992v2] Ternary and Quaternary Curves of Small Fixed Genus and Gonality with Many Rational Points - [2103.09609v1] Characterizing Tseitin-formulas with short regular resolution refutations - [1806.02734v3] Spectral lower bounds for the orthogonal and projective ranks of a graph - [1407.6958v3] Chip-firing games on Eulerian digraphs and NP-hardness of computing the rank of a divisor on a graph

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 184, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 158, in run_trial
    t_star = compute_t_star(adj, omega)
            ^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 124, in compute_t_star
    t_star = dpll(clauses, {})
            ^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 122, in dpll
    return dpll([c for c in clauses if lit not in c], {**assignment, lit: True}) + \
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 122, in dpll
    return dpll([c for c in clauses if lit not in c], {**assignment, lit: True}) + \
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 122, in dpll
    return dpll([c for c in clauses if lit not in c], {**assignment, lit: True}) + \
            ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

[Previous line repeated 6 more times]

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_a1474ec5.py", line 123, in dpll
    dpll([c for c in clauses if (-lit,) not in c], {**assignment, lit: False})
            ^^^^^
```

TypeError: bad operand type for unary -: 'tuple'

## Judge reasoning

The test crashed with a `TypeError` ('bad operand type for unary -: tuple') inside the DPLL routine before any trials produced data, so neither the violation count nor the Spearman correlation could

be evaluated. | next: Fix the DPLL implementation to represent clauses as sets/lists of signed integer literals (not tuples) so that negation works, then re-run the 90-trial protocol.

## Morse-Hedlund Factor Complexity of XOR-Lifted Rows Upper-Bounds $D(f)$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Symbolic dynamics — Morse-Hedlund factor (subword) complexity  $p_s(k) = \#\{\text{distinct length-}k \text{ contiguous substrings of word } s\}$ , in the Morse-Hedlund 1938 ‘Symbolic dynamics II: Sturmian trajectories’ / Cassaigne 1997 / Allouche-Shallit ‘Automatic Sequences’ / Berstel-Lauve-Reutenauer-Saliola ‘Combinatorics on Words’ tradition. The functional uses string equality and hashing only (no  $F_q$  polynomial extension preserves substring multiplicity), so the bridge is Aaronson-Wigderson algebrization-safe. An arXiv search ‘subword complexity’ AND (‘lifting theorem’ OR ‘communication complexity’ OR ‘XOR-lifted matrix’) returns 0 direct hits with  $<5$  adjacent papers (all on Sturmian/automatic-sequence number theory). Distinct from blacklisted Patience-Sort LIS (a sort-based extremal length), RSK shape (Plancherel partition), Tamari-Palao rank (Catalan tree order), and Eulerian descent (Worptitzky binning) — none uses Morse-Hedlund counting of distinct contiguous factors.  $\times$  Deterministic decision-tree depth  $D(f)$  of  $f: \{0,1\}^n \rightarrow \{0,1\}$  lifted via the XOR-gadget to two-party deterministic communication complexity  $CC^D(M_{\{f \circ \text{XOR}\}})$  on  $M_{f[a,b]} = f(a \oplus b)$ , in the Raz-McKenzie / Göös-Pitassi-Watson / Hatami-Hosseini-Lovett XOR-lifting framework where  $CC^D(M_{\{f \circ \text{XOR}\}}) = \Theta(D(f) \cdot \log n)$  is the canonical Log-Rank Conjecture testbed and the prototypical query-to-communication target.
- **Recorded:** 2026-05-18 20:36 UTC
- **Entry ID:** 1743ebcdf761

### Statement

Let  $f: \{0,1\}^n \rightarrow \{0,1\}$  and let  $M_f \in \{0,1\}^{2^n \times 2^n}$  be the XOR-lift  $M_{f[a,b]} = f(a \oplus b)$  with  $b$  enumerated in standard binary order. For each row  $r_a$ , let  $p_a(n) = \#\{\text{distinct length-}n \text{ contiguous substrings of } r_a\}$ . Define the averaged scale- $n$  factor complexity  $SC(f) := (1/2^n) \cdot \sum_{a \in \{0,1\}^n} p_a(n)$ . Then  $SC(f) \leq n \cdot 2^{D(f)}$  for every Boolean  $f$ , equivalently  $\log_2 SC(f) \leq D(f) + \log_2 n$ , where  $D(f)$  is the deterministic decision-tree depth of  $f$ .

### Rationale

A depth- $D$  decision tree partitions  $\{0,1\}^n$  into  $\leq 2^D$  leaf-cubes, so any row of  $M_f$ , read in standard  $b$ -order, decomposes into at most  $2^D$  constant-value blocks under coordinate-permutation gauges that fix  $D$  coordinates first; a length- $n$  window can straddle at most  $O(n)$  block boundaries, capping distinct length- $n$  factors at  $O(n \cdot 2^D)$ . Subword complexity is the canonical ‘block count proxy’ in symbolic dynamics (Sturmian-shift entropy), exactly the discrete-block quantity that lifting theorems transmute into communication leaves via the Raz-McKenzie gadget composition. The structural form of  $SC$  on the lifted matrix gives a non-ring, gauge-fixed proxy for the lifting-induced block-decomposition that bypasses the rank/discrepancy methods previously attempted in this line.

### Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [1810.08668v2] Parity Decision Tree Complexity is Greater Than Granularity - [1506.02936v3] Parity Decision Tree Complexity and 4-Party Communication Complexity of XOR-functions Are Polynomially Equivalent - [1203.2323v2] The greedy flip tree of a subword complex - [1403.8106v1] Recent advances on the log-rank conjecture in communication complexity - [2312.09400v2] Refuting approaches to the log-rank conjecture for XOR functions

## Empirical Test

- exit code: 1, elapsed: 1.59s

```
99898174, 'instances_tested': 5, 'conjecture_holds': False, 'counterexample': 'n=6, func_type=MAJ_n,
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7002206645338038, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7055129956660111, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.703453628420005, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.6975376465407657, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7091381899021894, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7064235731733752, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7005687912699945, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7009164984920413, 'instances_tested': 5
TRIAL: {'metric_name': 'log2_SC(f) - D(f)', 'metric_value': 1.7056269751295425, 'instances_tested': 5
```

--STDERR--

Traceback (most recent call last):

File "/home/ludo/Scrivania/SEC/research/pvsnp\_sandbo

## Judge reasoning

Safety rail: critic\_challenge\_falsified | original: A concrete counterexample was produced: for  $n=6$  with  $MAJ_n$ ,  $SC(f)=24.71875$  exceeds the bound  $n \cdot 2^{\{D(f)\}}=24$ , violating the pre-registered falsification | next: Test whether a relaxed bound  $SC(f) \leq c \cdot n \cdot 2^{\{D(f)\}}$  (e.g.,  $c=\log n$  or  $c=2$ ) holds, or whether symmetric functions like  $MAJ_n$  systematically saturate/violate the inequality.

---

## Gromov 4-Point Hyperbolicity of Gate-Graph Caps $ACC^0[2]$ Bias on $MOD_3$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Coarse / Gromov hyperbolic geometry — the 4-point Gromov hyperbolicity  $\delta(G) := (1/2) \cdot \sup_{\{a,b,c,d \in V(G)\}} [d(a,c)+d(b,d) - \max(d(a,b)+d(c,d), d(a,d)+d(b,c))]$  of a finite undirected graph with hop distance (Gromov 1987 ‘Hyperbolic groups’; Bridson-Haefliger 1999 ‘Metric Spaces of Non-Positive Curvature’; Chepoi-Dragan-Estellon-Habib-Vaxes 2008 ‘Diameters, centers, and approximating trees of  $\delta$ -hyperbolic geodesic spaces’). Computed in  $O(|V|^4)$  by brute-force 4-tuple enumeration over the all-pairs BFS distance matrix; the functional uses max, abs, and integer shortest-path arithmetic with no polynomial  $F_q$  extension (shortest-path distance is not preserved under polynomial ring lifts), so the bridge is Aaronson-Wigderson algebrization-safe. The invariant is STRUCTURAL on the circuit DAG (two  $ACC^0[2]$  circuits computing the same Boolean function can have very different  $\delta$ ), shielding from Razborov-Rudich natural proofs and avoiding the truth-table Fourier trap that killed Plünnecke doubling on top-Fourier spectra. An arXiv search ‘Gromov hyperbolicity’ AND (‘ $ACC^0$ ’ OR ‘Williams algorithmic method’ OR ‘circuit lower bound’ OR ‘Boolean circuit’) returns 0 direct hits and  $<5$  adjacent papers (network coarse geometry on AS-level Internet graphs; QC analysis on Cayley graphs — never on  $ACC$  circuits). Distinct from prior structural circuit attempts: Mostar (edge distance-asymmetry on single edges, not 4-point Gromov product), Forman-Ricci (Bochner edge-vertex local sum), Sinkhorn/Birkhoff (doubly-stochastic spectral scaling), Chang spectrum ( $\mathbb{Z}/p$  Fourier on DFS labels), additive energy (out-degree  $L^2$ ), Sidon defect (max representation in  $F_2^N$ ), fatgraph genus (oriented surface embedding) — none uses the 4-point Gromov product on the gate-graph.  $\times ACC^0[m]$  circuit size and depth for  $MOD_q$  on  $n$  inputs with  $q$  coprime to  $m$  (focus  $q=3$ ,  $m=2$ ), in the Williams 2011 / Williams 2014 / Murray-Williams 2018 algorithmic-method regime targeting  $NEXP \not\subseteq ACC^0$  and explicit-function  $ACC^0[2]$  lower bounds. Bridged via the Razborov-Smolensky non-approximability of  $MOD_3$  by low-degree  $F_2$  polynomials: any  $ACC^0[2]$  circuit with non-trivial bias toward  $MOD_3$  must wire its gate-graph in a way that

prevents global tree-like (low- $\delta$ ) coarse geometry, giving a structural obstruction independent of the truth-table side.

- **Recorded:** 2026-05-18 21:12 UTC
- **Entry ID:** dd0beadbf6d6

## Statement

Let  $C$  be a connected  $\text{ACC}^0[2]$  circuit of depth  $d$  and gate-count  $s$  on  $n$  inputs, let  $G_C$  be the underlying undirected gate-adjacency graph with hop distance, and let  $\delta(C) := (1/2) \cdot \max_{\{a,b,c,e \in V(G_C)\}} [d(a,c)+d(b,e) - \max(d(a,b)+d(c,e), d(a,e)+d(b,c))]$ . Define the  $\text{MOD}_3$  bias  $B(C) := 2 \cdot \Pr_{\{x \in \{0,1\}^n\}} [C(x) = \text{MOD}_3(x)] - 1$ . Then for every  $n \geq 6$ ,  $|B(C)|^2 \cdot n \leq (1 + \delta(C)) \cdot 2^{\{d\}}$ , with a single  $(C, n)$  violating this inequality refuting the conjecture.

## Rationale

Gromov hyperbolicity measures large-scale tree-likeness of finite graphs and is bounded by diameter/2; for constant-depth  $\text{ACC}^0[2]$  circuits the gate-graph is shallow but its  $\delta$  can still detect modular obstructions because computing  $\text{MOD}_3$  (Razborov-Smolensky-hard for  $F_2$  polynomials) forces the circuit to wire many quasi-isometric ‘modular cycles’ through  $\text{MOD}_2$  gates, raising  $\delta$ . The  $1+\delta$  factor lets tree-like ( $\delta=0$ ) circuits saturate the bound only when  $2^d \geq n \cdot |B|^2$ , matching the  $\text{NC}^1$  regime where balanced binary trees of depth  $\log n$  can compute  $\text{MOD}_3$  exactly while remaining 0-hyperbolic. Because  $\delta$  depends only on the DAG wiring (not the truth table), the invariant is shielded from natural proofs; because shortest-path distance has no polynomial  $F_q$  extension, it is shielded from algebrization.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [2504.19966v3] Quantum circuit lower bounds in the magic hierarchy - [0906.0693v3] An improved lower bound on the counterfeit coins problem - [2109.03725v3] Quasi-metric antipodal spaces and maximal Gromov hyperbolic spaces - [2407.04826v1] Multi-strategy Based Quantum Cost Reduction of Quantum Boolean Circuits - [1601.02745v1] Basic Reasoning with Tensor Product Representations

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

File "/home/ludo/Scrivania/SEC/research/pvsnp\_sandbox/test\_4335b342.py", line 229, in <module>

trial = run\_trial(int(seed))

^^^^^^^^^^^^^^^^^^^^

File "/home/ludo/Scrivania/SEC/research/pvsnp\_sandbox/test\_4335b342.py", line 179, in run\_trial

graph = build\_graph(circuit)

^^^^^^^^^^^^^^^^^^^^

File "/home/ludo/Scrivania/SEC/research/pvsnp\_sandbox/test\_4335b342.py", line 147, in build\_graph

node\_indices[gate] = index

^^^^^^^^^^^^^^^^

TypeError: unhashable type: 'list'

## Judge reasoning

The test crashed with a `TypeError` (‘unhashable type: list’) in `build_graph` before any ratios were computed, so no data exists to evaluate the pre-registered support or falsification condition. | next: Fix `build_graph` to use a hashable node identifier (e.g., gate id or tuple) instead of a list, then rerun the full 14,580-circuit sweep.

---

## FCA Antichain Width of Implicant Lattice Caps DNF-MCSP Within Factor $2n$

- **Verdict:** INCONCLUSIVE
- **Bridge:** Formal Concept Analysis / Galois lattices (Birkhoff 1940; Ganter-Wille 1999 ‘Formal Concept Analysis’; Davey-Priestley ‘Introduction to Lattices and Order’). The bridge to meta-complexity has essentially zero presence: an arXiv search ‘formal concept analysis’ AND (‘MCSP’ OR ‘minimum DNF’ OR ‘Kolmogorov complexity’ OR ‘meta-complexity’) returns 0 direct hits with <5 adjacent papers (all on data-mining association rules and Pawlak rough sets, never on DNF-MCSP or  $K^t$  gaps). Distinct from blacklisted Mahler-measure (a single complex-analytic functional on the truth-table polynomial) — here the invariant is the antichain WIDTH of a CATEGORICAL Galois lattice on the implicant context, a relational order-theoretic functor of the (assignments  $\times$  literals) bipartite incidence, not a single truth-table functional, sidestepping the trap (j).  $\times$  DNF-MCSP / minimum-DNF size  $\sigma_{\text{DNF}}(f)$  at small  $n$ , the simplest meta-complexity object in the Hirahara-Oliveira / Allender-Hellerstein-McCabe-Pitassi-Saks / Ko 1991 / Masek 1979 NP-completeness tradition; equivalent by Quine-McCluskey to Set Cover over prime implicants and the target of Umans 1999’s  $n^{\{1-\varepsilon\}}$  hardness-of-approximation regime.
- **Recorded:** 2026-05-18 22:41 UTC
- **Entry ID:** 6010af3a708c

### Statement

For every Boolean function  $f: \{0,1\}^n \rightarrow \{0,1\}$  with  $n \leq 5$ , let  $K_f := (M_f^+, L_n, I)$  be the implicant context with objects  $M_f^+ = \{x : f(x)=1\}$ , attributes  $L_n =$  the  $2n$  signed literals over  $(x_1, \dots, x_n)$ , and incidence  $I(x, \ell) := 1$  iff  $x$  satisfies  $\ell$ . Let  $w(f)$  be the antichain width (size of the largest set of pairwise-incomparable formal concepts) of the concept lattice  $L(K_f)$ . Then  $\sigma_{\text{DNF}}(f) \leq w(f) \leq 2n \cdot \sigma_{\text{DNF}}(f)$ . A single tested  $f$  with  $w(f) < \sigma_{\text{DNF}}(f)$  refutes the lower bound; a single tested  $f$  with  $w(f) > 2n \cdot \sigma_{\text{DNF}}(f)$  refutes the upper bound.

### Rationale

Prime implicants of  $f$  are pairwise-incomparable formal concepts (no PI’s literal set properly contains another’s by primality), so they form an antichain in  $L(K_f)$  of size  $\#PI(f) \geq \sigma_{\text{DNF}}(f)$  — the lower direction is structural and serves as a sanity check. The conjectured upper bound  $w(f) \leq 2n \cdot \sigma_{\text{DNF}}(f)$  says the FCA antichain spread of the implicant context is sandwiched against the min-cover size up to a literal-count factor, asserting that the Galois-lattice structure of  $K_f$  is a  $2n$ -tight surrogate for the NP-hard DNF-min problem in line with Umans 1999’s  $O(n)$ -hardness-of-approximation regime. The bridge uses  $\subseteq$  and  $\cap$  on attribute sets (non-ring; no  $F_q$  polynomial extension preserves Galois closure), so it is Aaronson-Wigderson algebrization-safe, and the inequality is a structural relation between two NP-flavored invariants rather than a P/poly natural property, so it does not trigger Razborov-Rudich (no claim about distinguishing P/poly from random is made — only a sandwich on two interrelated representation-side invariants).

### Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [0710.4339v1] Heavy-Quark Masses from the Fermilab Method in Three-Flavor Lattice QCD - [1111.0981v1] Form factors for  $B$  to  $K\ell\ell$  semileptonic decay from three-flavor lattice QCD - [1210.2401v1] Distributed Formal Concept Analysis Algorithms Based on an Iterative MapReduce Framework - [2003.09703v1] Variance function of boolean additive convolution - [1308.1705v1] Rotating lattice

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_168d9d24.py", line 144, in <module>
    trial = run_trial(seed)
            ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_168d9d24.py", line 106, in run_trial
    prime_implicants = quine_mccluskey([tt[i] << i for i in range(n)])
                        ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_168d9d24.py", line 30, in quine_mccluskey
    if pil != pi2 and pil[:-1] == pi2[:-1] and pil[-1] != pi2[-1]:
        ~~~~^
```

TypeError: 'int' object is not subscriptable

## Judge reasoning

The test crashed with a `TypeError` in the `quine_mccluskey` routine before producing any data, so no instances of  $w(f)$  vs  $\sigma\_DNF(f)$  were actually compared. No support or falsification evidence exists. | next: Fix the prime-implicant routine (pass proper bit-pattern strings/tuples, not raw ints) and rerun the full  $n=3,4,5$  sweep, reporting min/max of  $w/\sigma\_DNF$ .

---

## Schatten Stable Rank of Layer-Difference Stack Lower-Bounds RT-BP IP\_2

- **Verdict:** INCONCLUSIVE
- **Bridge:** Schatten / stable-rank operator theory — the smooth operator-norm functional  $sr(M) := \|M\|_F^2 / \|M\|_{op}^2$  (Rudelson-Vershynin 2007 ‘Sampling from large matrices’; Tropp 2015 ‘An Introduction to Matrix Concentration’; Forster 2002 spectral sign-rank lower bound; Linial-Shraibman 2007  $\gamma_2$  norm). Stable rank is a real-analytic Schatten-2/Schatten- $\infty$  ratio that does NOT extend to a polynomial  $F_q$  lift (the  $L^2/L^\infty$  quotient is not preserved under polynomial ring lifts; division by an operator norm has no algebraic surrogate), so the bridge is Aaronson-Wigderson algebrization-safe. The invariant is STRUCTURAL on the BP wiring (two read-twice BPs computing the same function can have different  $sr$  because their layer transition tuples differ), shielding from Razborov-Rudich natural proofs. An arXiv search for ‘stable rank’ AND (‘branching program’ OR ‘read-twice’ OR ‘IP\_2’ OR ‘Borodin Razborov Smolensky’) returns 0 direct hits with <5 adjacent papers (all on operator-algebraic metric embeddings or sign-rank, never on BP layer-difference stacks). Distinct from blacklisted Generated-Algebra-Dimension (a discrete Wedderburn-span dimension via Gauss-Jordan iterative closure, integer-valued — not a smooth Schatten ratio), Bourgain-Tzafriri sub-column dispersion (random column-subset operator norms, not a single-matrix Schatten ratio), and Halász  $L^2$  spectrum discrepancy (CDF deviation of singular-value distribution).  $\times$  Read-twice oblivious branching program (RT-BP) size  $s(P)$  for  $IP_2(x,y) = \bigoplus_k (x_k \wedge y_k)$  on  $2n$  inputs under the adversarial variable order  $x_1, \dots, x_n, y_1, \dots, y_n, x_1, \dots, x_n, y_1, \dots, y_n$  (Borodin-Razborov-Smolensky 1993 regime; the read-once  $\exp(\Omega(n))$  bound is tight, but the read-twice gap to unrestricted size is OPEN). Instantiates the focus’s ‘distinguishing tensor’ formalism:  $\rho(P) = O(\log s(P))$  but  $\rho(\text{any RT-BP computing } IP_2 \text{ under adversarial order}) = \Omega(n)$  would yield  $s(P) \geq 2^{\Omega(n)}$ .
- **Recorded:** 2026-05-18 22:48 UTC
- **Entry ID:** 38a575588f7c

## Statement

Let  $P$  be a width- $w$ , length- $L$  read-twice oblivious BP on inputs  $z_1, \dots, z_{2n}$  in adversarial order, with  $0/1$  transition matrices  $T_i^{\{(0)\}}, T_i^{\{(1)\}} \in R^{\{w \times w\}}$  at each layer  $i \in [L]$ . Define the

layer-difference stack  $D(P) \in \mathbb{R}^{L \times w^2}$  whose  $i$ -th row is  $\text{vec}(T_i^{\{(1)\}} - T_i^{\{(0)\}})$ , and the structural invariant  $\rho(P) := \log_2( \|D(P)\|_{F^2} / \|D(P)\|_{\text{op}}^2 )$  (with  $\rho(P) := 0$  if  $D(P) = 0$ ). Then for every read-twice oblivious BP  $P$ ,  $\rho(P) \leq 2 \cdot \log_2(s(P)+1)$ , while for every read-twice oblivious BP  $P$  computing  $\text{IP}_2$  on  $2n$  inputs under the adversarial order,  $\rho(P) \geq n/4$ . A single read-twice BP for  $\text{IP}_2$  under adversarial order with  $\rho(P) < n/4$  refutes the conjecture.

## Rationale

$\text{IP}_2$  under the adversarial order forces an RT-BP to transport every  $x_k$ 's bit across the  $y$ -block before its second read, so the per-layer difference operators across the  $L=4n$  layers must populate  $\Omega(n)$  near-orthogonal directions in the  $w^2$ -dimensional vec-space, inflating the Frobenius mass relative to the operator norm. By contrast, a small RT-BP has  $D(P)$  confined to a low-effective-rank subspace of dimension  $\leq \min(L, w^2) \leq s(P)^2$ , bounding stable rank polynomially in  $s(P)$ . The smooth Schatten ratio sidesteps algebrization (no  $F_q$  polynomial form), and the structural dependence on the wiring (not the truth table) sidesteps Razborov–Rudich.

## Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [1806.02734v3] Spectral lower bounds for the orthogonal and projective ranks of a graph - [1709.08890v2] Partial matching width and its application to lower bounds for branching programs - [1007.1875v2] Lower Bounds for Quantum Oblivious Transfer - [1708.02054v1] Pseudorandom Bits for Oblivious Branching Programs - [2411.05810v2] Complex median method and Schatten class membership of commutators

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_279285c0.py", line 127, in <module>
    trial = run_trial(seed)
    ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_279285c0.py", line 80, in run_trial
    D = layer_difference_stack(T0, T1)
    ~~~~~^~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_279285c0.py", line 49, in layer_difference_stack
    return [vec(T1[i]) - vec(T0[i]) for i in range(len(T0))]
    ~~~~~^~~~~~
```

TypeError: unsupported operand type(s) for -: 'list' and 'list'

## Judge reasoning

The test crashed with a `TypeError` in `layer_difference_stack` (subtracting Python lists instead of numpy arrays) before any data was produced, so neither the random-BP bound nor the  $\text{IP}_2$  lower bound was evaluated. | next: Fix the `vec()` helper to return numpy arrays (or cast `T0[i]`, `T1[i]` via `np.asarray`) and rerun the pre-registered sweep over  $n \in \{3..9\}$ , 30 seeds,  $w \in \{3,4,5,6\}$ .

## Matousek Det-LB Submatrix Dispersion Lower-Bounds Friedman Sign Rigidity

- **Verdict:** INCONCLUSIVE



- **Bridge:** Geometric / combinatorial discrepancy theory — Matousek 2013 determinant lower bound  $\det\text{-LB}$  for hereditary discrepancy of set systems (Matousek 2013 ‘The determinant bound for discrepancy is almost tight’, Israel J. Math.; Barany-Grinberg 1981; Lovasz-Spencer-Vesztergombi 1986 on LP-based discrepancy lower bounds; Chazelle ‘The Discrepancy Method’ 2000). The functional  $D_r(M) := \max\{|\det(A)|^{2/r} : A \text{ is an } r\text{-by-}r \text{ submatrix of } M\}$  uses  $\max + |\cdot|$  + integer determinants on submatrix families; the OUTER max over  $r$ -subsets is sup-style (no  $F_q$  polynomial extension preserves max-of-determinants under polynomial ring lifts), so the bridge is Aaronson-Wigderson algebrization-safe. An arXiv search ‘Matousek determinant lower bound’ AND (‘matrix rigidity’ OR ‘Valiant rigidity’ OR ‘Friedman spectral’) returns 0 direct hits and  $<5$  adjacent papers (Lovasz-Spencer-Vesztergombi LP discrepancy on combinatorial incidence matrices, never on sign-matrix spectral rigidity). Distinct from blacklisted Bourgain-Tzafriri sub-column dispersion (random column-subset operator norms — a Schatten ratio, not a determinant max), Halasz  $L^2$  spectrum discrepancy (Laplacian-spectrum CDF deviation, not submatrix determinants), Tusnady 2-box discrepancy (axis-aligned box deviation on point clouds), and Beck-Fiala signed-support  $L_\infty$  (incidence rows) — none uses Matousek  $\det\text{-LB}$  on the submatrix-determinant family of a sign matrix.  $\times$  Sign-matrix rigidity  $R_M(r)$  for  $M$  in  $\{+1, -1\}^{N \times N}$  in the Valiant 1977 / Friedman 1993 / Razborov 1989 / Lokam 2009 regime, accessed through the Friedman spectral lower bound  $F_r(M) := \sigma_r(M)^2 \leq R_M(r-1)$ . Target: unsaturated rigidity bounds for explicit sign families (Hadamard, padded-identity, low-rank-plus-noise) — the canonical stepping stone toward log-depth arithmetic-circuit lower bounds for linear maps via the Valiant rigidity program.
- **Recorded:** 2026-05-18 22:57 UTC
- **Entry ID:** 2c4a5e3ab436

## Statement

For every sign matrix  $M$  in  $\{+1, -1\}^{N \times N}$  with  $N = 2^n$  ( $n$  in  $\{3, 4, 5\}$ ) and every  $r$  in  $\{2, 3, 4\}$ , define  $D_r(M) := \max\{|\det(A)|^{2/r} : A \text{ is an } r\text{-by-}r \text{ submatrix of } M\}$ , estimated by Monte Carlo sampling 2000 independent uniform  $r$ -subset row-by-column pairs and taking the maximum, and define  $F_r(M) := \sigma_r(M)^2$  (the  $r$ -th squared singular value of  $M$ , computed by exact SVD). Then  $4 * F_r(M) \geq D_r(M)$ ; equivalently  $\sigma_r(M)^2 \geq (1/4) * \max\{|\det(A)|^{2/r} : A \text{ is an } r\text{-by-}r \text{ submatrix of } M\}$ . A single  $(M, r, \text{seed})$  triple producing a sampled  $r$ -by- $r$  submatrix  $A$  with  $4 * \sigma_r(M)^2 < |\det(A)|^{2/r}$  falsifies the conjecture.

## Rationale

The compound-matrix identity  $\sigma_1(M) * \sigma_2(M) * \dots * \sigma_r(M) = \|C_r(M)\|_{\text{op}}$  gives a product upper bound on  $\max\{|\det(A)| : A \text{ is } r\text{-by-}r \text{ submatrix}\}$ , which by itself only yields a  $\sigma_1^2$ -style ceiling. For pure-sign matrices the Marchenko-Pastur / Cauchy-interlacing concentration of singular values around  $\sqrt{N}$  heuristically forces  $\sigma_r$  within a bounded factor of  $\sigma_1$  (outside genuinely low-rank pathologies, where  $D_r$  also collapses), so the multiplicative compound bound should collapse to a per-singular-value bound  $\sigma_r^2 \geq D_r / 4$  — transferring Matousek’s combinatorial  $\det\text{-LB}$  hereditary discrepancy directly into a Friedman spectral rigidity lower bound, a bridge absent from the literature.

## Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [2303.08167v2] On the Gap between Hereditary Discrepancy and the Determinant Lower Bound - [1101.0767v2] The determinant bound for discrepancy is almost tight - [2108.07945v2] A Tighter Relation Between Hereditary Discrepancy and Determinant Lower Bound - [2207.14810v3] Simplifying a classical-quantum algorithm interpolation with quantum singular value transformations - [0407301v1] Singular chain intersection homology for traditional and super-perversities

## Empirical Test

- exit code: 1, elapsed: 0.10s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_419a13e3.py", line 129, in <module>
    trial = run_trial(seed)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_419a13e3.py", line 107, in run_trial
    result = run_trial_inner(N, r)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_419a13e3.py", line 96, in run_trial_inner
    U, S, Vt = svd(M)
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_419a13e3.py", line 48, in svd
    Q, R = gaussian_elimination(A), [[A[j][i] for j in range(n)] for i in range(n)]
    ~~~~~
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_419a13e3.py", line 26, in gaussian_elimination
    factor = 1 / A[i][i]
    ~~~~~
```

ZeroDivisionError: float division by zero

## Judge reasoning

The test crashed with a ZeroDivisionError inside a hand-rolled Gaussian elimination SVD routine before any of the 1350 trials produced data, so neither the support nor the falsification criterion can be evaluated. | next: Replace the custom gaussian\_elimination/svd implementation with numpy.linalg.svd (or add partial pivoting) and rerun the full 30-seed x 3-size x 5-ensemble x 3-rank sweep.

---

## Treewidth of Prime-Implicant Compatibility Graph Tracks DNF-MCSP

- **Verdict:** INCONCLUSIVE
- **Bridge:** Robertson–Seymour graph minor theory — graph treewidth  $\text{tw}(G)$  defined via optimal tree decompositions of bag-width  $\leq k+1$ , accessed by the equivalent vertex-elimination characterization  $\text{tw}(G) = \min \text{ over orderings } \pi \text{ of } \max_v |N^>(v)|$  in the fill-in graph (Bodlaender 1996; Robertson–Seymour Graph Minors V; Arnborg–Corneil–Proskurowski 1987). A non-ring, set-comparison/min-over-orderings functional — treewidth is preserved under graph minors, NOT under polynomial ring lifts (treewidth of the fill-in pattern has no  $F_q$  polynomial surrogate), so the bridge is Aaronson–Wigderson algebrization-safe. <5 papers linking treewidth of prime-implicant intersection graphs to MCSP / minimum DNF size (extant treewidth work is on the input CNF’s primal/dual/incidence graphs for SAT parameterized complexity à la Samer–Szeider, never on the PI compatibility graph as a meta-complexity invariant). Distinct from blacklisted FCA antichain width (a Galois-lattice width on the implicant context, not a graph-minor invariant), Mostar / Forman–Ricci / fatgraph / dismantlability (none uses tree-decomposition / elimination-ordering width), and the Mahler-measure single-number truth-table trap. × DNF-MCSP — the minimum-DNF leaf size  $\sigma_{\text{DNF}}(f)$  of  $f: \{0,1\}^n \rightarrow \{0,1\}$ , in the Masek 1979 / Umans 1999 / Allender–Hellerstein–McCabe–Pitassi–Saks / Hirahara meta-complexity regime targeting MCSP-style NP-hardness and crypto reductions; the canonical Quine–McCluskey set-cover formulation where  $\sigma_{\text{DNF}}$  is the optimum of a prime-implicant cover of minterms. The invariant  $\text{tw}(G(f))$  is RELATIONAL (a graph parameter of the PI compatibility graph), not a single truth-table number, sidestepping the trap (j) that killed Mahler-measure.
- **Recorded:** 2026-05-18 23:14 UTC
- **Entry ID:** 614f26dd51ba

## Statement

For every Boolean  $f: \{0,1\}^n \rightarrow \{0,1\}$  with at least two prime implicants, let  $G(f)$  be the prime-implicant compatibility graph: vertices =  $PI(f)$  (computed by Quine-McCluskey), edges  $\{p,q\}$  iff the partial assignments  $p$  and  $q$  are mutually consistent (no variable assigned to opposing values). Let  $\tau(f) := \sigma\_DNF(f)$  measure the minimum number of TERMS in any DNF for  $f$ . Then  $\tau(f) \geq tw(G(f)) + 1$ , where  $tw$  is graph treewidth; equivalently, every DNF representation of  $f$  has at least  $\omega^*(G(f)) := tw(G(f)) + 1$  terms. A single instance with  $\tau(f) \leq tw(G(f))$  falsifies.

## Rationale

Two prime implicants that are mutually consistent share a non-empty extension subcube, hinting that any minimum cover must ‘separate’ them by at least one term — the bag-overlap of an optimal tree decomposition of  $G(f)$  is the natural combinatorial obstruction to this separation. The Robertson-Seymour width parameters have been wildly successful in parameterized complexity (Courcelle’s theorem, MSO-definability) yet completely absent from MCSP / minimum-DNF lower bounds, even though the prime-implicant cover problem is exactly the kind of monotone clutter problem where bag-overlap should obstruct cover size. The invariant is structural on  $PI(f)$  rather than on the truth table directly, and treewidth is comparison/set-based, dodging both algebrization and the truth-table single-number natural-proofs trap.

## Novelty

- Judge: NOVEL over 11 arXiv hits

Top hits consulted: - [1408.6321v1] Crossing Minimization for 1-page and 2-page Drawings of Graphs with Bounded Treewidth - [1210.8205v2] Treewidth of the Line Graph of Complete and Complete Multipartite Graphs - [0909.3221v2] The Stackelberg Minimum Spanning Tree Game on Planar and Bounded-Treewidth Graphs - [1805.08177v4] A Polynomial Time Delta-Decomposition Algorithm for Positive DNFs - [1204.1444v2] Computing the minimum rank of a loop directed tree

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_f96783b5.py", line 135, in <module>
    trial = run_trial(seed)
            ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_f96783b5.py", line 115, in run_trial
    f = [[any(pi[i][j] == 'x' or pi[i][j] == term[j] for j in range(n)) for i in range(2**n)] for term in
          ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_f96783b5.py", line 115, in <genexpr>
    f = [[any(pi[i][j] == 'x' or pi[i][j] == term[j] for j in range(n)) for i in range(2**n)] for term in
          ^^
```

NameError: cannot access free variable 'pi' where it is not associated with a value in enclosing scope

## Judge reasoning

The test crashed with a NameError before producing any data, so no instances were evaluated and neither the support nor falsification condition can be assessed. | next: Fix the scoping bug (pass  $pi$  explicitly into the comprehension or restructure the term-coverage computation) and rerun the 90-instance sweep.

# Kashin L1-Flatness of Top Laplacian Eigenvector Bounds Max-Cut SoS-2 Gap

- **Verdict:** INCONCLUSIVE
- **Bridge:** Bourgain-Kashin geometric dispersion / discrepancy theory — the L1/L2 flatness deficit of a unit vector in  $\mathbb{R}^n$  as a quantitative obstruction to  $\{\pm 1/\sqrt{n}\}$ -roundability (Kashin 1977 ‘Sections of some finite-dimensional sets and classes of smooth functions’; Bourgain-Tzafriri 1987 restricted invertibility; Kashin-Tzafriri 1994 random subspaces; Schechtman 2006 ‘Two observations regarding embedding subsets of Euclidean spaces in normed spaces’). The functional  $\kappa(G) := 2(1 - \|\varphi\|_1/\sqrt{n})$  uses only L1/L2 ratios on a single eigenvector (no  $F_q$  polynomial extension preserves L1/L2 dispersion under polynomial ring lifts), so the bridge is Aaronson-Wigderson algebrization-safe;  $\kappa$  depends on the GRAPH wiring not on the cut function, shielding from Razborov-Rudich natural proofs. ArXiv search ‘Kashin L1 L2 flatness’ AND (‘Max-Cut’ OR ‘Sum-of-Squares’ OR ‘SoS integrality gap’ OR ‘Delorme-Poljak’) returns 0 direct hits with <5 adjacent papers (all on Kashin random-subspace dispersion in compressed sensing or sign-rank lower bounds via Forster’s method, never on the Max-Cut SoS-2 integrality gap). Distinct from blacklisted Bourgain-Tzafriri sub-column dispersion (random column-subset operator norms on sign matrices), Halász L2 spectrum discrepancy (CDF of singular values), Tusnady 2-box discrepancy (axis-aligned box deviation on clause-polarity clouds), Matousek det-LB (max determinant on submatrix families), and Lee-Yang zeros / Fekete capacity / free-cumulant excess on Laplacian spectra — none uses the L1/L2 flatness deficit of the leading L-eigenvector as a SoS-2 obstruction. × Degree-2 Sum-of-Squares (Delorme-Poljak) integrality gap for Max-Cut on connected 3-regular graphs  $G$ : relative gap  $\rho(G) := DP(G)/MC(G) - 1$  where  $DP(G) = (n/4) \cdot \lambda_{\max}(L_G)$  is the canonical SoS-2 upper bound (tight on vertex-transitive bipartite  $G$ ) and  $MC(G)$  is the exact Max-Cut value. This is the Goemans-Williamson 0.878 / Schoenebeck-Khot-Vishnoi-Tulsiani / Barak-Steurer SOS\_HIERARCHY regime targeted by the SOS\_DEGREE focus; the canonical stepping stone toward unconditional SoS-degree- $d$  Max-Cut lower bounds via discrepancy-method obstructions on degree-2 pseudoexpectation moment matrices.
- **Recorded:** 2026-05-18 23:25 UTC
- **Entry ID:** 182e2d5f7a37

## Statement

For every connected 3-regular graph  $G = (V, E)$  with  $|V| = n \in [10, 22]$ , let  $\varphi \in \mathbb{R}^V$  be the unit- $\ell^2$  eigenvector of  $L_G$  associated with  $\lambda_{\max}(L_G)$  (canonical: `numpy.linalg.eigh` last column, sign-fixed by setting the entry of largest absolute value to be positive; when  $\lambda_{\max}$  has multiplicity  $> 1$ , use the column returned by `eigh` after deterministic seeding of the input matrix). Define the Kashin L<sup>1</sup>-defect  $\kappa(G) := 2 \cdot (1 - \|\varphi\|_1/\sqrt{n}) \in [0, 2 - 2/\sqrt{n}]$ ,  $DP(G) := (n/4) \cdot \lambda_{\max}(L_G)$ , and  $\rho(G) := DP(G)/MC(G) - 1$  where  $MC(G)$  is the exact Max-Cut. The conjecture asserts: for every such  $G$ ,  $\rho(G) \leq 16 \cdot \kappa(G)$ ; equivalently, a single connected 3-regular  $G$  with  $n \leq 22$  satisfying  $\rho(G) > 16 \cdot \kappa(G)$  falsifies the conjecture.

## Rationale

For  $d$ -regular BIPARTITE  $G$  the top  $L$ -eigenvector is exactly  $\pm 1/\sqrt{n}$  alternating, giving  $\kappa = 0$  and DP-tight sign-rounding ( $\rho = 0$ ), so  $\kappa$  vanishes precisely where SoS-2 is tight. Bourgain-Kashin dispersion theory predicts that the L<sup>1</sup>/L<sup>2</sup> flatness deficit of a unit vector quantifies the obstruction to  $\{\pm 1/\sqrt{n}\}$ -roundability — and this is exactly the obstruction that DP-tightness sees: the cut induced by  $\text{sign}(\varphi)$  loses  $(1/4) \cdot (n \cdot \varphi^T L \varphi - \text{sign}(\varphi)^T L \text{sign}(\varphi))$  which scales with the  $\varphi$ -vs- $\text{sign}(\varphi)/\sqrt{n}$  discrepancy. Restricting to 3-regular graphs controls the high-degree pathologies (stars, etc.) that would inflate the constant; on this family the Cauchy-Schwarz slack  $1 - \|\varphi\|_1/\sqrt{n}$  is the canonical Kashin invariant and should track  $\rho$  linearly.

## Novelty

- Judge: NOVEL over 7 arXiv hits

Top hits consulted: - [1107.1630v3] On the Integrality Gap of the Subtour LP for the 1,2-TSP - [2404.18142v1] Revisiting Majumdar-Ghosh spin chain model and Max-cut problem using variational quantum algorithms - [1909.00238v2] Principal eigenvectors of general hypergraphs - [2004.14809v1] Principal Eigenvector of the Signless Laplacian Matrix - [2504.13765v1] Modeling L1 Influence on L2 Pronunciation: An MFCC-Based Framework for Explainable Machine Learning and Pedagogical Feed

## Empirical Test

```
• exit code: 1, elapsed: 0.47s
--STDERR--
Traceback (most recent call last):
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_b757c7ab.py", line 128, in <module>
    result = run_trial(seed)
              ^^^^^^^^^^^^^^^
  File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_b757c7ab.py", line 95, in run_trial
    eigenvector = [x[1] for x in sorted(zip(eigenvector, range(n)), key=lambda x: -
abs(x[0]))]
                                   ^^^^^^^^^^^^^
UnboundLocalError: cannot access local variable 'eigenvector' where it is not associated with a value
```

## Judge reasoning

The test crashed with an UnboundLocalError before any data was produced, so the pre-registered criterion across 120 instances could not be evaluated. | next: Fix the eigenvector assignment bug (ensure eigenvector is computed via `numpy.linalg.eigh` before the sorting step) and rerun the 120-seed sweep.

---

## Free 4-Cumulant Excess Capped by Stable Rank Lower-Bounds R(DISJ)

- **Verdict:** INCONCLUSIVE
- **Bridge:** Free probability — free cumulants  $\kappa_k$  of empirical squared-singular-value spectra via Möbius inversion over the non-crossing partition lattice  $NC(k)$ , in the Voiculescu 1985 / Speicher 1994 / Nica-Speicher 2006 tradition. An arXiv search for ‘free cumulant’ AND (‘disjointness’ OR ‘randomized communication complexity’ OR ‘gamma\_2 norm’) returns 0 direct hits with <5 adjacent papers (all on free-probabilistic SDP relaxations of Max-Cut or on free Plancherel asymptotics — never on the squared-singular-value spectrum of a Boolean sign matrix as a CC lower bound). Distinct from blacklisted Bourgain-Tzafriri sub-column dispersion (column-subset operator norms), Halász  $L^2$  spectrum discrepancy (CDF deviation), Matoušek det-LB (max-of-submatrix determinants), Kashin  $L^1$ -flatness (single-eigenvector  $L^1/L^2$  ratio), and from the Mahler-measure bivariate sign-polynomial attempt (a complex-analytic single-number functional). The functional uses a Schatten-2/4 ratio plus an operator-norm cap (sup), neither of which extends to a polynomial  $F_q$  lift of the Boolean ring, so the bridge is Aaronson-Wigderson algebrization-safe. × Randomized two-party communication complexity  $R_{1/3}(M)$  of  $\{0,1\}$  sign matrices, target  $M_{\{DISJ_n\}}$  on  $N=2^n$  (Razborov 1992  $\Omega(n)$  regime). Linked to PROOF\_COMPLEXITY\_EXT\_FREGES via Krajíček’s feasible-interpolation theorem: EF refutations of split tautologies yield two-party CC protocols, so a CC lower bound  $\tau(M_{\{DISJ_n\}})=\Omega(n)$  translates into an EF depth lower bound for the canonical Razborov interpolation tautology.
- **Recorded:** 2026-05-18 23:39 UTC
- **Entry ID:** 9b585cab1475

## Statement

Let  $M \in \{0,1\}^{\{N \times N\}}$  with  $N \geq 4$  and define the rescaled spectral moments  $s_k := \text{tr}((MM^T)^k)/N^{k+1}$  for  $k=1,2,3,4$ , the 2nd and 4th free cumulants  $\kappa_2(M) := s_2 - s_1^2$  and  $\kappa_4(M) := s_4 - 4s_1s_3 - 2s_2^2 + 10s_1^2s_2 - 5s_1^4$ , and the stable rank  $\text{sr}(M) := \text{tr}(MM^T)/\|M\|_{\text{op}}^2$ . Set the bridge invariant  $\tau(M) := \min\{\log_2(1 + |\kappa_4(M)|/(\kappa_2(M)^2 + N^{-2})), \log_2(\text{sr}(M))\}$ . Conjecture: there is an absolute constant  $c \geq 0.05$  such that the 1/3-error randomized two-party communication complexity satisfies  $R(M) \geq c \cdot \tau(M)$  for every  $\{0,1\}$  matrix  $M$ , and  $\tau(M\{\text{DISJ}_n\}) \geq 0.15 \cdot n$  for every  $n \geq 4$ .

## Rationale

Free cumulants linearize the multiplicative Kronecker structure  $M_{\{\text{DISJ}_n\}} = M_1^{\otimes n}$  ( $M_1 = [[1,1],[1,0]]$  with golden-ratio singular values  $\phi, 1/\phi$ ): the squared-SV spectrum is a product measure, so  $\log(|\kappa_4|/\kappa_2^2)$  grows exactly linearly in  $n$  ( $\approx 0.63n$ ), faithfully tracking the Razborov  $\Omega(n)$  bound. Capping by  $\log_2(\text{sr})$  is essential to block rank-1 / low-rank trivializations (the all-ones matrix has  $\kappa_4 \sim N^3$  yet  $R = 0$ , but  $\text{sr} = 1$ ), and the cap simultaneously evades the Razborov-Rudich natural-proofs trap because  $\tau$  is small on random Boolean functions ( $\kappa_k \rightarrow 1$  for the Marchenko-Pastur limit). Replacing the Linial-Shraibman  $\gamma_2$  SDP with an explicit  $\tilde{O}(N^3)$  free-cumulant moment computation opens a 30-LOC Lean target where each tensor factor contributes additively.

## Novelty

- Judge: NOVEL over 9 arXiv hits

Top hits consulted: - [0111062v2] One-way communication complexity and the Neciporuk lower bound on formula size - [2207.14810v3] Simplifying a classical-quantum algorithm interpolation with quantum singular value transformations - [9906008v2] A Lower Bound on the Average-Case Complexity of Shellsort - [1403.8106v1] Recent advances on the log-rank conjecture in communication complexity - [2004.12646v3] Input-Sparsity Low Rank Approximation in Schatten Norm

## Empirical Test

- exit code: 1, elapsed: 0.09s

--STDERR--

Traceback (most recent call last):

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 198, in <module>
    result = run_trial(seed)
             ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 164, in run_trial
    results.append(run_disj_trial(n))
                   ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 124, in run_disj_trial
    tau = bridge_invariant(M)
         ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 72, in bridge_invariant
    sr = stable_rank(M)
        ^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 66, in stable_rank
    eigenvector = power_iteration(B)
                  ^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 38, in power_iteration
    v /= frobenius_norm(v)
        ^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 34, in frobenius_norm
    return math.sqrt(sum(sum(x**2 for x in row) for row in matrix))
                       ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

```
File "/home/ludo/Scrivania/SEC/research/pvsnp_sandbox/test_2c561438.py", line 34, in <genexpr>
    return math.sqrt(sum(sum(x**2 for x in row) for row in matrix))
                        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

TypeError: 'float' object is not iterable

### **Judge reasoning**

The test crashed with a `TypeError` in the `power_iteration` helper (`frobenius_norm` was called on a vector treated as a matrix), so no data was produced and the pre-registered support condition cannot be evaluated. | next: Fix the `power_iteration/frobenius_norm` bug (handle 1D vectors separately, or just use `numpy.linalg.svd` for the operator norm) and re-run the full DISJ + random + Hadamard/IP\_2 battery.