Agentic STS Game-Assistant

for



🎙️ ask by voice · 📚 knows the game · 🧍 knows *your* world

Lukas A. Feldgrill

Motivation

- 🧩 New players often struggle to understand the game mechanics of Minecraft.
- 📚 The game is very complex and has many different mechanics.
- 🧭 Players lose overview of the game and often don't know what to do next.
- 🔍 Looking something up means alt-tabbing to the wiki, and the wiki knows nothing about **your** world.



Where we left off: the Feb 2026 prototype

Prototype (Feb 2026)	Next step we named back then	Now
Scope: food & farming only	Expand the scope	✅ the whole wiki, pulled on demand
3 hand-written guides + recipes in Chroma	Improve RAG, maybe Graph RAG	🔄 rebuilt; Graph RAG tried and dropped
Game state **not** observed	Take game state into account	✅ Fabric mod → Player DB
Classify → rewrite query → answer (3 LLM calls)	Add an orchestrator	✅ two of them: router & ReAct agent
Some hallucinations	Fine-tune the LLM	⏸️ not pursued; grounding + "I don't know" instead

Goal

Ask by **voice**, while playing, about the **game** *and* about **your world**.

“ 📚 *"What does a wither skeleton drop?"*
🧍 *"Where did I put my torches?"*
🔗 *"I'm hungry, do I have any food left?"* ”



🏠 100 % local
🎮 4 GB target · 12 GB ceiling, next to the running game
⏱️ fast enough to talk to

Outline

2. 🏗️ System architecture
3. 🔎 Gathering information: wiki & player
4. ⚙️ The two orchestrators in detail
5. ⚖️ Comparison
6. 💥 Drawbacks & known issues
7. 🔭 Future work


02

System Architecture

The big picture, and two ways to run it




The big picture



Two ways to orchestrate


Router

fixed pipeline · qwen3:4b-instruct



ReAct agent

reason → act → observe loop · qwen3:14b



03

Gathering Information

Game knowledge from the wiki, player state from the game





Two sources, two strategies


	📚 Game knowledge	🧍 Player state
Source	minecraft.wiki	Fabric mod in the running game
Filled	lazily, on the first question about a topic (*pull*)	continuously while playing (*push*)
Stored in	Chroma (text chunks) + SQLite ledger	SQLite (snapshots + history)
Queried by	semantic search, scoped to one page	exact lookups, no embeddings
Kept fresh by	revision-id check on every lookup	latest event wins

Why the wiki, and why lazily?

- 📦 Game files have recipes & loot tables, but no *explanations* (spawning, farming, mechanics)
- 📚 The wiki covers everything and follows every release
- 🐢 But it is huge and its wikitext is messy → don't scrape it all up front
- ♻️ **Read-through cache:** fetch a page the first time someone asks, keep it local afterwards
- 🎮 Small model: *retrieval* carries the knowledge, the LLM only phrases it



The wiki pipeline



cheap check on every lookup (prop=info returns the live revid) · expensive work only when something changed

Resolving a term to a Wiki page

1. **Direct lookup:** one cheap `prop=info` call → exists? redirect? current revision id
2. **Miss** → full-text search, minus edition/version & franchise pages
3. Remember search hits in an alias cache

⚠️ Wiki search ranks by **keyword overlap, not meaning.**
`"black monster"` → #1 **Minicraft**, an old Notch prototype game
✅ With the franchise filter → #1 **Wither Skeleton** (live, today)

💡 In the pipeline, the LLM extracts a clean entity first, so raw phrases rarely reach the search at all.



Parsing: wikitext → markdown an LLM can read

Raw wikitext (Diamond Sword)

```
The diamond sword has {{hp|7}} base damage {{in|je}} and {{hp|8}} base damage {{in|be}}, and can be enchanted
```

Parsed

```
The diamond sword has 7 base damage (Java Edition) and 8 base damage (Bedrock Edition), and can be enchanted
```

- ⚠️ The naive `plain_text()` deletes templates **with their values**: `{{hp|7}} base damage` → " base damage"
- ✅ Render known templates **in place**, then re-parse. Tables, infoboxes, drop & spawn tables become markdown right where they stood
- 🧹 Drop the noise: image fields, colour codes, *History / Trivia / Gallery* sections
- 🩹 Every bug found on a real page became a test against that page (Diamond Sword, Wither Skeleton, Cow, Cold Ocean, The Nether)

Storing & retrieving wiki text


- 🧱 One chunk per **section**; sections over 500 words are split
- 🧮 Embedded with *all-MiniLM-L6-v2* on the **CPU**: no VRAM taken from the game
- 🗂️ SQLite `pages` ledger: title · revision id · stored-at
- 🎯 Search is **scoped to the resolved page**: top-5 chunks of *that* page
  → "which section?" instead of "which page out of thousands?"
- 🥈 "What does a wither skeleton drop?": the *Drops* chunk ranked only **4th**
  → top-5, not top-1

Why there is no Graph RAG

The Feb plan: *"Switch to Graph RAG to more accurately structure the data of the game."*

- 🕸️ First attempt: an `edges` table built from the links on every page
- 📈 Diamond Sword alone → **91** `related` edges, mostly noise, e.g. `Diamond Sword —related→ Undead` (a link inside the *Smite* enchantment table)
- 👷 Real relations (*crafted from*, *dropped by*) must be **guessed** from templates that differ per page type
- 🧮 Microsoft-style GraphRAG = LLM extraction over the whole corpus: impossible for a lazy cache on a small local model
- ✂️ **Decision:** no graph. Tables & templates become markdown **inside their section**
- 💾 Nothing is lost: the raw wikitext stays cached, so a graph can be rebuilt later

From the game to the Player DB




Player DB: snapshots *and* history

- 🔄 **Snapshots** get replaced: inventory, vitals, position, … only *now* matters
- 📜 **History** accumulates: "Where did I put X?" is a question about the **past**
- 🔦 Placements: only notable blocks (torches, beds, furnaces, …), not every stone of a build
- 🧩 Read through fixed functions (`find_item` , `find_container` , `find_placements` , …), never text-to-SQL
- 🧭 Directions are computed in code: *"northeast, about 40 blocks away"*
- 🧪 Ingest is unit-tested over a real WebSocket, no mocks




04

The Orchestrators in Detail



Router first, then the ReAct agent

Router: route → gather → answer



Step 1: route with a JSON schema

```
Q: "What does a wither skeleton drop?"
{"entities": ["Wither Skeleton"], "player_info": "none",       "player_target": null}

Q: "Where did I put my torches?"
{"entities": [],                  "player_info": "placements", "player_target": "torch"}
```

- 📄 Ollama `format=` + JSON schema → the output always parses; `player_info` is an enum of 12 values
- 🎯 19 few-shot examples, one per category, temperature 0.1
- 💡 Without examples, *"How do I make a beacon?"* came back as **player state** with **no entity**

Steps 2 & 3: gather, then answer

Gather: plain Python, deterministic


- per entity: `ensure_page()` → `query_prose(title, question, k=5)`
- player info: one `player_db` lookup → one sentence of facts

Answer: one more call to the same model

- 📖 Only the given context. A gap means *"I don't know"*, not "it doesn't exist"
- 🗣️ Written for the ear: no lists, no markdown, *"you have…"*
- ⚡ Streamed: speech starts after the first sentence

✅ Fails gracefully: wrong page for "bingus bongus" → *"I don't know"* instead of nonsense

ReAct agent: think → act → observe



The agent loop in detail

- 🧠 `qwen3:14b` with `think="high"` : same model **family** as the router, so the comparison isolates the *architecture*
- 🔁 Up to `MAX_HOPS = 10` tool calls; then tools are withheld → one forced best-effort answer
- 🛡️ A failing tool returns `"error: …"` as a message and never crashes the turn
- 📃 Tool descriptions are the Python **docstrings**, written for the model
- 🔒 No tool takes a file path, so a hallucinated argument can't redirect a read
- 💬 REPL memory: the last 3 question/answer pairs, not the tool transcripts
- ♻️ Reuses the router's modules: one new function in the whole codebase (`resolve.search_candidates`)

Tools & skills

📚 Wiki (3)	🧍 Player (10)	🧠 Skills (4)
`wiki_search_candidates`	`player_find_items`	`skill_crafting_chain`
`wiki_page_overview`	`player_inventory`	`skill_player_navigation`
`wiki_page_search`	`position` · `vitals` · `equipment`	`skill_category_lookup`
	`effects` · `spawn_point` · `deaths`	`skill_wiki_search_strategy`
	`placements` · `structures`	

Skills are zero-argument tools that return *strategy text*, not game data.
They are pulled in on demand instead of bloating the system prompt: one hop, no I/O.

> 🧠 *"Don't search player_find_items for the category word itself (e.g. 'food') – real item names rarely contain it."*

Worked example: chaining both sources

"I am hungry, do I have any food left?"

HOP 1 · SKILL

`skill_category_lookup()`

→ strategy: don't search for the word "food"; look up real item names first

HOP 2 · WIKI

```
wiki_page_search(
"Food",
"list of food item names")
```

→ concrete food names

HOP 3 · PLAYER

```
player_find_items(
[ …all names… ])
```

→ inventory + every known chest, in a single call

ANSWER

whether the player has food, and where if so

3 hops of 10

ROUTER one routing decision up front → one player lookup by a name it must already know.

No step can first learn which items count as food, then check for them. Item ids never contain the word "food".

05

Comparison

❓ Can a model that chains lookups answer questions that need **both** sources?



Side by side

	🛤️ Router	🔁 ReAct agent
Model	`qwen3:4b-instruct` · ≈ 2.5 GB	`qwen3:14b`, thinking · ≈ 9.3 GB
LLM calls / question	always 2	1 + one per tool round (≤ 10 tool calls)
Who picks lookups	Python, from one routing decision	the model, after every result
Chained lookups	❌ single pass	✅ read → decide → read
Speed	streamed, voice-ready	slow: thinking on every call
Consistency	same route → same lookups	same question can take different paths
Memory	none	last 3 Q&A (REPL)
Interface	live voice loop	text CLI (proof of concept)

Which question, which architecture?

Question	🛤️ Router	🔁 Agent
📚 *"What does a wither skeleton drop?"*	✅ one page, fast	✅ slower
🧍 *"Where did I put my torches?"*	✅ exact lookup + direction	✅
🗺️ *"How do I get back to where I died?"*	✅	✅
🔗 *"I'm hungry, do I have any food left?"*	⚠️ needs item names up front	✅ *when* it consults the skill

Router: fast & predictable for one-shot questions.
Agent: the only way to chain lookups, paid for in speed and predictability.

06

Drawbacks & Known Issues



Mechanical fixes stuck, prompt fixes mostly didn't

Observed live (agent)	Rewording the prompt	Mechanical fix
🪄 Made-up `term=` argument on a zero-argument skill → crash, hop wasted	–	drop arguments the function doesn't accept ✅
📋 Ollama's schema converter drops defaults → every parameter "required"	–	`param: T | None = None` ✅
📚 Asked for 10 results → table dump → forgot the player check	reworded twice ❌	hard cap at 3 results ✅
🔍 Two single-item tools → checked one source, gave up early	–	one `player_find_items(names)` ✅
💭 Thinking model puts everything into `thinking`, empty answer	–	one free re-prompt ✅

Known issues: orchestration

🔁 ReAct agent

- 🎲 Whether a matching skill gets consulted varies run to run: 3 of 4 runs, at temperature 0.3 **and** 0.1
- 🌡️ Temperature 0.1 made it worse: `player_inventory()` called 7× in a row, budget gone
- 🐌 Slow, and 14B (≈ 9.3 GB) doesn't fit the 4 GB target next to the game → not in the voice loop

🛤️ Router

- ➡️ One pass: it cannot look something up *because of* what it just read
- 🎯 A wrong routing decision means a wrong lookup, with no second chance
- 💬 No conversation memory in the voice loop: every question stands alone

Known issues: data & retrieval

- 🥈 Small embedding model: the right chunk is in the top-5, not always at #1
- 🔤 Search fallback can still pick a wrong page, and the alias cache then remembers it
- 🏷️ Inventory holds registry ids (`minecraft:cooked_beef`), the wiki uses titles ("Cooked Beef"): no bridge yet
- ⏳ First question about a new page pays fetch + parse + embed (Creeper, cold: 4.3 s incl. answer)
- 🧱 Mod: only containers you opened; furnaces & structure visits still TODO; Java Edition only; server mod to gather global information.
- 🕒 System only knows of the player's data; data of other players in the same world is not yet available.
- 📏 Evaluated by eye: batch prompt files + 89 unit tests, but no benchmark of answer quality

07

Future Work



Future work

Next

- 🌱 Pre-seed common pages; say a filler line (*"let me check the wiki…"*) on a cache miss
- 🔎 Resolve against a local index of verified page titles instead of keyword search

Later

- 🔀 **Hybrid:** the router as the fast path, hand over to the agent only for chained questions
- 🧩 Better chunks: page/section context in the embedding, smaller chunks, a re-ranker
- 🏷️ Map registry ids ↔ wiki titles
- 🗣️ Agent in the voice loop: smaller thinking budget, faster STT/TTS (faster-whisper, Piper)
- 💡 Proactive hints from the live event stream: night is falling, health is low, …
- 👥 Multiplayer support: system gathers server-side data, answers about other players in the same world



Thank you! 🤠

Questions?

github.com/lufeld/game-assistant

Minecraft images © Mojang Studios, via minecraft.wiki